Package: APRScenario (via r-universe)

October 25, 2026

Title Structural Scenario Analysis for Bayesian Structural Vector Autoregression Models

Version 0.0.4.2

Author Giovanni Lombardo [aut, cre], Tito Quadri [aut]

Maintainer Giovanni Lombardo <giannilmbd@gmail.com>

Description Implements the scenario analysis proposed by Antolin-Diaz, Petrella and Rubio-Ramirez (2021) ``Structural scenario analysis with SVARs" <doi:10.1016/j.jmoneco.2020.06.001>.

License GPL (>= 3)

URL https://github.com/giannilmbd/APRScenario

BugReports https://github.com/giannilmbd/APRScenario/issues

Encoding UTF-8

Depends R (>= 4.1.0)

Imports dplyr, ggplot2, lubridate, parallel, MASS, tidyr, abind, psych, Rcpp (>= 1.0.12), RcppProgress

Suggests bsvars, bsvarSIGNs, devtools, ggfortify, gridExtra, zoo, knitr, rmarkdown, testthat (>= 3.0.0)

LinkingTo Rcpp, RcppArmadillo, RcppProgress

SystemRequirements LAPACK

RoxygenNote 7.3.2

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation yes

Repository https://cran.r-universe.dev

Date/Publication 2026-08-26 08:50:17 UTC

RemoteUrl https://github.com/cran/APRScenario

RemoteRef HEAD

RemoteSha 4a13f5f9690a6dc5952a92819682a593e5d6a30b

Contents

big_b_and_M . . . 2
forc_h . . . 3
full_scenarios_core . . . 4
gen_mats . . . 6
KL . . . 6
mat_forc . . . 8
NKdata . . . 9
plot_bvars . . . 10
plot_cond_forc . . . 11
plot_cond_histo . . . 12
scenarios . . . 13
SimScen . . . 15
simulate_conditional_forecasts . . . 16

Index **18**

`big_b_and_M` *big_b_and_M This function returns the extended b and M matrices as in APR*

Description

Computation is done draw by draw (all horizons in a single pass) and can be parallelized over posterior draws on every platform: forked processes (`parallel::mclapply`) on Unix/macOS, a PSOCK cluster (`parallel::parLapply`) on Windows.

Usage

```
big_b_and_M(
  h,
  n_draws,
  n_var,
  n_p,
  data_ = NULL,
  matrices = NULL,
  n_cores = 1,
  parallel = c("auto", "fork", "psock", "none")
)
```

Arguments

`h`	forecast horison
`n_draws`	Number of draws
`n_var`	Number of variables
`n_p`	Number of lags

data_	(matrix optional) The data, stacking Y over X (data and laggs) – columns are observations (default taken from matrices$Z) NB: this is not necessarily the same as the data used to estimate the model If run counterfactuals in previoius historical period (ie not forecast) must pass the data up to previous period relative to counterfactual
matrices	Optional matrices object from gen_mats() (default taken from calling environment)
n_cores	Number of parallel workers (default 1 = serial). If NULL, uses the number of physical cores minus one, capped by n_draws.
parallel	Parallel backend: "auto" (default; fork where available, i.e. Unix/macOS, otherwise PSOCK), "fork", "psock", or "none". Ignored when n_cores = 1.

Value

the big_b and big_M matrices of mean and IRF

Examples

```
## Not run:
# Example usage for creating extended matrices (serial)
result <- big_b_and_M(h = 4, n_draws = 1000, n_var = 3, n_p = 2,
                      matrices = matrices)
# parallel over draws, backend picked automatically for the platform
result <- big_b_and_M(h = 4, n_draws = 1000, n_var = 3, n_p = 2,
                      matrices = matrices, n_cores = 2)
big_b <- result[[1]]
big_M <- result[[2]]

## End(Not run)
```

---

forc_h *forc_h function*

Description

forc_h function

Usage

```
forc_h(
  h = 1,
  n_sim = 200,
  data_ = NULL,
  posterior = NULL,
  matrices = NULL,
  max_cores = 1
)
```

Arguments

h	forecast horizon
n_sim	length of shock simulation
data_	Optional matrix of data n_var*h+1 x T. If NULL, defaults to matrices$Z
posterior	Optional posterior object (default taken from calling environment)
matrices	Optional matrices object from gen_mats() (default taken from calling environment)
max_cores	number of workers used to parallelize over posterior draws (default 1 = serial; forked processes on Unix/macOS, PSOCK cluster on Windows). Given the same seed, results are identical for any value.

Value

a matrix of unconditional forecasts

Examples

```
## Not run:
# Example usage for unconditional forecasting
forecast <- forc_h(h = 4, n_sim = 1000,
                   posterior = posterior, matrices = matrices)

## End(Not run)
```

---

full_scenarios_core *Exported version of full_scenarios_core*

Description

This function wraps the Rcpp-exported version of `full_scenarios_core` and allows external users to call it with correct argument checks.

Usage

```
full_scenarios_core(
  big_b,
  big_M,
  obs,
  path,
  shocks,
  h,
  n_var,
  g_ = NULL,
  Sigma_g_ = NULL
)
```

Arguments

big_b	Cube of B matrices
big_M	Cube of M matrices
obs	Indices of constrained observables
path	Flattened path for observables
shocks	Indices of shocks to be recovered
h	Forecast horizon
n_var	Number of variables
g_	Optional vector of non-driving shocks
Sigma_g_	Optional covariance matrix of non-driving shocks

Value

A list with elements depending on the input configuration. Typically includes:

mu_eps Matrix of mean structural shocks

Sigma_eps Covariance matrix of structural shocks

mu_y Matrix of conditional means of observables

Sigma_y Covariance matrix of observables

big_b Slice of B matrices used

big_M Slice of M matrices used

draws_used Indices of posterior draws used in the simulation

Examples

```
## Not run:
# This function is typically called internally by scenarios()
# Example usage with simulated data:
big_b <- array(rnorm(9*4*10), dim = c(9, 4, 10))
big_M <- array(rnorm(9*9*10), dim = c(9, 9, 10))
result <- full_scenarios_core(big_b, big_M, obs = 1:2,
                              path = c(1.0, 1.1), shocks = NA,
                              h = 2, n_var = 3)

## End(Not run)
```

gen_mats *gen_mats function*

Description

this function returns the matrices necessary for forecasts

Usage

```
gen_mats(posterior = NULL, specification = NULL, max_cores = 1)
```

Arguments

posterior	Posterior estimation results (eg from BsvarSIGNs)
specification	Optional specification object (default taken from calling environment)
max_cores	number of workers used to parallelize over draws via forking (Unix/macOS; default 1 = serial). On Windows this step always runs serially (the computation is light; the heavy draw-level work in big_b_and_M()/scenarios() is parallelized on all platforms).

Value

Returns all objects necessary for scenario analysis (e.g., IRF matrix), including: M, M_inv, M_list, B, B_list, n_p, n_var, Y, X, and Z.

Examples

```
library(APRScenario)
data(NKdata)

# Minimal example with a toy specification
spec <- bsvarSIGNs::specify_bsvarSIGN$new(as.matrix(NKdata[,2:4]), p = 1)
est <- bsvars::estimate(spec, S = 10)  # Use small S for fast test
gen_mats(posterior = est, specification = spec)
```

KL *KL function APR suggest this measure to assess the "plausibility" of the conditional forecast. It is based on the Kullback-Leibler measure of distance between the unconditional forecast and the conditional/scenario forecast.*

Description

KL function APR suggest this measure to assess the "plausibility" of the conditional forecast. It is based on the Kullback-Leibler measure of distance between the unconditional forecast and the conditional/scenario forecast.

Usage

```
KL(Sigma_eps, mu_eps, h, plot_ = FALSE, max_cores = NULL)
```

Arguments

Sigma_eps	variance of innovation
mu_eps	mean of innovation
h	forecast horizon
plot_	logical; if TRUE then a histogram of the KL measure is returned
max_cores	number of workers used to parallelize over draws via forking (Unix/macOS; default NULL = 1 = serial). On Windows this step always runs serially (the computation is light; the heavy draw-level work in big_b_and_M()/scenarios() is parallelized on all platforms).

Value

Returns the APR 'q': ie distance from a fair binomial distribution

Examples

```
# Example with simulated innovation data
# Set dimensions
n_var <- 3
h <- 4
n_draws <- 10
n_innovations <- n_var * h

# Create simulated innovation means and covariances
set.seed(123)
mu_eps <- array(rnorm(n_innovations * 1 * n_draws, mean = 0, sd = 0.1),
                dim = c(n_innovations, 1, n_draws))

Sigma_eps <- array(0, dim = c(n_innovations, n_innovations, n_draws))
for (d in 1:n_draws) {
  temp_cov <- matrix(rnorm(n_innovations^2), n_innovations, n_innovations)
  Sigma_eps[,,d] <- temp_cov %*% t(temp_cov) + diag(n_innovations) * 0.5
}

# Calculate KL measure
kl_result <- KL(Sigma_eps, mu_eps, h, plot_ = FALSE)
print(head(kl_result[[1]]))  # Print first few q values
```

---

mat_forc *mat_forc function ## NB: HERE WE USE Antolin-Diaz et al notation # B is reduced form; # A is structural; # d is intercepts # M is reduced so that E(u*u') =Sigma=(A_0*A_0')^(-1) and M_0=A_0^(-1)*Q # Note that the code returns conflicting notation: # B=>A_0^(-1)*Q and # A=>B # ##*
The recursions (Antolin-Diaz et al. 2021, Appendix A) are implemented once, in the internal single-draw kernel `mat_forc_draw()`*;* `mat_forc()`*,* `big_b_and_M()` *and* `forc_h()` *are thin consumers of that kernel.*

Description

mat_forc function ## NB: HERE WE USE Antolin-Diaz et al notation # B is reduced form; # A is structural; # d is intercepts # M is reduced so that E(u*u')=Sigma=(A_0*A_0')^(-1) and M_0=A_0^(-1)*Q # Note that the code returns conflicting notation: # B=>A_0^(-1)*Q and # A=>B # ## The recursions (Antolin-Diaz et al. 2021, Appendix A) are implemented once, in the internal single-draw kernel `mat_forc_draw()`; `mat_forc()`, `big_b_and_M()` and `forc_h()` are thin consumers of that kernel.

Usage

```
mat_forc(
  h = 1,
  n_draws,
  n_var,
  n_p,
  data_ = NULL,
  matrices = NULL,
  max_cores = 1
)
```

Arguments

h	(integer) forecast horison
n_draws	(integer) Number of draws
n_var	(integer) Number of variables
n_p	(integer) Number of lags
data_	(matrix optional) The data, stacking Y over X (data and laggs) – columns are observations (default taken from matrices$Z) NB: this is not necessarily the same as the data used to estimate the model If run counterfactuals in previoius historical period (ie not forecast) must pass the data up to previous period relative to counterfactual

matrices	Optional matrices object from gen_mats() (default taken from calling environment)
max_cores	number of workers used to parallelize over posterior draws (default 1 = serial; forked processes on Unix/macOS, PSOCK cluster on Windows)

Value

the big_b and big_M matrices of mean and IRF

Examples

```
library(APRScenario)
data(NKdata)

# Minimal example with a toy specification
spec <- bsvarSIGNs::specify_bsvarSIGN$new(as.matrix(NKdata[,2:4]), p = 1)
est <- bsvars::estimate(spec, S = 10)  # Use small S for fast test
matrices<-gen_mats(posterior = est, specification = spec)

# Example usage for matrix forecasting
result <- mat_forc(h = 4, n_draws = 10, n_var = 3, n_p = 1,
                   matrices = matrices)
```

NKdata *Example Dataset NKdata*

Description

A dataset used in the APRScenario package.

Usage

```
data(NKdata)
```

Format

A data frame with 244 rows and 4 variables:

GDP.E GDP

pi.PCE.core inflation

i interest rate

year year

plot_bvars *plot_bvars: This function plots the IRFs generated with the BVAR*

Description

plot_bvars: This function plots the IRFs generated with the BVAR

Usage

```
plot_bvars(
  M,
  significance_level = 0.05,
  central_tendency = "mean",
  variable_names = NULL,
  shock_names = NULL
)
```

Arguments

M	IRFs produced by eg bvarSIGNs
significance_level	(eg 0.05)
central_tendency	eg 'mean' or 'median'
variable_names	vector of names of variables (strings)
shock_names	vector of names of variables (strings)

Value

a list of ggplot objects (plots)

Examples

```
# Example with simulated IRF data
# Create simulated IRF array (n_vars, n_shocks, n_periods, n_draws)
set.seed(123)
n_vars <- 3
n_shocks <- 3
n_periods <- 10
n_draws <- 50

# Generate IRF responses that decay over time
M <- array(0, dim = c(n_vars, n_shocks, n_periods, n_draws))
for (i in 1:n_vars) {
  for (j in 1:n_shocks) {
    for (t in 1:n_periods) {
      # Create decaying responses with some randomness
```

```
      base_response <- ifelse(i == j, 1, 0.3) * exp(-0.1 * (t-1))
      M[i, j, t, ] <- rnorm(n_draws, mean = base_response, sd = 0.1)
    }
  }
}

# Create plots
var_names <- c("GDP", "CPI", "FFR")
shock_names <- c("Supply", "Demand", "Monetary")

plots <- plot_bvars(M,
                    variable_names = var_names,
                    shock_names = shock_names,
                    significance_level = 0.1)

# plots is a list of ggplot objects
print(length(plots))
```

`plot_cond_forc` *plot_cond_forc function; Data should conatain the variable "variable", the "hor" horizon and a "history"*

Description

plot_cond_forc function; Data should conatain the variable "variable", the "hor" horizon and a "history"

Usage

```
plot_cond_forc(
  varbl2plot = NULL,
  y_h_cond = NULL,
  center = 0.5,
  lower = 0.16,
  upper = 0.84,
  T.start = NULL,
  T.end = NULL,
  before = 8,
  freq = "quarter",
  y_data = NULL
)
```

Arguments

`varbl2plot`	name of variable to be plotted (string)
`y_h_cond`	conditional forecast data frame (eg from SimScen) with names c("hor","variable","lower","center","upper hor is a Date object

center	(optional, default 0.5) quantile of the mid value
lower	(optional, default 0.16) quantile of lower range
upper	(optional, default 0.84) quantile of upper range
T.start	start date of the forecast
T.end	end of the forecast
before	(integer: optional) periods of data in the plot: default 8 periods
freq	(optional, default 'quarter') frequency of the data (eg 'quarter' or 'month')
y_data	Data used in the estimation eg t(specification$get_data_matrices()$Y) %>% as.data.frame(); true_data$hor=dates

Value

list of plot and data used

Examples

```
## Not run:
# Example usage with conditional forecast data
plot_result <- plot_cond_forc(varbl2plot = "GDP",
                              y_h_cond = forecast_data,
                              T.start = as.Date("2023-01-01"),
                              T.end = as.Date("2024-01-01"),
                              y_data = historical_data)

## End(Not run)
```

---

plot_cond_histo *plot_cond_histo function*

Description

This function uses the conditional probability calculations (eg scenarios) and plots the histogram of the selected variable

Usage

```
plot_cond_histo(
  variable = NULL,
  horizon = 1,
  threshold = NULL,
  data = NULL,
  above = TRUE,
  size = 5
)
```

Arguments

variable	(character) Name of variable to be plotted
horizon	(numeric) At which horizon (horizon<=h)
threshold	(numeric,optional) If present compute P(x>threshold)
data	data of conditional forecasts
above	(logical,optional): if TRUE then compute probability above threshold
size	(optional) size of annotation text in the plot

Value

ggplot object (plot)

Examples

```
# Example with simulated conditional forecast data
# Create sample forecast data matrix
set.seed(123)
n_sims <- 500
horizons <- 3
variables <- c("GDP", "CPI", "FFR")

# Create column names in the expected format (variable.horizon)
col_names <- outer(variables, 1:horizons, paste, sep = ".")

# Generate random forecast data
forecast_data <- matrix(rnorm(n_sims * length(col_names)),
                        nrow = n_sims, ncol = length(col_names))
colnames(forecast_data) <- as.vector(col_names)

# Plot histogram for GDP at horizon 2
p <- plot_cond_histo(data = t(forecast_data),
                     variable = "GDP",
                     horizon = 2,
                     threshold = 0.5,
                     above = TRUE)
```

---

scenarios *scenarios function (fully optimized with Rcpp) This function computes the mean and covariances to draw from the conditional forecast The actual draw is done in the simscen function*

Description

scenarios function (fully optimized with Rcpp) This function computes the mean and covariances to draw from the conditional forecast The actual draw is done in the simscen function

Usage

```
scenarios(
  h = 3,
  path = NULL,
  obs = NULL,
  free_shocks = NULL,
  n_sample = NULL,
  data_ = NULL,
  g = NULL,
  Sigma_g = NULL,
  posterior = NULL,
  matrices = NULL,
  n_cores = 1,
  parallel = c("auto", "fork", "psock", "none")
)
```

Arguments

h	forecast horizon
path	conditional path of observables
obs	position of observable(s)
free_shocks	position of non-driving shocks (NA if all driving)
n_sample	Number of draws to sample (<= n_draws)
data_	Optional matrix of data (default taken from matrices$Z). Note: the last observation in data_ is used as the starting point; it should not overlap with the scenario forecasting period.
g	Optional matrix of non-driving shocks
Sigma_g	Optional covariance matrix of non-driving shocks
posterior	Optional posterior object (default taken from calling environment)
matrices	Optional matrices object from gen_mats() (default taken from calling environment)
n_cores	Number of parallel workers used to build the forecast matrices (default 1 = serial; NULL = physical cores minus one); see big_b_and_M()
parallel	Parallel backend passed to big_b_and_M(): "auto" (default; fork on Unix/macOS, PSOCK on Windows), "fork", "psock", or "none"

Value

list of mu_eps, Sigma_eps, mu_y, Sigma_y, big_b, big_M, draws_used

Examples

```
library(APRScenario)
data(NKdata)
```

```
# Minimal example with a toy specification
spec <- bsvarSIGNs::specify_bsvarSIGN$new(as.matrix(NKdata[,2:4]), p = 1)
posterior <- bsvars::estimate(spec, S = 10)  # Use small S for fast test
matrices<-gen_mats(posterior = posterior, specification = spec)
# and having posterior object
 scenario_result <- scenarios(h = 2,
                              path = c(1.0, 1.1),
                              obs = 1,
                              free_shocks = NA,
                              posterior = posterior,
                              matrices = matrices)
```

`SimScen` *simscen function This function takes the mean and covariance of the conditional forecast to draw from the conditional forecast distribution The shock uncertainty is included in the simulation by default, but can be turned off.*

Description

simscen function This function takes the mean and covariance of the conditional forecast to draw from the conditional forecast distribution The shock uncertainty is included in the simulation by default, but can be turned off.

Usage

```
SimScen(
  mu_eps,
  Sigma_eps,
  mu_y,
  Sigma_y,
  big_b,
  big_M,
  n_sim,
  h,
  varbls,
  idx_sampled = 1:dim(mu_eps)[3],
  shock_uncertainty = TRUE
)
```

Arguments

`mu_eps`	mean innovation
`Sigma_eps`	variance innovation
`mu_y`	mean forecast
`Sigma_y`	variance forecast

big_b	history forecast
big_M	IRF (innovation loading)
n_sim	number of simulations
h	horizon
varbls	variable names
idx_sampled	index of random sample to use instead of full draws (from scenarios)
shock_uncertainty	(logical; optional) whether to include uncertainty in shocks (default is TRUE)

Value

conditional forecast path and distribution

Examples

```
## Not run:
# Example usage after scenarios() function call
# Requires scenario results from scenarios() function
result <- SimScen(mu_eps = scenario_output$mu_eps,
                  Sigma_eps = scenario_output$Sigma_eps,
                  mu_y = scenario_output$mu_y,
                  Sigma_y = scenario_output$Sigma_y,
                  big_b = scenario_output$big_b,
                  big_M = scenario_output$big_M,
                  n_sim = 1000, h = 3, varbls = c("GDP", "CPI", "FFR"))

## End(Not run)
```

---

simulate_conditional_forecasts

Simulate paths from conditional forecast distributions

Description

Simulate paths from conditional forecast distributions

Usage

```
simulate_conditional_forecasts(mu_y, Sigma_y, varnames, n_sim = 1000)
```

Arguments

mu_y	Array (n_state × 1 × n_draws): conditional forecast mean
Sigma_y	Array (n_state × n_state × n_draws): conditional forecast variance
varnames	Character vector of variable names (length = number of variables)
n_sim	Number of simulations per draw

Value

Array of dimensions (n_state x n_sim x n_draws) of simulated draws with named rows

Note

Users should set their own seed before calling this function if reproducible results are desired.

Examples

```
# Example with simulated data
# Create example data dimensions
n_var <- 3
h <- 2
n_draws <- 5
n_state <- n_var * h

# Simulate conditional forecast means and covariances
set.seed(123)
mu_y <- array(rnorm(n_state * 1 * n_draws), dim = c(n_state, 1, n_draws))
Sigma_y <- array(0, dim = c(n_state, n_state, n_draws))
for (d in 1:n_draws) {
  temp_cov <- matrix(rnorm(n_state^2), n_state, n_state)
  Sigma_y[,,d] <- temp_cov %*% t(temp_cov) + diag(n_state) * 0.1
}

# Variable names
varnames <- c("GDP", "CPI", "FFR")

# Simulate conditional forecasts
sims <- simulate_conditional_forecasts(mu_y, Sigma_y, varnames, n_sim = 50)
print(dim(sims))
print(rownames(sims)[1:6])
```

Index

∗ **datasets**
NKdata, 9

big_b_and_M, 2
big_b_and_M(), *6–8*, *14*

forc_h, 3
forc_h(), *8*
full_scenarios_core, 4

gen_mats, 6

KL, 6

mat_forc, 8

NKdata, 9

plot_bvars, 10
plot_cond_forc, 11
plot_cond_histo, 12

scenarios, 13
scenarios(), *6, 7*
SimScen, 15
simulate_conditional_forecasts, 16