

Package: BSSprep (via r-universe)

October 31, 2024

Type Package

Title Whitening Data as Preparation for Blind Source Separation

Version 0.1

Date 2021-03-25

Maintainer Markus Matilainen <markus.matilainen@outlook.com>

Imports Rcpp (>= 0.11.0)

LinkingTo Rcpp, RcppArmadillo

Description Whitening is the first step of almost all blind source separation (BSS) methods. A fast implementation of whitening for BSS is implemented to serve as a lightweight dependency for packages providing BSS methods.

License GPL (>= 2)

NeedsCompilation yes

Author Markus Matilainen [cre, aut]
(<<https://orcid.org/0000-0002-5597-2670>>), Klaus Nordhausen
[aut] (<<https://orcid.org/0000-0002-3758-8501>>)

Repository CRAN

Date/Publication 2021-03-29 09:32:16 UTC

Contents

BSSprep-package	2
BSSprep	2
Index	4

BSSprep-package

Whitening Data as Preparation for Blind Source Separation

Description

Whitening is the first step of almost all blind source separation (BSS) methods. A fast implementation of whitening for BSS is implemented to serve as a lightweight dependency for packages providing BSS methods.

Details

Package: BSSprep
Type: Package
Version: 0.1
Date: 2021-03-25
License: GPL (>= 2)

This package contains the single function [BSSprep](#) for whitening multivariate data as a preprocessing step for blind source separation (BSS). The package is meant as a fast and lightweight dependency for packages providing BSS methods as whitening is almost always the first step.

Author(s)

Markus Matilainen, Klaus Nordhausen

Maintainer: Markus Matilainen <markus.matilainen@outlook.com>

BSSprep*Whitening of Multivariate Data*

Description

A function for data whitening.

Usage

BSSprep(X)

Arguments

X A numeric matrix. Missing values are not allowed.

Details

A p -variate \mathbf{Y} with T observations is whitened, i.e. $\mathbf{Y} = \mathbf{S}^{-1/2}(\mathbf{X}_t - \frac{1}{T} \sum_{t=1}^T \mathbf{X}_t)$, where \mathbf{S} is the sample covariance matrix of \mathbf{X} .

This is often need as a preprocessing step like in almost all blind source separation (BSS) methods. The function is implemented using C++ and returns the whitened data matrix as well as the ingredients to back transform.

Value

A list containing the following components:

Y	The whitened data matrix.
X.C	The mean-centered data matrix.
COV.sqrt.i	The inverse square root of the covariance matrix of X.
MEAN	Mean vector of X.

Author(s)

Markus Matilainen, Klaus Nordhausen

Examples

```
n <- 100
X <- matrix(rnorm(10*n) - 1, nrow = n, ncol = 10)

res1 <- BSSprep(X)
res1$Y # The whitened matrix
colMeans(res1$Y) # should be close to zero
cov(res1$Y) # should be close to the identity matrix
res1$MEAN # Should hover around -1 for all 10 columns
```

Index

* **multivariate**

BSSprep, [2](#)

BSSprep-package, [2](#)

* **package**

BSSprep-package, [2](#)

* **ts**

BSSprep, [2](#)

BSSprep, [2](#), [2](#)

BSSprep-package, [2](#)