Package: BayesRegDTR (via r-universe)

October 23, 2026

Type Package

Title Bayesian Regression for Dynamic Treatment Regimes

Version 1.1.2

Description Methods to estimate optimal dynamic treatment regimes using Bayesian likelihood-based regression approach as described in Yu, W., & Bondell, H. D. (2023) <doi:10.1093/jrsssb/qkad016> Uses backward induction and dynamic programming theory for computing expected values. Offers options for future parallel computing.

License GPL (>= 3)

Imports Rcpp (>= 1.0.13-1), mvtnorm, foreach, progressr, stats, future

Depends doRNG

Suggests cli, testthat (>= 3.0.0), doFuture

LinkingTo Rcpp, RcppArmadillo

Encoding UTF-8

RoxygenNote 7.3.3

URL https://github.com/jlimrasc/BayesRegDTR

BugReports https://github.com/jlimrasc/BayesRegDTR/issues

Config/testthat/edition 3

NeedsCompilation yes

Author Jeremy Lim [aut], Weichang Yu [aut, cre] (ORCID: <https://orcid.org/0000-0002-0399-3779>)

Maintainer Weichang Yu <weichang.yu@unimelb.edu.au>

Repository https://cran.r-universe.dev

Date/Publication 2025-11-27 09:10:15 UTC

RemoteUrl https://github.com/cran/BayesRegDTR

RemoteRef HEAD

RemoteSha fca5b434cab330af9fee1ca5bfe9a33645677bf2

Contents

BayesRegDTR-package 2
BayesLinRegDTR.model.fit 3
generate_dataset 6

Index **8**

`BayesRegDTR-package` *BayesRegDTR: Bayesian Regression for Dynamic Treatment Regimes*

Description

Methods to estimate optimal dynamic treatment regimes using Bayesian likelihood-based regression approach as described in Yu, W., & Bondell, H. D. (2023) doi:10.1093/jrsssb/qkad016 Uses backward induction and dynamic programming theory for computing expected values. Offers options for future parallel computing.

Author(s)

Maintainer: Jeremy Lim <jeremylim23@gmail.com>

Authors:

- Weichang Yu <weichang.yu@unimelb.edu.au> (ORCID)

References

Yu, W., & Bondell, H. D. (2023), "Bayesian Likelihood-Based Regression for Estimation of Optimal Dynamic Treatment Regimes", Journal of the Royal Statistical Society Series B: Statistical Methodology, 85(3), 551-574. doi:10.1093/jrsssb/qkad016

See Also

`generate_dataset()` for generating a toy dataset to test the model fitting on

`BayesLinRegDTR.model.fit()` for obtaining an estimated posterior distribution of the optimal treatment option at a user-specified prediction stage

Useful links:

- https://github.com/jlimrasc/BayesRegDTR
- Report bugs at https://github.com/jlimrasc/BayesRegDTR/issues

`BayesLinRegDTR.model.fit` *Main function for fitting a Bayesian likelihood-based linear regression model*

Description

Fits the Bayesian likelihood-based linear model to obtain an estimated posterior distribution of the optimal treatment option at a user-specified prediction stage. Uses backward induction and dynamic programming theory for computing expected values.

Usage

```
BayesLinRegDTR.model.fit(
  Dat.train,
  Dat.pred,
  n.train,
  n.pred,
  num_stages,
  num_treats,
  p_list,
  t,
  R = 30,
  tau = 0.01,
  B = 10000,
  nu0 = 3,
  V0 = mapply(diag, p_list, SIMPLIFY = FALSE),
  alph = 1,
  gam = 1,
  showBar = TRUE
)
```

Arguments

`Dat.train`	Training data in format returned by `generate_dataset`: organised as a list of $\{y, X_1, X_2..., X_{num_stages}, A\}$ where y is a vector of the final outcomes, $X_1, X_2..., X_{num_stages}$ is a list of matrices of the intermediate covariates and A is an $n.train \times num_stages$ matrix of the assigned treatments, where num_stages is the total number of stages
`Dat.pred`	Prediction data in format returned by `generate_dataset`: organised as a list of $\{X_1, X_2..., X_t, A\}$ where $X_1, X_2..., X_t$ is a list of matrices of the intermediate covariates and A is an $n.pred \times (t-1)$ matrix of the assigned treatments, where t is the prediction stage
`n.train`	Number of samples/individuals in the training data
`n.pred`	Number of samples/individuals in the prediction data
`num_stages`	Total number of stages

num_treats	Vector of number of treatment options at each stage
p_list	Vector of intermediate covariate dimensions for each stage
t	Prediction stage t, where t $\leq$ num_stages
R	Draw size from distribution of intermediate covariates. default: 30
tau	Normal prior scale parameter for regression coefficients. Should be specified with a small value. default: 0.01
B	Number of MC draws from posterior of regression parameters. default 10000
nu0	Inverse-Wishart prior degrees of freedom for regression error Vcov matrix. Ignored if using a univariate dataset. default: 3
V0	List of Inverse-Wishart prior scale matrix for regression error Vcov matrix. Ignored if using a univariate dataset. default: list of identity matrices
alph	Inverse-Gamma prior shape parameter for regression error variance of y. default: 1
gam	Inverse-Gamma prior rate parameter for regression error variance of y. default: 1
showBar	Whether to show a progress bar. Uses API from progressr and future for parallel integration deafult: TRUE

Details

Utilises a future framework, so to enable parallel processing and register a parallel backend, plan and registerDoFuture must be called first.

Additionally, progress bars use progressr API, and a non-default progress bar (e.g. cli) is recommended. See below or registerDoFuture and handlers for examples.

Note that to have a progress bar for the parallel sections, future must be used. To turn off the immediate warnings, use `options(BRDTR_warn_imm = FALSE)`.

Value

GCV_results	An array of dimension $n.pred \times num_treats[t] \times B$, indicating the expected value under each treatment option at stage t.
post.prob	An $n.pred \times num_treats[t]$ matrix of the posterior probability that each treatment type at stage t is optimal
MC_draws.train	A list of Monte Carlo draws containing:

- *sigmat_B_list* - A list of length num_stages with each element a vector of size $B \times p_list[t]$
- *Wt_B_list* - A list of length num_stages with each element a matrix of size $B \times p_list[t]$
- *beta_B* - A list of length B
- *sigmay_2B* - A list of length B

Examples

```
# Code does not run within 10 seconds, so don't run

# ----------------------------
# Set Up Parallelism & Progress Bar
# ----------------------------
progressr::handlers("cli")          # Set handler to something with title/text
numCores <- parallel::detectCores() # Detect number of cores, use max
future::plan(future::multisession,  # Or plan(multicore, workers) on Unix
             workers = numCores)    # Set number of cores to use
doFuture::registerDoFuture()        # Or doParallel::registerDoParallel()
                                    # if no progress bar is needed and future
                                    # is unwanted

## UVT
# ----------------------------
# Initialise Inputs
# ----------------------------
num_stages  <- 5
t           <- 3
p_list      <- rep(1, num_stages)
num_treats  <- rep(2, num_stages)
n.train     <- 5000
n.pred      <- 10

# ----------------------------
# Generate Dataset
# ----------------------------
Dat.train  <- generate_dataset(n.train,  num_stages, p_list, num_treats)
Dat.pred  <- generate_dataset(n.pred,  num_stages, p_list, num_treats)
Dat.pred  <- Dat.pred[-1]
Dat.pred[[num_stages+1]]  <- Dat.pred[[num_stages+1]][1:n.pred, 1:(t-1), drop = FALSE]

# ----------------------------
# Main
# ----------------------------
gcv_uvt <- BayesLinRegDTR.model.fit(Dat.train, Dat.pred, n.train, n.pred,
                                    num_stages, num_treats,
                                    p_list, t, R = 30,
                                    tau = 0.01, B = 500, nu0 = NULL,
                                    V0 = NULL, alph = 3, gam = 4)

## MVT
# ----------------------------
# Initialise Inputs
# ----------------------------
num_stages  <- 3
t           <- 2
p_list      <- rep(2, num_stages)
num_treats  <- rep(2, num_stages)
n.train     <- 5000
n.pred      <- 10
```

```
# ----------------------------
# Generate Dataset
# ----------------------------
Dat.train <- generate_dataset(n.train, num_stages, p_list, num_treats)
Dat.pred  <- generate_dataset(n.pred,  num_stages, p_list, num_treats)
Dat.pred  <- Dat.pred[-1]
Dat.pred[[num_stages+1]]  <- Dat.pred[[num_stages+1]][1:n.pred, 1:(t-1), drop = FALSE]

# ----------------------------
# Main
# ----------------------------
gcv_res <- BayesLinRegDTR.model.fit(Dat.train, Dat.pred, n.train, n.pred,
                                    num_stages, num_treats,
                                    p_list, t, R = 30,
                                    tau = 0.01, B = 500, nu0 = 3,
                                    V0 = mapply(diag, p_list, SIMPLIFY = FALSE),
                                    alph = 3, gam = 4)
```

`generate_dataset` *Generate a toy dataset in the right format for testing BayesLinRegDTR.model.fit*

Description

Generates a toy dataset simulating observed data of treatments over time with final outcomes and intermediate covariates. Follows the method outlined in Toy-Datagen on Github

Usage

```
generate_dataset(n, num_stages, p_list, num_treats)
```

Arguments

`n`	Number of samples/individuals to generate
`num_stages`	Total number of stages per individual
`p_list`	Vector of dimension for each stage
`num_treats`	Vector of number of treatment options at each stage

Value

Observed data organised as a list of $\{y, X_1, X_2..., X_{num_stages}, A\}$ where y is a vector of the final outcomes, $X_1, X_2..., X_{num_stages}$ is a list of matrices of the intermediate covariates and A is an $n \times num_stages$ matrix of the assigned treatments

Examples

```
# ------------------------------
# Initialise Inputs
# ------------------------------
n           <- 5000
num_stages  <- 3
p_list_uvt  <- rep(1, num_stages)
p_list_mvt  <- c(1, 3, 3)
num_treats  <- rep(3, num_stages)

# ------------------------------
# Main
# ------------------------------
Data_uvt    <- generate_dataset(n, num_stages, p_list_uvt, num_treats)
Data_mvt    <- generate_dataset(n, num_stages, p_list_mvt, num_treats)
```

Index

BayesLinRegDTR.model.fit, 3
BayesLinRegDTR.model.fit(), *2*
BayesRegDTR *(*BayesRegDTR-package*)*, 2
BayesRegDTR-package, 2

future, *4*

generate_dataset, 6
generate_dataset(), *2*

handlers, *4*

plan, *4*
progressr, *4*

registerDoFuture, *4*