

Package: BayesianLasso (via r-universe)

June 3, 2026

Type Package

Title Bayesian Lasso Regression and Tools for the Lasso Distribution

Version 0.4.1

Date 2026-04-04

Maintainer Mohammad Javad Davoudabadi

<mohammad.davoudabadi@qut.edu.au>

Description Implements Bayesian Lasso regression using efficient Gibbs sampling algorithms, including modified versions of the Hans and Park Casella (PC) samplers. Includes functions for working with the Lasso distribution, such as its density, cumulative distribution, quantile, and random generation functions, along with moment calculations. Also includes a function to compute the Mills ratio. Designed for sparse linear models and suitable for high-dimensional regression problems.

License GPL-3

Imports Rcpp (>= 1.0.12)

LinkingTo Rcpp, RcppNumerical, RcppArmadillo, RcppEigen

RoxygenNote 7.3.2

Encoding UTF-8

URL <https://garhtarr.github.io/BayesianLasso/>,

<https://github.com/garhtarr/BayesianLasso>

VignetteBuilder knitr, rmarkdown

Suggests knitr, rmarkdown, monomvn, posterior, rstan, bayesreg, testthat (>= 3.0.0), MASS

Config/testthat/edition 3

BugReports <https://github.com/garhtarr/BayesianLasso/issues>

NeedsCompilation yes


```
Modified_PC_Gibbs(X, y, a1, b1, u1, v1,
                  nsamples, lambda_init, sigma2_init, thin, verbose)
```

Arguments

x, q	Vector of quantiles (vectorized).
p	Vector of probabilities.
a	Vector of precision parameter which must be non-negative.
b	Vector of off set parameter.
c	Vector of tuning parameter which must be non-negative values.
n	Number of observations.
logarithm	Logical. If TRUE, probabilities are returned on the log scale.
d	A scalar numeric value. Represents the point at which the Mills ratio is evaluated.
X	Design matrix (numeric matrix).
y	Response vector (numeric vector).
a1	Shape parameter of the prior on λ^2 .
b1	Rate parameter of the prior on λ^2 .
u1	Shape parameter of the prior on σ^2 .
v1	Rate parameter of the prior on σ^2 .
nsamples	Number of Gibbs samples to draw.
beta_init	Initial value for the model parameter β .
lambda_init	Initial value for the shrinkage parameter λ^2 .
sigma2_init	Initial value for the error variance σ^2 .
thin	Thinning interval for the MCMC chain. Only every 'thin'-th draw is stored. Default is 1 (no thinning).
verbose	Integer. If greater than 0, progress is printed every verbose iterations during sampling. Set to 0 to suppress output.
tune_lambda2	Logical; if TRUE (default), the tuning parameter λ^2 is estimated during sampling.
rao_blackwellization	Logical; if TRUE, Rao-Blackwellization is applied to improve posterior estimation. Default is FALSE.

Details

If $X \sim \text{Lasso}(a, b, c)$ then its density function is:

$$p(x; a, b, c) = Z^{-1} \exp\left(-\frac{1}{2}ax^2 + bx - c|x|\right)$$

where $x \in \mathbb{R}$, $a > 0$, $b \in \mathbb{R}$, $c > 0$, and Z is the normalizing constant.

More details are included for the CDF, quantile function, and normalizing constant in the original documentation.

Value

- `zlasso`, `dlasso`, `plasso`, `qlasso`, `rlasso`, `elasso`, `vlasso`, `mlasso`, `MillsRatio`: return the corresponding scalar or vector values related to the Lasso distribution and a numeric value representing the Mills ratio.
- `Modified_Hans_Gibbs`: returns a list containing:
 - `mBeta` Matrix of MCMC samples for the regression coefficients β , with `nsamples` rows and `p` columns.
 - `vsigma2` Vector of MCMC samples for the error variance σ^2 .
 - `vlambda2` Vector of MCMC samples for the shrinkage parameter λ^2 .
 - `mA` Matrix of sampled values for parameter a_j of the Lasso distribution for each β_j .
 - `mB` Matrix of sampled values for parameter b_j of the Lasso distribution for each β_j .
 - `mC` Matrix of sampled values for parameter c_j of the Lasso distribution for each β_j .
- `Modified_PC_Gibbs`: returns a list containing:
 - `mBeta` Matrix of MCMC samples for the regression coefficients β .
 - `vsigma2` Vector of MCMC samples for the error variance σ^2 .
 - `vlambda2` Vector of MCMC samples for the shrinkage parameter λ^2 .
 - `mM` Matrix of estimated means of the full conditional distributions of each β_j .
 - `mV` Matrix of estimated variances of the full conditional distributions of each β_j .
 - `va_til` Vector of estimated shape parameters for the full conditional inverse-gamma distribution of σ^2 .
 - `vb_til` Vector of estimated rate parameters for the full conditional inverse-gamma distribution of σ^2 .
 - `vu_til` Vector of estimated shape parameters for the full conditional inverse-gamma distribution of λ^2 .
 - `vv_til` Vector of estimated rate parameters for the full conditional inverse-gamma distribution of λ^2 .

See Also

[normalize](#) for preprocessing input data before applying the samplers.

Examples

```
a <- 2; b <- 1; c <- 3
x <- seq(-3, 3, length.out = 1000)
plot(x, dlasso(x, a, b, c, logarithm = FALSE), type = 'l')

r <- rlasso(1000, a, b, c)
hist(r, breaks = 50, probability = TRUE, col = "grey", border = "white")
lines(x, dlasso(x, a, b, c, logarithm = FALSE), col = "blue")

plasso(0, a, b, c)
qlasso(0.25, a, b, c)
elasso(a, b, c)
vlasso(a, b, c)
mlasso(a, b, c)
```

```
MillsRatio(2)

# The Modified_Hans_Gibbs() function uses the Lasso distribution to draw
# samples from the full conditional distribution of the regression coefficients.

y <- 1:20
X <- matrix(c(1:20,12:31,7:26),20,3,byrow = TRUE)

a1 <- b1 <- u1 <- v1 <- 0.01
sigma2_init <- 1
lambda_init <- 0.1
beta_init <- rep(1, ncol(X))
nsamples <- 1000
verbose <- 100
tune_lambda2 <- TRUE
rao_blackwellization <- FALSE

Output_Hans <- Modified_Hans_Gibbs(
  X, y, beta_init, a1, b1, u1, v1,
  nsamples, lambda_init, sigma2_init,
  verbose, tune_lambda2, rao_blackwellization
)

colMeans(Output_Hans$mBeta)
mean(Output_Hans$vlambda2)

Output_PC <- Modified_PC_Gibbs(
  X, y, a1, b1, u1, v1,
  nsamples, lambda_init, sigma2_init, verbose)

colMeans(Output_PC$mBeta)
mean(Output_PC$vlambda2)
```

normalize

Normalize Response and Covariates

Description

This function centers and (optionally) scales the response vector and each column of the design matrix using the population variance. It is used to prepare data for Bayesian Lasso regression.

Usage

```
normalize(y, X, scale = TRUE)
```

Arguments

<code>y</code>	A numeric response vector.
<code>X</code>	A numeric matrix or data frame of covariates (design matrix).
<code>scale</code>	Logical; if TRUE, variables are scaled to have unit population variance (default is TRUE).

Value

A list with the following elements:

- `vy`: Normalized response vector.
- `mX`: Normalized design matrix.
- `mu.y`: Mean of the response vector.
- `sigma2.y`: Population variance of the response vector.
- `mu.x`: Vector of column means of `X`.
- `sigma2.x`: Vector of population variances for columns of `X`.

Examples

```
set.seed(1)
X <- matrix(rnorm(100 * 10), 100, 10)
beta <- c(2, -3, rep(0, 8))
y <- as.vector(X %*% beta + rnorm(100))
norm_result <- normalize(y, X)
```

Index

dlasso (LassoDistribution), 2
elasso (LassoDistribution), 2
LassoDistribution, 2
MillsRatio (LassoDistribution), 2
mlasso (LassoDistribution), 2
Modified_Hans_Gibbs
 (LassoDistribution), 2
Modified_PC_Gibbs (LassoDistribution), 2
normalize, 4, 5
plasso (LassoDistribution), 2
qlasso (LassoDistribution), 2
rlasso (LassoDistribution), 2
vlasso (LassoDistribution), 2
zlasso (LassoDistribution), 2