Package: BigVAR (via r-universe)

October 8, 2026

Type Package

Title Dimension Reduction Methods for Multivariate Time Series

Version 1.1.5

Maintainer Will Nicholson <wbn8@cornell.edu>

Date 2026-03-29

Description Estimates VAR and VARX models with Structured Penalties.

Depends R (>= 3.5.0), methods, lattice

Imports MASS, zoo, Rcpp, stats, utils, grDevices, graphics, abind

License GPL (>= 2)

LazyLoad yes

LinkingTo Rcpp, RcppArmadillo, RcppEigen

URL https://github.com/wbnicholson/BigVAR

RoxygenNote 7.1.2

Encoding UTF-8

Suggests knitr, rmarkdown, gridExtra, expm, MCS, quantmod (>= 0.4.28), codetools, attempt, xts

VignetteBuilder knitr

NeedsCompilation yes

Author Will Nicholson [cre, aut], David Matteson [aut], Jacob Bien [aut]

Repository https://cran.r-universe.dev

Date/Publication 2026-03-30 08:04:46 UTC

RemoteUrl https://github.com/cran/BigVAR

RemoteRef HEAD

RemoteSha c76ff7ab68a7c713b26d0f9e3f35deb51d89949d

Contents

A . . . 2
BigVAR . . . 3
BigVAR-class . . . 4
BigVAR.est . . . 5
BigVAR.fit . . . 6
BigVAR.intermediate . . . 8
BigVAR.results . . . 9
coef . . . 11
constructModel . . . 11
CPI . . . 14
cv.BigVAR . . . 15
FFR . . . 16
GDP . . . 16
M1 . . . 16
MultVarSim . . . 17
plot . . . 18
plot.BigVAR . . . 18
predict . . . 19
PredictVARX . . . 20
show . . . 20
show.BigVAR . . . 21
SparsityPlot.BigVAR.results . . . 22
VarptoVar1MC . . . 22
VARXFit . . . 23
VARXForecastEval . . . 24
VARXLagCons . . . 26
Y . . . 27
Y1 . . . 27

Index **28**

A *Generator for Simulated Multivariate Time Series*

Description

Coefficient matrix for a stationary simulated multivariate time series

Details

Example generator matrix adapted from Table 3.2 of Gredenhoff and Karlsson (1997)

Author(s)

Will Nicholson

References

Gredenhoff, Mikael, and Sune Karlsson. "Lag-length selection in VAR-models using equal and unequal lag-length procedures." Computational Statistics 14.2 (1999): 171-187.

`BigVAR` *Dimension Reduction Methods for Multivariate Time Series.*

Description

BigVAR implements the HLAG and VARX-L frameworks which allow for the estimation of vector autoregressions and vector autoregressions with exogenous variables using structured convex penalties. This package originated as a 2014 Google "Summer of Code" Project. The development version of this package is hosted on github: `https://github.com/wbnicholson/BigVAR`.

Details

To use the facilities of this package, starting with an $T \times k + m$ multivariate time series (in which T denotes the length of the series, k the number of endogenous or "model") and run `constructModel` to create an object of class `BigVAR`. `cv.BigVAR` creates an object of class `BigVAR.results`, which chooses an optimal penalty parameter based on minimizing h-step ahead forecasts on a specified cross-validation period over a grid of values as well as comparisons against AIC, BIC, unconditional mean, and a random walk. There are plot functions for both BigVAR (`plot.BigVAR`) and BigVAR.results (`plot`) as well as a predict function for BigVAR.results (`predict`).

Author(s)

Will Nicholson <wbn8@cornell.edu>,

References

Lutkepohl "New Introduction to Multivariate Time Series", Banbura, Marta, Domenico Giannone, and Lucrezia Reichlin. 'Large Bayesian vector auto regressions.' Journal of Applied Econometrics 25.1 (2010): 71-92. Breheny P, Huang J (2011). "Coordinate descent algorithms for nonconvex penalized regression, with applications to biological feature selection." Annals of Applied Statistics, 5(1), 232–253. Nicholson, William, I. Wilms, J. Bien, and D. S. Matteson. High dimensional forecasting via interpretable vector autoregression. Journal of Machine Learning Research, 21(166):1–52, 2020. William B. Nicholson, David S. Matteson, Jacob Bien,VARX-L: Structured regularization for large vector autoregressions with exogenous variables, International Journal of Forecasting, Volume 33, Issue 3, 2017, Pages 627-651, William B Nicholson, David S. Matteson, and Jacob Bien (2016), 'BigVAR: Tools for Modeling Sparse High-Dimensional Multivariate Time Series' arxiv:1702.07094

See Also

`constructModel`, `cv.BigVAR`, `BigVAR.results`, `plot`, `predict`

Examples

```
# Fit a Basic VAR-L(3,4) on simulated data
data(Y)
T1=floor(nrow(Y)/3)
T2=floor(2*nrow(Y)/3)
m1=constructModel(Y,p=4,struct="Basic",gran=c(50,10),verbose=FALSE,T1=T1,T2=T2,IC=FALSE)
plot(m1)
results=cv.BigVAR(m1)
plot(results)
predict(results,n.ahead=1)
```

`BigVAR-class` *BigVAR Object Class*

Description

An object class to be used with cv.BigVAR

Details

To construct an object of class BigVAR, use the function `constructModel`

Slots

`Data` a $T \times k$ multivariate time series

`model_data` processed time series and lag matrix

`lagmax` Maximal lag order for modeled series

`intercept` Indicator as to whether an intercept should be included

`Structure` Penalty Structure

`Relaxed` Indicator for relaxed VAR

`Granularity` Granularity of penalty grid

`horizon` Desired Forecast Horizon

`crossval` Cross-Validation Procedure

`Minnesota` Minnesota Prior Indicator

`verbose` Indicator for Verbose output

`dates` dates extracted from an xts object

`ic` Indicator for including AIC and BIC benchmarks

`VARX` VARX Model Specifications

`VARXI` VARX Indicator

`T1` Index of time series in which to start cross validation

`T2` Index of times series in which to start forecast evaluation

`ONESE` Indicator for 'One Standard Error Heuristic'

`ownlambdas` Indicator for user-supplied lambdas

`tf` Indicator for transfer function

`alpha` Grid of candidate alpha values (applies only to Sparse VARX-L and Elastic Net models)

`recursive` Indicator as to whether recursive multi-step forecasts are used (applies only to multiple horizon VAR models)

`constvec` vector indicating variables to shrink toward a random walk instead of toward zero (valid only if Minnesota is `TRUE`)

`tol` optimization tolerance

`window.size` size of rolling window. If set to NULL an expanding window will be used.

`separate_lambdas` indicator to use separate penalty parameter for each time series (default `FALSE`)

`loss` Loss function to select penalty parameter (one of 'L1','L2','Huber').

`delta` delta parameter for Huber loss (default 2.5)

`gamma` gamma parameter for SCAD or MCP penalty (default 3)

`rolling_oos` True or False: indicator to update the penalty parameter over the evaluation period (default `False`)

`linear` indicator for linearly decrementing penalty grid (FALSE is log-linear).

`refit_fraction` fraction of least squares refit to incorporate (default is 1).

See Also

`constructModel`

`BigVAR.est` *BigVAR Estimation*

Description

Fit a BigVAR object with a structured penalty (VARX-L or HLAG).

Usage

```
BigVAR.est(object)
```

Arguments

`object`	BigVAR object created from `ConstructModel`

Details

Fits HLAG or VARX-L model on a BigVAR object. Does not perform cross-validation. This method allows the user to construct their own penalty parameter selection procedure.

Value

An array of $k \times kp \times n$ or $k \times kp + ms \times n$ coefficient matrices; one for each of the n values of lambda.

See Also

constructModel, BigVAR.results,cv.BigVAR

Examples

```
data(Y)
Y=Y[1:100,]
#construct a Basic VAR-L
Model1=constructModel(Y,p=4,struct='Basic',gran=c(50,10))
BigVAR.est(Model1)
```

BigVAR.fit *Simple function to fit BigVAR model with fixed penalty parameter*

Description

Simple function to fit BigVAR model with fixed penalty parameter

Usage

```
BigVAR.fit(
  Y,
  p,
  struct,
  lambda,
  alpha = NULL,
  VARX = list(),
  separate_lambdas = F,
  MN = F,
  C = as.double(NULL),
  intercept = TRUE,
  tf = F,
  tol = 1e-04,
  RVAR = F,
  refit_fraction = 1,
  beta = NULL,
  gamma = 3
)
```

Arguments

Y	$T \times k$ multivariate time series or Y $T \times (k+m)$ endogenous and exogenous series, respectively
p	Predetermined maximal lag order (for modeled series)
struct	The choice of penalty structure (see details).
lambda	vector or matrix of penalty parameters.
alpha	grid of candidate parameters for the alpha in the Sparse Lag and Sparse Own/Other VARX-L
VARX	List containing VARX model specifications.
separate_lambdas	indicator for separate penalty parameters for each time series (default FALSE)
MN	Minnesota Prior Indicator
C	vector of coefficients to shrink toward a random walk (if MN is TRUE)
intercept	True or False: option to fit an intercept
tf	transfer function indicator (i.e. VARX in which p=0 & s>0) (default false)
tol	optimization tolerance (default 1e-4)
RVAR	True or False: option to refit based upon the support selected using the Relaxed-VAR procedure
refit_fraction	fraction of least squares refit to incorporate (default 1)
beta	optional $k \times (k \times p + m \times s + 1)$ coefficient matrix to use as a 'warm start' (default NULL)
gamma	additional parameter for SCAD/MCP penalty (default 3)

@details The choices for 'struct' are as follows

- 'Basic' (Basic VARX-L)
- 'BasicEN' (Basic Elastic Net VARX-L)
- 'Lag' (Lag Group VARX-L)
- 'SparseLag' (Lag Sparse Group VARX-L)
- 'OwnOther' (Own/Other Group VARX-L)
- 'SparseOO' (Own/Other Sparse Group VARX-L)
- 'EFX' (Endogenous First VARX-L)
- 'HLAGC' (Componentwise HLAG)
- 'HLAGOO' (Own/Other HLAG)
- 'HLAGELEM' (Elementwise HLAG)
- 'Tapered' (Lag weighted Lasso VAR)
- 'BGR' (Bayesian Ridge Regression (cf. Banbura et al))
- 'MCP' (Minimax Concave Penalty (cf. Breheny and Huang))
- 'SCAD' (Smoothly Clipped Absolute Deviation (cf. Breheny and Huang))

VARX specifications consist of a list with entry k denoting the series that are to be modeled and entry s to denote the maximal lag order for exogenous series.

The argument alpha is ignored unless the structure choice is 'SparseLag' or 'Lag.' By default 'alpha' is set to NULL and will be initialized as 1/(k+1) in cv.BigVAR and BigVAR.est. Any user supplied values must be between 0 and 1.

Note

The specifications 'Basic', 'Lag,' 'SparseLag,' 'SparseOO,' and 'OwnOther' can accommodate both VAR and VARX models. EFX only applies to VARX models. 'HLAGC,' 'HLAGOO,' 'HLAGELEM,' and 'Tapered' can only be used with VAR models. Our implementation of the SCAD and MCP penalties is heavily influenced by the implementation in `ncvreg`.

References

Banbura, Marta, Domenico Giannone, and Lucrezia Reichlin. 'Large Bayesian vector auto regressions.' Journal of Applied Econometrics 25.1 (2010): 71-92. Breheny P, Huang J (2011). "Coordinate descent algorithms for nonconvex penalized regression, with applications to biological feature selection." Annals of Applied Statistics, 5(1), 232–253. William B Nicholson, Jacob Bien, and David S Matteson. 'High Dimensional Forecasting via Interpretable Vector Autoregression.' arXiv preprint arXiv:1412.5250, 2016. William B. Nicholson, David S. Matteson, Jacob Bien,VARX-L: Structured regularization for large vector autoregressions with exogenous variables, International Journal of Forecasting, Volume 33, Issue 3, 2017, Pages 627-651, William B Nicholson, David S. Matteson, and Jacob Bien (2016), 'BigVAR: Tools for Modeling Sparse High-Dimensional Multivariate Time Series' arxiv:1702.07094

See Also

`cv.BigVAR`,`BigVAR.est`,`constructModel`

Examples

```
# VARX Example
# Fit a Basic VARX-L with k=2, m=1, s=2, p=4, lambda=1e-2
VARX <- list()
VARX$k <- 2 # indicates that the first two series are modeled
VARX$s <- 2 # sets 2 as the maximal lag order for exogenous series
data(Y)
BigVAR.fit(Y, p = 4, "Basic", lambda = 1e-2, VARX = VARX)
```

`BigVAR.intermediate` *BigVAR.intermediate This class contains the in-sample results for cv.BigVAR*

Description

It inherits the class BigVAR, and contains the results from rolling validation

Fields

`ZFull` List containing full lag matrix and time series

`InSampMSFE` In-sample MSFE from optimal value of lambda

`LambdaGrid` Grid of candidate lambda values

`index` Index order of optimal lambda value

`OptimalLambda` Value of lambda that minimizes MSFE

`Data` a $T \times k$ or $T \times k + m$ multivariate time Series

`lagmax` Maximal lag order

`Structure` Penalty structure

`Relaxed` Indicator for relaxed VAR

`Granularity` Granularity of penalty grid

`horizon` Desired forecast horizon

`crossval` Cross-Validation procedure

`alpha` additional penalty parameter for Sparse Lag Group or Sparse Own/Other methods. Will contain either the heuristic choice of $1/(k+1)$ or the value selected by cross validation if the argument `dual` is set to `TRUE`

`Minnesota` Minnesota Prior Indicator

`verbose` verbose indicator

`dual` indicator as to whether dual cross validation was conducted

`contemp` indicator if contemporaneous exogenous predictors are used

Note

One can also access any object of class BigVAR from BigVAR.intermediate

Author(s)

Will Nicholson

`BigVAR.results` *BigVAR.results This class contains the results from cv.BigVAR.*

Description

It inherits the class BigVAR, but contains substantially more information.

Fields

`InSampMSFE` In-sample MSFE from optimal value of lambda

`LambdaGrid` Grid of candidate lambda values

`index` Rank of optimal lambda value

`OptimalLambda` Value of lambda that minimizes MSFE

`OOSMSFE` Average Out of sample MSFE of BigVAR model with optimal lambda

`seoosfmsfe` Standard error of out of sample MSFE of BigVAR model with optimal lambda

`MeanMSFE` Average out of sample MSFE of unconditional mean forecast

`MeanSD` Standard error of out of sample MSFE of unconditional mean forecast

`MeanPreds` predictions from conditional mean model

`RWMSFE` Average out of sample MSFE of random walk forecast

`RWPreds` Predictions from random walk model

`RWSD` Standard error of out of sample MSFE of random walk forecast

`AICMSFE` Average out of sample MSFE of AIC forecast

`AICSD` Standard error of out of sample MSFE of AIC forecast

`AICPreds` Predictions from AIC VAR/VARX model

`AICpvec` Lag orders selected from AIC VAR model

`AICpvec` Lag orders selected from AIC VARX model

`BICMSFE` Average out of sample MSFE of BIC forecast

`BICSD` Standard error of out of sample MSFE of BIC forecast

`BICPreds` Predictions from BIC VAR/VARX model

`BICpvec` Lag orders selected from BIC VAR model

`BICpvec` Lag orders selected from BIC VARX model

`betaPred` The final estimated $k \times kp + ms + 1$ coefficient matrix, to be used for prediction

`Zvals` The final lagged values of `Y`, to be used for prediction

`fitted` fitted values obtained from betaPred

`resids` residuals obtained from betaPred

`Data` a $T \times k$ or $T \times k + m$ multivariate time Series

`lagmax` Maximal lag order

`Structure` Penalty structure

`Relaxed` Indicator for relaxed VAR

`Granularity` Granularity of penalty grid

`horizon` Desired forecast horizon

`crossval` Cross-Validation procedure

`alpha` additional penalty parameter for Sparse Lag Group or Sparse Own/Other methods. Will contain either the heuristic choice of $1/(k+1)$ or the value selected by cross validation if the argument `dual` is set to `TRUE`

`VARXI` VARX Indicator

`Minnesota` Minnesota Prior Indicator

`verbose` verbose indicator

`dual` indicator as to whether dual cross validation was conducted

`contemp` indicator if contemporaneous exogenous predictors are used

`lagmatrix` matrix of lagged values used to compute residuals (of which Zvals is the final column)

`betaArray` array of VAR/VARX coefficients from out of sample forecasts

`sparse_count` average fraction of active coefficients in validation period

`lambda_evolve_path` evolution of lambda over evaluation period

Note

One can also access any object of class BigVAR from BigVAR.results

Author(s)

Will Nicholson

---

coef *Default coef method BigVAR-results, returns the last coefficient matrix from the evaluation period*

Description

Default coef method BigVAR-results, returns the last coefficient matrix from the evaluation period

Usage

```
## S4 method for signature 'BigVAR.results'
coef(object)
```

Arguments

object	BigVAR.results object created from cv.BigVAR

Details

displays formatted coefficient matrix

---

constructModel *Construct an object of class BigVAR*

Description

Construct an object of class BigVAR

Usage

```
constructModel(
  Y,
  p,
  struct,
  gran,
  h = 1,
  cv = "Rolling",
  verbose = TRUE,
```

```
  IC = TRUE,
  VARX = list(),
  T1 = floor(nrow(Y)/3),
  T2 = floor(2 * nrow(Y)/3),
  ONESE = FALSE,
  ownlambdas = FALSE,
  recursive = FALSE,
  dates = as.character(NULL),
  window.size = 0,
  separate_lambdas = FALSE,
  linear = FALSE,
  loss = "L2",
  rolling_oos = FALSE,
  model.controls = list()
)
```

Arguments

Y	$T \times k$ multivariate time series or Y $T \times (k+m)$ endogenous and exogenous series, respectively.
p	Predetermined maximal lag order (for modeled series).
struct	The choice of penalty structure (see details).
gran	vector of penalty parameter specifications.
h	Desired forecast horizon.
cv	Cross-validation approach, either 'Rolling' for rolling cross-validation or 'LOO' for leave-one-out cross-validation. 'None' for use with BigVAR.fit.
verbose	Verbose output while estimating.
IC	True or False: whether to include AIC and BIC benchmarks.
VARX	List containing VARX model specifications.
T1	Index of time series in which to start cross validation.
T2	Index of times series in which to start forecast evaluation.
ONESE	True or False: whether to use the 'One Standard Error Heuristic.'
ownlambdas	True or False: Indicator for user-supplied penalty parameters.
recursive	True or False: Indicator as to whether iterative multi-step predictions are desired in the VAR context if the forecast horizon is greater than 1.
dates	optional vector of dates corresponding to Y.
window.size	size of rolling window. If set to 0 an expanding window will be used.
separate_lambdas	indicator for separate penalty parameters for each time series (default FALSE).
linear	indicator for linearly decrementing penalty grid (FALSE is log-linear; default FALSE).
loss	Loss function to select penalty parameter (one of 'L1','L2','Huber')
rolling_oos	True or False: indicator to update the penalty parameter over the evaluation period (default False)
model.controls	named list of control parameters for BigVAR model estimation (see details).

Details

The choices for 'struct' are as follows

- 'Basic' (Basic VARX-L)
- 'BasicEN' (Elastic Net VARX-L)
- 'Lag' (Lag Group VARX-L)
- 'SparseLag' (Lag Sparse Group VARX-L)
- 'OwnOther' (Own/Other Group VARX-L)
- 'SparseOO' (Own/Other Sparse Group VARX-L)
- 'EFX' (Endogenous First VARX-L)
- 'HLAGC' (Componentwise HLAG)
- 'HLAGOO' (Own/Other HLAG)
- 'HLAGELEM' (Elementwise HLAG)
- 'Tapered' (Lag weighted Lasso VAR)
- 'BGR' (Bayesian Ridge Regression (cf. Banbura et al))
- 'MCP' (Minimax Concave Penalty (cf. Breheny and Huang))
- 'SCAD' (Smoothly Clipped Absolute Deviation Penalty (cf. Breheny and Huang))

The first number in the vector 'gran' specifies how deep to construct the penalty grid and the second specifies how many penalty parameters to use If ownlambas is set to TRUE, gran should contain the user-supplied penalty parameters.

VARX specifications consist of a named list with entry k denoting the series that are to be modeled and entry s to denote the maximal lag order for exogenous series.

As the capabilities of BigVAR have expanded, we have decided to consolidate parameters in the list model.controls. These parameters include:

- 'alpha:' grid of candidate parameters for the alpha in the Basic Elastic Net, Sparse Lag, Sparse Own/Other VARX-L.
- 'C:' vector of coefficients to shrink toward a random walk (if `MN` is `TRUE`).
- 'delta:' parameter for Huber loss (default 2.5)
- 'intercept:' option to fit an intercept, default `TRUE`
- 'loss:' Loss function to select penalty parameter (one of 'L1','L2','Huber')
- 'MN:' Minnesota Prior Indicator, default `FALSE`
- 'RVAR:' option to refit based upon the support selected using the Relaxed-VAR procedure (default FALSE).
- 'refit_fraction:' If RVAR is `TRUE`, proportional tradeoff between least squares fit and penalized fit (default 1).
- 'tol:' optimization tolerance (default 1e-4)

The argument alpha is ignored unless the structure choice is 'SparseLag' or 'Lag.' By default 'alpha' is set to `NULL` and will be initialized as 1/(k+1) in `cv.BigVAR` and `BigVAR.est`. Any user supplied values must be between 0 and 1.

Note

The specifications 'Basic','BasicEN', 'Lag,' 'SparseLag,' 'SparseOO','OwnOther', 'MCP', and 'SCAD.' can accommodate both VAR and VARX models. EFX only applies to VARX models. 'HLAGC,' 'HLAGOO,' 'HLAGELEM,' and 'Tapered' can only be used with VAR models. Our implementation of the SCAD and MCP penalties is heavily influenced by the package `ncvreg`.

References

Banbura, Marta, Domenico Giannone, and Lucrezia Reichlin. 'Large Bayesian vector auto regressions.' Journal of Applied Econometrics 25.1 (2010): 71-92. Breheny P, Huang J (2011). "Coordinate descent algorithms for nonconvex penalized regression, with applications to biological feature selection." Annals of Applied Statistics, 5(1), 232–253. Nicholson, William, I. Wilms, J. Bien, and D. S. Matteson. High dimensional forecasting via interpretable vector autoregression. Journal of Machine Learning Research, 21(166):1–52, 2020. William B. Nicholson, David S. Matteson, Jacob Bien,VARX-L: Structured regularization for large vector autoregressions with exogenous variables, International Journal of Forecasting, Volume 33, Issue 3, 2017, Pages 627-651, William B Nicholson, David S. Matteson, and Jacob Bien (2016), 'BigVAR: Tools for Modeling Sparse High-Dimensional Multivariate Time Series' arxiv:1702.07094

See Also

`cv.BigVAR`,`BigVAR.est`

Examples

```
# VARX Example
# Create a Basic VARX-L with k=2, m=1, s=2, p=4
VARX=list()
VARX$k=2 # indicates that the first two series are modeled
VARX$s=2 # sets 2 as the maximal lag order for exogenous series
data(Y)
T1=floor(nrow(Y)/3)
T2=floor(2*nrow(Y)/3)
Model1=constructModel(Y,p=4,struct='Basic',gran=c(50,10),verbose=FALSE,VARX=VARX,T1=T1,T2=T2)
```

CPI *US Consumer Price Index*

Description

CPI Data

Details

US Macroeconomic Time Series: CPI. Ranging from Q2 1959 to Q1 2025. Procured from FRED, Federal Reserve Bank of St. Louis.

Author(s)

Will Nicholson

`cv.BigVAR` *Cross Validation for BigVAR*

Description

Cross Validation for BigVAR

Usage

```
cv.BigVAR(object)
```

Arguments

`object`	BigVAR object created from `ConstructModel`

Details

The main function of the BigVAR package. Performs cross validation to select penalty parameters over a training sample (as the minimizer of in-sample MSFE), then evaluates them over a test set. Compares against sample mean, random walk, AIC, and BIC benchmarks. Creates an object of class `BigVAR.results`

Value

An object of class `BigVAR.results`.

See Also

`constructModel`, `BigVAR.results`,`BigVAR.est`

Examples

```
data(Y)
# Fit a Basic VARX-L with rolling cross validation
Model1=constructModel(Y,p=4,struct='Basic',gran=c(50,10), verbose=FALSE)
results=cv.BigVAR(Model1)
```

FFR *US Federal Funds Rate*

Description

FFR Data

Details

US Macroeconomic Time Series: FFR. Ranging from Q2 1959 to Q1 2025. Procured from FRED, Federal Reserve Bank of St. Louis.

Author(s)

Will Nicholson

GDP *US Gross Domestic Product*

Description

GDP Data

Details

US Macroeconomic Time Series: GDP. Ranging from Q2 1959 to Q1 2025. Procured from FRED, Federal Reserve Bank of St. Louis.

Author(s)

Will Nicholson

M1 *US M1*

Description

M1 Data

Details

US Macroeconomic Time Series: M1. Ranging from Q2 1959 to Q1 2025. Procured from FRED, Federal Reserve Bank of St. Louis.

Author(s)

Will Nicholson

MultVarSim *Simulate a VAR*

Description

Simulate a VAR

Usage

```
MultVarSim(k, A1, p, Sigma, T)
```

Arguments

k	Number of Series
A1	Either a $k \times k$ coefficient matrix or a $kp \times kp$ matrix created using VarptoVar1MC.
p	Maximum Lag Order
Sigma	Residual Covariance Matrix of dimension $k \times k$
T	Number of simulations

Value

Returns a $T \times k$ of realizations from a VAR.

References

Lutkepohl, 'A New Introduction to Multiple Time Series Analysis'

See Also

VarptoVar1MC

Examples

```
k=3;p=6
B=matrix(0,nrow=k,ncol=p*k)
A1<- matrix(c(.4,-.02,.01,-.02,.3,.02,.01,.04,.3),ncol=3,nrow=3)
A2 <- matrix(c(.2,0,0,0,.3,0,0,0,.13),ncol=3,nrow=3)
B[,1:k]=A1
B[,(4*k+1):(5*k)]=A2
A <- VarptoVar1MC(B,p,k)
Y <-MultVarSim(k,A,p,.1*diag(k),100)
```

plot *Plot an object of class BigVAR.results*

Description

Plot an object of class BigVAR.results

Usage

```
## S4 method for signature 'BigVAR.results'
plot(x, y = NULL, ...)
```

Arguments

x	BigVAR.results object created from cv.BigVAR
y	NULL
...	additional arguments

Details

Plots the in sample MSFE of all values of lambda with the optimal value highlighted.

plot.BigVAR *Plot a BigVAR object*

Description

Plot a BigVAR object

Usage

```
## S4 method for signature 'BigVAR'
plot(x, y = NULL, ...)
```

Arguments

x	BigVAR object created from ConstructModel
y	NULL
...	additional plot arguments

Details

Uses plot.zoo to plot each indivdual series of Y on a single plot

Value

NA, side effect is graph

See Also

constructModel

---

predict *Forecast using a BigVAR.results object*

Description

Forecast using a BigVAR.results object

Usage

```
predict(object,...)
```

Arguments

object	BigVAR.results object from cv.BigVAR
...	additional arguments affecting the predictions produced (e.g. n.ahead, confint)

Details

Provides n.ahead step forecasts using the model produced by cv.BigVAR. If confint is set to TRUE, a 95 percent confidence interval will also be returned.

See Also

cv.BigVAR

Examples

```
data(Y)
Y=Y[1:100,]
Model1=constructModel(Y,p=4,struct='Basic',gran=c(50,10),verbose=FALSE)
results=cv.BigVAR(Model1)
predict(results,n.ahead=1)
```

PredictVARX *One-step ahead predictions for VARX models*

Description

One-step ahead predictions for VARX models

Usage

```
PredictVARX(VARXRes)
```

Arguments

VARXRes	the results from VARXFit

Value

Returns a vector consisting of the out-of-sample forecasts for the provided VARXFit model.

See Also

VARXFit

Examples

```
data(Y)
# fit a VAR_3(3)
mod <- VARXFit(Y,3,NULL,NULL)
pred <-PredictVARX(mod)
```

show *Default show method for an object of class BigVAR.results*

Description

Default show method for an object of class BigVAR.results

Usage

```
## S4 method for signature 'BigVAR.results'
show(object)
```

Arguments

object	BigVAR.results object created from cv.BigVAR

Details

prints forecast results and additional diagnostic information as well as comparisons with mean, random walk, and AIC, and BIC benchmarks

See Also

cv.BigVAR,BigVAR.results

---

show.BigVAR *Default show method for an object of class BigVAR*

Description

Default show method for an object of class BigVAR

Usage

```
## S4 method for signature 'BigVAR'
show(object)
```

Arguments

object	BigVAR object created from ConstructModel

Value

Displays the following information about the BigVAR object:

- Prints the first 5 rows of Y
- Penalty Structure
- Relaxed Least Squares Indicator
- Maximum lag order
- VARX Specifications (if applicable)
- Start, end of cross validation period

See Also

constructModel

SparsityPlot.BigVAR.results *Sparsity Plot of a BigVAR.results object*

Description

Sparsity Plot of a BigVAR.results object

Usage

```
SparsityPlot.BigVAR.results(object)
```

Arguments

object	BigVAR.results object

Details

Uses levelplot from the lattice package to plot the magnitude of each coefficient in the last coefficient estimated by cv.BigVAR.

Value

NA, side effect is graph

See Also

cv.BigVAR, BigVAR.results

Examples

```
data(Y)
Y <- Y[1:100,]
Model1 <- constructModel(Y,p=4,struct='Basic',gran=c(50,10),verbose=FALSE)
SparsityPlot.BigVAR.results(cv.BigVAR(Model1))
```

VarptoVar1MC *Converts a VAR coefficient matrix of order p to multiple companion form*

Description

Converts a VAR coefficient matrix of order p to multiple companion form

Usage

```
VarptoVar1MC(B, p, k)
```

Arguments

B	a $k \times kp$ coefficient matrix
p	Lag order
k	Number of Series

Value

Returns a $kp \times kp$ coefficient matrix representing all coefficient matrices contained in Ai as a VAR(1).

References

See page 15 of Lutkepohl, 'A New Introduction to Multiple Time Series Analysis'

See Also

MultVarSim

Examples

```
k=3;p=6
B=matrix(0,nrow=k,ncol=p*k)
A1<- matrix(c(.4,-.02,.01,-.02,.3,.02,.01,.04,.3),ncol=3,nrow=3)
A2 <- matrix(c(.2,0,0,0,.3,0,0,0,.13),ncol=3,nrow=3)
B[,1:k]=A1
B[,(4*k+1):(5*k)]=A2
A <- VarptoVar1MC(B,p,k)
```

VARXFit *Fit a VAR or VARX model by least squares*

Description

Fit a VAR or VARX model by least squares

Usage

```
VARXFit(Y, p, IC, VARX = NULL)
```

Arguments

Y	a $t \times k$ multivariate time series
p	maximum lag order
IC	Information criterion indicator, if set to NULL, it will fit a least squares VAR(X) of orders p and s. Otherwise, if set to 'AIC' or 'BIC' it return the model with lag orders that minimize the given IC.
VARX	a list of VARX specifications (as in constructModel (or NULL)

Details

This function uses a modified form of the least squares technique proposed by Neumaier and Schneider (2001). It fits a least squares VAR or VARX via a QR decomposition that does not require explicit matrix inversion. This results in improved computational performance as well as numerical stability over the conventional least squares approach.

Value

Returns a list with four entries:

'Bhat'	Estimated $k \times kp + ms$ coefficient matrix
'SigmaU	Estimated $k \times k$ residual covariance matrix
'phat'	Selected lag order for VAR component
'shat'	Selected lag order for VARX component
'Y'	multivariate time series retained for prediction purposes
'Y'	number of endogenous (modeled) time series

References

Neumaier, Arnold, and Tapio Schneider. 'Estimation of parameters and eigenmodes of multivariate autoregressive models.' ACM Transactions on Mathematical Software (TOMS) 27.1 (2001): 27-57.

See Also

constructModel, cv.BigVAR,BigVAR.fit

Examples

```
data(Y)
# fit a VAR_3(3)
mod <- VARXFit(Y,3,NULL,NULL)
# fit a VAR_3 with p= 6 and lag selected according to AIC
modAIC <- VARXFit(Y,6,'AIC',NULL)
# Fit a VARX_{2,1} with p=6, s=4 and lags selected by BIC
modXBIC <- VARXFit(Y,6,'BIC',list(k=1,s=4))
```

VARXForecastEval *Evaluate forecasts from a VAR or VARX with lag orders selected by AIC/BIC*

Description

Evaluate forecasts from a VAR or VARX with lag orders selected by AIC/BIC

Usage

```
VARXForecastEval(
  Y,
  X,
  p,
  s,
  T1,
  T2,
  IC,
  h,
  iterated = FALSE,
  loss = "L2",
  delta = 2.5
)
```

Arguments

Y	a $T \times k$ multivariate time series
X	a $T \times m$ multivariate time series of unmodeled exogenous variables
p	maximum lag order for endogenous series
s	maximum lag order for exogenous series
T1	start of forecast evaluation period.
T2	end of forecast evaluation period
IC	specifies whether to select lag order according to 'AIC' or 'BIC'
h	desired forecast horizon
iterated	indicator as to whether to use iterated or direct multistep forecasts (if applicable, VAR context only)
loss	loss function (default 'L2', one of 'L1','L2','Huber')
delta	delta for Huber loss function (default 2.5)

Details

This function evaluates the one-step ahead forecasts of a VAR or VARX fit by least squares over an evaluation period. At every point in time, lag orders for the endogenous and exogenous series are selected according to AIC or BIC. This function is run automatically when `cv.BigVAR` is called unless `ic` is set to `FALSE` in `constructModel`.

Value

Returns the one-step ahead MSFE as well as the forecasts over the evaluation period and lag order selected.

References

Neumaier, Arnold, and Tapio Schneider. 'Estimation of parameters and eigenmodes of multivariate autoregressive models.' ACM Transactions on Mathematical Software (TOMS) 27.1 (2001): 27-57.

See Also

VARXFit,constructModel, cv.BigVAR

Examples

```
data(Y)

# Evaluate the performance of a VAR with lags selected by BIC.
p <- 4
T1 <- floor(nrow(Y))/3
T2 <- floor(2*nrow(Y))/3
# Matrix of zeros for X
X <- matrix(0,nrow=nrow(Y),ncol=ncol(Y))
BICMSFE <- VARXForecastEval(Y,X,p,0,T1,T2,'BIC',1)
```

VARXLagCons *Construct a VAR or VARX lag matrix*

Description

Construct a VAR or VARX lag matrix

Usage

```
VARXLagCons(Y, X = NULL, p, s = 0, oos = FALSE, contemp = FALSE)
```

Arguments

Y	a $T \times k$ matrix of endogenous (modeled) series
X	a $T \times m$ matrix of exogenous (unmodeled) series (default NULL)
p	Endogenous Lag order
s	exogenous lag order (default zero)
oos	indicator as to whether the data should be constructed for out of sample prediction (i.e. last available entries of Y as final lags default FALSE)
contemp	indicator as to whether to use contemporaneous exogenous predictors (for example, if exogenous series become available before exogenous default FALSE).

Details

This function is not required unless you which to design your own cross validation routine.

Value

list with two entries:

'Z'	$kp + ms + 1 \times T - max(p, s)$ VARX lag matrix
'Y'	adjusted $k \times T - max(p, s)$ endogenous series

References

See page 15 of Lutkepohl, 'A New Introduction to Multiple Time Series Analysis

See Also

MultVarSim

Examples

```
data(Y)
# construct VAR lag matrix with p=4
ZZ<-VARXLagCons(Y,X=NULL,p=4,s=0)
```

Y *Simulated Multivariate Time Series*

Description

Realization of a simulated multivariate time series

Details

100×3 multivariate time series distributed according to the generator matrix A.

Author(s)

Will Nicholson

Y1 *Example US quarterly macroeconomic data*

Description

Example multivariate macroeconomic time series

Details

US Macroeconomic Time Series: CPI, Federal Funds Rate, Gross Domestic Product, and M1. Ranging from Q2 1959 to Q1 2025. Procured from FRED, Federal Reserve Bank of St. Louis.

Author(s)

Will Nicholson

Index

A, 2, *27*

BigVAR, 3, *3*
BigVAR-class, 4
BigVAR.est, 5, *8*, *14, 15*
BigVAR.est,BigVAR-method *(*BigVAR.est*)*, 5
BigVAR.fit, 6, *24*
BigVAR.intermediate, 8
BigVAR.intermediate-class *(*BigVAR.intermediate*)*, 8
BigVAR.results, *3*, *6*, 9, *15*, *21, 22*
BigVAR.results-class *(*BigVAR.results*)*, 9

coef, 11
coef,BigVAR.results-method *(*coef*)*, 11
coef-methods *(*coef*)*, 11
constructModel, *3–6*, *8*, 11, *15*, *19*, *21*, *23–26*
CPI, 14
cv.BigVAR, *3*, *6*, *8*, *14*, 15, *19*, *21, 22*, *24–26*
cv.BigVAR,BigVAR-method *(*cv.BigVAR*)*, 15

FFR, 16

GDP, 16

M1, 16
MultVarSim, 17, *23*, *27*

plot, *3*, 18
plot,BigVAR-method *(*plot.BigVAR*)*, 18
plot,BigVAR.results-method *(*plot*)*, 18
plot-methods *(*plot*)*, 18
plot.BigVAR, *3*, 18
predict, *3*, 19
predict,BigVAR.results-method *(*predict*)*, 19
PredictVARX, 20

show, 20
show,BigVAR-method *(*show.BigVAR*)*, 21
show,BigVAR.results-method *(*show*)*, 20
show.BigVAR, 21
SparsityPlot.BigVAR.results, 22
SparsityPlot.BigVAR.results,BigVAR.results-method *(*SparsityPlot.BigVAR.results*)*, 22

VarptoVar1MC, *17*, 22
VARXFit, *20*, 23, *26*
VARXForecastEval, 24
VARXLagCons, 26

Y, 27
Y1, 27