

Package: CBPE (via r-universe)

September 10, 2024

Type Package

Title Correlation-Based Penalized Estimators

Version 0.1.0

Maintainer Mina Norouzirad <mina.norouzirad@gmail.com>

Description Provides correlation-based penalty estimators for both linear and logistic regression models by implementing a new regularization method that incorporates correlation structures within the data. This method encourages a grouping effect where strongly correlated predictors tend to be in or out of the model together. See Tutz and Ulbricht (2009) <doi:10.1007/s11222-008-9088-5> and Algamal and Lee (2015) <doi:10.1016/j.eswa.2015.08.016>.

License GPL (>= 2)

URL <https://github.com/mnrzrad/CBPE>

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 3.5)

Imports stats

NeedsCompilation no

Author Mohammad Arashi [ctb]
(<<https://orcid.org/0000-0002-5881-9241>>), Mahdi Rahimi [ctb],
Mina Norouzirad [aut, cre, cph]
(<<https://orcid.org/0000-0003-0311-6888>>), FCT, I.P. [fnd]
(under the scope of the projects UIDB/00297/2020 and
UIDP/00297/2020 (NovaMath))

Repository CRAN

Date/Publication 2024-07-02 15:30:02 UTC

Contents

CBPLinearE	2
CBPLogisticE	3

Index**5**

CBPLinearE

*Correlation-based Estimator for Linear Regression Models***Description**

This function computes the correlation-based estimator for linear regression models.

Usage

```
CBPLinearE(X, y, lambda)
```

Arguments

X	A numeric matrix of predictors where rows represent observations and columns represent variables.
y	A numeric vector of response variables.
lambda	A regularization parameter.

Details

The correlation-based penalized linear estimator is calculated as:

$$\hat{\beta} = \operatorname{argmin} \left\{ \sum_{i=1}^n (y_i - \mathbf{x}_i^T \boldsymbol{\beta})^2 + \lambda \sum_{i=1}^{p-1} \sum_{j>i} \left(\frac{(\beta_i - \beta_j)^2}{1 - \rho_{ij}} + \frac{(\beta_i + \beta_j)^2}{1 + \rho_{ij}} \right) \right\}$$

where ρ_{ij} denotes the (empirical) correlation between the i th and the j th predictor.

Value

A numeric vector of the estimated coefficients for the specified model.

References

Tutz, G., Ulbricht, J. (2009). Penalized regression with correlation-based penalty. *Stat Comput* 19, 239–253.

Examples

```
set.seed(42)
n <- 100
p <- 4
X <- matrix(rnorm(n * p), n, p)
beta_true <- c(0.5, -1, 2, 5)
y <- X %*% beta_true + rnorm(n)
lambda <- 0.1
```

```
result <- CBPLinearE(X, y, lambda = lambda)
print(result)
```

CBPLogisticE

Correlation-based Estimator for Logistic Regression Models

Description

This function computes the correlation-based estimator for logistic regression models.

Usage

```
CBPLogisticE(X, y, lambda, max_iter = 100, tol = 1e-06)
```

Arguments

X	A numeric matrix of predictors where rows represent observations and columns represent variables.
y	A numeric vector of binary outcomes (0 or 1).
lambda	A regularization parameter.
max_iter	An integer specifying the maximum number of iterations for the logistic regression algorithm. Default is 100.
tol	A numeric value specifying the convergence tolerance for the logistic regression algorithm. Default is 1e-10.

Details

The correlation-based penalized logistic estimator is calculated as:

$$\hat{\beta} = \operatorname{argmin} \left\{ \sum_{i=1}^n (y_i \ln(\pi_i) + (1 - y_i) \ln(1 - \pi_i)) + \lambda \sum_{i=1}^{p-1} \sum_{j>i} \left(\frac{(\beta_i - \beta_j)^2}{1 - \rho_{ij}} + \frac{(\beta_i + \beta_j)^2}{1 + \rho_{ij}} \right) \right\}$$

where $\pi_i = \Pr(y_i = 1 | \mathbf{x}_i)$ and ρ_{ij} denotes the (empirical) correlation between the i th and the j th predictor.

Value

A numeric vector of the estimated coefficients for the specified model.

References

Algamil, Z. Y., & Lee, M. H. (2015). Penalized logistic regression with the adaptive LASSO for gene selection in high-dimensional cancer classification. *Expert Systems with Applications*, 42(23), 9326-9332.

Examples

```
set.seed(42)
n <- 100
p <- 4
X <- matrix(rnorm(n * p), n, p)
beta_true <- c(0.5, -1, 2, 5)
y <- rbinom(n, 1, 1 / (1 + exp(-X %*% beta_true)))
lambda <- 0.1

result <- CBPLogisticE(X, y, lambda)
print(result)
```

Index

CBPLinearE, [2](#)
CBPLogisticE, [3](#)