

Package: CDsampling (via r-universe)

November 20, 2024

Type Package

Title 'CDsampling': Constraint Sampling in Paid Research Studies

Version 0.1.2

Maintainer Yifei Huang <yhuan39@uic.edu>

Description In the context of paid research studies and clinical trials, budget considerations and patient sampling from available populations are subject to inherent constraints. We introduce the 'CDsampling' package, which integrates optimal design theories within the framework of constrained sampling. This package offers the possibility to find both D-optimal approximate and exact allocations for samplings with or without constraints. Additionally, it provides functions to find constrained uniform sampling as a robust sampling strategy with limited model information. Our package offers functions for the computation of the Fisher information matrix under generalized linear models (including regular linear regression model) and multinomial logistic models. To demonstrate the applications, we also provide a simulated dataset and a real dataset embedded in the package. Yifei Huang, Liping Tong, and Jie Yang (2025)<[doi:10.5705/ss.202022.0414](https://doi.org/10.5705/ss.202022.0414)>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports lpSolve, Rglpk, stats

RoxygenNote 7.3.1

Depends R (>= 2.10)

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat.edition 3

NeedsCompilation no

Author Yifei Huang [aut, cre], Liping Tong [aut], Jie Yang [aut]

Repository CRAN**Date/Publication** 2024-11-19 16:00:03 UTC**Config/pak/sysreqs** libglpk-dev

Contents

approxtoexact_constrained_func	2
approxtoexact_func	4
bounded_uniform	4
Fdet_func_GLM	5
Fdet_func_MLM	6
Fdet_func_unif	7
Fi_func_MLM	8
F_func_GLM	9
F_func_MLM	10
iset_func_trauma	11
iset_func_trial	12
liftone_constrained_GLM	13
liftone_constrained_MLM	15
liftone_GLM	19
liftone_MLM	20
print.list_output	22
print.matrix_list	23
print.matrix_output	23
trauma_data	24
trial_data	24
W_func_GLM	25
Index	26

approxtoexact_constrained_func

Convert the approximate allocation (proportion) to exact allocation (integer) with bounded constraint ($ni \leq Ni$)

Description

Convert the approximate allocation (proportion) to exact allocation (integer) with bounded constraint ($ni \leq Ni$)

Usage

```
approxtoexact_constrained_func(
  n,
  w,
  m,
  beta = NULL,
  link = NULL,
  X = NULL,
  Fdet_func = Fdet_func_GLM,
  iset_func = NULL
)
```

Arguments

n	Sample size, must be a positive integer
w	Approximate allocation/proportion, must be a real-valued vector, can get from running liftone_constrained_GLM or liftone_constrained_MLM
m	The number of sampling groups
beta	Model parameter coefficients, default to be NULL for use in constrained uniform sampling
link	Link function of GLM or MLM, if used for GLM model (GLM_T is T), options are "identity", "logit", "probit", "cloglog", "loglog". If used for MLM (GLM_T is F), options are "continuation", "cumulative", "adjacent", and "baseline"
X	Design matrix of the model for GLM or MLM, default to be NULL for use in constrained uniform sampling
Fdet_func	determinant of Fisher information matrix function, Fdet_func can be self-defined, or use "Fdet_func_GLM", "Fdet_func_MLM" in the package, default is Fdet_func_GLM
iset_func	self-defined function for checking which index of sampling group fall within constraint if add 1 more subject (I set, see Algorithm 2 in Huang, Tong, Yang (2023)), two example functions are provided in the package, iset_func_trial and iset_func_trauma

Value

allocation is the exact allocation or integer value of the number of subjects sampled from the group
 allocation.real is the proportion or the approximate allocation of the number of subjects sampled from the group

det.maximum is the maximum of |F| from the current exact allocation

Examples

```
beta = c(0, 3, 3, 3) #main effect model beta_0, beta_1, beta_21, beta_22
X.liftone=matrix(data=c(1,0,0,0,1,0,1,0,1,0,0,1,1,1,0,0,1,1,1,0,1,0,1,0,1), ncol=4, byrow=TRUE)
exact_design = approxtoexact_constrained_func(n=200, w=c(0.25, 0.20, 0.05, 0.50, 0.00, 0.00),
m=6, beta=beta, link='logit', X=X.liftone, Fdet_func=Fdet_func_GLM, iset_func=set_func_trial)
```

<code>approptoexact_func</code>	<i>Convert the approximate allocation (proportion) to exact allocation (integer) without constraint</i>
---------------------------------	---

Description

Convert the approximate allocation (proportion) to exact allocation (integer) without constraint

Usage

```
approptoexact_func(n, w)
```

Arguments

- | | |
|----------------|--|
| <code>n</code> | Sample size, must be a positive integer |
| <code>w</code> | Approximate allocation/proportion, must be a real-valued vector, can get from running liftone_constrained_GLM or liftone_constrained_MLM |

Value

allocation is the exact allocation or integer value of the number of subjects sampled from the group

Examples

```
exact_design = approptoexact_func(n=600, w=c(0.2593526, 0.0000000, 0.0000000,
0.1565024, 0.2891565, 0.0000000, 0.0000000, 0.2949885))
```

<code>bounded_uniform</code>	<i>Find (constrained) uniform exact allocation of the study for bounded design</i>
------------------------------	--

Description

Find (constrained) uniform exact allocation of the study for bounded design

Usage

```
bounded_uniform(Ni, nsample)
```

Arguments

- | | |
|----------------------|---|
| <code>Ni</code> | a vector with size m, upper bound for exact design of each category/stratification group, if unconstrained, use Inf vector, the function will return unbounded uniform allocation |
| <code>nsample</code> | a number, the sample size |

Value

n is the constrained/unconstrained uniform exact allocation

Examples

```
bounded_uniform(Ni=c(50, 40, 10, 200, 150, 50), nsample=200)
```

Fdet_func_GLM

*Determinant of Fisher information matrix for GLM***Description**

Determinant of Fisher information matrix for GLM

Usage

```
Fdet_func_GLM(w, beta, X, link = "logit")
```

Arguments

w	allocation (can be exact or approximate)
beta	GLM model covariate coefficient
X	model matrix
link	link function, default "logit", choose from "logit", "cloglog", "loglog", "probit", and "identity"(for regular linear regression)

Value

the determinant of Fisher information matrix given X and model parameter beta

Examples

```
w = c(1/3,1/3, 1/3)
beta = c(0.5, 0.5, 0.5)
X = matrix(data=c(1,-1,-1,1,-1,1,1,1,-1), byrow=TRUE, nrow=3)
Fdet_func_GLM(w=w, beta=beta, X=X, link='logit')
```

Fdet_func_MLM	<i>Determinant of Fisher information matrix of multinomial logistic model (MLM)</i>
---------------	---

Description

Determinant of Fisher information matrix of multinomial logistic model (MLM)

Usage

```
Fdet_func_MLM(w, beta, X, link)
```

Arguments

w	allocation (can be exact or approximate)
beta	MLM model covariate coefficient
X	MLM model matrix
link	link function of Multinomial logistic regression model, options are "baseline", "cumulative", "adjacent", or "continuation"

Value

Determinant of the Fisher information matrix of MLM model

Examples

```
w = rep(1/8, 8)
Xi=rep(0,5*12*8) #response levels * num of parameters * num of design points
dim(Xi)=c(5,12,8)
#design matrix
Xi[, , 1] = rbind(c( 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 2] = rbind(c( 1, 2, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 2, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 1, 2, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 3] = rbind(c( 1, 3, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 3, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 1, 3, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
```

```

Xi[,4] = rbind(c( 1, 4, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 4, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 4, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,5] = rbind(c( 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,6] = rbind(c( 1, 2, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 2, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 2, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,7] = rbind(c( 1, 3, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 3, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 3, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,8] = rbind(c( 1, 4, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 4, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 4, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
bvec_temp = c(-4.047, -2.225, -0.302, 1.386, 4.214, 3.519,
2.420, 1.284, -0.131, -0.376, -0.237, -0.120)
link_temp = "cumulative"

Fdet_func_MLM(w=w, beta=bvec_temp, X=Xi, link=link_temp)

```

Fdet_func_unif

Determinant function to be used for finding constrained uniform samplings

Description

Determinant function to be used for finding constrained uniform samplings

Usage

```
Fdet_func_unif(w, beta = NULL, X = NULL, link = NULL)
```

Arguments

w	allocation (can be exact or approximate)
beta	use NULL (default to be NULL)
X	use NULL (default to be NULL)
link	use NULL (default to be NULL)

Value

product of all allocation

Examples

```
Fdet_func_unif(w=c(0.2,0.2,0.2,0.2,0.2))
```

Fi_func_MLM

Generate Fisher information matrix F_x at a design point x_i for Multinomial logistic regression model

Description

Generate Fisher information matrix F_x at a design point x_i for Multinomial logistic regression model

Usage

```
Fi_func_MLM(X_x, beta, link)
```

Arguments

X_x	model matrix given design point x_i (for example, X_x = h.func(x_i), where h.func transforms a design point to a model matrix)
beta	parameter coefficients in the Multinomial logistic regression model, the order of coefficients in bvec and the order of design points in X_x should be consistent
link	link function of Multinomial logistic regression model, options are "baseline", "cumulative", "adjacent", or "continuation"

Value

F_x is the Fisher information matrix at design point x_i (with model matrix X_x);
U_x is a middle step matrix for calculation of F_x, details see Corollary 3.1 in Bu, X., Majumdar, D., & Yang, J. (2020). D-optimal designs for multinomial logistic models

Examples

```
X_x_temp = rbind(c( 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
bvec_temp = c(-4.047, -2.225, -0.302, 1.386, 4.214, 3.519,
              2.420, 1.284, -0.131, -0.376, -0.237, -0.120)
link_temp = "cumulative"
Fi_func_MLM(X_x=X_x_temp, beta=bvec_temp, link=link_temp)
```

F_func_GLM

Fisher information matrix of generalized linear model (GLM)

Description

Fisher information matrix of generalized linear model (GLM)

Usage

```
F_func_GLM(w, beta, X, link = "logit")
```

Arguments

w	allocation (can be exact or approximate)
beta	GLM model covariate coefficient
X	model matrix
link	link function, default "logit", choose from "logit", "cloglog", "loglog", "probit", and "identity" (for regular linear regression)

Value

object of class "matrix_output", Fisher information matrix given X and model parameter beta

Examples

```
w = c(1/3,1/3, 1/3)
beta = c(0.5, 0.5, 0.5)
X = matrix(data=c(1,-1,-1,1,-1,1,1,1,-1), byrow=TRUE, nrow=3)
F_func_GLM(w=w, beta=beta, X=X, link='logit')
```

F_func_MLM*The Fisher information matrix of multinomial logistic model (MLM)***Description**

The Fisher information matrix of multinomial logistic model (MLM)

Usage

```
F_func_MLM(w, beta, X, link)
```

Arguments

w	allocation (can be exact or approximate)
beta	MLM model covariate coefficient
X	MLM model matrix
link	link function of Multinomial logistic regression model, options are "baseline", "cumulative", "adjacent", or "continuation"

Value

The Fisher information matrix of MLM model

Examples

```
w = rep(1/8, 8)
Xi=rep(0,5*12*8) #response levels * num of parameters * num of design points
dim(Xi)=c(5,12,8)
#design matrix
Xi[, , 1] = rbind(c( 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                    c( 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0),
                    c( 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0),
                    c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0),
                    c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 2] = rbind(c( 1, 2, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                    c( 0, 0, 0, 1, 2, 0, 0, 0, 0, 0, 0, 0),
                    c( 0, 0, 0, 0, 0, 0, 1, 2, 0, 0, 0, 0),
                    c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 0),
                    c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 3] = rbind(c( 1, 3, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                    c( 0, 0, 0, 1, 3, 0, 0, 0, 0, 0, 0, 0),
                    c( 0, 0, 0, 0, 0, 0, 1, 3, 0, 0, 0, 0),
                    c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 0),
                    c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 4] = rbind(c( 1, 4, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
```

```

c( 0, 0, 0, 1, 4, 0, 0, 0, 0, 0, 0, 0),
c( 0, 0, 0, 0, 0, 1, 4, 0, 0, 0, 0, 0),
c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 0),
c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,5] = rbind(c( 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,6] = rbind(c( 1, 2, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 2, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 2, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,7] = rbind(c( 1, 3, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 3, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 3, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,8] = rbind(c( 1, 4, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 4, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 4, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

bvec_temp = c(-4.047, -2.225, -0.302, 1.386, 4.214, 3.519, 2.420,
              1.284, -0.131, -0.376, -0.237, -0.120)
link_temp = "cumulative"

F_func_MLM(w=w, beta=bvec_temp, X=Xi, link=link_temp)

```

iset_func_trauma

trauma_data example (see Huang, Tong, Yang (2023)) specific function for finding index set that if allocation of that index add "1", the new allocation still falls within the constraint Used in approptoexact_constrained_func()

Description

trauma_data example (see Huang, Tong, Yang (2023)) specific function for finding index set that if allocation of that index add "1", the new allocation still falls within the constraint Used in approptoexact_constrained_func()

Usage

```
iset_func_trauma(allocation)
```

Arguments

allocation the exact allocation

Value

list of TRUE and FALSE, if TRUE, it means the allocation of this index will fall out of the constraint with more subject; if TURE, it means the allocation of this index can add more subjects

Examples

```
iset_func_trauma(allocation=c(50,30,10,10,100,100,200,10))
```

iset_func_trial *trial_data example (see Huang, Tong, Yang (2023)) specific function for finding index set that if allocation of that index add "1", the new allocation still falls within the constraint Used in approptoexact_constrained_func()*

Description

trial_data example (see Huang, Tong, Yang (2023)) specific function for finding index set that if allocation of that index add "1", the new allocation still falls within the constraint Used in approptoexact_constrained_func()

Usage

```
iset_func_trial(allocation)
```

Arguments

allocation the exact allocation

Value

list of TRUE and FALSE, if TRUE, it means the allocation of this index will fall out of the constraint with more subject; if TURE, it means the allocation of this index can add more subjects

Examples

```
iset_func_trial(allocation=c(50,30,10,100,100,40))
```

liftone_constrained_GLM

Find constrained D-optimal approximate design for generalized linear models (GLM)

Description

Find constrained D-optimal approximate design for generalized linear models (GLM)

Usage

```
liftone_constrained_GLM(
  X,
  W,
  g.con,
  g.dir,
  g.rhs,
  lower.bound,
  upper.bound,
  reltol = 1e-05,
  maxit = 500,
  random = TRUE,
  nram = 3,
  w00 = NULL,
  epsilon = 1e-12
)
```

Arguments

X	Model matrix, with nrow = num of design points and ncol = num of parameters
W	Diagonal of W matrix in Fisher information matrix, can be calculated from W_func_GLM in package
g.con	A matrix of numeric constraint coefficients, one row per constraint, one column per variable (to be used in as const.mat lp() and mat in Rglpk_solve_LP())
g.dir	Vector of character strings giving the direction of the constraint: each value should be one of "<," "<=," "=," "==" or ">" or ">=". (In each pair the two values are identical.) to be used as const.dir in lp() and dir in Rglpk_solve_LP()
g.rhs	Vector of numeric values for the right-hand sides of the constraints. to be used as const.rhs in lp() and rhs in Rglpk_solve_LP().
lower.bound	A function to determine lower bound r_i1 in Step 3 of Constrained lift-one algorithm from Yifei, H., Liping, T., Yang, J. (2023) Constrained D-optimal design for paid research study
upper.bound	A function to determine upper bound r_i2 in Step 3 of Constrained lift-one algorithm from Yifei, H., Liping, T., Yang, J. (2023) Constrained D-optimal design for paid research study

<code>reltol</code>	The relative convergence tolerance, default value 1e-5
<code>maxit</code>	The maximum number of iterations, default value 500
<code>random</code>	TRUE or FALSE, if TRUE then the function will run with additional "nram" number of random initial points, default to be TRUE
<code>nram</code>	When random == TRUE, the function will generate nram number of initial points, default is 3
<code>w00</code>	Specified initial design proportion; default to be NULL, this will generate a random initial design
<code>epsilon</code>	A very small number, for comparison of >0, <0, ==0, to reduce errors, default 1e-12

Value

`w` is the approximate D-optimal design
`w0` is the initial design used to get optimal design `w`
`maximum` is the maximized $|F|$ value
`itmax` is the number of iterations
`convergence` is TRUE or FALSE, if TRUE means the reported design is converged
`deriv.ans` is the derivative from step 6 of constrained lift-one algorithm
`gmax` is the maximum g function in step 8 of constrained lift-one algorithm
`reason` is the lift-one loops break reason, either "all derivatives ≤ 0 " or "gmax ≤ 0 "

Examples

```

#Example 6 in Section 3.4 of Yifei, H., Liping, T., Yang, J. (2025)
#Constrained D-optimal design for paid research study

#main effect model beta_0, beta_1, beta_21, beta_22
beta = c(0, -0.1, -0.5, -2)

#gives the 6 categories (0,0,0), (0,1,0),(0,0,1),(1,0,0),(1,1,0),(1,0,1)
X.liftone=matrix(data=c(1,0,0,0,1,0,1,0,1,0,0,1,1,1,0,0,1,1,1,0,1,1,0,1), 
ncol=4, byrow=TRUE)

#calculate W matrix based on beta's under logit link
W_matrix=W_func_GLM(X= X.liftone, b=beta)

m=6 #number of categories
nsample = 200
rc = c(50, 40, 10, 200, 150, 50)/nsample
g.con = matrix(0,nrow=(2*m+1), ncol=m)
g.con[1,] = rep(1, m)
g.con[2:(m+1),] = diag(m)
g.con[(m+2):(2*m+1), ] = diag(m)
g.dir = c("==", rep("<=", m), rep(">=", m))
g.rhs = c(1, rc, rep(0, m))
  
```

```

lower.bound=function(i, w){
  nsample = 200
  rc = c(50, 40, 10, 200, 150, 50)/nsample
  m=length(w) #num of categories
  temp = rep(0,m)
  temp[w>0]=1-pmin(1,rc[w>0])*(1-w[i])/w[w>0];
  temp[i]=0;
  max(0,temp);
}

upper.bound=function(i, w){
  nsample = 200
  rc = c(50, 40, 10, 200, 150, 50)/nsample
  m=length(w) #num of categories
  rc[i];
  min(1,rc[i]);
}

approximate_design = liftone_constrained_GLM(X=X.liftone, W=W_matrix,
g.con=g.con, g.dir=g.dir, g.rhs=g.rhs, lower.bound=lower.bound,
upper.bound=upper.bound, reltol=1e-10, maxit=100, random=TRUE, nram=4,
w0=NULL, epsilon = 1e-8)

```

liftone_constrained_MLM

*Find constrained D-optimal designs for Multinomial Logit Models
(MLM)*

Description

Find constrained D-optimal designs for Multinomial Logit Models (MLM)

Usage

```
liftone_constrained_MLM(
  m,
  p,
  Xi,
  J,
  beta,
  lower.bound,
  upper.bound,
  g.con,
  g.dir,
  g.rhs,
  w0 = NULL,
  link = "cumulative",
```

```

    Fi.func = Fi_func_MLM,
    reltol = 1e-05,
    maxit = 500,
    delta = 1e-06,
    epsilon = 1e-08,
    random = TRUE,
    nram = 3
)

```

Arguments

m	The number of design points; it is usually the number of combinations of all the stratification factors
p	The number of parameters in the MLM model
Xi	Model matrix, a J by p by m 3D array of predictors for separate response category at all design points(input to determine ppo,npo,po)
J	The number of response levels
beta	A p*1 vector, parameter coefficients for MLM, the order of beta should be consistent with Xi
lower.bound	A function to determine lower bound r_i1 in Step 3 of Constrained lift-one algorithm from Yifei, H., Liping, T., Yang, J. (2023) Constrained D-optimal design for paid research study
upper.bound	A function to determine upper bound r_i2 in Step 3 of Constrained lift-one algorithm from Yifei, H., Liping, T., Yang, J. (2023) Constrained D-optimal design for paid research study
g.con	A matrix of numeric constraint coefficients, one row per constraint, on column per variable (to be used in as const.mat lp() and mat in Rglpk_solve_LP())
g.dir	Vector of character strings giving the direction of the constraint: each value should be one of "<," "<=," "=," "==" ">," or ">=". (In each pair the two values are identical.) to be used as const.dir in lp() and dir in Rglpk_solve_LP()
g.rhs	Vector of numeric values for the right-hand sides of the constraints. to be used as const.rhs in lp() and rhs in Rglpk_solve_LP()
w00	Specified initial design proportion; default to be NULL, this will generate a random initial design
link	Link function of MLM, default to be "cumulative", options from "continuation", "cumulative", "adjacent", and "baseline"
Fi.func	A function for calculating Fisher information at a specific design point, default to be Fi_func_MLM function in the package
reltol	The relative convergence tolerance, default value 1e-5
maxit	The maximum number of iterations, default value 500
delta	A very small number, used in alpha_star calculation, default to be 1e-6.
epsilon	A very small number, for comparison of >0, <0, ==0, to reduce errors, default 1e-12

random	TRUE or FALSE, if TRUE then the function will run with additional "nram" number of random initial points, default to be TRUE
nram	When random == TRUE, the function will generate nram number of initial points, default is 3

Value

w is the approximate D-optimal design
w0 is the initial design used to get optimal design w
Maximum is the maximized |F| value
itmax is the number of iterations
convergence is TRUE or FALSE, if TRUE means the reported design is converged
deriv.ans is the derivative from step 6 of constrained lift-one algorithm
gmax is the maximum g function in step 8 of constrained lift-one algorithm
reason is the lift-one loops break reason, either "all derivatives <=0" or "gmax <=0"

Examples

```
#Example 8 of Trauma data example in Yifei, H., Liping, T., Yang, J. (2025)
#Constrained D-optimal design for paid research study

J = 5      # number of categories,  >= 3
p = 12     # number of parameters
m = 8       # number of design points
nsample=600 #collect 600 samples finally from the 802 subjects
lower.bound <- function(i, w0){
n = 600
constraint = c(392,410)
if(i <= 4){
  a.lower <- (sum(w0[5:8])-(constraint[2]/n)*(1-w0[i]))/(sum(w0[5:8]))
}
else{
  a.lower <- (sum(w0[1:4])-(constraint[1]/n)*(1-w0[i]))/(sum(w0[1:4]))
}
a.lower
}
upper.bound <- function(i, w0){
n = 600
constraint = c(392,410)
if(i <= 4){
  b.upper <- ((constraint[1]/n)*(1-w0[i]) - (sum(w0[1:4])-w0[i]))/(1-sum(w0[1:4]))
}
else{
  b.upper <- ((constraint[2]/n)*(1-w0[i]) - (sum(w0[5:8])-w0[i]))/(1-sum(w0[5:8]))
}
b.upper
}
```

```

constraint = c(392,410)
g.con = matrix(0,nrow=length(constraint)+1+m, ncol=m)
g.con[2:3,] = matrix(data=c(1,1,1,1,0,0,0,0,0,0,0,1,1,1,1), ncol = m, byrow=TRUE)
g.con[1,] = rep(1, m)
g.con[4:(length(constraint)+1+m), ] = diag(1, nrow=m)
g.dir = c("==", "<=", "<=", rep(">=",m))
g.rhs = c(1, ifelse((constraint/nsample<1),constraint/nsample,1), rep(0, m))
Xi=rep(0,J*p*m)
dim(Xi)=c(J,p,m)
Xi[, ,1] = rbind(c( 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,2] = rbind(c( 1, 2, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 2, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 2, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,3] = rbind(c( 1, 3, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 3, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 1, 3, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,4] = rbind(c( 1, 4, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 4, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 4, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,5] = rbind(c( 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,6] = rbind(c( 1, 2, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 2, 1, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 2, 1, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 1),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,7] = rbind(c( 1, 3, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 3, 1, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 3, 1, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 1),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
Xi[, ,8] = rbind(c( 1, 4, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 1, 4, 1, 0, 0, 0, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 1, 4, 1, 0, 0, 0, 0, 0),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 1),
                  c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))
thetavec = c(-4.3050, -0.0744, 4.3053, -2.3334, -0.3290, 3.4773,
             -0.1675, -0.3609, 2.7358, 1.2935, -0.1612, 1.4899)
set.seed(123)
liftone_constrained_MLM(m=m, p=p, Xi=Xi, J=J, beta=thetavec, lower.bound=lower.bound,

```

```
upper.bound=upper.bound, g.con=g.con,g.dir=g.dir, g.rhs=g.rhs, w0=NULL,
link='cumulative', Fi.func = Fi_func_GLM, reltol=1e-5, maxit=500,
delta = 1e-6, epsilon=1e-8, random=TRUE, nram=1)
```

liftone_GLM

Unconstrained lift-one algorithm to find D-optimal allocations for GLM

Description

Unconstrained lift-one algorithm to find D-optimal allocations for GLM

Usage

```
liftone_GLM(
  X,
  W,
  reltol = 1e-05,
  maxit = 500,
  random = TRUE,
  nram = 3,
  w0 = NULL
)
```

Arguments

X	Model matrix, with nrow = num of design points and ncol = num of parameters
W	Diagonal of W matrix in Fisher information matrix, can be calculated from W_func_GLM in package
reltol	The relative convergence tolerance, default value 1e-5
maxit	The maximum number of iterations, default value 500
random	TRUE or FALSE, if TRUE then the function will run with additional "nram" number of random initial points, default to be TRUE
nram	When random == TRUE, the function will generate nram number of initial points, default is 3
w0	Specified initial design proportion; default to be NULL, this will generate a random initial design

Value

w is the approximate D-optimal design

w0 is the initial design used to get optimal design w

Maximum is the maximized |F| value

itmax is the number of iterations

convergence is TRUE or FALSE, if TRUE means the reported design is converged

Examples

```
beta = c(0.5, 0.5, 0.5)
X = matrix(data=c(1,-1,-1,1,-1,1,1,1,-1), byrow=TRUE, nrow=3)
W_matrix = W_func_GLM(X=X, beta=beta)
w00 = c(1/6, 1/6, 2/3)
approximate_design = liftone_GLM(X=X, W=W_matrix, reltol=1e-10, maxit=100,
random=FALSE, nram=3, w00=w00)
```

liftone_MLM

Unconstrained lift-one algorithm to find D-optimal allocations for MLM

Description

Unconstrained lift-one algorithm to find D-optimal allocations for MLM

Usage

```
liftone_MLM(
  m,
  p,
  Xi,
  J,
  beta,
  link = "continuation",
  Fi.func = Fi_func_MLM,
  reltol = 1e-05,
  maxit = 500,
  w00 = NULL,
  random = TRUE,
  nram = 3
)
```

Arguments

m	The number of design points; it is usually the number of combinations of all the stratification factors
p	The number of parameters in the MLM model
Xi	Model matrix, a J by p by m 3D array of predictors for separate response category at all design points(input to determine ppo,npo,po)
J	The number of response levels
beta	A p*1 vector, parameter coefficients for MLM, the order of beta should be consistent with Xi
link	Link function of MLM, default to be "cumulative", options from "continuation", "cumulative", "adjacent", and "baseline"

<code>Fi.func</code>	A function for calculating Fisher information at a specific design point, default to be <code>Fi_func_MLM</code> function in the package
<code>reltol</code>	The relative convergence tolerance, default value 1e-5
<code>maxit</code>	The maximum number of iterations, default value 500
<code>w00</code>	Specified initial design proportion; default to be NULL, this will generate a random initial design
<code>random</code>	TRUE or FALSE, if TRUE then the function will run with additional "nram" number of random initial points, default to be TRUE
<code>nram</code>	When random == TRUE, the function will generate nram number of initial points, default is 3

Value

`w` is the approximate D-optimal design
`w0` is the initial design used to get optimal design
`Maximum` is the maximized $|F|$ value
`itmax` is the number of iterations
`convergence` is TRUE or FALSE, if TRUE means the reported design is converged

Examples

```
J = 5      # number of categories,  >= 3
p = 12     # number of parameters
m = 8      # number of design points
Xi=rep(0,J*p*m) #J*p*m=5*12*8
dim(Xi)=c(J,p,m)
#design matrix
Xi[, , 1] = rbind(c( 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 2] = rbind(c( 1, 2, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 2, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 1, 2, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 3] = rbind(c( 1, 3, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 3, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 1, 3, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 0),
                   c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[, , 4] = rbind(c( 1, 4, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 1, 4, 0, 0, 0, 0, 0, 0, 0),
                   c( 0, 0, 0, 0, 0, 0, 1, 4, 0, 0, 0, 0),
```

```

c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 0),
c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,5] = rbind(c( 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,6] = rbind(c( 1, 2, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 2, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 2, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 2, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,7] = rbind(c( 1, 3, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 3, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 3, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 3, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

Xi[,8] = rbind(c( 1, 4, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 1, 4, 1, 0, 0, 0, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 1, 4, 1, 0, 0, 0),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 4, 1),
                c( 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0))

thetavec = c(-4.047, -0.131, 4.214, -2.225, -0.376, 3.519,
             -0.302, -0.237, 2.420, 1.386, -0.120, 1.284)

liftone_MLM(m=m, p=p, Xi=Xi, J=J, beta=thetavec, link = "cumulative",
            Fi.func=Fi_func_MLM, reltol=1e-5, maxit=5000, w00=NULL, random=TRUE, nram=3)

```

print.list_output *Print Method for list_output Objects*

Description

Custom print method for objects of class ‘list_output’.

Usage

```
## S3 method for class 'list_output'
print(x, ...)
```

Arguments

- | | |
|-----|-----------------------------------|
| x | An object of class ‘list_output’. |
| ... | Additional arguments (ignored). |

Value

Invisibly returns ‘x‘ (the input object).

print.matrix_list *Print Method for matrix_list Objects*

Description

Custom print method for objects of class ‘matrix_list‘.

Usage

```
## S3 method for class 'matrix_list'  
print(x, ...)
```

Arguments

x An object of class ‘matrix_list‘.
... Additional arguments (ignored).

Value

Invisibly returns ‘x‘ (the input object).

print.matrix_output *Print Method for matrix_output Objects*

Description

Custom print method for objects of class ‘matrix_output‘.

Usage

```
## S3 method for class 'matrix_output'  
print(x, ...)
```

Arguments

x An object of class ‘matrix_output‘.
... Additional arguments (ignored).

Value

Invisibly returns ‘x‘ (the input object).

trauma_data*Trauma data with multinomial response***Description**

The data frame saves data from the trauma trial data from Chuang-Stein and Agresti (1997).

Usage

```
trauma_data
```

Format

A data frame with 802 rows and 5 variables:

Severity severity of the trauma symptoms, mild or moderate/severe

Dose dose levels applied to the patients, 4 levels, placebo, low, medium and high

Label stratification group in terms of severity and dose

Outcome treatment outcome, 5 levels, death, vegetative state, major disability, minor disability and good recovery

ID patient ID, 1-802

Source

Chuang-Stein and Agresti (1997)

Examples

```
data(trauma_data) #lazy loading
```

trial_data*Generated clinical trial data with binary response***Description**

Generated with logistic regression model:

$$\text{logit}(P(Y_{ij} = 1|gender_i, age_{i1}, age_{i2})) = 3 * gender_i + 3 * age_{i1} + 3 * age_{i2}$$

The data frame can be used to run GLM clinical trial example in Huang, Tong, Yang (2023)

Usage

```
trial_data
```

Format

A data frame with 500 rows and 6 variables:

- gender** gender of the patients
- age_1** 1 or 0, whether or not the patient belongs to 18-25 age group
- age_2** 1 or 0, whether or not the patient belongs to 26-64 age group
- label** stratification group in terms of gender and age, 1 to 6
- Y** treatment effective or not, Y=1 means treatment is effective to the patient
- ID** patient ID, 1-500

Source

Generated pseudo clinical trial data to serve as an example.

Examples

```
data(trial_data) #lazy loading
```

W_func_GLM

Calculate the diagonal elements nu of Fisher information matrix

Description

Calculate the diagonal elements nu of Fisher information matrix

Usage

```
W_func_GLM(X, beta, link = "logit")
```

Arguments

X	Model matrix
beta	Parameters of GLM model
link	GLM link function, default is "logit", options are "logit", "probit", "cloglog", "loglog", "identity", identity is the same as ordinary linear regression

Value

the diagonal element nu of GLM Fisher information matrix, can be used as w in liftone_constrained_GLM

Examples

```
beta = c(0, 3, 3, 3) #main effect model beta_0, beta_1, beta_21, beta_22
#gives the 6 categories (0,0,0), (0,1,0),(0,0,1),(1,0,0),(1,1,0),(1,0,1)
X.liftone=matrix(data=c(1,0,0,0,1,0,1,0,1,0,0,1,1,1,0,0,1,1,1,1,0,1,0,1), ncol=4, byrow=TRUE)
#calculate diagonal elements of W based on beta's under logit link
W=W_func_GLM(X=X.liftone, beta=beta, link="logit")
```

Index

- * **datasets**
 - trauma_data, [24](#)
 - trial_data, [24](#)
- approxtoexact_constrained_func, [2](#)
- approxtoexact_func, [4](#)
- bounded_uniform, [4](#)
- F_func_GLM, [9](#)
- F_func MLM, [10](#)
- Fdet_func_GLM, [5](#)
- Fdet_func MLM, [6](#)
- Fdet_func_unif, [7](#)
- Fi_func MLM, [8](#)
- iset_func_trauma, [11](#)
- iset_func_trial, [12](#)
- liftone_constrained_GLM, [13](#)
- liftone_constrained MLM, [15](#)
- liftone_GLM, [19](#)
- liftone MLM, [20](#)
- print.list_output, [22](#)
- print.matrix_list, [23](#)
- print.matrix_output, [23](#)
- trauma_data, [24](#)
- trial_data, [24](#)
- W_func_GLM, [25](#)