

Package: DEXiR (via r-universe)

November 17, 2024

Title 'DEXi' Library

Version 1.0.2

Description A software package for using 'DEXi' models. 'DEXi' models are hierarchical qualitative multi-criteria decision models developed according to the method DEX (Decision EXpert, <https://dex.ijs.si/documentation/DEX_Method/DEX_Method.html>), using the program 'DEXi' (<<https://kt.ijs.si/MarkoBohanec/dexi.html>>) or 'DEXiWin' (<<https://dex.ijs.si/dexisuite/dexiwin.html>>). A typical workflow with 'DEXiR' consists of: (1) reading a '.dxi' file, previously made using the 'DEXi' software (function `read_dexi()`), (2) making a data frame containing input values of one or more decision alternatives, (3) evaluating those alternatives (function `evaluate()`), (4) analyzing alternatives (`selective_explanation()`, `plus_minus()`, `compare_alternatives()`), (5) drawing charts. 'DEXiR' is restricted to using models produced externally by the 'DEXi' software and does not provide functionality for creating and/or editing 'DEXi' models directly in 'R'.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Suggests testthat (>= 3.0.0), grDevices, ggplot2, GGally, fmsb

Config/testthat/edition 3

Imports utils, xml2, methods, stringr, graphics

Collate 'DEXiR.R' 'DexiClasses.R' 'DexiAlternatives.R' 'DexiUtils.R'
'DexiAnalysis.R' 'DexiFunctions.R' 'DexiScales.R'
'DexiAttributes.R' 'DexiCharts.R' 'DexiData.R' 'DexiEvaluate.R'
'DexiModels.R' 'DexiValues.R'

NeedsCompilation no

Author Marko Bohanec [aut, cre]

(<<https://orcid.org/0000-0003-4317-2833>>)

Maintainer Marko Bohanec <marko.bohanec@ijs.si>

Repository CRAN

Date/Publication 2024-09-17 16:30:09 UTC

Config/pak/sysreqs libicu-dev libxml2-dev

Contents

DEXiR-package	4
alt_values	11
and_function	12
attribute_effect	12
att_names	13
bounded_scale_value	14
compare_alternatives	15
compare_two_alternatives	17
compare_values	18
compare_values_by_preference	19
compare_values_on_scale	20
convert_alternatives	21
convert_data_continuous	23
convert_data_discrete	24
default_quality	26
DexiAttribute-class	26
DexiContinuousScale-class	28
DexiDiscreteScale-class	29
DexiDiscretizeFunction-class	31
DexiFunction-class	32
DexiModel-class	33
DexiScale-class	36
DexiTabularFunction-class	37
dexi_bool	39
dexi_index	39
dexi_option_value	40
dexi_table	41
dexi_value	42
dexi_vector	43
distribution	43
distr_to_set	44
equal_scales	45
evaluate	45
evaluate_attribute	47
evaluate_attributes	48
evaluation_order	49
evaluation_parameters	50
expand_value_to_points	51
export_alternatives	52
export_dexi_value	53
flat_text	53

ggplot_parallel 54

has_bad 55

has_good 55

has_none 56

has_quality 56

is_distribution 57

is_in_range 57

lin_map 58

make_args 59

normalize_function 59

norm_max 60

norm_none 61

norm_sum 61

or_function 62

plotalt1 63

plotalt2 64

plotalt_parallel 65

plotalt_radar 67

plus_minus 70

plus_minus_setup 72

print_selective_explanation 73

read_dexi 73

reverse_value 74

rule_value 75

rule_values 75

scale_alternatives 76

scale_of 78

scale_value 78

scale_values 80

selective_explanation 81

select_quality 82

set_alternative 83

set_to_distr 84

transparent_colors 85

unique_names 86

values_to_str 86

value_qualities 87

value_text 87

value_to_set 88

write_alternatives 89

Description

DEXiR is a software package for using DEXi models in R. The main function is evaluating decision alternatives using a model previously developed by DEXi software.

DEXi Models

DEXi models are hierarchical qualitative rule-based multi-criteria decision models developed using the method DEX (Decision EXpert, https://en.wikipedia.org/wiki/Decision_EXpert), using the program DEXi (<https://kt.ijs.si/MarkoBohanec/dexi.html>) or DEXiWin (<https://dex.ijs.si/dexisuite/dexiwin.html>).

In general, a DEXi model consists of a hierarchy of qualitative (symbolic linguistic, discrete) variables, called *attributes*. Each attribute represents some observable property (such as Price or Performance) of decision alternatives under study. An attribute can take values from a set of words (such as "low; medium; high" or "unacc; acc; good; exc"), which is usually small (up to five elements) and preferentially ordered from "bad" to "good" values.

The *hierarchy* of attributes represents a decomposition of a decision problem into sub-problems, so that higher-level attributes depend on the lower-level ones. Consequently, the terminal nodes represent inputs, and non-terminal attributes represent the outputs of the model. Among these, the most important are one or more root attributes, which represent the final evaluation(s) of the alternatives.

The *evaluation* of decision alternatives (i.e., hierarchical aggregation of values from model inputs to outputs) is governed by *decision rules*, defined for each non-terminal attribute by the creator of the model (usually referred to as a "decision maker").

Terminological remarks

DEX DEX (Decision EXpert) refers to a general multi-attribute decision modeling method, characterized by using qualitative attribute hierarchies and decision tables. For further information, see (Trdin, Bohanec, 2018) and (Bohanec, 2022).

DEXi DEXi ("DEX for instruction") refers to DEXi software. DEXi implements a subset of DEX, for instance, it is restricted to set-based evaluation methods. DEXi supports the creation and editing of *DEXi models*, which are saved on `.dxi` files and subsequently read by DEXiR for processing in R. For further information on DEXi, see <https://kt.ijs.si/MarkoBohanec/dexi.html>.

DEXiWin A new backward-compatible implementation of DEXi, aimed at gradually replacing it in the future. For further information on DEXiWin and related software, see <https://dex.ijs.si/dexisuite/dexisuite.html>.

DEXiR DEXiR is this R package. It is capable of reading and processing DEXi models with some extensions towards the full DEX (for example, using value distributions).

DEXiR Functionality

Models developed using the DEXi software are stored in XML-formatted `.dxi` files. In order to use DEXi models in R, DEXiR supports the following tasks:

1. Reading DEXi models from `.dxi` files into the R environment, using `read_dexi`.
2. Making data frames containing data (both input and output) about considered decision alternatives, using `set_alternative`.
3. Evaluating decision alternatives, using `evaluate`.
4. Analyzing alternatives (`selective_explanation`, `plus_minus`, `compare_alternatives`).
5. Drawing charts.

By default, evaluation is based on sets, which is a standard evaluation procedure of DEXi. DEXiR extends this by supporting:

- evaluations using probabilistic and fuzzy value distributions (see `evaluate`);
- "pruned" evaluation, when the evaluation starts from selected non-terminal attribute(s) upwards.

Limitations

DEXiR has been designed to facilitate *using* DEXi models in R produced externally by the DEXi software. DEXiR does not provide any explicit means for creating and/or editing DEXi models in R.

A typical DEXiR workflow

This example uses a simple DEXi model for evaluating cars, which is distributed together with the DEXi software (including DEXiR) and is used throughout DEX literature to illustrate the methodological approach (https://en.wikipedia.org/wiki/Decision_EXpert).

First, this model is loaded into R and printed as follows:

```
> Car <- read_dexi("data/Car.dxi")
> Car
DEXi Model: CAR_MODEL
Description: Car demo
index id          structure          scale          funct
 [1] CAR_MODEL    CAR_MODEL
 [2] CAR           +- CAR           unacc; acc; good; exc (+) 12 3x4
 [3] PRICE         |- PRICE        high; medium; low (+)    9 3x3
 [4] BUY.PRICE     | |- BUY.PRICE  high; medium; low (+)
 [5] MAINT.PRICE   | +- MAINT.PRICE high; medium; low (+)
 [6] TECH.CHAR.    +- TECH.CHAR.   bad; acc; good; exc (+)  9 3x3
 [7] COMFORT       |- COMFORT      small; medium; high (+) 36 3x4x3
 [8] X.PERS        | |- #PERS      to_2; 3-4; more (+)
 [9] X.DOORS       | |- #DOORS     2; 3; 4; more (+)
[10] LUGGAGE       | +- LUGGAGE    small; medium; big (+)
[11] SAFETY        +- SAFETY      small; medium; high (+)
```

Rows in the table correspond to individual attributes. The columns represent the following:

`index` Indices of attributes.

`id` Unique attribute names, generated by DEXiR from original DEXi names, in order to provide syntactically correct variable names in R and allow unambiguous referencing of attributes.

`structure` The hierarchical structure of attributes, named as in the original DEXi model.

`scale` Value scales associated with each attribute. The symbol "(+)" indicates that the corresponding scale is ordered preferentially in increasing order.

`funct` Information about the size (number of rules) and dimensions of the corresponding decision tables.

Looking at the structure of attributes, please notice that the attribute at index [1] is virtual and does not actually appear in the original DEXi model. It is necessary in DEXiR to facilitate models that have multiple root attributes. The "real" root of the Car model is actually [2] CAR. It depends on two lower-level attributes, PRICE and TECH.CHAR. These are decomposed further. Overall, the model consists of

- six input (*basic*) attributes: BUY.PRICE, MAINT.PRICE, X.PERS, X.DOORS, LUGGAGE and SAFETY, and
- four output (*aggregate*) attributes: CAR, PRICE, TECH.CHAR. and COMFORT.

Among the latter, CAR is the most important and represents the overall evaluation of cars.

The next step usually consists of defining a data frame representing decision alternatives (i.e., cars in this case). The Car model already comes with a data table about two cars:

```
> Car$alternatives
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 Car1  4     3         2           3         4     3     3     3     3     3
2 Car2  3     2         2           2         3     3     3     3     3     2
```

In this data frame, attribute values are represented by ordinal numbers w.r.t. the corresponding scales. A more readable output can be made using `DexiModel$as_character`:

```
> Car$as_character(Car$alternatives)
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 Car1 exc  low  medium      low      exc  high  more    4   big  high
2 Car2 good medium medium    medium    good  high  more    4   big  medium
```

This data can be edited using common R data.frame functions. Also, DEXiR provides the method `DexiModel$alternative` for defining a single decision alternative, for example:

```
> alt <- Car$alternative("MyCar1",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS="more", X.DOORS="4",
  LUGGAGE=2, SAFETY="medium")
> alt
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 MyCar1 NA  NA         3           2         NA     NA     3     3     2     2
```

Finally, such data tables can be evaluated using `DexiModel$evaluate`:

```
> eval <- Car$evaluate(alt)
> eval
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 MyCar1 4 3 3 2 3 3 3 3 2 2
> Car$as_character(eval)
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 MyCar1 exc low low medium good high more 4 medium medium
```

Analysis of alternatives

Once defined and evaluated, alternatives can be analysed further. DEXiR provides three analysis methods:

[selective_explanation](#) Exposing particular weak and strong points of alternatives.

[plus_minus analysis](#) Exploring effects of changing individual attributes to evaluation results.

[compare_alternatives](#) Comparison of an alternative with other alternatives.

Examples:

```
> Car$selective_explanation(1)
```

Selective explanation of Car1

Weak points:

None

Strong points:

id	structure	Car1
CAR.1	+--CAR	4
PRICE	-PRICE	3
MAINT.PRICE	+--MAINT.PRICE	3
TECH.CHAR.	+--TECH.CHAR.	4
COMFORT	-COMFORT	3
X.PERS	--#PERS	3
LUGGAGE	+--LUGGAGE	3
SAFETY	+--SAFETY	3

```
> Car$plus_minus(1, as_character = TRUE)
```

id	structure	-2	-1	CAR.1=exc	1
BUY.PRICE	--BUY.PRICE	[unacc	medium	exc
MAINT.PRICE	+--MAINT.PRICE	unacc	exc	low]
X.PERS	--#PERS	unacc	exc	more]
X.DOORS	--#DOORS	unacc	exc	4	exc
LUGGAGE	+--LUGGAGE	unacc	exc	big]
SAFETY	+--SAFETY	unacc	exc	high]

```
> Car$compare_alternatives(1, as_character = TRUE)
```

id	structure	Car1	Car2
CAR	CAR	NULL	NULL
CAR.1	+--CAR	exc	> good
PRICE	-PRICE	low	> medium
BUY.PRICE	-BUY.PRICE	medium	
MAINT.PRICE	+-MAINT.PRICE	low	> medium
TECH.CHAR.	+--TECH.CHAR.	exc	> good
COMFORT	-COMFORT	high	
X.PERS	-#PERS	more	
X.DOORS	-#DOORS	4	
LUGGAGE	+-LUGGAGE	big	
SAFETY	+--SAFETY	high	> medium

Charts

Evaluation results can be drawn on charts. DEXiR provides four charts that display multiple alternatives:

`plotalt1` with respect to a single attribute, drawing a scatterplot "alternatives by attribute-values"

`plotalt2` with respect to two attributes, drawing a scatterplot "attribute1 by attribute2"

`plotalt_parallel` with respect to multiple attributes, drawing evaluation results using parallel axes

`plotalt_radar` with respect to multiple attributes, drawing evaluation results on a radar chart

The latter two plots scale evaluation results to the $[0:1]$ interval. Evaluation values represented by sets or distributions are plotted either as intervals (`aggregate = "minmax"`) or are aggregated to a single value (`aggregate = "min", "max" or "mean"`).

Examples:

```
Plot all Car alternatives with respect to Car$first() ("CAR.1")
> plotalt1(Car)
```

```
Plot evaluation results of all Car alternatives with respect to attribute "PRICE"
> plotalt1(Car, "PRICE")
```

```
Draw "TECH.CHAR." by "PRICE" scatterplot of all Car alternatives
> plotalt2(Car, "TECH.CHAR.", "PRICE")
```

```
Draw a "TECH.CHAR." by "PRICE" scatterplot of the second Car alternative
> plotalt2(Car, "TECH.CHAR.", "PRICE", 2)
```

```
Draw all Car alternatives on parallel axes
> plotalt_parallel(Car)
```

```
Draw all Car alternatives on a radar chart
> plotalt_radar(Car)
```


On the use of values in DEXi models

DEXi values are used throughout DEXi models. They provide input values and carry results of evaluations in data frames that contain data about decision alternatives. Values are also used in definitions of [DexiFunctions](#) and are returned by `DexiFunction$evaluate` when evaluating some function for a given set of arguments.

In DEXi, values are always bound to the context provided by a [DexiScale](#). Since each fully defined [DexiAttribute](#) is associated with some scale, we can generalize the scale context to attributes and speak about "assigning some value to an attribute".

The scale type determines the type and possible range of values that can be assigned to an attribute. DEXiR implements two scale types: [DexiContinuousScale](#) and [DexiDiscreteScale](#). Regarding the values, the former is really simple: it allows assigning any single real number to the corresponding attribute. In other words, continuous DEXi values are of type `numeric(1)`.

[DexiDiscreteScale](#) is the main scale type used throughout DEXi models and supports a wider range of value types.

The "normal" and most common discrete value is a "single qualitative value". For illustration, let us use the scale composed of four qualitative values: "unacc", "acc", "good", "exc". Then, "a single qualitative value" denotes one of these words. Internally in DEXiR, such values are not represented by character strings, but rather by ordinal numbers, so that `ord("unacc") = 1`, `ord("acc") = 2`, etc. Some DEXiR functions can convert between the two representations, see `DexiModel$as_character` and `set_alternative()`.

In order to cope with missing, incomplete or uncertain data, DEX extends the concept of single values to value *sets* and *distributions*. In DEXiR, wherever it is possible to use a single qualitative value, it is also possible to use a value set or distribution. This is the main reason that all DEXiR data structures related to DEXi values are represented by lists rather than plain vectors. This includes all data frames that represent decision alternatives and all functions that return qualitative values. Also note that while sets are fully implemented in the current DEXi software, distributions are not and are thus considered extensions towards the full DEX method.

A *DEXi value set* is a subset of the full range of a [DexiDiscreteScale](#) values. For the above example, the full range of ordinal values is 1:4, and some possible subsets are `c(2)`, `c(2, 4)`, `c(1, 2, 3)` and 1:4. Internally, sets are represented by plain integer vectors or plain numeric vectors containing integer numbers.

A *DEXi value distribution* associates each [DexiDiscreteScale](#) value with some number, generally denoted p and normally expected to be in the $[0,1]$ interval. Depending on the context and used evaluation method (see `evaluate()`), p can be interpreted as *probability* or *fuzzy set membership*. In DEXiR, value distributions are represented using the S3 class "distribution" (see [distribution](#)). For example, `distribution(0.5, 0, 0.2, 0.3)` represents a value distribution over the above scale example, assigning $p = 0.5$ to "unacc", $p = 0.0$ to "acc", $p = 0.2$ to "good" and $p = 0.3$ to "exc".

Remarks:

- The value `distribution(0.5, 0, 0.2, 0.3)` is internally represented as `c(0.5, 0, 0.2, 0.3)`, whose `class()` is "distribution".
- Using a special class for distributions is necessary to distinguish them from sets. For instance, the notation `c(1, 1)` is ambiguous and would be interpreted differently as a set or distribution.

- Some DEXiR functions (see `DexiModel$as_character` and `set_alternative()`) support the formulation of distributions in the form of named vectors or lists, for instance `list(unacc=0.5, good=0.2, exc=0.3)`.
- In data frames that contain data about decision alternatives, numeric vectors that contain non-integer values are implicitly interpreted as distributions rather than sets.

Examples of using value sets and distributions

First, let us consider a car for which we have no evidence about its possible maintenance costs. For the value of `MAINT.PRICE`, we may use `"*"`, which denotes the full range of the corresponding attribute values (equivalent to `1:3` or `c(1, 2, 3)` in this case). Notice how the evaluation method considers all the possible values of `MAINT.PRICE` and propagates them upwards.

```
alt <- Car$alternative("MyCar1a",
  BUY.PRICE="low", MAINT.PRICE="*", X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=2)
Car$evaluate(alt)
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 MyCar1a 1, 4 1, 3      3      1, 2, 3      3      3      3      3      2      2
```

The above evaluation result is not really useful, as the car turns out to be `c(1, 4)`, that is, either `"unacc"` or `"exc"`, depending on maintenance costs. Thus, let us try using value distribution for `MAINT.PRICE`, telling DEXiR that low maintenance costs are somewhat unexpected ($p = 0.1$) and that medium costs ($p = 0.6$) are more likely than high ($p = 0.3$). Using the evaluation method `"prob"` (where p 's are interpreted as probabilities) gives the following results:

```
alt <- Car$alternative("MyCar1b",
  BUY.PRICE="low", MAINT.PRICE=distribution(0.1, 0.6, 0.3),
  X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=2)
Car$evaluate(alt, method = "prob")
  name CAR PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS X.DOORS LUGGAGE SAFETY
1 MyCar1b 0.1, 0.0, 0.0, 0.9 0.1, 0.0, 0.9      3 0.1, 0.6, 0.3 0, 0, 1, 0, 0, 0, 1      3      3      2      2
```

In this case, the final evaluation of `CAR` is `distribution(0.1, 0.0, 0.0, 0.9)`, that is, `list(unacc=0.1, exc=0.9)`. It is much more likely that `MyCar1b` is `"exc"` than `"unacc"`.

References

- *Decision Expert*. Wikipedia, https://en.wikipedia.org/wiki/Decision_Expert.
- Trdin, N., Bohanec, M.: Extending the multi-criteria decision making method DEX with numeric attributes, value distributions and relational models. *Central European Journal of Operations Research*, 1-24, 2018 doi:10.1007/s1010001704689.
- Bohanec, M.: DEX (Decision Expert): A Qualitative Hierarchical Multi-criteria Method. In: Kulkarni, A.J. (ed.): *Multiple Criteria Decision Making: Techniques, Analysis and Applications*. Singapore: Springer, 39-78, 2022 doi:10.1007/9789811674143_3.
- *DEXi: A Program for Multi-Attribute Decision Making*. <https://kt.ijs.si/MarkoBohanec/dexi.html>.

- Bohanec, M.: *DEXi: Program for Multi-Attribute Decision Making, User's Manual, Version 5.04*. IJS Report DP-13100, Jožef Stefan Institute, Ljubljana, 2020. <https://kt.ijs.si/MarkoBohanec/pub/DEXiManual504.pdf>.
- Bohanec, M.: *DEXiWin: DEX Decision Modeling Software, User's Manual, Version 1.2*. IJS Report DP-14741, Jožef Stefan Institute, Ljubljana, 2024. https://kt.ijs.si/MarkoBohanec/pub/2024_DP14741_DEXiWin.pdf.
- *DEX Software*. <https://dex.ijs.si>.

Author(s)

Maintainer: Marko Bohanec <marko.bohanec@ijs.si> ([ORCID](#))

alt_values

alt_values

Description

Make a list of alternative's values corresponding to attributes.

Usage

```
alt_values(alt, attributes, as_character = TRUE, round = NULL)
```

Arguments

alt	data.frame representing a single alternative.
attributes	A vector of DexiAttribute objects.
as_character	logical(1).. Determines whether to represent alternative values numerically ("internal representation") (FALSE) or as character strings (using value_text()) (TRUE).
round	A single integer. An optional argument to value_text() .

Value

character(length(attributes)). String representation of alt's values.

See Also

[value_text\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

unlist(alt_values(Car$alternatives[1,], Car$attributes, as_character = TRUE))
# c("NULL", "exc", "low", "medium", "low", "exc", "high", "more", "4", "big", "high")
```

and_function	<i>and_function</i>
--------------	---------------------

Description

Determine the function to be used in the conjunctive aggregation step of [evaluate\(\)](#).

Usage

```
and_function(method = EnumEvalMethod, and = NULL)
```

Arguments

method	One of: "set" (default), "prob", "fuzzy" or "fuzzynorm".
and	Some conjunctive aggregation function of the form <code>function(num_vector)</code> , or NULL.

Value

Returns the function and if not NULL. Otherwise, it determines the result depending on method:

"set": `function(x) 0`

"prob": `prod`

"fuzzy": `min`

"fuzzynorm": `min`

Fails with an error if the result is not an R function.

See Also

[evaluate](#), [or_function\(\)](#).

attribute_effect	<i>attribute_effect</i>
------------------	-------------------------

Description

Given a single alternative, determine the effects of varying attribute on target attribute.

Usage

```
attribute_effect(model, attribute, alternative, target = NULL, seq = NULL, ...)
```

Arguments

model	A DexiModel object. Required.
attribute	A DexiAttribute with assigned discrete or continuous scale.
alternative	A data.frame containing a single alternative.
target	Target DexiAttribute . Defaults to model\$first().
seq	A sequence of attribute's numeric values for which to evaluate alternative. For discrete scales: Must be a sequence of integers. Defaults to attribute\$scale\$full_range(). For continuous scales: seq is required.
...	Optional parameters passed to evaluate_attribute() .

Value

A list of target evaluation results, indexed by the values of seq.

See Also

[evaluate_attribute\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY="medium")
# Determine the effect of changing "SAFETY" values on "CAR.1"
attribute_effect(Car, "SAFETY", alt)
# Returns a list of "CAR.1" values corresponding to consecutive values of "SAFETY"
attribute_effect(Car, "LUGGAGE", alt, "TECH.CHAR.")
# Returns a list of "TECH.CHAR." values corresponding to consecutive values of "LUGGAGE"
```

att_names

att_names

Description

Return names or IDs of [DexiAttribute](#) objects.

Usage

```
att_names(atts, use_id = TRUE)
```

Arguments

atts	A vector of DexiAttributes .
use_id	Determines whether to return attribute IDs or original DEXi names.

Value

A character vector of attribute IDs or names.

bounded_scale_value *bounded_scale_value*

Description

bounded_scale_value is a wrapper around [scale_value\(\)](#) that makes sure that the resulting values lie within the bounds set up by the scale.

Usage

```
bounded_scale_value(value, scale)
```

Arguments

value	Any DEXi value, including value sets and distributions.
scale	A DexiScale or derived object.

Value

For continuous scales, value is returned "as is". For discrete scales, all elements of value that lie outside of `scale$full_range()` are removed. If this results in an empty value set or distribution, NULL is returned.

See Also

[scale_value\(\)](#)

Examples

```
scl <- DexiDiscreteScale(values = c("low", "med", "high"))
bounded_scale_value(NA, scl) # NA
bounded_scale_value(1, scl) # 1
bounded_scale_value(4, scl) # NULL
bounded_scale_value(c(0, 1, 3, 4, 5), scl) # c(1, 3)
bounded_scale_value(distribution(0.1, 0.2, 0.3, 0.4), scl) # distribution(0.1, 0.2, 0.3)
```

compare_alternatives *compare_alternatives*

Description

Compare Alternatives Analysis: Compare alternative with each of alternatives. Display only values that differ and, optionally when compare = TRUE, include preference-relational operators.

Usage

```
compare_alternatives(
  model,
  alternative,
  alternatives = NULL,
  root = NULL,
  compare = TRUE,
  deep = TRUE,
  print = TRUE,
  as_character = FALSE,
  round = NULL,
  id = NULL,
  evaluate = FALSE,
  ...
)
```

Arguments

model	A DexiModel object. Required.
alternative	Either a data.frame representing a single alternative or an integer index to model\$alternatives.
alternatives	Either a data.frame representing one or more alternatives, or an integer numeric vector representing indices to model\$alternatives. By default, alternatives are set to model\$alternatives, possibly excluding alternative when indexed.
root	Optional DexiAttribute object. When specified, only attributes that affect root are included in the analysis. Otherwise, all model\$attributes are included.
compare	logical(1). Whether or not preference relations "<", ">", "<=", ">=" are included in results.
deep	logical(1). Whether of not "deep" comparison (see compare_two_alternatives()) is carried out.
print	logical(1). When TRUE, pretty print (left justify) the results.
as_character	logical(1). Whether to represent alternative values numerically (FALSE) or using text (TRUE).
round	An integer number, argument to value_text() .

id	character(1). Determines the contents of the first or first two columns of the resulting data.frame: "id" Attribute ID. "structure" Attribute \$structure() + \$name. anything else Equivalent to both "id" and "structure".
evaluate	logical(1). Whether or not to evaluate alternative and alternatives beforehand.
...	Optional parameters for <code>evaluate()</code> .

Value

Returns or prints a data.frame consisting of columns: id (if requested), structure (if requested), values of alternative and comparison results for each alternative from alternatives.

See Also

[compare_two_alternatives\(\)](#), [evaluate\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Extend Car$alternatives
car3 <- set_alternative(Car, Car$alternatives[2,], name = "Car3", LUGGAGE = 2)
Car$alternatives[3,] <- car3
car4 <- set_alternative(Car, Car$alternatives[2,], name = "Car4", LUGGAGE = 1)

# Compare Car1 with the other two, varying some arguments
compare_alternatives(Car, 1, evaluate=TRUE, compare=FALSE)
compare_alternatives(Car, 1, evaluate=TRUE, compare=TRUE)
compare_alternatives(Car, 1, evaluate=TRUE, compare=TRUE, deep=FALSE)

# Compare Car2 with Car1
compare_alternatives(Car, 2, 1)

# Compare car3 with Car1 and Car2
compare_alternatives(Car, car3, 1:2)

# Compare car4 with Car$alternatives
compare_alternatives(Car, car4)

# Compare Car$alternatives[1,] with car3
compare_alternatives(Car, 1, car3)
compare_alternatives(Car, Car$alternatives[1,], car3)
```

compare_two_alternatives
compare_two_alternatives

Description

Compare alternatives alt1 and alt2 with respect to attributes.

Usage

```
compare_two_alternatives(alt1, alt2, attributes, deep = TRUE)
```

Arguments

alt1	data.frame. First alternative.
alt2	data.frame. Second alternative.
attributes	Vector of DexiAttribute objects.
deep	logical(1). When TRUE and compared values are equal, input attributes are additionally investigated for possible preferential differences.

Value

numeric(length(attributes)). Each element represents the outcome of comparison w.r.t. the corresponding attribute. Possible outcomes:

0 Values are equal.

-1 alt1's value is worse than alt2's.

+1 alt1's value is better than alt2's.

NA Values are incomparable.

When deep = TRUE, the so-called deep comparison is performed: when the compared attribute's values are equal, subordinate attributes are checked for differences, possibly returning -0.5 (indicating the weak preference relation "<=") or +0.5 (indicating the weak preference relation ">=").

See Also

[compare_values_on_scale\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

compare_two_alternatives(Car$alternatives[1,], Car$alternatives[2,], Car$attributes)
# c(NA, 1, 1, 0, 1, 1, 0, 0, 0, 1)
```

compare_values	<i>compare_values</i>
----------------	-----------------------

Description

Compare two DEXi values. Internal representation is assumed for value1 and value2, i.e., a single number, an integer vector representing a set or `distribution()`. Distributions are compared as sets.

Usage

```
compare_values(value1, value2)
```

Arguments

value1	First value.
value2	Second value.

Value

0 if values are equal, -1 if value1 < value2, +1 if value1 > value2 and NA if values are incomparable. Values are incomparable if they are of a non-DEXiValue type or if they represent two overlapping sets.

Examples

```
compare_values(c(1,2), c(1,2))      # 0
compare_values(c(1,2), c(1,3))      # NA
compare_values(c(1,2), c(3,4))      # -1
compare_values(c(1,2), c(2,4))      # NA
compare_values(c(1,2), c(2.1,4))    # -1
compare_values(c(1,2.05), c(2.1,4)) # -1
compare_values(c(3,4), c(3,4))      # 0
compare_values(c(5,5), c(3,4))      # +1
compare_values(c(5,5), 2)           # +1
compare_values(c(5,2), 2)           # NA
compare_values(c(5,3), 2)           # +1
compare_values(distribution(5,3), 2) # NA
compare_values(distribution(5,3), 5) # -1
```

compare_values_by_preference
compare_values_by_preference

Description

Compare values, considering preference order. For value arguments, see [compare_values\(\)](#).

Usage

```
compare_values_by_preference(value1, value2, order = EnumOrder)
```

Arguments

value1	First value.
value2	Second value.
order	EnumOrder, i.e., one of the strings "ascending", "descending", "none".

Value

[compare_values\(\)](#) result, modified according to order. Results 0 (equal values) and NA (incomparable values) are always retained. Results -1 and +1 are retained when order="ascending" and reversed when order="descending". When order="none", non-equal values return NA.

See Also

[compare_values\(\)](#)

Examples

```
compare_values_by_preference(1, 1, "none")      # 0
compare_values_by_preference(1, 2, "none")      # NA
compare_values_by_preference(3, 2, "none")      # NA
compare_values_by_preference(1, 1, "ascending") # 0
compare_values_by_preference(1, 2, "ascending") # -1
compare_values_by_preference(3, 2, "ascending") # +1
compare_values_by_preference(1, 1, "descending") # 0
compare_values_by_preference(1, 2, "descending") # +1
compare_values_by_preference(3, 2, "descending") # -1
```

```
compare_values_on_scale
      compare_values_on_scale
```

Description

Compare values `value1` and `value2` considering `scale$order`. Internal DEXi representation is assumed for values, i.e., a single number, an integer vector representing a set or `distribution()`. Distributions are compared as sets.

Usage

```
compare_values_on_scale(value1, value2, scale, force_compare = FALSE)
```

Arguments

<code>value1</code>	First value.
<code>value2</code>	Second value.
<code>scale</code>	Normally a DEXiScale object or a DexiAttribute object with defined <code>\$scale</code> .
<code>force_compare</code>	logical(1). Applies when <code>scale</code> is NULL or anything other than expected. When <code>force_compare = TRUE</code> , comparison is enforced, assuming "ascending" scale order. When <code>force_compare = FALSE</code> , NA is returned.

Value

`compare_values()` result, modified according to `scale$order`.

See Also

`compare_values()`, `compare_values_by_preference()`

Examples

```
compare_values_on_scale(1, 2, NULL) # NA
compare_values_on_scale(2, 1, "") # NA
compare_values_on_scale(1, 2, NULL, force_compare = TRUE) # -1
compare_values_on_scale(2, 1, "", force_compare = TRUE) # +1

scl <- DexiDiscreteScale(values = c("a", "b", "c"))
compare_values_on_scale(1, 1, scl) # 0
compare_values_on_scale(1, 2, scl) # -1
compare_values_on_scale(3, 2, scl) # +1
compare_values_on_scale(c(1, 2), c(1, 2), scl) # 0
compare_values_on_scale(c(1, 2), c(2, 3), scl) # NA

scl <- DexiDiscreteScale(order = "descending", values = c("a", "b", "c"))
compare_values_on_scale(1, 1, scl) # 0
compare_values_on_scale(1, 2, scl) # +1
```

```

compare_values_on_scale(3, 2, scl)          # -1
compare_values_on_scale(c(1, 2), c(1, 2), scl) # 0
compare_values_on_scale(c(1, 2), c(2, 3), scl) # NA

scl <- DexiDiscreteScale(order = "none", values = c("a", "b", "c"))
compare_values_on_scale(1, 1, scl)          # 0
compare_values_on_scale(1, 2, scl)          # NA
compare_values_on_scale(3, 2, scl)          # NA
compare_values_on_scale(c(1, 2), c(1, 2), scl) # 0
compare_values_on_scale(c(1, 2), c(2, 3), scl) # NA

```

```
convert_alternatives  convert_alternatives
```

Description

Converts a data.frame of alternatives' data to another data.frame. The conversion generally involves: aggregating DEXi values originally represented by sets or distributions, scaling aggregated values to a given interval and/or reversing values assigned to "descending" [DexiScales](#).

Usage

```

convert_alternatives(
  model,
  alternatives = NULL,
  interpret = c("set", "distribution", "none"),
  aggregate = min,
  omin = 0,
  omax = 1,
  map_values = TRUE,
  reverse_descending = TRUE,
  verbatim = "name",
  skip = NULL,
  continuous = convert_data_continuous,
  discrete = convert_data_discrete
)

```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to model\$alternatives. The default value NULL selects model\$alternatives.
interpret	character(1). Determines how the original values in alternatives are interpreted, i.e., converted prior to submitting them to aggregate() : "set" As a set of values. Any distribution -type value is converted to a set, thus discarding the numeric membership information.

	"distribution" As a value distribution, i.e., a numeric vector of membership values.
	"none" No conversion.
	Values corresponding to continuous attributes are not converted nor affected by these settings.
aggregate	A function accepting the interpreted DEXi value (see <code>interpret</code>) and converting it to become part of the output data frame. Normally, this function is assumed to accept a numeric vector argument and aggregate it in a single numeric value. The default aggregation function is <code>min()</code> . Typical alternatives include <code>max()</code> and <code>mean()</code> .
omin	numeric(1). Lower bound of the output value interval (see <code>map_values</code>). Default: 0.
omax	numeric(1). Upper bound of the output value interval (see <code>map_values</code>). Default: 1.
map_values	logical(1). When TRUE, values produced by <code>aggregate()</code> are further scaled to the interval <code>[omin:omax]</code> . Input bounds are determined from the corresponding attribute scales (for discrete attributes) or as minimum/maximum values from <code>alternatives</code> (for continuous attributes).
reverse_descending	logical(1). Whether or not to reverse the values of attributes whose scales are of a "descending" preference order.
verbatim	character(). Names of alternatives' data columns that are included in the output without conversion. Default: "name".
skip	character(). Names of alternatives' data columns that are ignored in the process. Default: NULL.
continuous	A function converting a data column that corresponds to a continuous attribute. Default: <code>convert_data_continuous()</code> . Setting <code>continuous</code> to NULL excludes all continuous attributes from conversion.
discrete	A function converting a data column that corresponds to a discrete attribute. Default: <code>convert_data_discrete()</code> . Setting <code>discrete</code> to NULL excludes all discrete attributes from conversion.

Details

The rationale for `convert_alternatives()` is that data frames representing alternatives, particularly those produced by `evaluate()`, generally contain DEXi values of various and mixed data types, such as numbers and numeric vectors (sets and distributions). As such, this data is difficult to work with in R, as most R functions expect simpler and more uniform data structures. `convert_alternatives()` produces data frames that are more suitable for standard R data analysis and graph drawing. However, as the conversion generally involves aggregation and mapping of DEXi values, it may distort or lose information along the way.

Value

A converted `data.frame`.

See Also

[convert_data_continuous\(\)](#), [convert_data_discrete\(\)](#), [scale_alternatives\(\)](#), [DEXiR-package](#) notes on values in DEXi models.

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Map Car$alternatives' values to the [0, 1] interval.
convert_alternatives(Car)

# name   CAR.1 PRICE BUY.PRICE MAINT.PRICE TECH.CHAR. COMFORT X.PERS  X.DOORS LUGGAGE SAFETY
# 1 Car1 1.0000000  1.0    0.5      1.0 1.0000000    1    1 0.6666667    1  1.0
# 2 Car2 0.6666667  0.5    0.5      0.5 0.6666667    1    1 0.6666667    1  0.5
```

```
convert_data_continuous
      convert_data_continuous
```

Description

A helper function for converting individual columns of alternatives' data. It is assumed that data contains numeric data corresponding to a continuous [DexiAttribute](#). During conversion, values are optionally converted from some interval to another, using [lin_map\(\)](#), and/or reversed using [reverse_value\(\)](#) for scales whose `$order = "descending"`.

Usage

```
convert_data_continuous(
  data,
  scale,
  imin = NULL,
  imax = NULL,
  omin = 0,
  omax = 1,
  map_values = TRUE,
  reverse_descending = TRUE
)
```

Arguments

`data` A vector containing floating point numbers. Typically a `data.frame` column of DEXi alternatives' data.

`scale` A [DexiContinuousScale](#) object or a continuous [DexiAttribute](#) object.

imin	Lower input bound. Default: determined as <code>min(data)</code> .
imax	Upper input bound. Default: determined as <code>max(data)</code> .
omin	Lower output bound for <code>lin_map()</code> value scaling.
omax	Upper output bound for <code>lin_map()</code> value scaling.
map_values	logical(1). Whether or not to perform value scaling using <code>lin_map()</code> .
reverse_descending	logical(1). Whether or not to reverse values of a "descending" scale.

Value

`numeric()`. Vector of converted values.

See Also

[lin_map\(\)](#), [reverse_value\(\)](#)

Examples

```
scl <- DexiContinuousScale()
convert_data_continuous(c(1, 2, 5), scl) # c(0.0, 0.25, 1.00)
convert_data_continuous(c(1, 2, 5), scl, imin = 0, imax = 10, omin = 0, omax = 100)
# c(10, 20, 50)
```

convert_data_discrete *convert_data_discrete*

Description

#' A helper function for converting individual columns of alternatives' data. It is assumed that data contains data corresponding to a discrete [DexiAttribute](#). During conversion, data elements are converted either to sets or distributions, and function aggregate if applied on them. When `interpret = "set"`, values are also optionally converted to the interval `[omin:omax]`, and reversed using [reverse_value\(\)](#) for scales whose `$order = "descending"`.

Usage

```
convert_data_discrete(
  data,
  scale,
  interpret = c("set", "distribution", "none"),
  aggregate = min,
  omin = 0,
  omax = 1,
  map_values = TRUE,
  reverse_descending = TRUE
)
```


Arguments

data	A vector containing DEXi values: single numbers, integer vectors or distributions. Typically a data.frame column of DEXi alternatives' data.
scale	A DexiDiscreteScale object or a discrete DexiAttribute object.
interpret	Either "set" (default), "distribution" or "none". Determines how are individual data elements interpreted: as sets or distributions. Actually, each element is converted either to a set or distribution prior do applying <code>aggregate()</code> . When <code>interpret = "none"</code> , just <code>aggregate()</code> is applied on the original value from data, without any value scaling or reversal.
aggregate	A function applied on each interpreted data element. Normally a function that maps a numeric vector (set or distribution) to a single number. Default: <code>min()</code> .
omin	Lower output bound for <code>lin_map()</code> value scaling. Applies only when <code>interpret = "set"</code> .
omax	Upper output bound for <code>lin_map()</code> value scaling Applies only when <code>interpret = "set"</code> .
map_values	<code>logical(1)</code> . Whether or not to perform value scaling using <code>lin_map()</code> . Applies only when <code>interpret = "set"</code> .
reverse_descending	<code>logical(1)</code> . Whether or not to reverse values of a "descending" scale.

Value

Vector of converted values.

See Also

[lin_map\(\)](#), [reverse_value\(\)](#)

Examples

```
scla <- DexiDiscreteScale(values = c("L", "M", "H"))
sclD <- DexiDiscreteScale(values = c("L", "M", "H"), order = "descending")
convert_data_discrete(c(1, 2, 3), scla) # 0.0 0.5 1.0
convert_data_discrete(c(1, 2, 3), sclD) # 1.0 0.5 0.0
convert_data_discrete(list(1, 2, 3), scla) # 0.0 0.5 1.0
convert_data_discrete(list(1, 2, 3), sclD) # 1.0 0.5 0.0
convert_data_discrete(list(1, 2, 3), sclD, omax=10) # 10 5 0
data <- list(1, c(1,2), distribution(0.2, 0, 0.8), NA)
convert_data_discrete(data, scla, omax=10) # 0 0 0 NA
convert_data_discrete(data, sclD, omax=10) # 10 10 10 NA
convert_data_discrete(data, scla, aggregate=max, omax=10) # 0 5 10 NA
convert_data_discrete(data, scla, aggregate=mean, omax=10) # 0.0 2.5 5.0 NA
```

default_quality	<i>default_quality</i>
-----------------	------------------------

Description

Make a default discrete scale quality vector depending on the scale's order and nvals.

Usage

```
default_quality(order = EnumOrder, nvals)
```

Arguments

order	'character(1)1, one of "ascending", "descending" or "none".
nvals	integer(1). The number of qualitative values of considered DexiDiscreteScale .

Value

character vector of length nvals, containing "bad", "none" or "good".

Examples

```
default_quality("ascending", 5)
default_quality("descending", 5)
default_quality("none", 5)
default_quality("ascending", 2)
default_quality("ascending", 1)
```

DexiAttribute-class	<i>DexiAttribute</i>
---------------------	----------------------

Description

DexiAttribute is a RC class representing a DEXi attribute in R.

Details

In a DEXi model, attributes are variables that represent observed properties of decision alternatives. Attributes are structured in a tree, so each attribute may, but need not, have one or more direct descendants (lower-level attributes) in the tree. Attributes without descendants are called *basic* and serve as model inputs. Attributes with one or more descendants are called *aggregate* and represent model outputs. In order to represent attribute hierarchies rather than plain trees, some attributes may be *linked*: two attributes of which one links to another one collectively represent, in a conceptual sense, a single attribute in the hierarchy.

When completely defined, each attribute is associated with a value scale represented by a [DexiScale](#) object. An object [DexiFunction](#) is also defined for each aggregate attribute, aimed at defining the aggregation of the attribute's inputs to values of that attribute.

Fields

- `name` character. Name of the attribute as defined in the original DEXi model. Notice that such names may not be unique and may contain characters that cannot be used for variable names in R.
- `id` character. A unique identification of the attribute in the model. Derived from `name` so that it can be used as a variable name in R.
- `description` character. An optional textual description of the attribute.
- `inputs` list of [DexiAttributes](#). A list of immediate descendants of this attribute in the tree/hierarchy. NULL for basic attributes.
- `link` [DexiAttribute](#). NULL or a link to another [DexiAttribute](#)
- `scale` [DexiScale](#). Value scale associated with this attribute, or NULL.
- `funct` [DexiFunction](#). Aggregation function associated with this attribute, or NULL.
- `parent` [DexiAttribute](#) or [DexiModel](#) (only for `DexiModel$root`). Parent attribute of this attribute in the tree/hierarchy. The `DexiModel$root`'s parent is the [DexiModel](#), which contains all those attributes.
- `.alternatives` list. An internal field providing temporary storage for names or values of alternatives while reading them from a `.dxi` file.

Methods

- `affects(ant)` `ant` (as "antecedent") is some [DexiAttribute](#). The function returns TRUE if `ant` lies on the path leading from this attribute towards the root, and is therefore affected by this attribute.
- `count()` Return the number of inputs of this attribute.
- `dim()` Dimensions of the value space determined by this attribute's inputs. Result: a numeric vector of length equal to `ninp()`, containing `DexiScale$count()` of all descendant attributes, or NA for attributes without associated scales. For basic attributes, `dim()` returns NULL.
- `initialize(name = "", description = "", inputs = list(), id = "", link = NULL, scale = NULL, funct = NULL, pa`
Initialize a [DexiAttribute](#) object.
- `inp_index(inp)` Return the index of attribute `inp` in `inputs` of this attribute.
- `is_aggregate()` Logical: TRUE for aggregate attributes (attributes whose `ninp() > 0`).
- `is_basic(include_linked = TRUE)` Logical: TRUE for basic attributes (attributes whose `ninp() == 0`. `include_linked` determines whether linked attributes are counted as basic (TRUE) or not (FALSE).
- `is_continuous()` Logical: Indicates whether or not this is a continuous attribute.
- `is_discrete()` Logical: Indicates whether or not this is a discrete attribute.
- `is_link()` Logical: Indicates whether or not this is a linked attribute.
- `level()` Return the level of this attribute in the hierarchy. The level of `DexiModel$root` is 0.
- `model()` Return the [DexiModel](#) that contains this attribute.
- `ninp()` Return the number of inputs of this attribute.
- `structure()` Make an indentation string for this attribute, used for printing it in `show()`.

`tree_indent(none = " ", thru = "|", link = "* ", last = "+", line = "-")` Construct a string for representing the indentation of this attribute in the model structure. The arguments `none`, `thru`, `link`, `last` and `line` are character strings to be used in the construction.

`verify()` Check the correctness of a `DexiAttribute` object and its fields. Result: `error()` or `TRUE`.

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# For example, consider attribute PRICE
att <- Car$attrib("PRICE")

# Print fields and basic properties of att
att$verify()
att$name
att$id
att$description
att_names(att$inputs)
att$link
att$scale
att$funct
att_names(att$parent)
att$is_aggregate()
att$is_basic()
att$is_link()
att$level()
att$count()
att$ninp()
att$dim()
att$model()
att$structure()

# Check if att affects attribute CAR
att$affects(Car$attrib("CAR"))

# Find the index of other attributes in att's inputs
att$inp_index(Car$attrib("MAINT.PRICE"))
att$inp_index(Car$attrib("CAR"))
```

DexiContinuousScale-class

DexiContinuousScale

Description

`DexiContinuousScale` is a `RC` class, derived from `DexiScale`, representing continuous value scales in R.

Details

An attribute associated with a continuous scale can take any single numeric value from $[-\text{Inf}, +\text{Inf}]$.

DexiContinuousScale defines two numeric bounds, called `low_point` and `high_point`, such that `low_point <= high_point`. These values partition preferentially ordered scales in three preferential classes ("qualities"): "bad", "none" (in the sense of "neutral"), and "good". For a scale with `order = "ascending"`, the three corresponding intervals are $[-\text{Inf}, \text{low_point}]$, $(\text{low_point}, \text{high_point})$ and $[\text{high_point}, +\text{Inf}]$. For `order = "descending"`, the order of qualities is reversed. Scales with `order = "none"` have only one associated quality, "none", for the whole range of values.

Continuous scales are supported in DEXi Suite software (DEXiWin), but not in older DEXi Classic software (DEXi).

Fields

`low_point` numeric. A bound for the quality interval $[-\text{Inf}, \text{low_point}]$.

`high_point` numeric. A bound for the quality interval $[\text{high_point}, +\text{Inf}]$.

Methods

`count()` Return the number of scale elements. Equal to NA for DexiScale, 0 for DexiContinuousScale, and equal to `nvals >= 0` for DexiDiscreteScale.

`equal(scl)` Check if this scale is equal to scale `scl`. Needed for attribute linking.

`initialize(order = EnumOrder, ...)` Initialize a DexiScale object.

`to_string()` Return a string representation of this scale for printing.

`value_quality(value)` Return the quality (preferential class) of value on this scale: one of the strings "bad", "none" or "good". Always "none" for DexiScale and scales with `order = "none"`.

`verify()` Check the correctness of this scale object and its fields. Result: `error()` or TRUE.

DexiDiscreteScale-class

DexiDiscreteScale

Description

DexiDiscreteScale is a RC class, derived from [DexiScale](#), representing qualitative (symbolic, discrete, verbal) value scales in R. Such scales are typical for DEXi models and are the only scale type supported by the DEXi software. DEXiWin software supports both continuous and discrete scales.

Details

An attribute associated with a discrete scale can take values from a finite (and usually small) set of string values contained in the character vector `values`. Additionally, each of these values is associated with one of the qualities "bad", "none" or "good". The latter are contained in the character vector `quality`, which is of the same length as `values`.

Fields

- `values` character. Vector of qualitative scale values. Example: `scale$values <- c("low", "medium", "high")`.
- `nvals` integer. Equal to `length(values)`.
- `quality` character. Vector of qualities, corresponding to values. Should be the of the same length as values. Example: `scale$quality <- c("bad", "none", "good")`.
- `descriptions` character. A vector of textual descriptions of the corresponding values. Should be of the same length as values.

Methods

- `count()` Return the number of scale elements. Equal to NA for `DexiScale`, 0 for `DexiContinuousScale`, and equal to `nvals >= 0` for `DexiDiscreteScale`.
- `equal(scl)` Check if this scale is equal to scale `scl`. Needed for attribute linking.
- `full_range()` Return the vector that represents the full range of values on this scale. Equal to NA for `DexiScale` and `DexiContinuousScale`, and `1 : scale$nvals` for `DexiDiscreteScale`.
- `initialize(order = EnumOrder, ...)` Initialize a `DexiScale` object.
- `is_discrete()` Logical: Is this scale discrete?
- `to_string()` Return a string representation of this scale for printing.
- `value_index(value)` Find the index of value (character(1)) on this scale. Equal to NA for `DexiScale` and `DexiContinuousScale`. With `DexiDiscreteScale` objects, it returns a numeric index or NA of value in `scale$values`.
- `value_quality(value)` Return the quality (preferential class) of value on this scale: one of the strings "bad", "none" or "good". Always "none" for `DexiScale` and scales with `order = "none"`.
- `verify()` Check the correctness of this scale object and its fields. Result: `error()` or TRUE.

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# For example, consider the scale of attribute PRICE
scl <- Car$attrib("PRICE")$scale

# Print fields and basic properties of scl
scl$verify()
scl$values
scl$quality
scl$descriptions
scl$nvals
scl$count()
scl$is_discrete()
scl$is_continuous()
scl$to_string()
```

```

scl$full_range()

# Find value indices
scl$value_index("medium")
scl$value_index("med")

# Is scl equal to the scale of BUY.PRICE?
scl$equal(Car$attrib("PRICE")$scale)

```

```

DexiDiscretizeFunction-class
      DexiDiscretizeFunction

```

Description

DexiDiscretizeFunction is a RC class, derived from [DexiFunction](#). Functions of this type discretize numerical values of continuous attributes to qualitative values of discrete attributes. More precisely, a DexiDiscretizeFunction can be defined only for a discrete attribute that has exactly one continuous input. Then, the function discretizes numeric values of the input attribute and maps them to discrete values of the parent attribute.

Details

Objects of class DexiDiscretizeFunction define discretization rules in terms of three lists: values, bounds and assoc. Using $n \leftarrow nvals()$ to denote the length of values, the required lengths of bounds and assoc are $n - 1$.

The list bounds refers to values of the input attribute and partitions its scale in n intervals $[-Inf, bound[[1]]], [bound[[1]], bound[[2]]], \dots, [bound[[n - 1]], +Inf]$. The list values then defines the output values for each interval. The list assoc contains strings "up" or "down" that indicate to which interval, lower or higher, belong the corresponding bounds.

Fields

attribute [DexiAttribute](#). The attribute this function is associated with. Requirements: attribute must be discrete (i.e., associated with a [DexiDiscreteScale](#)) and must have exactly one continuous input attribute (i.e., associated with a [DexiContinuousScale](#)).

values A list of output values corresponding to each interval defined by bounds. List elements are in general value sets, i.e., integer vectors of value indices w.r.t. attribute\$scale.

bounds A vector of numeric values that partitions the input scale in intervals.

assoc A vector of strings "up" or "down". For each i in $1:n-1$, assoc[[i]] indicates how to map the value of bounds[[i]]: to value[[i]] ("down") or value[[$i + 1$]] ("up").

Methods

`bound_assoc(idx, default = "down")` Given `idx`, a bounds index, return the corresponding association ("down" or "up").

`evaluate(x)` A silent wrapper around `value(x)`; it returns NULL when `value(x)` fails with an error.

`nargs()` Return the number of function arguments.

`nvals()` Return the length of values.

`to_string()` Return an informative string about this function's values and bounds.

`value(x)` Return the function value for arguments `x`, where arguments are a numeric vector of length equal to `att$inputs`. Additionally, arguments of a `DexiTabularFunctions$value()` must be integer numbers, and the argument of `DexiDiscretizeFunctions$value()` must be a single number.

`verify()` Check the correctness of this function object and its fields. Result: `error()` or TRUE.

Examples

```
# Create a DexiDiscretizeFunction (without association to any attributes or scales)
fnc <- DexiDiscretizeFunction(bounds = c(-1, 2), values = list(1, 3, 5), assoc = c("up", "down"))

# Print fields and basic properties of fnc

fnc$verify()
fnc$nargs()
fnc$nvals()
fnc$to_string()

fnc$bound_assoc(1)
fnc$bound_assoc(2)

# Try some discretizations
sapply(c(-1.1, -1, 0, 1, 2, 3), fnc$evaluate)
```

DexiFunction-class *DexiFunction*

Description

`DexiFunction` is a base RC class for representing DEXi aggregation and discretization functions in R.

Details

DEXi functions are generally associated with aggregate attributes. For some aggregate attribute `att`, `att$funct` defines the mapping from values of `att$inputs` to values of `att`.

[DexiFunction](#) is a base class that defines fields and methods common to all functions:

- method `value(x)`: returns the function value for arguments `x`. Arguments are assumed to be a numeric vector of length equal to `att$inputs`.
- method `evaluate(x)` is a silent wrapper around `value(x)`; it returns `NULL` when `value(x)` fails with an error.

DEXiR implements two other function classes derived from `DexiFunction`: [DexiTabularFunction](#) and [DexiDiscretizeFunction](#).

Methods

- `evaluate(x)` A silent wrapper around `value(x)`; it returns `NULL` when `value(x)` fails with an error.
- `value(x)` Return the function value for arguments `x`, where arguments are a numeric vector of length equal to `att$inputs`. Additionally, arguments of a `DexiTabularFunctions$value()` must be integer numbers, and the argument of `DexiDiscretizeFunctions$value()` must be a single number.
- `verify()` Check the correctness of this function object and its fields. Result: `error()` or `TRUE`.

DexiModel-class	<i>DexiModel</i>
-----------------	------------------

Description

`DexiModel` is a RC class representing a DEXi model in R.

Details

Normally, `DexiModel` objects are created by reading from a `.dxi` file, previously developed by the DEXi software. In principle, all fields of a `DexiModel` should be considered read-only. DEXiR does not provide any explicit functionality for creating and changing DEXi models in R. Of course, models can still be created and modified in R, but without integrity and consistency guarantees.

Fields

- `name` character. Name of the model.
- `description` character. An optional textual description of the model.
- `linking` logical. Indicates whether or not the model uses linked attributes, which are used in DEXi to represent hierarchies of attributes (i.e., directed acyclic graphs) rather than trees.
- `root` [DexiAttribute](#). The virtual root of all subtrees/hierarchies of attributes in the model.
- `attributes` list. A list of all [DexiAttributes](#) that constitute the model.
- `att_names` character. A list of all attribute names, as defined in the original DEXi model. Notice that these names may contain whitespace and other "strange" characters, and may not be unique.
- `att_ids` character. A list of unique attribute IDs generated by DEXiR from `att_names` using [make.unique](#). When using the DEXiR package, it is strongly advised to refer to attributes with their IDs rather than DEXi names.

`basic` list. A list of all basic (input) [DexiAttributes](#) in the model.

`aggregate` list. A list of all aggregate (output) [DexiAttributes](#) in the model.

`links` list. A list of all linked [DexiAttributes](#) in the model.

`basic_ids` character. A vector of all basic attributes' unique names.

`aggregate_ids` character. A vector of all aggregate attributes' unique names.

`link_ids` character. A vector of all linked attributes' unique names.

`alternatives` data.frame. A data frame representing decision alternatives contained in the `.dxi` file.

Methods

`alternative(name = "NewAlternative", ...)` Create a data frame containing data of one decision alternative. `name`, character(1), represents the alternative's name. The arguments `...` define the alternative's values to be put in the data frame. Please see [set_alternative](#) for the syntax of `...`

`as_character(alt, transpose = FALSE, structure = FALSE, round = NULL)` The argument `alt` is assumed to be a data frame containing data of one or more decision alternatives with values represented by numeric vectors. `as_character(alt)` transforms the values of `alt` into a more human-readable form using character strings. Additionally, `transpose = TRUE` transposes the data frame, so that rows correspond to attributes and columns to alternatives. `structure = TRUE` additionally displays the tree structure of attributes; the latter works only with `transpose = TRUE`. `round` denotes the number of decimal digits for printing numeric values.

`att_index(attrs, use_id = TRUE)` Find the indices of attributes. `attrs` is a character vector of attribute IDs (when `use_id = TRUE`) or original DEXi attribute names (when `use_id = FALSE`). Result: a numeric vector containing the set of indices. Example: `Car$att_index(c("PRICE", "TECH.CHAR."))`

`att_stat()` Count the number of all attributes (including the virtual root), as well as the number of basic, aggregate and linked attributes in the model. Result: a list of the form `list(all=..., basic=..., aggregate=..., link=...)`.

`attrib(attrs)` A general function for finding attributes in the model. `attrs` is a vector or list of [DexiAttributes](#), attribute indices (integer) or attribute IDs (character). Result: a list of found [DexiAttributes](#) (or NAs if not found). Example: `Car$attrib(list(5, "PRICE", "TECH.CHAR."))`

`compare_alternatives(...)` Calls [compare_alternatives\(.self, ...\)](#) to carry out Comparison of Alternatives. Please see [compare_alternatives](#) for the description of `...` arguments.

`convert(...)` Calls [convert_alternatives\(.self, ...\)](#) to convert decision alternatives' data. Please see [convert_alternatives](#) for the description of `...` arguments.

`evaluate(...)` Calls [evaluate\(.self, ...\)](#) to evaluate decision alternatives. Please see [evaluate](#) for the description of `...` arguments.

`first()` Return first non-virtual model attribute, i.e., first descendant of `model$root`.

`initialize(name = "", description = "", root = NULL, linking = FALSE, ...)` Initialize a [DexiModel](#) object.

`link_attributes()` Carries out the linking of attributes. DEXi attributes that have the same names and value scales, and satisfy some other constraints to prevent making cycles in the model, are linked together so that they logically represent a single attribute. In this way, a tree of attributes is conceptually turned in a hierarchy (directed acyclic graph). If `linking = TRUE`, `link_attributes` is called by `setup()` after reading the model.

`plus_minus(...)` Calls `plus_minus(.self, ...)` to carry out Plus-Minus Analysis. Please see [plus_minus](#) for the description of ... arguments.

`scale(attrs)` Find attribute scales. `attrs` is a vector of `DexiAttributes`. Result: a vector of the corresponding `DexiScales` (or NAs).

`selective_explanation(...)` Calls `selective_explanation(.self, ...)` to carry out Selective Explanation. Please see [selective_explanation](#) for the description of ... arguments.

`setup()` Called by `initialize()` as the last step that establishes consistent internal data structures by making unique attribute IDs, linking attributes (if required), making lists of attributes and their IDs, and creating a data frame of alternatives.

`verify()` Check the correctness of a `DexiModel` object and its fields. Result: `error()` or `TRUE`.

See Also

[evaluate](#), [set_alternative](#), [read_dexi\(\)](#)

Examples

```
# Get ".dexi" file name
CarDexi <- system.file("extdata", "Car.dexi", package = "DEXiR")

# Read DEXi model
Car <- read_dexi(CarDexi)

# Print fields of Car
Car
Car$verify()
Car$name
Car$description
Car$linking
att_names(Car$attributes)
Car$att_names
Car$att_ids
Car$basic_ids
Car$aggregate_ids
Car$att_stat()
Car$scale(Car$aggregate)

# Find some attributes in the model
Car$first()
Car$attributes[[3]]
Car$attrib("PRICE")
Car$att_index("PRICE")

# Display alternatives loaded from "Car.dexi"
Car$alternatives
```

```

Car$as_character(Car$alternatives)
Car$as_character(Car$alternatives, transpose = TRUE)
Car$as_character(Car$alternatives, transpose = TRUE, structure = TRUE)

# Define and evaluate a decision alternative (some car)
alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS=3, X.DOORS=3, LUGGAGE="medium", SAFETY=2)
Car$evaluate(alt)
Car$as_character(Car$evaluate(alt))

# Employ the set-based evaluation (notice how the value of SAFETY propagates upwards to TECH.CHAR.)
alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS=3, X.DOORS=3, LUGGAGE="medium", SAFETY=c(2,3))
Car$evaluate(alt)
Car$as_character(Car$evaluate(alt))

# Analysis of alternatives
Car$selective_explanation(1)
Car$selective_explanation(alt)
Car$plus_minus(alt)
Car$compare_alternatives(alt)
Car$compare_alternatives(1, 2)
Car$compare_alternatives(1, alt)

```

DexiScale-class

DexiScale

Description

DexiScale is a base RC class representing value scales in R.

Details

A value scale defines the type and set of values that can be assigned to some [DexiAttribute](#). [DexiScale](#) is a base scale class that defines fields and methods common to all scales:

- whether or not the scale is preferentially ordered (and in which direction),
- scale type (discrete or continuous),
- the number of scale elements, if countable,
- partition of scale elements in three preferential classes: "bad", "good" and "none",
- helper methods `value_index()` and `full_range()`.

DEXiR implements two other scale classes derived from DexiScale: [DexiContinuousScale](#) and [DexiDiscreteScale](#).

Fields

`order` character. Preferential order of the scale. Possible values: "ascending", "descending" or "none".

Methods

- `count()` Return the number of scale elements. Equal to NA for `DexiScale`, 0 for `DexiContinuousScale`, and equal to `nvals >= 0` for `DexiDiscreteScale`.
- `equal(sc1)` Check if this scale is equal to scale `sc1`. Needed for attribute linking.
- `full_range()` Return the vector that represents the full range of values on this scale. Equal to NA for `DexiScale` and `DexiContinuousScale`, and `1 : scale$nvals` for `DexiDiscreteScale`.
- `initialize(order = EnumOrder, ...)` Initialize a `DexiScale` object.
- `is_continuous()` Logical: Is this scale continuous?
- `is_discrete()` Logical: Is this scale discrete?
- `to_string()` Return a string representation of this scale for printing.
- `value_index(value)` Find the index of `value` (`character(1)`) on this scale. Equal to NA for `DexiScale` and `DexiContinuousScale`. With `DexiDiscreteScale` objects, it returns a numeric index or NA of `value` in `scale$values`.
- `value_quality(value)` Return the quality (preferential class) of `value` on this scale: one of the strings "bad", "none" or "good". Always "none" for `DexiScale` and scales with `order = "none"`.
- `verify()` Check the correctness of this scale object and its fields. Result: `error()` or TRUE.

DexiTabularFunction-class

DexiTabularFunction

Description

`DexiTabularFunction` is a RC class, derived from [DexiFunction](#). Functions of this type aggregate attribute values according to *decision rules*, defined in terms of a *decision table*.

Details

A decision table contains as many decision rules as there are possible combinations of input attributes' values. For instance, if some attribute has two inputs whose discrete scales have three and four values, respectively (i.e., `attribute$dim() == c(3, 4)`), then the number of rules is equal to `prod(attribute$dim()) == 12`. Each rule defines the value of attribute for one of the possible combinations of values of `attribute$inputs`. Thus, a decision table can be interpreted as a lookup table that, given a vector of values of `attribute$inputs` (i.e., function arguments) returns the corresponding attribute value.

Objects of class `DexiTabularFunction` store decision rules in `values`, a multi-dimensional list that contains rule values. In most cases, a rule value is a single integer, representing an ordinal number of some value from `attribute$scale`. In a general case, however, a rule value can be an integer vector, representing a (sub)set of values from `attribute$scale`.

Fields

- `attribute` [DexiAttribute](#). The attribute this function is associated with. Both the attribute and its inputs are required to be discrete (i.e., associated with `DexiDiscreteScales`).
- `values` A multi-dimensional list of rule values. The dimensions of the list are equal to `attribute$dim()`, and the length of the list is `nvals() == prod(dim)`. The list contains rule values that are in general value sets, i.e., integer vectors of value indices w.r.t. `attribute$scale`.
- `args` A list of integer vectors, containing all possible combinations of values of `attribute$inputs`. `args` and `values` are of the same length and ordered so that, for each `i`, `args[[i]]` defines function arguments that map to `values[[i]]`.

Methods

- `evaluate(x)` A silent wrapper around `value(x)`; it returns `NULL` when `value(x)` fails with an error.
- `nargs()` Return the number of function arguments.
- `nvals()` Return the function size (number of rules).
- `to_string()` Return a short informative string about the size and dimensions of `values`.
- `value(x)` Return the function value for arguments `x`, where arguments are a numeric vector of length equal to `att$inputs`. Additionally, arguments of a `DexiTabularFunctions$value()` must be integer numbers, and the argument of `DexiDiscretizeFunctions$value()` must be a single number.
- `verify()` Check the correctness of this function object and its fields. Result: `error()` or `TRUE`.

See Also

[dexi_index\(\)](#), [dexi_table\(\)](#), [make_args\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# For example, consider the function of attribute CAR
fnc <- Car$attrib("CAR")$funct

# Print fields and basic properties of fnc
fnc$verify()
att_names(fnc$attribute)
fnc$values
fnc$args
fnc$nargs()
fnc$nvals()
fnc$to_string()

# Try some args to value mappings
fnc$evaluate(c(1, 1))
fnc$evaluate(c(2, 2))
```

```
fnc$evaluate(c(3, 4))
fnc$evaluate(c(4, 4)) # the first argument is out of bounds, returns NULL
```

dexi_bool	<i>dexi_bool</i>
-----------	------------------

Description

Convert a DEXi string to logical. "TRUE", "T" and "1" are interpreted as TRUE, all other strings as FALSE.

Usage

```
dexi_bool(x)
```

Arguments

x character(1).

Value

logical(1).

Examples

```
dexi_bool("TRUE")
sapply(c("TRUE", "T", "1", TRUE, 1, "FALSE", "F", "0", NULL, NA, NaN), dexi_bool)
```

dexi_index	<i>dexi_index</i>
------------	-------------------

Description

Return the index of argument vector `vec` in the decision space `dim`. The index is calculated according to DEXi's sorting rules, which are different to R's.

Usage

```
dexi_index(vec, dim)
```

Arguments

`vec` Integer vector, representing arguments of some decision rule.
`dim` Integer vector, representing dimensions of the corresponding decision space.
Assumptions: `length(vec) == length(dim)` and, for each `i`, `1 <= vec[[i]] <= dim[[i]]`.

Value

Integer, index of vec.

Examples

```
dexi_index(c(1,1,1), c(2,2,3))
dexi_index(c(1,1,2), c(2,2,3))
dexi_index(c(1,2,3), c(2,2,3))
```

dexi_option_value *dexi_option_value*

Description

Conversion of a string to a "DEXi value" (see [DEXiR-package](#)) according to "old" DEXi syntax. In .dxi files, the old syntax is used with OPTION XML tags. The reason for replacing the old with the new syntax (see [dexi_value\(\)](#)) was that the old syntax can not unambiguously represent value distributions.

Usage

```
dexi_option_value(x)
```

Arguments

x character(1). Contains a sequence of characters, each of which represents an individual ordinal number.

Value

A numeric vector. The conversion uses `rule_values(x, add = 1)`. For special-type parameters, the conversion results are:

x	result
NULL	NULL
a non-character object	NA
"" or "*"	"*"
a string starting with "undef"	NA

See Also

[DEXiR-package](#), [dexi_value\(\)](#), [rule_value\(\)](#)

Examples

```
dxi_option_value(NULL)
dxi_option_value(NA)
dxi_option_value("")
dxi_option_value("*")
dxi_option_value("undef")
dxi_option_value("1")
dxi_option_value("012")
```

dxi_table	<i>dxi_table</i>
-----------	------------------

Description

Create a representation of DEXi's decision table in R.

Usage

```
dxi_table(dim, low, high = NULL)
```

Arguments

dim	An integer vector, representing dimensions of the underlying decision space.
low	character(1). A string normally read from a .dxi file, representing the lower bounds of the corresponding decision rule values (assuming the order according to dxi_index()). Notice that the string contains zero-based characters, which are converted to one-based integer values used in R.
high	character(1) or NULL. A string representing the upper bounds of corresponding decision rule values. If high = NULL, high is assumed to be equal to low.

Value

length(dim)-dimensional matrix of rule values, which are normally single integer values, but might also be sets of values. Each set is represented by a numeric vector.

Examples

```
# Converting DEXi's value strings to R's numeric vectors.
dxi_table(c(2, 3), "011012")
dxi_table(c(2, 3), "011012", "012112")
```

dexi_value	<i>dexi_value</i>
------------	-------------------

Description

Conversion of a string to a "DEXi value" (see [DEXiR-package](#)) according to "new" DEXi syntax rules. In .dxi files, this syntax is used in ALTERNATIVE and RULE XML tags. Examples of possible options include:

x	result
NULL or ""	NULL
"*"	"*"
a string starting with "undef"	NA
"2"	a single ordinal value, c(2) in this case
"2.1"	a single number, c(2.1) in this case
"1:3"	interval, equivalent to c(1, 2, 3)
"{0;2;3}"	a value set, equivalent to c(0, 2, 3)
"<0;0.3;0.7>"	a value distribution, distribution(0.0, 0.3, 0.7)

Usage

```
dexi_value(x, add = 0)
```

Arguments

x	character(1).
add	A numeric constant to be added to the result. Useful when converting DEXi's zero-based representation to one-based representation used in R, which requires the setting add = 1.

Value

A single integer or real number, an integer numeric vector, or a [distribution](#).

See Also

[DEXiR-package](#), [dexi_option_value\(\)](#), [distribution](#)

Examples

```
dexi_value("")
dexi_value(NULL)
dexi_value("*")
dexi_value("UNDEF")
dexi_value("2")
dexi_value("2.1")
dexi_value("1:3")
```

```
dexi_value("{0;2;3}")  
dexi_value("{0;2;3}", add = 1)  
dexi_value("<0;0.3;0.7>")
```

dexi_vector

dexi_vector

Description

Interpret a string, composed of ";"-separated numbers, as a numeric vector.

Usage

```
dexi_vector(x)
```

Arguments

x character(1).

Value

Numeric vector.

Examples

```
dexi_vector("1;2")  
dexi_vector("1.2; 2.3")
```

distribution

distribution

Description

Create an object as a S3 class distribution.

Usage

```
distribution(...)
```

Arguments

... Expected a comma-separated list of numeric values.

Value

An object, call it obj, such that all(obj == c(...)) and class(obj) == "distribution".

See Also

[DEXiR-package](#), [set_to_distr\(\)](#), [distr_to_set\(\)](#)

Examples

```
distribution(0.1, 0.2, 0.7)
```

<code>distr_to_set</code>	<i>distr_to_set</i>
---------------------------	---------------------

Description

Convert a DEXi value distribution to a DEXi value set.

Usage

```
distr_to_set(distr, eps = .Machine$double.eps)
```

Arguments

<code>distr</code>	An S3 object of class <code>distribution</code> .
<code>eps</code>	A numeric value representing the threshold value of p (see DEXiR-package) above which the corresponding elements are considered set members.

Value

A numeric vector determined as `which(distr > eps)`. Notice that `distr_to_set` is generally a lossy conversion, so that multiple different `distr`s are converted to the same sets.

See Also

[DEXiR-package](#), [distribution](#), [set_to_distr\(\)](#)

Examples

```
distr_to_set(distribution(0.2, 0, 0.5, 0.3))
distr_to_set(distribution(0.1, 0, 0.7, 0.2))
distr_to_set(distribution(0.1, 0, 0.7, 0.2), eps = 0.5)
```

equal_scales	<i>equal_scales</i>
--------------	---------------------

Description

Check if two scales are equal. NULL arguments, indicating undefined scales, are allowed. Two NULL scales are considered equal.

Usage

```
equal_scales(scl1, scl2)
```

Arguments

scl1	A DexiScale (or derived) object, or NULL.
scl2	A DexiScale (or derived) object, or NULL.

Value

logical(1).

evaluate	<i>evaluate</i>
----------	-----------------

Description

Evaluates decision alternatives. Essentially, this is a bottom-up aggregation method: starting with basic attributes (or pruned aggregate attributes), values of each alternative are gradually aggregated towards the root attribute, according to [evaluation_order\(\)](#). The aggregation at each individual [DexiAttribute](#) is governed by the corresponding `DexiAttribute$funct`. When alternative values are sets or distributions (see [DEXiR-package](#)), then [evaluate\(\)](#) tries all possible combinations of values of the descendant attributes.

Usage

```
evaluate(
  model,
  alternatives = model$alternatives,
  root = model$root,
  method = EnumEvalMethod,
  bounding = FALSE,
  prune = list(),
  norm = NULL,
  and = NULL,
  or = NULL
)
```

Arguments

model	DexiModel .
alternatives	A data frame containing data of one or more decision alternatives.
root	DexiAttribute . Default: model\$root.
method	One of: "set" (default), "prob", "fuzzy" or "fuzzynorm".
bounding	logical(1). When TRUE, evaluation results are additionally subjected to bounded_scale_value() to keep them in the bounds set up by the corresponding scale.
prune	character(), containing IDs of aggregate attributes that should be treated as evaluation inputs (rather than basic attributes).
norm	Some normalization function of the form function(num_vector), or NULL.
and	Some conjunctive aggregation function of the form function(num_vector), or NULL.
or	Some disjunctive aggregation function of the form function(num_vector), or NULL.

Details

[evaluate\(\)](#) implements four aggregation methods: "set", "prob", "fuzzy" and "fuzzynorm".

The "set" method interprets DEXi values as sets. The output value assigned to some attribute is composed of the union of all `attribute$funct` evaluations for all possible combinations of values of `attribute$inputs`.

The remaining three methods interpret DEXi values as value distributions. They follow the same algorithm, but use different functions (see [evaluation_parameters\(\)](#)) in three algorithm steps: normalization, and conjunctive and disjunctive aggregation. All values distributions involved in calculations are normalized by the function `norm()`. All combinations of `attribute$input` values are individually evaluated by the corresponding tabular function `attribute$funct`. The value p of each set of `attribute$funct` arguments is determined by the conjunctive aggregation function `and()` over p 's of individual arguments. Finally, the p of some output value `val` is determined by the disjunctive aggregation function `or()`, applied on the p 's of all partial evaluations that map to `val`.

For the mathematical background and more details about aggregation in DEX, please see (Trdin, Bohanec, 2018). For default normalization and aggregation functions, see [normalize_function\(\)](#), [and_function\(\)](#) and [or_function\(\)](#).

Value

A data frame containing both input and output (evaluated) values of alternatives.

See Also

[evaluation_parameters\(\)](#), [normalize_function\(\)](#), [norm_none\(\)](#), [norm_max\(\)](#), [norm_sum\(\)](#), [and_function\(\)](#), [or_function\(\)](#), [bounded_scale_value\(\)](#).

Examples

```

# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

alt <- Car$alternative("MyCar_set",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY="medium")
Car$evaluate(alt)

# Try the set-based evaluation using the default "set" method
alt <- Car$alternative("MyCar2",
  BUY.PRICE="low", MAINT.PRICE="*", X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=2)
Car$evaluate(alt)

# Use value distributions and try the methods "prob", "fuzzy" and "fuzzynorm"
alt <- Car$alternative("MyCar_distr",
  BUY.PRICE="low", MAINT.PRICE=distribution(0.1, 0.6, 0.3),
  X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=2)
Car$evaluate(alt, method = "prob")
Car$evaluate(alt, method = "fuzzy")
Car$evaluate(alt, method = "fuzzynorm")

```

evaluate_attribute *evaluate_attribute*

Description

Evaluate alternative for a sequence of attribute values.

Usage

```
evaluate_attribute(model, attribute, alternative, seq = NULL, ...)
```

Arguments

model	A DexiModel .
attribute	A DexiAttribute with an assigned discrete or continuous scale.
alternative	A data.frame containing a single alternative.
seq	A sequence of attribute numeric values for which to evaluate alternative. For discrete scales: Must be a sequence of integers. Defaults to <code>attribute\$scale\$full_range()</code> . For continuous scales: seq is required.
...	Optional parameters passed to evaluate() .

Value

A list of evaluated alternatives for consecutive attribute values from seq.

See Also[evaluate\(\)](#)**Examples**

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY="medium")
safety <- Car$attrib("SAFETY")
# Evaluate alt for all values of att
evaluate_attribute(Car, safety, alt)
# Returns a list of three alternatives for values SAFETY=c("small", "medium", "high")
```

evaluate_attributes *evaluate_attributes*

Description

Apply `evaluate_attribute()` for all discrete attributes.

Usage

```
evaluate_attributes(model, alternative, attributes = NULL, ...)
```

Arguments

<code>model</code>	A DexiModel object. Required.
<code>alternative</code>	A data.frame containing a single alternative.
<code>attributes</code>	List of attributes or vector of attribute names, ID's or indices. Default: All basic attributes of model.
<code>...</code>	Optional parameters passed to evaluate_attribute() .

Value

A list of `evaluate_attribute()` results for each attribute

See Also[evaluate_attribute\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE=2, X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY="medium")
safety <- Car$attrib("SAFETY")
# Perform evaluate_attribute() for all basic attributes of CarDxi
evaluate_attributes(Car, alt)
# Returns a list of evaluate_attribute() results corresponding to all basic attributes,
# indexed by attribute id
```

evaluation_order	<i>evaluation_order</i>
------------------	-------------------------

Description

Determine the evaluation order of attributes. Interpreted as a sequence, the order guarantees that whenever some attribute is reached as a candidate for evaluation, all the previous attributes have been already evaluated.

Usage

```
evaluation_order(att, prune = list())
```

Arguments

att	DexiAttribute . The starting point of evaluation.
prune	A character vector. May contain IDs of aggregate attributes at which the evaluation should stop, treating them as if they were basic attributes.

Value

A character vector of attribute IDs.

See Also

[evaluate\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Full evaluation order, starting with Car$root and without pruning
evaluation_order(Car$root)
```

```
# Evaluation order, starting with the TECH.CHAR. attribute
evaluation_order(Car$attrib("TECH.CHAR.))

# evaluation order, starting with Car$root and pruned at "PRICE"
evaluation_order(Car$root, prune = "PRICE")
```

evaluation_parameters *evaluation_parameters*

Description

Make a list containing parameters of DEXi evaluation. The parameters determine which method and normalization/aggregation functions should be used by `evaluate()`.

Usage

```
evaluation_parameters(
  method = EnumEvalMethod,
  norm = NULL,
  and = NULL,
  or = NULL
)
```

Arguments

method	One of: "set" (default), "prob", "fuzzy" or "fuzzynorm".
norm	Some normalization function of the form <code>function(num_vector)</code> , or NULL.
and	Some conjunctive aggregation function of the form <code>function(num_vector)</code> , or NULL.
or	Some disjunctive aggregation function of the form <code>function(num_vector)</code> , or NULL.

Value

`list(method, norm, and, or)`. For NULL norm, and, and or arguments, defaults are taken depending on the method.

See Also

`evaluate`, `normalize_function()`, `norm_none()`, `norm_max()`, `norm_sum()`, `and_function()`, `or_function()`.

Examples

```
evaluation_parameters("prob", norm = norm_none)
```

```
expand_value_to_points
      expand_value_to_points
```

Description

Expand a DEXi value to a sequence of individual elements (points). Particularly aimed for graphic functions that display DEXi values with dots of different sizes and colors.

Usage

```
expand_value_to_points(value, scale, colors = c("red", "black", "green"))
```

Arguments

value	A DEXi value: a single value (integer or float), a set (integer vector) or a distribution .
scale	A DexiScale object.
colors	numeric(3) representing colors to display "bad", "neutral" and "good" values, respectively.

Value

A data.frame consisting of:

points numeric(). value expanded to a vector of ordinal values.

sizes numeric(). Numeric values assigned to each corresponding ordinal values. Normally 1.0 for set elements and in the (0, 1] interval for distribution membership values.

colors Colors assigned to corresponding value qualities.

Examples

```
scl <- DexiDiscreteScale(values = c("L", "M", "H"))

expand_value_to_points(c(1, 3), scl)
# points sizes colors
# 1      1      1   red
# 2      3      1 green

expand_value_to_points(distribution(0.1, 0, 0.9), scl)
# points sizes colors
# 1      1  0.1   red
# 2      3  0.9 green
```

export_alternatives *export_alternatives*

Description

Convert alternatives' data to a data frame formatted so that it can be imported by DEXi/DEXiWin software.

Usage

```
export_alternatives(model, alternatives = NULL)
```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to model\$alternatives. The default value NULL selects model\$alternatives.

Details

In order to import the output of `export_alternative()` in DEXi/DEXiWin software, proper Import/Export settings must be ensured in these programs:

DEXi Option values: "base 1", Attributes: "all", Orientation: "normal", Indent: "indent".

DEXiWin Option values: "Base 1", Attributes: "All", Orientation: "Attributes \ Alternatives", Indent: "Indent tree levels", CSV Format: "Invariant" when format = "csv" and "Local" when format = "csv2".

If alternatives contain value distributions, they can be imported only by DEXiWin and not by DEXi.

Value

A data frame consisting of character strings that can be further written out by [write_alternatives\(\)](#).

See Also

[write_alternatives\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

export_alternatives(Car)    # export both alternatives from Car
export_alternatives(Car, 1) # export only the first alternative
```

export_dexi_value	<i>export_dexi_value</i>
-------------------	--------------------------

Description

Convert a DEXi value to a character string that is understood by DEXi/DEXiWin software while importing data about alternatives.

Usage

```
export_dexi_value(value)
```

Arguments

value A DEXi value: NA, NULL, a single number, integer vector (a set) or a distribution.

Value

A string representation of value.

Examples

```
export_dexi_value(NULL)                    # "<undefined>"
export_dexi_value(NA)                    # "<undefined>"
export_dexi_value(1)                    # "1"
export_dexi_value(3.2)                   # "3.2"
export_dexi_value(c(1, 3, 5))            # "1;3;5"
export_dexi_value(distribution(0.1, 0.9)) # "1/0.1;2/0.9"
export_dexi_value(distribution(0, 0.1, 0, 0.9, 0)) # "2/0.1;4/0.9"
```

flat_text	<i>flat_text</i>
-----------	------------------

Description

"Flatten" the function argument using `c(value)`, concatenate the elements and separate them by a single space.

Usage

```
flat_text(value)
```

Arguments

value Any object that can occur as an argument of `c()` and `as.character()`.

Value

character(1).

ggplot_parallel	ggplot_parallel
-----------------	-----------------

Description

Makes a basic ggplot2 chart for displaying DEXi alternatives using parallel axes. Generally, axes are uniformly scaled to the $[0, 1]$ interval.

Usage

```
ggplot_parallel(
  model,
  alternatives = NULL,
  attids = NULL,
  aggregate = c("minmax", "min", "max", "mean", "none"),
  name = "name",
  shift = 0.01
)
```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to <code>model\$alternatives</code> . The default value NULL selects the whole <code>model\$alternatives</code> .
attids	<code>character()</code> . A character vector of DexiAttribute IDs to be included in the result. Default: all <code>model</code> attributes.
aggregate	One of "minmax", "min", "max", "mean" or "none". Determines how to aggregate alternatives' values that are represented by sets or distributions.
name	<code>character(1)</code> , The name of the column in alternatives that contains alternatives' names. Default: "name".
shift	<code>numeric(1)</code> . Used to "shift" numeric values by a small amount to avoid overlapping lines in charts. Default: 0.01. You may want to experiment with charts to determine the right value,

Details

Uses [GGally::ggparcoord\(\)](#) and requires package "GGally" to be installed. Data presented in the chart is prepared by [scale_alternatives\(\)](#).

Value

A basic 'ggplot2' chart. Generally, this chart needs to be further enhanced by graph layers, such as themes, labels, `geom_points()` and `geom_line()`. See [plotalt_parallel\(\)](#) that already provides some such layers.

See Also

[scale_alternatives\(\)](#), [plotalt_parallel\(\)](#)

Examples

```
if (requireNamespace("GGally", quietly = TRUE)) {
  # Load "Car.dxi"
  CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
  Car <- read_dexi(CarDxi)

  # Plot all Car$alternatives with points and lines
  ggplot_parallel(Car) + ggplot2::geom_line(linewidth = 2) + ggplot2::geom_point(size = 3)
}
```

has_bad	<i>has_bad</i>
---------	----------------

Description

has_bad

Usage

```
has_bad(value, scale)
```

Arguments

value	A DEXi value.
scale	A DexiScale or derived object.

Value

logical(1). Whether or not `value_qualities(value, scale)` contains "bad".

has_good	<i>has_good</i>
----------	-----------------

Description

has_good

Usage

```
has_good(value, scale)
```

Arguments

value	A DEXi value.
scale	A DexiScale or derived object.

Value

logical(1). Whether or not `value_qualities(value, scale)` contains "good".

<code>has_none</code>	<i>has_none</i>
-----------------------	-----------------

Description

`has_none`

Usage

```
has_none(value, scale)
```

Arguments

value	A DEXi value.
scale	A DexiScale or derived object.

Value

logical(1). Whether or not `value_qualities(value, scale)` contains "none".

<code>has_quality</code>	<i>has_quality</i>
--------------------------	--------------------

Description

`has_quality`

Usage

```
has_quality(quality = EnumQuality, value, scale)
```

Arguments

quality	A character string from <code>EnumQuality</code> .
value	A DEXi value.
scale	A DexiScale or derived object.

Value

logical(1). Whether or not `value_qualities(value, scale)` contains quality.

is_distribution	<i>is_distribution</i>
-----------------	------------------------

Description

Checks whether value is of `DexDistributionClass` or not.

Usage

```
is_distribution(value)
```

Arguments

value Any value or object to be checked.

Value

logical(1). Returns TRUE if value is distribution.

Examples

```
is_distribution(NULL)
is_distribution(3)
is_distribution("text")
is_distribution(c(1,2,3))
is_distribution(distribution(1,0,2))
```

is_in_range	<i>is_in_range</i>
-------------	--------------------

Description

Check whether or not x lies the specified range.

Usage

```
is_in_range(x, lb, hb, lassoc = c("up", "down"), hassoc = c("down", "up"))
```

Arguments

x	Any object type, but using a non-numeric argument always returns FALSE.
lb	numeric(1). Lower bound of the interval.
hb	numeric(1). Upper bound of the interval.
lassoc	"up" or "down", indicating whether lb is included in the [lb:hb] interval ("up") or not ("down"). The default is "up".
hassoc	"up" or "down", indicating whether hb is included in the [lb:hb] interval ("down") or not ("up"). The default is "down".

Value

logical(1), indicating whether or not x lies in the interval [lb:hb] according to function arguments.

Examples

```
is_in_range(3, 2, 5)
is_in_range(7, 2, 5)
is_in_range(3, 3, 5)
is_in_range(3, 3, 5, lassoc = "down")
```

lin_map

lin_map

Description

Map value x linearly from interval [imin:imax] to [omax:omax].

Usage

```
lin_map(x, imin, imax, omin = 0, omax = 1)
```

Arguments

x	numeric(). Value(s) to be mapped.
imin	numeric(). Lower bound of the input range.
imax	numeric(). Upper bound of the input range.
omin	numeric(). Lower bound of the output range.
omax	numeric(). Upper bound of the output range.

Value

numeric(). Mapped value(s).

Examples

```
lin_map(2, 1, 3) # 0.5
```

 make_args

make_args

Description

Make a list of all possible combinations of values in a decision space defined by `dim`.

Usage

```
make_args(dim)
```

Arguments

`dim` A numeric vector containing upper bounds of the corresponding decision space dimensions. For example, `dim = c(3, 4)` defines the space of $3 * 4 == 12$ combinations.

Value

A list containing all possible value combinations. List elements are numeric vectors of length equal to `length(dim)`.

Examples

```
make_args(c(3, 4))
```

 normalize_function

normalize_function

Description

Determine the function to be used in the normalization step of `evaluate()`.

Usage

```
normalize_function(method = EnumEvalMethod, norm = NULL)
```

Arguments

`method` One of: "set" (default), "prob", "fuzzy" or "fuzzynorm".
`norm` Some normalization function of the form `function(num_vector)`, or NULL.

Value

Returns function norm if not NULL. Otherwise, it determines the result depending on method:

"set": `norm_none()`

"prob": `norm_sum()`

"fuzzy": `norm_none()`

"fuzzynorm": `norm_max()`

Fails with an error if the result is not an R function.

See Also

`evaluate`, `norm_none()`, `norm_max()`, `norm_sum()`,

norm_max

norm_max

Description

Normalize values so that `max(values) == max`.

Usage

```
norm_max(values, max = 1)
```

Arguments

values A numeric vector.

max `numeric(1)`.

Value

values normalized so that `max(result) == max`. Returns unchanged values when `max(values) == 0`.

See Also

`norm_none()`, `norm_sum()`

Examples

```
norm_max(c(0, 0.5, 0.7))
```

norm_none	<i>norm_none</i>
-----------	------------------

Description

A "do nothing" normalization function.

Usage

```
norm_none(values)
```

Arguments

values A numeric vector.

Value

Returns unchanged values.

See Also

[norm_max\(\)](#), [norm_sum\(\)](#)

Examples

```
norm_none(c(0, 0.5, 0.7))
```

norm_sum	<i>norm_sum</i>
----------	-----------------

Description

Normalize values so that `sum(values) == sum`.

Usage

```
norm_sum(values, sum = 1)
```

Arguments

values A numeric vector.
sum `numeric(1)`.

Value

values normalized so that `sum(result) == sum`. Returns unchanged values when `sum(values) == 0`

See Also

[norm_none\(\)](#), [norm_max\(\)](#)

Examples

```
norm_sum(c(0, 0.5, 0.7))
```

or_function

or_function

Description

Determine the function to be used in the disjunctive aggregation step of [evaluate\(\)](#).

Usage

```
or_function(method = EnumEvalMethod, or = NULL)
```

Arguments

method	One of: "set" (default), "prob", "fuzzy" or "fuzzynorm".
or	Some disjunctive aggregation function of the form <code>function(num_vector)</code> , or NULL.

Value

Returns the function or if not NULL. Otherwise, it determines the result depending on method:

"set": `function(x) 1`

"prob": `sum`

"fuzzy": `max`

"fuzzynorm": `max`

Fails with an error if the result is not an R function.

See Also

[evaluate](#), [and_function\(\)](#).

plotalt1	<i>plotalt1</i>
----------	-----------------

Description

Plot alternatives with respect to a single attribute.

Usage

```
plotalt1(
  model,
  attribute = model$first(),
  alternatives = NULL,
  colors = c("red", "black", "green"),
  pch = 20,
  size = 5,
  linetype = 2,
  margins = NULL,
  lm = NULL,
  ...
)
```

Arguments

model	A DexiModel object. Required.
attribute	A single DexiAttribute selector. It may be an DexiAttribute object or an argument to <code>model\$attrib()</code> . <code>attribute\$scale</code> must be defined. Default: <code>model\$first()</code> .
alternatives	A data frame of alternatives (normally an output of evaluate()) or indices to <code>model\$alternatives</code> . The default value NULL selects the whole <code>model\$alternatives</code> .
colors	character(3) representing colors corresponding to "bad", "neutral" and "good" scale values, respectively. Default: <code>c("red", "black", "green")</code> .
pch	Plotting character, see graphics::points() . Default: 20.
size	numeric(1). Multiplication size factor for drawing individual points. Base point size depends on pch.
linetype	integer(). Line type for drawing chart grid. Default: 2.
margins	numeric(4). Chart margins, passed to graphics::par() prior to drawing.
lm	numeric(1). Left chart margin. May be used to adjust the display of alternatives' names.
...	Optional parameters passed to graphics::plot() .

Details

Standard scatterplot [base::plot](#) is used.

Value

Draws a chart.

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Plot all Car$alternatives with respect to "TECH.CHAR." attribute
plotalt1(Car, "TECH.CHAR.")

# Plot the first Car alternative with respect to "MAINT.PRICE" attribute
plotalt1(Car, "MAINT.PRICE", 1)
```

plotalt2

plotalt2

Description

Draw a scatterplot of alternatives with attribute1 and attribute2 on the x and y axis, respectively.

Usage

```
plotalt2(
  model,
  attribute1,
  attribute2,
  alternatives = NULL,
  colors = NULL,
  pch = 20,
  size = 5,
  margins = NULL,
  lm = NULL,
  pos = 4,
  offset = 1,
  ...
)
```

Arguments

model	A DexiModel object. Required.
attribute1	First attribute. It may be an DexiAttribute object or an argument to <code>model\$attrib()</code> . The attribute must be discrete.

attribute2	Second attribute. It may be an DexiAttribute object or an argument to <code>model\$attrib()</code> . The attribute must be discrete.
alternatives	A data.frame of alternatives (normally an output of <code>evaluate()</code>) or indices to <code>model\$alternatives</code> . The default value NULL selects the whole <code>model\$alternatives</code> .
colors	<code>character()</code> . Colors for displaying subsequent alternatives.
pch	Plotting character, see <code>graphics::points()</code> . Default: 20.
size	<code>numeric(1)</code> . Multiplication size factor for drawing individual points. Base point size depends on pch.
margins	<code>numeric(4)</code> . Chart margins, passed to <code>graphics::par()</code> prior to drawing.
lm	<code>numeric(1)</code> . Left chart margin. May be used to adjust the display of <code>attribute2</code> 's values.
pos	A position specifier for legend text, see <code>graphics::text()</code> . Default: 4.
offset	When <code>pos</code> is specified, this value controls the distance of the text label from the specified coordinate in fractions of a character width. Default: 1.
...	Optional parameters passed to <code>graphics::plot()</code> .

Details

Standard scatterplot `graphics::plot()` is used. Continuous attributes are not supported.

Value

Draws a chart.

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Plot all Car$alternatives with respect to "PRICE" and "TECH.CHAR." attributes
plotalt2(Car, "PRICE", "TECH.CHAR.")

# Plot the first Car alternative with respect to "BUY.PRICE" and "MAINT.PRICE" attributes
plotalt2(Car, "BUY.PRICE", "MAINT.PRICE", 1)
```

plotalt_parallel *plotalt_parallel*

Description

Makes and plots DEXi alternatives on parallel axes, corresponding to attributes. Generally, axes are uniformly scaled to the $[0, 1]$ interval.

Usage

```
plotalt_parallel(
  model,
  alternatives = NULL,
  attids = NULL,
  aggregate = c("minmax", "min", "max", "mean", "none"),
  name = "name",
  shift = 0.01,
  linewidth = 2,
  pointsize = 3,
  split = c("no", "h", "v")
)
```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to <code>model\$alternatives</code> . The default value NULL selects the whole <code>model\$alternatives</code> .
attids	<code>character()</code> . A character vector of DexiAttribute IDs to be included in the result. Default: all <code>model</code> attributes.
aggregate	One of "minmax", "min", "max", "mean" or "none". Determines how to aggregate alternatives values that are represented by sets or distributions.
name	<code>character(1)</code> , The name of the column in <code>alternatives</code> that contains alternatives' names. Default: "name".
shift	<code>numeric(1)</code> . Used to "shift" numeric results by a small amount to avoid overlapping lines in charts. Default: 0.01. You may want to experiment with charts to determine the right value,
linewidth	<code>numeric(1)</code> . Widths of lines drawn.
pointsize	<code>numeric(1)</code> . Size of points drawn.
split	One of: "no" Draw all alternatives on the same chart. "v" Split the chart vertically and draw alternatives separately. "h" Split the chart horizontally and draw alternatives separately.

Details

Data presented in the chart is prepared by [scale_alternatives\(\)](#). `plotalt_parallel()` invokes [ggplot_parallel\(\)](#) to make a basic chart and then enhances it with graphic layers that are suitable for presenting DEXi alternatives.

Value

A 'ggplot2' chart, enhanced with additional graph layers.

See Also

[scale_alternatives\(\)](#), [ggplot_parallel\(\)](#)

Examples

```

if (requireNamespace("GGally", quietly = TRUE)) {

# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Plot all Car$alternatives with points and lines
plotalt_parallel(Car)

# Show alternatives on two separate chart segments, shown one above the other.
plotalt_parallel(Car, split = "v")

alts3 <- structure(
list(
  name = c("MyCar", "MyCar2", "MyCar1b"),
  CAR.1 = list(4L, 4L, c(1L, 4L)),
  PRICE = list(3L, 3L, c(1L, 3L)),
  BUY.PRICE = list(3L, 3L, 3L),
  MAINT.PRICE = list(2, 1, structure(c(0.1, 0.6, 0.3), class = "distribution")),
  TECH.CHAR. = list(3L, 3:4, 3L),
  COMFORT = list(3L, 2, 3L),
  X.PERS = list(3, 3, 3L),
  X.DOORS = list(3, 3, 3L),
  LUGGAGE = list(2L, 2L, 2),
  SAFETY = list(2, c(2, 3), 2)
),
  row.names = c(NA, -3L),
  class = "data.frame"
)

# Plot `alts2` with points and lines.
# Notice the "minmax" aggregation of sets and distributions.
plotalt_parallel(Car, alts3)
plotalt_parallel(Car, alts3, split = "v")

# Now with "mean" aggregation
plotalt_parallel(Car, alts3, split = "v", aggregate = "mean")
}

```

plotalt_radar

plotalt_radar

Description

Plots DEXi alternatives on a radar chart. Generally, axes are uniformly scaled to the $[0, 1]$ interval.

Usage

```

plotalt_radar(
  model,
  alternatives = NULL,
  attids = NULL,
  aggregate = c("minmax", "min", "max", "mean", "none"),
  name = "name",
  shift = 0.01,
  linewidth = 2,
  ptype = 16,
  colors = NULL,
  unicolors = NULL,
  fillcolors = NULL,
  transparency = 85,
  circular = FALSE,
  split = FALSE,
  fill = FALSE,
  ...
)

```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to <code>model\$alternatives</code> . The default value NULL selects the whole <code>model\$alternatives</code> .
attids	<code>character()</code> . A character vector of DexiAttribute IDs to be included in the result. Default: all <code>model</code> attributes.
aggregate	One of "minmax", "min", "max", "mean" or "none". Determines how to aggregate alternatives values that are represented by sets or distributions.
name	<code>character(1)</code> , The name of the column in <code>alternatives</code> that contains alternatives' names. Default: "name".
shift	<code>numeric(1)</code> . Used to "shift" numeric values by a small amount to avoid overlapping lines in charts. Default: 0.01. You may want to experiment with charts to determine the right value,
linewidth	<code>numeric(1)</code> . Widths of lines drawn.
ptype	A vector to specify point symbol: Default 16 (closed circle). Should be 32 to not plot the points. This vector is repeatedly used for data series.
colors	Colors to be used (repeatably) for data series. Default 1:8.
unicolors	A vector of one or two colors to be used for displaying the minimum and maximum data series, respectively. Applies only when <code>split = TRUE</code> .
fillcolors	A vector of color codes for filling polygons. Applies only when <code>fill = TRUE</code> .
transparency	A number between 0 and 100 representing the transparency of colors used for filling polygons.
circular	<code>logical(1)</code> . Whether to make a circular (using fmsb::radarchartcirc()) or polygonal (fmsb::radarchart()) radar grid.

split	logical(1). Whether to plot all alternatives on a single chart (FALSE, default) or make a series of plots of individual alternatives (TRUE).
fill	logical(1). Whether or not to fill polygons using fillcolors.
...	Optional parameters passed to <code>fmsb::radarchart()</code> .

Details

Uses `fmsb::radarchart()` and requires package "fmsb" to be installed. Data presented in the chart is prepared by `scale_alternatives()`.

Value

Draws a chart or, when `split = TRUE` a series of charts corresponding to individual alternatives.

See Also

[scale_alternatives\(\)](#), [fmsb::radarchart\(\)](#)

Examples

```
if (requireNamespace("fmsb", quietly = TRUE)) {

# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Plot all Car$alternatives with points and lines
plotalt_radar(Car)

# Use different colors and fill polygons
plotalt_radar(Car, colors = c("blue", "brown"), fill = TRUE)
plotalt_radar(Car, colors = c("blue", "brown"), fillcolors = c("green", "red"), fill = TRUE)

# Draw separate charts
plotalt_radar(Car, split = TRUE)

# Draw separate charts, using the same color settings on all charts
plotalt_radar(Car, split = TRUE, unicolors = c("green", "red"))
plotalt_radar(Car, split = TRUE, unicolors = c("green", "red"), circular = TRUE)

alts3 <- structure(
list(
name = c("MyCar", "MyCar2", "MyCar1b"),
CAR.1 = list(4L, 4L, c(1L, 4L)),
PRICE = list(3L, 3L, c(1L, 3L)),
BUY.PRICE = list(3L, 3L, 3L),
MAINT.PRICE = list(2, 1, structure(c(0.1, 0.6, 0.3), class = "distribution")),
TECH.CHAR. = list(3L, 3:4, 3L),
COMFORT = list(3L, 2, 3L),
X.PERS = list(3, 3, 3L),
X.DOORS = list(3, 3, 3L),
```

```

    LUGGAGE = list(2L, 2L, 2),
    SAFETY = list(2, c(2, 3), 2)
  ),
  row.names = c(NA, -3L),
  class = "data.frame"
)

# The same chart types as above, but using more varied alternatives data
# Plot all Car$alternatives with points and lines
plotalt_radar(Car, alts3)

# Use different colors and fill polygons
plotalt_radar(Car, alts3, colors = c("blue", "brown", "purple"), fill = TRUE)
plotalt_radar(Car, alts3, colors = c("blue", "brown", "purple"),
  fillcolors = c("green", "red", "yellow"), fill = TRUE)

# Draw separate charts
plotalt_radar(Car, alts3, split = TRUE)
plotalt_radar(Car, alts3, split = TRUE, fill = TRUE)

# Draw separate charts, using the same color settings on all charts
plotalt_radar(Car, alts3, split = TRUE, unicolors = c("red", "green"))
plotalt_radar(Car, alts3, split = TRUE, unicolors = c("green", "darkgreen"), fill = TRUE)
plotalt_radar(Car, alts3, split = TRUE, unicolors = c("red", "green"), circular = TRUE)
}

```

plus_minus

plus_minus

Description

Plus-Minus Analysis: Investigate the effects of changing single attributes values on the evaluation of alternative. The values of discrete basic attributes ("input attributes") are changed, one attribute at a time, by a particular number of steps downwards (minus) and upwards (plus), while observing the changes of the target attribute values.

Usage

```

plus_minus(
  model,
  alternative,
  target = model$first(),
  minus = .Machine$integer.max,
  plus = .Machine$integer.max,
  print = TRUE,
  as_character = FALSE,
  round = NULL,
  id = NULL,

```

```

    evaluate = FALSE,
    ...
  )

```

Arguments

model	A DexiModel object.
alternative	Either a <code>data.frame</code> representing a single alternative or an index to <code>model\$alternatives</code> .
target	The attribute on which effects are observed. Default: <code>model\$first()</code> .
minus	The maximum number of downward steps to be made for each input attribute. Default: <code>.Machine\$integer.max</code> . The actual minus value is further determined with respect to alternative values and involved attributes' scales.
plus	The maximum number of upward steps to be made for each input attribute. Default: <code>.Machine\$integer.max</code> . The actual plus value is further determined with respect to alternative values and involved attributes' scales.
print	<code>logical(1)</code> . When TRUE, pretty print (left justify) the results.
as_character	<code>logical(1)</code> . Whether to represent alternative values numerically (FALSE) or using text (TRUE).
round	An integer number, argument to value_text() .
id	<code>character(1)</code> . Determines the contents of the first or first two columns of the resulting <code>data.frames</code> : "id" Attribute ID. "structure" Attribute <code>\$structure() + \$name</code> . anything else Equivalent to both "id" and "structure".
evaluate	<code>logical(1)</code> . Whether or not to evaluate alternative beforehand.
...	Optional parameters for evaluate() .

Value

A data frame consisting of columns:

`id` IDs of input attributes (unless excluded by the `id` argument).

`structure` Structure and names of input attributes (unless excluded by the `id` argument).

'For -minus to -1 Evaluation value of `target` when decreasing the corresponding attribute value by the corresponding number of steps.

`target$id` Original alternative value assigned to the corresponding attribute `id`.

For 1 to plus Evaluation value of `target` when increasing the corresponding attribute value by the corresponding number of steps.

Special values "[" and "]" denote that it is not possible to decrease of increase, respectively, the corresponding attributes value further.

See Also

[evaluate\(\)](#), [value_text\(\)](#)

Examples

```

# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE="*", X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=c(1, 3))
alte <- Car$evaluate(alt)

# Default plus-minus analysis, evaluating `alt`.
plus_minus(Car, alt, evaluate = TRUE)

# Plus-minus analysis of `alte`, using character strings,
# no pretty-printing and excluding structure info.
plus_minus(Car, alte, as_character=TRUE, print=FALSE, id = "id")

# Plus-minus analysis on `target="PRICE"`, using character strings.
plus_minus(Car, alt, target="PRICE", as_character=TRUE, evaluate=TRUE)

```

plus_minus_setup	<i>plus_minus_setup</i>
------------------	-------------------------

Description

A helper function: Initializes a data frame for `plus_minus()`.

Usage

```
plus_minus_setup(evaluated, attributes, minus, plus)
```

Arguments

evaluated	An evaluated alternative.
attributes	Vector of <code>DexiAttribute</code> objects involved in plus-minus analysis.
minus	A single integer: Maximum steps down.
plus	A single integer: Maximum steps up.

Value

A data frame consisting of columns:

- "id" Attribute IDs.
- "structure" Attribute `$structure()` + `$name`.
- counts Attributes' scale sizes.
- low_bounds Low bounds of attributes' values.
- high_bounds High bounds of attributes' values.

low_diff Maximum possible value decrease given low_bound and attribute scale.
 high_diff Maximum possible value increase given high_bound and attribute scale.
 evals Alternative evaluation for the corresponding attribute (from evaluated).
 sets evals represented as value sets.

See Also

[plus_minus\(\)](#)

print_selective_explanation
print_selective_explanation

Description

A helper function for [selective_explanation\(\)](#): Pretty-prints its results.

Usage

print_selective_explanation(explanation)

Arguments

explanation A list of lists, containing selective explanation results produced by [selective_explanation\(\)](#).

Value

NULL. Pretty-prints the contents of explanation.

read_dexi *read_dexi*

Description

read_dexi() reads a definition of a DEXi model from a .dexi file or XML string.

Usage

read_dexi(dxi)

Arguments

dxi character(1). A .dexi file name or XML string.

Value

A [DexiModel](#) RC object.

See Also

[DexiModel](#)

Examples

```
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)
```

reverse_value

reverse_value

Description

Numeric value(s) x are assumed to lie within the $[lb:hb]$ interval. The function "reverses" x linearly so that $x = lb$ maps to hb and $x = hb$ maps to lb . In DEXiR, this function is used to reverse values defined on a [DexiScale](#) from "ascending" to "descending" order or vice versa.

Usage

```
reverse_value(x, lb, hb)
```

Arguments

<code>x</code>	<code>numeric()</code> . Value(s) to be reversed.
<code>lb</code>	<code>numeric()</code> . Lower interval bound(s).
<code>hb</code>	<code>numeric()</code> . Upper interval bound(s).

Value

`numeric()`. Reversed value.

Examples

```
reverse_value(1, 1, 5) # 5
reverse_value(3, 1, 5) # 3
reverse_value(5, 1, 5) # 1
reverse_value(c(1, 3, 5), 1, 5) # c(5, 3, 1)
```

rule_value

rule_value

Description

Values of decision rules are in .dxi files encoded using character strings, where each individual character encodes some function value. The encoding is zero-based, so that "0" represents the lowest ordinal number on the corresponding discrete scale. rule_value(char) converts a single character to the corresponding ordinal value.

Usage

```
rule_value(ch)
```

Arguments

ch A single character, such as "3" or "Z".

Value

Corresponding integer value.

Examples

```
rule_value("1")  
rule_value("Z")
```

rule_values

rule_values

Description

Values of decision rules are in .dxi files encoded using character strings, where each individual character encodes some function value. The encoding is zero-based, so that the character "0" represents the lowest ordinal number on the corresponding discrete scale. Encoding of characters is according to ASCII, starting with "0". rule_values(str) converts the character string to a numeric vector of corresponding ordinal values.

Usage

```
rule_values(str, add = 0)
```

Arguments

<code>str</code>	character(1), a DEXi encoding of a vector of ordinal numbers.
<code>add</code>	An integer constant to be added to the resulting vector. The default is <code>add = 0</code> , however DEXi's ordinal numbers should normally be converted to R's using <code>add = 1</code> .

Value

A numeric vector of the same length as `str`.

Examples

```
rule_values("01122:")
rule_values("01122:", add = 1)
```

`scale_alternatives` *scale_alternatives*

Description

A helper function for preparing alternatives' data for charts that involve multiple attributes (such as [plotalt_parallel\(\)](#) and [plotalt_radar\(\)](#)). `scale_alternatives()` carries out three main operations:

1. Aggregates DEXi values, represented by sets and distributions, into single numeric values, using one of the aggregate operators: "minmax", "min", "max" or "mean",
2. scales the aggregated values to the $[\emptyset, 1]$ interval so that they can be drawn uniformly on multiple chart axes,
3. optionally "shifts" the values by a small amount to avoid overlapping chart lines.

Usage

```
scale_alternatives(  
  model,  
  alternatives = NULL,  
  attids = NULL,  
  aggregate = c("minmax", "min", "max", "mean", "none"),  
  name = "name",  
  shift = 0.01  
)
```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to model\$alternatives. The default value NULL selects the whole model\$alternatives.
attids	character() . A character vector of DexiAttribute IDs to be included in the result. Default: all model attributes.
aggregate	Determines how to aggregate DEXi values that are represented/interpreted as sets in alternatives: "min" Uses the function min() to take the minimal set element. "max" Uses the function max() to take the maximal set element. "mean" Uses the function mean() to take the average set value. "minmax" (default) Takes both "min" and "max", so that each alternative appears in the result twice. "none" No aggregation. Any distributions that appear in alternatives are interpreted as sets prior to aggregation. The default operator "minmax" is suitable particularly for alternatives containing non-single-values (sets and/or distributions). For alternatives containing only single numeric values, any of the other three operators is preferred.
name	character(1) , The name of the column in alternatives that contains alternatives' names. Default: "name".
shift	numeric(1) . Used to "shift" numerical values by a small amount to avoid overlapping lines in charts. Default: 0.01.

Value

A list containing the elements:

data A data frame containing the aggregated/scaled/shifted numeric values.

nalt The number of alternatives. Notice that with aggregate = "minmax", data contains twice as many rows.

groups A numeric vector mapping data rows to alternatives' indices.

altnames Names of alternatives.

See Also

[plotalt_parallel\(\)](#), [plotalt_radar\(\)](#)

scale_of	<i>scale_of</i>
----------	-----------------

Description

scale_of

Usage

scale_of(obj)

Arguments

obj A [DexiAttribute](#) or [DexiScale](#).

Value

A [DexiScale](#) associated with obj, or NA for an undefined scale.

scale_value	<i>scale_value</i>
-------------	--------------------

Description

Check and interpret value on scale.

Usage

scale_value(value, scale)

Arguments

value A wide range of possible value types, including integer, double, character and list vectors.

scale A [DexiScale](#) or derived object.

Value

The result is produced depending on value and scale according to the following tables. For any scale type:

value	result
NULL	NULL
length(value == 0)	NULL
NA	scale\$full_range()
other types	ERROR
value contains any NULL or NA	ERROR

For continuous scales:

value	result
length(value != 1)	ERROR
character	ERROR
named object	ERROR
length(value == 1)	unclass(value)

For discrete scales:

value	result
distribution class	value
all-integer numeric vector	value
non all-integer numeric vector	distribution(value)
"*" or "undef"...	scale\$full_range()
list of value names	matched value set
list of name=p	distribution(value)

Examples

```
# Examples of successfully checked (without error) values on a continuous scale
scl <- DexiContinuousScale()
scale_value(NULL, scl)           # NA
scale_value(c(), scl)           # NA
scale_value(list(), scl)        # NA
scale_value(character(), scl)   # NA
scale_value(NA, scl)           # NA
scale_value(c(NA), scl)        # NA
scale_value(15.5, scl)         # 15.5
scale_value(distribution(15.5), scl) # 15.5

# Examples of successfully checked (without error) values on a discrete scale
scl <- DexiDiscreteScale(values = c("low", "med", "high"))
scale_value(NULL, scl)         # NA
scale_value(c(), scl)         # NA
scale_value(list(), scl)      # NA
scale_value(NA, scl)         # NA
```

```

scale_value("*", scl)           # 1:3
scale_value("Undefined", scl)  # 1:3
scale_value(2, scl)            # 2
scale_value(c(-1, 2, 4), scl)  # c(-1, 2, 4))
scale_value(distribution(c(-1, 2, 4)), scl) # distribution(c(-1, 2, 4))
scale_value(c(-1, 2.2, 4), scl) # distribution(c(-1, 2.2, 4))
scale_value("high", scl)      # 3
scale_value(c("low", "high"), scl) # c(1,3))
v <- c(0.5, 0.4)
names(v) <- c("low", "high")
scale_value(v, scl)           # distribution(c(0.5, 0, 0.4))
scale_value(list(high = 1.1, low = 2.2), scl) # distribution(c(2.2, 0, 1.1))

```

scale_values

scale_values

Description

A vectorized version of `scale_value`.

Usage

```
scale_values(values, scale)
```

Arguments

`values` A list of values. For possible value types, see `scale_value()`.

`scale` A `DexiScale` or derived object.

Value

A list determined as `lapply(values, function (v) scale_value(v, scale))`.

See Also

[scale_value\(\)](#)

 selective_explanation *selective_explanation*

Description

Selective Explanation: Displays subtrees of alternatives' values in which values are particularly weak (value quality is "bad") and particularly strong (value quality is "good").

Usage

```
selective_explanation(
  model,
  alternatives = NULL,
  print = TRUE,
  as_character = FALSE,
  round = NULL,
  id = NULL,
  evaluate = FALSE,
  ...
)
```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives or indices to model\$alternatives. The default value NULL selects model\$alternatives.
print	logical(1). When TRUE, pretty print (add headings and left justify) the results, using print_selective_explanation() .
as_character	logical(1). Whether to represent alternative values numerically (FALSE) or using text (TRUE).
round	An integer number, argument to value_text() .
id	character(1). Determines the contents of the first or first two columns of the resulting data.frames: "id" Attribute IDs. "structure" Attribute \$structure() + \$name. anything else Equivalent to both "id" and "structure".
evaluate	logical(1). Whether or not to evaluate alternatives beforehand.
...	Optional parameters for evaluate() .

Value

A list of lists: For each alternative contains a list of two data.frames, corresponding to "bad" and "good" qualities, respectively. May be pretty-printed using [print_selective_explanation\(\)](#).

See Also

[value_qualities\(\)](#), [value_text\(\)](#), [print_selective_explanation\(\)](#), [evaluate\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Print selective explanation of two Car$alternatives.
selective_explanation(Car)

alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE="*", X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=c(1, 3))
alte <- Car$evaluate(alt)

# Print selective explanation of `alte`.
selective_explanation(Car, alte)

# Print selective explanation of both `alt` and `alte`.
selective_explanation(Car, rbind.data.frame(alt, alte))
```

select_quality

select_quality

Description

Select from alt only those attributes whose values have the given quality. Used primarily in `selective_explanation()`.

Usage

```
select_quality(model, alt, quality)
```

Arguments

model	A DexiModel object.
alt	data.frame. A single DEXi alternative.
quality	Requested EnumQuality: "bad", "good" or "none".

Value

alt containing only values that have the requested quality.

See Also

[value_qualities\(\)](#), [selective_explanation\(\)](#)

Examples

```

# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

alt <- Car$alternative("MyCar",
  BUY.PRICE="low", MAINT.PRICE="*", X.PERS="more", X.DOORS="4", LUGGAGE=2, SAFETY=c(1, 3))
alte <- Car$evaluate(alt)
alts <- select_quality(Car, alte, "bad")
names(alts)
# c("CAR", "PRICE", "MAINT.PRICE", "TECH.CHAR.", "SAFETY")
alts <- select_quality(Car, alte, "none")
names(alts)
# c("MAINT.PRICE", "X.DOORS", "LUGGAGE")
alts <- select_quality(Car, alte, "good")
names(alts)
# c("CAR", "PRICE", "BUY.PRICE", "MAINT.PRICE", "TECH.CHAR.", "COMFORT", "X.PERS", "SAFETY")

```

set_alternative	<i>set_alternative</i>
-----------------	------------------------

Description

Set values of a single decision alternative and represent it with a data frame. Usually, only input values are set in this way. The data frame can then be [evaluated](#) to set the values of output attributes.

Usage

```
set_alternative(model, alternative, ...)
```

Arguments

model	A DexiModel object. Required.
alternative	character(1) or data.frame. The first form sets the name of the newly created decision alternative. The second form copies values from alternative[1,] to initialize the corresponding columns of the resulting data frame.
...	<p>A list of parameters specifying the values of the newly created decision alternative. Each parameter is expected to be in the form attribute_id=attribute_value, or is a list of elements of the same form.</p> <p>There are several possible ways to specify attribute_value. Taking the scale CAR = {"unacc"; "acc"; "good"; "exc"} as an example, the options are:</p> <p>CAR="unacc" A single qualitative value.</p> <p>CAR=2 An ordinal number, indicating "acc" in this case.</p> <p>CAR=c("good", "exc") A set of qualitative values.</p> <p>CAR=c(3, 4) A set of ordinal numbers, equivalent to the above.</p> <p>CAR=list("good", 4) A set specified by a mixture of qualitative values and ordinal numbers.</p>

CAR="*" A full range of ordinal numbers, in this case equivalent to 1:4.
 CAR=distribution(0, 0, 0.7, 0.3) A value distribution.
 CAR=list("good"=0.7, "exc"=0.3) A value distribution, equivalent to the above.
 CAR="undef" An unknown value, interpreted as NA.

For attributes associated with continuous scales, only `numeric(1)` `attribute_values` are allowed.

Value

A one-row data frame with columns corresponding to model's attributes, collectively representing a single decision alternative. The columns not copied from `alternative` (as a data frame) nor set by any parameter contain NAs.

See Also

[DEXiR-package](#) notes on values in DEXi models.

set_to_distr

set_to_distr

Description

Convert a DEXi value set to DEXi value distribution.

Usage

```
set_to_distr(set, length = 0)
```

Arguments

set	Normally a numeric vector containing integer numbers.
length	The required length of the resulting distribution vector. The actual length is determined as <code>max(length, max(set))</code> , so the length is extended when too small to hold the whole distribution.

Value

A [distribution](#) object of length `length`. Arguments that are already distributions are returned "as is". Input vectors of length 0 and other types of objects return NA.

See Also

[DEXiR-package](#), [distribution](#), [distr_to_set\(\)](#)

Examples

```
set_to_distr(c(1, 3, 4))
set_to_distr(c(1, 3, 4), length = 5)
set_to_distr(c(1, 3, 4), length = 0)
```

transparent_colors	<i>transparent_colors</i>
--------------------	---------------------------

Description

A helper function for making colors transparent.

Usage

```
transparent_colors(colors, percent = 50)
```

Arguments

colors	A vector of color numbers or names.
percent	Required color transparency, in the range [0:100].

Details

Requires installed package "grDevices".

Value

A vector of colors of the same length as colors.

Examples

```
transparent_colors(c("red", "green", "blue"), 50)
# c("#FF00007F", "#00FF007F", "#0000FF7F")
```

unique_names	<i>unique_names</i>
--------------	---------------------

Description

Convert names strings to ID strings that are unique and conformant with R's syntactic rules for variable names.

Usage

```
unique_names(names, reserved = c())
```

Arguments

names	character(). Names to be converted to IDs.
reserved	character(). Reserved names that should not be used as IDs.

Value

character().

See Also

[base::make.unique\(\)](#)

values_to_str	<i>values_to_str</i>
---------------	----------------------

Description

Convert numbers to a DEXi string. Implements the reverse operation of [rule_values\(\)](#).

Usage

```
values_to_str(vals, add = 0)
```

Arguments

vals	Numeric vector, containing ordinal values.
add	An integer constant to be added to vals prior to conversion.

Value

A string representing DEXi's representation of ordinal values. Fails when vals + add contains negative numbers.

Examples

```
values_to_str(c(0, 1, 1, 2, 2, 10, 12))
values_to_str(c(1, 2, 2, 3, 3, 11, 13), -1)
```

value_qualities	<i>value_qualities</i>
-----------------	------------------------

Description

Returns a vector of qualities corresponding to consecutive elements of `value`. In contrast with `DexiScale$value_quality(value)`, which can handle only single values, this function can handle `value` arguments that contain multiple elements, such as value sets and distributions.

Usage

```
value_qualities(value, scale)
```

Arguments

<code>value</code>	A DEXi value, internal representation: numeric value or vector, or distribution .
<code>scale</code>	A DexiScale or derived object.

Value

A vector consisting of `EnumQuality` elements corresponding to individual value elements.

Examples

```
scl <- DexiDiscreteScale(values = c("low", "med", "high"))
value_qualities(1, scl)      # "bad"
value_qualities(1:3, scl)   # c("bad", "none", "good")
value_qualities(c(3, 2), scl) # c("good", "none")
```

value_text	<i>value_text</i>
------------	-------------------

Description

Converts a DEXi value to a human-readable character string that can be printed. Used, for instance, by `DexiModel$as_character()`.

Usage

```
value_text(value, scale, round = NULL)
```

Arguments

value	Any DEXi value type (see DEXiR-package).
scale	A DexiScale or derived object.
round	An integer number. Indicates the number of decimals for rounding numeric values prior to printing. If NULL, no rounding takes place.

Value

character.

Examples

```
scl <- DexiDiscreteScale(values = c("low", "med", "high"))
value_text(NA, scl)
value_text(1, scl)
value_text(c(1, 3), scl)
value_text(distribution(0.1, 0.2, 0.3), scl)
```

value_to_set

value_to_set

Description

value_to_set

Usage

```
value_to_set(value, scale)
```

Arguments

value	A DEXi value, internal representation: numeric value or vector, or distribution .
scale	A DexiScale or derived object.

Value

An integer vector or NA for: non-discrete scale, NA/NULL value(s), non-integer value(s).

Examples

```
scl <- DexiDiscreteScale(values = c("low", "med", "high"))
value_to_set(1, scl) # 1
value_to_set(1:2, scl) # c(1, 2)
value_to_set(c(1,3), scl) # c(1, 3)
value_to_set(distribution(1, 0, 0.5), scl) # c(1, 3)
```

write_alternatives *write_alternatives*

Description

Write out alternatives' data. First convert DEXi alternatives to a data frame using [export_alternatives\(\)](#) and then write it to a file.

Usage

```
write_alternatives(  
  model,  
  alternatives = NULL,  
  file = "",  
  quote = FALSE,  
  format = c("tab", "csv", "csv2"),  
  ...  
)
```

Arguments

model	A DexiModel object. Required.
alternatives	A data.frame of alternatives (normally an output of evaluate()) or indices to <code>model\$alternatives</code> . The default value NULL selects <code>model\$alternatives</code> .
file	Write the data frame contents to a file. When <code>file = ""</code> , the contents is written to the console (default). <code>file = "clipboard"</code> might also work to copy the contents to the clipboard.
quote	<code>logical(1)</code> . Whether or not to quote output character strings.
format	One of "tab", "csv" or "csv2" to invoke write.table() , write.csv() or write.csv2() , respectively.
...	Optional parameters to write.table() functions.

Value

Writes a "tab"- or "csv"-formatted alternatives' data to a file, console or clipboard. This data is meant to be subsequently imported to 'DEXi' software.

See Also

[export_alternatives\(\)](#), [write.table\(\)](#)

Examples

```
# Load "Car.dxi"
CarDxi <- system.file("extdata", "Car.dxi", package = "DEXiR")
Car <- read_dexi(CarDxi)

# Write both Car alternatives to console
write_alternatives(Car, file = "")
```

Index

alt_values, 11
and_function, 12
and_function(), 46, 50, 62
as.character(), 53
att_names, 13
attribute_effect, 12

base::make.unique(), 86
base::plot, 63
bounded_scale_value, 14
bounded_scale_value(), 46

c(), 53
compare_alternatives, 5, 7, 15, 34
compare_two_alternatives, 17
compare_two_alternatives(), 15, 16
compare_values, 18
compare_values(), 19, 20
compare_values_by_preference, 19
compare_values_by_preference(), 20
compare_values_on_scale, 20
compare_values_on_scale(), 17
convert_alternatives, 21, 34
convert_data_continuous, 23
convert_data_continuous(), 22, 23
convert_data_discrete, 24
convert_data_discrete(), 22, 23

default_quality, 26
dexi_bool, 39
dexi_index, 39
dexi_index(), 38, 41
dexi_option_value, 40
dexi_option_value(), 42
dexi_table, 41
dexi_table(), 38
dexi_value, 42
dexi_value(), 40
dexi_vector, 43

DexiAttribute, 9, 11, 13, 15, 17, 23–25, 27, 31, 33, 34, 36, 38, 45–47, 49, 54, 63–66, 68, 72, 77, 78
DexiAttribute (DexiAttribute-class), 26
DexiAttribute-class, 26
DexiContinuousScale, 9, 23, 31, 36
DexiContinuousScale (DexiContinuousScale-class), 28
DexiContinuousScale-class, 28
DexiDiscreteScale, 9, 25, 26, 31, 36
DexiDiscreteScale (DexiDiscreteScale-class), 29
DexiDiscreteScale-class, 29
DexiDiscretizeFunction, 33
DexiDiscretizeFunction (DexiDiscretizeFunction-class), 31
DexiDiscretizeFunction-class, 31
DexiFunction, 9, 26, 27, 31, 32, 37
DexiFunction (DexiFunction-class), 32
DexiFunction-class, 32
DexiModel, 13, 15, 21, 27, 46–48, 52, 54, 63, 64, 66, 68, 71, 74, 77, 81–83, 89
DexiModel (DexiModel-class), 33
DexiModel-class, 33
DEXiR (DEXiR-package), 4
DEXiR-package, 4, 23, 40, 42, 44, 45, 84, 88
DexiScale, 9, 14, 21, 26, 27, 29, 35, 36, 45, 51, 55, 56, 74, 78, 80, 87, 88
DexiScale (DexiScale-class), 36
DexiScale-class, 36
DexiTabularFunction, 33
DexiTabularFunction (DexiTabularFunction-class), 37
DexiTabularFunction-class, 37
distr_to_set, 44
distr_to_set(), 44, 84
distribution, 9, 21, 42, 43, 44, 51, 84, 87, 88
distribution(), 18, 20

- equal_scales, 45
- evaluate, 5, 12, 34, 35, 45, 50, 60, 62, 83
- evaluate(), 9, 12, 16, 21, 22, 45–50, 52, 54, 59, 62, 63, 65, 66, 68, 71, 77, 81, 82, 89
- evaluate_attribute, 47
- evaluate_attribute(), 13, 48
- evaluate_attributes, 48
- evaluation_order, 49
- evaluation_order(), 45
- evaluation_parameters, 50
- evaluation_parameters(), 46
- expand_value_to_points, 51
- export_alternatives, 52
- export_alternatives(), 89
- export_dexi_value, 53

- flat_text, 53
- fmsb::radarchart(), 68, 69
- fmsb::radarchartcirc(), 68

- GGally::ggparcoord(), 54
- ggplot_parallel, 54
- ggplot_parallel(), 66
- graphics::par(), 63, 65
- graphics::plot(), 63, 65
- graphics::points(), 63, 65
- graphics::text(), 65

- has_bad, 55
- has_good, 55
- has_none, 56
- has_quality, 56

- is_distribution, 57
- is_in_range, 57

- lin_map, 58
- lin_map(), 23–25

- make.unique, 33
- make_args, 59
- make_args(), 38
- max, 62
- max(), 22, 77
- mean(), 22, 77
- min, 12
- min(), 22, 25, 77

- norm_max, 60
- norm_max(), 46, 50, 60–62
- norm_none, 61
- norm_none(), 46, 50, 60, 62
- norm_sum, 61
- norm_sum(), 46, 50, 60, 61
- normalize_function, 59
- normalize_function(), 46, 50

- or_function, 62
- or_function(), 12, 46, 50

- plotalt1, 8, 63
- plotalt2, 8, 64
- plotalt_parallel, 8, 65
- plotalt_parallel(), 54, 55, 76, 77
- plotalt_radar, 8, 67
- plotalt_radar(), 76, 77
- plus_minus, 5, 7, 35, 70
- plus_minus(), 72, 73
- plus_minus_setup, 72
- print_selective_explanation, 73
- print_selective_explanation(), 81, 82
- prod, 12

- read_dexi, 5, 73
- read_dexi(), 35
- reverse_value, 74
- reverse_value(), 23–25
- rule_value, 75
- rule_value(), 40
- rule_values, 75
- rule_values(), 86

- scale_alternatives, 76
- scale_alternatives(), 23, 54, 55, 66, 69
- scale_of, 78
- scale_value, 78
- scale_value(), 14, 80
- scale_values, 80
- select_quality, 82
- selective_explanation, 5, 7, 35, 81
- selective_explanation(), 73, 82
- set_alternative, 5, 34, 35, 83
- set_alternative(), 9, 10
- set_to_distr, 84
- set_to_distr(), 44
- sum, 62

- transparent_colors, 85

unique_names, 86

value_qualities, 87
value_qualities(), 82
value_text, 87
value_text(), 11, 15, 71, 81, 82
value_to_set, 88
values_to_str, 86

write.csv(), 89
write.csv2(), 89
write.table(), 89
write_alternatives, 89
write_alternatives(), 52