Package: DecorateR (via r-universe)

October 24, 2026

Type Package

Title Fit and Deploy DECORATE Trees

Version 0.1.2

Imports RWeka, RWekajars, rJava, stats

Author Matthias Bogaert

Maintainer Matthias Bogaert <Matthias.Bogaert@UGent.Be>

Description DECORATE (Diverse Ensemble Creation by Oppositional Relabeling of Artificial Training Examples) builds an ensemble of J48 trees by recursively adding artificial samples of the training data (``Melville, P., & Mooney, R. J. (2005) <DOI:10.1016/j.inffus.2004.04.001>'').

License GPL (>= 2)

Depends R(>= 2.10.0)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

Repository https://cran.r-universe.dev

Date/Publication 2020-11-20 10:20:02 UTC

RemoteUrl https://github.com/cran/DecorateR

RemoteRef HEAD

RemoteSha 0e98858afd9af7238001110abe1d52bf89e1d7ee

Contents

DECORATE 2
predict.DECORATE 3

Index **4**

DECORATE *Binary classification with DECORATE (Melville and Mooney, 2005)*

Description

DECORATE (Diverse Ensemble Creation by Oppositional Relabeling of Artificial Training Examples) builds an ensemble of J48 trees by recursively adding artificial samples of the training data.

Usage

```
DECORATE(x, y, C = 15, I = 50, R = 1, verbose = FALSE)
```

Arguments

x	a data frame of predictor (numeric, integer or factors). Character variables should be transformed to factors.
y	a vector of response labels. Only {0, 1} is allowed.
C	the desired ensemble size. Set to 15 as recommended by Melville and Mooney (2005).
I	the maximum number of iterations. Set to 50 as recommended by Melville and Mooney (2005).
R	the amount of articially generated examples, expressed as a fraction of the number of training examples. R is set to 1, meaning that the number of artificially created samples is equal to the training set size.
verbose	TRUE or FALSE. Should information be printed on the screen?

Value

an object of class DECORATE.

Author(s)

Authors: Matthias Bogaert, Maintainer: <Matthias.Bogaert@UGent.Be>

References

Melville, P., & Mooney, R. J. (2005). Creating diversity in ensembles using artificial data. Information Fusion, 6(1), 99-111. <doi: 10.1016/j.inffus.2004.04.001>

See Also

predict.DECORATE

Examples

```
data(iris)
y <- as.factor(ifelse(iris$Species[1:100]=="setosa",0,1))
x <- iris[1:100,-5]
dec <- DECORATE(x = x, y = y)
```

---

predict.DECORATE *Predict method for DECORATE objects*

Description

Prediction of new data using DECORATE

Usage

```
## S3 method for class 'DECORATE'
predict(object, newdata, type = "prob", all = FALSE, ...)
```

Arguments

object	an object of the class DECORATE, as created by the function DECORATE.
newdata	a data frame containing the same predictors as in the training phase.
type	character specifying whether to return the probabilites ('prob') or class ('class'). Default: prob.
all	Return the predictions per tree instead of the average (default = FALSE).
...	Not used currently.

Value

vector containing the response probabilities.

Examples

```
data(iris)
y <- as.factor(ifelse(iris$Species[1:100]=="setosa",0,1))
x <- iris[1:100,-5]
dec <- DECORATE(x = x, y = y)
predict(object=dec,newdata=x)
```

Index

DECORATE, 2

predict.DECORATE, *2*, 3