

Package: ErlangC (via r-universe)

December 6, 2024

Type Package

Title Solve Erlang-C Model

Version 0.1.0

Maintainer Damonsoul <chenmaowei96@gmail.com>

Description Provides a set of functions to solve Erlang-C model. The Erlang C formula was invented by the Danish Mathematician A.K. Erlang and is used to calculate the number of advisors and the service level.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports bsicons, bslib, DT, gmp, lubridate, shiny, tidyr

RoxygenNote 7.3.2

Depends R (>= 2.10)

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Damonsoul [aut, cre]

Repository CRAN

Date/Publication 2024-12-05 18:30:15 UTC

Config/pak/sysreqs libgmp3-dev make libicu-dev zlib1g-dev

Contents

calculate_agents	2
erlang_c	3
erlang_c_app	4
translations	4

Index	5
--------------	----------

calculate_agents	<i>Calculate Required Number of Agents This function calculates the required number of agents to achieve a specified service level and occupancy.</i>
------------------	---

Description

Calculate Required Number of Agents This function calculates the required number of agents to achieve a specified service level and occupancy.

Usage

```
calculate_agents(
    call_count,
    call_period,
    avg_handle_time,
    target_anser_time,
    require_service_level,
    max_occupancy,
    shrinkage,
    max_agents = NULL
)
```

Arguments

call_count	Numeric. The total number of incoming calls.
call_period	Duration. The time period over which calls are counted.
avg_handle_time	Duration. The average time taken to handle a call.
target_anser_time	Duration. The targeted time to answer a call.
require_service_level	Numeric. The required service level.
max_occupancy	Numeric. The maximum allowed occupancy level .
shrinkage	Numeric. The shrinkage factor to account for non-productive time .
max_agents	Integer. The maximum number of agents allowed.

Value

A list containing the calculated metrics and the number of agents required.

Examples

```
calculate_agents(  
  call_count = 100,  
  call_period = lubridate::duration(30, "minutes"),  
  avg_handle_time = lubridate::duration(180, "seconds"),  
  target_anser_time = lubridate::duration(20, "seconds"),  
  require_service_level = 0.8,  
  max_occupancy = 0.85,  
  shrinkage = 0.3,  
  max_agents = 200  
)
```

erlang_c

Erlang C

Description

Calculate the performance metrics of an Erlang C model with n agents.

Usage

```
erlang_c(call_count, call_period, avg_handle_time, target_anser_time, n)
```

Arguments

call_count	Numeric. The total number of incoming calls.
call_period	Duration. The time period over which calls are counted.
avg_handle_time	Duration. The average time taken to handle a call.
target_anser_time	Duration. The targeted time to answer a call.
n	Integer. The number of agents.

Value

A list containing the calculated metrics.

Examples

```
erlang_c(  
  call_count = 100,  
  call_period = lubridate::duration(30, "minutes"),  
  avg_handle_time = lubridate::duration(180, "seconds"),  
  target_anser_time = lubridate::duration(20, "seconds"),  
  n = 14  
)
```

`erlang_c_app`*Shiny App for Erlang C Calculator*

Description

This function creates a Shiny app for calculating Erlang C metrics.

Usage

```
erlang_c_app(language = "en")
```

Arguments

`language` Character. The language to use for translations (default: "en").

Value

A Shiny app object.

`translations`*Translations*

Description

This dataset contains translations for all the strings used in the app. It is used to create a Shiny string translation interface.

Usage

```
translations
```

Format

A data frame with variables:

key The key of the string to translate

en The translation in English

zh The translation in Chinese

Source

Local

Index

* **datasets**

translations, 4

calculate_agents, 2

erlang_c, 3

erlang_c_app, 4

translations, 4