Package: FSelector (via r-universe)

October 29, 2026

Type Package

Title Selecting Attributes

Version 0.34

Date 2023-08-22

Author Piotr Romanski, Lars Kotthoff, Patrick Schratz

Maintainer Lars Kotthoff <larsko@uwyo.edu>

BugReports https://github.com/larskotthoff/fselector/issues

URL https://github.com/larskotthoff/fselector

Description Functions for selecting attributes from a given dataset. Attribute subset selection is the process of identifying and removing as much of the irrelevant and redundant information as possible.

License GPL-2

Imports digest, entropy, randomForest, RWeka

Suggests mlbench, rpart

Encoding UTF-8

LazyLoad yes

NeedsCompilation no

Repository https://cran.r-universe.dev

Date/Publication 2023-08-22 18:30:40 UTC

RemoteUrl https://github.com/cran/FSelector

RemoteRef HEAD

RemoteSha 1acf016f2b5cbaf99f6418c3eb7d5734215ebcf1

Contents

FSelector-package 2
as.simple.formula 3
best.first.search 3

cfs 5
chi.squared 6
consistency 7
correlation 8
cutoff 9
entropy.based 10
exhaustive.search 11
greedy.search 12
hill.climbing.search 14
oneR 15
random.forest.importance 16
relief 17

Index **19**

`FSelector-package` *Package for selecting attributes*

Description

Package containing functions for selecting attributes from a given dataset and a destination attribute.

Details

This package contains:

- -Algorithms for filtering attributes: cfs, chi.squared, information.gain, gain.ratio, symmetrical.uncertainty, linear.correlation, rank.correlation, oneR, relief, consistency, random.forest.importance
- -Algorithms for wrapping classifiers and search attribute subset space: best.first.search, backward.search, forward.search, hill.climbing.search
- -Algorithm for choosing a subset of attributes based on attributes' weights: cutoff.k, cutoff.k.percent, cutoff.biggest.diff
- -Algorithm for creating formulas: as.simple.formula

Author(s)

Piotr Romanski
Maintainer: Lars Kotthoff <larsko@uwyo.edu>

as.simple.formula *Converting to formulas*

Description

Converts character vector of atrributes' names and destination attribute's name to a simple formula.

Usage

```
as.simple.formula(attributes, class)
```

Arguments

attributes	character vector of attributes' names
class	name of destination attribute

Value

A simple formula like "class ~ attr1 + attr2"

Author(s)

Piotr Romanski

Examples

```
data(iris)
result <- cfs(Species ~ ., iris)
f <- as.simple.formula(result, "Species")
```

best.first.search *Best-first search*

Description

The algorithm for searching atrribute subset space.

Usage

```
best.first.search(attributes, eval.fun, max.backtracks = 5)
```

Arguments

attributes	a character vector of all attributes to search in
eval.fun	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is
max.backtracks	an integer indicating a maximum allowed number of backtracks, default is 5

Details

The algorithm is similar to forward.search besides the fact that is chooses the best node from all already evaluated ones and evaluates it. The selection of the best node is repeated approximately max.backtracks times in case no better node found.

Value

A character vector of selected attributes.

Author(s)

Piotr Romanski

See Also

forward.search, backward.search, hill.climbing.search, exhaustive.search

Examples

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- best.first.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

cfs *CFS filter*

Description

The algorithm finds attribute subset using correlation and entropy measures for continous and discrete data.

Usage

```
cfs(formula, data)
```

Arguments

formula	a symbolic description of a model
data	data to process

Details

The alorithm makes use of `best.first.search` for searching the attribute subset space.

Value

a character vector containing chosen attributes

Author(s)

Piotr Romanski

See Also

`best.first.search`

Examples

```
data(iris)

subset <- cfs(Species~., iris)
f <- as.simple.formula(subset, "Species")
print(f)
```

`chi.squared` *Chi-squared filter*

Description

The algorithm finds weights of discrete attributes basing on a chi-squared test.

Usage

```
chi.squared(formula, data)
```

Arguments

`formula`	a symbolic description of a model
`data`	a symbolic description of a model

Details

The result is equal to Cramer's V coefficient between source attributes and destination attribute.

Value

a data.frame containing the worth of attributes in the first column and their names as row names

Author(s)

Piotr Romanski

Examples

```
library(mlbench)
data(HouseVotes84)

weights <- chi.squared(Class~., HouseVotes84)
print(weights)
subset <- cutoff.k(weights, 5)
f <- as.simple.formula(subset, "Class")
print(f)
```

`consistency` *Consistency-based filter*

Description

The algorithm finds attribute subset using consistency measure for continous and discrete data.

Usage

```
consistency(formula, data)
```

Arguments

`formula`	a symbolic description of a model
`data`	data to process

Details

The alorithm makes use of `best.first.search` for searching the attribute subset space.

Value

a character vector containing chosen attributes

Author(s)

Piotr Romanski

See Also

`best.first.search`

Examples

```
## Not run:
  library(mlbench)
  data(HouseVotes84)

  subset <- consistency(Class~., HouseVotes84)
  f <- as.simple.formula(subset, "Class")
  print(f)

## End(Not run)
```

`correlation` *Correlation filter*

Description

The algorithm finds weights of continous attributes basing on their correlation with continous class attribute.

Usage

```
linear.correlation(formula, data)
rank.correlation(formula, data)
```

Arguments

`formula`	a symbolic description of a model
`data`	data to process

Details

`linear.correlation` uses Pearson's correlation

`rank.correlation` uses Spearman's correlation

Rows with `NA` values are not taken into consideration.

Value

a data.frame containing the worth of attributes in the first column and their names as row names

Author(s)

Piotr Romanski

Examples

```
library(mlbench)
data(BostonHousing)
d=BostonHousing[-4] # only numeric variables

weights <- linear.correlation(medv~., d)
print(weights)
subset <- cutoff.k(weights, 3)
f <- as.simple.formula(subset, "medv")
print(f)

weights <- rank.correlation(medv~., d)
print(weights)
subset <- cutoff.k(weights, 3)
f <- as.simple.formula(subset, "medv")
print(f)
```

cutoff *Cutoffs*

Description

The algorithms select a subset from a ranked attributes.

Usage

```
cutoff.k(attrs, k)
cutoff.k.percent(attrs, k)
cutoff.biggest.diff(attrs)
```

Arguments

attrs	a data.frame containing ranks for attributes in the first column and their names as row names
k	a positive integer in case of `cutoff.k` and a numeric between 0 and 1 in case of `cutoff.k.percent`

Details

`cutoff.k` chooses k best attributes

`cutoff.k.percent` chooses best k * 100% of attributes

`cutoff.biggest.diff` chooses a subset of attributes which are significantly better than other.

Value

A character vector containing selected attributes.

Author(s)

Piotr Romanski

Examples

```
data(iris)

weights <- information.gain(Species~., iris)
print(weights)

subset <- cutoff.k(weights, 1)
f <- as.simple.formula(subset, "Species")
print(f)

subset <- cutoff.k.percent(weights, 0.75)
f <- as.simple.formula(subset, "Species")
print(f)
```

```
subset <- cutoff.biggest.diff(weights)
f <- as.simple.formula(subset, "Species")
print(f)
```

`entropy.based` *Entropy-based filters*

Description

The algorithms find weights of discrete attributes basing on their correlation with continous class attribute.

Usage

```
information.gain(formula, data, unit)
gain.ratio(formula, data, unit)
symmetrical.uncertainty(formula, data, unit)
```

Arguments

`formula`	A symbolic description of a model.
`data`	Data to process.
`unit`	Unit for computing entropy (passed to `entropy`. Default is "log".

Details

`information.gain` is

$$H(Class) + H(Attribute) - H(Class, Attribute)$$

.

`gain.ratio` is

$$\frac{H(Class) + H(Attribute) - H(Class, Attribute)}{H(Attribute)}$$

`symmetrical.uncertainty` is

$$2\frac{H(Class) + H(Attribute) - H(Class, Attribute)}{H(Attribute) + H(Class)}$$

Value

a data.frame containing the worth of attributes in the first column and their names as row names

Author(s)

Piotr Romanski, Lars Kotthoff

Examples

```
data(iris)

weights <- information.gain(Species~., iris)
print(weights)
subset <- cutoff.k(weights, 2)
f <- as.simple.formula(subset, "Species")
print(f)

weights <- information.gain(Species~., iris, unit = "log2")
print(weights)

weights <- gain.ratio(Species~., iris)
print(weights)
subset <- cutoff.k(weights, 2)
f <- as.simple.formula(subset, "Species")
print(f)

weights <- symmetrical.uncertainty(Species~., iris)
print(weights)
subset <- cutoff.biggest.diff(weights)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

exhaustive.search *Exhaustive search*

Description

The algorithm for searching atrribute subset space.

Usage

```
exhaustive.search(attributes, eval.fun)
```

Arguments

attributes	a character vector of all attributes to search in
eval.fun	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is

Details

The algorithm searches the whole attribute subset space in breadth-first order.

Value

A character vector of selected attributes.

Author(s)

Piotr Romanski

See Also

forward.search, backward.search, best.first.search, hill.climbing.search

Examples

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- exhaustive.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

greedy.search *Greedy search*

Description

The algorithms for searching atrribute subset space.

Usage

```
backward.search(attributes, eval.fun)
forward.search(attributes, eval.fun)
```

Arguments

attributes	a character vector of all attributes to search in
eval.fun	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is

Details

These algorithms implement greedy search. At first, the algorithms expand starting node, evaluate its children and choose the best one which becomes a new starting node. This process goes only in one direction. forward.search starts from an empty and backward.search from a full set of attributes.

Value

A character vector of selected attributes.

Author(s)

Piotr Romanski

See Also

best.first.search, hill.climbing.search, exhaustive.search

Examples

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- forward.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

`hill.climbing.search` *Hill climbing search*

Description

The algorithm for searching atrribute subset space.

Usage

```
hill.climbing.search(attributes, eval.fun)
```

Arguments

`attributes`	a character vector of all attributes to search in
`eval.fun`	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is

Details

The algorithm starts with a random attribute set. Then it evaluates all its neighbours and chooses the best one. It might be susceptible to local maximum.

Value

A character vector of selected attributes.

Author(s)

Piotr Romanski

See Also

`forward.search`, `backward.search`, `best.first.search`, `exhaustive.search`

Examples

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
```

```
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- hill.climbing.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

oneR *OneR algorithm*

Description

The algorithms find weights of discrete attributes basing on very simple association rules involving only one attribute in condition part.

Usage

```
oneR(formula, data)
```

Arguments

formula	a symbolic description of a model
data	data to process

Details

The algorithm uses OneR classifier to find out the attributes' weights. For each attribute it creates a simple rule based only on that attribute and then calculates its error rate.

Value

a data.frame containing the worth of attributes in the first column and their names as row names

Author(s)

Piotr Romanski

Examples

```
library(mlbench)
data(HouseVotes84)

weights <- oneR(Class~., HouseVotes84)
print(weights)
subset <- cutoff.k(weights, 5)
f <- as.simple.formula(subset, "Class")
print(f)
```

`random.forest.importance` *RandomForest filter*

Description

The algorithm finds weights of attributes using RandomForest algorithm.

Usage

```
random.forest.importance(formula, data, importance.type = 1)
```

Arguments

`formula`	a symbolic description of a model
`data`	data to process
`importance.type`	either 1 or 2, specifying the type of importance measure (1=mean decrease in accuracy, 2=mean decrease in node impurity)

Details

This is a wrapper for `importance`.

Value

a data.frame containing the worth of attributes in the first column and their names as row names

Author(s)

Piotr Romanski

Examples

```
library(mlbench)
data(HouseVotes84)

weights <- random.forest.importance(Class~., HouseVotes84, importance.type = 1)
print(weights)
subset <- cutoff.k(weights, 5)
f <- as.simple.formula(subset, "Class")
print(f)
```

---

relief *RReliefF filter*

Description

The algorithm finds weights of continous and discrete attributes basing on a distance between instances.

Usage

```
relief(formula, data, neighbours.count = 5, sample.size = 10)
```

Arguments

formula	a symbolic description of a model
data	data to process
neighbours.count	number of neighbours to find for every sampled instance
sample.size	number of instances to sample

Details

The algorithm samples instances and finds their nearest hits and misses. Considering that result, it evaluates weights of attributes.

Value

a data.frame containing the worth of attributes in the first column and their names as row names

Author(s)

Piotr Romanski

References

- -Igor Kononenko: Estimating Attributes: Analysis and Extensions of RELIEF. In: European Conference on Machine Learning, 171-182, 1994.
- -Marko Robnik-Sikonja, Igor Kononenko: An adaptation of Relief for attribute estimation in regression. In: Fourteenth International Conference on Machine Learning, 296-304, 1997.

Examples

```
data(iris)

weights <- relief(Species~., iris, neighbours.count = 5, sample.size = 20)
print(weights)
subset <- cutoff.k(weights, 2)
f <- as.simple.formula(subset, "Species")
print(f)
```

Index

∗ **package**
FSelector-package, 2

as.simple.formula, 3

backward.search, *4*, *12*, *14*
backward.search *(*greedy.search*)*, 12
best.first.search, 3, *5*, *7*, *12–14*

cfs, 5
chi.squared, 6
consistency, 7
correlation, 8
cutoff, 9

entropy, *10*
entropy.based, 10
exhaustive.search, *4*, 11, *13, 14*

forward.search, *4*, *12*, *14*
forward.search *(*greedy.search*)*, 12
FSelector *(*FSelector-package*)*, 2
FSelector-package, 2

gain.ratio *(*entropy.based*)*, 10
greedy.search, 12

hill.climbing.search, *4*, *12, 13*, 14

importance, *16*
information.gain *(*entropy.based*)*, 10

linear.correlation *(*correlation*)*, 8

oneR, 15

random.forest.importance, 16
rank.correlation *(*correlation*)*, 8
relief, 17

symmetrical.uncertainty
*(*entropy.based*)*, 10