Package: FastHamming (via r-universe)

October 20, 2026

Title Fast Computation of Pairwise Hamming Distances

Type Package

Version 1.3

Depends R (>= 4.0.0)

Description Pairwise Hamming distances are computed between the rows of a binary (0/1) matrix using highly optimized 'C' code. The input is an integer matrix where each row represents a binary feature vector and returns a symmetric integer matrix of pairwise distances. Internally, rows are bit-packed into 64-bit words for fast XOR-based comparisons, with hardware-accelerated popcount operations to count differences. 'OpenMP' parallelization ensures efficient performance for large matrices.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.3

SystemRequirements C compiler (C99), OpenMP

NeedsCompilation yes

Author Ravi Varadhan [aut, cre]

Maintainer Ravi Varadhan <ravi.varadhan@jhu.edu>

Repository https://cran.r-universe.dev

Date/Publication 2026-08-21 14:50:07 UTC

RemoteUrl https://github.com/cran/FastHamming

RemoteRef HEAD

RemoteSha eb3a49d6e9a5a304da454efa38e063e619f9e1c7

Contents

hamming_distance 2

Index **3**

`hamming_distance` *Pairwise Hamming distances*

Description

Computes the pairwise Hamming distances between rows of a binary matrix.

Usage

```
hamming_distance(X, nthreads = NULL)
```

Arguments

`X`	A binary (0/1) numeric matrix.
`nthreads`	Integer; number of OpenMP threads to use. If `NULL` (the default) use all available cores,

Value

An integer matrix of pairwise Hamming distances.

Examples

```
n <- 10000
m <- 1000
set.seed(2468)
X <- matrix(sample(0:1, n * m, replace = TRUE), nrow = n)
# Use all available threads
system.time(result <- hamming_distance(X))
# limit to 2 threads
system.time(hamming_distance(X, nthreads = 2))
```

Index

hamming_distance, 2