Package: GDINA (via r-universe)

October 7, 2026

Type Package

Title The Generalized DINA Model Framework

Version 2.13.2

Date 2026-10-04

Description A set of psychometric tools for cognitive diagnosis modeling based on the generalized deterministic inputs, noisy and gate (G-DINA) model by de la Torre (2011) <DOI:10.1007/s11336-011-9207-7> and its extensions, including the sequential G-DINA model by Ma and de la Torre (2016) <DOI:10.1111/bmsp.12070> for polytomous responses, and the polytomous G-DINA model by Chen and de la Torre <DOI:10.1177/0146621613479818> for polytomous attributes. Joint attribute distribution can be independent, saturated, higher-order, loglinear smoothed or structured. Q-matrix validation, item and model fit statistics, model comparison at test and item level and differential item functioning can also be conducted. A graphical user interface is also provided. For tutorials, please check Ma and de la Torre (2020) <DOI:10.18637/jss.v093.i14>, Ma and de la Torre (2019) <DOI:10.1111/emip.12262>, Ma (2019) <DOI:10.1007/978-3-030-05584-4_29> and de la Torre and Akbay (2019).

License GPL-3

LazyData TRUE

Depends R (>= 3.5)

Imports alabama, foreach, graphics, ggplot2, MASS, numDeriv, nloptr, Rcpp (>= 0.12.1), rlang, Rsolnp, stats, shiny, shinydashboard, utils

Suggests CDM, cdmTools, doRNG, doParallel, Matrix, testthat, poLCA, stringr, knitr, rmarkdown

LinkingTo Rcpp, RcppArmadillo

URL https://github.com/Wenchao-Ma/GDINA, https://wenchao-ma.github.io/GDINA/

BugReports https://github.com/Wenchao-Ma/GDINA/issues

Encoding UTF-8

NeedsCompilation yes

Author Wenchao Ma [aut, cre, cph], Jimmy de la Torre [aut, cph], Samuel Huang [ctb], Miguel Sorrel [ctb], Zhehan Jiang [ctb], Pablo Najera [ctb]

Maintainer Wenchao Ma <wma@umn.edu>

VignetteBuilder knitr

Collate 'CA.R' 'CM.R' 'CR.R' 'DTM.R' 'ExportedFuncs.R' 'GDINA.R' 'GDI.R' 'GDINA-package.R' 'GMSCDM.R' 'HO.R' 'ILCA.R' 'M2.R' 'MCmodel.R' 'Mstep.R' 'Mstep_DTM.R' 'MultipleGroup_Estimation.R' 'RcppExports.R' 'SingleGroup_Estimation.R' 'anova.GDINA.R' 'autoGDINA.R' 'bootSE.R' 'coef.R' 'dif.R' 'estimation_utils.R' 'simGDINA.R' 'itemfit.R' 'modelcomp.R' 'extract.R' 'itemfitPD.R' 'itemparm.GDINA.R' 'monocheck.R' 'pairwiseDIF.R' 'personparm.GDINA.R' 'plotIRF.GDINA.R' 's3GDINA.R' 'print.GDINA.R' 'realdata_ECPE.R' 'realdata_Tatsuoka1990.R' 'score.R' 'sim10GDINA.R' 'sim10MCDINA.R' 'sim10MCDINA2.R' 'sim20seqGDINA.R' 'sim21seqDINA.R' 'sim30DINA.R' 'sim30GDINA.R' 'sim30pGDINA.R' 'startGDINA.R' 'structuralparm.R' 'summary.GDINA.R' 'utils.R' 'zzz.R'

Config/roxygen2/version 8.1.0

Repository https://cran.r-universe.dev

Date/Publication 2026-10-05 22:46:05 UTC

RemoteUrl https://github.com/cran/GDINA

RemoteRef HEAD

RemoteSha 5833199ba3c72e7169eb8f1859bb8e7a91fec062

Contents

GDINA-package 4
att.structure 5
attributepattern 6
autoGDINA 7
bdiagMatrix 11
bootSE 12
CA 13
cjoint 14
ClassRate 15
CM 16
designmatrix 17
dif 18
DTM 22

extract . . . 24
GDINA . . . 26
GMSCDM . . . 47
ILCA . . . 50
indlogLik . . . 51
indlogPost . . . 51
itemfit . . . 52
itemfitPD . . . 54
itemparm . . . 56
LC2LG . . . 57
MCmodel . . . 58
modelcomp . . . 61
modelfit . . . 65
monocheck . . . 66
npar . . . 67
pairwiseDIF . . . 68
personparm . . . 70
plot.GDINA . . . 71
plot.itemfit . . . 72
plot.pairwiseDIF . . . 73
plot.Qval . . . 74
Qval . . . 75
realdata_ECPE . . . 78
realdata_Tatsuoka1990 . . . 79
rowMatch . . . 81
score . . . 81
sim10GDINA . . . 82
sim10MCDINA . . . 83
sim10MCDINA2 . . . 83
sim20seqGDINA . . . 84
sim21seqDINA . . . 85
sim30DINA . . . 85
sim30GDINA . . . 86
sim30pGDINA . . . 87
simDTM . . . 87
simGDINA . . . 88
startGDINA . . . 100
unique_only . . . 101
unrestrQ . . . 102

Index **103**

GDINA-package *The Generalized DINA Model Framework*

Description

For conducting CDM analysis within the G-DINA model framework

Details

This package (Ma & de la Torre, 2020a) provides a framework for a series of cognitively diagnostic analyses for dichotomous and polytomous responses.

Various cognitive diagnosis models (CDMs) can be calibrated using the `GDINA` function, including the G-DINA model (de la Torre, 2011), the deterministic inputs, noisy and gate (DINA; de la Torre, 2009; Junker & Sijtsma, 2001) model, the deterministic inputs, noisy or gate (DINO; Templin & Henson, 2006) model, the reduced reparametrized unified model (R-RUM; Hartz, 2002), the additive CDM (A-CDM; de la Torre, 2011), and the linear logistic model (LLM; Maris, 1999), the multiple-strategy DINA model (de la Torre, & Douglas, 2008) and models defined by users under the G-DINA framework using different link functions and design matrices (de la Torre, 2011). Note that the LLM is also called compensatory RUM and the RRUM is equivalent to the generalized NIDA model.

For ordinal and nominal responses, the sequential G-DINA model (Ma, & de la Torre, 2016) can be fitted and most of the aforementioned CDMs can be used as the processing functions (Ma, & de la Torre, 2016) at the category level. Different CDMs can be assigned to different items within a single assessment. Item parameters are estimated using the MMLE/EM algorithm. Details about the estimation algorithm can be found in Ma and de la Torre (2020). The joint attribute distribution can be modeled using an independent model, a higher-order IRT model (de la Torre, & Douglas, 2004), a loglinear model (Xu & von Davier, 2008), a saturated model or a hierarchical structures (e.g., linear, divergent). Monotonicity constraints for item/category success probabilities can also be specified.

In addition, to handle multiple strategies, generalized multiple-strategy CDMs for dichotomous response (Ma & Guo, 2019) can be fitted using `GMSCDM` function and diagnostic tree model (Ma, 2019) can also be estimated using `DTM` function for polytomous responses. Note that these functions are experimental, and are expected to be further extended in the future. Other diagnostic approaches include the multiple-choice model (de la Torre, 2009) and an iterative latent class analysis (ILCA; Jiang, 2019).

Various Q-matrix validation methods (de la Torre, & Chiu, 2016; de la Torre & Ma, 2016; Ma & de la Torre, 2020b; Najera, Sorrel, & Abad, 2019; see `Qval`), model-data fit statistics (Chen, de la Torre, & Zhang, 2013; Hansen, Cai, Monroe, & Li, 2016; Liu, Tian, & Xin, 2016; Ma, 2020; see `modelfit` and `itemfit`), model comparison at test and item level (de la Torre, 2011; de la Torre, & Lee, 2013; Ma, Iaconangelo, & de la Torre, 2016; Ma & de la Torre, 2019; Sorrel, Abad, Olea, de la Torre, & Barrada, 2017; Sorrel, de la Torre, Abad, & Olea, 2017; see `modelcomp`), and differential item functioning (Hou, de la Torre, & Nandakumar, 2014; Ma, Terzi, Lee, & de la Torre, 2017; see `dif`) can also be conducted.

To use the graphical user interface, check `startGDINA`.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Jimmy de la Torre, The University of Hong Kong

See Also

CDM for estimating G-DINA model and a set of other CDMs; **ACTCD** and **NPCD** for nonparametric CDMs; **dina** for DINA model in Bayesian framework

---

att.structure *Generate hierarchical attribute structures*

Description

This function can be used to generate hierarchical attributes structures, and to provide prior joint attribute distribution with hierarchical structures.

Usage

```
att.structure(hierarchy.list = NULL, K, Q, att.prob = "uniform")
```

Arguments

`hierarchy.list`	a list specifying the hierarchical structure between attributes. Each element in this list specifies a DIRECT prerequisite relation between two or more attributes. See `example` for more information.
`K`	the number of attributes involved in the assessment
`Q`	Q-matrix
`att.prob`	How are the probabilities for latent classes simulated? It can be `"random"` or `"uniform"`.

Value

att.str reduced latent classes under the specified hierarchical structure

impossible.latentclass impossible latent classes under the specified hierarchical structure

att.prob probabilities for all latent classes; 0 for impossible latent classes

Author(s)

Wenchao Ma, The University of Alabama, <wenchao.ma@ua.edu>
Jimmy de la Torre, The University of Hong Kong

See Also

GDINA, autoGDINA

Examples

```
## Not run:
#################
#
# Leighton et al. (2004, p.210)
#
##################
# linear structure A1->A2->A3->A4->A5->A6
K <- 6
linear=list(c(1,2),c(2,3),c(3,4),c(4,5),c(5,6))
att.structure(linear,K)

# convergent structure A1->A2->A3->A5->A6;A1->A2->A4->A5->A6
K <- 6
converg <- list(c(1,2),c(2,3),c(2,4),
              c(3,4,5), #this is how to show that either A3 or A4 is a prerequisite to A5
               c(5,6))
att.structure(converg,K)

# convergent structure [the difference between this one and the previous one is that
#                       A3 and A4 are both needed in order to master A5]
K <- 6
converg2 <- list(c(1,2),c(2,3),c(2,4),
               c(3,5), #this is how to specify that both A3 and A4 are needed for A5
               c(4,5), #this is how to specify that both A3 and A4 are needed for A5
               c(5,6))
att.structure(converg2,K)

# divergent structure A1->A2->A3;A1->A4->A5;A1->A4->A6
diverg <- list(c(1,2),
               c(2,3),
               c(1,4),
               c(4,5),
               c(4,6))
att.structure(diverg,K)

# unstructured A1->A2;A1->A3;A1->A4;A1->A5;A1->A6
unstru <- list(c(1,2),c(1,3),c(1,4),c(1,5),c(1,6))
att.structure(unstru,K)

## See Example 4 and 5 in GDINA function

## End(Not run)
```

`attributepattern` *Generate all possible attribute patterns*

Description

This function generates all possible attribute patterns. The Q-matrix needs to be specified for polytomous attributes.

Usage

```
attributepattern(K, Q)
```

Arguments

K	number of attributes
Q	Q-matrix; required when Q-matrix is polytomous

Value

A $2^K \times K$ matrix consisting of attribute profiles for 2^K latent classes

Author(s)

Wenchao Ma, The University of Alabama, <wenchao.ma@ua.edu>
Jimmy de la Torre, The University of Hong Kong

Examples

```
attributepattern(3)

q <- matrix(scan(text = "0 1 2 1 0 1 1 2 0"),ncol = 3)
q
attributepattern(Q=q)

q <- matrix(scan(text = "0 1 1 1 0 1 1 1 0"),ncol = 3)
q
attributepattern(K=ncol(q),Q=q)
```

---

autoGDINA *Q-matrix validation, model selection and calibration in one run*

Description

autoGDINA conducts a series of CDM analyses within the G-DINA framework. Particularly, the GDINA model is fitted to the data first using the GDINA function; then, the Q-matrix is validated using the function Qval. Based on the suggested Q-matrix, the data is fitted by the G-DINA model again, followed by an item level model selection via the Wald test using modelcomp. Lastly, the selected models are calibrated based on the suggested Q-matrix using the GDINA function. The Q-matrix validation and item-level model selection can be disabled by the users. Possible reduced CDMs for Wald test include the DINA model, the DINO model, A-CDM, LLM and RRUM. See Details for the rules of item-level model selection.

Usage

```
autoGDINA(
  dat,
  Q,
  modelselection = TRUE,
  modelselectionrule = "simpler",
  alpha.level = 0.05,
  modelselection.args = list(),
  Qvalid = TRUE,
  Qvalid.args = list(),
  GDINA1.args = list(),
  GDINA2.args = list(),
  CDM.args = list()
)

## S3 method for class 'autoGDINA'
summary(object, ...)
```

Arguments

dat	A required $N \times J$ matrix or data.frame consisting of the responses of N individuals to J items. Missing values need to be coded as NA.
Q	A required matrix; The number of rows occupied by a single-strategy dichotomous item is 1, by a polytomous item is the number of nonzero categories, and by a mutiple-strategy dichotomous item is the number of strategies. The number of column is equal to the number of attributes if all items are single-strategy dichotomous items, but the number of attributes + 2 if any items are polytomous or have multiple strategies. For a polytomous item, the first column represents the item number and the second column indicates the nonzero category number. For a multiple-strategy dichotomous item, the first column represents the item number and the second column indicates the strategy number. For binary attributes, 1 denotes the attributes are measured by the items and 0 means the attributes are not measured. For polytomous attributes, non-zero elements indicate which level of attributes are needed (see Chen, & de la Torre, 2013). See Examples.
modelselection	logical; conducting model selection or not?
modelselectionrule	how to conducted model selection? Possible options include simpler, largestp and DS. See Details.
alpha.level	nominal level for the Wald test. The default is 0.05.
modelselection.args	arguments passed to modelcomp
Qvalid	logical; validate Q-matrix or not? TRUE is the default.
Qvalid.args	arguments passed to Qval
GDINA1.args	arguments passed to GDINA function for initial G-DINA calibration
GDINA2.args	arguments passed to GDINA function for the second G-DINA calibration

CDM.args	arguments passed to GDINA function for final calibration
object	GDINA object for various S3 methods
...	additional arguments

Details

After the Wald statistics for each reduced CDM were calculated for each item, the reduced models with p values less than the pre-specified alpha level were rejected. If all reduced models were rejected for an item, the G-DINA model was used as the best model; if at least one reduced model was retained, three diferent rules can be implemented for selecting the best model:

When modelselectionrule is simpler:

If (a) the DINA or DINO model was one of the retained models, then the DINA or DINO model with the larger p value was selected as the best model; but if (b) both DINA and DINO were rejected, the reduced model with the largest p value was selected as the best model for this item. Note that when the p-values of several reduced models were greater than 0.05, the DINA and DINO models were preferred over the A-CDM, LLM, and R-RUM because of their simplicity. This procedure is originally proposed by Ma, Iaconangelo, and de la Torre (2016).

When modelselectionrule is largestp:

The reduced model with the largest p-values is selected as the most appropriate model.

When modelselectionrule is DS:

The reduced model with non-significant p-values but the smallest dissimilarity index is selected as the most appropriate model. Dissimilarity index can be viewed as an effect size measure, which quatifies how dis-similar the reduced model is from the G-DINA model (See Ma, Iaconangelo, and de la Torre, 2016 for details).

Value

a list consisting of the following elements:

GDINA1.obj initial GDINA calibration of class GDINA

GDINA2.obj second GDINA calibration of class GDINA

Qval.obj Q validation object of class Qval

Wald.obj model comparison object of class modelcomp

CDM.obj Final CDM calibration of class GDINA

Methods (by generic)

- summary(autoGDINA): print summary information

Note

Returned GDINA1.obj, GDINA2.obj and CDM.obj are objects of class GDINA, and all S3 methods suitable for GDINA objects can be applied. See GDINA and extract. Similarly, returned Qval.obj and Wald.obj are objects of class Qval and modelcomp.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Ma, W., Iaconangelo, C., & de la Torre, J. (2016). Model similarity, model selection and attribute classification. *Applied Psychological Measurement, 40*, 200-217.

See Also

GDINA, modelcomp, Qval

Examples

```
## Not run:
# simulated responses
Q <- sim10GDINA$simQ
dat <- sim10GDINA$simdat

#misspecified Q
misQ <- Q
misQ[10,] <- c(0,1,0)
out1 <- autoGDINA(dat,misQ,modelselectionrule="largestp")
out1
summary(out1)
AIC(out1$CDM.obj)

# simulated responses
Q <- sim30GDINA$simQ
dat <- sim30GDINA$simdat

#misspecified Q
misQ <- Q
misQ[1,] <- c(1,1,0,1,0)
auto <- autoGDINA(dat,misQ,Qvalid = TRUE, Qvalid.args = list(method = "wald"),
                  modelselectionrule="simpler")
auto
summary(auto)
AIC(auto$CDM.obj)

#using the other selection rule
out11 <- autoGDINA(dat,misQ,modelselectionrule="simpler",
                   modelselection.args = list(models = c("DINO","DINA")))
out11
summary(out11)

# disable model selection function
out12 <- autoGDINA(dat,misQ,modelselection=FALSE)
out12
```

```
summary(out12)


# Disable Q-matrix validation
out3 <- autoGDINA(dat = dat, Q = misQ, Qvalid = FALSE)
out3
summary(out3)

## End(Not run)
```

---

bdiagMatrix *Create a block diagonal matrix*

Description

Create a block diagonal matrix

Usage

```
bdiagMatrix(mlist, fill = 0)
```

Arguments

mlist	a list of matrices
fill	value to fill the non-diagnoal elements

Value

a block diagonal matrix

See Also

bdiag in **Matrix**

Examples

```
m1 <- bdiagMatrix(list(matrix(1:4, 2), diag(3)))
m2 <- bdiagMatrix(list(matrix(1:4, 2), diag(3)),fill = NA)
```

bootSE *Calculating standard errors and variance-covariance matrix using bootstrap methods*

Description

This function conducts nonparametric and parametric bootstrap to calculate standard errors of model parameters. Parametric bootstrap is only applicable to single group models.

Usage

```
bootSE(
  GDINA.obj,
  bootsample = 50,
  type = "nonparametric",
  cores = 1,
  seed = 12345
)
```

Arguments

GDINA.obj	an object of class GDINA
bootsample	the number of bootstrap samples
type	type of bootstrap method. Can be parametric or nonparametric
cores	number of cores to be used for calculation; Default = 1; if cores>1, bootstrap will run in parallel with foreach package.
seed	random seed for resampling

Value

itemparm.se standard errors for item probability of success in list format

delta.se standard errors for delta parameters in list format

lambda.se standard errors for structural parameters of joint attribute distribution

boot.est resample estimates

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Examples

```
## Not run:
# For illustration, only 5 resamples are run
# results are definitely not reliable

dat <- sim30GDINA$simdat
Q <- sim30GDINA$simQ
fit <- GDINA(dat = dat, Q = Q, model = "GDINA",att.dist = "higher.order")
boot.fit <- bootSE(fit,bootsample = 5,seed=123)
boot.fit$delta.se
boot.fit$lambda.se

## End(Not run)
```

CA *Calculate classification accuracy*

Description

This function calculates test-, pattern- and attribute-level classification accuracy indices based on GDINA estimates from the GDINA function using approaches in Iaconangelo (2017) and Wang, Song, Chen, Meng, and Ding (2015). It is only applicable for dichotomous attributes.

Usage

```
CA(GDINA.obj, what = "MAP")
```

Arguments

GDINA.obj	estimated GDINA object returned from GDINA
what	what attribute estimates are used? Default is "MAP".

Value

a list with elements

tau estimated overall pattern-level classification accuracy, see Iaconangelo (2017)

tau_l estimated pattern-level classification accuracy, see Iaconangelo (2017)

tau_k estimated attribute-level classification accuracy, see Wang, et al (2015)

CCM Conditional classification matrix, see Iaconangelo (2017)

gamma_k Wang et al.'s (2015) attribute-level classification consistency estimator

gamma estimated overall pattern-level classification consistency

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Iaconangelo, C.(2017). *Uses of Classification Error Probabilities in the Three-Step Approach to Estimating Cognitive Diagnosis Models.* (Unpublished doctoral dissertation). New Brunswick, NJ: Rutgers University.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Wang, W., Song, L., Chen, P., Meng, Y., & Ding, S. (2015). Attribute-Level and Pattern-Level Classification Consistency and Accuracy Indices for Cognitive Diagnostic Assessment. *Journal of Educational Measurement, 52* , 457-476.

Examples

```
## Not run:
dat <- realdata_ECPE$dat
Q <- realdata_ECPE$Q
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
fit
CA(fit)



## End(Not run)
```

---

cjoint *Combine R Objects by Columns*

Description

Combine a sequence of vector, matrix or data-frame arguments by columns. Vector is treated as a column matrix.

Usage

```
cjoint(..., fill = NA)
```

Arguments

`...`	vectors or matrices
`fill`	a scalar used when these objects have different number of rows.

Value

a data frame

See Also

`cbind`

Examples

```
cjoint(2,c(1,2,3,4),matrix(1:6,2,3))
cjoint(v1 = 2, v2 = c(3,2), v3 = matrix(1:6,3,2),
       v4 = data.frame(c(3,4,5,6,7),rep("x",5)),fill = 99)
```

ClassRate *Classification Rate Evaluation*

Description

This function evaluates the classification rates for two sets of attribute profiles

Usage

```
ClassRate(att1, att2)
```

Arguments

att1	a matrix or data frame of attribute profiles
att2	a matrix or data frame of attribute profiles

Value

a list with the following components:

PCA the proportion of correctly classified attributes (i.e., attribute level classification rate)

PCV a vector giving the proportions of correctly classified attribute vectors (i.e., vector level classification rate). The fist element is the proportion of at least one attribute in the vector are correctly identified; the second element is the proportion of at least two attributes in the vector are correctly identified; and so forth. The last element is the proportion of all elements in the vector are correctly identified.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Examples

```
## Not run:
N <- 2000
# model does not matter if item parameter is probability of success
Q <- sim30GDINA$simQ
J <- nrow(Q)
gs <- matrix(0.1,J,2)

set.seed(12345)
sim <- simGDINA(N,Q,gs.parm = gs)
GDINA.est <- GDINA(sim$dat,Q)

CR <- ClassRate(sim$attribute,personparm(GDINA.est))
CR

## End(Not run)
```

CM *Calculate Misclassification Matrices*

Description

This function computes profile-level and attribute-level misclassification matrices from a fitted GDINA model. This function is only applicable to models with binary attributes.

Usage

```
CM(object, classification = "MAP", matrixtype = "profile")
```

Arguments

object	An estimated GDINA object returned from GDINA.
classification	A character string specifying the classification rule. Supported values are "MAP", "MLE", and "EAP". Alternatively, a matrix of user-supplied classifications can be provided, with one row per respondent and one column per attribute.
matrixtype	A character string specifying which matrix to return. Supported values are "profile", "attribute", and "both".

Details

The profile-level matrix is computed from posterior latent class probabilities. The attribute-level matrices are computed from marginal attribute mastery probabilities and the chosen classifications.

Value

Depending on `matrixtype`, the function returns one of the following:

`"profile"` A class-by-class matrix of estimated $P(\hat{\alpha} = c' \mid \alpha = c)$.

`"attribute"` A list of 2×2 matrices, one for each attribute, with estimated $P(\hat{\alpha}_k = a' \mid \alpha_k = a)$.

`"both"` A list with elements `profile_classification` and `att_classification`.

For both pattern-level and attribute-level matrices, rows correspond to true classes and columns correspond to classified classes.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

Examples

```
## Not run:
dat <- realdata_ECPE$dat
Q <- realdata_ECPE$Q
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
CM(fit)
CM(fit, matrixtype = "both")

## End(Not run)
```

---

designmatrix *Generate design matrix*

Description

This function generates the design matrix for an item

Usage

```
designmatrix(Kj = NULL, model = "GDINA", Qj = NULL, no.bugs = 0)
```

Arguments

`Kj`	Required except for the MS-DINA model; The number of attributes required for item j
`model`	the model associated with the design matrix; It can be "GDINA","DINA","DINO", "ACDM","LLM", "RRUM", "MSDINA", "BUGDINO", and "SISM". The default is "GDINA". Note that models "LLM" and "RRUM" have the same design matrix as the "ACDM".
`Qj`	the Q-matrix for item j; This is required for "MSDINA", and "SISM" models; The number of rows is equal to the number of strategies for "MSDINA", and the number of columns is equal to the number of attributes.
`no.bugs`	the number of bugs (or misconceptions). Note that bugs must be given in the last no.bugs columns.

Value

a design matrix (Mj). See de la Torre (2011) for details.

References

de la Torre, J. (2011). The generalized DINA model framework. *Psychometrika, 76*, 179-199.

Examples

```
## Not run:
designmatrix(Kj = 2, model = "GDINA")
designmatrix(Kj = 3, model = "DINA")
msQj <- matrix(c(1,0,0,1,
                 1,1,0,0),nrow=2,byrow=TRUE)
designmatrix(model = "MSDINA",Qj = msQj)

## End(Not run)
```

---

dif *Differential item functioning for cognitive diagnosis models*

Description

This function is used to detect differential item functioning using the Wald test (Hou, de la Torre, & Nandakumar, 2014; Ma, Terzi, & de la Torre, 2021) and the likelihood ratio test (Ma, Terzi, & de la Torre, 2021). The forward anchor item search procedure developed in Ma, Terzi, and de la Torre (2021) was implemented.

Usage

```
dif(
  dat,
  Q,
  group,
  model = "GDINA",
  sequential = FALSE,
  method = "wald",
  anchor.items = NULL,
  dif.items = "all",
  p.adjust.methods = "holm",
  approx = FALSE,
  SE.type = 2,
  FS.args = list(on = FALSE, alpha.level = 0.05, maxit = 10, verbose = FALSE),
  ...
)

## S3 method for class 'dif'
summary(object, ...)
```

Arguments

dat	item responses from two or more groups; missing data need to be coded as NA
Q	Q-matrix specifying the association between items and attributes
group	a factor or a vector indicating the group each individual belongs to. Its length must be equal to the number of individuals.
model	model for each item.
sequential	Logical; whether a sequential model is fit to the data. Default is FALSE.
method	DIF detection method; It can be "wald" for Hou, de la Torre, and Nandakumar's (2014) Wald test method, and "LR" for likelihood ratio test (Ma, Terzi, Lee,& de la Torre, 2017).
anchor.items	which items will be used as anchors? Default is NULL, which means none of the items are used as anchors. For LR method, it can also be an integer vector giving the item numbers for anchors or "all", which means all items are treated as anchor items.
dif.items	which items are subject to DIF detection? Default is "all". It can also be an integer vector giving the item numbers.
p.adjust.methods	adjusted p-values for multiple hypothesis tests. This is conducted using p.adjust function in **stats**, and therefore all adjustment methods supported by p.adjust can be used, including "holm", "hochberg", "hommel", "bonferroni", "BH" and "BY". See p.adjust for more details. "holm" is the default.
approx	Whether an approximated LR test is implemented? If TRUE, parameters of items except the studied one will not be re-estimated.
SE.type	Type of standard error estimation methods for the Wald test.
FS.args	arguments for the forward anchor item search procedure developed in Ma, Terzi, and de la Torre (2021). A list with the following elements: • on - logical; TRUE if activate the forward anchor item search procedure. Default = FALSE. • alpha.level - nominal level for Wald or LR test. Default = .05. • maxit - maximum number of iterations allowed. Default = 10. • verbose - logical; print information for each iteration or not? Default = FALSE.
...	arguments passed to GDINA function for model calibration
object	dif object for S3 method

Value

A data frame giving the Wald statistics and associated p-values.

Methods (by generic)

- summary(dif): print summary information

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Jimmy de la Torre, The University of Hong Kong

References

Hou, L., de la Torre, J., & Nandakumar, R. (2014). Differential item functioning assessment in cognitive diagnostic modeling: Application of the Wald test to investigate DIF in the DINA model. *Journal of Educational Measurement, 51*, 98-125.

Ma, W., Terzi, R., & de la Torre, J. (2021). Detecting differential item functioning using multiple-group cognitive diagnosis models. *Applied Psychological Measurement*.

See Also

GDINA

Examples

```
## Not run:

###################################
#          Example 1.             #
#        two-group DIF            #
###################################

set.seed(123456)
N <- 3000
Q <- sim30GDINA$simQ
gs <- matrix(.2,ncol = 2, nrow = nrow(Q))
# By default, individuals are simulated from uniform distribution
# and deltas are simulated randomly
sim1 <- simGDINA(N,Q,gs.parm = gs,model="DINA")
sim2 <- simGDINA(N,Q,gs.parm = gs,model=c(rep("DINA",nrow(Q)-1),"DINO"))
dat <- rbind(extract(sim1,"dat"),extract(sim2,"dat"))
gr <- rep(c("G1","G2"),each=N)

# DIF using Wald test
dif.wald <- dif(dat, Q, group=gr, method = "Wald")
dif.wald
# DIF using LR test
dif.LR <- dif(dat, Q, group=gr, method="LR")
dif.LR
# DIF using Wald test + forward search algorithm
dif.wald.FS <- dif(dat, Q, group=gr, method = "Wald", FS.args = list(on = TRUE, verbose = TRUE))
dif.wald.FS
# DIF using LR test + forward search algorithm
dif.LR.FS <- dif(dat, Q, group=gr, method = "LR", FS.args = list(on = TRUE, verbose = TRUE))
dif.LR.FS

###################################
#          Example 2.             #
```

```
#        two-group DIF             #
#    with attribute structure.     #
####################################
# --- User-specified attribute structure ----#
Q <- sim30GDINA$simQ
K <- ncol(Q)
# linear structure A1->A2->A3->A4->A5
linear <- list(c(1,2),
               c(2,3),
               c(3,4),
               c(4,5))
struc <- att.structure(linear,K)
set.seed(123)
# data simulation
N <- 1000
true.lc <- sample(c(1:2^K),N,replace=TRUE,prob=struc$att.prob)
table(true.lc) #check the sample
true.att <- attributepattern(K)[true.lc,]
 gs <- matrix(rep(0.1,2*nrow(Q)),ncol=2)
 # data simulation
 simD <- simGDINA(N,Q,gs.parm = gs, model = "ACDM",attribute = true.att)
 dat <- extract(simD,"dat")
gr <- rep(1:2,each=N/2)
dif.wald <- dif(dat, Q, group=gr, method = "Wald",
                att.str = diverg, att.dist = "saturated")
dif.wald


####################################
#          Example 3.              #
#        Three-group DIF           #
####################################

set.seed(123456)
N <- 500
Q <- sim30GDINA$simQ
gs <- matrix(.2,ncol = 2, nrow = nrow(Q))
# By default, individuals are simulated from uniform distribution
# and deltas are simulated randomly
sim1 <- simGDINA(N,Q,gs.parm = gs,model="DINA")
sim2 <- simGDINA(N,Q,gs.parm = gs,model=c(rep("DINA",nrow(Q)-1),"DINO"))
sim3 <- simGDINA(N,Q,gs.parm = gs,model="DINA")
dat <- rbind(extract(sim1,"dat"),extract(sim2,"dat"),extract(sim3,"dat"))
gr <- rep(c("G1","G2","G3"),each=N)

# DIF using Wald test - omnibus test
dif.wald <- dif(dat, Q, group=gr, method = "Wald", FS.args = list(on = TRUE, verbose = TRUE))
dif.wald
# pairwise comparison between all pair of groups
dif.pair = pairwiseDIF(dif.wald)
dif.pair
# draw plot to show the DIF
plot(dif.pair, withSE = TRUE)
```

```
## End(Not run)
```

DTM *Diagnostic multiple-strategy CDMs*

Description

This function estimates the diagnostic tree model (Ma, 2018) for polytomous responses with multiple strategies. It can also handle various polytomous models discussed in Gao, et al. (2021).

Usage

```
DTM(
  dat,
  Qc,
  type = "tree",
  linkfunc = "logit",
  eq.const = FALSE,
  delta = NULL,
  Tmatrix = NULL,
  conv.crit = 0.001,
  conv.type = "pr",
  maxitr = 1000
)
```

Arguments

dat	A required $N \times J$ data matrix of N examinees to J items. Missing values are currently not allowed.
Qc	A required $J \times K + 2$ category and attribute association matrix, where J represents the number of items or nonzero categories and K represents the number of attributes. Entry 1 indicates that the attribute is measured by the item, and 0 otherwise. The first column gives the item number, which must be numeric and match the number of column in the data. The second column indicates the category number.
type	what type of model is to be fit; can be `'tree'`,`'sequential'`,or `'adjacent'`.
linkfunc	link function used; `'logit'` is the default.
eq.const	whether effects are constrained to be equal across categories; `FALSE` is the default.
delta	initial item parameters
Tmatrix	The mapping matrix showing the relation between the OBSERVED responses (rows) and the PSEDUO items (columns); The first column gives the observed responses.
conv.crit	The convergence criterion for max absolute change in item parameters.

conv.type	convergence criteria; Can be pr,LL and delta, indicating category response function, log-likelihood and delta parameters,respectively.
maxitr	The maximum iterations allowed.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Gao, X., Ma, W., Wang, D., Cai, Y., & Tu, D. (2021). A class of cognitive diagnosis models for polytomous data. *Journal of Educational and Behavioral Statistics, 46*, 297-322. Ma, W. (2018). A Diagnostic Tree Model for Polytomous Responses with Multiple Strategies. *British Journal of Mathematical and Statistical Psychology.*

See Also

GDINA for MS-DINA model and single strategy CDMs, and GMSCDM for generalized multiple strategies CDMs for dichotomous response data

Examples

```
## Not run:

###################################
#        Example 1.               #
#     sequential G-DINA model.    #
#                                 #
###################################

dat <- sim20seqGDINA$simdat
Qc <- sim20seqGDINA$simQ
fit=DTM(sim20seqGDINA$simdat,Qc,type="sequential")
fit
fit$testfit$AIC

###################################
#        Example 2.               #
#        Tree model               #
#                                 #
###################################
K=5
g=0.2
item.no <- rep(1:6,each=4)
# the first node has three response categories: 0, 1 and 2
node.no <- rep(c(1,1,2,3),6)
Q1 <- matrix(0,length(item.no),K)
Q2 <- cbind(7:(7+K-1),rep(1,K),diag(K))
for(j in 1:length(item.no)) {
  Q1[j,sample(1:K,sample(3,1))] <- 1
}
Qc <- rbind(cbind(item.no,node.no,Q1),Q2)
```

```
Tmatrix.set <- list(cbind(c(0,1,2,3,3),c(0,1,2,1,2),c(NA,0,NA,1,NA),c(NA,NA,0,NA,1)),
cbind(c(0,1,2,3,4),c(0,1,2,1,2),c(NA,0,NA,1,NA),c(NA,NA,0,NA,1)),
cbind(c(0,1),c(0,1)))
Tmatrix <- Tmatrix.set[c(1,1,1,1,1,1,rep(3,K))]
sim <- simDTM(N=2000,Qc=Qc,gs.parm=matrix(0.2,nrow(Qc),2),Tmatrix=Tmatrix)
est <- DTM(dat=sim$dat,Qc=Qc,Tmatrix = Tmatrix)

## End(Not run)
```

`extract` *extract elements from objects of various classes*

Description

A generic function to extract elements from objects of class `GDINA`, `itemfit`, `modelcomp`, `Qval` or `simGDINA`. This page gives the elements that can be extracted from the class `GDINA`. To see what can be extracted from `itemfit`, `modelcomp`, and `Qval`, go to the corresponding function help page.

Objects which can be extracted from `GDINA` objects include:

AIC AIC

att.prior attribute prior weights for calculating marginalized likelihood in the last EM iteration

attributepattern all attribute patterns involved in the current calibration

BIC BIC

CAIC Consistent AIC

catprob.cov covariance matrix of item probability parameter estimates; Need to specify `SE.type`

catprob.parm item parameter estimates

catprob.se standard error of item probability parameter estimates; Need to specify `SE.type`

convergence `TRUE` if the calibration is converged.

dat raw data

del.ind deleted observation number

delta.cov covariance matrix of delta parameter estimates; Need to specify `SE.type`

delta.parm delta parameter estimates

delta.se standard error of delta parameter estimates; Need to specify `SE.type`

designmatrix A list of design matrices for each item/category

deviance deviance, or negative two times observed marginal log likelihood

discrim GDINA discrimination index

expectedCorrect expected # of examinees in each latent group answering item correctly

expectedTotal expected # of examinees in each latent group

higher.order higher-order model specifications

LCprob.parm success probabilities for all latent classes

logLik observed marginal log likelihood

linkfunc link functions for each item

initial.catprob initial item category probability parameters

natt number of attributes

ncat number of categories

ngroup number of groups

nitem number of items

nitr number of EM iterations

nobs number of observations, or sample size

nLC number of latent classes

prevalence prevalence of each attribute

posterior.prob posterior weights for each latent class

reduced.LG Reduced latent group for each item

SABIC Sample size Adusted BIC

sequential is a sequential model fitted?

Usage

```
extract(object, what, ...)
```

Arguments

`object`	objects from class `GDINA`,`itemfit`, `modelcomp`, `Qval` or `simGDINA`
`what`	what to extract
`...`	additional arguments

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
extract(fit,"discrim")
extract(fit,"designmatrix")

## End(Not run)
```

GDINA *CDM calibration under the G-DINA model framework*

Description

GDINA calibrates the generalized deterministic inputs, noisy and gate (G-DINA; de la Torre, 2011) model for dichotomous responses, and its extension, the sequential G-DINA model (Ma, & de la Torre, 2016a; Ma, 2017) for ordinal and nominal responses. By setting appropriate constraints, the deterministic inputs, noisy and gate (DINA; de la Torre, 2009; Junker & Sijtsma, 2001) model, the deterministic inputs, noisy or gate (DINO; Templin & Henson, 2006) model, the reduced reparametrized unified model (R-RUM; Hartz, 2002), the additive CDM (A-CDM; de la Torre, 2011), the linear logistic model (LLM; Maris, 1999), and the multiple-strategy DINA model (MS-DINA; de la Torre & Douglas, 2008; Huo & de la Torre, 2014) can also be calibrated. Note that the LLM is equivalent to the C-RUM (Hartz, 2002), a special case of the GDM (von Davier, 2008), and that the R-RUM is also known as a special case of the generalized NIDA model (de la Torre, 2011).

In addition, users are allowed to specify design matrix and link function for each item, and distinct models may be used in a single test for different items. The attributes can be either dichotomous or polytomous (Chen & de la Torre, 2013). Joint attribute distribution may be modelled using independent or saturated model, structured model, higher-order model (de la Torre & Douglas, 2004), or loglinear model (Xu & von Davier, 2008). Marginal maximum likelihood method with Expectation-Maximization (MMLE/EM) alogrithm is used for item parameter estimation.

To compare two or more GDINA objects, use method anova.

To calculate structural parameters for item and joint attribute distributions, use method coef.

To calculate lower-order incidental (person) parameters use method personparm. To extract other components returned, use extract. To plot item/category response function, use plot. To check whether monotonicity is violated, use monocheck. To conduct anaysis in graphical user interface, use startGDINA.

Usage

```
GDINA(
  dat,
  Q,
  model = "GDINA",
  sequential = FALSE,
  att.dist = "saturated",
  mono.constraint = FALSE,
  group = NULL,
  linkfunc = NULL,
  design.matrix = NULL,
  no.bugs = 0,
  att.prior = NULL,
  att.str = NULL,
  verbose = 1,
  higher.order = list(),
```

```
  loglinear = 2,
  catprob.parm = NULL,
  control = list(),
  item.names = NULL,
  solver = NULL,
  nloptr.args = list(),
  auglag.args = list(),
  solnp.args = list(),
  ...
)

## S3 method for class 'GDINA'
anova(object, ...)

## S3 method for class 'GDINA'
coef(
  object,
  what = c("catprob", "delta", "gs", "itemprob", "LCprob", "rrum", "lambda"),
  withSE = FALSE,
  SE.type = 2,
  digits = 4,
  ...
)

## S3 method for class 'GDINA'
extract(object, what, SE.type = 2, ...)

## S3 method for class 'GDINA'
personparm(object, what = c("EAP", "MAP", "MLE", "mp", "HO"), digits = 4, ...)

## S3 method for class 'GDINA'
logLik(object, ...)

## S3 method for class 'GDINA'
deviance(object, ...)

## S3 method for class 'GDINA'
nobs(object, ...)

## S3 method for class 'GDINA'
vcov(object, ...)

## S3 method for class 'GDINA'
npar(object, ...)

## S3 method for class 'GDINA'
indlogLik(object, ...)
```

```
## S3 method for class 'GDINA'
indlogPost(object, ...)

## S3 method for class 'GDINA'
summary(object, ...)
```

Arguments

dat	A required $N \times J$ matrix or data.frame consisting of the responses of N individuals to J items. Missing values need to be coded as NA.
Q	A required matrix; The number of rows occupied by a single-strategy dichotomous item is 1, by a polytomous item is the number of nonzero categories, and by a mutiple-strategy dichotomous item is the number of strategies. The number of column is equal to the number of attributes if all items are single-strategy dichotomous items, but the number of attributes + 2 if any items are polytomous or have multiple strategies. For a polytomous item, the first column represents the item number and the second column indicates the nonzero category number. For a multiple-strategy dichotomous item, the first column represents the item number and the second column indicates the strategy number. For binary attributes, 1 denotes the attributes are measured by the items and 0 means the attributes are not measured. For polytomous attributes, non-zero elements indicate which level of attributes are needed (see Chen, & de la Torre, 2013). See Examples.
model	A vector for each item or nonzero category, or a scalar which will be used for all items or nonzero categories to specify the CDMs fitted. The possible options include "GDINA","DINA","DINO","ACDM","LLM", "RRUM", "MSDINA", "BUGDINO", "SISM", and "UDF". Note that model can also be "logitGDINA" and "logGDINA", indicating the saturated G-DINA model in logit and log link functions. They are equivalent to the identity link saturated G-DINA model. The logit G-DINA model is identical to the log-linear CDM. When "UDF", indicating user defined function, is specified for any item, arguments design.matrix and linkfunc need to be specified.
sequential	logical; TRUE if the sequential model is fitted for polytomous responses.
att.dist	How is the joint attribute distribution estimated? It can be (1) saturated, which is the default, indicating that the proportion parameter for each permissible latent class is estimated separately; (2) higher.order, indicating that a higher-order joint attribute distribution is assumed (higher-order model can be specified in higher.order argument); (3) fixed, indicating that the weights specified in att.prior argument are fixed in the estimation process. If att.prior is not specified, a uniform joint attribute distribution is employed initially; (4) independent, indicating that all attributes are assumed to be independent; and (5) loglinear, indicating a loglinear model is employed. If different groups have different joint attribute distributions, specify att.dist as a character vector with the same number of elements as the number of groups. However, if a higher-order model is used for any group, it must be used for all groups.
mono.constraint	logical; TRUE indicates that $P(\boldsymbol{\alpha}_1) <= P(\boldsymbol{\alpha}_2)$ if for all k, $\alpha_{1k} < \alpha_{2k}$. Can be

a vector for each item or nonzero category or a scalar which will be used for all items to specify whether monotonicity constraint should be added.

`group` a factor or a vector indicating the group each individual belongs to. Its length must be equal to the number of individuals.

`linkfunc` a vector of link functions for each item/category; It can be `"identity"`,`"log"` or `"logit"`. Only applicable when, for some items, `model="UDF"`.

`design.matrix` a list of design matrices; Its length must be equal to the number of items (or nonzero categories for sequential models). If CDM for item j is specified as "UDF" in argument `model`, the corresponding design matrix must be provided; otherwise, the design matrix can be `NULL`, which will be generated automatically.

`no.bugs` A numeric scalar (whole numbers only) indicating the number of bugs or misconceptions in the Q-matrix. The bugs must be included in the last `no.bugs` columns. It can be used along with the `BUGDINO` and `SISM` models (see, Kuo, Chen, Yang & Mok, 2016; Kuo, Chen, & de la Torre, 2018). This argument will be ignored if the model is not specified in `model` argument. Note that the `BUGDINO` and `SISM` models are reparametrized - see `Details` below. By default, `no.bugs=0`, implying that there is no bugs/misconceptions.

`att.prior` A vector of length 2^K for single group model, or a matrix of dimension $2^K \times$ no. of groups to specify attribute prior distribution for 2^K latent classes for all groups under a multiple group model. Only applicable for dichotomous attributes. The sum of all elements does not have to be equal to 1; however, it will be normalized so that the sum is equal to 1 before calibration. The label for each latent class can be obtained by calling `attributepattern(K)`. See `examples` for more info.

`att.str` Specify attribute structures. `NULL`, by default, means there is no structure. Attribute structure needs be specified as a list - which will be internally handled by `att.structure` function. See examples. It can also be a matrix giving all permissible attribute profiles.

`verbose` How to print calibration information after each EM iteration? Can be 0, 1 or 2, indicating to print no information, information for current iteration, or information for all iterations.

`higher.order` A list specifying the higher-order joint attribute distribution with the following components:

- `model` - a number indicating the model for higher-order joint attribute distribution. Can be 1, 2 or 3, representing the intercept only approach, common slope approach and varied slope approach (see `Details`).
- `nquad` - a scalar specifying the number of integral nodes. Default = 25.
- `SlopeRange` - a vector of length two specifying the range of slope parameters. Default = [0.1, 5].
- `InterceptRange` - a vector of length two specifying the range of intercept parameters. Default = [-4, 4].
- `SlopePrior` - a vector of length two specifying the mean and variance of log(slope) parameters, which are assumed normally distributed. Default: mean = 0 and sd = 0.25.

- `InterceptPrior` - a vector of length two specifying the mean and variance of intercept parameters, which are assumed normally distributed. Default: mean = 0 and sd = 1.
- `Prior` - logical; indicating whether prior distributions should be imposed to slope and intercept parameters. Default is `FALSE`.

`loglinear` the order of loglinear smooth for attribute space. It can be either 1 or 2 indicating the loglinear model with main effect only and with main effect and first-order interaction; It can also be a matrix, representing the design matrix for the loglinear model.

`catprob.parm` A list of initial success probability parameters for each nonzero category.

`control` A list of control parameters with elements:

- `maxitr` A vector for each item or nonzero category, or a scalar which will be used for all items or nonzero categories to specify the maximum number of EM cycles allowed. Default = 2000.
- `conv.crit` The convergence criterion. Default = 0.0001.
- `conv.type` How is the convergence criterion evaluated? A vector with possible elements: `"ip"`, indicating the maximum absolute change in item success probabilities, `"mp"`, representing the maximum absolute change in mixing proportion parameters, `"delta"`, indicating the maximum absolute change in delta parameters, `neg2LL` indicating the absolute change in negative two times loglikeihood, or `neg2LL` indicating the relative absolute change in negative two times loglikeihood (i.e., the absolute change divided by -2LL of the previous iteration). Multiple criteria can be specified. If so, all criteria need to be met. Default = c("ip", "mp").
- `nstarts` how many sets of starting values? Default = 3.
- `lower.p` A vector for each item or nonzero category, or a scalar which will be used for all items or nonzero categories to specify the lower bound for success probabilities. Default = .0001.
- `upper.p` A vector for each item or nonzero category, or a scalar which will be used for all items or nonzero categories to specify the upper bound for success probabilities. Default = .9999.
- `lower.prior` The lower bound for mixing proportion parameters (latent class sizes). Default = .Machine$double.eps.
- `randomseed` Random seed for generating initial item parameters. Default = 123456.
- `smallNcorrection` A numeric vector with two elements specifying the corrections applied when the expected number of individuals in some latent groups are too small. If the expected no. of examinees is less than the second element, the first element and two times the first element will be added to the numerator and denominator of the closed-form solution of probabilities of success. Only applicable for the G-DINA, DINA and DINO model estimation without monotonic constraints.
- `MstepMessage` Integer; Larger number prints more information from Mstep optimizer. Default = 1.

`item.names` A vector giving the item names. By default, items are named as "Item 1", "Item 2", etc.

`solver` A string indicating which solver should be used in M-step. By default, the solver is automatically chosen according to the models specified. Possible options include slsqp, nloptr, solnp and auglag.

`nloptr.args` a list of control parameters to be passed to `opts` argument of nloptr function.

`auglag.args` a list of control parameters to be passed to the alabama::auglag() function. It can contain two elements: `control.outer` and `control.optim`. See auglag.

`solnp.args` a list of control parameters to be passed to `control` argument of solnp function.

`...` additional arguments

`object` GDINA object for various S3 methods

`what` argument for various S3 methods; For calculating structural parameters using `coef`, `what` can be

- `itemprob` - item success probabilities of each reduced attribute pattern.
- `catprob` - category success probabilities of each reduced attribute pattern; the same as `itemprob` for dichtomous response data.
- `LCprob` - item success probabilities of each attribute pattern.
- `gs` - guessing and slip parameters of each item/category.
- `delta` - delta parameters of each item/category, see G-DINA formula in details.
- `rrum` - RRUM parameters when items are estimated using `RRUM`.
- `lambda` - structural parameters for joint attribute distribution.

For calculating incidental parameters using `personparm`, `what` can be

- `EAP` - EAP estimates of attribute pattern.
- `MAP` - MAP estimates of attribute pattern.
- `MLE` - MLE estimates of attribute pattern.
- `mp` - marginal mastery probabilities.
- `HO` - EAP estimates of higher-order ability if a higher-order is fitted.

`withSE` argument for method `coef`; estimate standard errors or not?

`SE.type` type of standard errors. For now, SEs are calculated based on outper-product of gradient. It can be `1` based on item-wise information, `2` based on incomplete information and `3` based on complete information.

`digits` How many decimal places in each number? The default is 4.

Value

`GDINA` returns an object of class `GDINA`. Methods for `GDINA` objects include `extract` for extracting various components, `coef` for extracting structural parameters, `personparm` for calculating incidental (person) parameters, `summary` for summary information. `AIC`, `BIC`,`logLik`, `deviance` and `npar` can also be used to calculate AIC, BIC, observed log-likelihood, deviance and number of parameters.

Methods (by generic)

- `anova(GDINA)`: Model comparison using likelihood ratio test
- `coef(GDINA)`: extract structural parameter estimates
- `extract(GDINA)`: extract various elements of GDINA estimates
- `personparm(GDINA)`: calculate person attribute patterns and higher-order ability
- `logLik(GDINA)`: calculate log-likelihood
- `deviance(GDINA)`: calculate deviance
- `nobs(GDINA)`: calculate number of observations
- `vcov(GDINA)`: calculate covariance-matrix for delta parameters
- `npar(GDINA)`: calculate the number of parameters
- `indlogLik(GDINA)`: extract log-likelihood for each individual
- `indlogPost(GDINA)`: extract log posterior for each individual
- `summary(GDINA)`: print summary information

The G-DINA model

The generalized DINA model (G-DINA; de la Torre, 2011) is an extension of the DINA model. Unlike the DINA model, which collaspes all latent classes into two latent groups for each item, if item j requires K_j^* attributes, the G-DINA model collapses 2^K latent classes into $2^{K_j^*}$ latent groups with unique success probabilities on item j, where $K_j^* = \sum_{k=1}^{K} q_{jk}$.

Let $\boldsymbol{\alpha}_{lj}^*$ be the reduced attribute pattern consisting of the columns of the attributes required by item j, where $l = 1, \ldots, 2^{K_j^*}$. For example, if only the first and the last attributes are required, $\boldsymbol{\alpha}_{lj}^* = (\alpha_{l1}, \alpha_{lK})$. For notational convenience, the first K_j^* attributes can be assumed to be the required attributes for item j as in de la Torre (2011). The probability of success $P(X_j = 1|\boldsymbol{\alpha}_{lj}^*)$ is denoted by $P(\boldsymbol{\alpha}_{lj}^*)$. To model this probability of success, different link functions as in the generalized linear models are used in the G-DINA model. The item response function of the G-DINA model using the identity link can be written as

$$f[P(\boldsymbol{\alpha}_{lj}^*)] = \delta_{j0} + \sum_{k=1}^{K_j^*} \delta_{jk}\alpha_{lk} + \sum_{k'=k+1}^{K_j^*} \sum_{k=1}^{K_j^*-1} \delta_{jkk'}\alpha_{lk}\alpha_{lk'} + \cdots + \delta_{j12\cdots K_j^*} \prod_{k=1}^{K_j^*} \alpha_{lk},$$

or in matrix form,

$$f[\boldsymbol{P}_j] = \boldsymbol{M}_j\boldsymbol{\delta}_j,$$

where δ_{j0} is the intercept for item j, δ_{jk} is the main effect due to α_{lk}, $\delta_{jkk'}$ is the interaction effect due to α_{lk} and $\alpha_{lk'}$, $\delta_{j12\ldots K_j^*}$ is the interaction effect due to $\alpha_{l1}, \cdots, \alpha_{lK_j^*}$. The log and logit links can also be employed.

Other CDMs as special cases

Several widely used CDMs can be obtained by setting appropriate constraints to the G-DINA model. This section introduces the parameterization of different CDMs within the G-DINA model framework very breifly. Readers interested in this please refer to de la Torre(2011) for details.

`DINA model` In DINA model, each item has two item parameters - guessing (g) and slip (s). In traditional parameterization of the DINA model, a latent variable η for person i and item j is defined as

$$\eta_{ij} = \prod_{k=1}^{K} \alpha_{ik}^{q_{jk}}$$

Briefly speaking, if individual i master all attributes required by item j, $\eta_{ij} = 1$; otherwise, $\eta_{ij} = 0$. Item response function of the DINA model can be written by

$$P(X_{ij} = 1|\eta_{ij}) = (1 - s_j)^{\eta_{ij}} g_j^{1-\eta_{ij}}$$

To obtain the DINA model from the G-DINA model, all terms in identity link G-DINA model except δ_0 and $\delta_{12...K_j^*}$ need to be fixed to zero, that is,

$$P(\boldsymbol{\alpha}_{lj}^*) = \delta_{j0} + \delta_{j12\cdots K_j^*} \prod_{k=1}^{K_j^*} \alpha_{lk}$$

In this parameterization, $\delta_{j0} = g_j$ and $\delta_{j0} + \delta_{j12\cdots K_j^*} = 1 - s_j$.

`DINO model` The DINO model can be given by

$$P(\boldsymbol{\alpha}_{lj}^*) = \delta_{j0} + \delta_{j1} I(\boldsymbol{\alpha}_{lj}^* \neq \mathbf{0})$$

where $I(\cdot)$ is an indicator variable. The DINO model is also a constrained identity link G-DINA model. As shown by de la Torre (2011), the appropriate constraint is

$$\delta_{jk} = -\delta_{jk'k''} = \cdots = (-1)^{K_j^*+1} \delta_{j12\cdots K_j^*},$$

for $k = 1, \cdots, K_j^*, k^{'} = 1, \cdots, K_j^* - 1$, and $k^{''} > k^{'}, \cdots, K_j^*$.

`Additive models with different link functions` The A-CDM, LLM and R-RUM can be obtained by setting all interactions to be zero in identity, logit and log link G-DINA model, respectively. Specifically, the A-CDM can be formulated as

$$P(\boldsymbol{\alpha}_{lj}^*) = \delta_{j0} + \sum_{k=1}^{K_j^*} \delta_{jk} \alpha_{lk}$$

The item response function for LLM can be given by

$$logit[P(\boldsymbol{\alpha}_{lj}^*)] = \delta_{j0} + \sum_{k=1}^{K_j^*} \delta_{jk} \alpha_{lk},$$

and lastly, the RRUM, can be written as

$$log[P(\boldsymbol{\alpha}_{lj}^*)] = \delta_{j0} + \sum_{k=1}^{K_j^*} \delta_{jk} \alpha_{lk}.$$

It should be noted that the LLM is equivalent to the compensatory RUM, which is subsumed by the GDM, and that the RRUM is a special case of the generalized noisy inputs, deterministic "And" gate model (G-NIDA).

`Simultaneously identifying skills and misconceptions (SISM)` The SISM can be can be reformulated as

$$P(\boldsymbol{\alpha}_{lj}^*) = \delta_{j0}+\delta_{j1}I[masteringallskills]+\delta_{j2}I[havingnobugs]+\delta_{j12}I[masteringallskillsandhavingnobugs].$$

As a result,the success probability of students who have mastered all the measured skills and possess none of the measured misconceptions (h_j in Equation 4 of Kuo, et al, 2018) is $\delta_{j0} + \delta_{j1} + \delta_{j2} + \delta_{j12}$, the success probability of students who have mastered all the measured skills but possess some of the measured misconceptions (ω_j) is $\delta_{j0} + \delta_{j1}$, the success probability of students who have not mastered all the measured skills and possess none of the measured misconceptions (g_j) is $\delta_{j0} + \delta_{j2}$ and success probability of students who have not mastered all the measured skills and possess at least one of the measured misconceptions(ϵ_j) is δ_{j0}.

By specifying `no.bugs` being equal to the number of attributes, the Bug-DINO is obtained, as in

$$P(\boldsymbol{\alpha}_{lj}^*) = \delta_{j0} + \delta_{j1}I[havingnobugs].$$

Joint Attribute Distribution

The joint attribute distribution can be modeled using various methods. This section mainly focuses on the so-called higher-order approach, which was originally proposed by de la Torre and Douglas (2004) for the DINA model. It has been extended in this package for all condensation rules. Particularly, three approaches are available for the higher-order attribute structure: intercept only approach, common slope approach and varied slope approach. For the intercept only approach, the probability of mastering attribute k for individual i is defined as

$$P(\alpha_k = 1|\theta_i, \lambda_{0k}) = \frac{exp(\theta_i + \lambda_{0k})}{1 + exp(\theta_i + \lambda_{0k})}$$

For the common slope approach, the probability of mastering attribute k for individual i is defined as

$$P(\alpha_k = 1|\theta_i, \lambda_{0k}, \lambda_1) = \frac{exp(\lambda_1\theta_i + \lambda_{0k})}{1 + exp(\lambda_1\theta_i + \lambda_{0k})}$$

For the varied slope approach, the probability of mastering attribute k for individual i is defined as

$$P(\alpha_k = 1|\theta_i, \lambda_{0k}, \lambda_{1k}) = \frac{exp(\lambda_{1k}\theta_i + \lambda_{0k})}{1 + exp(\lambda_{1k}\theta_i + \lambda_{0k})}$$

where θ_i is the ability of examinee i. λ_{0k} and λ_{1k} are the intercept and slope parameters for attribute k, respectively. The probability of joint attributes can be written as

$$P(\boldsymbol{\alpha}|\theta_i, \boldsymbol{\lambda}) = \prod_k P(\alpha_k|\theta_i, \boldsymbol{\lambda})$$

.

Model Estimation

The MMLE/EM algorithm is implemented in this package. For G-DINA, DINA and DINO models, closed-form solutions exist. See de la Torre (2009) and de la Torre (2011) for details. For ACDM, LLM and RRUM, closed-form solutions do not exist, and therefore some general optimization techniques are adopted in M-step (Ma, Iaconangelo & de la Torre, 2016). The selection of optimization techniques mainly depends on whether some specific constraints need to be added.

The sequential G-DINA model is a special case of the diagnostic tree model (DTM; Ma, 2019) and estimated using the mapping matrix accordingly (See Tutz, 1997; Ma, 2019).

The Number of Parameters

For dichotomous response models: Assume a test measures K attributes and item j requires K_j^* attributes: The DINA and DINO model has 2 item parameters for each item; if item j is ACDM, LLM or RRUM, it has $K_j^* + 1$ item parameters; if it is G-DINA model, it has $2^{K_j^*}$ item parameters. Apart from item parameters, the parameters involved in the estimation of joint attribute distribution need to be estimated as well. When using the saturated attribute structure, there are $2^K - 1$ parameters for joint attribute distribution estimation; when using a higher-order attribute structure, there are K, $K + 1$, and $2 \times K$ parameters for the intercept only approach, common slope approach and varied slope approach, respectively. For polytomous response data using the sequential G-DINA model, the number of item parameters are counted at category level.

Note

anova function does NOT check whether models compared are nested or not.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Jimmy de la Torre, The University of Hong Kong

References

Bock, R. D., & Aitkin, M. (1981). Marginal maximum likelihood estimation of item parameters: Application of an EM algorithm. *Psychometrika, 46*, 443-459.

Bock, R. D., & Lieberman, M. (1970). Fitting a response model forn dichotomously scored items. *Psychometrika, 35*, 179-197.

Bor-Chen Kuo, Chun-Hua Chen, Chih-Wei Yang, & Magdalena Mo Ching Mok. (2016). Cognitive diagnostic models for tests with multiple-choice and constructed-response items. *Educational Psychology, 36*, 1115-1133.

Carlin, B. P., & Louis, T. A. (2000). Bayes and empirical bayes methods for data analysis. New York, NY: Chapman & Hall

de la Torre, J., & Douglas, J. A. (2008). Model evaluation and multiple strategies in cognitive diagnosis: An analysis of fraction subtraction data. *Psychometrika, 73*, 595-624.

de la Torre, J. (2009). DINA Model and Parameter Estimation: A Didactic. *Journal of Educational and Behavioral Statistics, 34*, 115-130.

de la Torre, J. (2011). The generalized DINA model framework. *Psychometrika, 76*, 179-199.

de la Torre, J., & Douglas, J. A. (2004). Higher-order latent trait models for cognitive diagnosis. *Psychometrika, 69*, 333-353.

de la Torre, J., & Lee, Y. S. (2013). Evaluating the wald test for item-level comparison of saturated and reduced models in cognitive diagnosis. *Journal of Educational Measurement, 50*, 355-373.

Haertel, E. H. (1989). Using restricted latent class models to map the skill structure of achievement items. *Journal of Educational Measurement, 26*, 301-321.

Hartz, S. M. (2002). A bayesian framework for the unified model for assessing cognitive abilities: Blending theory with practicality (Unpublished doctoral dissertation). University of Illinois at Urbana-Champaign.

Huo, Y., & de la Torre, J. (2014). Estimating a Cognitive Diagnostic Model for Multiple Strategies via the EM Algorithm. *Applied Psychological Measurement, 38*, 464-485.

Junker, B. W., & Sijtsma, K. (2001). Cognitive assessment models with few assumptions, and connections with nonparametric item response theory. *Applied Psychological Measurement, 25*, 258-272.

Kuo, B.-C., Chen.-H., & de la Torre,J. (2018). A cognitive diagnosis model for identifying coexisting skills and misconceptions.*Applied Psychological Measuremet*, 179–191.

Ma, W., & de la Torre, J. (2016). A sequential cognitive diagnosis model for polytomous responses. *British Journal of Mathematical and Statistical Psychology. 69,* 253-275.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Ma, W. (2019). A diagnostic tree model for polytomous responses with multiple strategies. *British Journal of Mathematical and Statistical Psychology, 72*, 61-82.

Ma, W., Iaconangelo, C., & de la Torre, J. (2016). Model similarity, model selection and attribute classification. *Applied Psychological Measurement, 40*, 200-217.

Ma, W. (2017). *A Sequential Cognitive Diagnosis Model for Graded Response: Model Development, Q-Matrix Validation,and Model Comparison. Unpublished doctoral dissertation.* New Brunswick, NJ: Rutgers University.

Maris, E. (1999). Estimating multiple classification latent class models. *Psychometrika, 64*, 187-212.

Tatsuoka, K. K. (1983). Rule space: An approach for dealing with misconceptions based on item response theory. *Journal of Educational Measurement, 20*, 345-354.

Templin, J. L., & Henson, R. A. (2006). Measurement of psychological disorders using cognitive diagnosis models. *Psychological Methods, 11*, 287-305.

Tutz, G. (1997). Sequential models for ordered responses. In W.J. van der Linden & R. K. Hambleton (Eds.), Handbook of modern item response theory p. 139-152). New York, NY: Springer.

Xu, X., & von Davier, M. (2008). Fitting the structured general diagnostic model to NAEP data. ETS research report, RR-08-27.

See Also

See `autoGDINA` for Q-matrix validation, item-level model comparison and model calibration in one run; See `modelfit` and `itemfit` for model and item fit analysis, `Qval` for Q-matrix validation, `modelcomp` for item level model comparison and `simGDINA` for data simulation. `GMSCDM` for a series of multiple strategy CDMs for dichotomous data, and `DTM` for diagnostic tree model for multiple strategies in polytomous response data Also see `gdina` in **CDM** package for the G-DINA model estimation.

Examples

```
## Not run:
####################################
#        Example 1.                #
#     GDINA, DINA, DINO            #
#    ACDM, LLM and RRUM            #
# estimation and comparison        #
```

```
#                                  #
####################################

dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ

#--------GDINA model --------#

mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")
mod1
# summary information
summary(mod1)

AIC(mod1) #AIC
BIC(mod1) #BIC
logLik(mod1) #log-likelihood value
deviance(mod1) # deviance: -2 log-likelihood
npar(mod1) # number of parameters


head(indlogLik(mod1)) # individual log-likelihood
head(indlogPost(mod1)) # individual log-posterior

# structural parameters
# see ?coef
coef(mod1) # item probabilities of success for each latent group
coef(mod1, withSE = TRUE) # item probabilities of success & standard errors
coef(mod1, what = "delta") # delta parameters
coef(mod1, what = "delta",withSE=TRUE) # delta parameters
coef(mod1, what = "gs") # guessing and slip parameters
coef(mod1, what = "gs",withSE = TRUE) # guessing and slip parameters & standard errors

# person parameters
# see ?personparm
personparm(mod1) # EAP estimates of attribute profiles
personparm(mod1, what = "MAP") # MAP estimates of attribute profiles
personparm(mod1, what = "MLE") # MLE estimates of attribute profiles

#plot item response functions for item 10
plot(mod1,item = 10)
plot(mod1,item = 10,withSE = TRUE) # with error bars
#plot mastery probability for individuals 1, 20 and 50
plot(mod1,what = "mp", person =c(1,20,50))

# Use extract function to extract more components
# See ?extract

# ------- DINA model --------#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod2 <- GDINA(dat = dat, Q = Q, model = "DINA")
mod2
coef(mod2, what = "gs") # guess and slip parameters
```

```
coef(mod2, what = "gs",withSE = TRUE) # guess and slip parameters and standard errors

# Model comparison at the test level via likelihood ratio test
anova(mod1,mod2)

# -------- DINO model -------#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod3 <- GDINA(dat = dat, Q = Q, model = "DINO")
#slip and guessing
coef(mod3, what = "gs") # guess and slip parameters
coef(mod3, what = "gs",withSE = TRUE) # guess and slip parameters + standard errors

# Model comparison at test level via likelihood ratio test
anova(mod1,mod2,mod3)

# --------- ACDM model -------#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod4 <- GDINA(dat = dat, Q = Q, model = "ACDM")
mod4
# --------- LLM model -------#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod4b <- GDINA(dat = dat, Q = Q, model = "LLM")
mod4b
# --------- RRUM model -------#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod4c <- GDINA(dat = dat, Q = Q, model = "RRUM")
mod4c

# --- Different CDMs for different items --- #

dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
models <- c(rep("GDINA",3),"LLM","DINA","DINO","ACDM","RRUM","LLM","RRUM")
mod5 <- GDINA(dat = dat, Q = Q, model = models)
anova(mod1,mod2,mod3,mod4,mod4b,mod4c,mod5)


####################################
#        Example 2.                #
#        Model estimations         #
# With monotonocity constraints    #
####################################

dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
# for item 10 only
mod11 <- GDINA(dat = dat, Q = Q, model = "GDINA",mono.constraint = c(rep(FALSE,9),TRUE))
mod11
mod11a <- GDINA(dat = dat, Q = Q, model = "DINA",mono.constraint = TRUE)
```

```
mod11a
mod11b <- GDINA(dat = dat, Q = Q, model = "ACDM",mono.constraint = TRUE)
mod11b
mod11c <- GDINA(dat = dat, Q = Q, model = "LLM",mono.constraint = TRUE)
mod11c
mod11d <- GDINA(dat = dat, Q = Q, model = "RRUM",mono.constraint = TRUE)
mod11d
coef(mod11d,"delta")
coef(mod11d,"rrum")

####################################
#           Example 3a.            #
#        Model estimations         #
# With Higher-order att structure  #
####################################

dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
# --- Higher order G-DINA model ---#
mod12 <- GDINA(dat = dat, Q = Q, model = "DINA",
               att.dist="higher.order",higher.order=list(nquad=31,model = "2PL"))
personparm(mod12,"HO") # higher-order ability
# structural parameters
# first column is slope and the second column is intercept
coef(mod12,"lambda")
# --- Higher order DINA model ---#
mod22 <- GDINA(dat = dat, Q = Q, model = "DINA", att.dist="higher.order",
               higher.order=list(model = "2PL",Prior=TRUE))

####################################
#           Example 3b.            #
#        Model estimations         #
#   With log-linear att structure  #
####################################

# --- DINA model with loglinear smoothed attribute space ---#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod23 <- GDINA(dat = dat, Q = Q, model = "DINA",att.dist="loglinear",loglinear=1)
coef(mod23,"lambda") # intercept and three main effects

####################################
#           Example 3c.            #
#        Model estimations         #
#  With independent att structure  #
####################################

# --- GDINA model with independent attribute space ---#
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod33 <- GDINA(dat = dat, Q = Q, att.dist="independent")
coef(mod33,"lambda") # mastery probability for each attribute
```

```
###################################
#          Example 4.             #
#        Model estimations        #
#    With fixed att structure     #
###################################

# --- User-specified attribute priors ----#
# prior distribution is fixed during calibration
# Assume each of 000,100,010 and 001 has probability of 0.1
# and each of 110, 101,011 and 111 has probability of 0.15
# Note that the sum is equal to 1
#
prior <- c(0.1,0.1,0.1,0.1,0.15,0.15,0.15,0.15)
# fit GDINA model  with fixed prior dist.
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
modp1 <- GDINA(dat = dat, Q = Q, att.prior = prior, att.dist = "fixed")
extract(modp1, what = "att.prior")

###################################
#          Example 5a.            #
#             G-DINA              #
# with hierarchical att structure  #
###################################

# --- User-specified attribute structure ----#
Q <- sim30GDINA$simQ
K <- ncol(Q)
# divergent structure A1->A2->A3;A1->A4->A5
diverg <- list(c(1,2),
               c(2,3),
               c(1,4),
               c(4,5))
struc <- att.structure(diverg,K)
set.seed(123)
# data simulation
N <- 1000
true.lc <- sample(c(1:2^K),N,replace=TRUE,prob=struc$att.prob)
table(true.lc) #check the sample
true.att <- attributepattern(K)[true.lc,]
 gs <- matrix(rep(0.1,2*nrow(Q)),ncol=2)
 # data simulation
 simD <- simGDINA(N,Q,gs.parm = gs, model = "GDINA",attribute = true.att)
 dat <- extract(simD,"dat")

modp1 <- GDINA(dat = dat, Q = Q, att.str = diverg, att.dist = "saturated")
modp1
coef(modp1,"lambda")

###################################
#          Example 5b.            #
#   Reduced model (e.g.,ACDM)     #
# with hierarchical att structure  #
```

```
####################################

# --- User-specified attribute structure ----#
Q <- sim30GDINA$simQ
K <- ncol(Q)
# linear structure A1->A2->A3->A4->A5
linear <- list(c(1,2),
               c(2,3),
               c(3,4),
               c(4,5))
struc <- att.structure(linear,K)
set.seed(123)
# data simulation
N <- 1000
true.lc <- sample(c(1:2^K),N,replace=TRUE,prob=struc$att.prob)
table(true.lc) #check the sample
true.att <- attributepattern(K)[true.lc,]
 gs <- matrix(rep(0.1,2*nrow(Q)),ncol=2)
 # data simulation
 simD <- simGDINA(N,Q,gs.parm = gs, model = "ACDM",attribute = true.att)
 dat <- extract(simD,"dat")

modp1 <- GDINA(dat = dat, Q = Q, model = "ACDM",
               att.str = linear, att.dist = "saturated")
coef(modp1)
coef(modp1,"lambda")

####################################
#           Example 6.             #
# Specify initial values for item  #
# parameters                       #
####################################

 # check initials to see the format for initial item parameters
 initials <- sim10GDINA$simItempar

 dat <- sim10GDINA$simdat
 Q <- sim10GDINA$simQ
 mod.initial <- GDINA(dat,Q,catprob.parm = initials)

 # compare initial item parameters
 Map(rbind, initials,extract(mod.initial,"initial.catprob"))

####################################
#           Example 7a.            #
# Fix item and structure parameters#
# Estimate person attribute profile#
####################################

 # check initials to see the format for initial item parameters
 initials <- sim10GDINA$simItempar
 prior <- c(0.1,0.1,0.1,0.1,0.15,0.15,0.15,0.15)
 dat <- sim10GDINA$simdat
```

```
Q <- sim10GDINA$simQ
mod.ini <- GDINA(dat,Q,catprob.parm = initials,att.prior = prior,
                 att.dist = "fixed",control=list(maxitr = 0))
personparm(mod.ini)
# compare item parameters
Map(rbind, initials,coef(mod.ini))

####################################
#           Example 7b.            #
#   Fix parameters for some items  #
# Estimate person attribute profile#
####################################

# check initials to see the format for initial item parameters
initials <- sim10GDINA$simItempar
prior <- c(0.1,0.1,0.1,0.1,0.15,0.15,0.15,0.15)
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
# fix parameters of the first 5 items; do not fix mixing proportion parameters
mod.ini <- GDINA(dat,Q,catprob.parm = initials,
                 att.dist = "saturated",control=list(maxitr = c(rep(0,5),rep(2000,5))))
personparm(mod.ini)
# compare item parameters
Map(rbind, initials,coef(mod.ini))

####################################
#           Example 8.             #
#        polytomous attribute      #
#          model estimation        #
#    see Chen, de la Torre 2013    #
####################################


# --- polytomous attribute G-DINA model --- #
dat <- sim30pGDINA$simdat
Q <- sim30pGDINA$simQ
#polytomous G-DINA model
pout <- GDINA(dat,Q)

# ----- polymous DINA model --------#
pout2 <- GDINA(dat,Q,model="DINA")
anova(pout,pout2)

####################################
#           Example 9.             #
#        Sequential G-DINA model   #
#    see Ma, & de la Torre 2016    #
####################################

# --- polytomous attribute G-DINA model --- #
dat <- sim20seqGDINA$simdat
Q <- sim20seqGDINA$simQ
Q
```

```
#    Item Cat A1 A2 A3 A4 A5
#       1   1  1  0  0  0  0
#       1   2  0  1  0  0  0
#       2   1  0  0  1  0  0
#       2   2  0  0  0  1  0
#       3   1  0  0  0  0  1
#       3   2  1  0  0  0  0
#       4   1  0  0  0  0  1
#       ...

#sequential G-DINA model
sGDINA <- GDINA(dat,Q,sequential = TRUE)
sDINA <- GDINA(dat,Q,sequential = TRUE,model = "DINA")
anova(sGDINA,sDINA)
coef(sDINA) # processing function
coef(sDINA,"itemprob") # success probabilities for each item
coef(sDINA,"LCprob") # success probabilities for each category for all latent classes

####################################
#           Example 10a.           #
#    Multiple-Group G-DINA model   #
####################################

Q <- sim10GDINA$simQ
K <- ncol(Q)
# parameter simulation
# Group 1 - female
N1 <- 3000
gs1 <- matrix(rep(0.1,2*nrow(Q)),ncol=2)
# Group 2 - male
N2 <- 3000
gs2 <- matrix(rep(0.2,2*nrow(Q)),ncol=2)

# data simulation for each group
sim1 <- simGDINA(N1,Q,gs.parm = gs1,model = "DINA",att.dist = "higher.order",
                 higher.order.parm = list(theta = rnorm(N1),
                 lambda = data.frame(a=rep(1.5,K),b=seq(-1,1,length.out=K))))
sim2 <- simGDINA(N2,Q,gs.parm = gs2,model = "DINO",att.dist = "higher.order",
                 higher.order.parm = list(theta = rnorm(N2),
                 lambda = data.frame(a=rep(1,K),b=seq(-2,2,length.out=K))))

# combine data - all items have the same item parameters
dat <- rbind(extract(sim1,"dat"),extract(sim2,"dat"))
gr <- rep(c(1,2),c(3000,3000))
# Fit G-DINA model
mg.est <- GDINA(dat = dat,Q = Q,group = gr)
summary(mg.est)
extract(mg.est,"posterior.prob")
coef(mg.est,"lambda")


####################################
#           Example 10b.           #
```

```
#    Multiple-Group G-DINA model   #
#####################################

Q <- sim30GDINA$simQ
K <- ncol(Q)
# parameter simulation
N1 <- 3000
gs1 <- matrix(rep(0.1,2*nrow(Q)),ncol=2)
N2 <- 3000
gs2 <- matrix(rep(0.2,2*nrow(Q)),ncol=2)

# data simulation for each group
# two groups have different theta distributions
sim1 <- simGDINA(N1,Q,gs.parm = gs1,model = "DINA",att.dist = "higher.order",
                 higher.order.parm = list(theta = rnorm(N1),
                 lambda = data.frame(a=rep(1,K),b=seq(-2,2,length.out=K))))
sim2 <- simGDINA(N2,Q,gs.parm = gs2,model = "DINO",att.dist = "higher.order",
                 higher.order.parm = list(theta = rnorm(N2,1,1),
                 lambda = data.frame(a=rep(1,K),b=seq(-2,2,length.out=K))))

# combine data - different groups have distinct item parameters
# see ?bdiagMatrix
dat <- bdiagMatrix(list(extract(sim1,"dat"),extract(sim2,"dat")),fill=NA)
Q <- rbind(Q,Q)
gr <- rep(c(1,2),c(3000,3000))
mg.est <- GDINA(dat = dat,Q = Q,group = gr)
# Fit G-DINA model
mg.est <- GDINA(dat = dat,Q = Q,group = gr,att.dist="higher.order",
higher.order=list(model = "Rasch"))
summary(mg.est)
coef(mg.est,"lambda")
personparm(mg.est)
personparm(mg.est,"HO")
extract(mg.est,"posterior.prob")


#####################################
#           Example 11.             #
#           Bug DINO model          #
#####################################

set.seed(123)
Q <- sim10GDINA$simQ # 1 represents misconceptions/bugs
N <- 1000
J <- nrow(Q)

gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))

sim <- simGDINA(N,Q,gs.parm = gs,model = "BUGDINO")
dat <- extract(sim,"dat")
est <- GDINA(dat=dat,Q=Q,model = "BUGDINO")
coef(est)
```

```
####################################
#           Example 12.            #
#           SISM model             #
####################################

# The Q-matrix used in Kuo, et al (2018)
# The first four columns are for Attributes 1-4
# The last three columns are for Bugs 1-3
Q <- matrix(c(1,0,0,0,0,0,0,
0,1,0,0,0,0,0,
0,0,1,0,0,0,0,
0,0,0,1,0,0,0,
0,0,0,0,1,0,0,
0,0,0,0,0,1,0,
0,0,0,0,0,0,1,
1,0,0,0,1,0,0,
0,1,0,0,1,0,0,
0,0,1,0,0,0,1,
0,0,0,1,0,1,0,
1,1,0,0,1,0,0,
1,0,1,0,0,0,1,
1,0,0,1,0,0,1,
0,1,1,0,0,0,1,
0,1,0,1,0,1,1,
0,0,1,1,0,1,1,
1,0,1,0,1,1,0,
1,1,0,1,1,1,0,
0,1,1,1,1,1,0),ncol = 7,byrow = TRUE)

J <- nrow(Q)
N <- 1000
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))

sim <- simGDINA(N,Q,gs.parm = gs,model = "SISM",no.bugs=3)
dat <- extract(sim,"dat")
est <- GDINA(dat=dat,Q=Q,model="SISM",no.bugs=3)
coef(est,"delta")

####################################
#           Example 13a.           #
#     user specified design matrix #
#        LCDM (logit G-DINA)       #
####################################

dat <- sim30GDINA$simdat
Q <- sim30GDINA$simQ

# LCDM
lcdm <- GDINA(dat = dat, Q = Q, model = "logitGDINA", control=list(conv.type="neg2LL"))

#Another way is to find design matrix for each item first => must be a list
D <- lapply(rowSums(Q),designmatrix,model="GDINA")
# for comparison, use change in -2LL as convergence criterion
```

```
# LCDM
lcdm2 <- GDINA(dat = dat, Q = Q, model = "UDF", design.matrix = D,
linkfunc = "logit", control=list(conv.type="neg2LL"),solver="slsqp")

# identity link GDINA
iGDINA <- GDINA(dat = dat, Q = Q, model = "GDINA",
control=list(conv.type="neg2LL"),solver="slsqp")

# compare all three models => identical
anova(lcdm,lcdm2,iGDINA)

####################################
#           Example 13b.           #
#     user specified design matrix #
#            RRUM                  #
####################################

dat <- sim30GDINA$simdat
Q <- sim30GDINA$simQ

# specify design matrix for each item => must be a list
# D can be defined by the user
D <- lapply(rowSums(Q),designmatrix,model="ACDM")
# for comparison, use change in -2LL as convergence criterion
# RRUM
logACDM <- GDINA(dat = dat, Q = Q, model = "UDF", design.matrix = D,
linkfunc = "log", control=list(conv.type="neg2LL"),solver="slsqp")

# identity link GDINA
RRUM <- GDINA(dat = dat, Q = Q, model = "RRUM",
              control=list(conv.type="neg2LL"),solver="slsqp")

# compare two models => identical
anova(logACDM,RRUM)

####################################
#           Example 14.            #
#     Multiple-strategy DINA model #
####################################

Q <- matrix(c(1,1,1,1,0,
1,2,0,1,1,
2,1,1,0,0,
3,1,0,1,0,
4,1,0,0,1,
5,1,1,0,0,
5,2,0,0,1),ncol = 5,byrow = TRUE)
d <- list(
  item1=c(0.2,0.7),
  item2=c(0.1,0.6),
  item3=c(0.2,0.6),
  item4=c(0.2,0.7),
  item5=c(0.1,0.8))
```

```
  set.seed(12345)
sim <- simGDINA(N=1000,Q = Q, delta.parm = d,
               model = c("MSDINA","MSDINA","DINA",
                         "DINA","DINA","MSDINA","MSDINA"))

# simulated data
dat <- extract(sim,what = "dat")
# estimation
# MSDINA need to be specified for each strategy
est <- GDINA(dat,Q,model = c("MSDINA","MSDINA","DINA",
                             "DINA","DINA","MSDINA","MSDINA"))
coef(est,"delta")

## End(Not run)
```

GMSCDM *Estimating multiple-strategy cognitive diagnosis models*

Description

An (experimental) function for calibrating the multiple-strategy CDMs for dichotomous response data (Ma & Guo, 2019)

Usage

```
GMSCDM(
  dat,
  msQ,
  model = "ACDM",
  s = 1,
  att.prior = NULL,
  delta = NULL,
  control = list()
)
```

Arguments

dat	A required binary item response matrix
msQ	A multiple-strategy Q-matrix; the first column gives item numbers and the second column gives the strategy number. See examples.
model	CDM used; can be "DINA","DINO","ACDM","LLM", and "RRUM", representing the GMS-DINA, GMS-DINO, GMS-ACDM, GMS-LLM and GMS-RRUM in Ma & Guo (2019), respectively. It can also be "rDINA" and "rDINO", representing restricted GMS-DINA and GMS-DINO models where δ_{jm1} are equal for all strategies. Note that only a single model can be used for the whole test.
s	strategy selection parameter. It is equal to 1 by default.

att.prior	mixing proportion parameters.
delta	delta parameters in list format.
control	a list of control arguments

Value

an object of class GMSCDM with the following components:

IRF A matrix of success probabilities for each latent class on each item (IRF)

delta A list of delta parameters

attribute A list of estimated attribute profiles including EAP, MLE and MAP estimates.

testfit A list of test fit statistics including deviance, number of parameters, AIC and BIC

sIRF strategy-specific item response function

pjmc Probability of adopting each strategy on each item for each latent class

sprv Strategy pravelence

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Ma, W., & Guo, W. (2019). Cognitive Diagnosis Models for Multiple Strategies. *British Journal of Mathematical and Statistical Psychology.*

See Also

GDINA for MS-DINA model and single strategy CDMs, and DTM for diagnostic tree model for multiple strategies in polytomous response data

Examples

```
## Not run:
##################
#
# data simulation
#
##################
set.seed(123)
msQ <- matrix(
c(1,1,0,1,
1,2,1,0,
2,1,1,0,
3,1,0,1,
4,1,1,1,
5,1,1,1),6,4,byrow = T)
```

```
# J x L - 00,10,01,11
LC.prob <- matrix(c(
0.2,0.7727,0.5889,0.8125,
0.1,0.9,0.1,0.9,
0.1,0.1,0.8,0.8,
0.2,0.5,0.4,0.7,
0.2,0.4,0.7,0.9),5,4,byrow=TRUE)
N <- 10000
att <- sample(1:4,N,replace=TRUE)
dat <- 1*(t(LC.prob[,att])>matrix(runif(N*5),N,5))


est <- GMSCDM(dat,msQ)
# item response function
est$IRF
# strategy specific IRF
est$sIRF


################################
#
# Example 14 from GDINA function
#
################################
Q <- matrix(c(1,1,1,1,0,
1,2,0,1,1,
2,1,1,0,0,
3,1,0,1,0,
4,1,0,0,1,
5,1,1,0,0,
5,2,0,0,1),ncol = 5,byrow = TRUE)
d <- list(
  item1=c(0.2,0.7),
  item2=c(0.1,0.6),
  item3=c(0.2,0.6),
  item4=c(0.2,0.7),
  item5=c(0.1,0.8))

  set.seed(123)
sim <- simGDINA(N=1000,Q = Q, delta.parm = d,
               model = c("MSDINA","MSDINA","DINA",
                         "DINA","DINA","MSDINA","MSDINA"))

# simulated data
dat <- extract(sim,what = "dat")
# estimation
# MSDINA need to be specified for each strategy
est <- GDINA(dat,Q,model = c("MSDINA","MSDINA","DINA",
                             "DINA","DINA","MSDINA","MSDINA"),
             control = list(conv.type = "neg2LL",conv.crit = .01))

# Approximate the MS-DINA model using GMS DINA model
est2 <- GMSCDM(dat, Q, model = "rDINA", s = 10,
```

```
                control = list(conv.type = "neg2LL",conv.crit = .01))

## End(Not run)
```

ILCA *Iterative latent-class analysis*

Description

This function implements an iterative latent class analysis (ILCA; Jiang, 2019) approach to estimating attributes for cognitive diagnosis.

Usage

```
ILCA(dat, Q, seed.num = 5)
```

Arguments

dat	A required binary item response matrix.
Q	A required binary item and attribute association matrix.
seed.num	seed number; Default = 5.

Value

Estimated attribute profiles.

Author(s)

Zhehan Jiang, Peking University

References

Jiang, Z. (2019). Using the iterative latent-class analysis approach to improve attribute accuracy in diagnostic classification models. *Behavior research methods*, 1-10.

Examples

```
## Not run:
ILCA(sim10GDINA$simdat, sim10GDINA$simQ)

## End(Not run)
```

indlogLik *Extract log-likelihood for each individual*

Description

Extract individual log-likelihood.

Usage

```
indlogLik(object, ...)
```

Arguments

object	GDINA object
...	additional arguments

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ

fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
iL <- indlogLik(fit)
iL[1:6,]

## End(Not run)
```

indlogPost *Extract log posterior for each individual*

Description

Extract individual log posterior.

Usage

```
indlogPost(object, ...)
```

Arguments

object	GDINA object
...	additional arguments

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
iP <- indlogPost(fit)
iP[1:6,]

## End(Not run)
```

`itemfit` *Item fit statistics*

Description

Calculate item fit statistics (Chen, de la Torre, & Zhang, 2013) and draw heatmap plot for item pairs. For polytomous response data and sequential models, the log odds is calculated by dichotomizing the data by a cutoff (default:>0), transformed correlation is based on the raw data.

Usage

```
itemfit(
  GDINA.obj,
  person.sim = "post",
  p.adjust.methods = "holm",
  cor.use = "pairwise.complete.obs",
  seq.cut = 0,
  digits = 4,
  N.resampling = NULL,
  randomseed = 123456
)

## S3 method for class 'itemfit'
extract(object, what, ...)

## S3 method for class 'itemfit'
summary(object, ...)
```

Arguments

`GDINA.obj`	An estimated model object of class `GDINA`
`person.sim`	Simulate expected responses from the posterior or based on EAP, MAP and MLE estimates.
`p.adjust.methods`	p-values for the proportion correct (mean response), transformed correlation, and log-odds ratio can be adjusted for multiple comparisons at test and item level. This is conducted using `p.adjust` function in **stats**, and therefore all

	adjustment methods supported by `p.adjust` can be used, including `"holm"`, `"hochberg"`, `"hommel"`, `"bonferroni"`, `"BH"` and `"BY"`. See `p.adjust` for more details. `"holm"` is the default.
`cor.use`	how to deal with missing values when calculating correlations? This argument will be passed to `use` when calling `stats::cor`.
`seq.cut`	the cutoff for dichotomizing the data for sequential models (default=0). A response that is great than `seq.cut` is converted to 1; otherwise 0.
`digits`	How many decimal places in each number? The default is 4.
`N.resampling`	the sample size of resampling. By default, it is the maximum of 1e+5 and ten times of current sample size.
`randomseed`	random seed; This is used to make sure the results are replicable. The default random seed is 123456.
`object`	objects of class `itemfit` for various S3 methods
`what`	argument for S3 method `extract` indicating what to extract; It can be `"p"` for proportion correct statistics, `"r"` for transformed correlations, `logOR` for log odds ratios and `"maxitemfit"` for maximum statistics for each item.
`...`	additional arguments

Value

an object of class `itemfit` consisting of several elements that can be extracted using method `extract`. Components that can be extracted include:

p the proportion correct (mean) statistics, adjusted and unadjusted p values for each item

r the transformed correlations, adjusted and unadjusted p values for each item pair

logOR the log odds ratios, adjusted and unadjusted p values for each item pair

maxitemfit the maximum proportion correct, transformed correlation, and log-odds ratio for each item with associated item-level adjusted p-values

Methods (by generic)

- `extract(itemfit)`: extract various elements from `itemfit` objects
- `summary(itemfit)`: print summary information

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Jimmy de la Torre, The University of Hong Kong

References

Chen, J., de la Torre, J., & Zhang, Z. (2013). Relative and Absolute Fit Evaluation in Cognitive Diagnosis Modeling. *Journal of Educational Measurement, 50*, 123-140.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ

mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")
mod1
itmfit <- itemfit(mod1)

# Print "test-level" item fit statistics
# p-values are adjusted for multiple comparisons
# for proportion correct, there are J comparisons
# for log odds ratio and transformed correlation,
# there are J*(J-1)/2 comparisons

itmfit

# The following gives maximum item fit statistics for
# each item with item level p-value adjustment
# For each item, there are J-1 comparisons for each of
# log odds ratio and transformed correlation
summary(itmfit)

# use extract to extract various components
extract(itmfit,"r")

mod2 <- GDINA(dat,Q,model="DINA")
itmfit2 <- itemfit(mod2)
#misfit heatmap
plot(itmfit2)
itmfit2

## End(Not run)
```

---

itemfitPD *Item fit statistics from the power-divergence family*

Description

Calculate item fit statistics from the power-divergence family

Usage

```
itemfitPD(
  GDINA.obj,
  lambda = 2/3,
  bootstrap = FALSE,
  R = 1000,
  Stone = FALSE,
```

```
  init.parm = FALSE,
  p.adjust.method = "holm",
  person.sim = "post",
  cores = 2,
  digits = 4,
  bound = 1e-10,
  seed = 123456
)
```

Arguments

GDINA.obj	Object containing a model fitted with the GDINA::GDINA function.
lambda	Numeric; parameter for the power-divergence fit statistic.
bootstrap	Logical; whether parametric bootstrap should be used.
R	Integer; number of replicates in the bootstrap procedure if used.
Stone	Logical; whether Stone indices should be computed (only available if bootstrap = TRUE).
init.parm	Logical; whether the estimated item parameters are used in the estimation of the bootstrap replications.
p.adjust.method	p-values can be adjusted for multiple comparisons at item level. This is conducted using p.adjust function in **stats**, and therefore all adjustment methods supported by p.adjust can be used, including "holm", "hochberg", "hommel", "bonferroni", "BH" and "BY". See p.adjust for more details. "holm" is the default.
person.sim	Character; how to simulate attribute profiles in the bootstrap replications.
cores	Integer; number of cores for parallelization during bootstrap.
digits	Integer; number of decimal digits to report.
bound	Numeric; minimum possible value for probabilities.
seed	random seed.

Value

an object of class itemfitPD consisting of several elements including:

X2 Chi square statistics, adjusted and unadjusted p values for each item

G2 G square statistics, adjusted and unadjusted p values for each item

PD PD statistics, adjusted and unadjusted p values for each item

time time used for the computation

Author(s)

Pablo Najera Universidad Pontificia Comillas <pnajera@comillas.edu>

Wenchao Ma University of Minnesota <wma@umn.edu>

References

Najera, P., Ma, W., Sorrel, M. A. and Abad, F. J. (2025). Assessing Item-Level Fit for the Sequential G-DINA Model.*Behaviormetrika*.

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ

mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")
mod1
PDfit <- itemfitPD(mod1)
PDfit

dat <- sim21seqDINA$simdat
Q <- sim21seqDINA$simQ
sDINA <- GDINA(dat,Q,model="DINA",sequential = TRUE)
PDfit <- itemfitPD(sDINA)
PDfit
PDfit <- itemfitPD(sDINA, bootstrap = TRUE, Stone = TRUE, cores = 10)
PDfit

## End(Not run)
```

---

itemparm *extract item parameters (deprecated)*

Description

This function has been deprecated; use `coef` instead.

Usage

```
itemparm(
  object,
  what = c("catprob", "gs", "delta", "rrum", "itemprob", "LCprob"),
  withSE = FALSE,
  SE.type = 2,
  digits = 4,
  ...
)

## S3 method for class 'GDINA'
itemparm(
  object,
  what = c("catprob", "gs", "delta", "rrum", "itemprob", "LCprob"),
  withSE = FALSE,
```

```
  SE.type = 2,
  digits = 4,
  ...
)
```

Arguments

object	estimated GDINA object returned from GDINA
what	what to show.
withSE	show standard errors or not?
SE.type	Type of standard errors.
digits	how many decimal places for the output?
...	additional arguments

References

Philipp, M., Strobl, C., de la Torre, J., & Zeileis, A.(2017). On the estimation of standard errors in cognitive diagnosis models. *Journal of Educational and Behavioral Statistics, 43*, 88-115.

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
# deprecated
itemparm(fit)
coef(fit)

## End(Not run)
```

LC2LG *Transformation between latent classes and latent groups*

Description

This function gives the equivalent latent classes which have the same category success probabilities for each category or item.

Usage

```
LC2LG(Q, sequential = FALSE, att.str = NULL)
```

Arguments

Q	A required $J \times K$ binary Q-matrix. J represents test length and K represents the number of attributes of this test. Entry 1 at row j and column k represents the k^{th} attribute is measured by item j, and 0 means item j does not measure attribute k.
sequential	logical; whether the Q-matrix is a Qc-matrix for sequential models?
att.str	attribute structure. See GDINA for details.

Value

An item or category by latent class matrix. In the G-DINA model, if item j measures Kj attributes, 2^K latent classes can be combined into 2^{Kj} latent groups. This matrix gives which latent group each of 2^K latent classes belongs to for each item.

Author(s)

Wenchao Ma, The University of Alabama, <wenchao.ma@ua.edu>
Jimmy de la Torre, The University of Hong Kong

Examples

```
attributepattern(3)

q <- matrix(scan(text = "0 1 0 1 0 1 1 1 0"),ncol = 3)
q
LC2LG(Q = q)
```

MCmodel *Multiple-choice models*

Description

This function estimates the multiple-choice DINA model (de la Torre, 2009).

Usage

```
MCmodel(
  dat,
  Qc,
  model = "MCDINA",
  key = NULL,
  group = NULL,
  conv.crit = 0.001,
  maxitr = 2000,
  conv.type = "pr",
  SE = FALSE
)
```

Arguments

dat	A required $N \times J$ data matrix of N examinees to J items. Values must be 1, 2,... representing nominal categories. Missing values are currently not allowed.
Qc	A required category and attribute association matrix. The first column gives the item number, which must be numeric (i.e., 1,2,...) and match the number of column in the data. The second column indicates the coded category of each item. The number in the second column must match with the number in the data, but if a category is not coded, it should not be included in the Q-matrix. Entry 1 indicates that the attribute is measured by the category, and 0 otherwise. Note that the MC-DINA model assumes that the category with the largest number of 1s is the key and that the coded distractors should allow to assign examinees uniquely.
model	MCDINA only currently. Other MC models may be incorporated.
key	a numeric vector giving the key of each item. See Examples. NULL by default indicating the coded category requiring the largest number of 1s is the key.
group	Group membership vector if a multiple group model is considered. It must only contain whole numbers and start from 1. The length must be equal to the number of rows of the data.
conv.crit	The convergence criterion for max absolute change in conv.type for two consecutive iterations.
maxitr	The maximum iterations allowed.
conv.type	convergence criteria; Can be pr or LL, indicating category response function, or -2 times log-likelihood,respectively.
SE	logical; estimating standard error of item parameters? Default is FALSE.

Value

an object of class MCmodel with the following components:

prob.parm A list of success probabilities for each reduced latent class on each item (IRF)

prob.se A list of standard errors of item parameters

attribute A list of estimated attribute profiles including EAP, MLE and MAP estimates.

testfit A list of test fit statistics including deviance, number of parameters, AIC and BIC

R expected # of individuals in each latent group choosing each option

lik posterior probability

itr Total # of iterations

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

De La Torre, J. (2009). A cognitive diagnosis model for cognitively based multiple-choice options. *Applied Psychological Measurement, 33*, 163–183.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

See Also

GDINA for G-DINA model

Examples

```
## Not run:
 # check the format of the data
 # Entry 0 is not allowed
 head(sim10MCDINA$simdat)

 #---------------------------------
 # check the format of the Q-matrix
 #---------------------------------
 # Take item 1 as an example:
 # category 2 has a q-vector (1,0,0)
 # category 1 has a q-vector (0,1,0)
 # category 4 has a q-vector (1,1,0)
 # category 3 is not included in the Q-matrix because it is not coded
 # the order of the coded categories in the Q-matrix doesn't matter

 sim10MCDINA$simQ
  #     Item coded cat A1 A2 A3
  #        1         2  1  0  0
  #        1         1  0  1  0
  #        1         4  1  1  0
  #...
 est <- MCmodel(sim10MCDINA$simdat,sim10MCDINA$simQ)
 est
 est$testfit

 #--------------------------------------
 # Distractors involving more attributes
 #--------------------------------------
 # some distractors may involve attributes that are not invovled by the key option
 # this is not allowed by the "original" MC-DINA (de la Torre, 2009) but is allowed
 # in the current implementation

 # Users need to specify the key for each item to appropriate handle such an issue
 # Note item 1 below: category 1 is the key (as indicated in the key argument below)
 # The distractor (category 4) involves an attribute not included by the key option

 Qc <- matrix(c(1, 1, 0, 1, 1,
                1, 2, 0, 1, 0,
                1, 3, 1, 0, 0,
                1, 4, 1, 0, 1,
                2, 1, 1, 0, 0,
                2, 3, 1, 1, 0,
                2, 2, 1, 1, 1,
                3, 4, 1, 1, 1,
                3, 2, 1, 1, 0,
                3, 3, 0, 1, 1,
                4, 1, 0, 1, 1,
```

```
                4, 2, 0, 0, 1,
                5, 1, 1, 0, 0,
                6, 3, 0, 1, 0,
                7, 2, 0, 0, 1,
                8, 4, 1, 0, 0,
                9, 1, 0, 1, 0,
                10, 4, 0, 0, 1),ncol = 5,byrow = TRUE)

 est2 <- MCmodel(sim10MCDINA2$simdat,Qc, key = c(1,2,4,1,1,3,2,4,1,4))
 est2
 est2$prob.parm
 est2$testfit
 est2$attribute


 ##############################
 # a multiple group model
 ##############################
est <- MCmodel(sim10MCDINA$simdat, sim10MCDINA$simQ, group = rep(1:2, 1500))
# log posterior of different groups
est$lik$logprior


## End(Not run)
```

---

modelcomp *Item-level model comparison using Wald, LR or LM tests*

Description

This function evaluates whether the saturated G-DINA model can be replaced by reduced CDMs without significant loss in model data fit for each item using the Wald test, likelihood ratio (LR) test or Lagrange multiplier (LM) test. For Wald test, see de la Torre (2011), de la Torre and Lee (2013), Ma, Iaconangelo and de la Torre (2016) and Ma & de la Torre (2018) for details. For LR test and a two-step LR approximation procedure, see Sorrel, de la Torre, Abad, and Olea (2017), Ma (2017) and Ma & de la Torre (2019). For LM test, which is only applicable for DINA, DINO and ACDM, see Sorrel, Abad, Olea, de la Torre, and Barrada (2017). This function also calculates the dissimilarity between the reduced models and the G-DINA model, which can be viewed as a measure of effect size (Ma, Iaconangelo & de la Torre, 2016).

Usage

```
modelcomp(
  GDINA.obj = NULL,
  method = "Wald",
  items = "all",
  p.adjust.methods = "holm",
  models = c("DINA", "DINO", "ACDM", "LLM", "RRUM"),
  decision.args = list(rule = "largestp", alpha.level = 0.05, adjusted = FALSE),
```

```
  DS = FALSE,
  Wald.args = list(SE.type = 2, varcov = NULL),
  LR.args = list(LR.approx = FALSE),
 LM.args = list(reducedMDINA = NULL, reducedMDINO = NULL, reducedMACDM = NULL, SE.type =
    2)
)

## S3 method for class 'modelcomp'
extract(
  object,
  what = c("stats", "pvalues", "adj.pvalues", "df", "DS", "selected.model"),
  digits = 4,
  ...
)

## S3 method for class 'modelcomp'
summary(object, ...)
```

Arguments

GDINA.obj	An estimated model object of class GDINA
method	method for item level model comparison; can be wald, LR or LM.
items	a vector of items to specify the items for model comparsion
p.adjust.methods	adjusted p-values for multiple hypothesis tests. This is conducted using p.adjust function in **stats**, and therefore all adjustment methods supported by p.adjust can be used, including "holm", "hochberg", "hommel", "bonferroni", "BH" and "BY". See p.adjust for more details. "holm" is the default, indicating the Holm method.
models	a vector specifying which reduced CDMs are possible reduced CDMs for each item. The default is "DINA","DINO","ACDM","LLM",and "RRUM".
decision.args	a list of options for determining the most appropriate models including (1) rule can be either "simpler" or "largestp". See details; (2) alpha.level for the nominal level of decision; and (3) adjusted can be either TRUE or FALSE indicating whether the decision is based on p value (adjusted = FALSE) or adjusted p values.
DS	whether dissimilarity index should be calculated? FALSE is the default.
Wald.args	a list of options for Wald test including (1) SE.type giving the type of covariance matrix for the Wald test; by default, it uses outer product of gradient based on incomplete information matrix; (2) varcov for user specified variance-covariance matrix. If supplied, it must be a list, giving the variance covariance matrix of success probability for each item or category. The default is NULL, in which case, the estimated variance-covariance matrix from the GDINA function is used.
LR.args	a list of options for LR test including for now only LR.approx, which is either TRUE or FALSE, indicating whether a two-step LR approximation is implemented or not.

LM.args	a list of options for LM test including reducedMDINA, reducedMDINO, and reducedMACDM for DINA, DINO and ACDM estimates from the GDINA function; SE.type specifies the type of covariance matrix.
object	object of class modelcomp for various S3 methods
what	argument for S3 method extract indicating what to extract; It can be "wald" for wald statistics, "wald.p" for associated p-values, "df" for degrees of freedom, and "DS" for dissimilarity between G-DINA and other CDMs.
digits	How many decimal places in each number? The default is 4.
...	additional arguments

Details

After the test statistics for each reduced CDM were calculated for each item, the reduced models with p values less than the pre-specified alpha level were rejected. If all reduced models were rejected for an item, the G-DINA model was used as the best model; if at least one reduced model was retained, two diferent rules can be implemented for selecting the best model specified in argument decision.args:

(1) when rule="simpler",

If (a) the DINA or DINO model was one of the retained models, then the DINA or DINO model with the larger p value was selected as the best model; but if (b) both DINA and DINO were rejected, the reduced model with the largest p value was selected as the best model for this item. Note that when the p-values of several reduced models were greater than 0.05, the DINA and DINO models were preferred over the A-CDM, LLM, and R-RUM because of their simplicity.

(2) When rule="largestp" (default),

The reduced model with the largest p-values is selected as the most appropriate model.

Value

an object of class modelcomp. Elements that can be extracted using extract method include

stats Wald or LR statistics

pvalues p-values associated with the test statistics

adj.pvalues adjusted p-values

df degrees of freedom

DS dissimilarity between G-DINA and other CDMs

Methods (by generic)

- extract(modelcomp): extract various elements from modelcomp objects
- summary(modelcomp): print summary information

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Miguel A. Sorrel, Universidad Autonoma de Madrid Jimmy de la Torre, The University of Hong Kong

References

de la Torre, J., & Lee, Y. S. (2013). Evaluating the wald test for item-level comparison of saturated and reduced models in cognitive diagnosis. *Journal of Educational Measurement, 50*, 355-373.

Ma, W., Iaconangelo, C., & de la Torre, J. (2016). Model similarity, model selection and attribute classification. *Applied Psychological Measurement, 40*, 200-217.

Ma, W. (2017). *A Sequential Cognitive Diagnosis Model for Graded Response: Model Development, Q-Matrix Validation,and Model Comparison. Unpublished doctoral dissertation.* New Brunswick, NJ: Rutgers University.

Ma, W., & de la Torre, J. (2019). Category-Level Model Selection for the Sequential G-DINA Model. *Journal of Educational and Behavioral Statistics*. 44, 61-82.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Sorrel, M. A., Abad, F. J., Olea, J., de la Torre, J., & Barrada, J. R. (2017). Inferential Item-Fit Evaluation in Cognitive Diagnosis Modeling. *Applied Psychological Measurement, 41,* 614-631.

Sorrel, M. A., de la Torre, J., Abad, F. J., & Olea, J. (2017). Two-Step Likelihood Ratio Test for Item-Level Model Comparison in Cognitive Diagnosis Models. *Methodology, 13*, 39-47.

See Also

GDINA, autoGDINA

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
# --- GDINA model ---#
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
fit

###################
#
# Wald test
#
###################

w <- modelcomp(fit)
w
# wald statistics
extract(w,"stats")
#p values
extract(w,"pvalues")
# selected models
extract(w,"selected.model")
#########################
#
# LR and Two-step LR test
#
#########################
```

```
lr <- modelcomp(fit,method = "LR")
lr
TwostepLR <- modelcomp(fit,items =c(6:10),method = "LR",LR.args = list(LR.approx = TRUE))
TwostepLR

#########################
#
# LM test
#
#########################

dina <- GDINA(dat = dat, Q = Q, model = "DINA")
dino <- GDINA(dat = dat, Q = Q, model = "DINO")
acdm <- GDINA(dat = dat, Q = Q, model = "ACDM")
lm <- modelcomp(method = "LM",LM.args=list(reducedMDINA = dina,
reducedMDINO = dino, reducedMACDM  = acdm))
lm



## End(Not run)
```

`modelfit` *Model fit statistics*

Description

Calculate various absolute model-data fit statistics

Usage

```
modelfit(GDINA.obj, CI = 0.9, ItemOnly = FALSE)
```

Arguments

`GDINA.obj`	An estimated model object of class `GDINA`
`CI`	numeric value from 0 to 1 indicating the range of the confidence interval for RMSEA. Default returns the 90% interval.
`ItemOnly`	should joint attribute distribution parameters be considered? Default = FALSE. See Ma (2019).

Details

Various model-data fit statistics including M2 statistic for G-DINA model with dichotmous responses (Liu, Tian, & Xin, 2016; Hansen, Cai, Monroe, & Li, 2016) and for sequential G-DINA model with graded responses (Ma, 2020). It also calculates SRMSR and RMSEA2.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Hansen, M., Cai, L., Monroe, S., & Li, Z. (2016). Limited-information goodness-of-fit testing of diagnostic classification item response models. *British Journal of Mathematical and Statistical Psychology. 69,* 225–252.

Liu, Y., Tian, W., & Xin, T. (2016). An Application of M2 Statistic to Evaluate the Fit of Cognitive Diagnostic Models. *Journal of Educational and Behavioral Statistics, 41*, 3-26.

Ma, W. (2020). Evaluating the fit of sequential G-DINA model using limited-information measures. *Applied Psychological Measurement, 44*, 167-181.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Maydeu-Olivares, A. (2013). Goodness-of-Fit Assessment of Item Response Theory Models. *Measurement, 11*, 71-101.

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod1 <- GDINA(dat = dat, Q = Q, model = "DINA")
modelfit(mod1)

## End(Not run)
```

`monocheck` *This function checks if monotonicity is violated*

Description

If mastering an additional attribute lead to a lower probabilities of success, the monotonicity is violated.

Usage

```
monocheck(object, strict = FALSE)
```

Arguments

`object`	object of class `GDINA`
`strict`	whether a strict monotonicity is checked?

Value

a logical vector for each item or category indicating whether the monotonicity is violated (TRUE) or not (FALSE)

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ


mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")
check <- monocheck(mod1)
check
mod2 <- GDINA(dat = dat, Q = Q, model = "GDINA",mono.constraint = check)
check2 <- monocheck(mod2)
check2

## End(Not run)
```

---

npar *Calculate the number of parameters*

Description

Calculate the number of parameters for GDINA estimates. Returned the total number of parameters, the number of item parameters and the number parameters of joint attribute distribution.

Usage

```
npar(object, ...)
```

Arguments

object	GDINA object
...	additional arguments

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ

fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
npar(fit)

## End(Not run)
```

`pairwiseDIF` *Pairwise post hoc DIF analysis*

Description

Conduct pairwise Wald follow-up tests after omnibus DIF analysis with three or more groups. This function can also be used for DIF detection based on the Wald test by specifying the studied (potentially DIF) items and anchor items manually.

The input can be a `dif` object returned by `dif()`, in which case DIF items are selected using adjusted omnibus p-values, or raw data plus user-specified DIF items and anchor items.

For DIF detection, the data are rearranged so that anchor items appear once and DIF items are duplicated once for each observed group. For example, if Item 3 is flagged as DIF in a three-group analysis and Items 1 and 2 are not, the refit is arranged as Item 1, Item 2, Item 3 (Group 1), Item 3 (Group 2), and Item 3 (Group 3).

The Wald test is used for comparison of item parameters across all pairs of groups for each DIF item. The p-values are adjusted for multiple comparisons.

The returned object stores this mapping in `posthoc.rearrangement`, which records the refit position, original item number, item label, item type, and group label for each row of the posthoc GDINA calibration. `plot()` function can be used to draw grouped bar chart for DIF items.

Usage

```
pairwiseDIF(
  object = NULL,
  dat = NULL,
  Q = NULL,
  group = NULL,
  model = "GDINA",
  sequential = FALSE,
  dif.items = NULL,
  anchor.items = NULL,
  alpha.level = 0.05,
  p.adjust.methods = "holm",
  SE.type = NULL,
  ...
)
```

Arguments

`object`	an object returned by `dif()`.
`dat`	item responses from two or more groups; missing data need to be coded as `NA`.
`Q`	Q-matrix specifying the association between items and attributes.
`group`	a factor or a vector indicating the group each individual belongs to.
`model`	model for each item.

sequential	Logical; whether a sequential model is fit to the data. Default is FALSE.
dif.items	which items are subject to pairwise DIF follow-up.
anchor.items	optional anchor items. If omitted, all non-DIF items are treated as shared across groups.
alpha.level	adjusted omnibus p-value cutoff used to flag DIF items when object is supplied.
p.adjust.methods	adjusted p-values for pairwise Wald tests within each item.
SE.type	Type of standard error estimation methods for the Wald test.
...	arguments passed to GDINA() for the final post hoc refit.

Value

A pairwiseDIF object with key elements including:

- test: a data frame of pairwise Wald test results with columns for item, group pair, Wald statistic, degrees of freedom, raw p-value, and adjusted p-value.
- dif.items: numeric indices of items included in pairwise DIF follow-up.
- anchor.items: numeric indices of items treated as shared (non-DIF) in the final post hoc refit.
- group.labels: observed group labels used in pairwise comparisons.
- posthoc.rearrangement: a data frame describing how original items were rearranged for refit (refit position, original item number, item label, item type, and group information).
- posthoc.fit: the fitted GDINA object from the final post hoc calibration.
- posthoc.config: the internal item/group configuration aligned with the refit design matrix.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

See Also

dif

Examples

```
## Not run:

set.seed(123456)
N <- 500
Q <- sim30GDINA$simQ
gs <- matrix(.2,ncol = 2, nrow = nrow(Q))
# By default, individuals are simulated from uniform distribution
# and deltas are simulated randomly
sim1 <- simGDINA(N,Q,gs.parm = gs,model="DINA")
sim2 <- simGDINA(N,Q,gs.parm = gs,model=c(rep("DINA",nrow(Q)-1),"DINO"))
sim3 <- simGDINA(N,Q,gs.parm = gs,model="DINA")
dat <- rbind(extract(sim1,"dat"),extract(sim2,"dat"),extract(sim3,"dat"))
```

```
gr <- rep(c("G1","G2","G3"),each=N)

# DIF using Wald test - omnibus test
dif.wald <- dif(dat, Q, group=gr, method = "Wald")
dif.wald
# pairwise comparison between all pair of groups
dif.pair = pairwiseDIF(dif.wald)
dif.pair
# draw plot to show the DIF
plot(dif.pair, withSE = TRUE)

## End(Not run)
```

`personparm` *calculate person (incidental) parameters*

Description

Function to calculate various person attribute parameters, including `"EAP"`, `"MAP"`, and `"MLE"`, for EAP, MAP and MLE estimates of attribute patterns (see Huebner & Wang, 2011), `"mp"` for marginal mastery probabilities, and `"HO"` for higher-order ability estimates if a higher-order model is fitted. See `GDINA` for examples.

Usage

```
personparm(object, what = c("EAP", "MAP", "MLE", "mp", "HO"), digits = 4, ...)
```

Arguments

`object`	estimated GDINA object returned from `GDINA`
`what`	what to extract; It can be `"EAP"`, `"MAP"`, and `"MLE"`, for EAP, MAP and MLE estimates of attribute patterns, and `"mp"` for marginal mastery probabilities, and `"HO"` for higher-order ability estimates if a higher-order model is fitted.
`digits`	number of decimal places.
`...`	additional arguments

Author(s)

Wenchao Ma, The University of Alabama, <wenchao.ma@ua.edu>
Jimmy de la Torre, The University of Hong Kong

References

Huebner, A., & Wang, C. (2011). A note on comparing examinee classification methods for cognitive diagnosis models. *Educational and Psychological Measurement, 71*, 407-419.

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
# EAP
head(personparm(fit))
# MAP
head(personparm(fit, what = "MAP"))

## End(Not run)
```

`plot.GDINA` *Create plots for GDINA estimates*

Description

Create various plots for GDINA estimates

Usage

```
## S3 method for class 'GDINA'
plot(
  x,
  what = "IRF",
  item = "all",
  withSE = FALSE,
  SE.type = 2,
  person = 1,
  att.names = NULL,
  ...
)
```

Arguments

`x`	model object of class `GDINA`
`what`	type of plot. Can be `"IRF"` for item/category response function plot, or `"mp"` for mastery probabilities for individuals.
`item`	A scalar or vector specifying the item(s) for IRF plots.
`withSE`	logical; Add error bar (estimate - SE, estimate + SE) to the IRF plots?
`SE.type`	How is SE estimated. By default, it's based on OPG using incomplete information.
`person`	A scalar or vector specifying the number of individuals for mastery plots.
`att.names`	Optional; a vector for attribute names.
`...`	additional arguments

See Also

GDINA, autoGDINA

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")
#plot item response functions for item 10
plot(mod1, item = 10)
plot(mod1, what = "IRF", item = 10,withSE = TRUE)

# plot mastery probabilities for individuals 4 and 10
plot(mod1, what = "mp", person = c(4,10))
plot(mod1, what = "mp", person = c(4,10,15),
att.names = c("addition","subtraction","multiplication"))

## End(Not run)
```

---

plot.itemfit *Item fit plots*

Description

Create plots of bivariate heatmap for item fit

Usage

```
## S3 method for class 'itemfit'
plot(x, type = "all", adjusted = TRUE, ...)
```

Arguments

x	model object of class itemfit
type	type of heatmap plot
adjusted	logical; plot adjusted or unadjusted p-values?
...	additional arguments

See Also

GDINA, itemfit

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ

fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
ift <- itemfit(fit)
# plot the adjusted p values for log odds or transformed correlation
plot(ift)
# plot unadjusted p values for log odds
plot(ift,adjusted = FALSE, type = "logOR")

## End(Not run)
```

`plot.pairwiseDIF` *Grouped bar plots for pairwise DIF posthoc analysis*

Description

Create grouped bar charts of group-specific item/category response probabilities for DIF items identified by `pairwiseDIF()`.

Usage

```
## S3 method for class 'pairwiseDIF'
plot(x, item = "all", withSE = FALSE, SE.type = 2, ...)
```

Arguments

`x`	model object of class `pairwiseDIF`
`item`	A scalar or vector specifying the DIF item(s) to plot.
`withSE`	logical; Add error bar (estimate - SE, estimate + SE) to the plots?
`SE.type`	How is SE estimated. By default, it's based on OPG using incomplete information.
`...`	additional arguments

See Also

`pairwiseDIF`, `dif`

plot.Qval *Mesa plot for Q-matrix validation*

Description

The mesa plot was first proposed by de la Torre and Ma (2016) for graphically illustrating the best q-vector(s) for each item. The q-vector on the edge of the mesa is likely to be the best q-vector.

Usage

```
## S3 method for class 'Qval'
plot(
  x,
  item,
  type = "best",
  no.qvector = 10,
  data.label = TRUE,
  eps = "auto",
  original.q.label = TRUE,
  auto.ylim = TRUE,
  ...
)
```

Arguments

x	model object of class Qvalidation
item	a vector specifying which item(s) the plots are drawn for
type	types of the plot. It can be "best" or "all". If "best", for all q-vectors requiring the same number of attributes, only the one with the largest PVAF is plotted, which means K_j q-vectors are plotted; If "all", all q-vectors will be plotted.
no.qvector	the number of q vectors that need to be plotted when type="all". The default is 10, which means the 10 q vectors with the largest PVAFs are plotted.
data.label	logical; To show data label or not?
eps	the cutoff for PVAF. If not NULL, it must be a value between 0 and 1. A horizontal line will be drawn accordingly.
original.q.label	logical; print the label showing the original q-vector or not?
auto.ylim	logical; create y range automatically or not?
...	additional arguments passed to plot function

References

de la Torre, J., & Ma, W. (2016, August). Cognitive diagnosis modeling: A general framework approach and its implementation in R. A Short Course at the Fourth Conference on Statistical Methods in Psychometrics, Columbia University, New York.

See Also

Qval, autoGDINA

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
Q[1,] <- c(0,1,0)
mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")
out <- Qval(mod1,eps = 0.9)
item <- c(1,2,10)
plot(out,item=item,data.label=FALSE,type="all")
plot(out,item=10,type="best",eps=0.95)
plot(out,item=10,type="all",no.qvector=6)

## End(Not run)
```

Qval *Q-matrix validation*

Description

Q-matrix validation for the (sequential) G-DINA model based on PVAF (de la Torre & Chiu, 2016; Najera, Sorrel, & Abad, 2019; Najera et al., 2020), stepwise Wald test (Ma & de la Torre, 2020) or mesa plot (de la Torre & Ma, 2016). All these methods are suitable for dichotomous and ordinal response data. If too many modifications are suggested based on the default PVAF method, you are suggested to try the stepwise Wald test method, iterative procedures or predicted cutoffs. You should always check the mesa plots for further examination.

Usage

```
Qval(
  GDINA.obj,
  method = "PVAF",
  iter = "none",
  eps = 0.95,
  digits = 4,
  wald.args = list(),
  iter.args = list(empty.att = FALSE, max.iter = 150, verbose = FALSE)
)

## S3 method for class 'Qval'
extract(object, what = c("sug.Q", "varsigma", "PVAF", "eps", "Q"), ...)

## S3 method for class 'Qval'
summary(object, ...)
```

Arguments

GDINA.obj	an estimated model object of class GDINA
method	which Q-matrix validation method is used? Can be either "PVAF" or "wald".
iter	implement the method iteratively? Can be "none" for non-iterative validation (by default), "test", "test.att", or "item" (Najera et al., 2020).
eps	cutoff value for PVAF from 0 to 1. Default = 0.95. Note that it can also be -1, indicating the predicted cutoff based on Najera, Sorrel, and Abad (2019).
digits	how many decimal places in each number? The default is 4.
wald.args	a list of arguments for the stepwise Wald test method.
	SE.type type of covariance matrix for the Wald test
	alpha.level alpha level for the wald test
	GDI it can be 0, 1 or 2; 0 means GDI is not used to choose the attribute - when more than one attributes are significant, the one with the largest p-value will be selected; GDI=1 means the attribute with the largest GDI will be selected; GDI=2 means the q-vector with the largest GDI will be selected.
	verbose print detailed information or not?
	stepwise TRUE for stepwise approach and FALSE for forward approach
iter.args	a list of arguments for the iterative implementation.
	empty.att can a Q-matrix with an empty attribute (i.e., measured by no items) be provided? Default is FALSE
	max.iter maximum number of iterations. Default is 150
	verbose print information after each iteration? Default is FALSE
object	Qval objects for S3 methods
what	argument for S3 method extract indicating what to extract; It can be "sug.Q" for suggested Q-matrix, "Q" for original Q-matrix, "varsigma" for varsigma index, and "PVAF" for PVAF.
...	additional arguments

Value

An object of class Qval. Elements that can be extracted using extract method include:

sug.Q suggested Q-matrix

Q original Q-matrix

varsigma varsigma index

PVAF PVAF

Methods (by generic)

- extract(Qval): extract various elements from Qval objects
- summary(Qval): print summary information

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Miguel A. Sorrel, Universidad Autónoma de Madrid Jimmy de la Torre, The University of Hong Kong

References

de la Torre, J. & Chiu, C-Y. (2016). A General Method of Empirical Q-matrix Validation. *Psychometrika, 81*, 253-273.

de la Torre, J., & Ma, W. (2016, August). Cognitive diagnosis modeling: A general framework approach and its implementation in R. A Short Course at the Fourth Conference on Statistical Methods in Psychometrics, Columbia University, New York.

Ma, W., & de la Torre, J. (2020). An empirical Q-matrix validation method for the sequential G-DINA model. *British Journal of Mathematical and Statistical Psychology, 73*, 142-163.

Najera, P., Sorrel, M. A., & Abad, F.J. (2019). Reconsidering cutoff points in the general method of empirical Q-matrix validation. *Educational and Psychological Measurement, 79*, 727-753.

Najera, P., Sorrel, M. A., de la Torre, J., & Abad, F. J. (2020). Improving robustness in Q-matrix validation using an iterative and dynamic procedure. *Applied Psychological Measurement*.

See Also

GDINA

Examples

```
## Not run:
################################
#
# Binary response
#
################################
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
Q[10,] <- c(0,1,0)

# Fit the G-DINA model
mod1 <- GDINA(dat = dat, Q = Q, model = "GDINA")

# Q-validation using de la Torre and Chiu's method
pvaf <- Qval(mod1,method = "PVAF",eps = 0.95)
pvaf
extract(pvaf,what = "PVAF")
#See also:
extract(pvaf,what = "varsigma")
extract(pvaf,what = "sug.Q")

# Draw mesa plots using the function plot

plot(pvaf,item=10)
```

```
#The stepwise Wald test
stepwise <- Qval(mod1,method = "wald")
stepwise
extract(stepwise,what = "PVAF")
#See also:
extract(stepwise,what = "varsigma")
extract(stepwise,what = "sug.Q")

#Set eps = -1 to determine the cutoff empirically
pvaf2 <- Qval(mod1,method = "PVAF",eps = -1)
pvaf2

#Iterative procedure (test-attribute level)
pvaf3 <- Qval(mod1, method = "PVAF", eps = -1,
              iter = "test.att", iter.args = list(verbose = 1))
pvaf3

################################
#
# Ordinal response
#
################################
seq.est <- GDINA(sim20seqGDINA$simdat,sim20seqGDINA$simQ, sequential = TRUE)
stepwise <- Qval(seq.est, method = "wald")

## End(Not run)
```

`realdata_ECPE` *Examination for the Certificate of Proficiency in English (ECPE) data*

Description

Examination for the Certificate of Proficiency in English (ECPE) data (the grammar section) has been used in Henson and Templin (2007), Templin and Hoffman (2013), Feng, Habing, and Huebner (2014), and Templin and Bradshaw (2014), among others.

Usage

```
realdata_ECPE
```

Format

A list of responses and Q-matrix with components:

`dat` Responses of 2922 examinees to 28 items.

`Q` The 28×3 Q-matrix.

Details

The data consists of responses of 2922 examinees to 28 items involving 3 attributes. Attribute 1 is morphosyntactic rules, Attribute 2 is cohesive rules and Attribute 3 is lexical rules.

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Feng, Y., Habing, B. T., & Huebner, A. (2014). Parameter estimation of the reduced RUM using the EM algorithm. *Applied Psychological Measurement, 38*, 137-150.

Henson, R. A., & Templin, J. (2007, April). Large-scale language assessment using cognitive diagnosis models. Paper presented at the annual meeting of the National Council for Measurement in Education in Chicago, Illinois.

Templin, J., & Bradshaw, L. (2014). Hierarchical diagnostic classification models: A family of models for estimating and testing attribute hierarchies. *Psychometrika, 79*, 317-339.

Templin, J., & Hoffman, L. (2013). Obtaining diagnostic classification model estimates using Mplus. *Educational Measurement: Issues and Practice, 32*, 37-50.

Examples

```
## Not run:
mod1 <- GDINA(realdata_ECPE$dat,realdata_ECPE$Q)
mod1
summary(mod1)

mod2 <- GDINA(realdata_ECPE$dat,realdata_ECPE$Q,model="RRUM")
mod2
anova(mod1,mod2)
# You may compare the following results with Feng, Habing, and Huebner (2014)
coef(mod2,"rrum")

# G-DINA with hierarchical structure
# see Templin & Bradshaw, 2014
ast <- att.structure(list(c(3,2),c(2,1)),K=3)

est.gdina2 <- GDINA(realdata_ECPE$dat,realdata_ECPE$Q,model = "GDINA",
                    control = list(conv.crit = 1e-6),
                    att.str = list(c(3,2),c(2,1)))
# see Table 7 in Templin & Bradshaw, 2014
summary(est.gdina2)

## End(Not run)
```

---

realdata_Tatsuoka1990 *Tatsuoka's fraction subtraction data*

Description

Fraction Subtraction data (Tatsuoka, 1990, 2002) consists of responses of 536 examinees to 20 items measuring 8 attributes.

Usage

```
realdata_Tatsuoka1990
```

Format

A list of responses and Q-matrix with components:

`dat` responses of 536 examinees to 20 items

`Q` The 20×8 Q-matrix

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26. Tatsuoka, K. K. (1990). Toward an integration of item-response theory and cognitive error diagnosis. In N. Frederiksen, R. Glaser, A. Lesgold, & M. Shafto (Eds.), Diagnostic monitoring of skill and knowledge acquisition (pp. 453-488). Hillsdale, NJ: Erlbaum. Tatsuoka, C. (2002). Data analytic methods for latent partially ordered classification models. *Journal of the Royal Statistical Society, Series C, Applied Statistics, 51*, 337-350.

Examples

```
## Not run:
mod1 <- GDINA(realdata_Tatsuoka1990$dat,realdata_Tatsuoka1990$Q,model="DINA")
mod1
summary(mod1)
# Higher order model
mod2 <- GDINA(realdata_Tatsuoka1990$dat,
realdata_Tatsuoka1990$Q,model="DINA",
att.dist="higher.order")
mod2
anova(mod1,mod2)

## End(Not run)
```

rowMatch *Count the frequency of a row vector in a data frame*

Description

Count the frequency of a row vector in a data frame

Usage

```
rowMatch(df, vec = NULL)
```

Arguments

df	a data frame or matrix
vec	the vector for matching

Value

count the number of vector vec in the data frame

row.no row numbers of the vector vec in the data frame

Examples

```
df <- data.frame(V1=c(1L,2L),V2=LETTERS[1:3],V3=rep(1,12))
rowMatch(df,c(2,"B",1))
```

score *Score function*

Description

Calculate score function for each dichotomous item or each nonzero category for polytomous items Only applicable to saturated model ofr joint attribute distribution

Usage

```
score(object, parm = "delta")
```

Arguments

object	an object of class GDINA
parm	Either delta or prob indicating score function for delta parameters and success probabily parameters

Value

a list where elements give the score functions for each item or category

Examples

```
## Not run:
dat <- sim10GDINA$simdat
Q <- sim10GDINA$simQ
fit <- GDINA(dat = dat, Q = Q, model = "GDINA")
score(fit)

## End(Not run)
```

---

sim10GDINA *Simulated data (10 items, G-DINA model)*

Description

Simulated data, Q-matrix and item parameters for a 10-item test with 3 attributes.

Usage

```
sim10GDINA
```

Format

A list with components:

`simdat` simulated responses of 1000 examinees

`simQ` artificial Q-matrix

`simItempar` artificial item parameters (probability of success for each latent group)

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

sim10MCDINA *Simulated data (10 items, MC-DINA model)*

Description

Simulated data, Q-matrix and item parameters for a 10-item test measuring 3 attributes.

Usage

```
sim10MCDINA
```

Format

A list with components:

`simdat` simulated responses of 3000 examinees

`simQ` artificial Q-matrix

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

sim10MCDINA2 *Simulated data (10 items, MC-DINA model)*

Description

Simulated data, Q-matrix and item parameters for a 10-item test measuring 5 attributes.

Usage

```
sim10MCDINA2
```

Format

A list with components:

`simdat` simulated responses of 3000 examinees

`simQ` artificial Q-matrix

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

---

sim20seqGDINA *Simulated data (20 items, sequential G-DINA model)*

Description

Simulated data, Qc-matrix and item parameters for a 20-item test measuring 5 attributes.

Usage

```
sim20seqGDINA
```

Format

A list with components:

`simdat` simulated polytomous responses of 2000 examinees

`simQ` artificial Qc-matrix

`simItempar` artificial item parameters (category level probability of success for each latent group)

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

sim21seqDINA *Simulated data (21 items, sequential DINA model)*

Description

Simulated data, and Qc-matrix for a 21-item test measuring 5 attributes.

Usage

```
sim21seqDINA
```

Format

A list with components:

`simdat` simulated responses of 2000 examinees

`simQ` artificial Qc-matrix

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

sim30DINA *Simulated data (30 items, DINA model)*

Description

Simulated data, Q-matrix and item parameters for a 30-item test measuring 5 attributes.

Usage

```
sim30DINA
```

Format

A list with components:

`simdat` simulated responses of 1000 examinees

`simQ` artificial Q-matrix

`simItempar` artificial item parameters (probability of success for each latent group)

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

`sim30GDINA` *Simulated data (30 items, G-DINA model)*

Description

Simulated data, Q-matrix and item parameters for a 30-item test measuring 5 attributes.

Usage

```
sim30GDINA
```

Format

A list with components:

`simdat` simulated responses of 1000 examinees

`simQ` artificial 30×5 Q-matrix

`simItempar` artificial item parameters(probability of success for each latent group)

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

sim30pGDINA *Simulated data (30 items, polytomous G-DINA model)*

Description

Simulated data, Q-matrix and item parameters for a 30-item test measuring 5 attributes.

Usage

```
sim30pGDINA
```

Format

A list with components:

`simdat` simulated responses of 3000 examinees

`simQ` artificial Q-matrix

`simItempar` artificial item parameters(probability of success for each latent group)

simDTM *Simulating data for diagnostic tree model*

Description

Data generation for diagnostic tree model

Usage

```
simDTM(N, Qc, gs.parm, Tmatrix, red.delta = NULL, att.gr = NULL)
```

Arguments

`N`	sample size
`Qc`	Association matrix between attributes (column) and PSEUDO items (row); The first column is item number and the second column is the pseudo item number for each item. If a pseudo item has more than one nonzero categories, more than one rows are needed.
`gs.parm`	the same as the gs.parm in simGDINA function in the GDINA package. It is a list with the same number of elements as the number of rows in the Qc matrix
`Tmatrix`	mapping matrix showing the relation between the OBSERVED responses (rows) and the PSEDUO items (columns); The first column gives the observed responses.
`red.delta`	reduced delta parameters using logit link function
`att.gr`	attribute group indicator

Examples

```
## Not run:
K=5
g=0.2
item.no <- rep(1:6,each=4)
# the first node has three response categories: 0, 1 and 2
node.no <- rep(c(1,1,2,3),6)
Q1 <- matrix(0,length(item.no),K)
Q2 <- cbind(7:(7+K-1),rep(1,K),diag(K))
for(j in 1:length(item.no)) {
  Q1[j,sample(1:K,sample(3,1))] <- 1
}
Qc <- rbind(cbind(item.no,node.no,Q1),Q2)
Tmatrix.set <- list(cbind(c(0,1,2,3,3),c(0,1,2,1,2),c(NA,0,NA,1,NA),c(NA,NA,0,NA,1)),
cbind(c(0,1,2,3,4),c(0,1,2,1,2),c(NA,0,NA,1,NA),c(NA,NA,0,NA,1)),
cbind(c(0,1),c(0,1)))
Tmatrix <- Tmatrix.set[c(1,1,1,1,1,1,rep(3,K))]
sim <- simDTM(N=2000,Qc=Qc,gs.parm=matrix(0.2,nrow(Qc),2),Tmatrix=Tmatrix)
est <- DTM(dat=sim$dat,Qc=Qc,Tmatrix = Tmatrix)

## End(Not run)
```

`simGDINA` *Data simulation based on the G-DINA models*

Description

Simulate responses based on the G-DINA model (de la Torre, 2011) and sequential G-DINA model (Ma & de la Torre, 2016), or CDMs subsumed by them, including the DINA model, DINO model, ACDM, LLM and R-RUM. Attributes can be simulated from uniform, higher-order or multivariate normal distributions, or be supplied by users. See `Examples` and `Details` for how item parameter specifications. See the help page of `GDINA` for model parameterizations.

Usage

```
simGDINA(
  N,
  Q,
  gs.parm = NULL,
  delta.parm = NULL,
  catprob.parm = NULL,
  model = "GDINA",
  sequential = FALSE,
  no.bugs = 0,
  gs.args = list(type = "random", mono.constraint = TRUE),
  design.matrix = NULL,
  linkfunc = NULL,
  att.str = NULL,
```

```
  attribute = NULL,
  att.dist = "uniform",
  item.names = NULL,
  higher.order.parm = list(theta = NULL, lambda = NULL),
  mvnorm.parm = list(mean = NULL, sigma = NULL, cutoffs = NULL),
  att.prior = NULL,
  digits = 4
)

## S3 method for class 'simGDINA'
extract(
  object,
 what = c("dat", "Q", "attribute", "catprob.parm", "delta.parm", "higher.order.parm",
    "mvnorm.parm", "LCprob.parm"),
  ...
)
```

Arguments

N	Sample size.
Q	A required matrix; The number of rows occupied by a single-strategy dichotomous item is 1, by a polytomous item is the number of nonzero categories, and by a mutiple-strategy dichotomous item is the number of strategies. The number of column is equal to the number of attributes if all items are single-strategy dichotomous items, but the number of attributes + 2 if any items are polytomous or have multiple strategies. For a polytomous item, the first column represents the item number and the second column indicates the nonzero category number. For a multiple-strategy dichotomous item, the first column represents the item number and the second column indicates the strategy number. For binary attributes, 1 denotes the attributes are measured by the items and 0 means the attributes are not measured. For polytomous attributes, non-zero elements indicate which level of attributes are needed. See `Examples`.
gs.parm	A matrix or data frame for guessing and slip parameters. The number of rows occupied by a dichotomous item is 1, and by a polytomous item is the number of nonzero categories. The number of columns must be 2, where the first column represents the guessing parameters (or $P(0)$), and the second column represents slip parameters (or $1 - P(1)$). This may need to be used in conjunction with the argument `gs.args`.
delta.parm	A list of delta parameters of each latent group for each item or category. This may need to be used in conjunction with the argument `delta.args`.
catprob.parm	A list of success probabilities of each latent group for each non-zero category of each item. See `Examples` and `Details` for more information.
model	A character vector for each item or nonzero category, or a scalar which will be used for all items or nonzero categories to specify the CDMs. The possible options include `"GDINA"`,`"DINA"`,`"DINO"`,`"ACDM"`,`"LLM"`, `"RRUM"`, `"MSDINA"` and `"UDF"`. When `"UDF"`, indicating user defined function, is specified for any item, `delta.parm` must be specified, as well as options `design.matrix` and `linkfunc` in argument `delta.args`.

`sequential` logical; `TRUE` if the sequential model is used for polytomous responses simulation, and `FALSE` if there is no polytomously scored items.

`no.bugs` the number of bugs (or misconceptions) for the `SISM` model. Note that bugs must be given in the last no.bugs columns.

`gs.args` a list of options when `gs.parm` is specified. It consists of two components:

- `type` How are the delta parameters for ACDM, LLM, RRUM generated? It can be either `"random"` or `"equal"`. `"random"` means the delta parameters are simulated randomly, while `"equal"` means that each required attribute contributes equally to the probability of success (P), logit(P) or log(P) for ACDM, LLM and RRUM, respectively. See `Details` for more information.
- `mono.constraint` A vector for each item/category or a scalar which will be used for all items/categories to specify whether monotonicity constraints should be satisfied if the generating model is the G-DINA model. Note that this is applicable only for the G-DINA model when `gs.parm` is used. For ACDM, LLM and RRUM, monotonicity constraints are always satisfied and therefore this argument is ignored.

`design.matrix` a list of design matrices; Its length must be equal to the number of items (or nonzero categories for sequential models).

`linkfunc` a vector of link functions for each item/category; It can be `"identity"`,`"log"` or `"logit"`. Only applicable when when `delta.parm` or `catprob.parm` are provided.

`att.str` attribute structure. `NULL`, by default, means there is no structure. Attribute structure needs be specified as a list - which will be internally handled by `att.structure` function. It can also be a matrix giving all permissible attribute profiles.

`attribute` optional user-specified person attributes. It is a $N \times K$ matrix or data frame. If this is not supplied, attributes are simulated from a distribution specified in `att.dist`.

`att.dist` A string indicating the distribution for attribute simulation. It can be `"uniform"`, `"higher.order"`, `"mvnorm"` or `"categorical"` for uniform, higher-order, multivariate normal and categorical distributions, respectively. The default is the uniform distribution. To specify structural parameters for the higher-order and multivariate normal distributions, see `higher.order.parm` and `mvnorm.parm`, respectively. To specify the probabilities for the categorical distribution, use `att.prior` argument.

`item.names` A vector giving the name of items or categories. If it is `NULL` (default), items are named as "Item 1", "Item 2", etc.

`higher.order.parm`
A list specifying parameters for higher-order distribution for attributes if `att.dist=higher.order`. Particularly, `theta` is a vector of length N representing the higher-order ability for each examinee. and `lambda` is a $K \times 2$ matrix. Column 1 gives the slopes for the higher-order model and column 2 gives the intercepts. See `GDINA` for the formulations of the higher-order models.

`mvnorm.parm` a list of parameters for multivariate normal attribute distribution. `mean` is a vector of length K specifying the mean of multivariate normal distribution; and `sigma` is a positive-definite symmetric matrix specifying the variance-covariance matrix. `cutoffs` is a vector giving the cutoff for each attribute. See `Examples`.

att.prior	probability for each attribute pattern. Order is the same as that returned from attributepattern(Q = Q). This is only applicable when att.dist="categorical".
digits	How many decimal places in each number? The default is 4.
object	object of class simGDINA for method extract
what	argument for S3 method extract indicating what to extract
...	additional arguments

Details

Item parameter specifications in simGDINA:

Item parameters can be specified in one of three different ways.

The first and probably the easiest way is to specify the guessing and slip parameters for each item or nonzero category using gs.parm, which is a matrix or data frame for $P(\boldsymbol{\alpha}_{lj}^* = 0)$ and $1 - P(\boldsymbol{\alpha}_{lj}^* = 1)$ for all items for dichotomous items and $S(\boldsymbol{\alpha}_{ljh}^* = 0)$ and $1 - S(\boldsymbol{\alpha}_{ljh}^* = 1)$ for all nonzero categories for polytomous items. Note that $1 - P(\boldsymbol{\alpha}_{lj}^* = 0) - P(\boldsymbol{\alpha}_{lj}^* = 1)$ or $1 - S(\boldsymbol{\alpha}_{lj}^* = 0) - S(\boldsymbol{\alpha}_{lj}^* = 1)$ must be greater than 0. For generating ACDM, LLM, and RRUM, delta parameters are generated randomly if type="random", or in a way that each required attribute contributes equally, as in Ma, Iaconangelo, & de la Torre (2016) if type="equal". For ACDM, LLM and RRUM, generated delta parameters are always positive, which implies that monotonicity constraints are always satisfied. If the generating model is the G-DINA model, mono.constraint can be used to specify whether monotonicity constraints should be satisfied.

The second way of simulating responses is to specify success probabilities (i.e., $P(\boldsymbol{\alpha}_{lj}^*)$ or $S(\boldsymbol{\alpha}_{ljh}^*)$) for each nonzero category of each item directly using the argument catprob.parm. If an item or category requires K_j^* attributes, $2^{K_j^*}$ success probabilities need to be provided. catprob.parm must be a list, where each element gives the success probabilities for nonzero category of each item. Note that success probabilities cannot be negative or greater than one.

The third way is to specify delta parameters for data simulation. For DINA and DINO model, each nonzero category requires two delta parameters. For ACDM, LLM and RRUM, if a nonzero category requires K_j^* attributes, $K_j^* + 1$ delta parameters need to be specified. For the G-DINA model, a nonzero category requiring K_j^* attributes has $2^{K_j^*}$ delta parameters. It should be noted that specifying delta parameters needs to ascertain the derived success probabilities are within the $[0, 1]$ interval.

Please note that you need to specify item parameters in ONLY one of these three ways. If gs.parm is specified, it will be used regardless of the inputs in catprob.parm and delta.parm. If gs.parm is not specified, simGDINA will check if delta.parm is specified; if yes, it will be used for data generation. if both gs.parm and delta.parm are not specified, catprob.parm is used for data generation.

Value

an object of class simGDINA. Elements that can be extracted using method extract include:

dat simulated item response matrix

Q Q-matrix

attribute A $N \times K$ matrix for inviduals' attribute patterns

catprob.parm a list of non-zero category success probabilities for each latent group

delta.parm a list of delta parameters

higher.order.parm Higher-order parameters

mvnorm.parm multivariate normal distribution parameters

LCprob.parm A matrix of item/category success probabilities for each latent class

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu> Jimmy de la Torre, The University of Hong Kong

References

Chiu, C.-Y., Douglas, J. A., & Li, X. (2009). Cluster analysis for cognitive diagnosis: Theory and applications. *Psychometrika, 74*, 633-665.

de la Torre, J. (2011). The generalized DINA model framework. *Psychometrika, 76*, 179-199.

de la Torre, J., & Douglas, J. A. (2004). Higher-order latent trait models for cognitive diagnosis. *Psychometrika, 69*, 333-353.

Haertel, E. H. (1989). Using restricted latent class models to map the skill structure of achievement items. *Journal of Educational Measurement, 26*, 301-321.

Hartz, S. M. (2002). A bayesian framework for the unified model for assessing cognitive abilities: Blending theory with practicality (Unpublished doctoral dissertation). University of Illinois at Urbana-Champaign.

Junker, B. W., & Sijtsma, K. (2001). Cognitive assessment models with few assumptions, and connections with nonparametric item response theory. *Applied Psychological Measurement, 25*, 258-272.

Ma, W., & de la Torre, J. (2016). A sequential cognitive diagnosis model for polytomous responses. *British Journal of Mathematical and Statistical Psychology. 69,* 253-275.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Ma, W., Iaconangelo, C., & de la Torre, J. (2016). Model similarity, model selection and attribute classification. *Applied Psychological Measurement, 40*, 200-217.

Maris, E. (1999). Estimating multiple classification latent class models. *Psychometrika, 64*, 187-212.

Templin, J. L., & Henson, R. A. (2006). Measurement of psychological disorders using cognitive diagnosis models. *Psychological Methods, 11*, 287-305.

Examples

```
## Not run:
#####################################################
#                     Example 1                     #
#             Data simulation (DINA)                #
#####################################################
N <- 500
```

```
Q <- sim30GDINA$simQ
J <- nrow(Q)
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))

# Simulated DINA model; to simulate G-DINA model
# and other CDMs, change model argument accordingly

sim <- simGDINA(N,Q,gs.parm = gs,model = "DINA")

# True item success probabilities
extract(sim,what = "catprob.parm")

# True delta parameters
extract(sim,what = "delta.parm")

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")

#####################################################
#                     Example 2                     #
#             Data simulation (RRUM)                #
#####################################################
N <- 500
Q <- sim30GDINA$simQ
J <- nrow(Q)
gs <- data.frame(guess=rep(0.2,J),slip=rep(0.2,J))
# Simulated RRUM
# deltas except delta0 for each item will be simulated
# randomly subject to the constraints of RRUM
sim <- simGDINA(N,Q,gs.parm = gs,model = "RRUM")

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")

#####################################################
#                     Example 3                     #
#             Data simulation (LLM)                 #
#####################################################
N <- 500
Q <- sim30GDINA$simQ
J <- nrow(Q)
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))
# Simulated LLM
# By specifying type="equal", each required attribute is
# assumed to contribute to logit(P) equally
sim <- simGDINA(N,Q,gs.parm = gs,model = "LLM",gs.args = list (type="equal"))
#check below for what the equal contribution means
```

```
extract(sim,what = "delta.parm")

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")

#####################################################
#                   Example 4                       #
#          Data simulation (all CDMs)               #
#####################################################

set.seed(12345)

N <- 500
Q <- sim10GDINA$simQ
J <- nrow(Q)
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))
# Simulated different CDMs for different items
models <- c("GDINA","DINO","DINA","ACDM","LLM","RRUM","GDINA","LLM","RRUM","DINA")
sim <- simGDINA(N,Q,gs.parm = gs,model = models,gs.args = list(type="random"))

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")

#####################################################
#                   Example 5a                      #
#          Data simulation (all CDMs)               #
#  using probability of success in list format      #
#####################################################

# success probabilities for each item need to be provided in list format as follows:
# if item j requires Kj attributes, 2^Kj success probabilities
# need to be specified
# e.g., item 1 only requires 1 attribute
# therefore P(0) and P(1) should be specified;
# similarly, item 10 requires 3 attributes,
# P(000),P(100),P(010)...,P(111) should be specified;
# the latent class represented by each element can be obtained
# by calling attributepattern(Kj)
itemparm.list <- list(item1=c(0.2,0.9),
                      item2=c(0.1,0.8),
                      item3=c(0.1,0.9),
                      item4=c(0.1,0.3,0.5,0.9),
                      item5=c(0.1,0.1,0.1,0.8),
                      item6=c(0.2,0.9,0.9,0.9),
                      item7=c(0.1,0.45,0.45,0.8),
                      item8=c(0.1,0.28,0.28,0.8),
                      item9=c(0.1,0.4,0.4,0.8),
```

```
                    item10=c(0.1,0.2,0.3,0.4,0.4,0.5,0.7,0.9))
set.seed(12345)
N <- 500
Q <- sim10GDINA$simQ
# When simulating data using catprob.parm argument,
# it is not necessary to specify model and type
sim <- simGDINA(N,Q,catprob.parm = itemparm.list)

####################################################
#                   Example 5b                     #
#          Data simulation (all CDMs)              #
#  using probability of success in list format     #
#  attribute has a linear structure                #
####################################################

est <- GDINA(sim10GDINA$simdat,sim10GDINA$simQ,att.str = list(c(1,2),c(2,3)))
# design matrix
# link function
# item probabilities
ip <- extract(est,"itemprob.parm")
sim <- simGDINA(N=500,sim10GDINA$simQ,catprob.parm = ip,
design.matrix = dm,linkfunc = lf,att.str = list(c(1,2),c(2,3)))


####################################################
#                   Example 6a                     #
#            Data simulation (all CDMs)            #
#      using delta parameters in list format       #
####################################################

delta.list <- list(c(0.2,0.7),
                   c(0.1,0.7),
                   c(0.1,0.8),
                   c(0.1,0.7),
                   c(0.1,0.8),
                   c(0.2,0.3,0.2,0.1),
                   c(0.1,0.35,0.35),
                   c(-1.386294,0.9808293,1.791759),
                   c(-1.609438,0.6931472,0.6),
                   c(0.1,0.1,0.2,0.3,0.0,0.0,0.1,0.1))

model <- c("GDINA","GDINA","GDINA","DINA","DINO","GDINA","ACDM","LLM","RRUM","GDINA")
N <- 500
Q <- sim10GDINA$simQ
sim <- simGDINA(N,Q,delta.parm = delta.list, model = model)
####################################################
#                   Example 6b                     #
#          Data simulation (all CDMs)              #
#  using delta parameters in list format           #
#  attribute has a linear structure                #
####################################################

est <- GDINA(sim10GDINA$simdat,sim10GDINA$simQ,att.str = list(c(1,2),c(2,3)))
```

```
# design matrix
# link function
# item probabilities
ip <- extract(est,"delta.parm")
sim <- simGDINA(N=500,sim10GDINA$simQ,delta.parm =  d,
design.matrix = dm,linkfunc = lf,att.str = list(c(1,2),c(2,3)))

####################################################
#                   Example 7                      #
#      Data simulation (higher order DINA model)   #
####################################################

Q <- sim30GDINA$simQ
gs <- matrix(0.1,nrow(Q),2)
N <- 500
set.seed(12345)
theta <- rnorm(N)
K <- ncol(Q)
lambda <- data.frame(a=rep(1,K),b=seq(-2,2,length.out=K))
sim <- simGDINA(N,Q,gs.parm = gs, model="DINA", att.dist = "higher.order",
                higher.order.parm = list(theta = theta,lambda = lambda))

####################################################
#                   Example 8                      #
#      Data simulation (higher-order CDMs)         #
####################################################

Q <- sim30GDINA$simQ
gs <- matrix(0.1,nrow(Q),2)
models <- c(rep("GDINA",5),
            rep("DINO",5),
            rep("DINA",5),
            rep("ACDM",5),
            rep("LLM",5),
            rep("RRUM",5))
N <- 500
set.seed(12345)
theta <- rnorm(N)
K <- ncol(Q)
lambda <- data.frame(a=runif(K,0.7,1.3),b=seq(-2,2,length.out=K))
sim <- simGDINA(N,Q,gs.parm = gs, model=models, att.dist = "higher.order",
                higher.order.parm = list(theta = theta,lambda = lambda))


####################################################
#                   Example 9                      #
#      Data simulation (higher-order model)        #
#  using the multivariate normal threshold model   #
####################################################


# See Chiu et al., (2009)
```

```
N <- 500
Q <- sim10GDINA$simQ
K <- ncol(Q)
gs <- matrix(0.1,nrow(Q),2)
cutoffs <- qnorm(c(1:K)/(K+1))
m <- rep(0,K)
vcov <- matrix(0.5,K,K)
diag(vcov) <- 1
simMV <- simGDINA(N,Q,gs.parm = gs, att.dist = "mvnorm",
                  mvnorm.parm=list(mean = m, sigma = vcov,cutoffs = cutoffs))

####################################
#          Example 10              #
#        Simulation using          #
#      user-specified att structure#
####################################

# --- User-specified attribute structure ----#
Q <- sim30GDINA$simQ
K <- ncol(Q)
# divergent structure A1->A2->A3;A1->A4->A5;A1->A4->A6
diverg <- list(c(1,2),
               c(2,3),
               c(1,4),
               c(4,5))
struc <- att.structure(diverg,K)

# data simulation
N <- 1000
# data simulation
gs <- matrix(0.1,nrow(Q),2)
simD <- simGDINA(N,Q,gs.parm = gs,
                   model = "DINA",att.dist = "categorical",att.prior = struc$att.prob)


#####################################################
#                   Example 11                      #
#                Data simulation                    #
#  (GDINA with monotonicity constraints)            #
#####################################################

set.seed(12345)

N <- 500
Q <- sim30GDINA$simQ
J <- nrow(Q)
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))
# Simulated different CDMs for different items
sim <- simGDINA(N,Q,gs.parm = gs,model = "GDINA",gs.args=list(mono.constraint=TRUE))

# True item success probabilities
extract(sim,what = "catprob.parm")
```

```
# True delta parameters
extract(sim,what = "delta.parm")

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")

#####################################################
#                   Example 12                      #
#                Data simulation                    #
# (Sequential G-DINA model - polytomous responses) #
#####################################################

set.seed(12345)

N <- 2000
# restricted Qc matrix
Qc <- sim20seqGDINA$simQ
#total number of categories
J <- nrow(Qc)
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))
# simulate sequential DINA model
simseq <- simGDINA(N, Qc, sequential = TRUE, gs.parm = gs, model = "GDINA")

# True item success probabilities
extract(simseq,what = "catprob.parm")

# True delta parameters
extract(simseq,what = "delta.parm")

# simulated data
extract(simseq,what = "dat")

# simulated attributes
extract(simseq,what = "attribute")


#####################################################
#                   Example 13
#         DINA model Attribute generated using
#             categorical distribution
#####################################################

Q <- sim10GDINA$simQ
gs <- matrix(0.1,nrow(Q),2)
N <- 5000
set.seed(12345)
prior <- c(0.1,0.2,0,0,0.2,0,0,0.5)
sim <- simGDINA(N,Q,gs.parm = gs, model="DINA", att.dist = "categorical",att.prior = prior)
# check latent class sizes
table(sim$att.group)/N
```

```
#####################################################
#                   Example 14
#                  MS-DINA model
#####################################################


Q <- matrix(c(1,1,1,1,0,
1,2,0,1,1,
2,1,1,0,0,
3,1,0,1,0,
4,1,0,0,1,
5,1,1,0,0,
5,2,0,0,1),ncol = 5,byrow = TRUE)
d <- list(
  item1=c(0.2,0.7),
  item2=c(0.1,0.6),
  item3=c(0.2,0.6),
  item4=c(0.2,0.7),
  item5=c(0.1,0.8))

  set.seed(12345)
sim <- simGDINA(N=1000,Q = Q, delta.parm = d,
               model = c("MSDINA","MSDINA","DINA","DINA","DINA","MSDINA","MSDINA"))

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")


#############################################################
#                   Example 15
#  reparameterized SISM model (Kuo, Chen, & de la Torre, 2018)
#  see GDINA function for more details
#############################################################

# The Q-matrix used in Kuo, et al (2018)
# The first four columns are for Attributes 1-4
# The last three columns are for Bugs 1-3
Q <- matrix(c(1,0,0,0,0,0,0,
0,1,0,0,0,0,0,
0,0,1,0,0,0,0,
0,0,0,1,0,0,0,
0,0,0,0,1,0,0,
0,0,0,0,0,1,0,
0,0,0,0,0,0,1,
1,0,0,0,1,0,0,
0,1,0,0,1,0,0,
0,0,1,0,0,0,1,
0,0,0,1,0,1,0,
1,1,0,0,1,0,0,
```

```
1,0,1,0,0,0,1,
1,0,0,1,0,0,1,
0,1,1,0,0,0,1,
0,1,0,1,0,1,1,
0,0,1,1,0,1,1,
1,0,1,0,1,1,0,
1,1,0,1,1,1,0,
0,1,1,1,1,1,0),ncol = 7,byrow = TRUE)

J <- nrow(Q)
N <- 500
gs <- data.frame(guess=rep(0.1,J),slip=rep(0.1,J))

sim <- simGDINA(N,Q,gs.parm = gs,model = "SISM",no.bugs=3)

# True item success probabilities
extract(sim,what = "catprob.parm")

# True delta parameters
extract(sim,what = "delta.parm")

# simulated data
extract(sim,what = "dat")

# simulated attributes
extract(sim,what = "attribute")

## End(Not run)
```

`startGDINA` *Graphical user interface of the GDINA function*

Description

An interactive Shiny application for running GDINA function. See Ma and de la Torre (2019) and de la Torre and Akbay (2019) for tutorials.

Usage

```
startGDINA()
```

Author(s)

Wenchao Ma, The University of Minnesota, <wma@umn.edu>

References

de la Torre, J & Akbay, L. (2019). Implementation of Cognitive Diagnosis Modeling using the GDINA R Package. *Eurasian Journal of Educational Research, 80*, 171-192.

Ma, W., & de la Torre, J. (2019). Digital Module 05: Diagnostic measurement-The G-DINA framework. *Educational Measurement: Issues and Practice, 39*, 114-115.

Ma, W., & de la Torre, J. (2020). GDINA: An R Package for Cognitive Diagnosis Modeling. *Journal of Statistical Software, 93(14)*, 1-26.

Examples

```
## Not run:
library(shiny)
library(shinydashboard)
startGDINA()

## End(Not run)
```

`unique_only` *Unique values in a vector*

Description

Unique values in a vector

Usage

```
unique_only(vec)
```

Arguments

`vec`	a vector

Value

sorted unique values

See Also

unique

Examples

```
vec <- c(4,2,3,5,4,4,4)
unique_only(vec)
# see the difference from unique
unique(vec)

vec <- letters[1:5]
unique_only(vec)
```

---

unrestrQ *Generate unrestricted Qc matrix from an restricted Qc matrix*

Description

Generate unrestricted Qc matrix from an restricted Qc matrix

Usage

```
unrestrQ(Qc)
```

Arguments

Qc	an restricted Qc matrix

Value

an unrestricted Qc matrix

Examples

```
Qc <- sim21seqDINA$simQc
Qc
unrestrQ(Qc)
```

Index

∗ **datasets**
realdata_ECPE, 78
realdata_Tatsuoka1990, 79
sim10GDINA, 82
sim10MCDINA, 83
sim10MCDINA2, 83
sim20seqGDINA, 84
sim21seqDINA, 85
sim30DINA, 85
sim30GDINA, 86
sim30pGDINA, 87

anova, *26*
anova.GDINA *(*GDINA*)*, 26
att.structure, 5
attributepattern, 6
auglag, *31*
autoGDINA, *5*, 7, *36*, *64*, *72*, *75*

bdiagMatrix, 11
bootSE, 12

CA, 13
cbind, *14*
cjoint, 14
ClassRate, 15
CM, 16
coef, *26*, *31*
coef.GDINA *(*GDINA*)*, 26

designmatrix, 17
deviance.GDINA *(*GDINA*)*, 26
dif, *4*, 18, *69*, *73*
DTM, *4*, 22, *36*, *48*

extract, *9*, 24, *26*, *31*
extract.GDINA *(*GDINA*)*, 26
extract.itemfit *(*itemfit*)*, 52
extract.modelcomp *(*modelcomp*)*, 61
extract.Qval *(*Qval*)*, 75
extract.simGDINA *(*simGDINA*)*, 88

GDINA, *4, 5*, *7*, *9, 10*, *13*, *16*, *20*, *23*, 26, *48*, *57*, *60*, *64*, *66*, *70–72*, *77*, *88*, *90*
GDINA-package, 4
GMSCDM, *4*, *23*, *36*, 47

ILCA, 50
indlogLik, 51
indlogLik.GDINA *(*GDINA*)*, 26
indlogPost, 51
indlogPost.GDINA *(*GDINA*)*, 26
itemfit, *4*, *24*, *36*, 52, *72*
itemfitPD, 54
itemparm, 56

LC2LG, 57
logLik.GDINA *(*GDINA*)*, 26

MCmodel, 58
modelcomp, *4*, *7*, *9, 10*, *24*, *36*, 61
modelfit, *4*, *36*, 65
monocheck, *26*, 66

nloptr, *31*
nobs.GDINA *(*GDINA*)*, 26
npar, 67
npar.GDINA *(*GDINA*)*, 26

pairwiseDIF, 68, *73*
personparm, *26*, *31*, 70
personparm.GDINA *(*GDINA*)*, 26
plot, *26*
plot.GDINA, 71
plot.itemfit, 72
plot.pairwiseDIF, 73
plot.Qval, 74

Qval, *4*, *7*, *9, 10*, *24*, *36*, 75, *75*

realdata_ECPE, 78
realdata_Tatsuoka1990, 79
rowMatch, 81

score, 81
sim10GDINA, 82
sim10MCDINA, 83
sim10MCDINA2, 83
sim20seqGDINA, 84
sim21seqDINA, 85
sim30DINA, 85
sim30GDINA, 86
sim30pGDINA, 87
simDTM, 87
simGDINA, *36*, 88
slsqp, *31*
solnp, *31*
startGDINA, *4*, *26*, 100
summary.autoGDINA *(*autoGDINA*)*, 7
summary.dif *(*dif*)*, 18
summary.GDINA *(*GDINA*)*, 26
summary.itemfit *(*itemfit*)*, 52
summary.modelcomp *(*modelcomp*)*, 61
summary.Qval *(*Qval*)*, 75

unique, *101*
unique_only, 101
unrestrQ, 102

vcov.GDINA *(*GDINA*)*, 26