

Package: MKLE (via r-universe)

September 17, 2024

Type Package

Title Maximum Kernel Likelihood Estimation

Version 1.0.1

Author Thomas Jaki

Maintainer Thomas Jaki <thomas.jaki@protonmail.com>

Description Package for fast computation of the maximum kernel likelihood estimator (mkle).

License GPL

NeedsCompilation no

Repository CRAN

Date/Publication 2023-08-21 08:02:38 UTC

Contents

MKLE-package	1
klik	3
mkle	4
mkle.ci	5
opt.bw	6
state	8

Index	9
--------------	----------

MKLE-package	<i>Maximum kernel likelihood estimation</i>
--------------	---

Description

Computes the maximum kernel likelihood estimator using fast fourier transforms.

Details

Package: MKLE
 Type: Package
 Version: 1.01
 Date: 2023-08-21
 License: GPL

The maximum kernel likelihood estimator is defined to be the value $\hat{\theta}$ that maximizes the estimated kernel likelihood based on the general location model,

$$f(x|\theta) = f_0(x - \theta).$$

This model assumes that the mean associated with f_0 is zero which of course implies that the mean of X_i is θ . The kernel likelihood is the estimated likelihood based on the above model using a kernel density estimate, $\hat{f}(\cdot|h, X_1, \dots, X_n)$, and is defined as

$$\hat{L}(\theta|X_1, \dots, X_n) = \prod_{i=1}^n \hat{f}(X_i - (\bar{X} - \theta)|h, X_1, \dots, X_n).$$

The resulting estimator therefore is an estimator of the mean of X_i .

Author(s)

Thomas Jaki

Maintainer: Thomas Jaki <jaki.thomas@gmail.com>

References

Jaki T., West R. W. (2008) Maximum kernel likelihood estimation. *Journal of Computational and Graphical Statistics* Vol. 17(No 4), 976-993.

Silverman, B. W. (1986), *Density Estimation for Statistics and Data Analysis*, Chapman & Hall, 2nd ed.

Examples

```
data(state)
mkle(state$CRIME)
```

klik *Kernel log likelihood*

Description

The function computes the kernel log likelihood for a given $\hat{\theta}$.

Usage

```
klik(delta , data, kde, grid, min)
```

Arguments

delta	the difference of the parameter theta for which the kernel log likelihood will be computed and the sample mean.
data	the data for which the kernel log likelihood will be computed.
kde	an object of the class "density".
grid	the stepsize between the x-values in kde.
min	the smallest x-value in kde.

Details

This function is intended to be called through the function [mkle](#) and is optimized for fast computation.

Value

The log likelihood based on the shifted kernel density estimator.

Author(s)

Thomas Jaki

References

Jaki T., West R. W. (2008) Maximum kernel likelihood estimation. *Journal of Computational and Graphical Statistics* Vol. 17(No 4), 976-993.

See Also

[mkle](#)

Examples

```

data(state)
attach(state)
bw<-2*sd(CRIME)
kdensity<-density(CRIME,bw=bw,kernel="biweight",
                  from=min(CRIME)-2*bw,to=max(CRIME)+2*bw,n=2^12)
min<-kdensity$x[1]
grid<-kdensity$x[2]-min

# finds the kernel log likelihood at the sample mean
klik(0,CRIME, kdensity, grid, min)

```

mkle

Maximum kernel likelihood estimation

Description

Computes the maximum kernel likelihood estimator for a given dataset and bandwidth.

Usage

```

mkle(data,bw=2*sd(data),kernel=c("gaussian", "epanechnikov", "rectangular", "triangular",
                                "biweight", "cosine", "optcosine"),gridsize=2^14)

```

Arguments

data	the data for which the estimator should be found.
bw	the smoothing bandwidth to be used.
kernel	a character string giving the smoothing kernel to be used. This must be one of "gaussian", "rectangular", "triangular", "epanechnikov", "biweight", "cosine" or "optcosine", with default "gaussian". May be abbreviated to a unique prefix (single letter).
gridsize	the number of points at which the kernel density estimator is to be evaluated with 2^{14} as the default.

Details

The default for the bandwidth is $2s$, which is the near-optimal value if a Gaussian kernel is used. If the bandwidth is zero, the sample mean will be returned.

Larger gridsize results in more accurate estimates but also longer computation times. The use of gridsizes between 2^{11} and 2^{20} is recommended.

Value

The maximum kernel likelihood estimator.

Note

[optimize](#) is used for the optimization and [density](#) is used to estimate the kernel density.

Author(s)

Thomas Jaki

References

Jaki T., West R. W. (2008) Maximum kernel likelihood estimation. *Journal of Computational and Graphical Statistics* Vol. 17(No 4), 976-993.

See Also

[klik](#)

Examples

```
data(state)
plot(density(state$CRIME))
abline(v=mean(state$CRIME),col='red')
abline(v=mkle(state$CRIME),col='blue')
```

mkle.ci

Confidence intervals for the maximum kernel likelihood estimator

Description

Computes different confidence intervals for the maximum kernel likelihood estimator for a given dataset and bandwidth.

Usage

```
mkle.ci(data, bw=2*sd(data), alpha=0.1, kernel=c("gaussian", "epanechnikov",
"rectangular", "triangular", "biweight", "cosine", "optcosine"),
method=c("percentile", "wald", "boott"), B=1000, gridsize=2^14)
```

Arguments

data	the data for which the confidence interval should be found.
bw	the smoothing bandwidth to be used.
alpha	the significance level.
kernel	a character string giving the smoothing kernel to be used. This must be one of "gaussian", "rectangular", "triangular", "epanechnikov", "biweight", "cosine" or "optcosine", with default "gaussian", and may be abbreviated to a unique prefix (single letter).

method	a character string giving the type of interval to be used. This must be one of "percentile", "wald" or "boott".
B	number of resamples used to estimate the mean squared error with 1000 as the default.
gridsize	the number of points at which the kernel density estimator is to be evaluated with 2^{14} as the default.

Details

The method can be a vector of strings containing the possible choices.

The bootstrap-t-interval can be very slow for large datasets and a large number of resamples as a two layered resampling is necessary.

Value

A dataframe with the requested intervals.

Author(s)

Thomas Jaki

References

Jaki T., West R. W. (2008) Maximum kernel likelihood estimation. *Journal of Computational and Graphical Statistics* Vol. 17(No 4), 976-993.

Davison, A. C. and Hinkley, D. V. (1997), *Bootstrap Methods and their Applications*, Cambridge Series in Statistical and Probabilistic Mathematics, Cambridge University Press.

See Also

[mkle](#)

Examples

```
data(state)
mkle.ci(state$CRIME,method=c('wald','percentile'),B=100,gridsize=2^11)
```

opt.bw

Optimal bandwidth for the maximum kernel likelihood estimator

Description

Estimates the optimal bandwidth for the maximum kernel likelihood estimator using a Gaussian kernel for a given dataset using the bootstrap.

Usage

```
opt.bw(data, bws=c(sd(data),4*sd(data)), B=1000, gridsize=2^14)
```

Arguments

data	the data for which the optimal bandwidth should be found.
bws	a vector with the upper and lower bound for the bandwidth.
B	number of resamples used to estimate the mean squared error with 1000 as the default.
gridsize	the number of points at which the kernel density estimator is to be evaluated with 2^{14} as the default.

Details

The bandwidth considered fall between one and 4 standard deviations. In addition the mse of the [mkle](#) for a bandwidth of zero will also be included.

The estimation of the optimal bandwidth might take several minutes depending on the number of bootstrap resamples and the gridsize used.

Value

The estimated optimal bandwidth.

Note

The [optimize](#) is used for the optimization.

Author(s)

Thomas Jaki

References

Jaki T., West R. W. (2008) Maximum kernel likelihood estimation. Submitted to *Journal of Computational and Graphical Statistics* Vol. 17(No 4), 976-993.

Davison, A. C. and Hinkley, D. V. (1997), *Bootstrap Methods and their Applications*, Cambridge Series in Statistical and Probabilistic Mathematics, Cambridge University Press.

See Also

[mkle](#)

Examples

```
data(state)
opt.bw(state$CRIME, B=10)
```

state

Violent death in the USA

Description

The dataset gives the number of violent death per 100,000 population per state

Usage

```
data(state)
```

Format

A data frame with 50 observations on the following 2 variables.

STATE a factor with levels AK AL AR AZ CA CO CT DE FL GA HI IA ID IL IN KS KY LA MA MD ME MI MN
MO MS MT NC ND NE NH NJ NM NV NY OH OK OR PA RI SC SD TN TX UT VA VT WA WI WV WY

CRIME a numeric vector

Source

Shapiro, Robert~J. 1998. Statistical Abstract of the United States. 118 edn. U.S. Bureau of the Census.

Examples

```
data(state)
hist(state$CRIME)
mkle(state$CRIME)
```


Index

- * **datasets**
 - state, 8
- * **distribution**
 - klik, 3
- * **htest**
 - mkle.ci, 5
- * **nonparametric**
 - klik, 3
 - mkle, 4
 - mkle.ci, 5
 - opt.bw, 6
- * **package**
 - MKLE-package, 1
- * **univar**
 - mkle, 4

density, 5

klik, 3, 5

MKLE (MKLE-package), 1

mkle, 3, 4, 6, 7

MKLE-package, 1

mkle.ci, 5

opt.bw, 6

optimize, 5, 7

state, 8