Package: MonotonicityTest (via r-universe)

October 28, 2026

Type Package

Author Dylan Huynh [aut, cre]

Maintainer Dylan Huynh <dylanhuynh@utexas.edu>

Title Nonparametric Bootstrap Test for Regression Monotonicity

Version 1.3

Description Implements nonparametric bootstrap tests for detecting monotonicity in regression functions from Hall, P. and Heckman, N. (2000) <doi:10.1214/aos/1016120363> Includes tools for visualizing results using Nadaraya-Watson kernel regression and supports efficient computation with 'C++'. Tutorials and shiny application demo are available at <https://www.laylaparast.com/monotonicitytest> and <https://parastlab.shinyapps.io/MonotonicityTest>.

License GPL

Encoding UTF-8

RoxygenNote 7.3.3

LinkingTo Rcpp, RcppEigen

Imports Rcpp (>= 1.0.13-1), parallel, stats, graphics, ggplot2 (>= 3.0.0), rlang

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation yes

Depends R (>= 3.5.0)

Repository https://cran.r-universe.dev

Date/Publication 2025-11-06 16:40:02 UTC

RemoteUrl https://github.com/cran/MonotonicityTest

RemoteRef HEAD

RemoteSha 411f33808bbc4c81b68dc694389aea2ba90678f2

Contents

create_kernel_plot 2
diabetes 3
monotonicity_test 4

Index **6**

`create_kernel_plot` *Generate Kernel Plot*

Description

Creates a scatter plot of the input vectors X and Y, and overlays a Nadaraya-Watson kernel regression curve using the specified bandwidth.

Usage

```
create_kernel_plot(X, Y, bandwidth = bw.nrd(X) * (length(X)^-0.1), nrows = 4)
```

Arguments

`X`	Vector of x values.
`Y`	Vector of y values.
`bandwidth`	Kernel bandwidth used for the Nadaraya-Watson estimator. Can be a single numeric value or a vector of bandwidths. Default is calculated as `bw.nrd(X) * (length(X) ^ -0.1)`.
`nrows`	Number of rows in the facet grid if multiple bandwidths are provided. Does not do anything if only a single bandwidth value is provided. Default is `4`.

Value

A ggplot object containing the scatter plot(s) with the kernel regression curve(s). If a vector of bandwidths is supplied, the plots are put into a grid using faceting.

References

Nadaraya, E. A. (1964). On estimating regression. *Theory of Probability and Its Applications*, **9**(1), 141–142.

Watson, G. S. (1964). Smooth estimates of regression functions. *Sankhyā: The Indian Journal of Statistics, Series A*, 359-372.

Examples

```
# Example 1: Basic plot on quadratic function
seed <- 42
set.seed(seed)
X <- runif(500)
Y <- X ^ 2 + rnorm(500, sd = 0.1)
plot <- create_kernel_plot(X, Y, bandwidth = bw.nrd(X) * (length(X) ^ -0.1))
```

---

diabetes *A Simulated Diabetes Dataset*

Description

This dataset contains simulated medical measurements for Diabetes and is emulated after data from the Diabetes Prevention Program. Each column represents change in a key metabolic indicators after two years for the placebo group receiving no treatment.

Usage

```
data("diabetes", package="MonotonicityTest")
```

Format

A data frame with 1000 rows and 4 variables:

CLDL Change in low-density lipoprotein (LDL) cholesterol (mg/dL).

GLUCOSE Change in fasting plasma glucose levels (mg/dL).

TRIG Change in triglyceride levels (mg/dL).

HBA1C Change in hemoglobin A1c levels (%).

Examples

```
data("diabetes", package="MonotonicityTest")
names(diabetes)
```

`monotonicity_test` *Perform Monotonicity Test*

Description

Performs a monotonicity test between the vectors X and Y as described in Hall and Heckman (2000). This function uses a bootstrap approach to test for monotonicity in a nonparametric regression setting.

Usage

```
monotonicity_test(
  X,
  Y,
  bandwidth = bw.nrd(X) * (length(X)^-0.1),
  boot_num = 200,
  m = floor(0.05 * length(X)),
  ncores = 1,
  negative = FALSE,
  check_m = FALSE,
  seed = NULL
)
```

Arguments

`X`	Numeric vector of predictor variable values. Must not contain missing or infinite values.
`Y`	Numeric vector of response variable values. Must not contain missing or infinite values.
`bandwidth`	Numeric value for the kernel bandwidth used in the Nadaraya-Watson estimator. Default is calculated as `bw.nrd(X) * (length(X) ^ -0.1)`.
`boot_num`	Integer specifying the number of bootstrap samples. Default is `200`.
`m`	Integer parameter used in the calculation of the test statistic. Corresponds to the minimum window size to calculate the test statistic over or a "smoothing" parameter. Lower values increase the sensitivity of the test to local deviations from monotonicity. Default is `floor(0.05 * length(X))`.
`ncores`	Integer specifying the number of cores to use for parallel processing. Default is `1`.
`negative`	Logical value indicating whether to test for a monotonic decreasing (negative) relationship. Default is `FALSE`.
`check_m`	Boolean value indicating whether to run the test for many different values of `m`. This produces extra plots when calling `plot` and has a marginal impact on performance. Default is `FALSE`.
`seed`	Optional integer for setting the random seed. If NULL (default), the global random state is used.

Details

The test evaluates the following hypotheses:

H_0: The regression function is monotonic

- *Non-decreasing* if `negative = FALSE`
- *Non-increasing* if `negative = TRUE`

H_A: The regression function is not monotonic

Value

A `monotonicity_result` object. Has associated 'print', 'summary', and 'plot' S3 functions.

Note

For large datasets (e.g., $n \geq 6500$) this function may require significant computation time due to having to compute the statistic for every possible interval. Consider reducing `boot_num`, using a subset of the data, or using parallel processing with `ncores` to improve performance.

In addition to this, a minimum of 300 observations is recommended for kernel estimates to be reliable.

References

Hall, P., & Heckman, N. E. (2000). Testing for monotonicity of a regression mean by calibrating for linear functions. *The Annals of Statistics*, **28**(1), 20–39.

Examples

```
# Example 1: Usage on monotonic increasing function
# Generate sample data
seed <- 42
set.seed(seed)

X <- runif(500)
Y <- 4 * X + rnorm(500, sd = 1)
result <- monotonicity_test(X, Y, boot_num = 25, seed = seed)

print(result)

# Example 2: Usage on non-monotonic function
seed <- 42
set.seed(seed)

X <- runif(500)
Y <- (X - 0.5) ^ 2 + rnorm(500, sd = 0.5)
result <- monotonicity_test(X, Y, boot_num = 25, seed = seed)

print(result)
```

Index

∗ **datasets**
diabetes, 3

create_kernel_plot, 2

diabetes, 3

monotonicity_test, 4