

Package: NeutroSplitStripAnalysis (via r-universe)

June 22, 2026

Type Package

Title Neutrosophic Analysis of Split-Plot and Strip-Plot Designs

Version 0.0.1

Maintainer Vinaykumar L.N. <vinaymandya123@gmail.com>

Description Provides methods for Neutrosophic Analysis of Variance (NANOVA) for split-plot and strip-plot experimental designs using interval-valued observations. The package computes neutrosophic sums of squares, mean squares, interval-valued F-statistics, significance tests, and Least Significant Difference (LSD) based multiple comparisons for main plot, sub plot, horizontal factor, vertical factor, and interaction effects. For crisp data, users may provide identical lower and upper response values to obtain results equivalent to classical analysis of variance. The basic idea of neutrosophic statistics is obtained from Smarandache (2014) <<https://fs.unm.edu/NeutrosophicStatistics.pdf>>, while the analysis procedures implemented in this package are newly developed.

License GPL-3

Encoding UTF-8

Imports MASS, stats

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

NeedsCompilation no

Author Boyina Devi Priyanka [aut, ctb], Neethu R.S [aut, ctb], Cini Varghese [aut, ctb], Mohd Harun [aut, ctb], Anindita Datta [aut, ctb], Susheel kumar [aut, ctb], Vinaykumar L.N. [aut, cre]

Repository <https://cran.r-universe.dev>

Date/Publication 2026-06-22 18:30:56 UTC

RemoteUrl <https://github.com/cran/NeutroSplitStripAnalysis>

RemoteRef HEAD

RemoteSha 6ae8d3731692bdf105147d47d7d52c6cfbdd688c

Contents

SplitPlotDnsANOVA	2
StripPlotDnsANOVA	4
Index	6

SplitPlotDnsANOVA *Neutrosophic Analysis of Variance for Split-Plot Designs*

Description

Performs Neutrosophic Analysis of Variance (NANOVA) for split-plot designs using interval-valued observations. The function provides neutrosophic ANOVA tables, interval-valued F-tests, significance tests, and Least Significant Difference (LSD) based multiple comparisons. For crisp data, users may provide identical lower and upper response values to obtain results equivalent to classical split-plot ANOVA.

Usage

```
SplitPlotDnsANOVA(Lower_y, Upper_y, design, alpha = 0.05, verbose = FALSE)
```

Arguments

Lower_y	A matrix containing the lower values of the response variable.
Upper_y	A matrix containing the upper values of the response variable.
design	A data frame containing three columns corresponding to replication, main plot treatments, and sub plot treatments, respectively.
alpha	Significance level used for hypothesis testing and LSD-based multiple comparisons. Default is 0.05.
verbose	Logical. If TRUE, the neutrosophic ANOVA table, significance tests, LSD values, and multiple comparison results are displayed. Default is FALSE.

Value

A list containing:

Split_Plot_NANOVA Neutrosophic ANOVA table containing sources of variation, degrees of freedom, neutrosophic sums of squares, mean squares, F-statistics, and significance levels.

LSD_MainPlot Neutrosophic LSD interval for main plot effects, returned only when the main plot effect is significant.

LSD_SubPlot Neutrosophic LSD interval for sub plot effects, returned only when the sub plot effect is significant.

LSD_Interaction Neutrosophic LSD interval for interaction effects, returned only when the interaction effect is significant.

Comparison_MainPlot Pairwise neutrosophic comparisons among main plot treatment means.

Comparison_SubPlot Pairwise neutrosophic comparisons among sub plot treatment means.

Comparison_Interaction Pairwise neutrosophic comparisons among interaction treatment means.

Examples

```
Lower_y <- matrix(c(
  13.81,13.11,18.16,
  18.54,19.84,28.43,
  11.48,14.33,14.29,
  14.50,15.99,21.19,
  11.65,18.08,17.37,
  11.78,12.46,17.21,
  11.67,11.28,8.65,
  18.81,16.27,21.46,
  11.96,16.15,18.19,
  10.34,11.28,16.91,
  9.08,14.91,11.95,
  11.04,10.80,6.48
), ncol = 3, byrow = TRUE)
```

```
Upper_y <- matrix(c(
  17.19,21.89,23.44,
  22.46,29.16,31.97,
  19.72,22.07,22.71,
  23.30,24.41,27.81,
  18.35,22.92,20.43,
  20.22,19.14,19.39,
  14.13,17.72,18.35,
  21.59,20.73,29.34,
  19.84,24.85,26.81,
  15.46,15.72,20.09,
  17.92,20.09,17.85,
  13.96,13.00,14.52
), ncol = 3, byrow = TRUE)
```

```
Rep <- factor(rep(paste0("R",1:4), each = 9))
MainPlot <- factor(rep(rep(paste0("M",1:3), each = 3), 4))
SubPlot <- factor(rep(paste0("S",1:3), 12))
design <- data.frame(Rep, MainPlot, SubPlot)
```

```
result <- SplitPlotDnsANOVA(Lower_y = Lower_y, Upper_y = Upper_y, design = design,
  alpha = 0.05, verbose = TRUE)
```

StripPlotDnsANOVA *Neutrosophic Analysis of Variance for Strip-Plot Designs*

Description

Performs Neutrosophic Analysis of Variance (NANOVA) for strip-plot designs using interval-valued observations. The function provides neutrosophic ANOVA tables, interval-valued F-tests, significance tests, and Least Significant Difference (LSD) based multiple comparisons for horizontal factors, vertical factors, and their interaction effects. For crisp data, users may provide identical lower and upper response values to obtain results equivalent to classical strip-plot ANOVA.

Usage

```
StripPlotDnsANOVA(Lower_y, Upper_y, design, alpha = 0.05, verbose = FALSE)
```

Arguments

Lower_y	A matrix containing the lower values of the response variable.
Upper_y	A matrix containing the upper values of the response variable.
design	A data frame containing three columns corresponding to replication, horizontal factor treatments, and vertical factor treatments, respectively.
alpha	Significance level used for hypothesis testing and LSD-based multiple comparisons. Default is 0.05.
verbose	Logical. If TRUE, the neutrosophic ANOVA table, significance tests, LSD values, and multiple comparison results are displayed. Default is FALSE.

Value

A list containing:

Strip_Plot_NANOVA Neutrosophic ANOVA table containing sources of variation, degrees of freedom, neutrosophic sums of squares, mean squares, F-statistics, and significance levels.

LSD_Horizontal Neutrosophic LSD interval for horizontal factor effects, returned only when the horizontal factor effect is significant.

LSD_Vertical Neutrosophic LSD interval for vertical factor effects, returned only when the vertical factor effect is significant.

LSD_Interaction Neutrosophic LSD interval for horizontal x vertical interaction effects, returned only when the interaction effect is significant.

Comparison_Horizontal Pairwise neutrosophic comparisons among horizontal factor treatment means.

Comparison_Vertical Pairwise neutrosophic comparisons among vertical factor treatment means.

Comparison_Interaction Pairwise neutrosophic comparisons among horizontal x vertical treatment combinations.

Examples

```
Lower_y <- matrix(c(
  10,12,
  11,13,
  12,14,
  13,15,
  11,12,
  12,13
), nrow = 6, byrow = TRUE)

Upper_y <- matrix(c(
  12,14,
  13,15,
  14,16,
  15,17,
  13,14,
  14,15
), nrow = 6, byrow = TRUE)

# Strip-plot design
# 2 Replications x 3 Horizontal Factors x 2 Vertical Factors
Rep <- factor(rep(c("R1","R2"), each = 6))
Horizontal <- factor(rep(c("H1","H2","H3"), each = 2, times = 2))
Vertical <- factor(rep(c("S1","S2"), times = 6))
design <- data.frame(Rep, Horizontal, Vertical)

result <- StripPlotDnsANOVA(
  Lower_y = Lower_y,
  Upper_y = Upper_y,
  design = design,
  alpha = 0.05,
  verbose = TRUE
)
```

Index

SplitPlotDnsANOVA, [2](#)
StripPlotDnsANOVA, [4](#)