Package: OptimalRerandExpDesigns (via r-universe)

October 7, 2026

Type Package

Title Optimal Rerandomization Experimental Designs

Version 1.1

Date 2021-01-25

Author Adam Kapelner, Michael Sklar, Abba M. Krieger and David Azriel

Maintainer Adam Kapelner <kapelner@qc.cuny.edu>

Description This is a tool to find the optimal rerandomization threshold in non-sequential experiments. We offer three procedures based on assumptions made on the residuals distribution: (1) normality assumed (2) excess kurtosis assumed (3) entire distribution assumed. Illustrations are included. Also included is a routine to unbiasedly estimate Frobenius norms of variance-covariance matrices. Details of the method can be found in ``Optimal Rerandomization via a Criterion that Provides Insurance Against Failed Experiments" Adam Kapelner, Abba M. Krieger, Michael Sklar and David Azriel (2020) <doi:10.48550/arXiv.1905.03337>.

License GPL-3

Depends R (>= 3.2.0), ggplot2 (>= 3.0), momentchi2 (>= 0.1.5), GreedyExperimentalDesign (>= 1.3)

Imports stats

RoxygenNote 7.1.0

URL https://github.com/kapelner/OptimalRerandExpDesigns

NeedsCompilation no

Repository https://cran.r-universe.dev

Date/Publication 2021-01-28 11:50:06 UTC

RemoteUrl https://github.com/cran/OptimalRerandExpDesigns

RemoteRef HEAD

RemoteSha 3c8a64ac4be382adac3f9c7c5333ff19bef0fe59

Contents

complete_randomization_plus_one_min_one . . . 2
complete_randomization_with_forced_balance_plus_one_min_one . . . 3
compute_objective_val_plus_one_min_one_enc . . . 3
frob_norm_sq . . . 4
frob_norm_sq_debiased . . . 5
frob_norm_sq_debiased_times_matrix . . . 5
generate_W_base_and_sort . . . 6
optimal_rerandomization_exact . . . 7
optimal_rerandomization_normality_assumed . . . 9
optimal_rerandomization_tail_approx . . . 10
OptimalRerandExpDesigns . . . 12
plot.optimal_rerandomization_obj . . . 12
plot.W_base_object . . . 13
print.optimal_rerandomization_obj . . . 13
print.W_base_object . . . 14
summary.optimal_rerandomization_obj . . . 14
summary.W_base_object . . . 15

Index **16**

`complete_randomization_plus_one_min_one` *Implements the complete randomization design (CRD) AKA Bernoulli Trial*

Description

Implements the complete randomization design (CRD) AKA Bernoulli Trial

Usage

```
complete_randomization_plus_one_min_one(n, r)
```

Arguments

`n`	number of observations
`r`	number of randomized designs you would like

Value

a matrix where each column is one of the `r` designs

Author(s)

Adam Kapelner

`complete_randomization_with_forced_balance_plus_one_min_one` *Implements the balanced complete randomization design (BCRD)*

Description

Implements the balanced complete randomization design (BCRD)

Usage

```
complete_randomization_with_forced_balance_plus_one_min_one(n, r)
```

Arguments

`n`	number of observations
`r`	number of randomized designs you would like

Value

a matrix where each column is one of the `r` designs

Author(s)

Adam Kapelner

`compute_objective_val_plus_one_min_one_enc` *Returns the objective value given a design vector as well an an objective function. This is code duplication since this is implemented within Java. This is only to be run if...*

Description

Returns the objective value given a design vector as well an an objective function. This is code duplication since this is implemented within Java. This is only to be run if...

Usage

```
compute_objective_val_plus_one_min_one_enc(
  X,
  indic_T,
  objective = "abs_sum_diff",
  inv_cov_X = NULL
)
```

Arguments

X	The n x p design matrix
indic_T	The n-length binary allocation vector
objective	The objective function to use. Default is abs_sum_diff.
inv_cov_X	Optional: the inverse sample variance covariance matrix. Use this argument if you will be doing many calculations since passing this in will cache this data.

Value

A vector of computed objective values.

Author(s)

Adam Kapelner

---

frob_norm_sq *Naive Frobenius Norm Squared*

Description

Compute naive / vanilla squared Frobenius Norm of matrix A

Usage

```
frob_norm_sq(A)
```

Arguments

A	The matrix of interest

Value

The Frobenius Norm of A squared.

Author(s)

Adam Kapelner

`frob_norm_sq_debiased` *Debiased Frobenius Norm Squared Var-Cov matrix*

Description

Compute debiased Frobenius Norm of matrix Sigmahat (Appendix 5.8). Note that for S <= 2, it returns the naive estimate.

Usage

```
frob_norm_sq_debiased(
  Sigmahat,
  s,
  n,
  frob_norm_sq_bias_correction_min_samples = 10
)
```

Arguments

`Sigmahat`	The var-cov matrix of interest
`s`	The number of vectors `Sigmahat` was generated from
`n`	The length of each vector
`frob_norm_sq_bias_correction_min_samples`	This estimate suffers from high variance when there are not enough samples. Thus, we only implement the correction beginning at this number of samples otherwise we return the naive estimate. Default is 10.

Value

The unbiased estimate of the Frobenius Norm of a variance-covariance matrix squared.

Author(s)

Adam Kapelner

`frob_norm_sq_debiased_times_matrix`
Debiased Frobenius Norm Squared Constant Times Var-Cov matrix

Description

Compute debiased Frobenius Norm of matrix P times Sigmahat (Appendix 5.9). Note that for S <= 2, it returns the naive estimate.

Usage

```
frob_norm_sq_debiased_times_matrix(
  Sigmahat,
  A,
  s,
  n,
  frob_norm_sq_bias_correction_min_samples = 10
)
```

Arguments

`Sigmahat`	The var-cov matrix of interest
`A`	The matrix that multiplies Sigmahat
`s`	The number of vectors `Sigmahat` was generated from
`n`	The length of each vector
`frob_norm_sq_bias_correction_min_samples`	This estimate suffers from high variance when there are not enough samples. Thus, we only implement the correction beginning at this number of samples otherwise we return the naive estimate. Default is 10.

Value

The unbiased estimate of the Frobenius Norm of `A` times a variance-covariance matrix quantity squared.

Author(s)

Adam Kapelner

`generate_W_base_and_sort`

Generate Base Assignments and Sorts

Description

Generates the base vectors to be used when locating the optimal rerandomization threshold

Usage

```
generate_W_base_and_sort(
  X,
  max_designs = 25000,
  imbalance_function = "mahal_dist",
  r = 0,
  max_max_iters = 5
)
```

Arguments

X	The data as an $n \times p$ matrix.
max_designs	The maximum number of designs. Default is 25,000.
imbalance_function	A string indicating the imbalance function. Currently, "abs_sum_difference" and "mahal_dist" are the options with the latter being the default.
r	An experimental feature that adds lower imbalance vectors to the base set using the GreedyExperimentalDesign package. This controls the number of vectors to search through on each iteration.
max_max_iters	An experimental feature that adds lower imbalance vectors to the base set using the GreedyExperimentalDesign package. The maximum number of iterations to use for the greedy search.

Value

A list including all arguments plus a matrix W_base_sorted whose max_designs rows are n-length allocation vectors and the allocation vectors are in

Author(s)

Adam Kapelner

Examples

```
n = 100
p = 10
X = matrix(rnorm(n * p), nrow = n, ncol = p)
X = apply(X, 2, function(xj){(xj - mean(xj)) / sd(xj)})
S = 1000

W_base_obj = generate_W_base_and_sort(X, max_designs = S)
W_base_obj
```

---

optimal_rerandomization_exact

Find the Optimal Rerandomization Design Exactly

Description

Finds the optimal rerandomization threshold based on a user-defined quantile and a function that generates the non-linear component of the response

Usage

```
optimal_rerandomization_exact(
  W_base_object,
  estimator = "linear",
  q = 0.95,
  skip_search_length = 1,
  smoothing_degree = 1,
  smoothing_span = 0.1,
  z_sim_fun,
  N_z = 1000,
  dot_every_x_iters = 100
)
```

Arguments

W_base_object	An object that contains the assignments to begin with sorted by
estimator	"linear" for the covariate-adjusted linear regression estimator (default).
q	The tail criterion's quantile of MSE over z's. The default is 95%.
skip_search_length	In the exhaustive search, how many designs are skipped? Default is 1 for full exhaustive search through all assignments provided for in W_base_object.
smoothing_degree	The smoothing degree passed to loess.
smoothing_span	The smoothing span passed to loess.
z_sim_fun	This function returns vectors of numeric values of size n. No default is provided.
N_z	The number of times to simulate z's within each strategy.
dot_every_x_iters	Print out a dot every this many iterations. The default is 100. Set to NULL for no printout.

Value

A list containing the optimal design threshold, strategy, and other information.

Author(s)

Adam Kapelner

Examples

```
n = 100
p = 10
X = matrix(rnorm(n * p), nrow = n, ncol = p)
X = apply(X, 2, function(xj){(xj - mean(xj)) / sd(xj)})
S = 25000

W_base_obj = generate_W_base_and_sort(X, max_designs = S)
```

```
design = optimal_rerandomization_exact(W_base_obj,
   z_sim_fun = function(){rnorm(n)},
   skip_search_length = 10)
design
```

`optimal_rerandomization_normality_assumed` *Find the Optimal Rerandomization Design Under the Gaussian Approximation*

Description

Finds the optimal rerandomization threshold based on a user-defined quantile and a function that generates the non-linear component of the response

Usage

```
optimal_rerandomization_normality_assumed(
  W_base_object,
  estimator = "linear",
  q = 0.95,
  skip_search_length = 1,
  dot_every_x_iters = 100
)
```

Arguments

`W_base_object`	An object that contains the assignments to begin with sorted by
`estimator`	"linear" for the covariate-adjusted linear regression estimator (default).
`q`	The tail criterion's quantile of MSE over z's. The default is 95%.
`skip_search_length`	In the exhaustive search, how many designs are skipped? Default is 1 for full exhaustive search through all assignments provided for in `W_base_object`.
`dot_every_x_iters`	Print out a dot every this many iterations. The default is 100. Set to `NULL` for no printout.

Value

A list containing the optimal design threshold, strategy, and other information.

Author(s)

Adam Kapelner

Examples

```
n = 100
p = 10
X = matrix(rnorm(n * p), nrow = n, ncol = p)
X = apply(X, 2, function(xj){(xj - mean(xj)) / sd(xj)})
S = 25000

W_base_obj = generate_W_base_and_sort(X, max_designs = S)
design = optimal_rerandomization_normality_assumed(W_base_obj,
   skip_search_length = 10)
design
```

`optimal_rerandomization_tail_approx` *Find the Optimal Rerandomization Design Under the Tail and Kurtosis Approximation*

Description

Finds the optimal rerandomization threshold based on a user-defined quantile and kurtosis based on an approximation of tail standard errors

Usage

```
optimal_rerandomization_tail_approx(
  W_base_object,
  estimator = "linear",
  q = 0.95,
  c_val = NULL,
  skip_search_length = 1,
  binary_search = FALSE,
  excess_kurtosis_z = 0,
  use_frob_norm_sq_unbiased_estimator = TRUE,
  frob_norm_sq_bias_correction_min_samples = 10,
  smoothing_degree = 1,
  smoothing_span = 0.1,
  dot_every_x_iters = 100
)
```

Arguments

`W_base_object`	An object that contains the assignments to begin with sorted by imbalance.
`estimator`	"linear" for the covariate-adjusted linear regression estimator (default).
`q`	The tail criterion's quantile of MSE over z's. The default is 95%.
`c_val`	The c value used (see Equation 8 in the paper). The default is `NULL` corresponding to `qnorm(q)`.

skip_search_length
: In the exhaustive search, how many designs are skipped? Default is 1 for full exhaustive search through all assignments provided for in W_base_object.

binary_search
: If TRUE, a binary search is employed to find the optimal threshold instead of an exhaustive search. Default is FALSE.

excess_kurtosis_z
: An estimate of the excess kurtosis in the measure on z. Default is 0.

use_frob_norm_sq_unbiased_estimator
: If TRUE, this would use the debiased Frobenius norm estimator instead of the naive. Default is TRUE.

frob_norm_sq_bias_correction_min_samples
: The bias-corrected estimate suffers from high variance when there are not enough samples. Thus, we only implement the correction beginning at this number of vectors. Default is 10 and this parameter is only applicable if use_frob_norm_sq_unbiased_estimator is TRUE.

smoothing_degree
: The smoothing degree passed to loess.

smoothing_span
: The smoothing span passed to loess.

dot_every_x_iters
: Print out a dot every this many iterations. The default is 100. Set to NULL for no printout.

Value

A list containing the optimal design threshold, strategy, and other information.

Author(s)

Adam Kapelner

Examples

```
n = 100
p = 10
X = matrix(rnorm(n * p), nrow = n, ncol = p)
X = apply(X, 2, function(xj){(xj - mean(xj)) / sd(xj)})
S = 25000

W_base_obj = generate_W_base_and_sort(X, max_designs = S)
design = optimal_rerandomization_tail_approx(W_base_obj,
   skip_search_length = 10)
design
```

OptimalRerandExpDesigns

Optimal Rerandomization Threshold Search for Experimental Design

Description

A tool to find the optimal rerandomization threshold in non-sequential experiments

Author(s)

Adam Kapelner <kapelner@qc.cuny.edu>

References

Kapelner, A

plot.optimal_rerandomization_obj

Plots a summary of a `optimal_rerandomization_obj` *object*

Description

Plots a summary of a `optimal_rerandomization_obj` object

Usage

```
## S3 method for class 'optimal_rerandomization_obj'
plot(x, ...)
```

Arguments

`x`	The `optimal_rerandomization_obj` object to be summarized in the plot
`...`	The option `advanced = TRUE` can be passed here for optimal rerandomization results from algorithm type "approx" to see how all the terms in the criterion behave. You can pass `s_min` which controls the minimum number of vectors the plot begins at. Below a certain number, the criterion is unstable. Also, `title`, `subtitle`, `xlab` and `ylab` can be passed here.

Value

No return value, called for side effects

Author(s)

Adam Kapelner

plot.W_base_object *Plots a summary of the imbalances in a* W_base_object *object*

Description

Plots a summary of the imbalances in a W_base_object object

Usage

```
## S3 method for class 'W_base_object'
plot(x, ...)
```

Arguments

x	The W_base_object object to be summarized in the plot
...	title, subtitle, xlab, bins can be specified here to be passed to the ggplot plotting function. Also log10 can be set to FALSE to not log the x-axis.

Value

No return value, called for side effects

Author(s)

Adam Kapelner

print.optimal_rerandomization_obj *Prints a summary of a* optimal_rerandomization_obj *object*

Description

Prints a summary of a optimal_rerandomization_obj object

Usage

```
## S3 method for class 'optimal_rerandomization_obj'
print(x, ...)
```

Arguments

x	The optimal_rerandomization_obj object to be summarized in the console
...	Other parameters to pass to the default print function

Value

No return value, called for side effects

Author(s)

Adam Kapelner

`print.W_base_object` *Prints a summary of a* `W_base_object` *object*

Description

Prints a summary of a `W_base_object` object

Usage

```
## S3 method for class 'W_base_object'
print(x, ...)
```

Arguments

`x`	The `W_base_object` object to be summarized in the console
`...`	Other parameters to pass to the default print function

Value

No return value, called for side effects

Author(s)

Adam Kapelner

`summary.optimal_rerandomization_obj` *Prints a summary of a* `optimal_rerandomization_obj` *object*

Description

Prints a summary of a `optimal_rerandomization_obj` object

Usage

```
## S3 method for class 'optimal_rerandomization_obj'
summary(object, ...)
```

Arguments

object	The optimal_rerandomization_obj object to be summarized in the console
...	Other parameters to pass to the default summary function

Author(s)

Adam Kapelner

---

summary.W_base_object *Prints a summary of a* W_base_object *object*

Description

Prints a summary of a W_base_object object

Usage

```
## S3 method for class 'W_base_object'
summary(object, ...)
```

Arguments

object	The W_base_object object to be summarized in the console
...	Other parameters to pass to the default summary function

Author(s)

Adam Kapelner

Index

complete_randomization_plus_one_min_one, 2
complete_randomization_with_forced_balance_plus_one_min_one, 3
compute_objective_val_plus_one_min_one_enc, 3

frob_norm_sq, 4
frob_norm_sq_debiased, 5
frob_norm_sq_debiased_times_matrix, 5

generate_W_base_and_sort, 6

optimal_rerandomization_exact, 7
optimal_rerandomization_normality_assumed, 9
optimal_rerandomization_tail_approx, 10
OptimalRerandExpDesigns, 12

plot.optimal_rerandomization_obj, 12
plot.W_base_object, 13
print.optimal_rerandomization_obj, 13
print.W_base_object, 14

summary.optimal_rerandomization_obj, 14
summary.W_base_object, 15