Package: RNOmni (via r-universe)

October 28, 2026

Title Rank Normal Transformation Omnibus Test

Version 1.0.1.2

Date 2023-09-10

Description Inverse normal transformation (INT) based genetic association testing. These tests are recommend for continuous traits with non-normally distributed residuals. INT-based tests robustly control the type I error in settings where standard linear regression does not, as when the residual distribution exhibits excess skew or kurtosis. Moreover, INT-based tests outperform standard linear regression in terms of power. These tests may be classified into two types. In direct INT (D-INT), the phenotype is itself transformed. In indirect INT (I-INT), phenotypic residuals are transformed. The omnibus test (O-INT) adaptively combines D-INT and I-INT into a single robust and statistically powerful approach. See McCaw ZR, Lane JM, Saxena R, Redline S, Lin X. ``Operating characteristics of the rank-based inverse normal transformation for quantitative trait analysis in genome-wide association studies" <doi:10.1111/biom.13214>.

Depends R (>= 3.2.2)

Imports plyr, Rcpp, stats

LinkingTo Rcpp, RcppArmadillo

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.2

Suggests testthat (>= 3.0.0), withr, R.rsp

VignetteBuilder R.rsp

Config/testthat/edition 3

NeedsCompilation yes

Author Zachary McCaw [aut, cre] (<https://orcid.org/0000-0002-2006-9828>)

Maintainer Zachary McCaw <zmccaw@alumni.harvard.edu>

Repository https://cran.r-universe.dev

Date/Publication 2023-09-11 06:32:36 UTC

RemoteUrl https://github.com/cran/RNOmni

RemoteRef HEAD

RemoteSha 37586340b6851efe1db503e2157605a16c9dd722

Contents

BasicInputChecks 2
BAT 3
CauchyToP 4
DINT 4
FitOLS 5
IINT 6
OINT 7
OmniP 8
PartitionData 9
PtoCauchy 9
RankNorm 10

Index **11**

`BasicInputChecks` *Basic Input Checks*

Description

Stops evaluation if inputs are improperly formatted.

Usage

```
BasicInputChecks(y, G, X)
```

Arguments

`y`	Numeric phenotype vector.
`G`	Genotype matrix with observations as rows, SNPs as columns.
`X`	Covariate matrix.

Value

None.

BAT *Basic Association Test*

Description

Conducts tests of association between the loci in `G` and the untransformed phenotype `y`, adjusting for the model matrix `X`.

Usage

```
BAT(y, G, X = NULL, test = "Score", simple = FALSE)
```

Arguments

`y`	Numeric phenotype vector.
`G`	Genotype matrix with observations as rows, SNPs as columns.
`X`	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
`test`	Either Score or Wald.
`simple`	Return the p-values only?

Value

If `simple = TRUE`, returns a vector of p-values, one for each column of `G`. If `simple = FALSE`, returns a numeric matrix, including the Wald or Score statistic, its standard error, the Z-score, and the p-value.

See Also

- Direct INT `DINT`
- Indirect INT `IINT`
- Omnibus INT `OINT`

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, stats::rnorm(1e3))
# Genotypes
G <- replicate(1e3, stats::rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- as.numeric(X %*% c(1, 1)) + stats::rnorm(1e3)
# Association test
p <- BAT(y = y, G = G, X = X)
```

CauchyToP *Convert Cauchy Random Variable to P*

Description

Convert Cauchy Random Variable to P

Usage

```
CauchyToP(z)
```

Arguments

z	Numeric Cauchy random variable.

Value

Numeric p-value.

DINT *Direct-INT*

Description

Applies the rank-based inverse normal transformation (RankNorm) to the phenotype y. Conducts tests of association between the loci in G and transformed phenotype, adjusting for the model matrix X.

Usage

```
DINT(
  y,
  G,
  X = NULL,
  k = 0.375,
  test = "Score",
  ties.method = "average",
  simple = FALSE
)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
k	Offset applied during rank-normalization. See RankNorm.
test	Either Score or Wald.
ties.method	Method of breaking ties, passed to base::rank.
simple	Return the p-values only?

Value

If simple = TRUE, returns a vector of p-values, one for each column of G. If simple = FALSE, returns a numeric matrix, including the Wald or Score statistic, its standard error, the Z-score, and the p-value.

See Also

- Basic association test BAT.
- Indirect INT test IINT.
- Omnibus INT test OINT.

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, stats::rnorm(1e3))
# Genotypes
G <- replicate(1e3, stats::rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- exp(as.numeric(X %*% c(1, 1)) + stats::rnorm(1e3))
# Association test
p <- DINT(y = y, G = G, X = X)
```

FitOLS *Ordinary Least Squares*

Description

Fits the standard OLS model.

Usage

```
FitOLS(y, X)
```

Arguments

y	Nx1 Numeric vector.
X	NxP Numeric matrix.

Value

List containing the following:

Beta	Regression coefficient.
V	Outcome variance.
Ibb	Information matrix for beta.
Resid	Outcome residuals.

IINT *Indirect-INT*

Description

Two-stage association testing procedure. In the first stage, phenotype y and genotype G are each regressed on the model matrix X to obtain residuals. The phenotypic residuals are transformed using RankNorm. In the next stage, the INT-transformed residuals are regressed on the genotypic residuals.

Usage

```
IINT(y, G, X = NULL, k = 0.375, ties.method = "average", simple = FALSE)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
k	Offset applied during rank-normalization. See RankNorm.
ties.method	Method of breaking ties, passed to base::rank.
simple	Return the p-values only?

Value

If simple = TRUE, returns a vector of p-values, one for each column of G. If simple = FALSE, returns a numeric matrix, including the Wald or Score statistic, its standard error, the Z-score, and the p-value.

See Also

- Basic association test BAT.
- Direct INT test DINT.
- Omnibus INT test OINT.

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, stats::rnorm(1e3))
# Genotypes
G <- replicate(1e3, stats::rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- exp(as.numeric(X %*% c(1,1)) + stats::rnorm(1e3))
# Association test
p <- IINT(y = y, G = G, X = X)
```

OINT *Omnibus-INT*

Description

Association test that synthesizes the DINT and IINT tests. The first approach is most powerful for traits that could have arisen from a rank-preserving transformation of a latent normal trait. The second approach is most powerful for traits that are linear in covariates, yet have skewed or kurtotic residual distributions. During the omnibus test, the direct and indirect tests are separately applied, then the p-values are combined via the Cauchy combination method.

Usage

```
OINT(
  y,
  G,
  X = NULL,
  k = 0.375,
  ties.method = "average",
  weights = c(1, 1),
  simple = FALSE
)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.

k	Offset applied during rank-normalization. See RankNorm.
ties.method	Method of breaking ties, passed to base::rank.
weights	Respective weights to allocate the DINT and IINT tests.
simple	Return the OINT p-values only?

Value

A numeric matrix of p-values, three for each column of G.

See Also

- Basic association test BAT.
- Direct INT test DINT.
- Indirect INT test IINT.

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, rnorm(1e3))
# Genotypes
G <- replicate(1e3, rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- exp(as.numeric(X %*% c(1, 1)) + rnorm(1e3))
# Omnibus
p <- OINT(y = y, G = G, X = X, simple = TRUE)
```

OmniP *Omnibus P-value.*

Description

Obtains an omnibus p-value from a vector of potentially dependent p-values using the method of Cauchy combination. The p-values are converted to Cauchy random deviates then averaged. The distribution of the average of these deviates is well-approximated by a Cauchy distribution in the tails. See <https://doi.org/10.1080/01621459.2018.1554485>.

Usage

```
OmniP(p, w = NULL)
```

Arguments

p	Numeric vector of p-values.
w	Numeric weight vector.

Value

OINT p-value.

`PartitionData` *Partition Data*

Description

Partition y and X according to the missingness pattern of g.

Usage

```
PartitionData(e, g, X)
```

Arguments

`e`	Numeric residual vector.
`g`	Genotype vector.
`X`	Model matrix of covariates.

Value

List containing:

- "g_obs", observed genotype vector.
- "X_obs", covariates for subjects with observed genotypes.
- "X_mis", covariates for subjects with missing genotypes.
- "e_obs", residuals for subjects with observed genotypes.

`PtoCauchy` *Convert P-value to Cauchy Random*

Description

Convert P-value to Cauchy Random

Usage

```
PtoCauchy(p)
```

Arguments

`p`	Numeric p-value.

Value

Numeric Cauchy random variable.

RankNorm *Rank-Normalize*

Description

Applies the rank-based inverse normal transform (INT) to a numeric vector. The INT can be broken down into a two-step procedure. In the first, the observations are transformed onto the probability scale using the empirical cumulative distribution function (ECDF). In the second, the observations are transformed onto the real line, as Z-scores, using the probit function.

Usage

```
RankNorm(u, k = 0.375, ties.method = "average")
```

Arguments

u	Numeric vector.
k	Offset. Defaults to (3/8), corresponding to the Blom transform.
ties.method	Method of breaking ties, passed to base::rank.

Value

Numeric vector of rank normalized values.

See Also

- Direct INT test DINT.
- Indirect INT test IINT.
- Omnibus INT test OINT.

Examples

```
# Draw from chi-1 distribution
y <- stats::rchisq(n = 1e3, df = 1)
# Rank normalize
z <- RankNorm(y)
# Plot density of transformed measurement
plot(stats::density(z))
```

Index

BasicInputChecks, 2
BAT, 3, *5*, *7, 8*

CauchyToP, 4

DINT, *3*, 4, *7, 8*, *10*

FitOLS, 5

IINT, *3*, *5*, 6, *7, 8*, *10*

OINT, *3*, *5*, 7, *7*, *10*
OmniP, 8

PartitionData, 9
PtoCauchy, 9

RankNorm, *4–6*, *8*, 10