

Package: RProbSup (via r-universe)

September 18, 2024

Type Package

Title Calculates Probability of Superiority

Version 3.0

Author John Ruscio

Maintainer John Ruscio <ruscio@tcnj.edu>

Description The A() function calculates the A statistic, a nonparametric measure of effect size for two independent groups that's also known as the probability of superiority (Ruscio, 2008), along with its standard error and a confidence interval constructed using bootstrap methods (Ruscio & Mullen, 2012). Optional arguments can be specified to calculate variants of the A statistic developed for other research designs (e.g., related samples, more than two independent groups or related samples; Ruscio & Gera, 2013). <DOI:10.1037/1082-989X.13.1.19>. <DOI:10.1080/00273171.2012.658329>. <DOI:10.1080/00273171.2012.738184>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2020-10-19 04:40:06 UTC

Contents

A	2
A1	3
A2	4
AAD1	5
AAD2	6
AAPD1	7
AAPD2	8
CalcA1	9

CalcA2	10
CalcAAD1	11
CalcAAD2	12
CalcAAPD1	13
CalcAAPD2	14
CalcIK1	15
CalcIK2	16
CalcOrd1	17
CalcOrd2	18
IK1	19
IK2	20
Ord1	21
Ord2	22
RemoveMissing	23

Index 24

A

A

Description

Calculates probability of superiority (A), its standard error, and a confidence interval.

Usage

```
A(data, design = 1, statistic = 1, weights = FALSE,
  w = 0, w1 = 0, w2 = 0, increase = FALSE, ref = 1, r = 0,
  n.bootstrap = 1999, conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

data	For a between subjects design, a matrix of cases (rows) by scores (column 1) and group codes (column 2). For a within subjects design, a matrix of scores with each sample in its own column (matrix).
design	Design of experiment (scalar, default = 1 (for between subjects design), user can also call 2 (for within subjects design)).
statistic	Statistic to be calculated (scalar, default = 1 (A), user can also call 2 (A.AAD), 3 (A.AAPD), 4 (A.IK), or 5 (A.Ord)).
weights	Whether to assign weights to cases (default = FALSE); if set to TRUE, data contains case weights in final column.
w	Weights for cases (vector; default = 0).
w1	Weights for cases in group 1 (vector; default = 0).
w2	Weights for cases in group 2 (vector; default = 0).
increase	Set to TRUE if scores are predicted to increase with group codes (default = FALSE).

<code>ref</code>	Reference group (to compare to all others) (scalar, default = 1).
<code>r</code>	Vector of proportions (vector, default = 0, represents equal proportions).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile)).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

Returns list object with the following elements: `A` : A statistic (scalar). `SE` : Standard error of A (scalar). `ci.lower` : Lower bound of confidence interval (scalar). `ci.upper` : Upper bound of confidence interval (scalar). `conf.level` : Confidence level (scalar). `n.bootstrap` : Number of bootstrap samples (scalar). `boot.method` : Bootstrap method ("BCA" or "percentile"). `n` : Sample size (after missing data removed; scalar). `n.missing` : Number of cases of missing data, removed listwise (scalar).

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
data <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
A(data, 1, 2)
```

A1

A1

Description

Calculates the standard error and constructs a confidence interval for the A statistic using bootstrap methods.

Usage

```
A1(y1, y2, weights = FALSE, w1 = 0, w2 = 0, n.bootstrap = 1999,
  conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

y1	Scores for group 1 (vector).
y2	Scores for group 2 (vector).
weights	Whether to weight cases (default = FALSE).
w1	Weights for cases in group 1 (optional) (vector, default is 0).
w2	Weights for cases in group 2 (optional) (vector, default is 0).
n.bootstrap	Number of bootstrap samples (scalar, default = 1999).
conf.level	Confidence level (scalar, default = .95).
ci.method	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
seed	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
#Example used in Ruscio and Mullen (2012)
y1 <- c(6, 7, 8, 7, 9, 6, 5, 4, 7, 8, 7, 6, 9, 5, 4)
y2 <- c(4, 3, 5, 3, 6, 2, 2, 1, 6, 7, 4, 3, 2, 4, 3)
A1(y1, y2)
```

A2

A2

Description

Calculates the standard error and constructs a confidence interval for the A statistic for two correlated samples using bootstrap methods.

Usage

```
A2(y1, y2, weights = FALSE, w = 0, n.bootstrap = 1999,
conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y1</code>	Scores for group 1 (vector).
<code>y2</code>	Scores for group 2 (vector).
<code>weights</code>	Whether to weight cases (default = FALSE).
<code>w</code>	Weights for cases in group 1 (optional) (vector, default is 0).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
y1 <- c(6, 7, 8, 7, 9, 6, 5, 4, 7, 8, 7, 6, 9, 5, 4)
y2 <- c(7, 5, 6, 7, 6, 4, 3, 5, 4, 5, 4, 5, 7, 4, 5)
A2(y1, y2)
```

AADI

AADI

Description

Calculates the confidence interval for the A statistic for the average absolute deviation for two or more groups.

Usage

```
AAD1(y, r = 0, weights = FALSE, n.bootstrap = 1999, conf.level = .95,
ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>r</code>	Vector of proportions (default = 0, represents equal proportions) (vector).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
AAD1(y)
```

AAD2

AAD2

Description

Calculates the confidence interval for the A statistic for the average absolute deviation for two or more correlated samples.

Usage

```
AAD2(y, r = 0, weights = FALSE, n.bootstrap = 1999,
conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>r</code>	Vector of proportions (default = 0, represents equal proportions) (vector).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
AAD2(y)
```

AAPD1

AAPD1

Description

Calculates the confidence interval for the A statistic for the average absolute paired deviation for two or more groups.

Usage

```
AAPD1(y, weights = FALSE, n.bootstrap = 1999,
conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
AAPD1(y)
```

AAPD2

AAPD2

Description

Calculates the confidence interval for the A statistic for the average absolute paired deviation for two or more correlated samples.

Usage

```
AAPD2(y, weights = FALSE, n.bootstrap = 1999,
conf.level = .95, ci.method = 1, seed = 1)
```


Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
AAPD2(y)
```

CalcA1

CalcA1

Description

Calculates the A statistic for 2 groups.

Usage

```
CalcA1(y1, y2, weights = FALSE, w1 = 0, w2 = 0)
```

Arguments

y1	Scores for group 1 (vector).
y2	Scores for group 2 (vector).
weights	Whether to weight cases (default = FALSE).
w1	Weights for cases in group 1 (optional) (vector, default is 0).
w2	Weights for cases in group 2 (optional) (vector, default is 0).

Value

a	The A statistic.
---	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
#Example used in Ruscio and Mullen (2012)
y1 <- c(6, 7, 8, 7, 9, 6, 5, 4, 7, 8, 7, 6, 9, 5, 4)
y2 <- c(4, 3, 5, 3, 6, 2, 2, 1, 6, 7, 4, 3, 2, 4, 3)
CalcA1(y1, y2)
```

CalcA2

CalcA2

Description

Calculates the A statistic for 2 correlated samples.

Usage

```
CalcA2(y1, y2, weights = FALSE, w = 0)
```

Arguments

y1	Scores for variable 1 (vector).
y2	Scores for variable 2 (vector).
weights	Whether to weight cases (default = FALSE).
w	Weights (optional) (vector, default is 0).

Value

a	The A statistic.
---	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```

y1 <- c(6, 7, 8, 7, 9, 6, 5, 4, 7, 8, 7, 6, 9, 5, 4)
y2 <- c(7, 5, 6, 7, 6, 4, 3, 5, 4, 5, 4, 5, 7, 4, 5)
CalcA2(y1, y2)

```

CalcAAD1

CalcAAD1

Description

Calculates the A statistic for the average absolute deviation for two or more groups. Note: This function is not meant to be called by the user, but it is called by AAD1.

Usage

```
CalcAAD1(y, r = 0, weights = FALSE)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>r</code>	Vector of proportions (default = 0, represents equal proportions) (vector).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).

Value

<code>a</code>	The A statistic.
----------------	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
CalcAAD1(y)
```

 CalcAAD2

CalcAAD2

Description

Calculates the A statistic for the average absolute deviation for two or more correlated samples.
 Note: This function is not meant to be called by the user, but it is called by AAD2.

Usage

```
CalcAAD2(y, r = 0, weights = FALSE)
```

Arguments

y	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
r	Vector of proportions (default = 0, represents equal proportions) (vector).
weights	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).

Value

a	The A statistic.
---	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
CalcAAD2(y)
```

`CalcAAPDI`*CalcAAPDI*

Description

Calculates the A statistic for the average absolute paired deviation for two or more groups. Note: This function is not meant to be called by the user, but it is called by AAPDI.

Usage

```
CalcAAPDI(y, weights = FALSE)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).

Value

<code>a</code>	The A statistic.
----------------	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
AAPDI(y)
```

`CalcAAPD2`*CalcAAPD2*

Description

Calculates the A statistic for the average absolute paired deviation for two or more correlated samples. Note: This function is not meant to be called by the user, but it is called by AAPD2.

Usage

```
CalcAAPD2(y, weights = FALSE)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).

Value

<code>a</code>	The A statistic.
----------------	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
AAPD2(y)
```

`CalcIK1`*CalcIK1*

Description

Calculates the A statistic while singling out one group for two or more groups. Note: This function is not meant to be called by the user, but it is called by IK1.

Usage

```
CalcIK1(y, ref = 1, weights = FALSE)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>ref</code>	Reference group (to compare to all others) (scalar, default = 1).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).

Value

<code>a</code>	The A statistic.
----------------	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
CalcIK1(y)
```

`CalcIK2`*CalcIK2*

Description

Calculates the A statistic while singling out one group for two or more correlated samples. Note: This function is not meant to be called by the user, but it is called by IK2.

Usage

```
CalcIK2(y, ref = 1, weights = FALSE)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>ref</code>	Reference group (to compare to all others) (scalar, default = 1).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).

Value

<code>a</code>	The A statistic.
----------------	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
CalcIK2(y)
```

`CalcOrd1`*CalcOrd1*

Description

Calculates the ordinal comparison of the A statistic for two or more groups. Note: This function is not meant to be called by the user, but it is called by AOrd1.

Usage

```
CalcOrd1(y, weights = FALSE, increase = FALSE)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>increase</code>	Set to TRUE if scores are predicted to increase with group codes (default = FALSE).

Value

<code>a</code>	The A statistic.
----------------	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
CalcOrd1(y)
```

CalcOrd2

CalcOrd2

Description

Calculates the ordinal comparison of the A statistic for two or more correlated samples. Note: This function is not meant to be called by the user, but it is called by AOrd2.

Usage

```
CalcOrd2(y, weights = FALSE, increase = FALSE)
```

Arguments

y	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
weights	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
increase	Set to TRUE if scores are predicted to increase with group codes (default = FALSE).

Value

a	The A statistic.
---	------------------

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
CalcOrd2(y)
```

IK1

*IK1***Description**

Calculates the confidence interval for the A statistic while singling out one group for two or more groups.

Usage

```
IK1(y, ref = 1, weights = FALSE, n.bootstrap = 1999,
    conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>ref</code>	Reference group (to compare to all others) (scalar, default = 1).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
IK1(y)
```

IK2

IK2

Description

Calculates the confidence interval for the A statistic while singling out one group for two or more correlated samples.

Usage

```
IK2(y, ref = 1, weights = FALSE, n.bootstrap = 1999,
    conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>ref</code>	Reference group (to compare to all others) (scalar, default = 1).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
IK2(y)
```

 Ord1

Ord1

Description

Calculates the confidence interval for the ordinal comparison of the A statistic for two or more groups.

Usage

```
Ord1(y, weights = FALSE, increase = FALSE, n.bootstrap = 1999,
     conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>increase</code>	Set to TRUE if scores are predicted to increase with group codes (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(c(x1, x2, x3), c(rep(1, 25), rep(2, 25), rep(3, 25)))
Ord1(y)
```

 Ord2

Ord2

Description

Calculates the confidence interval for the ordinal comparison of the A statistic for two or more correlated samples.

Usage

```
Ord2(y, weights = FALSE, increase = FALSE, n.bootstrap = 1999,
     conf.level = .95, ci.method = 1, seed = 1)
```

Arguments

<code>y</code>	Matrix of cases (rows) by scores (column 1) and group codes (column 2) (matrix).
<code>weights</code>	Weight of each case. Set to TRUE to weight cases; if so, column 3 contains case weights (default = FALSE).
<code>increase</code>	Set to TRUE if scores are predicted to increase with group codes (default = FALSE).
<code>n.bootstrap</code>	Number of bootstrap samples (scalar, default = 1999).
<code>conf.level</code>	Confidence level (scalar, default = .95).
<code>ci.method</code>	Method used to construct confidence interval (scalar, default = 1 (for BCA), user can also call 2 (for percentile).
<code>seed</code>	Random number seed (scalar, default = 1).

Value

A vector containing the A statistic, its estimated standard error, and the upper and lower bounds of the confidence interval.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- rnorm(25)
x2 <- x1 - rnorm(25, mean = 1)
x3 <- x2 - rnorm(25, mean = 1)
y <- cbind(x1, x2, x3)
Ord2(y)
```

RemoveMissing	<i>RemoveMissing</i>
---------------	----------------------

Description

Checks for missing data and performs listwise deletion if any is detected.

Usage

```
RemoveMissing(data)
```

Arguments

data	For a between subjects design, a matrix of cases (rows) by scores (column 1) and group codes (column 2). For a within subjects design, a matrix of scores with each sample in its own column (matrix).
------	--

Value

Data matrix with any missing data removed using listwise deletion of cases.

Author(s)

John Ruscio

References

Ruscio (2008) & Ruscio and Mullen (2012) & Ruscio and Gera (2013)

Examples

```
x1 <- c(rnorm(25), NA)
x2 <- x1 - rnorm(26, mean = 1)
x3 <- x2 - rnorm(26, mean = 1)
data <- cbind(c(x1, x2, x3), c(rep(1, 26), rep(2, 26), rep(3, 26)))
A(data, 1, 2)
```

Index

A, [2](#)
A1, [3](#)
A2, [4](#)
AAD1, [5](#)
AAD2, [6](#)
AAPD1, [7](#)
AAPD2, [8](#)

CalcA1, [9](#)
CalcA2, [10](#)
CalcAAD1, [11](#)
CalcAAD2, [12](#)
CalcAAPD1, [13](#)
CalcAAPD2, [14](#)
CalcIK1, [15](#)
CalcIK2, [16](#)
CalcOrd1, [17](#)
CalcOrd2, [18](#)

IK1, [19](#)
IK2, [20](#)

Ord1, [21](#)
Ord2, [22](#)

RemoveMissing, [23](#)