Package: RaschSampler (via r-universe)

October 22, 2026

Type Package

Title Rasch Sampler

Version 0.8-10

Date 2023-09-25

Imports stats

Depends R (>= 4.0.0)

Description MCMC based sampling of binary matrices with fixed margins as used in exact Rasch model tests.

License GPL-2

NeedsCompilation yes

Author Patrick Mair [cre, aut], Reinhold Hatzinger [aut], Norman D. Verhelst [aut]

Maintainer Patrick Mair <mair@fas.harvard.edu>

Repository https://cran.r-universe.dev

Date/Publication 2023-09-27 13:30:25 UTC

RemoteUrl https://github.com/cran/RaschSampler

RemoteRef HEAD

RemoteSha 2e5c5e2630b10a7fab68e3d0b3682089686d6405

Contents

RaschSampler-package 2
phi.range 3
rsampler 4
RSctr 5
rsctrl 6
rsextrmat 7
rsextrobj 8
RSmpl 10
rstats 11
summary.RSctr 12

summary.RSmpl 13
xmpl 13

Index **15**

`RaschSampler-package` *Rasch Sampler Package*

Description

The package implements an MCMC algorithm for sampling of binary matrices with fixed margins complying to the Rasch model. Its stationary distribution is uniform. The algorithm also allows for square matrices with fixed diagonal.

Parameter estimates in the Rasch model only depend on the marginal totals of the data matrix that is used for the estimation. From this it follows that, if the model is valid, all binary matrices with the same marginals as the observed one are equally likely. For any statistic of the data matrix, one can approximate the null distribution, i.e., the distribution if the Rasch model is valid, by taking a random sample from the collection of equally likely data matrices and constructing the observed distribution of the statistic. One can then simply determine the exceedence probability of the statistic in the observed sample, and thus construct a non-parametric test of the Rasch model. The main purpose of this package is the implementation of a methodology to build nonparametric tests for the Rasch model.

In the context of social network theories, where the structure of binary asymmetric relations is studied, for example, person a esteems person b, which correponds to a 1 in cell (a, b) of the associated adjacency matrix. If one wants to study the distribution of a statistic defined on the adjacency matrix and conditional on the marginal totals, one has to exclude the diagonal cells from consideration, i.e., by keeping the diagonal cells fixed at an arbitrary value. The `RaschSampler` package has implemented an appropriate option, thus it can be also used for sampling random adjacency matrices with given marginal totals.

Details

The user has to supply a binary input matrix. After defining appropriate control parameters using `rsctrl` the sampling function `rsampler` may be called to obtain an object of class `RSmpl` which contains the generated random matrices in encoded form. After defining an appropriate function to operate on a binary matrix (e.g., calculate a statistic such as `phi.range`) the application of this function to the sampled matrices is performed using `rstats`. Prior to applying the user defined function, `rstats` decodes the matrices packed in the `RSmpl`-object.

The package also defines a utility function `rsextrobj` for extracting certains parts from the `RSmpl`-object resulting in an object of class `RSmplext`. Both types of objects can be saved and reloaded for later use.

Summary methods are available to print information on these objects, as well as on the control object `RSctr` which is obtained from using `rsctrl` containing the specification for the sampling routine.

Note

The current implementation allows for data matrices up to 4096 rows and 128 columns. This can be changed by setting `nmax` and `kmax` in `RaschSampler.f90` to values which are a power of 2. These values should also be changed in `rserror.R`.

For convenience, we reuse the Fortran code of package version 0.8-1 which cicumvents the compiler bug in Linux distributions of GCC 4.3. In case of compilation errors (due to a bug in Linux distributions of GCC 4.3) please use `RaschSampler.f90` from package version 0.8-1 and change `nmax` and `kmax` accordingly (or use GCC 4.4).

Author(s)

Reinhold Hatzinger, Patrick Mair, Norman D. Verhelst

Maintainer: <mair@fas.harvard.edu>

References

Verhelst, N. D. (2008) An Efficient MCMC Algorithm to Sample Binary Matrices with Fixed Marginals. Psychometrika, Volume 73, Number 4
Verhelst, N. D., Hatzinger, R., and Mair, P. (2007) The Rasch Sampler. Journal of Statistical Software, Vol. 20, Issue 4, Feb 2007

`phi.range` *Example User Function*

Description

Calculates the R_ϕ statistic, i.e., the range of the inter-column correlations (ϕ-coefficients) for a binary matrix.

Usage

```
phi.range(mat)
```

Arguments

`mat`	a binary matrix

Value

the range of the inter-column correlations

Examples

```
ctr <- rsctrl(burn_in = 10, n_eff = 5, step=10, seed = 123, tfixed = FALSE)
mat <- matrix(sample(c(0,1), 50, replace = TRUE), nr = 10)
rso <- rsampler(mat, ctr)
rso_st <- rstats(rso,phi.range)
print(unlist(rso_st))
```

rsampler *Sampling Binary Matrices*

Description

The function implements an MCMC algorithm for sampling of binary matrices with fixed margins complying to the Rasch model. Its stationary distribution is uniform. The algorithm also allows for square matrices with fixed diagonal.

Usage

```
rsampler(inpmat, controls = rsctrl())
```

Arguments

inpmat	A binary (data) matrix with n rows and k columns.
controls	An object of class RSctr. If not specified, the default parameters as returned by function rsctrl are used.

Details

rsampler is a wrapper function for a Fortran routine to generate binary random matrices based on an input matrix. On output the generated binary matrices are integer encoded. For further processing of the generated matrices use the function rstats.

Value

A list of class RSmpl with components

n	number of rows of the input matrix
k	number of columns of the input matrix
inpmat	the input matrix
tfixed	TRUE, if diagonals of inpmat are fixed
burn_in	length of the burn in process
n_eff	number of generated matrices (effective matrices)
step	controls the number number of void matrices generated in the the burn in process and when effective matrices are generated (see note in rsctrl).
seed	starting value for the random number generator
n_tot	number of matrices in outvec, n_tot = n_eff + 1
outvec	vector of encoded random matrices
ier	error code

Note

An element of `outvec` is a four byte (or 32 bits) integer. The matrices to be output are stored bitwise (some bits are unused, since a integer is used for every row of a matrix. So the number of integers per row needed equals (k+31)/32 (integer division), which is one to four in the present implementation since the number of columns and rows must not exceed 128 and 4096, respectively.

The summary method (`summary.RSmpl`) prints information on the content of the output object.

Author(s)

Reinhold Hatzinger, Norman Verhelst

References

Verhelst, N. D. (2008) An Efficient MCMC Algorithm to Sample Binary Matrices with Fixed Marginals. Psychometrika, Volume 73, Number 4

See Also

`rsctrl`, `rstats`

Examples

```
data(xmpl)
ctr<-rsctrl(burn_in=10, n_eff=5, step=10, seed=0, tfixed=FALSE)
res<-rsampler(xmpl,ctr)
summary(res)
```

RSctr *Control Object*

Description

The object of class `RSctr` represents the control parameter specification for the sampling function `rsampler`.

Value

A legitimate `RSctr` object is a list with components

`burn_in`	the number of matrices to be sampled to come close to a stationary distribution.
`n_eff`	the number of effective matrices, i.e., the number of matrices to be generated by the sampling function `rsampler`.
`step`	controls the number number of void matrices generated in the the burn in process and when effective matrices are generated (see note in `rsctrl`).
`seed`	is the indicator for the seed of the random number generator. If the value of seed at equals zero, a seed is generated by the sampling function `rsampler`

tfixed	TRUE or FALSE. tfixed = TRUE has no effect if the input matrix is not quadratic, i.e., all matrix elements are considered free (unrestricted). If the input matrix is quadratic, and tfixed = TRUE, the main diagonal of the matrix is considered as fixed.

Generation

This object is returned from function rsctrl.

Methods

This class has a method for the generic summary function.

See Also

rsctrl

---

rsctrl *Controls for the Sampling Function*

Description

Various parameters that control aspects of the random generation of binary matrices.

Usage

```
rsctrl(burn_in = 100, n_eff = 100, step = 16, seed = 0, tfixed = FALSE)
```

Arguments

burn_in	the number of sampled matrices to come close to a stationary distribution. The default is burn_in = 100. (The actual number is 2 * burn_in * step.)
n_eff	the number of effective matrices, i.e., the number of matrices to be generated by the sampling function rsampler. n_eff must be positive and not larger than 8191 (2^13-1). The default is n_eff = 100.
step	controls the number number of void matrices generated in the the burn in process and when effective matrices are generated (see note below). The default is step = 16.
seed	is the indicator for the seed of the random number generator. Its value must be in the range 0 and 2147483646 (2**31-2). If the value of seed equals zero, a seed is generated by the sampling function rsampler (dependent on the system's clock) and its value is returned in the output. If seed is not equal to zero, its value is used as the seed of the random number generator. In that case its value is unaltered at output. The default is seed = 0.
tfixed	logical, – specifies if in case of a quadratic input matrix the diagonal is considered fixed (see note below). The default is tfixed = FALSE.

Value

A list of class `RSctr` with components `burn_in`, `n_eff`, `step`, `seed`, `tfixed`.,

Note

If one of the components is incorrectly specified the error function `rserror` is called and some informations are printed. The ouput object will not be defined.

The specification of `step` controls the sampling algorithm as follows: If , e.g., `burn_in = 10`, `n_eff = 5`, and `step = 2`, then during the burn in period `step * burn_in = 2 * 10` matrices are generated. After that, `n_eff * step = 5 * 2` matrices are generated and every second matrix of these last ten is returned from `link{rsampler}`.

`tfixed` has no effect if the input matrix is not quadratic, i.e., all matrix elements are considered free (unrestricted). If the input matrix is quadratic, and `tfixed = TRUE`, the main diagonal of the matrix is considered as fixed. On return from `link{rsampler}` all diagonal elements of the generated matrices are set to zero. This specification applies, e.g., to analyzing square incidence matrices representing binary asymmetric relation in social network theory.

The summary method (`summary.RSctr`) prints the current definitions.

See Also

`rsampler`

Examples

```
ctr <- rsctrl(n_eff = 1, seed = 987654321)  # specify new controls
summary(ctr)

## Not run:
ctr2 <- rsctrl(step = -3, n_eff = 10000) # incorrect specifications

## End(Not run)
```

---

rsextrmat *Extracting a Matrix*

Description

Convenience function to extract a matrix.

Usage

```
rsextrmat(RSobj, mat.no = 1)
```

Arguments

RSobj	object as obtained from using rsampler or rsextrobj
mat.no	number of the matrix to extract from the sample object.

Value

One of the matrices (either the original or a sampled matrix)

See Also

rsampler, rsextrobj,rstats,

Examples

```
ctr <- rsctrl(burn_in = 10, n_eff = 3, step=10, seed = 0, tfixed = FALSE)
mat <- matrix(sample(c(0,1), 50, replace = TRUE), nr = 10)
all_m <- rsampler(mat, ctr)
summary(all_m)

# extract the third sampled matrix (here the fourth)
third_m <- rsextrmat(all_m, 4)
head(third_m)
```

---

rsextrobj *Extracting Encoded Sample Matrices*

Description

Utility function to extract some of the generated matrices, still in encoded form.

Usage

```
rsextrobj(RSobj, start = 1, end = 8192)
```

Arguments

RSobj	object as obtained from using rsampler
start	number of the matrix to start with. When specifying 1 (the default value) the original input matrix is included in the output object.
end	last matrix to be extracted. If end is not specified, all matrices from RSobj are extracted (the maximal value is 8192, see rsctrl). If end is larger than the number of matrices stored in RSobj, end is set to the highest possible value (i.e., n_tot).

Value

A list of class RSmpl with components

n	number of rows of the input matrix
k	number of columns of the input matrix
inpmat	the input matrix
tfixed	TRUE, if diagonals of inpmat are fixed
burn_in	length of the burn in process
n_eff	number of generated matrices (effective matrices)
step	controls the number number of void matrices generated in the burn in process and when effective matrices are generated (see note in rsctrl).
seed	starting value for the random number generator
n_tot	number of matrices in outvec.
outvec	vector of encoded random matrices
ier	error code

Note

By default, all generated matrices plus the original matrix (in position 1) are contained in outvec, thus n_tot = n_eff + 1. If the original matrix is not in outvec then n_tot = n_eff.
For saving and loading objects of class RSobj see the example below.

For extracting a decoded (directly usable) matrix use rsextrmat.

See Also

rsampler, rsextrmat

Examples

```
ctr <- rsctrl(burn_in = 10, n_eff = 3, step=10, seed = 0, tfixed = FALSE)
mat <- matrix(sample(c(0,1), 50, replace = TRUE), nr = 10)
all_m <- rsampler(mat, ctr)
summary(all_m)

some_m <- rsextrobj(all_m, 1, 2)
summary(some_m)

## Not run:
save(some_m, file = "some.RSobj")
some_new <- load("some.RSobj")
summary(some_new)

## End(Not run)
```

RSmpl *Sample Objects*

Description

The objects of class RSmpl and RSmplext contain the original input matrix, the generated (encoded) random matrices, and some information about the sampling process.

Value

A list of class RSmpl or RSmplext with components

n	number of rows of the input matrix
k	number of columns of the input matrix
inpmat	the input matrix
tfixed	TRUE, if diagonals of inpmat are fixed
burn_in	length of the burn in process
n_eff	number of generated matrices (effective matrices)
step	controls the number number of void matrices generated in the the burn in process and when effective matrices are generated (see note in rsctrl).
seed	starting value for the random number generator
n_tot	number of matrices in outvec.
outvec	vector of encoded random matrices
ier	error code (see below)

Generation

These classes of objects are returned from rsampler and rsextrobj.

Methods

Both classes have methods for the generic summary function.

Note

By default, all generated matrices plus the original matrix (in position 1) are contained in outvec, thus n_tot = n_eff + 1. If the original matrix is not in outvec then n_tot = n_eff.

If ier is 0, no error was detected. Otherwise use the error function rserror(ier) to obtain some informations.

For saving and loading objects of class RSmpl or RSmplext see the example in rsextrobj.

See Also

rsampler, rsextrobj

rstats *Calculating Statistics for the Sampled Matrices*

Description

This function is used to calculate user defined statistics for the (original and) sampled matrices. A user defined function has to be provided.

Usage

```
rstats(RSobj, userfunc, ...)
```

Arguments

RSobj	object as obtained from using rsampler or rsextrobj
userfunc	a user defined function which performs operations on the (original and) sampled matrices. The first argument in the definition of the user function must be an object of type matrix.
...	further arguments, that are passed to the user function

Value

A list of objects as specified in the user supplied function

Note

The encoded matrices that are contained in the input object RSobj are decoded and passed to the user function in turn. If RSobj is not an object obtained from either rsampler or rsextrobj or no user function is specified an error message is printed. A simple user function, phi.range, is included in the RaschSampler package for demonstration purposes.

rstats can be used to obtain the 0/1 values for any of the sampled matrices (see second example below). Please note, that the output from the user function is stored in a list where the number of components corresponds to the number of matrices passed to the user function (see third example).

See Also

rsampler, rsextrobj

Examples

```
ctr <- rsctrl(burn_in = 10, n_eff = 5, step=10, seed = 12345678, tfixed = FALSE)
mat <- matrix(sample(c(0,1), 50, replace = TRUE), nr = 10)
rso <- rsampler(mat, ctr)
rso_st <- rstats(rso,phi.range)
unlist(rso_st)
```

```
# extract the third generated matrix
# (here, the first is the input matrix)
# and decode it into rsmat

rso2 <- rsextrobj(rso,4,4)
summary(rso2)
rsmat <- rstats(rso2, function(x) matrix(x, nr = rso2$n))
print(rsmat[[1]])

# extract only the first r rows of the third generated matrix

mat<-function(x, nr = nr, r = 3){
  m <- matrix(x, nr = nr)
  m[1:r,]
}
rsmat2 <- rstats(rso2, mat, nr=rso$n, r = 3)
print(rsmat2[[1]])

# apply a user function to the decoded object
print(phi.range(rsmat[[1]]))
```

---

summary.RSctr *Summary Method for Control Objects*

Description

Prints the current definitions for the sampling function.

Usage

```
## S3 method for class 'RSctr'
summary(object, ...)
```

Arguments

object	object of class RSctr as obtained from rsctrl
...	potential further arguments (ignored)

See Also

rsctrl

Examples

```
ctr <- rsctrl(n_eff = 1, seed = 123123123)  # specify controls
summary(ctr)
```

summary.RSmpl *Summary Methods for Sample Objects*

Description

Prints a summary list for sample objects of class RSmpl and RSmplext.

Usage

```
## S3 method for class 'RSmpl'
summary(object, ...)
## S3 method for class 'RSmplext'
summary(object, ...)
```

Arguments

object	object as obtained from rsampler or rsextrobj
...	potential further arguments (ignored)

Details

Describes the status of an sample object.

See Also

rsampler, rsextrobj

Examples

```
ctr <- rsctrl(burn_in = 10, n_eff = 3, step=10, seed = 0, tfixed = FALSE)
mat <- matrix(sample(c(0,1), 50, replace = TRUE), nr = 10)
all_m <- rsampler(mat, ctr)
summary(all_m)

some_m <- rsextrobj(all_m, 1, 2)
summary(some_m)
```

xmpl *Example Data*

Description

Ficitious data sets - matrices with binary responses

Usage

```
data(xmpl)
```

Format

The format of `xmpl` is:
300 rows (referring to subjects)
30 columns (referring to items)

The format of `xmplbig` is:
4096 rows (referring to subjects)
128 columns (referring to items)
`xmplbig` has the maximum dimensions that the RaschSampler package can handle currently.

Examples

```
data(xmpl)
print(head(xmpl))
```

Index

∗ **datasets**
xmpl, 13
∗ **misc**
phi.range, 3
rsampler, 4
RSctr, 5
rsctrl, 6
rsextrmat, 7
rsextrobj, 8
RSmpl, 10
rstats, 11
summary.RSctr, 12
summary.RSmpl, 13
∗ **package**
RaschSampler-package, 2

phi.range, *2*, 3, *11*

RaschSampler-package, 2
rsampler, *2*, 4, *5–11*, *13*
RSctr, *2*, *4*, 5, *5*
rsctrl, *2*, *4, 5*, 6, *6*, *9, 10*, *12*
rsextrmat, 7, *9*
rsextrobj, *2*, 8, *8*, *10, 11*, *13*
RSmpl, *2*, *4*, *9*, 10, *13*
RSmplext, *2*, *13*
RSmplext *(*RSmpl*)*, 10
rstats, *2*, *4, 5*, *8*, 11

summary.RSctr, *7*, 12
summary.RSmpl, *5*, 13
summary.RSmplext *(*summary.RSmpl*)*, 13

xmpl, 13
xmplbig *(*xmpl*)*, 13