# Package: RastaRocket (via r-universe)

October 27, 2026

**Title** Rocket-Fast Clinical Research Reporting

**Version** 1.1.6

**Description** Description of the tables, both grouped and not grouped, with some associated data management actions, such as sorting the terms of the variables and deleting terms with zero numbers.

**License** GPL (>= 3)

**URL** https://github.com/biostatusmr/RastaRocket, https://biostatusmr.github.io/RastaRocket/, https://github.com/BiostatUSMR/RastaRocket

**BugReports** https://github.com/BiostatUSMR/RastaRocket/issues

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Depends** R (>= 4.1.0)

**Imports** dplyr, tidyr, labelled, rlang, gtsummary, forcats, gt, cardx, glue, purrr, ggh4x, ggplot2, ggrepel, scales, viridis, here, pillar

**Suggests** testthat (>= 3.0.0), knitr, rmarkdown, haven

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** USMR CHU de Bordeaux [aut, cre], Valentine Renaudeau [aut], Marion Kret [aut], Matisse Decilap [aut], Sahardid Mohamed Houssein [aut], Mohamedou Sow [aut], Thomas Ferté [aut]

**Maintainer** USMR CHU de Bordeaux <astreinte.usmr@chu-bordeaux.fr>

**Repository** https://cran.r-universe.dev

**Date/Publication** 2026-10-27 18:47:51 UTC

**RemoteUrl** https://github.com/cran/RastaRocket

**RemoteRef** HEAD

**RemoteSha** ae930fd78b77820d9ab6eae576efca09db041fa5

# Contents

add_missing_info . . . 2
add_pvalues . . . 3
ajouter_label_ndm . . . 4
base_table . . . 5
css_generator . . . 6
custom_format . . . 7
custom_headers . . . 8
custom_round . . . 9
customize_table . . . 9
customize_table_body . . . 11
desc_ei_per_grade . . . 12
desc_ei_per_pt . . . 14
desc_var . . . 15
df_builder_ae . . . 18
from_name_to_adress . . . 19
indent_gt_table . . . 20
indent_gtsummary_table . . . 20
intermediate_header . . . 21
plot_butterfly_stacked_barplot . . . 22
plot_dumbell . . . 24
plot_patient_panchart . . . 26
plot_volcano . . . 27
prepare_table . . . 29
remove_labelled_type . . . 30
reverselog_trans . . . 31
riskdifference . . . 32
select_plus . . . 33
start_new_reporting . . . 34
write_css . . . 35
write_html_file . . . 36
write_qmd . . . 37
write_quarto_yml . . . 38
write_rendercopy . . . 38

**Index** **40**

---

`add_missing_info` *Add missing value information to a gtsummary table*

---

## Description

This function merge missing data row into label row of gtsummary object

## Usage

```
add_missing_info(base_table)
```

### Arguments

| | |
|---|---|
| base_table | A gtsummary table object. |

### Value

A gtsummary table object with missing value information and modifications applied.

---

## add_pvalues *Add p-values and separate footnotes to a gtsummary object*

---

### Description

This function adds p-values to a gtsummary table using the specified tests and separates the p-value footnotes.

### Usage

```
add_pvalues(res, tests)
```

### Arguments

| | |
|---|---|
| res | A gtsummary table object. |
| tests | A list of tests to pass to gtsummary::add_p(), or TRUE to use default tests. |

### Value

A gtsummary table object with p-values added and footnotes separated.

### Examples

```
library(gtsummary)
tbl <- trial %>% tbl_summary(by = trt)
tbl <- add_pvalues(tbl, tests = TRUE)
```

`ajouter_label_ndm` *Add "n (dm ; %dm)" to Variable Labels*

## Description

This function appends the text "n (dm ; %dm)" to the labels of all variables in a dataset. It uses the `labelled` package to modify and update variable labels in-place.

## Usage

```
ajouter_label_ndm(data, col_to_skip = NULL)
```

## Arguments

| | |
|---|---|
| `data` | A data frame containing the dataset whose variable labels need to be updated. |
| `col_to_skip` | A column to skip when adding `"n (dm ; %dm)"`. Default is `NULL`. |

## Details

The function iterates over all columns in the dataset and performs the following steps:

1. Retrieves the current label of each variable using `labelled::var_label`.
2. Creates a new label by appending the text `"n (dm ; %dm)"` to the existing label.
3. Updates the variable's label using `labelled::set_variable_labels`.

This is useful when preparing a dataset for descriptive analysis, where it is helpful to display missing data statistics (`n`, `dm`, and `%dm`) alongside variable labels in summary tables.

## Value

A data frame with updated variable labels.

## Examples

```
# Example usage:
library(labelled)

# Create a sample dataset
data <- data.frame(
  var1 = c(1, 2, NA),
  var2 = c("A", "B", NA)
)

# Assign initial labels
data <- labelled::set_variable_labels(
  data,
  var1 = "Variable 1",
  var2 = "Variable 2"
)
```

```
# Add "n (dm ; %dm)" to labels
data <- ajouter_label_ndm(data)

# Check updated labels
labelled::var_label(data)
```

---

base_table *Create a Summary Table with Grouping and Custom Formatting*

---

## Description

This function generates a summary table from a data frame with specified grouping and variable types. It uses the `gtsummary` package to create descriptive statistics for categorical and continuous variables, with options for customizing the rounding and labels.

## Usage

```
base_table(
  data1,
  show_missing_data,
  by_group = FALSE,
  var_group,
  quali = NULL,
  quanti = NULL,
 stat_var_quanti = c("{mean} ({sd})", "{median} ({p25} ; {p75})", "{min} ; {max}"),
  digits = list(r_quanti = 1, r_quali = 1),
  freq_relevel = FALSE
)
```

## Arguments

| | |
|---|---|
| `data1` | A data frame containing the dataset to be analyzed. |
| `show_missing_data` | Default to `NULL`. Should the missing data be displayed. Can be either :<br>• `FALSE`: No missing data displayed<br>• `TRUE`: Missing data displayed<br>• `NULL` (default): will be switch to `anyNA(data1)` value. |
| `by_group` | A boolean (default is FALSE) to analyse by group. |
| `var_group` | A variable used for grouping (if applicable). Defaults to `NULL`. |
| `quali` | A vector of qualitative variables to be described. Defaults to `NULL`. |
| `quanti` | A vector of quantitative variables to be described. Defaults to `NULL`. |
| `stat_var_quanti` | A character vector specifying the statistics to display for continuous variables. Default is `c("{mean} ({sd})", "{median} ({p25}; {p75})", "{min}; {max}")`. |

| | |
|---|---|
| digits | A list, the number of decimal places to round categorical and continuous variable. r_quanti and r_quali can be a single integer or a vector of integer. Default is list(r_quanti = 1, r_quali = 1) |
| freq_relevel | Boolean (default = FALSE). If TRUE, reorder factors by frequency (most to least frequent) using gtsummary. |

## Value

A gtsummary table summarizing the specified variables, grouped by var_group if provided, with customizable statistics and rounding options.

## Examples

```
# Example usage with the iris dataset
base_table(iris, var_group = "Species", show_missing_data = TRUE)
```

---

# css_generator *css_generator*

---

## Description

Generate css to be included in quarto.

## Usage

```
css_generator(path_logo = NULL)
```

## Arguments

| | |
|---|---|
| path_logo | The path to logo, will automatically be guessed on the package. |

## Value

A css string

custom_format *Custom formatting for* gtsummary *and* gt *tables*

## Description

This function takes a gtsummary or gt table and applies custom formatting. It allows you to align columns, apply bold text to certain rows, and adjust column widths if specified.

## Usage

```
custom_format(gt_table, align = "right", column_size = NULL)
```

## Arguments

| | |
|---|---|
| gt_table | A gt table object (also handles gtsummary tables by converting them). |
| align | A character string defining the alignment of specific columns. Passed to the gt::cols_align() function (e.g., "left", "right", "center"). Default is "right". |
| column_size | A named list or vector defining the width of columns (optional). The list should specify the width for one or more columns. If not provided, column widths will not be modified. |

## Value

A gt table object with the specified formatting applied. The table will have columns aligned according to the align parameter, and cells in the "label" rows will have bold text. If column_size is provided, the column widths will be adjusted accordingly.

## Examples

```
# Example usage
tbl <- RastaRocket::desc_var(iris,
  table_title = "test",
  group = TRUE,
  var_group = "Species")
formatted_tbl <- custom_format(tbl,
  align = "center",
  column_size = list(label ~ gt::pct(50)))
formatted_tbl
```

custom_headers *Modify gtsummary table headers and add a spanning header*

## Description

This function customizes the column headers, optional spanning header, and table caption for a gtsummary table. It supports adding a feature name, total label, group title, and formats missing data presentation.

## Usage

```
custom_headers(
  base_table_missing,
  var_characteristic = NULL,
  show_missing_data = TRUE,
  show_n_per_group = TRUE,
  var_tot = NULL,
  var_group = NULL,
  group_title = NULL,
  table_title
)
```

## Arguments

| | |
|---|---|
| base_table_missing | A gtsummary table object (typically output from previous steps). |
| var_characteristic | Optional. A string to label the features column. |
| show_missing_data | Logical. If TRUE, adds missing data info to column headers. |
| show_n_per_group | A boolean indicating whether to display group sizes (n) for each level of the grouping variable. |
| var_tot | Optional. A string to label the total column. |
| var_group | Optional. Name of a grouping variable for adding a spanning header. |
| group_title | Optional. Title for the spanning header. If NULL, uses the variable label or name. |
| table_title | Title for the entire table. |

## Value

A gtsummary table object with updated headers, spanning header, and caption.

## custom_round *Custom Round and Format*

### Description

Rounds a numeric value to a specified number of decimal places and formats it to always show the specified number of decimal places, including trailing zeros.

### Usage

```
custom_round(x, digits = 1)
```

### Arguments

| | |
|---|---|
| x | A numeric vector to be rounded and formatted. |
| digits | An integer indicating the number of decimal places to round to. Defaults to 1. |

### Value

A character vector with the rounded and formatted numbers.

### Examples

```
RastaRocket::custom_round(3.14159)      # "3.1"
RastaRocket::custom_round(3.14159, 3)   # "3.142"
RastaRocket::custom_round(c(2, 2.5), 2) # "2.00" "2.50"
```

## customize_table *Customize a Summary Table with Grouping, Missing Data, and Custom Titles*

### Description

This function customizes a `gtsummary` summary table by adding an overall column, handling missing data, applying group-specific statistics, and updating headers and captions. It provides flexible options for grouping, displaying missing data, and customizing table titles.

### Usage

```
customize_table(
  base_table,
  by_group = FALSE,
  var_group,
  add_total,
  show_missing_data,
```

```
  show_n_per_group,
  group_title,
  table_title,
  var_title,
  var_tot = NULL,
  var_characteristic = NULL
)
```

## Arguments

| | |
|---|---|
| base_table | A gtsummary table object, typically generated using functions like gtsummary::tbl_summary. |
| by_group | A boolean (default is FALSE) to analyse by group. |
| var_group | A variable used for grouping (if applicable). Defaults to NULL. |
| add_total | A boolean (default is TRUE) to add total column or not when var_group is specified. |
| show_missing_data | Default to NULL. Should the missing data be displayed. Can be either :<br>• FALSE: No missing data displayed<br>• TRUE: Missing data displayed<br>• NULL (default): will be switch to anyNA(data1) value. |
| show_n_per_group | Default to FALSE. Should the 'N' appears in the column header of the groups. Can be either :<br>• FALSE: No 'N' is shown<br>• TRUE: 'N' is shown |
| group_title | A character string specifying the title for the grouping variable. Default is NULL and get the label or the variable. |
| table_title | A character string specifying the title of the table. |
| var_title | A character string for the title of the variable column in the table. Defaults to "Variable". |
| var_tot | A string specifying the name of total column. Default is NULL and will guess from theme_gtsummary_language(). |
| var_characteristic | A string specifying the name of characteristic column. Default is NULL and will guess from theme_gtsummary_language(). |

## Details

- The show_missing_data parameter determines whether missing data counts and percentages are displayed:
  - If TRUE, missing data columns are added.
  - If FALSE, only non-missing data counts are displayed.
- Headers for columns and spanning headers are customized using the group_title, table_title, and var_title arguments.

## Value

A customized gtsummary table object with added columns, headers, captions, and modifications based on the provided arguments.

## Examples

```
# Example usage with a sample gtsummary table
library(gtsummary)
base_table <- trial %>%
  gtsummary::tbl_summary(
    type = list(
      gtsummary::all_continuous() ~ "continuous2"
    ),
    by = "trt",
    missing = "always",
    missing_stat = "{N_nonmiss} ({N_miss})",
    statistic = list(
      gtsummary::all_continuous2() ~ c("{mean} ({sd})",
                                       "{median} ({p25} ; {p75})",
                                       "{min} ; {max}")
    ))

customize_table(
  base_table,
  var_group = "trt",
  add_total = TRUE,
  show_missing_data = TRUE,
  show_n_per_group = FALSE,
  group_title = "Treatment Group",
  table_title = "Summary Statistics",
  var_title = "Variables",
  var_tot = "Total"
)
```

---

# customize_table_body *Customize Table Body*

---

## Description

This function modifies a data frame by updating the stat_0 column. If any values in stat_0 are missing (NA), they are replaced by the values from the n column. After the replacement, the n column is removed from the data frame.

## Usage

```
customize_table_body(data)
```

### Arguments

| | |
|---|---|
| data | A data frame that must contain at least two columns:<br>• stat_0: A column whose missing (NA) values are to be replaced.<br>• n: A column providing replacement values for stat_0 when its values are missing. |

### Details

- The function uses dplyr::case_when to conditionally update the stat_0 column.
- After the replacement process, the n column is dropped using dplyr::select(-n).
- This function is particularly useful for cleaning and preparing table data.

### Value

A modified data frame with:

- Updated stat_0 values (replaced with n values where NA is found).
- The n column removed after integration.

### Examples

```
# Example data
data <- data.frame(
  stat_0 = c(NA, "B", "C"),
  n = c(10, 20, 30)
)

# Apply the function
modified_data <- RastaRocket::customize_table_body(data)
print(modified_data)
```

---

## desc_ei_per_grade *desc_ei_per_grade*

---

### Description

A function to describe adverse events (AE) by grade.

### Usage

```
desc_ei_per_grade(
  df_pat_grp,
  df_pat_grade,
  id_col = "USUBJID",
  group_col = "RDGRPNAME",
  ei_num_col = "EINUM",
```

```
  ei_grdm_col = "EIGRDM",
  ei_grav_col = "EIGRAV",
  severity = TRUE,
  digits = 1,
  language = "fr"
)
```

## Arguments

| | |
|---|---|
| df_pat_grp | A dataframe with two columns: USUBJID (Patient id) and RDGRPNAME (the RCT arm). |
| df_pat_grade | A dataframe with four columns: USUBJID (Patient id), EINUM (the AE id), EIGRDM (the AE grade) and EIGRAV (the AE severity which must be "Grave" and "Non grave"). |
| id_col | Patient id column (default: "USUBJID"). |
| group_col | group column, the rct arm (default: "RDGRPNAME"). |
| ei_num_col | AE id column (default: "EINUM"). |
| ei_grdm_col | AE grade column (default: "EIGRDM"). |
| ei_grav_col | AE severity column (default: "EIGRAV"). |
| severity | A boolean to show severe adverse event line or not (default: TRUE). |
| digits | Number of digits for percentages |
| language | 'fr' default or 'en' |

## Value

A gt table summarizing the AE by grade.

## Examples

```
df_pat_grp <- data.frame(USUBJID = paste0("ID_", 1:10),
                         RDGRPNAME = c(rep("A", 3), rep("B", 3), rep("C", 4)))

df_pat_grade <- data.frame(USUBJID = c("ID_1", "ID_1",
                                       "ID_2",
                                       "ID_8",
                                       "ID_9"),
                           EINUM = c(1, 2,
                                     1,
                                     1,
                                     1),
                           EIGRDM = c(1, 3,
                                      4,
                                      2,
                                      4),
                           EIGRAV = c("Grave", "Non grave",
                                      "Non grave",
                                      "Non grave",
                                      "Grave"))
```

```
desc_ei_per_grade(df_pat_grp = df_pat_grp,
                  df_pat_grade = df_pat_grade)
```

---

`desc_ei_per_pt` *desc_ei_per_pt*

---

## Description

A function to describe AE by soc and pt

## Usage

```
desc_ei_per_pt(
  df_pat_grp,
  df_pat_llt,
  id_col = "USUBJID",
  group_col = "RDGRPNAME",
  ei_num_col = "EINUM",
  ei_llt_col = "EILLTN",
  ei_soc_col = "EISOCPN",
  ei_pt_col = "EIPTN",
  language = "fr",
  order_by_freq = TRUE,
  digits = 1
)
```

## Arguments

| | |
|---|---|
| `df_pat_grp` | A dataframe with two columns: USUBJID (Patient id) and RDGRPNAME (the RCT arm). |
| `df_pat_llt` | A dataframe with columns: USUBJID (patient id), EINUM (AE id), llt (AE LLT), pt (AE PT), soc (AE SOC) |
| `id_col` | Patient id column (default: "USUBJID"). |
| `group_col` | group column, the rct arm (default: "RDGRPNAME"). |
| `ei_num_col` | AE id column (default: "EINUM"). |
| `ei_llt_col` | AE LLT column (default: "EILLTN"). |
| `ei_soc_col` | AE SOC column (default: "EISOCPN"). |
| `ei_pt_col` | AE PT column (default: "EIPTN") |
| `language` | 'fr' default or 'en' |
| `order_by_freq` | Logical. Should PT and SOC be ordered by frequency? Defaults to TRUE. If FALSE, PT and SOC are ordered alphabetically. |
| `digits` | Number of digits for percentages |

## Value

A gt table

## Examples

```
df_pat_grp <- data.frame(USUBJID = paste0("ID_", 1:10),
                         RDGRPNAME = c(rep("A", 3), rep("B", 3), rep("C", 4)))

df_pat_llt <- data.frame(USUBJID = c("ID_1", "ID_1",
                                     "ID_2",
                                     "ID_4",
                                     "ID_9"),
                         EINUM = c(1, 2, 1, 1, 1),
                         EILLTN = c("llt1", "llt1",
                                 "llt4", "llt3",
                                 "llt1"),
                         EIPTN = c("Arrhythmia", "Myocardial Infarction",
                                 "Arrhythmia", "Pneumonia",
                                 "Pneumonia"),
                         EISOCPN = c("Cardiac Disorders", "Cardiac Disorders",
                                 "Cardiac Disorders", "Infections",
                                 "Infections"))

desc_ei_per_pt(df_pat_grp = df_pat_grp,
               df_pat_llt = df_pat_llt)
```

---

# desc_var *Generate Descriptive Tables for Variables*

---

## Description

This function creates descriptive tables for variables in a dataset. It can handle qualitative and quantitative variables, grouped or ungrouped, and supports multiple configurations for handling missing data (DM).

## Usage

```
desc_var(
  data1,
  table_title = "",
  quali = NULL,
  quanti = NULL,
  add_total = TRUE,
  var_title = "Variable",
  by_group = FALSE,
  var_group = NULL,
  group_title = NULL,
```

```
 stat_var_quanti = c("{mean} ({sd})", "{median} ({p25} ; {p75})", "{min} ; {max}"),
  digits = list(r_quanti = 1, r_quali = 0),
  drop_levels = TRUE,
  freq_relevel = FALSE,
  tests = FALSE,
  show_n_per_group = FALSE,
  show_missing_data = NULL,
  var_tot = NULL,
  var_characteristic = NULL,
  include_all_na_cat = TRUE
)
```

## Arguments

| | |
|---|---|
| data1 | A data frame containing the dataset to be analyzed. |
| table_title | A character string specifying the title of the table. |
| quali | A vector of qualitative variables to be described. Defaults to NULL. |
| quanti | A vector of quantitative variables to be described. Defaults to NULL. |
| add_total | A boolean (default is TRUE) to add total column or not when var_group is specified. |
| var_title | A character string for the title of the variable column in the table. Defaults to "Variable". |
| by_group | A boolean (default is FALSE) to analyse by group. |
| var_group | A variable used for grouping (if applicable). Defaults to NULL. |
| group_title | A character string specifying the title for the grouping variable. Default is NULL and get the label or the variable. |
| stat_var_quanti | A character vector specifying the statistics to display for continuous variables. Default is c("{mean} ({sd})", "{median} ({p25}; {p75})", "{min}; {max}"). |
| digits | A list, the number of decimal places to round categorical and continuous variable. r_quanti and r_quali can be a single integer or a vector of integer. Default is list(r_quanti = 1, r_quali = 1) |
| drop_levels | Boolean (default = TRUE). Drop unused levels. |
| freq_relevel | Boolean (default = FALSE). If TRUE, reorder factors by frequency (most to least frequent) using gtsummary. |
| tests | A value in order to add p value. Default to FALSE OPTION :<br>• FALSE: No p-value add<br>• TRUE: Add p-value made by default by gtsummary. See gtsummary add_p() options.<br>• list(): To force tests. See gtsummary add_p() options. |
| show_n_per_group | Default to FALSE. Should the 'N' appears in the column header of the groups. Can be either :<br>• FALSE: No 'N' is shown |

- TRUE: 'N' is shown

show_missing_data
: Default to NULL. Should the missing data be displayed. Can be either :
  - FALSE: No missing data displayed
  - TRUE: Missing data displayed
  - NULL (default): will be switch to anyNA(data1) value.

var_tot
: A string specifying the name of total column. Default is NULL and will guess from theme_gtsummary_language().

var_characteristic
: A string specifying the name of characteristic column. Default is NULL and will guess from theme_gtsummary_language().

include_all_na_cat
: Should the categorical variable with a missing levels (all values are NA) be displayed. Default to TRUE

## Details

The function processes the dataset according to the specified parameters and generates descriptive tables.

- It first uses the ajouter_label_ndm() function to append missing data statistics to variable labels.
- Depending on the group and DM arguments, it adjusts the dataset and creates tables using helper functions like desc_group, desc_degroup, and desc_degroup_group.
- Qualitative variables are reordered, and unused levels are dropped when necessary.

## Value

A gtsummary table object containing the descriptive statistics.

## Examples

```
# Example usage:
library(dplyr)

# Sample dataset
data1 <- data.frame(
  group = c("A", "B", "B", "C"),
  var1 = c(1, 2, 3, NA),
  var2 = c("X", "Y", "X", NA)
)

# Generate descriptive table
table <- desc_var(
  data1 = data1,
  table_title = "Descriptive Table",
  quanti = "var1"
)
```

```
# Order categorical features by frequency
table1 <- desc_var(
  data1 = data1,
  table_title = "Descriptive Table",
  quanti = "var1",
  freq_relevel = TRUE)

  # Round quantitative and qualitative features using  a vector of integer
  table2 <- desc_var(
    data1 = iris,
    quanti = "Sepal.Length",
    stat_var_quanti = c("{sum}", "{mean} ({sd})"),
    digits = list(r_quanti = c(1, 3, 2), r_quali = c(0, 2))
    )
```

---

`df_builder_ae` *Prepare a dataframe for creating AE plots*

---

## Description

Prepare a dataframe for creating AE plots

## Usage

```
df_builder_ae(
  df_pat_grp,
  df_pat_llt,
  id_col = "USUBJID",
  group_col = "RDGRPNAME",
  ei_num_col = "EINUM",
  ei_llt_col = "EILLTN",
  ei_soc_col = "EISOCPN",
  ei_pt_col = "EIPTN",
  ref_grp = NULL
)
```

## Arguments

| | |
|---|---|
| `df_pat_grp` | A dataframe with two columns: USUBJID (Patient id) and RDGRPNAME (the RCT arm). |
| `df_pat_llt` | A dataframe with columns: USUBJID (patient id), EINUM (AE id), llt (AE LLT), pt (AE PT), soc (AE SOC) |
| `id_col` | Patient id column (default: "USUBJID"). |
| `group_col` | group column, the rct arm (default: "RDGRPNAME"). |
| `ei_num_col` | AE id column (default: "EINUM"). |

| | |
|---|---|
| ei_llt_col | AE LLT column (default: "EILLTN"). |
| ei_soc_col | AE SOC column (default: "EISOCPN"). |
| ei_pt_col | AE PT column (default: "EIPTN") |
| ref_grp | (Optional) A reference group for comparisons. Defaults to the first group in df_pat_grp. |

## Value

A dataframe with all the info to build AE plots

---

# from_name_to_adress *Convert a Name to an Email Address*

---

## Description

This function transforms a given name into an email address following the format firstname.lastname@chu-bordeaux.fr.

## Usage

```
from_name_to_adress(name = "Peter Parker")
```

## Arguments

| | |
|---|---|
| name | A character string representing a full name. Default is "Peter Parker". |

## Value

A character string containing the generated email address.

## Examples

```
from_name_to_adress("John Doe")
from_name_to_adress()
```

## indent_gt_table *Text indentation for* gt *tables*

### Description

Text indentation for gt tables

### Usage

```
indent_gt_table(g_table, indent = 0)
```

### Arguments

| | |
|---|---|
| g_table | A gt table object |
| indent | A numerical value corresponding to the pixel value, which defines the text indentation (default = 0 corresponding to px(0)). 30 ~ px(30) should be a good compromise. |

### Value

A gt table object with indentation applied.

### Examples

```
tbl_bis <- RastaRocket::desc_var(
iris,
table_title = "test",
quali = "Species")

tbl_bis |> indent_gt_table(indent = 30)
tbl_bis |> indent_gt_table(indent = 60)
```

## indent_gtsummary_table *Text indentation for* gtsummary *tables*

### Description

Text indentation for gtsummary tables

### Usage

```
indent_gtsummary_table(gts_table, indent = 4)
```

### Arguments

| | |
|---|---|
| gts_table | A gtsummary table object |
| indent | A numerical value indicating how many space to indent text (default = 4). A value of 8 should be a good compromise. |

### Value

A gtsummary table object with indentation applied.

### Examples

```
tbl <- iris |>  dplyr::select(Species, Sepal.Length) |> RastaRocket::desc_var(
table_title = "test",
quali = "Species")
tbl_1 <- tbl |> indent_gtsummary_table(indent = 4)
tbl_2 <- tbl |> indent_gtsummary_table(indent = 8)
tbl_3 <- tbl |> indent_gtsummary_table(indent = 16)
```

---

## intermediate_header *Intermediate Header*

---

### Description

Combines multiple descriptive tables into a single table with customized row group headers and styling. This function accepts a list of tables and corresponding group headers, applies consistent styling, and outputs a styled gt table.

### Usage

```
intermediate_header(
  tbls,
  group_header,
  color = "#8ECAE6",
  size = 16,
  align = "center",
  weight = "bold"
)
```

### Arguments

| | |
|---|---|
| tbls | A list of descriptive tables (generated by RastaRocket::desc_var or similar functions). |
| group_header | A character vector specifying the headers for each group of tables. Must be the same length as tbls. |
| color | A character string specifying the background color for the row group headers. Default is "#8ECAE6". |

| | |
|---|---|
| size | An integer specifying the font size for the row group headers. Default is 16. |
| align | A character string specifying text alignment for the row group headers. Options are "left", "center", or "right". Default is "center". |
| weight | A character string specifying the font weight for the row group headers. Options include "normal", "bold", etc. Default is "bold". |

## Value

A styled gt table combining the input tables with row group headers.

## Examples

```
# Load necessary libraries
library(RastaRocket)
library(dplyr)

# Generate sample data
data <- data.frame(
  Age = c(rnorm(45, mean = 50, sd = 10), rep(NA, 5)),
  sexe = sample(c("Femme", "Homme"), 50, replace = TRUE, prob = c(0.6, 0.4)),
  quatre_modalites = sample(c("A", "B", "C", "D"), 50, replace = TRUE)
)

# Create descriptive tables
tb1 <- data %>%
  dplyr::select(Age, sexe) %>%
  RastaRocket::desc_var(table_title = "Demographics", group = FALSE)

tb2 <- data %>%
  dplyr::select(quatre_modalites) %>%
  RastaRocket::desc_var(table_title = "Modalities", group = FALSE)

# Combine and style tables
intermediate_header(
  tbls = list(tb1, tb2),
  group_header = c("Demographics", "Modalities")
)
```

---

# plot_butterfly_stacked_barplot

*Butterfly Stacked Bar Plot for Adverse Event Grades*

---

## Description

Creates a butterfly stacked bar plot to visualize the frequency of adverse event (AE) grades across patient groups, with system organ class (SOC) and preferred terms (PT) as labels.

## Usage

```
plot_butterfly_stacked_barplot(
  df_pat_grp,
  df_pat_llt,
  id_col = "USUBJID",
  group_col = "RDGRPNAME",
  ei_num_col = "EINUM",
  ei_pt_col = "EIPTN",
  ei_soc_col = "EISOCPN",
  ei_grdm_col = "EIGRDM",
  ei_llt_col = "EILLTN",
  ref_grp = NULL,
  max_text_width = 9,
  vec_fill_color = viridis::viridis(n = 4)
)
```

## Arguments

| | |
|---|---|
| df_pat_grp | A dataframe with two columns: USUBJID (Patient id) and RDGRPNAME (the RCT arm). |
| df_pat_llt | A dataframe with columns: USUBJID (patient id), EINUM (AE id), llt (AE LLT), pt (AE PT), soc (AE SOC) and EIGRDM (severity grade) |
| id_col | Name of the patient ID column (default: "USUBJID"). |
| group_col | Name of the randomization group column (default: "RDGRPNAME"). |
| ei_num_col | Name of the AE id column (default: "EINUM"). |
| ei_pt_col | Name of the AE PT column (default: "EIPTN"). |
| ei_soc_col | Name of the AE SOC column (default: "EISOCPN"). |
| ei_grdm_col | AE grade column (default: "EIGRDM"). |
| ei_llt_col | Name of the AE LLT column (default: "EILLTN"). |
| ref_grp | A character string specifying the reference group (used for alignment in the plot). If NULL (default), the first level of df_pat_grp$grp is used. |
| max_text_width | An integer specifying the maximum width (in characters) for SOC labels before wrapping to the next line. Default is 9. |
| vec_fill_color | A vector of colors used for filling the AE grade bars. Default is viridis::viridis(n = 4). |

## Details

The function processes input data to calculate the frequency of adverse events per patient group and AE grade. It then generates a stacked bar plot where:

- The x-axis represents the percentage of patients experiencing an AE.
- The y-axis represents PTs (with SOCs as facets).
- Bars are stacked by AE grade.
- Labels for PTs are displayed in the center.

- The left and right panels correspond to different patient groups.

The function utilizes the ggh4x package to adjust panel sizes and axes for a symmetrical butterfly plot.

## Value

A ggplot2 object representing the butterfly stacked bar plot.

## Examples

```
df_pat_grp <- data.frame(
 USUBJID = paste0("ID_", 1:10),
 RDGRPNAME = c(rep("A", 5), rep("B", 5))
)

df_pat_llt <- data.frame(
  USUBJID = c("ID_1", "ID_1", "ID_2", "ID_4", "ID_9"),
  EINUM = c(1, 2, 1, 1, 1),
  EILLTN = c("llt1", "llt2", "llt1", "llt3", "llt4"),
 EIPTN = c("Arrhythmia", "Myocardial Infarction", "Arrhythmia", "Pneumonia", "Pneumonia"),
  EISOCPN = c("Cardiac Disorders", "Cardiac Disorders", "Cardiac Disorders",
  "Infections", "Infections"),
  EIGRDM = c(1, 3, 4, 2, 4)
)

plot_butterfly_stacked_barplot(df_pat_grp, df_pat_llt)
```

---

# plot_dumbell *Plot a Dumbbell Chart for Adverse Events Analysis*

---

## Description

This function creates a dumbbell plot comparing the occurrence of adverse events across different patient groups. The plot includes the total number of adverse events, the proportion of patients affected, and the risk difference with confidence intervals.

## Usage

```
plot_dumbell(
  df_pat_grp,
  df_pat_llt,
  id_col = "USUBJID",
  group_col = "RDGRPNAME",
  ei_num_col = "EINUM",
  ei_llt_col = "EILLTN",
  ei_soc_col = "EISOCPN",
  ei_pt_col = "EIPTN",
```

```
  ref_grp = NULL,
  colors_arm = c("#1b9e77", "#7570b3"),
  color_label = "Arm"
)
```

## Arguments

| | |
|---|---|
| df_pat_grp | A dataframe with two columns: USUBJID (Patient id) and RDGRPNAME (the RCT arm). |
| df_pat_llt | A dataframe with columns: USUBJID (patient id), EINUM (AE id), llt (AE LLT), pt (AE PT), soc (AE SOC) |
| id_col | Name of the patient ID column (default: "USUBJID"). |
| group_col | Name of the randomization group column (default: "RDGRPNAME"). |
| ei_num_col | Name of the AE id column (default: "EINUM"). |
| ei_llt_col | Name of the AE LLT column (default: "EILLTN"). |
| ei_soc_col | Name of the AE SOC column (default: "EISOCPN"). |
| ei_pt_col | Name of the AE PT column (default: "EIPTN"). |
| ref_grp | (Optional) A reference group for comparisons. Defaults to the first group in df_pat_grp. |
| colors_arm | A vector of colors for the patient groups. Defaults to c("#1b9e77", "#7570b3"). |
| color_label | A string specifying the legend label for the groups. Defaults to "Arm". |

## Value

A ggplot object displaying the dumbbell chart.

## Examples

```
df_pat_grp <- data.frame(
 USUBJID = paste0("ID_", 1:10),
 RDGRPNAME = c(rep("A", 5), rep("B", 5))
)

df_pat_llt <- data.frame(
  USUBJID = c("ID_1", "ID_1", "ID_2", "ID_4", "ID_9"),
  EINUM = c(1, 2, 1, 1, 1),
  EILLTN = c("llt1", "llt2", "llt1", "llt3", "llt4"),
 EIPTN = c("Arrhythmia", "Myocardial Infarction", "Arrhythmia", "Pneumonia", "Pneumonia"),
  EISOCPN = c("Cardiac Disorders", "Cardiac Disorders", "Cardiac Disorders",
  "Infections", "Infections"),
  EIGRDM = c(1, 3, 4, 2, 4)
)

plot_dumbell(df_pat_llt = df_pat_llt, df_pat_grp = df_pat_grp)
```

`plot_patient_panchart` *Plot a Patient Span Chart (Panchart)*

## Description

This function visualizes the timeline of adverse events (AEs), treatments, and randomization for a selected patient. The span chart helps track AE duration and treatment events relative to randomization.

## Usage

```
plot_patient_panchart(
  df_soc_pt,
  df_pat_grp_rando,
  df_pat_pt_grade_date,
  df_pat_treatment_date,
  pat_id,
 vec_fill_color = viridis::viridis(n = 4, direction = -1, end = 0.95, option = "magma")
)
```

## Arguments

| | |
|---|---|
| `df_soc_pt` | A data frame mapping System Organ Class (SOC) to Preferred Terms (PT). |
| `df_pat_grp_rando` | A data frame containing patient IDs, randomization groups, and randomization dates. |
| `df_pat_pt_grade_date` | A data frame with patient IDs, PT terms, AE grades, start and end dates of AEs. |
| `df_pat_treatment_date` | A data frame with patient IDs and treatment dates. |
| `pat_id` | A character string specifying the patient ID to plot. |
| `vec_fill_color` | A vector of colors for AE grades. Default is `viridis::viridis(n = 4)`. |

## Value

A ggplot object representing the patient span chart.

## Examples

```
df_pat_grp_rando <- data.frame(
  id_pat = c("ID_1", "ID_2"),
  grp = c("A", "B"),
  rando_date = c("2020-12-01", "2021-01-03")
)

df_pat_pt_grade_date <- data.frame(
  id_pat = c("ID_1", "ID_1", "ID_1", "ID_1", "ID_2"),
```

```
  pt = c("Arrhythmia", "Myocardial Infarction", "Arrhythmia",
         "Pneumonia", "Pneumonia"),
  grade = c(4, 2, 1, 3, 4),
  start = c("2021-01-01", "2021-02-03", "2021-01-02", "2021-03-05", "2021-02-01"),
  end = c("2021-01-14", "2021-03-03", "2021-01-22", "2021-05-05", "2021-02-03")
)

df_pat_treatment_date <- data.frame(
  id_pat = c("ID_1", "ID_1", "ID_1"),
  treatment_date = c("2021-01-25", "2021-03-01", "2021-01-20")
)
df_soc_pt <- data.frame(
  pt = c("Arrhythmia", "Myocardial Infarction", "Pneumonia", "Sepsis"),
  soc = c("Cardiac Disorders", "Cardiac Disorders", "Infections", "Infections")
)

plot_patient_panchart(
  df_soc_pt = df_soc_pt,
  df_pat_grp_rando = df_pat_grp_rando,
  df_pat_pt_grade_date = df_pat_pt_grade_date,
  df_pat_treatment_date = df_pat_treatment_date,
  pat_id = "ID_1"
)
```

---

`plot_volcano` *Volcano Plot for Adverse Event Analysis*

---

## Description

Generates a volcano plot to visualize the association between adverse events and patient groups.

## Usage

```
plot_volcano(
  df_pat_grp,
  df_pat_llt,
  id_col = "USUBJID",
  group_col = "RDGRPNAME",
  ei_num_col = "EINUM",
  ei_llt_col = "EILLTN",
  ei_soc_col = "EISOCPN",
  ei_pt_col = "EIPTN",
  ref_grp = NULL,
  colors_arm = c("#1b9e77", "#7570b3"),
  size = "nb_pat"
)
```

## Arguments

| | |
|---|---|
| df_pat_grp | A dataframe with two columns: USUBJID (Patient id) and RDGRPNAME (the RCT arm). |
| df_pat_llt | A data frame with USUBJID (subject ID), EINUM (AE ID), EINUM (AE id), EILLTN (LLT identifier), EIPTN (PT identifier), EISOCPN (soc identifier) and EIGRDM (severity grade) |
| id_col | Name of the patient ID column (default: "USUBJID"). |
| group_col | Name of the randomization group column (default: "RDGRPNAME"). |
| ei_num_col | Name of the AE id column (default: "EINUM"). |
| ei_llt_col | Name of the AE LLT column (default: "EILLTN"). |
| ei_soc_col | Name of the AE SOC column (default: "EISOCPN"). |
| ei_pt_col | Name of the AE PT column (default: "EIPTN"). |
| ref_grp | (Optional) A reference group for comparisons. Defaults to the first group in df_pat_grp. |
| colors_arm | A character vector of length two specifying the colors for the two patient groups in the plot. Default is c("#1b9e77", "#7570b3"). |
| size | A character string specifying the metric used for point sizes in the plot. Options are:<br>• "nb_pat": Number of patients (default).<br>• "nb_ei": Number of adverse events. |

## Details

The function first processes input data using df_builder_ae(), then calculates relevant statistics such as risk difference (RD) and p-values. The volcano plot displays:

- RD on the x-axis (risk difference between groups).
- -log10(p-value) on the y-axis (significance level).
- Point colors indicating which group has an increased risk.
- Point sizes reflecting either the number of patients or events.
- A horizontal dashed line at p = 0.05 for significance threshold.

## Value

A ggplot2 object representing the volcano plot.

## Examples

```
df_pat_grp <- data.frame(
 USUBJID = paste0("ID_", 1:10),
 RDGRPNAME = c(rep("A", 5), rep("B", 5))
)

df_pat_llt <- data.frame(
  USUBJID = c("ID_1", "ID_1", "ID_2", "ID_4", "ID_9"),
```

```
  EINUM = c(1, 2, 1, 1, 1),
  EILLTN = c("llt1", "llt2", "llt1", "llt3", "llt4"),
 EIPTN = c("Arrhythmia", "Myocardial Infarction", "Arrhythmia", "Pneumonia", "Pneumonia"),
  EISOCPN = c("Cardiac Disorders", "Cardiac Disorders", "Cardiac Disorders",
  "Infections", "Infections"),
  EIGRDM = c(1, 3, 4, 2, 4)
)

plot_volcano(df_pat_grp, df_pat_llt)
```

---

`prepare_table` *Prepare a Data Frame for Summarization with Custom Missing Data Handling and Factor Ordering*

---

## Description

This function prepares a data frame for summarization by handling missing data based on the `show_missing_data` argument and applying the specified data manipulation (DM) option to factor variables. It provides flexibility for data cleaning and ordering before summarizing with functions like `gtsummary`.

## Usage

```
prepare_table(
  data1,
  by_group = FALSE,
  var_group = NULL,
  drop_levels = TRUE,
  show_missing_data = TRUE,
  include_all_na_cat = TRUE
)
```

## Arguments

| | |
|---|---|
| `data1` | A data frame containing the dataset to be analyzed. |
| `by_group` | A boolean (default is FALSE) to analyse by group. |
| `var_group` | A variable used for grouping (if applicable). Defaults to `NULL`. |
| `drop_levels` | Boolean (default = TRUE). Drop unused levels. |
| `show_missing_data` | Default to `NULL`. Should the missing data be displayed. Can be either :<br>• `FALSE`: No missing data displayed<br>• `TRUE`: Missing data displayed<br>• `NULL` (default): will be switch to `anyNA(data1)` value. |
| `include_all_na_cat` | Should the categorical variable with a missing levels (all values are NA) be displayed. Default to `TRUE` |

### Details

- The DM option defines the data manipulation to be applied to factor variables:
  - "tout": Both order factor levels and drop unused levels.
  - "tri": Only order factor levels.
  - "remove": Drop unused factor levels without ordering.

### Examples

```
# Example usage with the iris dataset
prepare_table(iris)
```

---

## remove_labelled_type *Remove the "labelled" class from a variable while keeping its label*

---

### Description

Strips the labelled type (as created by the **haven** or **labelled** packages) from a vector and converts it back to a plain base R character or numeric vector. The variable label, stored in the "label" attribute, is preserved on the returned vector. Value labels ("labels" attribute) are not carried over.

### Usage

```
remove_labelled_type(x)
```

### Arguments

| | |
|---|---|
| x | A vector, typically a column of a data frame. If x is a labelled character or numeric vector, it is converted to a base character or numeric vector. Otherwise it is returned as is. |

### Details

Detection relies on pillar::type_sum(), so a vector is treated as labelled when its type summary is "labelled". Any other input is returned unchanged.

### Value

A vector of the same values as x:

- if x is labelled and character, a character vector;
- if x is labelled and numeric, a numeric vector;
- if x is not labelled, x unchanged.

When x carries a variable label, it is kept in the "label" attribute of the result.

## Errors

An error is thrown if x is labelled but is neither character nor numeric (for example a labelled factor or logical vector).

## See Also

pillar::type_sum(), haven::zap_labels(), haven::labelled()

## Examples

```
library(haven)

# Labelled numeric vector
x <- labelled(c(1, 2, 1), labels = c(No = 1, Yes = 2))
attr(x, "label") <- "Answer to question 1"

y <- remove_labelled_type(x)
class(y)          # "numeric"
attr(y, "label")  # "Answer to question 1"

# Labelled character vector
z <- labelled(c("a", "b"), labels = c(Alpha = "a", Beta = "b"))
remove_labelled_type(z)

# Non-labelled input is returned unchanged
remove_labelled_type(c(1, 2, 3))
```

---

# reverselog_trans *Reverse Log Transformation*

---

## Description

Creates a transformation object for a reverse log scale, which can be used in ggplot2 scales.

## Usage

```
reverselog_trans(base = exp(1))
```

## Arguments

| | |
|---|---|
| base | A numeric value specifying the logarithm base. Default is the natural logarithm (exp(1)). |

## Details

This function defines a reverse logarithmic transformation, where the transformation function is

$$-\log(x, \text{base})$$

and the inverse function is

$$\text{base}^{-x}$$

. It is useful for cases where a decreasing log scale is needed.

## Value

A transformation object compatible with ggplot2 scales.

## Examples

```
library(scales)
rev_log <- reverselog_trans(10)
rev_log$trans(100)  # -2
rev_log$inverse(-2) # 100
```

---

`riskdifference` *riskdifference*

---

## Description

A function from the fmsb package to compute risk difference. Calculate risk difference (a kind of attributable risk / excess risk) and its confidence intervals based on approximation, followed by null hypothesis (risk difference equals to 0) testing.

## Usage

```
riskdifference(a, b, N1, N0, CRC = FALSE, conf.level = 0.95)
```

## Arguments

| | |
|---|---|
| `a` | The number of disease occurence among exposed cohort. |
| `b` | The number of disease occurence among non-exposed cohort. |
| `N1` | The population at risk of the exposed cohort. |
| `N0` | The population at risk of the unexposed cohort. |
| `CRC` | Logical. If TRUE, calculate confidence intervals for each risk. Default is FALSE. |
| `conf.level` | Probability for confidence intervals. Default is 0.95. |

## Value

A list with the results

`select_plus` *Column selection with optional grouping variable*

## Description

This function extends `dplyr::select()` by allowing the dynamic addition of one or more grouping variables (`var_group`) to the selection.

## Usage

```
select_plus(.data, ..., var_group = NULL)
```

## Arguments

| | |
|---|---|
| `.data` | A data frame. |
| `...` | Columns to select (as in `dplyr::select()`). |
| `var_group` | A character string or vector of column names to additionally include, typically one or more grouping variables. Can be `NULL`. |

## Details

It is especially useful when switching between an ungrouped analysis (e.g., all observations together) and a grouped analysis (e.g., stratified or including interaction terms), without rewriting code.

For instance, this allows you to write a single analysis command for both the RDD (Rapport de Démarrage des Données) and the final report, simply by changing the `.qmd` file, without modifying the core analysis code.

## Value

A data frame with the selected columns, including `var_group` if specified.

## Examples

```
library(dplyr)
df <- data.frame(x = 1:3, y = 4:6, z = 7:9)

# Simple selection
select_plus(df, x, y)

# Selection with grouping variable
select_plus(df, x, var_group = "z")
```

`start_new_reporting` *Generate qmd, html and css files for reporting*

## Description

This function creates and writes a qmd file with css and html to report statistical analysis.

## Usage

```
start_new_reporting(
  folder_path,
  output_folder,
  name = "report",
  structure = "USMR",
  path_logo = NULL,
  confidential = FALSE,
  report_type = "Data review report",
  study_id = "CHUBXYYYY/NN",
  study_name = "The Study Name",
  study_abbreviation = "TSN",
  investigator = "Investigator name",
  methodologist = "Jean Dupont",
  biostatistician = "George Frais",
  datamanager = "Peter Parker",
  methodologist_mail = NULL,
  biostatistician_mail = NULL,
  datamanager_mail = NULL,
  language = "fr"
)
```

## Arguments

| | |
|---|---|
| `folder_path` | The folder where this should be created |
| `output_folder` | The folder where the html will be recorded. |
| `name` | The name of the files |
| `structure` | Character string indicating the organizational structure, either "USMR" or "EU-CLID". Default is "USMR". |
| `path_logo` | Character string specifying the path to the logo image. If NULL, a default logo is used. |
| `confidential` | Logical value indicating whether the report should be marked as confidential. Default is FALSE. |
| `report_type` | Character string specifying the type of report. Default is "Data review report". |
| `study_id` | Character string representing the study identifier. Default is "CHUBXYYYY/NN". |
| `study_name` | Character string specifying the name of the study. Default is "The Study Name". |

`study_abbreviation`
: Character string providing the abbreviation of the study. Default is "TSN".

`investigator`
: Character string representing the investigator's name. Default is "Investigator name".

`methodologist`
: Character string specifying the methodologist's name. Default is "Jean Dupont".

`biostatistician`
: Character string specifying the biostatistician's name. Default is "George Frais".

`datamanager`
: Character string specifying the data manager's name. Default is "Peter Parker".

`methodologist_mail`
: Character string specifying the methodologist's email. If NULL, it is generated automatically.

`biostatistician_mail`
: Character string specifying the biostatistician's email. If NULL, it is generated automatically.

`datamanager_mail`
: Character string specifying the data manager's email. If NULL, it is generated automatically.

`language`
: Character string indicating the language of the report, either "fr" (French) or "en" (English). Default is "fr".

## Value

None. The function writes an HTML report to the specified file path.

---

`write_css` *Generate a CSS File*

---

## Description

This function creates and writes a CSS file with predefined styling for tables and text formatting.

## Usage

```
write_css(path)
```

## Arguments

`path`
: Character string specifying the file path where the CSS file will be saved.

## Value

None. The function writes a CSS file to the specified file path.

`write_html_file` *Generate an HTML Report File*

## Description

This function creates and writes an HTML report file based on specified study and structure details.

## Usage

```
write_html_file(
  path,
  structure = "USMR",
  path_logo = NULL,
  confidential = FALSE,
  report_type = "Data review report",
  study_id = "CHUBXYYYY/NN",
  study_name = "The Study Name",
  study_abbreviation = "TSN",
  investigator = "Investigator name",
  methodologist = "Jean Dupont",
  biostatistician = "George Frais",
  datamanager = "Peter Parker",
  methodologist_mail = NULL,
  biostatistician_mail = NULL,
  datamanager_mail = NULL,
  language = "fr"
)
```

## Arguments

| | |
|---|---|
| `path` | Character string specifying the file path where the HTML file will be saved. |
| `structure` | Character string indicating the organizational structure, either "USMR" or "EUCLID". Default is "USMR". |
| `path_logo` | Character string specifying the path to the logo image. If NULL, a default logo is used. |
| `confidential` | Logical value indicating whether the report should be marked as confidential. Default is FALSE. |
| `report_type` | Character string specifying the type of report. Default is "Data review report". |
| `study_id` | Character string representing the study identifier. Default is "CHUBXYYYY/NN". |
| `study_name` | Character string specifying the name of the study. Default is "The Study Name". |
| `study_abbreviation` | Character string providing the abbreviation of the study. Default is "TSN". |
| `investigator` | Character string representing the investigator's name. Default is "Investigator name". |

`methodologist` Character string specifying the methodologist's name. Default is "Jean Dupont".

`biostatistician` Character string specifying the biostatistician's name. Default is "George Frais".

`datamanager` Character string specifying the data manager's name. Default is "Peter Parker".

`methodologist_mail` Character string specifying the methodologist's email. If NULL, it is generated automatically.

`biostatistician_mail` Character string specifying the biostatistician's email. If NULL, it is generated automatically.

`datamanager_mail` Character string specifying the data manager's email. If NULL, it is generated automatically.

`language` Character string indicating the language of the report, either "fr" (French) or "en" (English). Default is "fr".

## Value

None. The function writes an HTML report to the specified file path.

---

`write_qmd` *Write a Quarto Markdown (.qmd) file*

---

## Description

This function generates a Quarto Markdown (.qmd) file with predefined metadata and a sample table.

## Usage

```
write_qmd(path, path_html, path_css, study_abbreviation, name)
```

## Arguments

`path` Character string specifying the output file path for the .qmd file.

`path_html` Character string specifying the path to an HTML file to be included before the body of the document.

`path_css` Character string specifying the path to a CSS file for styling the document.

`study_abbreviation` Character string providing the abbreviation of the study.

`name` The name of the files

### Details

The function creates a Quarto Markdown file with metadata fields such as title, author, date, and format settings. The HTML file specified in `path_html` is included before the body, and the CSS file specified in `path_css` is used for styling. The generated document includes an example of a start of report.

### Value

None. The function writes a .qmd file to the specified `path`.

---

## `write_quarto_yml` *write_quarto_yml*

---

### Description

Write quarto extension

### Usage

```
write_quarto_yml(path)
```

### Arguments

| | |
|---|---|
| `path` | The path toward quarto yaml file |

### Value

nothing

---

## `write_rendercopy` *write_rendercopy*

---

### Description

A function to write a R file rendercopy

### Usage

```
write_rendercopy(output_folder, path, name)
```

### Arguments

| | |
|---|---|
| `output_folder` | The output folder |
| `path` | The path of the R script |
| `name` | The name of the files |

**Value**

Nothing

# Index


add_missing_info, 2
add_pvalues, 3
ajouter_label_ndm, 4

base_table, 5

css_generator, 6
custom_format, 7
custom_headers, 8
custom_round, 9
customize_table, 9
customize_table_body, 11

desc_ei_per_grade, 12
desc_ei_per_pt, 14
desc_var, 15
df_builder_ae, 18

from_name_to_adress, 19

haven::labelled(), *31*
haven::zap_labels(), *31*

indent_gt_table, 20
indent_gtsummary_table, 20
intermediate_header, 21

pillar::type_sum(), *30, 31*
plot_butterfly_stacked_barplot, 22
plot_dumbell, 24
plot_patient_panchart, 26
plot_volcano, 27
prepare_table, 29

remove_labelled_type, 30
reverselog_trans, 31
riskdifference, 32

select_plus, 33
start_new_reporting, 34

write_css, 35
write_html_file, 36
write_qmd, 37
write_quarto_yml, 38
write_rendercopy, 38