Package: RcppTrust (via r-universe)

October 31, 2026

Type Package

Title Thread-Safe C++ Trust Region Optimizers

Version 0.2.1

Description Thread-safe C++ trust region optimizers, each exposed both as an R function and as a C-callable entry point (with function pointers registered for other packages to call without linking against this package's shared library) so they can be used from parallel C++ code such as in 'nlmixr2est'. Includes a port of the two-derivative trust region algorithm in the 'trust' package by Charles J. Geyer; a port of the Steihaug truncated conjugate-gradient trust region method from the 'basin' Rust crate (Steihaug (1983) <doi:10.1137/0720042>); and ports of M. J. D. Powell's derivative-free BOBYQA (Powell (2009), Report DAMTP 2009/NA06) and NEWUOA (Powell (2006) <doi:10.1007/0-387-30065-1_16>) Fortran 77 code <https://github.com/libprima/prima/tree/main/fortran/original>, as modified and distributed in the 'minqa' package, whose R interface is reproduced.

License GPL-2

Copyright See inst/COPYRIGHTS for the sources, copyright holders and licenses of code ported from 'trust', 'basin', 'minqa' and Powell's Fortran.

URL https://github.com/nlmixr2/RcppTrust/, https://nlmixr2.github.io/RcppTrust/, http://www.stat.umn.edu/geyer/trust/

Encoding UTF-8

Depends R (>= 4.2.0)

Imports Rcpp

LinkingTo Rcpp, RcppArmadillo, BH

Suggests testthat (>= 3.0.0), stats, knitr, rmarkdown, trust, minqa, microbenchmark

Config/testthat/edition 3

SystemRequirements C++17

VignetteBuilder knitr

Config/roxygen2/version 8.1.0

NeedsCompilation yes

Author Charles J. Geyer [aut, cph] (ORCID: <https://orcid.org/0000-0003-1471-1703>), Matthew Fidler [aut, cre] (ORCID: <https://orcid.org/0000-0001-8538-6691>), Michael J. D. Powell [aut] (BOBYQA and NEWUOA algorithms and original Fortran 77 code), Douglas Bates [ctb, cph] (minqa), Katharine M. Mullen [ctb, cph] (minqa), John C. Nash [ctb, cph] (minqa), Ravi Varadhan [ctb, cph] (minqa), Johan Larsson [ctb, cph] (basin trust-region / Steihaug implementation)

Maintainer Matthew Fidler <matthew.fidler@gmail.com>

Repository https://cran.r-universe.dev

Date/Publication 2026-10-31 12:48:40 UTC

RemoteUrl https://github.com/cran/RcppTrust

RemoteRef HEAD

RemoteSha c46f4fa89bd3393261239682f8672d0d95d815d7

Contents

.RcppTrustPtr 2
bobyqa 3
newuoa 4
print.minqa 5
steihaug 5
trust 7

Index **9**

`.RcppTrustPtr` *Positionally-indexed function pointer table for downstream packages*

Description

Returns the list of native function pointers a consuming package (e.g. nlmixr2est) resolves via the header-only registration pattern in `inst/include/RcppTrust.h` – the same pattern rxode2/n1qn1c/lbfgsb3c use, so no linker dependency on this package's shared library is required. Not intended to be called directly by end users.

Usage

```
.RcppTrustPtr()
```

Value

An unclassed list of external pointers.

---

bobyqa *Nonlinear optimization with box constraints (BOBYQA)*

Description

Thread-safe C++ port of `minqa::bobyqa()`: minimizes a function of many variables subject to box constraints by a trust region method that forms quadratic models by interpolation, using M. J. D. Powell's BOBYQA algorithm. Arguments, defaults, and return value are those of `minqa::bobyqa()`; see its documentation for details.

Usage

```
bobyqa(par, fn, lower = -Inf, upper = Inf, control = list(), ...)
```

Arguments

`par`	numeric vector of starting parameters.
`fn`	function to be minimized; its first argument must be the parameter vector and it must return a scalar numeric value.
`lower, upper`	numeric vectors of lower and upper bounds (recycled when of length 1).
`control`	a list of control settings: `npt`, `rhobeg`, `rhoend`, `iprint`, `maxfun`, `obstop` and `force.start`, as in `minqa::bobyqa()`.
`...`	further arguments passed to `fn`.

Value

A list of class `c("bobyqa", "minqa")` with components `par`, `fval`, `feval`, `ierr` and `msg`.

Source

M. J. D. Powell's original Fortran 77 BOBYQA code, archived at https://github.com/libprima/prima/tree/main/fortran/original/bobyqa; R interface following the **minqa** package.

References

M. J. D. Powell (2009), "The BOBYQA algorithm for bound constrained optimization without derivatives", Report No. DAMTP 2009/NA06, Centre for Mathematical Sciences, University of Cambridge.

See Also

[newuoa()], and [minqa_c_api] for calling the solvers from parallel C/C++ code.

Examples

```
fr <- function(x) 100 * (x[2] - x[1]^2)^2 + (1 - x[1])^2
bobyqa(c(1, 2), fr, lower = c(0, 0), upper = c(4, 4))
```

---

newuoa *Unconstrained derivative-free optimization (NEWUOA)*

Description

Thread-safe C++ port of `minqa::newuoa()`: minimizes a function of many variables by a trust region method that forms quadratic models by interpolation, using M. J. D. Powell's NEWUOA algorithm.

Usage

```
newuoa(par, fn, control = list(), ...)
```

Arguments

`par`	numeric vector of starting parameters.
`fn`	function to be minimized; its first argument must be the parameter vector and it must return a scalar numeric value.
`control`	a list of control settings: `npt`, `rhobeg`, `rhoend`, `iprint` and `maxfun`, as in `minqa::newuoa()`.
`...`	further arguments passed to `fn`.

Value

A list of class `c("newuoa", "minqa")` with components `par`, `fval`, `feval`, `ierr` and `msg`.

Source

M. J. D. Powell's original Fortran 77 NEWUOA code, archived at https://github.com/libprima/prima/tree/main/fortran/original/newuoa; R interface following the **minqa** package.

References

M. J. D. Powell (2006), "The NEWUOA software for unconstrained optimization without derivatives", in Large-Scale Nonlinear Optimization, Springer, 255-297. doi:10.1007/0387300651_16

See Also

[bobyqa()], [minqa_c_api]

Examples

```
fr <- function(x) 100 * (x[2] - x[1]^2)^2 + (1 - x[1])^2
newuoa(c(1, 2), fr)
```

print.minqa *Print method for minqa objects*

Description

Print method for minqa objects

Usage

```
## S3 method for class 'minqa'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

x	an object inheriting from class minqa.
digits	unused; kept for compatibility with minqa.
...	unused.

Value

invisible(x)

steihaug *Steihaug truncated-CG trust-region Newton minimization*

Description

Thread-safe C++ port of the trust-region Newton minimizer with the Steihaug truncated conjugate-gradient subproblem from the Rust crate basin (TrustRegion with its default Steihaug subproblem, driven by basin's executor). Each iteration approximately minimizes the quadratic model $m(p) = f + g^T p + \frac{1}{2} p^T B p$ over $\|p\| \leq \Delta$ by conjugate gradients, stopping at the boundary on negative curvature. Unlike [trust()] it never factorizes the Hessian, and with hessvec it never forms it at all (basin's matrix-free mode).

Usage

```
steihaug(par, fn, gr, hess = NULL, hessvec = NULL, control = list(), ...)
```

Arguments

par	numeric vector of starting parameters.
fn	objective function of the parameter vector returning a scalar.
gr	gradient function returning a numeric vector of length length(par).
hess	Hessian function returning a symmetric length(par) by length(par) matrix. May be NULL when hessvec is supplied.
hessvec	optional Hessian-vector product function(x, v) returning $H(x)v$. When supplied, the matrix-free mode is used and hess is never called.
control	a list of control settings (defaults in brackets; a NULL tolerance or budget is disabled): **rinit** initial trust region radius [1] **rmax** maximum trust region radius [100] **eta** step acceptance threshold on the reduction ratio, in $[0, 1/4)$ [0.125] **maxInner** radius reductions (re-solves) per outer iteration [10] **cgMaxit** CG iteration cap per subproblem; 0 means length(par) [0] **kappa, theta** CG forcing rule: stop when $\|r\| < \min(\kappa, \|g\|^{\theta})\|g\|$ [0.5, 0.5] **maxit** maximum outer iterations [100] **maxCostEvals, maxGradEvals** evaluation budgets [NULL] **targetCost** stop once the objective is at or below this [NULL] **gradTol** absolute gradient tolerance on $\|g\|_2$ [1e-8] **relGradTol** gradient tolerance relative to the initial gradient norm [NULL] **stepTol, relStepTol** absolute / relative step tolerance [NULL] **costTol, relCostTol** absolute / relative objective change tolerance [NULL] **trace** if TRUE, return a per-attempt trace [FALSE]
...	further arguments passed to fn, gr, hess and hessvec.

Details

Evaluation pattern (identical to basin): fn and gr once at the start; hess once per outer iteration (exact mode) or hessvec once per CG product (matrix-free mode); fn at each trial point; gr after each accepted step. fn may return Inf (or NaN) at a trial point to reject it.

Value

A list with components par, value, gradient, iterations, converged, status (integer), message (the basin termination reason, e.g. "GradientTolerance", "MaxIter"), radius (final trust radius), counts (evaluations of fn, gr, hess, hessvec), and, when control$trace is TRUE, trace, a data frame with one row per subproblem attempt.

References

Steihaug, T. (1983). The conjugate gradient method and trust regions in large scale optimization. SIAM Journal on Numerical Analysis, 20(3), 626-637.

Nocedal, J. and Wright, S. J. (2006). Numerical Optimization (2nd ed.), Algorithms 4.1 and 7.2. Springer.

See Also

[trust()], [bobyqa()], [newuoa()]

Examples

```
fr <- function(x) 100 * (x[2] - x[1]^2)^2 + (1 - x[1])^2
grr <- function(x) c(-400 * x[1] * (x[2] - x[1]^2) - 2 * (1 - x[1]),
                     200 * (x[2] - x[1]^2))
hr <- function(x) matrix(c(1200 * x[1]^2 - 400 * x[2] + 2, -400 * x[1],
                           -400 * x[1], 200), 2, 2)
steihaug(c(-1.2, 1), fr, grr, hr)

# matrix-free: only Hessian-vector products
hv <- function(x, v) drop(hr(x) %*% v)
steihaug(c(-1.2, 1), fr, grr, hessvec = hv)$counts
```

`trust` *Non-Linear Optimization by a Trust Region Algorithm*

Description

Thread-safe C++ port of `trust::trust()` (Geyer). Carries out a minimization or maximization of a function using a trust region algorithm; see the original package's documentation for the algorithm and argument semantics, which this function reproduces exactly.

Usage

```
trust(
  objfun,
  parinit,
  rinit,
  rmax,
  parscale,
  iterlim = 100,
  fterm = sqrt(.Machine$double.eps),
  mterm = sqrt(.Machine$double.eps),
  minimize = TRUE,
  blather = FALSE,
  ...
)
```

Arguments

`objfun`	an R function computing value, gradient, and Hessian; see `trust::trust` for the exact contract.
`parinit`	starting parameter values.
`rinit`	starting trust region radius.

rmax	maximum allowed trust region radius.
parscale	optional parameter scale vector.
iterlim	maximum number of iterations.
fterm	function-value termination tolerance.
mterm	model-decrease termination tolerance.
minimize	if TRUE minimize, if FALSE maximize.
blather	if TRUE return extra per-iteration information.
...	additional arguments passed to objfun.

Value

A list with the same components as trust::trust().

Index

.RcppTrustPtr, 2

bobyqa, 3

newuoa, 4

print.minqa, 5

steihaug, 5

trust, 7