

Package: ReliaGrowR (via r-universe)

November 17, 2024

Title Reliability Growth Analysis

Version 0.1.3

Description Modeling and plotting functions for Reliability Growth Analysis (RGA). Models include the Duane (1962) <[doi:10.1109/TA.1964.4319640](https://doi.org/10.1109/TA.1964.4319640)>, Non-Homogeneous Poisson Process (NHPP) by Crow (1975) <<https://apps.dtic.mil/sti/citations/ADA020296>>, Piecewise Weibull NHPP by Guo et al. (2010) <[doi:10.1109/RAMS.2010.5448029](https://doi.org/10.1109/RAMS.2010.5448029)>, and Piecewise Weibull NHPP with Change Point Detection based on the 'segmented' package by Muggeo (2024) <<https://cran.r-project.org/package=segmented>>.

Imports stats, graphics, segmented

License CC BY 4.0

Encoding UTF-8

RoxygenNote 7.3.2

Suggests knitr, rmarkdown, spelling, testthat (>= 3.0.0)

Language en-US

URL <https://paulgovan.github.io/ReliaGrowR/>,
<https://github.com/paulgovan/ReliaGrowR>

Config/testthat/edition 3

VignetteBuilder knitr

BugReports <https://github.com/paulgovan/ReliaGrowR/issues>

NeedsCompilation no

Author Paul Govan [aut, cre, cph]
<<https://orcid.org/0000-0002-1821-8492>>

Maintainer Paul Govan <paul.govan2@gmail.com>

Repository CRAN

Date/Publication 2024-11-16 05:00:02 UTC

Contents

duane_plot	2
plot_rga	3
rga	4
weibull_to_rga	5
Index	6

duane_plot	<i>Plotting Function for Duane Analysis.</i>
------------	--

Description

Plotting Function for Duane Analysis.

Usage

```
duane_plot(
  times,
  failures,
  plot = TRUE,
  point_col = "black",
  line_col = "black",
  xlab = "Cumulative Time",
  ylab = "Cumulative MTBF",
  main = "Duane Plot with Cumulative MTBF"
)
```

Arguments

times	A vector of cumulative times at which failures occurred.
failures	A vector of the number of failures at each corresponding time in times.
plot	Show Duane Plot (TRUE) or hide plot (FALSE).
point_col	Color for the data points (default: "black").
line_col	Color for the fitted line (default: "black").
xlab	Label for the x-axis (default: "Cumulative Time").
ylab	Label for the y-axis (default: "Cumulative MTBF").
main	Title for the plot (default: "Duane Plot with Cumulative MTBF").

Value

The function returns a list of the fitted linear model, Cumulative Time, Cumulative MTBF.

Examples

```
library(ReliaGrowR)
times <- c(100, 200, 300, 400, 500)
failures <- c(1, 2, 1, 3, 2)
fit <- duane_plot(times, failures)
summary(fit)
```

plot_rga

Plotting Function for Reliability Growth Analysis

Description

Plotting Function for Reliability Growth Analysis

Usage

```
plot_rga(
  rga_obj,
  point_col = "black",
  line_col = "black",
  xlab = "Cumulative Time",
  ylab = "Cumulative Failures",
  main = "Reliability Growth Analysis"
)
```

Arguments

rga_obj	An object of class rga, which contains the results from the RGA model.
point_col	Color for the data points (default: "black").
line_col	Color for the fitted line (default: "black").
xlab	Label for the x-axis (default: "Cumulative Time").
ylab	Label for the y-axis (default: "Cumulative Failures").
main	Title for the plot (default: "Reliability Growth Analysis").

Value

The function does not return a value.

Examples

```
times <- c(100, 200, 300, 400, 500)
failures <- c(1, 2, 1, 3, 2)
result <- rga(times, failures)
plot_rga(result)
```

rga

Reliability Growth Analysis.

Description

Reliability Growth Analysis.

Usage

```
rga(  
  times,  
  failures,  
  model_type = "Crow-AMSAA",  
  breakpoints = NULL,  
  conf_level = 0.95  
)
```

Arguments

<code>times</code>	A vector of cumulative times at which failures occurred.
<code>failures</code>	A vector of the number of failures at each corresponding time in <code>times</code> .
<code>model_type</code>	The model type. Either Crow-AMSAA (default) or Piecewise Weibull NHPP with change point detection.
<code>breakpoints</code>	An optional vector of breakpoints for the Piecewise Weibull NHPP model.
<code>conf_level</code>	The desired confidence level, which defaults to 95%.

Value

The function returns an object of class `rga` that contains the results for the model.

Examples

```
times <- c(100, 200, 300, 400, 500)  
failures <- c(1, 2, 1, 3, 2)  
result <- rga(times, failures)  
print(result)
```

weibull_to_rga	<i>Convert Weibull Data to Reliability Growth Data</i>
----------------	--

Description

Convert Weibull Data to Reliability Growth Data

Usage

```
weibull_to_rga(failures, suspensions = NULL)
```

Arguments

failures A vector of failure times.
suspensions A vector of suspension (censoring) times.

Value

A data frame with times and failure counts suitable for reliability growth analysis.

Examples

```
failures <- c(100, 200, 200, 400)  
suspensions <- c(250, 350, 450)  
result <- weibull_to_rga(failures, suspensions)  
print(result)
```

Index

duane_plot, 2

plot_rga, 3

rga, 4

weibull_to_rga, 5