Package: Rfast (via r-universe)

October 29, 2026

Type Package

Title A Collection of Efficient and Extremely Fast R Functions

Version 2.1.5.2

Date 2025-10-10

Maintainer Manos Papadakis <rfastofficial@gmail.com>

Depends R (>= 3.5.0), Rcpp (>= 0.12.3), zigg, RcppParallel

LinkingTo Rcpp (>= 0.12.3), RcppArmadillo, RcppParallel, zigg

Suggests philentropy

SystemRequirements C++17

BugReports https://github.com/RfastOfficial/Rfast/issues

URL https://github.com/RfastOfficial/Rfast

Description A collection of fast (utility) functions for data analysis. Column and row wise means, medians, variances, minimums, maximums, many t, F and G-square tests, many regressions (normal, logistic, Poisson), are some of the many fast functions. References: a) Tsagris M., Papadakis M. (2018). Taking R to its limits: 70+ tips. PeerJ Preprints 6:e26605v1 <doi:10.7287/peerj.preprints.26605v1>. b) Tsagris M. and Papadakis M. (2018). Forward regression in R: from the extreme slow to the extreme fast. Journal of Data Science, 16(4): 771--780. <doi:10.6339/JDS.201810_16(4).00006>. c) Chatzipantsiou C., Dimitriadis M., Papadakis M. and Tsagris M. (2020). Extremely Efficient Permutation and Bootstrap Hypothesis Tests Using Hypothesis Tests Using R. Journal of Modern Applied Statistical Methods, 18(2), eP2898. <doi:10.48550/arXiv.1806.10947>. d) Tsagris M., Papadakis M., Alenazi A. and Alzeley O. (2024). Computationally Efficient Outlier Detection for High-Dimensional Data Using the MDP Algorithm. Computation, 12(9): 185. <doi:10.3390/computation12090185>. e) Tsagris M. and Papadakis M. (2025). Fast and light-weight energy statistics using the R package Rfast. <doi:10.48550/arXiv.2501.02849>.

License GPL (>= 2.0)

NeedsCompilation yes

Author Manos Papadakis [aut, cre, cph], Michail Tsagris [aut], Marios Dimitriadis [aut], Stefanos Fafalios [aut], Matteo Fasiolo [aut], Morgan Jacob [ctb], Giorgos Borboudakis [aut], John Burkardt [aut], Changliang Zou [aut]

Repository https://cran.r-universe.dev

Date/Publication 2025-10-10 13:40:02 UTC

RemoteUrl https://github.com/cran/Rfast

RemoteRef HEAD

RemoteSha 8dff98abdf8da3af561c1141390c9a134942e4c4

Contents

Rfast-package 7
All k possible combinations from n elements 8
Analysis of covariance 9
Analysis of variance with a count variable 11
Angular central Gaussian random values simulation 12
ANOVA for two quasi Poisson regression models 13
Apply method to Positive and Negative number 14
Apply to each column a method under condition 15
Backward selection regression 16
BIC (using partial correlation) forward regression 17
BIC forward regression with generalised linear models 18
Binary search algorithm 20
Binomial coefficient and its logarithm 21
Bootstrap t-test for 2 independent samples 22
Check if any column or row is fill with values 23
Check if values are integers and convert to integer 24
Check Namespace and Rd files 25
Check whether a square matrix is symmetric 28
Chi-square and G-square tests of (unconditional) indepdence 29
Cholesky decomposition of a square matrix 30
Circular or angular regression(s) 31
Circular-linear correlation 33
Coefficient matrices 34
Colum-wise cumulative operations (sum, prod, min, max) 35
Column and row wise coefficients of variation 36
Column and row-wise Any/All 37
Column and row-wise means of a matrix 38
Column and row-wise medians of a matrix or median of a vector. 39
Column and row-wise nth smallest value of a matrix/vector 40
Column and row-wise Order - Sort Indices 41
Column and row-wise products 43
Column and row-wise range of values of a matrix 44

Column and row-wise ranks . . . 45
Column and row-wise Shuffle . . . 46
Column and row-wise sums of a matrix . . . 47
Column and row-wise tabulate . . . 48
Column and row-wise variances and standard deviations . . . 49
Column and rows-wise mean absolute deviations . . . 50
Column-wise differences . . . 51
Column-wise kurtosis and skewness coefficients . . . 52
Column-wise matching coefficients . . . 53
Column-wise minimum and maximum . . . 54
Column-wise MLE of some univariate distributions . . . 55
Column-wise true/false value . . . 57
Column-wise uniformity Watson test for circular data . . . 58
Column-wise Yule's Y (coefficient of colligation) . . . 59
Convert a dataframe to matrix . . . 60
Convert R function to the Rfast's coresponding . . . 61
Correlation based forward regression . . . 62
Correlation between pairs of variables . . . 63
Correlations . . . 65
Covariance and correlation matrix . . . 66
Cox confidence interval for the ratio of two Poisson variables . . . 67
Cross-Validation for the k-NN algorithm . . . 68
Cross-Validation for the k-NN algorithm using the arc cosinus distance . . . 70
Deep copy . . . 72
Density of the multivariate normal and t distributions . . . 73
Design Matrix . . . 74
Diagonal Matrix . . . 75
Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix. 76
Distance matrix - Sum of all pairwise distances in a distance matrix . . . 78
Distance variance, covariance and correlation . . . 80
Eigenvalues and eigenvectors in high dimensional principal component analysis . . . 82
Empirical and exponential empirical likelihood tests for one sample . . . 83
Empirical and exponential empirical likelihood tests for two samples . . . 84
Energy distance between matrices . . . 86
Estimation of an AR(1) model . . . 87
Estimation of the Box-Cox transformation . . . 88
Exact t-test for 2 independent samples . . . 89
Exponential empirical likelihood for a one sample mean vector hypothesis testing . . . 90
Exponential empirical likelihood hypothesis testing for two mean vectors . . . 92
Fast and general - untyped represantation of a factor variable . . . 93
FBED variable selection method using the correlation . . . 94
Find element . . . 96
Find the given value in a hash table . . . 97
Fitted probabilities of the Terry-Bradley model . . . 98
Fitting a Dirichlet distribution via Newton-Rapshon . . . 99
Floyd-Warshall algorithm . . . 100
Forward selection with generalised linear regression models . . . 101
G-square and Chi-square test of conditional indepdence . . . 102

Gamma regression with a log-link . . . 104
Gaussian regression with a log-link . . . 105
Generates random values from a normal and puts them in a matrix . . . 107
Get specific columns/rows fo a matrix . . . 108
Hash - Pair function . . . 109
Hash object . . . 110
Hash object to a list object . . . 111
High dimensional MCD based detection of outliers . . . 112
Hypothesis test for the distance correlation . . . 113
Hypothesis test for two means of percentages . . . 114
Hypothesis test for von Mises-Fisher distribution over Kent distribution . . . 115
Hypothesis testing between two skewness or kurtosis coefficients . . . 116
Index of the columns of a data.frame which are a specific type . . . 117
Insert/remove function names in/from the NAMESPACE file . . . 118
Inverse Gaussian regression with a log-link . . . 120
Inverse of a symmetric positive definite matrix . . . 121
Iterator . . . 122
James multivariate version of the t-test . . . 123
k nearest neighbours algorithm (k-NN) . . . 125
k-NN algorithm using the arc cosinus distance . . . 127
Limited number of eigenvalues and eigenvectors of a symmetric matrix . . . 128
Linear models for large scale data . . . 129
Logistic and Poisson regression models . . . 130
Logistic or Poisson regression with a single categorical predictor . . . 132
Lower and Upper triangular of a matrix . . . 133
Mahalanobis distance . . . 134
Many (and one) area under the curve values . . . 135
Many 2 sample proportions tests . . . 136
Many 2 sample tests . . . 137
Many analysis of variance tests with a discrete variable . . . 139
Many ANCOVAs . . . 140
Many ANOVAS for count data with Poisson or quasi Poisson models . . . 141
Many exponential regressions . . . 142
Many F-tests with really huge matrices . . . 144
Many G-square and Chi-square tests of indepedence . . . 145
Many hypothesis tests for two means of percentages . . . 147
Many moment and maximum likelihood estimations of variance components . . . 148
Many multi-sample tests . . . 150
Many multivariate simple linear regressions coefficients . . . 151
Many non parametric multi-sample tests . . . 152
Many odds ratio tests . . . 154
Many one sample goodness of fit tests for categorical data . . . 155
Many one sample tests . . . 156
Many random intercepts LMMs for balanced data with a single identical covariate. . . . 157
Many regression based tests for single sample repeated measures . . . 159
Many score based regressions . . . 161
Many Shapiro-Francia normality tests . . . 163
Many simple geometric regressions . . . 164

Many simple linear mixed model regressions . . . 165
Many simple linear regressions coefficients . . . 166
Many simple multinomial regressions . . . 167
Many simple regressions for positive valued data . . . 168
Many tests for the dispersion parameter in Poisson distribution . . . 169
Many two-way ANOVAs . . . 171
Many univariate generalised linear models . . . 172
Many univariate simple linear regressions . . . 173
Many univariate simple logistic and Poisson regressions . . . 175
Many univariate simple quasi poisson regressions . . . 176
Many Welch's F-tests . . . 177
Match . . . 178
Matrix multiplication . . . 179
Matrix with all pairs of t-tests . . . 180
Matrix with G-square tests of indepedence . . . 181
Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices . . . 183
Minimum and maximum . . . 184
Minimum and maximum frequencies . . . 185
MLE for multivariate discrete data . . . 186
MLE of (hyper-)spherical distributions . . . 187
MLE of continuous univariate distributions defined on the positive line . . . 189
MLE of continuous univariate distributions defined on the real line . . . 191
MLE of count data (univariate discrete distributions) . . . 192
MLE of distributions defined in the (0, 1) interval . . . 194
MLE of some circular distributions . . . 196
MLE of the inverted Dirichlet distribution . . . 197
MLE of the multivariate (log-) normal distribution . . . 198
MLE of the multivariate t distribution . . . 200
MLE of the ordinal model without covariates . . . 201
MLE of the tobit model . . . 202
Moment and maximum likelihood estimation of variance components . . . 203
Multi-sample tests for vectors . . . 205
Multinomial regression . . . 207
Multivariate kurtosis . . . 208
Multivariate Laplace random values simulation . . . 209
Multivariate normal and t random values simulation . . . 210
Naive Bayes classifiers . . . 211
Natural Logarithm each element of a matrix . . . 213
Natural logarithm of the beta function . . . 214
Natural logarithm of the gamma function and its derivatives . . . 215
Norm of a matrix . . . 216
Number of equal columns between two matrices . . . 217
Odds ratio and relative risk . . . 218
One and many Gini coefficients . . . 219
One sample t-test for a vector . . . 220
Operations between two matrices or matrix and vector . . . 221
Orthogonal matching pursuit variable selection . . . 222

Outer function . . . 224
Partial distance correlation . . . 225
Permutation . . . 226
Permutation based p-value for the Pearson correlation coefficient . . . 227
Polyserial correlation . . . 228
Pooled covariance matrix . . . 229
Prediction with some naive Bayes classifiers . . . 230
Quasi binomial regression for proportions . . . 231
Quasi Poisson regression for count data . . . 233
Random intercepts linear mixed models . . . 235
Random values simulation from a von Mises distribution . . . 236
Reading the files of a directory . . . 237
Repeated measures anova . . . 238
Replicate columns/rows . . . 240
Represantation of Stack . . . 241
Round each element of a matrix/vector . . . 242
Row - Wise matrix/vector count the frequency of a value . . . 243
Row-wise minimum and maximum . . . 244
Row-wise true value . . . 245
Search for variables with zero range in a matrix . . . 246
Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression 247
Simulation of random values from a Bingham distribution . . . 248
Simulation of random values from a Bingham distribution with any symmetric matrix . . . 249
Simulation of random values from a normal distribution . . . 251
Simulation of random values from a von Mises-Fisher distribution . . . 252
Skeleton of the PC algorithm . . . 253
Skewness and kurtosis coefficients . . . 255
Some summary statistics of a vector for each level of a grouping variable . . . 256
Sort - Integer Sort - Sort a vector coresponding to another . . . 257
Sort and unique numbers . . . 259
Sorting of the columns-rows of a matrix . . . 260
Source many R files . . . 261
Spatial median for Euclidean data . . . 262
Spatial median regression . . . 263
Spatial sign covariance matrix . . . 264
Spherical and hyperspherical median . . . 265
Standardisation . . . 266
Sub-matrix . . . 267
Table Creation - Frequency of each value . . . 268
Tests for the dispersion parameter in Poisson distribution . . . 270
Topological sort of a DAG . . . 271
Transpose of a matrix . . . 272
Uniformity test for circular data . . . 273
Variance of a vector . . . 274
Vector allocation in a symmetric matrix . . . 275
Weibull regression model . . . 276
Yule's Y (coefficient of colligation) . . . 277

Index **279**

Rfast-package *A Collection of Efficient and Extremely Fast R Functions*

Description

A collection of fast (utility) functions for data analysis. Column and row wise means, medians, variances, minimums, maximums, many t, F and G-square tests, many regressions (normal, logistic, Poisson), are some of the many fast functions. References: a) Tsagris M., Papadakis M. (2018). Taking R to its limits: 70+ tips. PeerJ Preprints 6:e26605v1 <doi:10.7287/peerj.preprints.26605v1>. b) Tsagris M. and Papadakis M. (2018). Forward regression in R: from the extreme slow to the extreme fast. Journal of Data Science, 16(4): 771–780. <doi:10.6339/JDS.201810_16(4).00006>. c) Chatzipantsiou C., Dimitriadis M., Papadakis M. and Tsagris M. (2020). Extremely Efficient Permutation and Bootstrap Hypothesis Tests Using Hypothesis Tests Using R. Journal of Modern Applied Statistical Methods, 18(2), eP2898. <doi:10.48550/arXiv.1806.10947>. d) Tsagris M., Papadakis M., Alenazi A. and Alzeley O. (2024). Computationally Efficient Outlier Detection for High-Dimensional Data Using the MDP Algorithm. Computation, 12(9): 185. <doi:10.3390/computation12090185>. e) Tsagris M. and Papadakis M. (2025). Fast and light-weight energy statistics using the R package Rfast. <doi:10.48550/arXiv.2501.02849>.

Details

Package:	Rfast
Type:	Package
Version:	2.1.5.2
Date:	2025-10-10
License:	GPL (>= 2.0)

Maintainers

Manos Papadakis <rfastofficial@gmail.com>

Note

Acknowledgments: We would like to acknowledge:

- Professor Kurt Hornik, Doctor Uwe Ligges (and the rest of R core team) for their invaluable help with this R package.
- Erich Studerus for his invaluable comments.
- Neal Fultz for his suggestions.
- Vassilis Vasdekis for his invaluable help with the random effects models.
- Marios Dimitriadis' work was funded by the Special Account for Research Funds of the University of Crete, Department of Computer Science.

- Phillip Si is greatly acknowledged for his help with the Floyd-Warshal algorithm.
- Keefe Murphy for his invaluable help with NEWS file and for his suggestions.
- Zacharias Papadovassilakis gave us the inspiration for the memory efficient version of the k-NN algorithm.
- Yannis Pantazis explained us how the orhtogonal matching pursuit works.
- Achim Zeileis for his help with the quasi Poisson regression models.
- Pedro J. Aphalo for finding a bug.
- Dimitris Kyriakis for finding a bug.
- Cyrille Conord for finding a bug.
- Aaron Robotham for finding a bug.
- Calvin Pan from the Department of Human Genetics at UCLA found a bug in the function glm_logistic and he is greatly acknowledged for that.
- Adam Muschielok from Rodenstock GmbH found a bug in the function vmf.mle and he is greatly acknowledged for that.
- Bret Presnell for detecting and correcting a bug in the function rvmf.
- Gabriel Hoffman for spotting a mistake in the fuction dirimultinom.mle.
- Lutz von der Burchard for spotting a bug in the function bic.corfsreg.

Author(s)

- Manos Papadakis <papadakm95@gmail.com>
- Michail Tsagris <mtsagris@uoc.gr>
- Marios Dimitriadis <kmdimitriadis@gmail.com>
- Stefanos Fafalios <stefanosfafalios@gmail.com>
- Ioannis Tsamardinos <tsamard@csd.uoc.gr>
- Matteo Fasiolo <matteo.fasiolo@gmail.com>
- Giorgos Borboudakis <borbudak@gmail.com>
- John Burkardt <jburkardt@fsu.edu>
- Changliang Zou <nk.chlzou@gmail.com>

`All k possible combinations from n elements`

All k possible combinations from n elements

Description

All k possible combinations from n elements.

Usage

```
comb_n(n, k,simplify=TRUE)
```

Arguments

n	A positive **INTEGER** number or a vector with numbers.
k	A positive integer number at most equal to n or at most equal to the length of n, if n is a vector.
simplify	A logical value for return List instead of matrix.

Value

A matrix with k columns and rows equal to the number of possible unique combinations of n with k elements. If simplify is set to TRUE then a list with k values where each value has length equal to the number of possible unique combinations of n with k elements.

Author(s)

Manos Papadakis and Marios Dimitriadis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Marios Dimitriadis <kmdimitriadis@gmail.com>.

References

Nijenhuis A. and Wilf H.S. (1978). Combinatorial Algorithms for Computers and Calculators. Academic Press, NY.

See Also

nth, colMaxs, colMins, colrange

Examples

```
comb_n(20, 4)
combn(20, 4)
x <- rnorm(5)
res<-comb_n(x, 3)
```

`Analysis of covariance`

Analysis of covariance

Description

Analysis of covariance

Usage

```
ancova1(y, ina, x, logged = FALSE)
```

Arguments

y	A numerical vector with the data, the response variable.
ina	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Be careful, the function is desinged to accept numbers greater than zero.
x	A numerical vector whose length is equal to the number of rows of y. This is the covariate.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

Analysis of covariance is performed. No interaction between the factor and the covariate is tested. Only the main effects. The design need not be balanced. The values of ina need not have the same frequency. The sums of squares have been adjusted to accept balanced and unbalanced designs.

Value

A matrix with the test statistic and the p-value for the factor variable and the covariate.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

D.C. Montgomery (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons

See Also

ancovas, ftests, ttests, anova1

Examples

```
y <- rnorm(90)
ina <- rbinom(90, 2, 0.5) + 1
x <- rnorm(90)
a <- ancova1(y, ina, x)
```

`Analysis of variance with a count variable`
Analysis of variance with a count variable

Description

Analysis of variance with a count variable.

Usage

```
poisson.anova(y, ina, logged = FALSE)
geom.anova(y, ina, type = 1, logged = FALSE)
quasipoisson.anova(y, ina, logged = FALSE)
```

Arguments

`y`	A numerical vector with discrete valued data, i.e. counts.
`ina`	A numerical vector with discrete numbers starting from 1, i.e. 1, 2, 3, 4,... or a factor variable. This is suppose to be a categorical predictor. If you supply a continuous valued vector the function will obviously provide wrong results.
`type`	This argument is for the geometric distribution. Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

This is the analysis of variance with Poisson or geometric distributed data. What we do is a log-likelihood ratio test. However, this is exactly the same as Poisson regression with a single predictor variable who happens to be categorical. Needless to say that this is faster function than the glm command in R. For the same purpose with a Bernoulli variable use `g2Test`. The quasinpoisson.anova is when in the glm function you specify family = quasipoisson. This is suitable for the case of over or under-dispersed data.

Value

A vector with two values, the difference in the deviances (or the scale difference in the case of quasi poisson) and the relevant p-value. The quasipoisson.anova also returns the estimate of the ϕ parameter.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

logistic.cat1, g2Test, poisson.anovas, anova, poisson_only,poisson.mle

Examples

```
y <- rpois(300, 10)
ina <- rbinom(300, 3, 0.5) + 1
a1 <- poisson.anova(y, ina)
a2 <- glm(y ~ ina, poisson)


res<-anova(a2, test = "Chisq")

y <- rgeom(300, 0.7)
res<-geom.anova(y, ina)
```

`Angular central Gaussian random values simulation`

Angular central Gaussian random values simulation

Description

Angular central Gaussian random values simulation.

Usage

```
racg(n, sigma, seed = NULL)
```

Arguments

n	The sample size, a numerical value.
sigma	The covariance matrix in R^d.
seed	If you want the same to be generated again use a seed for the generator, an integer number.

Details

The algorithm uses univariate normal random values and transforms them to multivariate via a spectral decomposition. The vectors are then scaled to have unit length.

Value

A matrix with the simulated data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Tyler D. E. (1987). Statistical analysis for the angular central Gaussian distribution on the sphere. Biometrika 74(3): 579-589.

See Also

acg.mle, rmvnorm, rmvlaplace, rmvt

Examples

```
s <- cov( iris[, 1:4] )
#x <- racg(100, s)
#res<-acg.mle(x)
#res<-vmf.mle(x)  ## the concentration parameter, kappa, is very low, close to zero, as expected.
```

`ANOVA for two quasi Poisson regression models`

ANOVA for two quasi Poisson regression models

Description

ANOVA for two quasi Poisson regression models.

Usage

```
anova_quasipois.reg(mod0, mod1, n)
```

Arguments

mod0	An object as returned by the "qpois.reg" function. This is the null model.
mod1	An object as returned by the "qpois.reg" function. This is the alternative model.
n	The sample size. This is necessary to calculate the degrees of freedom.

Details

This is an ANOVA type significance testing for two quasi Poisson models.

Value

A vector with 4 elements, the test statistic value, its associated p-value and the relevant degrees of freedom of the numerator and the denominator.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Papke L. E. & Wooldridge J. (1996). Econometric methods for fractional response variables with an application to 401(K) plan participation rates. Journal of Applied Econometrics, 11(6): 619–632.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

anova_qpois.reg, qpois.reg, univglms, quasipoisson.anova

Examples

```
y <- rnbinom(200, 10, 0.5)
x <- matrix(rnorm(200 * 3), ncol = 3)
a1 <- qpois.reg(x, y)
a0 <- qpois.reg(x[, 1], y)
res<-anova_quasipois.reg(a0, a1, 200)
b1 <- glm(y ~ x, family = quasipoisson)
b0 <- glm(y ~ x[, 1], family = quasipoisson)
res<-anova(b0, b1, test = "F")
c1 <- glm(y ~ x, family = poisson)
c0 <- glm(y ~ x[, 1], family = poisson)
res<-anova(c0, c1, test = "Chisq")
```

Apply method to Positive and Negative number

Apply method to Positive and Negative number

Description

Apply method to Positive and Negative number.

Usage

```
negative(x,method = "min")
positive(x,method = "min")
positive.negative(x,method = "min")
```

Arguments

x	A numerical vector with data.
method	Accept 3 values. "min", "max", "min.max".

Details

These functions apply the chosen method to the chosen subset (negative, positive, or both) from the vector and return the result.

Value

negative: apply the chosen method to every negative number of the input vector. positive: apply the chosen method to every positive number of the input vector. positive.negative: apply the chosen method to every negative and positive number of the input vector.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`nth`, `colnth`, `rownth`,`sort_unique`, `Round`

Examples

```
x <- rnorm(1000)

identical(negative(x,"min"), min(x<0))
identical(positive(x,"min"), min(x>0))
identical(positive.negative(x,"min"), c(min(x<0),min(x>0)))

x<-NULL
```

`Apply to each column a method under condition`

Apply to each column a method under condition

Description

Apply to each column a method under condition.

Usage

```
apply.condition(x,method = "+",oper = ">",cond.val = 0)
```

Arguments

`x`	An integer matrix.
`method`	One of: "+", "-", "*", "min", "max".
`oper`	One of: ">, "<", ">=", "<=".
`cond.val`	An integer value for the condition.

Details

Apply to each col the specified method using the condition.

Value

An integer vector with the coresponding values.

Author(s)

Manos Papadakis and Michail Tsagris

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>.

See Also

colsums, colMedians, colVars

Examples

```
x <- matrix(rpois(100,6),10, 10)
identical(apply(x,2,function(x){ sum(x[x>0]) }), apply.condition(x,"+",">",0))
x<-NULL
```

`Backward selection regression`

Backward selection regression

Description

Backward selection regression.

Usage

```
bs.reg(y, x, alpha = 0.05, type = "logistic")
```

Arguments

`y`	A numerical vector with the response variable values. It can either be of 0 and 1 values (Logistic regression) or of integer values 0, 1, 2,... (Poisson regression).
`x`	A numerical matrix with the candidate variables.
`alpha`	Threshold (suitable values are in [0,1]) for assessing the significance of p-values. The default value is at 0.05.
`type`	For the Logistic regression put "logistic" (default value) and for Poisson type "poisson".

Details

This function currently implements only the binary Logistic and Poisson regressions. If the sample size is less than the number of variables a notification message will appear and no backward regression will be performed.

Value

The output of the algorithm is an S3 object including:

`info`	A matrix with the non selected variables and their latest test statistics and p-values.
`Vars`	A vector with the selected variables.

Author(s)

Marios Dimitriadis

R implementation and documentation: Marios Dimitriadis <mtsagris@csd.uoc.gr>

See Also

`fs.reg`, `univglms`, `cor.fsreg`

Examples

```
y <- rbinom(50, 1, 0.5)
x <- matrnorm(50, 10)
res<-bs.reg(y, x)
```

`BIC (using partial correlation) forward regression`

BIC (using partial correlation) forward regression

Description

BIC (using partial correlation) forward regression.

Usage

```
bic.corfsreg(y, x, tol = 2)
```

Arguments

`y`	A numerical vector.
`x`	A matrix with data, the predictor variables.
`tol`	If the BIC difference between two successive models is less than the tolerance value, the variable will not enter the model.

Details

The forward regression tries one by one the variables using the F-test, basically partial F-test every time for the latest variable. This is the same as testing the significance of the coefficient of this latest enetered variable. Alternatively the correlation can be used and this case the partial correlation coefficient. There is a direct relationship between the t-test statistic and the partial correlation coefficient. Now, instead of having to calculate the test statistic, we calculate the partial correlation coefficient. The largest partial correlation indicates the candidate variable to enter the model. If the BIC of the regression model with that variable included, reduces, less than "tol" from the previous model without this variable, the variable enters.

Value

A matrix with two columns, the index of the selected variable(s) and the BIC of each model. The first line is always 0 and the BIC of the model with no predictor variables.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

See Also

cor.fsreg, score.glms, univglms, logistic_only, poisson_only, regression

Examples

```
x <- matrnorm( 50, 10 )
y <- rnorm(50)
a1 <- bic.corfsreg(y, x)
a2 <- cor.fsreg(y, x)
x <- NULL
```

BIC forward regression with generalised linear models

BIC forward regression with generalised linear models

Description

BIC forward regression with generalised linear models.

Usage

```
bic.fs.reg(y, x, tol = 2, type = "logistic")
```

Arguments

`y`	A numerical vector.
`x`	A matrix with data, the predictor variables.
`tol`	If the BIC difference between two successive models is less than the tolerance value, the variable will not enter the model.
`type`	If you have a binary dependent variable, put "logistic". If you have count data, put "poisson".

Details

The forward regression tries one by one the variables using the BIC at each step for the latest variable. If the BIC of the regression model with that variable included, is less than "tol" from the previous model without this variable, the variable enters.

Value

A matrix with two columns, the index of the selected variable(s) and the BIC of each model.

Author(s)

Marios Dimitriadis

R implementation and documentation: Marios Dimitriadis <kmdimitriadis@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

See Also

`fs.reg`, `bic.corfsreg`, `cor.fsreg`, `score.glms`, `univglms`, `logistic_only`, `poisson_only`, `regression`

Examples

```
x <- matrix(rnorm(200 * 50), ncol = 50)
## 200 variables, hence 200 univariate regressions are to be fitted
y <- rbinom(200, 1, 0.5)
a <- bic.fs.reg(y, x)
x <- NULL
```

Binary search algorithm

Binary search algorithm

Description

Search a value in an ordered vector.

Usage

```
binary_search(x, v, index=FALSE)
```

Arguments

x	A vector with the data.
v	A value to check if exists in the vector x.
index	A boolean value for choose to return the position inside the vector.

Details

The functions is written in C++ in order to be as fast as possible.

Value

Search if the v exists in x. Then returns TRUE/FALSE if the value is been found.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

is_element

Examples

```
x <- sort(rnorm(1000))
v <- x[50]
b <- binary_search(x,v)
b1 <- binary_search(x,v,TRUE)
```

`Binomial coefficient and its logarithm`
Binomial coefficient and its logarithm

Description

Binomial coefficient and its logarithm.

Usage

```
Lchoose(x, k)
Choose(x, k)
```

Arguments

x	A vector with integer values numbers.
k	A positive non zero at most equal to x.

Details

The binomial coefficient or its logarithm are evaluated.

Value

A vector with the answers.

Author(s)

Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

See Also

comb_n, Lbeta, Lgamma

Examples

```
x <- sample(20:30, 100, replace = TRUE)
res<-Choose(x, 4)
res<-Lchoose(x, 4)

x<-NULL
```

`Bootstrap t-test for 2 independent samples`
Bootstrap t-test for 2 independent samples

Description

Bootstrap t-test for 2 independent samples.

Usage

```
boot.ttest2(x, y, B = 999)
```

Arguments

x	A numerical vector with the data.
y	A numerical vector with the data.
B	The number of bootstrap samples to use.

Details

Instead of sampling B times from each sample, we sample $\sqrt{B}$ from each of them and then take all pairs. Each bootstrap sample is independent of each other, hence there is no violation of the theory.

Value

A vector with the test statistic and the bootstrap p-value.

Author(s)

Michail Tsagris and Christina Chatzipantsiou

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Christina Chatzipantsiou <chatzipantsiou@gmail.com>.

References

B.L. Welch (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

Efron Bradley and Robert J. Tibshirani (1993). An introduction to the bootstrap. New York: Chapman & Hall/CRC.

Chatzipantsiou C., Dimitriadis M., Papadakis M. and Tsagris M. (2019). Extremely efficient permutation and bootstrap hypothesis tests using R. To appear in the Journal of Modern Applied Statistical Methods.

https://arxiv.org/ftp/arxiv/papers/1806/1806.10947.pdf

See Also

`ttest2`, `exact.ttest2`, `ftest`

Examples

```
tic <- proc.time()
x <- rexp(40, 4)
y <- rbeta(50, 2.5, 7.5)
a <- boot.ttest2(x, y, 9999)
a
```

`Check if any column or row is fill with values`

Check if any column or row is fill with values

Description

Check if any column or row is fill with values.

Usage

```
colrow.value(x,value=0)
```

Arguments

`x`	A vector with data.
`value`	A value to check.

Details

Check all the column if any has all its elements equal to argument value. If found, return "TRUE". Otherwise continues with rows. If columns and rows hasn't any value vector then return "FALSE". Even if it returns "FALSE" that doesn't mean the determinant can't be value. It might be but if check before and found any value vector then for sure the determinant it'll be value.

Value

A boolean value, "TRUE" if any column OR row is all filled with value. "FALSE" otherwise.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`rowMins`, `rowFalse`, `nth`, `colrange`, `colMedians`, `colVars`, `colSort`, `rowSort`, `rowTrue`

Examples

```
x <- matrix(runif(10*10),10,10)
res<-colrow.value(x)

x<-NULL
```

Check if values are integers and convert to integer

Check if values are integers and convert to integer

Description

Check if values are integers and convert to integer.

Usage

```
is_integer(x)
as_integer(x,result.sort = TRUE,init = 1, parallel = FALSE)
```

Arguments

x	is_integer: A vector with numeric data. as_integer: A vector with data.
result.sort	A logical value for sorting the result.
init	An integer value to start.
parallel	Run the algorithm in parallel.

Details

The behavior of these functions are different than R's built in.

is_integer: check if all the values are integers in memory. If typeof is double, and the values are integers in range -2^31 : 2^31 then it is better to convert to integer vector for using less memory. Also you can decrease the time complexity.

as_integer: converts the discrete values to integers.

Value

is_integer: A logical value, TRUE if all values are integers and in range -2^31 : 2^31. Otherwise FALSE.

as_integer: By default the function will return the same result with "as.numeric" but the user can change the "init" value not start from 1 like R's. Also the result can be unsorted using "result.sort".

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

as_integer, colVars, colmeans

Examples

```
x<-runif(10)
y1<-is_integer(x) # y1 is FALSE
x<-as.numeric(rpois(10,10)) # integers but typeof is double
y1<-is_integer(x) # y1 is TRUE so you can convert to integer vector.

as_integer(letters) ## as.numeric(letters) produce errors
x<-y1<-NULL
```

Check Namespace and Rd files

Check Namespace and Rd files

Description

Check Namespace/Rd and examples files.

Usage

```
checkNamespace(path.namespace,path.rfolder,paths.full = FALSE)
checkAliases(path.man,path.rfolder,paths.full = FALSE)
checkTF(path.man,paths.full = FALSE)
checkExamples(path.man,package,each = 1,print.errors = stderr(),
 print.names = FALSE,paths.full = FALSE)
checkUsage(path.man,path.rfolder,paths.full = FALSE)
```

Arguments

path.namespace	An full path to the "NAMESPACE" file.
package	A character vector with the name of the package.
path.rfolder	An full path to the directory that contains the "R" files.
path.man	An full path to the directory that contains the "Rd" files.
each	An integer value for running **each** example.
print.errors	Print the errors to a file. By default it's "stderr()".
print.names	A boolean value (TRUE/FALSE) for printing the names of the files before running the examples.
paths.full	Print or return the full paths.

Details

checkNamespace: reads from the NAMESPACE folder all the export R functions, reads from folder R all the R functions and check if all the functions are export.

checkAliases: reads from the man directory all the Rd files, then reads from each file the aliases and check if:

- All the R files has man file or an alias.
- All aliases belongs to functions.
- If there are dublicated aliases.

checkExamples: reads from the man directory all the Rd files, then read from each file the examples and then run each of them. If you want to print the errors in any file then set "print.errors=file_name" or in the standard error "print.errors=stderr()" and then you will see all the errors for every file. Set to argument "package" the name of your package. The argument "print.names" it is very helpful because if any of you function crashes R during running you will never know which one was. So setting it "TRUE", it will print the name of each file before running it's example.It might crash, but you will know which file. **Remember that there is always an error timeout so it might didn't crash the current file but one from the previous.**

checkTF: reads from the man directory all the Rd files, then read from each file the examples and checks if any examples has the values "T" and "F" instead "TRUE" and "FALSE". The "T","F" is wrong.

checkUsage: reads from the man directory all the Rd files and for each man check if the usage section has the right signature for the functions from the R directory.

checkTF, **checkUsage**, **checkAliases**: you can choose which files not to read for both R and Rd. You must add in the first line of the file in comment the "attribute" "[dont read]". Then each function will know which file to read or not. For Rd you add "%[dont read]" and for R "#[dont read]". Finally, these functions will return in the result a list of which files had this attribute.

Value

checkNamespace: a vector with the names of missing R files. (Don't use it for now)

checkAliases: a list with 4 fields.

- **Missing Man files**: A vector with the names of the missing Rd files or nothing.
- **Missing R files**: A vector with the names of the missing R files or nothing.
- **Duplicate alias**: A vector with the names of the dublicate aliases or nothing.
- **dont read**: A list with 2 fields
  - **R**: A character vector whith the names of the files that had attribute "#[dont read]" or nothing.
  - **Rd**: A character vector whith the names of the files that had attribute "%[dont read]" or nothing.

checkExamples: a list with 3 fields

- **Errors**: A character vector with the names of the Rd files that produced an error.

- **Big Examples**: A character vector with the names of the Rd files that has big examples per line.
- **dont read**: A list with 2 fields
  - **R**: A character vector whith the names of the files that had attribute "#[dont read]" or nothing.
  - **Rd**: A character vector whith the names of the files that had attribute "%[dont read]" or nothing.

checkTF: a list with 3 fields

- **TRUE**: A character vector with the names of the Rd files that has "T" or nothing.
- **FALSE**: A character vector with the names of the Rd files that has "F" or nothing.
- **dont read**: A list with 2 fields
  - **R**: A character vector whith the names of the files that had attribute "#[dont read]" or nothing.
  - **Rd**: A character vector whith the names of the files that had attribute "%[dont read]" or nothing.

checkUsage: a list with 3 fields

- **missing functions**: A character vector with the name of the file that is missing and the Rd file that is found or nothing.
- **missmatch functions**: A character vector with the name of the file that has missmatch function and the Rd file that is found or nothing.
- **dont read**: A list with 2 fields
  - **R**: A character vector whith the names of the files that had attribute "#[dont read]" or nothing.
  - **Rd**: A character vector whith the names of the files that had attribute "%[dont read]" or nothing.
- **hidden functions**: A character vector with the name of the functions thath have been declared as hidden.
- **usage lines wider than 90 characters**: A list with the Rd's that have usages that are wider than 90 characters.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

AddToNamespace, sourceR, sourceRd, read.examples

Examples

```
#for example: path.namespace="C:\some_file\NAMESPACE"
#for example: path.rfolder="C:\some_file\R\"
#for example: path.man="C:\some_file\man\"
#system.time( a<-checkNamespace(path.namespace,path.rfolder) )
#system.time( b<-checkAliases(path.man,path.rfolder) )
#system.time( b<-checkExamples(path.man) )
#system.time( b<-checkExamples(path.man,2) )
#system.time( b<-checkTF(path.man) )
#system.time( b<-checkTF(path.man,path.rfolder) )
```

Check whether a square matrix is symmetric

Check whether a square matrix is symmetric

Description

Check whether a square matrix is symmetric.

Usage

```
is.symmetric(x)
```

Arguments

x	A square matrix with data.

Details

Instead of going through the whole matrix, the function will stop if the first disagreement is met.

Value

A boolean value, TRUE of FALSE.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

cholesky, cora, cova

Examples

```
x <-matrix( rnorm( 100 * 400), ncol = 400 )
s1 <- cor(x)
is.symmetric(s1)
x <- x[1:100, ]
is.symmetric(x)

x<-s1<-NULL
```

`Chi-square and G-square tests of (unconditional) indepdence`
Chi-square and G-square tests of (unconditional) indepdence

Description

Chi-square and G-square tests of (unconditional) indepdence.

Usage

```
gchi2Test(x, y, logged = FALSE)
```

Arguments

`x`	A numerical vector or a factor variable with data. The data must be consecutive numbers.
`y`	A numerical vector or a factor variable with data. The data must be consecutive numbers.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The function calculates the test statistic of the χ^2 and the G^2 tests of unconditional independence between x and y. x and y need not be numerical vectors like in `g2Test`.

Value

A matrix with two rows. In each row the X2 or G2 test statistic, its p-value and the degrees of freedom are returned.

Author(s)

Manos Papadakis and Michail Tsagris.

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>.

References

Tsagris M. (2017). Conditional independence test for categorical data using Poisson log-linear model. Journal of Data Science, 15(2): 347–356.

See Also

g2Test_univariate, g2Test_univariate_perm, g2Test

Examples

```
nvalues <- 3
nvars <- 2
nsamples <- 2000
data <- matrix( sample( 0:(nvalues - 1), nvars * nsamples, replace = TRUE ), nsamples, nvars )

res<-gchi2Test(data[, 1], data[, 2])
res<-g2Test_univariate( data, rep(3, 2) )  ## G^2 test
res<-chisq.test(data[, 1], data[, 2])  ## X^2 test from R

data<-NULL
```

`Cholesky decomposition of a square matrix`

Cholesky decomposition of a square matrix

Description

Cholesky decomposition of a square matrix.

Usage

```
cholesky(x,parallel = FALSE)
```

Arguments

x	A square positive definite matrix.
parallel	A boolean value for parallel version.

Details

The Cholesky decomposition of a square positive definite matrix is computed. The use of parallel is suggested for matrices with dimensions of 1000 or more.

Value

An upper triangular matrix.

Author(s)

Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

See Also

`is.symmetric`

Examples

```
x = matrix(rnorm(1000 * 50), ncol = 50)
s = cov(x)
a1 <- cholesky(s)
#a2 <- chol(s)
#all.equal(a1[upper.tri(a1)], a2[upper.tri(a2)])
x <- NULL
s <- NULL
a1 <- NULL
a2 <- NULL
```

Circular or angular regression(s)

Circular or angular regression(s)

Description

Regression with circular dependent variable and Euclidean or categorical independent variables.

Usage

```
spml.reg(y, x, tol = 1e-07, seb = FALSE, maxiters = 100)
spml.regs(y, x, tol = 1e-07, logged = FALSE, maxiters = 100, parallel = FALSE)
```

Arguments

`y`	The dependent variable, it can be a numerical vector with data expressed in radians or it can be a matrix with two columns, the cosinus and the sinus of the circular data. The benefit of the matrix is that if the function is to be called multiple times with the same response, there is no need to transform the vector every time into a matrix.
`x`	The independent variable(s) of the single regression model. Can be Euclidean or categorical (factor variables). For the many regression models, a matrix with continuous variables.
`tol`	The tolerance value to terminatate the Newton-Raphson algorithm.
`seb`	Do you want the standard error of the estimates to be returned? TRUE or FALSE.

logged	Do you want the logarithm of the p-value be returned? TRUE or FALSE.
maxiters	The maximum number of iterations to implement.
parallel	Do you want the regression models to run in parallel? Default value is FALSE.

Details

The Newton-Raphson algorithm is fitted in this regression as described in Presnell et al. (1998).

For the case of spml.regs(), for each colum of x a circual regression model is fitted and the hypothesis testing of no association between y and this variable is performed.

Value

For the spml.reg() a list including:

iters	The number of iterations required until convergence of the EM algorithm.
be	The regression coefficients.
seb	The standard errors of the coefficients.
loglik	The value of the maximised log-likelihood.
seb	The covariance matrix of the beta values.

For the spml.regs() a matrix with two columns, the test statistics and their associated (log) p-values.

Author(s)

Michail Tsagris and Stefanos Fafalios.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Stefanos Fafalios <stefanosfafalios@gmail.com>.

References

Presnell Brett, Morrison Scott P. and Littell Ramon C. (1998). Projected multivariate linear models for directional data. Journal of the American Statistical Association, 93(443): 1068-1077.

See Also

spml.mle, iag.mle, acg.mle

Examples

```
x <- rnorm(100)
z <- cbind(3 + 2 * x, 1 -3 * x)
y <- cbind( rnorm(100,z[ ,1], 1), rnorm(100, z[ ,2], 1) )
y <- y / sqrt( rowsums(y^2) )
a1 <- spml.reg(y, x)
y <- atan( y[, 2] / y[, 1] ) + pi * I(y[, 1] < 0)
a2 <- spml.reg(y, x)

x <- matrnorm(100, 5)
a3 <- spml.regs(y, x)
```

`Circular-linear correlation` *Circular-linear correlation*

Description

It calculates the squared correlation between a circular and one or more linear variables.

Usage

```
circlin.cor(theta, x)
```

Arguments

`theta`	A circular variable expressed in radians.
`x`	The linear variable or a matrix containing many linear variables.

Details

The squared correlation between a circular and one or more linear variables is calculated.

Value

A matrix with as many rows as linear variables including:

`R-squared`	The value of the squared correlation.
`p-value`	The p-value of the zero correlation hypothesis testing.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Mardia, K. V. and Jupp, P. E. (2000). Directional statistics. Chicester: John Wiley & Sons.

See Also

`spml.reg`

Examples

```
#phi <- rvonmises(50, 2, 20, rads = TRUE)
#x <- 2 * phi + rnorm(50)
#y <- matrix(rnorm(50 * 5), ncol = 5)
#res<-circlin.cor(phi, x)
#res<-circlin.cor(phi, y)
y <- NULL
```

Coefficient matrices *Coefficient matrices*

Description

Coefficient matrices.

Usage

```
coeff(x, method,vector = FALSE)
```

Arguments

x	A matrix with data. The distances will be calculated between pairs of rows. In the case of **vecdist** this is a vector. For the **haversine** distance it must be a matrix with two columns, the first column is the latitude and the second the longitude.
method	See details for the available methods.
vector	For return a vector instead a matrix.

Details

- bhattacharyya : $\sum \sqrt{(P_i * Q_i)}$

Value

A square matrix with the pairwise coefficients.

Author(s)

Manos Papadakis.

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

dista, Dist

Examples

```
x <- matrix(rnorm(50 * 10), ncol = 10)
a1 <- coeff(x,"bhattacharyya")
x<-a1<-NULL
```

`Colum-wise cumulative operations (sum, prod, min, max)`
Colum-wise cumulative operations (sum, prod, min, max)

Description

Colum-wise cumulative operations (sum, prod, min, max).

Usage

```
colCumSums(x)
colCumProds(x)
colCumMins(x)
colCumMaxs(x)
```

Arguments

x	A numerical matrix.

Details

Cumulative mins, maxs, sums and prods are returned.

Value

A matrix with the results. It has one row less than the initial matrix.

Author(s)

Manos Papadakis and Michail Tsagris

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>.

See Also

`colsums`, `colMedians`, `colVars`

Examples

```
x <- matrnorm(10, 10)
res<-colCumSums(x)
res<-colCumMins(x)
res<-colCumMaxs(x)
res<-colCumProds(x)
```

Column and row wise coefficients of variation

Column and row wise coefficients of variation

Description

Column and row wise coefficients of variation.

Usage

```
colcvs(x, ln = FALSE, unbiased = FALSE)
rowcvs(x, ln = FALSE, unbiased = FALSE)
```

Arguments

x	A numerical matrix with the data.
ln	If you have log-normally distributed data (or assume you do), then set this to TRUE.
unbiased	A boolean variable indicating whether the unbiased for shpould be returned. This is applicable in case of small samples.

Details

The colum-wise coefficients of variation are calculated.

Value

A vector with the coefficient of variation for each column or row.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

colsums, colVars

Examples

```
m <- rnorm(100, 10)
x <- matrix(rnorm(100 * 100, m, 1), ncol = 100)
a1 <- colcvs(x)
a2 <- colcvs(x[1:25, ], unbiased = TRUE)
a3 <- colcvs( exp(x), ln = TRUE)
x <- NULL
```

`Column and row-wise Any/All` *Column and row-wise Any*

Description

Column and row-wise Any/All of a matrix.

Usage

```
colAny(x)
rowAny(x)
colAll(x, parallel = FALSE, cores = 0)
rowAll(x, parallel = FALSE, cores = 0)
```

Arguments

`x`	A logical matrix with the data.
`parallel`	Do you want the computations to take place in parallel? The default value is FALSE.
`cores`	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

The functions is written in C++ in order to be as fast as possible.

Value

A vector where item "i" is true if found Any/All true in column/row "i". Otherwise false.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`Median`, `colMedians`, `colMeans` (buit-in R function)

Examples

```
x <- matrix(as.logical(rbinom(100*100,1,0.5)),100,100)
a<-colAny(x)
#b<-apply(x,2,any)
#all.equal(a,b)

a<-rowAny(x)
#b<-apply(x,1,any)
```

```
#all.equal(a,b)

a<-colAll(x)
#b<-apply(x,2,all)
#all.equal(a,b)

a<-b<-x<-NULL
```

Column and row-wise means of a matrix

Column and row-wise means of a matrix

Description

Column and row-wise means of a matrix.

Usage

```
colmeans(x, parallel = FALSE, cores = 0)
## S3 method for class 'matrix'
colmeans(x, parallel = FALSE, cores = 0)
## S3 method for class 'data.frame'
colmeans(x, parallel = FALSE, cores = 0)
rowmeans(x)
colhameans(x, parallel = FALSE)
rowhameans(x)
```

Arguments

x	A numerical matrix or data.frame with data.
parallel	Do you want to do it in parallel in C++? TRUE or FALSE.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Value

A vector with the column or row arithmetic or harmonic means.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colsums, rowsums, colMins, colMedians, colMads

Examples

```
x <- matrix(rpois(100 * 100, 10),ncol = 100)
x1 <- colmeans(x)
#x2 <- colMeans(x)
#all.equal(x1,x2)

x1 <- rowmeans(x)
#x2 <- rowMeans(x)
#all.equal(x1,x2)

colhameans(x)
rowhameans(x)

x<-x1<-x2<-NULL
```

`Column and row-wise medians of a matrix or median of a vector.`
Column and row-wise medians of a matrix or median of a vector

---

Description

Column and row-wise medians of a matrix or median of a vector.

Usage

```
colMedians(x,na.rm = FALSE, parallel = FALSE, cores = 0)
rowMedians(x,na.rm = FALSE, parallel = FALSE, cores = 0)
Median(x,na.rm=FALSE)
med(x,na.rm=FALSE)
```

Arguments

`x`	A vector, matrix or data.frame with the data.
`parallel`	Do you want to do it in parallel in C++? TRUE or FALSE.
`na.rm`	TRUE or FAlSE for remove NAs if exists.
`cores`	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

The functions is written in C++ in order to be as fast as possible.

Value

A vector with the column medians.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Median, colVars, colMeans (buit-in R function)

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
a <- apply(x, 2, median)
b1 <- colMedians(x)
all.equal(as.vector(a), b1)

x<-a<-b1<-NULL
```

Column and row-wise nth smallest value of a matrix/vector

Column and row-wise nth smallest value of a matrix/vector

Description

Column and row-wise nth smallest value of a matrix/vector.

Usage

```
colnth(x,elems, num.of.nths = 1,descending = FALSE,na.rm = FALSE,
 index.return = FALSE, parallel = FALSE, cores = 0)
rownth(x,elems, num.of.nths = 1,descending = FALSE,na.rm = FALSE,
 index.return = FALSE, parallel = FALSE, cores = 0)
nth(x, k, num.of.nths = 1,descending = FALSE,index.return = FALSE,na.rm = FALSE)
```

Arguments

x	A matrix with the data.
elems	An integer vector with the kth smallest number to be returned for each column/row.
k	The kth smallest/biggest number to be returned.
num.of.nths	The number of the returned nths. By default is 1. Not use with argument parallel, for now.
descending	A boolean value (TRUE/FALSE) for descending order (biggest number). By default is ascending (smallest number).
index.return	Return the index of the kth smallest/biggest number.
parallel	Do you want to do it in parallel in C++? TRUE or FALSE only for col-row wise.
na.rm	TRUE or FAlSE for remove NAs if exists. Only for function "nth".
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

The functions is written in C++ in order to be as fast as possible.

Value

For "colnth" , "rownth": A vector with the column/row nth

For "nth": The nth value.

Author(s)

Manos Papadakis <papadakm95@gmail.com>

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`Median`, `colMedians`, `colMeans` (buit-in R function)

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
elems <- sample(1:100,100,TRUE)
colnth(x,elems)
rownth(x,elems)
x <- rnorm(1000)

nth(x, 500)
#sort(x)[500]

x<-elems<-NULL
```

`Column and row-wise Order - Sort Indices`

Column and row-wise Order - Sort Indices

Description

Column and row-wise Order - Sort Indices.

Usage

```
colOrder(x,stable=FALSE,descending=FALSE, parallel = FALSE, cores = 0)
rowOrder(x,stable=FALSE,descending=FALSE, parallel = FALSE, cores = 0)
Order(x,stable=FALSE,descending=FALSE,partial = NULL,parallel = FALSE)
```

Arguments

x	A matrix with numbers or a numeric/character vector.
stable	A boolean value for using a stable sorting algorithm.
descending	A boolean value (TRUE/FALSE) for sorting the vector in descending order. By default sorts the vector in ascending.
parallel	A boolean value for parallel version. For Order, this argument is supported on Windows and most of the unix.
partial	A boolean value for partial sorting.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE column - major ordering. Default value is 0 and it means the maximum supported cores.

Details

The function applies "order" in a column or row-wise fashion or Order a vector. If you want the same results as R's, then set "stable=TRUE" because "stable=FALSE" uses a sorting algorithm that it is not stable like R's sort. But it is faster to use the default. This version is faster for large data, more than 300.

Value

For "colOrder" and "rowOrder" a matrix with integer numbers. The result is the same as apply(x, 2, order) or apply(x, 1, order).

For "Order" sort the vector and returns the indices of each element that it has before the sorting. The result is the same as order(x) but for the same exactly results set argument "stable" to "TRUE".

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colsums, coldiffs, colMedians, colprods

Examples

```
x <- matrix( runif(10 * 10), ncol = 10 )
res<-colOrder(x)
res<-apply(x, 2, order)
res<-rowOrder(x)
t(apply(x, 1, order))

y <- rnorm(100)
b <- Order(y)
a <- order(y)
all.equal(a,b) ## false because it is not stable
b <- Order(y,stable=TRUE)
```

```
all.equal(a,b) ## true because it is stable

x<-y<-b<-a<-NULL
```

Column and row-wise products

Column and row-wise products

Description

Column and row-wise products.

Usage

```
colprods(x, method = "direct")
rowprods(x)
```

Arguments

x	A matrix with numbers.
method	The type of colCumProds to use. For direct multiplication use "direct" or "expsumlog" for a more numerically stable, but slower way.

Details

The product of the numbers in a matrix is returned either column-wise or row-wise.

Value

A vector with the column or the row products.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colsums, coldiffs, colMedians

Examples

```
x <- matrix( runif(100 * 10), ncol = 10 )
res<-colprods(x)
res<-rowprods(x)

x<-NULL
```

Column and row-wise range of values of a matrix

Column and row-wise range of values of a matrix

Description

Column and row-wise range of values of a matrix.

Usage

```
colrange(x, cont = TRUE, parallel = FALSE,cores = 0)
rowrange(x, cont = TRUE)
```

Arguments

x	A numerical matrix or data.frame with data.
parallel	Execute algorithm in parallel for data.frame.
cont	If the data are continuous, leave this TRUE and it will return the range of values for each variable (column). If the data are integers, categorical, or if you want to find out the number of unique numbers in each column set this to FALSE.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Value

A vector with the relevant values.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colMins, colMaxs, rowMins, rowMaxs, nth, colMedians, colVars, colSort, rowSort

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )

a1 <- colrange(x)
a2 <- apply(x, 2, function(x) diff( range(x)) )
all.equal(a1, a2)

a1 <- rowrange(x)
a2 <- apply(x, 1, function(x) diff( range(x)) )
all.equal(a1, a2)
```

```
x<-a1<-a2<-NULL
```

Column and row-wise ranks

Column and row-wise ranks

Description

Column and row-wise ranks.

Usage

```
colRanks(x,method = "average",descending = FALSE,
     stable = FALSE, parallel = FALSE, cores = 0)
rowRanks(x,method = "average",descending = FALSE,
     stable = FALSE, parallel = FALSE, cores = 0)
Rank(x,method = "average",descending = FALSE,stable = FALSE, parallel = FALSE)
```

Arguments

x	A mumerical matrix or data.frame with the data.
parallel	A boolean value for parallel version.
method	a character string for choosing method. Must be one of: • average : a permutation with theri mean values at each index set of ties • min : a permutation with minimum values at each index set of ties • max : a permutation with maximum values at each index set of ties • first : a permutation with increasing values at each index set of ties • random : a permutation with random values at each index set of ties
descending	A boolean value (TRUE/FALSE) for sorting the vector in descending order. By default sorts the vector in ascending.
stable	A boolean value (TRUE/FALSE) for choosing a stable sort algorithm. Stable means that discriminates on the same elements. Only for the method "first".
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

For each column or row of a matrix the ranks are calculated and they are returned.

Value

A matrix with the column or row-wise ranks.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Rank, correls

Examples

```
x <- matrnorm(100, 10)
a1 <- colRanks(x)
a2 <- apply(x, 2, rank)
b1 <- rowRanks(x)
b2 <- apply(x, 1, rank)

a1 <- Rank(x[,1])
a1 <- rank(x[,1])

x<-a1<-a2<-b1<-b2<-NULL
```

Column and row-wise Shuffle

Column and row-wise Shuffle

Description

Column and row-wise shuffle of a matrix.

Usage

```
colShuffle(x)
rowShuffle(x)
```

Arguments

x	A matrix or data.frame with the data.

Details

The functions is written in C++ in order to be as fast as possible.

Value

A vector with the column/row Shuffle.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Median, colVars, colMeans (buit-in R function)

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
colShuffle(x)
rowShuffle(x)

x<-NULL
```

Column and row-wise sums of a matrix

Column and row-wise sums of a matrix

Description

Column and row-wise sums of a matrix.

Usage

```
colsums(x,indices = NULL, parallel = FALSE, na.rm = FALSE, cores = 0)
rowsums(x,indices = NULL, parallel = FALSE, na.rm = FALSE, cores = 0)
```

Arguments

x	A numerical matrix with data.
indices	An integer vector with the indices to sum the columns/rows.
parallel	Do you want to do it in parallel in C++? TRUE or FALSE. Doens't work with argument "indices".
na.rm	A logical value indicating to remove NAs. The algorithm run in parallel so do not use with option parallel.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Value

A vector with sums.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colMedians, colmeans, colVars

Examples

```
x <- matrix(rpois(500 * 100, 10),ncol = 100)
x1 <- colsums(x)
x2 <- colSums(x)
all.equal(x1,x2)

x1 <- rowsums(x)
x2 <- rowSums(x)
all.equal(x1,x2)

x<-x1<-x2<-NULL
```

`Column and row-wise tabulate`

Column and row-wise tabulate

Description

Column and row-wise tabulate of a matrix.

Usage

```
colTabulate(x, max_number = max(x))
rowTabulate(x, max_number = max(x))
```

Arguments

`x`	An integer matrix with the data. The numbers must start from 1, i.e. 1, 2, 3, 4,... No zeros are allowed. Anything else may cause a crash.
`max_number`	The maximum value of vector x. If you know which is the max number use this argument for faster results or by default max(x).

Details

The functions is written in C++ in order to be as fast as possible.

Value

A matrix where in each column the command "tabulate" has been performed. The number of rows of the returned matrix will be equal to the max_number if given. Otherwise, the functions will find this number.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`colShuffle`, `colVars`, `colmeans`

Examples

```
x <- matrix( rbinom(100 * 100, 4, 0.5), ncol = 100 )
colTabulate(x)
rowTabulate(x)

x<-NULL
```

Column and row-wise variances and standard deviations

Column and row-wise variances and standard deviations of a matrix

---

Description

Column and row-wise variances and standard deviations of a matrix

Usage

```
## S3 method for class 'matrix'
colVars(x, std = FALSE, na.rm = FALSE, parallel = FALSE, cores = 0)
## S3 method for class 'data.frame'
colVars(x, std = FALSE, na.rm = FALSE, parallel = FALSE, cores = 0)
colVars(x, std = FALSE, na.rm = FALSE, parallel = FALSE, cores = 0)
rowVars(x, std = FALSE, na.rm = FALSE, parallel = FALSE, cores = 0)
```

Arguments

x	A matrix with the data.
std	A boolean variable specyfying whether you want the variances (FALSE) or the standard deviations (TRUE) of each column.
na.rm	TRUE or FAlSE for remove NAs if exists.
parallel	Should parallel implentations take place in C++? The default value is FALSE.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

We found this on stackoverflow which was created by David Arenburg. We then modified the function to match the sums type formula of the variance, which is faster.

Value

A vector with the column variances or standard deviations.

Author(s)

Michail Tsagris and Manos Papadakis.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

colmeans, colMedians, colrange

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
a2 <- colVars(x)
x<-a2<-NULL
```

Column and rows-wise mean absolute deviations

Column and row-wise mean absolute deviations

Description

Column and row-wise mean absolute deviations.

Usage

```
colMads(x,method = "median",na.rm=FALSE,parallel = FALSE, cores = 0)
rowMads(x,method = "median",na.rm=FALSE,parallel = FALSE, cores = 0)
Mad(x,method = "median",na.rm=FALSE)
```

Arguments

x	A vector, matrix or data.frame with the data.
method	A character vector with values "median", for median absolute deviation or "mean", for mean absolute deviation.
na.rm	A logical value TRUE/FALSE to remove NAs.
parallel	A boolean value for parallel version.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

The functions is written in C++ in order to be as fast as possible.

Value

A vector with the column-wise mean absolute deviations.

Author(s)

Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

colMedians, rowMedians, colVars, colmeans, colMeans (buit-in R function)

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
a <- colMads(x)

x<-NULL
```

`Column-wise differences`

Column-wise differences

Description

Column-wise differences.

Usage

```
coldiffs(x)
```

Arguments

x	A matrix with numbers.

Details

This function simply does this function x[, -1] - x[, -k], where k is the last column of the matrix x. But it does it a lot faster. That is, 2nd column - 1st column, 3rd column - 2nd column, and so on.

Value

A matrix with one column less containing the differences between the successive columns.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Dist, dista, colmeans

Examples

```
x <- matrix( rnorm(50 * 10), ncol = 10 )
res<-coldiffs(x)

x<-NULL
```

Column-wise kurtosis and skewness coefficients
Column-wise kurtosis and skewness coefficients

Description

Column-wise kurtosis and skewness coefficients.

Usage

```
colkurtosis(x, pvalue = FALSE)

colskewness(x, pvalue = FALSE)
```

Arguments

x	A matrix with the data, where the rows denote the samples and the columns are the variables.
pvalue	If you want a hypothesis test that the skewness or kurtosis are significant set this to TRUE. This checks whether the skewness is significantly different from 0 and whether the kurtosis is significantly different from 3.

Details

The skewness and kurtosis coefficients are calculated. For the skewness coefficient we use the sample unbiased version of the standard deviation. For the kurtosis, we do not subtract 3.

Value

If "pvalue" is FALSE, a vector with the relevant coefficient. Otherwise a matrix with two columns. The kurtosis or skewness coefficient and the p-value from the hypothesis test that they are significantly different from 3 or 0 respectively.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

skew, skew.test2, colMedians, colmeans, colVars, sftests

Examples

```
## 200 variables, hence 200 F-tests will be performed
x = matrix( rnorm(200 * 50), ncol = 50 )
## 200 observations in total
colkurtosis(x)
colskewness(x)
x <- NULL
```

`Column-wise matching coefficients`
Column-wise matching coefficients

Description

Column-wise matching coefficients.

Usage

```
match.coefs(x, y = NULL, ina, type = "jacc")
```

Arguments

`x`	A matrix with the data, where the rows denote the samples and the columns are the variables.
`y`	A second matrix with the data of the second group. If this is NULL (default value) then the argument ina must be supplied. Notice that when you supply the two matrices the procedure is two times faster.
`ina`	A numerical vector with 1s and 2s indicating the two groups. Be careful, the function is designed to accept only these two numbers. In addition, if your "y" is NULL, you must specify "ina".
`type`	This denotes the type of matching coefficient to calculate. For the Jaccard index put "jacc". For the simple matching coefficient put "smc" or else both of them will be calculated.

Details

Two matrices are given as imput and for each column matching coefficients are calculated, either the Jaccard or the simple matching coefficient or both.

Value

A matrix with one or two columns, depending on the type you have specified. If you specify "both", there will be two columns, if you specify "jacc" or "smc" then just one column.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

odds, colTabulate

Examples

```
x <- matrix(rbinom(400 * 10, 1, 0.5), ncol = 10)
y <- matrix(rbinom(400 * 10, 1, 0.5), ncol = 10)
a <- match.coefs(x, y, type = "both")
x <- NULL
y <- NULL
```

Column-wise minimum and maximum

Column-wise minimum and maximum of a matrix

Description

Column-wise minimum and maximum of a matrix.

Usage

```
colMins(x, value = FALSE, parallel = FALSE, cores = 0)
colMaxs(x, value = FALSE, parallel = FALSE, cores = 0)
colMinsMaxs(x, parallel = FALSE, cores = 0)
```

Arguments

x	A numerical matrix or data.frame with data.
value	If the value is FALSE it returns the indices of the minimum/maximum, otherwise it returns the minimum and maximum values.
parallel	Do you want to do it in parallel in C++? TRUE or FALSE. The parallel will return the minimum/maximum value only. It will never return the indices.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Value

A vector with the relevant values.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, rowMaxs, nth, colrange, colMedians, colVars, colSort, rowSort

Examples

```
x <- matrix( rnorm(100 * 200), ncol = 200 )

s1 <- colMins(x)
s2 <- apply(x, 2, min)

s1 <- colMaxs(x)
s2 <- apply(x, 2, max)

s1 <- colMinsMaxs(x)
s2 <- c(apply(x, 2, min), apply(x, 2, max))

x<-s1<-s2<-NULL
```

Column-wise MLE of some univariate distributions

Column-wise MLE of some univariate distributions

Description

Column-wise MLE of some univariate distributions.

Usage

```
colexpmle(x)
colexp2.mle(x)
colgammamle(x, tol = 1e-07)
colinvgauss.mle(x)
collaplace.mle(x)
collindley.mle(x)
colmaxboltz.mle(x)
colnormal.mle(x)
colpareto.mle(x)
colrayleigh.mle(x)
colvm.mle(x, tol = 1e-07)
colweibull.mle(x, tol = 1e-09, maxiters = 100, parallel = FALSE)
colnormlog.mle(x)
```

Arguments

x	A numerical matrix with data. Each column refers to a different vector of observations of the same distribution. For exponential, 2 parameter exponential, Weibull, gamma, inverse Gaussian, Maxwell-Boltzman, Lindley, Rayleigh and Pareto distributions, the numbers must be greater than zero. For the Poisson and geometric distributions, the numbers must be integers, 0, 1, 2,... For the Normal and Laplace distribution the numbers can take any value. The von Mises distribution takes values beween 0 and 2 π (radians).
tol	The tolerance value to terminate the Newton-Fisher algorithm.
maxiters	The maximum number of iterations to implement.
parallel	Do you want to calculations to take place in parallel? The default value is FALSE

Details

For each column, the same distribution is fitted and its parameter and log-likelihood are computed.

Value

A matrix with two, three or five (for the colnormlog.mle) columns. The first one or the first two contain the parameter(s) of the distribution and the other columns contain the log-likelihood values.

Author(s)

Michail Tsagris and Stefanos Fafalios

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Stefanos Fafalios <stefanosfafalios@gmail.com>

References

Kalimuthu Krishnamoorthy, Meesook Lee and Wang Xiao (2015). Likelihood ratio tests for comparing several gamma distributions. Environmetrics, 26(8):571-583.

N.L. Johnson, S. Kotz and N. Balakrishnan (1994). Continuous Univariate Distributions, Volume 1 (2nd Edition).

N.L. Johnson, S. Kotz and N. Balakrishnan (1970). Distributions in statistics: continuous univariate distributions, Volume 2.

Sharma V. K., Singh S. K., Singh U. and Agiwal V. (2015). The inverse Lindley distribution: a stress-strength reliability model with application to head and neck cancer data. Journal of Industrial and Production Engineering, 32(3): 162-173.

See Also

vm.mle, poisson.mle, normal.mle, gammamle

Examples

```
x <- matrix(rnorm(1000 * 50), ncol = 50)
a <- colnormal.mle(x)
b <- collaplace.mle(x)
x <- NULL
```

Column-wise true/false value

Column-wise true/false value of a matrix

Description

Column-wise true/false value of a matrix.

Usage

```
colTrue(x)
colFalse(x)
colTrueFalse(x)
```

Arguments

x	A logical matrix with data.

Value

An integer vector where item "i" is the number of the true/false values of "i" column.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, rowFalse, nth, colrange, colMedians, colVars, colSort, rowSort, rowTrue

Examples

```
x <- matrix(as.logical(rbinom(100*100,1,0.5)),100,100)

s1 <- colTrue(x)

s1 <- colFalse(x)

s1 <- colTrueFalse(x)

x<-s1<-NULL
```

Column-wise uniformity Watson test for circular data
Column-wise uniformity tests for circular data

Description

Column-wise uniformity tests for circular data.

Usage

```
colwatsons(u)
```

Arguments

u	A numeric matrix containing the circular data which are expressed in radians. Each column is a different sample.

Details

These tests are used to test the hypothesis that the data come from a circular uniform distribution. The Kuiper test is much more time consuming and this is why it not implemented yet. Once we figure out a way to make it fast, we will incldue it.

Value

A matrix with two columns, the value of the test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Jammalamadaka, S. Rao and SenGupta, A. (2001). Topics in Circular Statistics, pg. 153-55 (Kuiper's test) & 156-157 (Watson's test).

See Also

watson, vmf.mle, rvonmises

Examples

```
#x <- matrix( rvonmises(n = 50 * 10, m = 2, k = 0), ncol = 10 )
#res<-colwatsons(x)
x <- NULL
```

`Column-wise Yule's Y (coefficient of colligation)`
Column-wise Yule's Y (coefficient of colligation)

Description

Column-wise Yule's Y (coefficient of colligation).

Usage

```
col.yule(x, y = NULL, ina)
```

Arguments

x	A matrix with 0 and 1. Every column refers to a different sample or variable.
y	A second matrix, of the same dimensions as x, with 0 and 1. Every column refers to a different sample or variable.
ina	If y is NULL, ina must be specified. This is a numeric vector with 1s and 2s, indicating the group of each row.

Details

Yule's coefficient of colligation is calculated for every column.

Value

A vector with Yule's Y, one for every column of x is returned.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Yule G. Udny (1912). On the Methods of Measuring Association Between Two Attributes. Journal of the Royal Statistical Society, 75(6):579-652.

See Also

`yule`, `odds`

Examples

```
x <- matrix(rbinom(300 * 10, 1, 0.5), ncol = 10)
ina <- rep(1:2, each = 150)
res<-col.yule( x, ina = ina )
```

Convert a dataframe to matrix

Convert a dataframe to matrix

Description

Convert a dataframe to matrix.

Usage

```
data.frame.to_matrix(x,col.names = NULL,row.names = NULL)
```

Arguments

x	A Numeric matrix with data and NAs.
col.names	A boolean value for keeping the colnames for argument x or a character vector for the new colnames.
row.names	A boolean value for keeping the rownames for argument x or a character vector for the new rownames.

Details

This functions converts a dataframe to matrix. Even if there are factors, the function converts them into numerical values. Attributes are not allowed for now.

Value

A matrix wich has the numrical values from the dataframe.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

Match, is.symmetric, permutation

Examples

```
res<-data.frame.to_matrix(iris)
```

`Convert R function to the Rfast's coresponding`
Convert R function to the Rfast's coresponding

Description

Convert R function to the Rfast's coresponding.

Usage

```
as.Rfast.function(Rfunction.name,margin=NULL)
```

Arguments

`Rfunction.name`	An character value with the name of the function.
`margin`	A logical function for return the column-row wise function.

Details

Given the name of R function, it returns the coresponding function's name from Rfast.

Value

The coresponding Rfast function.

Author(s)

Manos Papadakis and Michail Tsagris

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>.

See Also

`colsums`, `colMedians`, `colVars`

Examples

```
res<-as.Rfast.function("var")
```

Correlation based forward regression
Correlation based forward regression

Description

Correlation based forward regression.

Usage

```
cor.fsreg(y, x, ystand = TRUE, xstand = TRUE, threshold = 0.05,
tolb = 2, tolr = 0.02, stopping = "BIC")
```

Arguments

y	A numerical vector.
x	A matrix with data, the predictor variables.
ystand	If this is TRUE the response variable is centered. The mean is subtracted from every value.
xstand	If this is TRUE the independent variables are standardised.
threshold	The significance level, set to 0.05 by default. Bear in mind that the logarithm of it is used, as the logarithm of the p-values is calculated at every point. This will avoid numerical overflows and small p-values, less than the machine epsilon, being returned as zero.
tolb	If we see only the significane of the variables, many may enter the linear regression model. For this reason, we also use the BIC as a way to validate the inclusion of a candidate variable. If the BIC difference between two successive models is less than the tolerance value, the variable will not enter the model, even if it statistically significant. Set it to 0 if you do not want this extra check.
tolr	This is an alternative to the BIC change and it uses the adjusted coefficient of determination. If the increase in the adjusted R^2 is more than the tolr continue.
stopping	This refers to the type of extra checking to do. If you want the BIC check, set it to "BIC". If you want the adjusted R^2 check set this to "ar2". Or, if you want both of them to take place, both of these criteria to be satisfied make this "BICR2".

Details

The forward regression tries one by one the variables using the F-test, basically partial F-test every time for the latest variable. This is the same as testing the significance of the coefficient of this latest enetered variable. Alternatively the correlation can be used and this case the partial correlation coefficient. There is a direct relationship between the t-test statistic and the partial correlation coefficient. Now, instead of having to calculate the test statistic, we calculate the partial correlation coefficient. Using Fisher's z-transform we get the variance imediately. The partial correlation coefficient, using Fisher's z-transform, and the partial F-test (or the coefficient's t-test statistic) are not identical. They will be identical for large sample sizes though.

Value

A matrix with three columns, the index of the selected variables, the logged p-value and the the test statistic value and the BIC or adjusted R^2 of each model. In the case of stopping="BICR2" both of these criteria will be returned.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

See Also

score.glms, univglms, logistic_only, poisson_only, regression

Examples

```
## 200 variables, hence 200 univariate regressions are to be fitted
x <- matrnorm(200,  100)
y <- rnorm(200)
cor.fsreg(y, x)
x <- NULL
```

Correlation between pairs of variables

Correlation between pairs of variables

Description

Correlations between pairs of variables.

Usage

```
corpairs(x, y, rho = NULL, logged = FALSE, parallel = FALSE)
```

Arguments

x	A matrix with real valued data.
y	A matrix with real valued data whose dimensions match those of x.
rho	This can be a vector of assumed correlations (equal to the number of variables or the columns of x or y) to be tested. If this is not the case, leave it NULL and only the correlations will be returned.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)? This is taken into account only if "rho" is a vector.
parallel	Should parallel implentations take place in C++? The default value is FALSE.

Details

The paired correlations are calculated. For each column of the matrices x and y the correlation between them is calculated.

Value

A vector of correlations in the case of "rho" being NULL, or a matrix with two extra columns, the test statistic and the (logged) p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Lambert Diane (1992). Zero-Inflated Poisson Regression, with an Application to Defects in Manufacturing. Technometrics. 34(1):1-14.

Johnson Norman L., Kotz Samuel and Kemp Adrienne W. (1992). Univariate Discrete Distributions (2nd ed.). Wiley

Cohen, A. Clifford (1960). Estimating parameters in a conditional Poisson distribution. Biometrics. 16:203-211.

Johnson, Norman L. Kemp, Adrianne W. Kotz, Samuel (2005). Univariate Discrete Distributions (third edition). Hoboken, NJ: Wiley-Interscience.

See Also

correls, allbetas, mvbetas

Examples

```
x <- matrnorm(100, 100)
y <- matrnorm(100, 100)
corpairs(x, y)
a <- corpairs(x, y)
x <- NULL
y <- NULL
```

`Correlations` *Correlation between a vector and a set of variables*

Description

Correlation between a vector and a set of variables.

Usage

```
correls(y, x, type = "pearson", a = 0.05, rho = 0)
groupcorrels(y, x, type = "pearson", ina)
```

Arguments

`y`	A numerical vector.
`x`	A matrix with the data.
`type`	The type of correlation you want. "pearson" and "spearman" are the two supported types for the "correls" because their standard error is easily calculated. For the "groupcorrels" you can also put "kendall" because no hypothesis test is performed in that function.
`a`	The significance level used for the confidence intervals.
`rho`	The value of the hypothesised correlation to be used in the hypothesis testing.
`ina`	A factor variable or a numeric variable idicating the group of each observation.

Details

The functions uses the built-in function "cor" which is very fast and then includes confidence intervals and produces a p-value for the hypothesis test.

Value

For the "correls" a matrix with 5 column; the correlation, the p-value for the hypothesis test that each of them is eaqual to "rho", the test statistic and the $a/2%$ lower and upper confidence limits.

For the "groupcorrels" a matrix with rows equal to the number of groups and columns equal to the number of columns of x. The matrix contains the correlations only, no statistical hypothesis test is performed.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`allbetas`, `univglms`

Examples

```
x <- matrnorm(60, 100 )
y <- rnorm(60)
r <- cor(y, x)  ## correlation of y with each of the xs
a <- allbetas(y, x)  ## the coefficients of each simple linear regression of y with x
b <- correls(y, x)
ina <- rep(1:2, each = 30)
b2 <- groupcorrels(y, x, ina = ina)
x <- NULL
```

Covariance and correlation matrix

Fast covariance and correlation matrix calculation

Description

Fast covariance and correlation matrix calculation.

Usage

```
cova(x, center = FALSE, large = FALSE)

cora(x, large = FALSE)
```

Arguments

x	A matrix with data. It has to be matrix, if it is data.frame for example the function does not turn it into a matrix.
center	If you want to center the data prior to applying the cross product of the mateix set this equal to TRUE, otherwise leave it NULL.
large	If you have large matrices, with thousands of rows and or many tens or hundreds of columns set this equal to TRUE in order to use Rfast's Crossprod or Tcrossprod functions. These functions are twice or up to 3 times faster than the correpsonding built-in functions.

Details

The calculations take place faster than the built-in functions cor as the number of variables increases. This is true if the number of variables is high, say from 500 and above. The "cova" on the other hand is always faster. For the "cova" in specific, we have an option to center the data prior to the cross product. This can be more stable if you have many tens of thousands of rows due to numerical issues that can arise.

For the correlation matrix we took the code from here

https://stackoverflow.com/questions/18964837/fast-correlation-in-r-using-c-and-parallelization/18965892#18965892

Value

The covariance or the correlation matrix.

Author(s)

Michail Tsagris and Manos Papadakis <papadakm95@gmail.com>.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`colVars`, `cor`, `cov`

Examples

```
x <- matrnorm(100, 40)
s1 <- cov(x)
s2 <- cova(x)
all.equal(s1, s2)
x <- NULL
```

`Cox confidence interval for the ratio of two Poisson variables`

Cox confidence interval for the ratio of two Poisson variables

---

Description

Cox confidence interval for the ratio of two Poisson variables.

Usage

```
cox.poisrat(x, y, alpha = 0.05)
col.coxpoisrat(x, y, alpha = 0.05)
```

Arguments

`x`	A numeric vector or a matrix with count data.
`y`	A numeric vector or a matrix with count data.
`alpha`	The 1 - confidence level. The default value is 0.05.

Details

Cox confidence interval for the ratio of two Poisson means is calculated.

Value

For the cox.poisrat a vector with three elements, the ratio and the lower and upper confidence interval limits. For the col.coxpoisrat a matrix with three columns, the ratio and the lower and upper confidence interval limits.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Krishnamoorthy K., Peng J. and Zhang D. (2016). Modified large sample confidence intervals for Poisson distributions: Ratio, weighted average, and product of means. Communications in Statistics-Theory and Methods, 45(1): 83-97.

See Also

correls, Table

Examples

```
x <- rpois(100, 10)
y <- rpois(100, 10)
res<-cox.poisrat(x, y)
```

`Cross-Validation for the k-NN algorithm`

Cross-Validation for the k-NN algorithm

Description

Cross-Validation for the k-NN algorithm.

Usage

```
knn.cv(folds = NULL, nfolds = 10, stratified = FALSE, seed = NULL, y, x, k,
dist.type = "euclidean", type = "C", method = "average", freq.option = 0,
pred.ret = FALSE, mem.eff = FALSE)
```

Arguments

folds	A list with the indices of the folds.
nfolds	The number of folds to be used. This is taken into consideration only if "folds" is NULL.

`stratified`	Do you want the folds to be selected using stratified random sampling? This preserves the analogy of the samples of each group. Make this TRUE if you wish, but only for the classification. If you have regression (type = "R"), do not put this to TRUE as it will cause problems or return wrong results.
`seed`	If NULL different folds will be created every time. Otherwise set your own seed.
`y`	A vector of data. The response variable, which can be either continuous or categorical (factor is acceptable).
`x`	A matrix with the available data, the predictor variables.
`k`	A vector with the possible numbers of nearest neighbours to be considered.
`dist.type`	The type of distance to be used, "euclidean" or "manhattan".
`type`	Do you want to do classification ("C") or regression ("R")?
`method`	If you do regression (type = "R"), then how should the predicted values be calculated? Choose among the average ("average"), median ("median") or the harmonic mean ("harmonic") of the closest neighbours.
`freq.option`	If classification (type = "C") and ties occur in the prediction, more than one class have the same number of k nearest neighbours, there are three strategies available. Option 0 selects the first most frequent encountered. Option 1 randomly selects the most frequent value, in the case that there are duplicates.
`pred.ret`	If you want the predicted values returned set this to TRUE.
`mem.eff`	Boolean value indicating a conservative or not use of memory. Lower usage of memory/Having this option on will lead to a slight decrease in execution speed and should ideally be on when the amount of memory in demand might be a concern.

Details

The concept behind k-NN is simple. Suppose we have a matrix with predictor variables and a vector with the response variable (numerical or categorical). When a new vector with observations (predictor variables) is available, its corresponding response value, numerical or categorical, is to be predicted. Instead of using a model, parametric or not, one can use this ad hoc algorithm.

The k smallest distances between the new predictor variables and the existing ones are calculated. In the case of regression, the average, median, or harmonic mean of the corresponding response values of these closest predictor values are calculated. In the case of classification, i.e. categorical response value, a voting rule is applied. The most frequent group (response value) is where the new observation is to be allocated.

This function does the cross-validation procedure to select the optimal k, the optimal number of nearest neighbours. The optimal in terms of some accuracy metric. For the classification it is the percentage of correct classification and for the regression the mean squared error.

Value

A list including:

`preds`	If pred.ret is TRUE the predicted values for each fold are returned as elements in a list.

`crit` A vector whose length is equal to the number of k and is the accuracy metric for each k. If you want to compute other metrics of accuracy we suggest you choose "pred.ret = TRUE" when running the function and then write a simple function to compute more metrics. See **col.accs()** or **colmses()** in the package **Rfast2**.

Author(s)

Marios Dimitriadis

R implementation and documentation: Marios Dimitriadis <kmdimitriadis@gmail.com>

References

Friedman J., Hastie T. and Tibshirani R. (2017). The elements of statistical learning. New York: Springer.

Cover TM and Hart PE (1967). Nearest neighbor pattern classification. IEEE Transactions on Information Theory. 13(1):21-27.

Tsagris Michail, Simon Preston and Andrew T.A. Wood (2016). Improved classification for compositional data using the α-transformation. Journal of classification 33(2): 243-261.

See Also

`knn`, `Dist`, `dista`, `dirknn.cv`

Examples

```
x <- as.matrix(iris[, 1:4])
y <- iris[, 5]
mod <- knn.cv(folds = NULL, nfolds = 10, stratified = FALSE, seed = NULL, y = y, x = x,
k = c(3, 4), dist.type = "euclidean", type = "C", method = "average",
freq.option = 0, pred.ret = FALSE, mem.eff = FALSE)
```

Cross-Validation for the k-NN algorithm using the arc cosinus distance

Cross-Validation for the k-NN algorithm using the arc cosinus distance

---

Description

Cross-Validation for the k-NN algorithm using the arc cosinus distance.

Usage

```
dirknn.cv(y, x, k = 5:10, type = "C", folds = NULL, nfolds = 10,
stratified = TRUE, seed = NULL, parallel = FALSE, pred.ret = FALSE)
```

Arguments

`y`	A vector of data. The response variable, which can be either continuous or categorical (factor is acceptable).
`x`	A matrix with the available data, the predictor variables.
`k`	A vector with the possible numbers of nearest neighbours to be considered.
`type`	If your response variable y is numerical data, then this should be "R" (regression) or "WR" for distance weighted based nearest neighbours. If y is in general categorical set this argument to "C" (classification) or to "WC" for distance weighted based nearest neighbours.
`folds`	A list with the indices of the folds.
`nfolds`	The number of folds to be used. This is taken into consideration only if "folds" is NULL.
`stratified`	Do you want the folds to be selected using stratified random sampling? This preserves the analogy of the samples of each group. Make this TRUE if you wish, but only for the classification. If you have regression (type = "R"), do not put this to TRUE as it will cause problems or return wrong results.
`seed`	If NULL different folds will be created every time. Otherwise set your own seed.
`parallel`	Do you want th ecalculations to take place in parallel? The default value is FALSE.
`pred.ret`	If you want the predicted values returned set this to TRUE.

Details

The concept behind k-NN is simple. Suppose we have a matrix with predictor variables and a vector with the response variable (numerical or categorical). When a new vector with observations (predictor variables) is available, its corresponding response value, numerical or categorical, is to be predicted. Instead of using a model, parametric or not, one can use this ad hoc algorithm.

The k smallest distances between the new predictor variables and the existing ones are calculated. In the case of regression, the average, median, or harmonic mean of the corresponding response values of these closest predictor values are calculated. In the case of classification, i.e. categorical response value, a voting rule is applied. The most frequent group (response value) is where the new observation is to be allocated.

This function does the cross-validation procedure to select the optimal k, the optimal number of nearest neighbours. The optimal in terms of some accuracy metric. For the classification it is the percentage of correct classification and for the regression the mean squared error.

Value

A list including:

`preds`	If pred.ret is TRUE the predicted values for each fold are returned as elements in a list.
`crit`	A vector whose length is equal to the number of k and is the accuracy metric for each k. For the classification case it is the percentage of correct classification. For the regression case the mean square of prediction error.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Friedman J., Hastie T. and Tibshirani R. (2017). The elements of statistical learning. New York: Springer.

Cover TM and Hart PE (1967). Nearest neighbor pattern classification. IEEE Transactions on Information Theory. 13(1):21-27.

See Also

dirknn, knn.cv, knn

Examples

```
x <- as.matrix(iris[, 1:4])
x <- x / sqrt( Rfast::rowsums(x^2) )
y <- iris[, 5]
mod <- dirknn.cv(y = y, x = x, k = c(3, 4) )
```

Deep copy *Deep copy*

Description

Deep copy.

Usage

```
env.copy(x,all.names=FALSE)
```

Arguments

x	An environment object.
all.names	An logical value (TRUE or FALSE). Copy all the hidden variables or not.

Details

Deep copy of the environment object.

Value

A copy of the first argument.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`colShuffle`, `colVars`, `colmeans`

Examples

```
x <- new.env()
x$imaginary <- NULL
x$real <- NULL

# you can library the package and just press x and R will understand
# and search automatically for a function to print the environment
x

y <- env.copy(x)

x$real <- 10

x$real == y$real # FALSE
```

`Density of the multivariate normal and t distributions`

Density of the multivariate normal and t distributions

Description

Density of the multivariate normal and t distributions.

Usage

```
dmvnorm(x, mu, sigma, logged = FALSE)
dmvt(x, mu, sigma, nu, logged = FALSE)
```

Arguments

`x`	A numerical matrix with the data. The rows correspond to observations and the columns to variables.
`mu`	The mean vector.
`sigma`	The covariance matrix.
`nu`	The degrees of freedom for the multivariate t distribution.
`logged`	Should the logarithm of the density be returned (TRUE) or not (FALSE)?

Details

The (log) density of the multivariate normal distribution is calculated for given mean vector and covariance matrix.

Value

A numerical vector with the density values calculated at each vector (row of the matrix x).

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Kanti V. Mardia, John T. Kent and John M. Bibby (1979). Multivariate analysis. Academic Press, London.

See Also

`rmvnorm`, `rmvt`, `mvnorm.mle`, `iag.mle`

Examples

```
x <- matrnorm(100, 20)
mu <- colmeans(x)
s <- cova(x)
#1 <- dmvnorm(x, mu, s)
#2 <- dmvt(x, mu, s, 1)
x <- NULL
```

Design Matrix *Design Matrix*

Description

Design Matrix.

Usage

```
design_matrix(x, ones = TRUE)
```

Arguments

x	A character vector or a factor type vector or a dataframe. Do not supply a numerical vector.
ones	A boolean variable specifying whether to include the ones in the design matrix or not. The default value is TRUE.

Details

This function implements the R's "model.matrix" function and is used only when the x is a factor/charactervector or Dataframe.

Value

Returns the same matrix with model.matrix.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

`model.matrix`

Examples

```
a <- design_matrix( iris[, 5] )
b <- model.matrix( ~ iris[,5] )  ## R's built-in function
all.equal(as.vector(a),as.vector(b)) ## true

a<-b<-NULL
```

Diagonal Matrix *Diagonal Matrix*

Description

Fill the diagonal of a matrix or create a diagonal and initialize it with a specific value.

Usage

```
Diag.fill(x,v=0)
Diag.matrix(len,v=0)
```

Arguments

x	A matrix with data.
len	Number of columns or rows.
v	Value or vector to initialize the diagonal of a matrix.By default "v=0".

Value

Diag.fill returns a diagonal matrix where all the elements in the diagonal are equal to "v".

Diag.matrix returns a diagonal matrix where has dimension "len,len" and all the elements in the diagonal are equal to "v". It is fast for huge matrices with dimensions more than [row,col] = [500,500]

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, colFalse, nth, rowrange, rowMedians, rowVars, colSort, rowSort, colTrue

Examples

```
x <- matrix(rbinom(100*100,1,0.5),100,100)

f <- Diag.fill(x,1)
f <- Diag.fill(x,1:100) ##equals to diag(x)<-1:100
f <- Diag.matrix(100,1) ##equals to diag(1,100,100)
f <- Diag.matrix(100,1:100) ##equals to diag(1:100,100,100)

f<-x<-NULL
```

Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix.

Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix

---

Description

Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix..

Usage

```
dista(xnew, x, type = "euclidean", k = 0, index = FALSE,
 trans = TRUE, square = FALSE, p = 0, result = "matrix", parallel = FALSE)
total.dista(xnew, x, type = "euclidean", k = 0,
 square = FALSE, p = 0, parallel = FALSE)
```

Arguments

xnew	A matrix with some data or a vector.
x	A matrix with the data, where rows denotes observations (vectors) and the columns contain the variables.
type	This can be either "euclidean" or "manhattan".
k	Should the k smaller distances or their indices be returned? If k > 0 this will happen.
index	In case k is greater than 0, you have the option to get the indices of the k smallest distances.

`trans`	Do you want the returned matrix to be transposed? TRUE or FALSE.
`square`	If you choose "euclidean" or "hellinger" as the method, then you can have the option to return the squared Euclidean distances by setting this argument to TRUE.
`p`	This is for the the Minkowski, the power of the metric.
`parallel`	For methods **kullback_leibler**, **jensen_shannon** and **itakura_saito**, you can run the algorithm in parallel.
`result`	One of the: • "matrix" : Return the result as matrix • "vector" : Return the result as vector • "sum" : Return the sum of the result

Details

The target of this function is to calculate the distances between xnew and x without having to calculate the whole distance matrix of xnew and x. The latter does extra calculations, which can be avoided.

- euclidean : $\sum \sqrt{(\sum |P_i - Q_i|^2)}$
- manhattan : $\sum \sum |P_i - Q_i|$
- minimum : $\sum \min |P_i - Q_i|$
- maximum : $\sum \max |P_i - Q_i|$
- minkowski : $\sum (\sum |P_i - Q_i|^p)^{\frac{1}{p}}$
- bhattacharyya : $\sum -ln \sum \sqrt{(P_i * Q_i)}$
- hellinger : $\sum 2 * \sqrt{(1 - \sum \sqrt{(P_i * Q_i)})}$
- kullback_leibler : $\sum \sum P_i * log(\frac{P_i}{Q_i})$
- jensen_shannon : $\sum 0.5 * (\sum P_i * log(2 * \frac{P_i}{Q_i} + Q_i) + \sum Q_i * log(2 * \frac{Q_i}{P_i} + Q_i))$
- canberra : $\sum \sum \frac{|P_i - Q_i|}{P_i + Q_i}$
- chi_square X^2 : $\sum \sum (\frac{(P_i - Q_i)^2}{P_i + Q_i})$
- soergel : $\sum \frac{\sum |P_i - Q_i|}{\sum \max(P_i, Q_i)}$
- sorensen : $\sum \frac{\sum |P_i - Q_i|}{\sum (P_i + Q_i)}$
- cosine : $\sum \frac{\sum (P_i * Q_i)}{\sqrt{(\sum P_i^2)} * \sqrt{(\sum Q_i^2)}}$
- wave_hedges : $\sum \frac{\sum |P_i - Q_i|}{\max(P_i, Q_i)}$
- motyka : $\sum \sum \frac{\min(P_i, Q_i)}{(P_i + Q_i)}$
- harmonic_mean : $\sum 2 * \frac{\sum P_i * Q_i}{P_i + Q_i}$
- jeffries_matusita : $\sum \sqrt{(2 - 2 * \sum \sqrt{(P_i * Q_i)})}$
- gower : $\sum \frac{1}{d} * \sum |P_i - Q_i|$
- kulczynski : $\sum \frac{\sum |P_i - Q_i|}{\sum \min(P_i, Q_i)}$
- itakura_saito : $\sum \frac{P_i}{Q_i} - log(\frac{P_i}{Q_i}) - 1$

Value

A matrix with the distances of each xnew from each vector of x. The number of rows of the xnew and and the number of columns of xnew are the dimensions of this matrix.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

mahala, Dist, total.dist, total.dista

Examples

```
xnew <- as.matrix( iris[1:10, 1:4] )
x <- as.matrix( iris[-c(1:10), 1:4] )
a <- dista(xnew, x)
b <- as.matrix( dist( rbind(xnew, x) ) )
b <- b[ 1:10, -c(1:10) ]
sum( abs(a - b) )

## see the time
x <- matrix( rnorm(1000 * 4), ncol = 4 )
dista(xnew, x)
as.matrix( dist( rbind(xnew, x) ) )

x<-b<-a<-xnew<-NULL
```

Distance matrix - Sum of all pairwise distances in a distance matrix

Distance matrix - Sum of all pairwise distances in a distance matrix

---

Description

Distance matrix - Sum of all pairwise distances in a distance matrix.

Usage

```
Dist(x,method = "euclidean", square = FALSE,p=0,
    result = "matrix" ,vector = FALSE, parallel = FALSE)
total.dist(x, method = "euclidean", square = FALSE, p = 0)
vecdist(x)
```

Arguments

`x`	A matrix with data. The distances will be calculated between pairs of rows. In the case of **vecdist** this is a vector. For the **haversine** distance it must be a matrix with two columns, the first column is the latitude and the second the longitude (in radians).
`method`	See details for the available methods.
`square`	If you choose "euclidean" or "hellinger" as the method, then you can have the option to return the squared Euclidean distances by setting this argument to TRUE.
`p`	This is for the Minkowski method, the power of the metric.
`vector`	For return a vector instead a matrix.
`result`	One of the: • "matrix" : Return the result as matrix. • "vector" : Return the result as vector. • "sum" : Return the sum of the result.
`parallel`	For methods **euclidean**, **canberra** and **minkowski**, you can run the algorithm in parallel.

Details

The distance matrix is compute with an extra argument for the Euclidean distances. The "kullback_leibler" refers to the symmetric Kullback-Leibler divergence.

- euclidean : $\sum \sqrt{(\sum |P_i - Q_i|^2)}$
- manhattan : $\sum |P_i - Q_i|$
- minimum : $\sum \min |P_i - Q_i|$
- maximum : $\sum \max |P_i - Q_i|$
- minkowski : $(\sum |P_i - Q_i|^p)^{\frac{1}{p}}$
- bhattacharyya : $-ln(\sum \sqrt{(P_i * Q_i)})$
- hellinger : $2 * \sqrt{(1 - \sum \sqrt{(P_i * Q_i)})}$
- kullback_leibler : $\sum P_i * log(\frac{P_i}{Q_i})$
- jensen_shannon : $0.5 * (\sum P_i * log(2 * \frac{P_i}{Q_i + Q_i}) + \sum Q_i * log(2 * \frac{Q_i}{P_i + Q_i}))$
- canberra : $\sum \frac{|P_i - Q_i|}{P_i + Q_i}$
- chi_square X^2 : $\sum (\frac{(P_i - Q_i)^2}{P_i + Q_i})$
- soergel : $\frac{\sum |P_i - Q_i|}{\sum \max(P_i, Q_i)}$
- sorensen : $\frac{\sum |P_i - Q_i|}{\sum (P_i + Q_i)}$
- cosine : $\sum \frac{\sum (P_i * Q_i)}{\sqrt{(\sum P_i^2)} * \sqrt{(\sum Q_i^2)}}$
- wave_hedges : $\sum \frac{\sum |P_i - Q_i|}{\max(P_i, Q_i)}$
- motyka : $\sum \frac{\min(P_i, Q_i)}{(P_i + Q_i)}$

- harmonic_mean : $2 * \frac{\sum P_i * Q_i}{P_i + Q_i}$
- jeffries_matusita : $\sum \sqrt{(2 - 2 * \sum \sqrt{(P_i * Q_i)})}$
- gower : $\sum \frac{1}{d} * \sum |P_i - Q_i|$
- kulczynski : $\sum \frac{\sum |P_i - Q_i|}{\sum \min(P_i, Q_i)}$
- itakura_saito : $\sum \frac{P_i}{Q_i} - log(\frac{P_i}{Q_i}) - 1$
- haversine : $2 * R * \arcsin(\sqrt{(} \sin((lat_2 - lat_1)/2)^2 + \cos(lat_1) * \cos(lat_2) * \sin((lon_2 - lon_1)/2)^2))$

Value

A square matrix with the pairwise distances.

Author(s)

Manos Papadakis.

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Mardia K. V., Kent J. T. and Bibby J. M. (1979). Multivariate Analysis. Academic Press.

See Also

dista, colMedians

Examples

```
x <- matrix(rnorm(50 * 10), ncol = 10)
a1 <- Dist(x)
a2 <- as.matrix( dist(x) )

x<-a1<-a2<-NULL
```

Distance variance, covariance and correlation

Distance variance, covariance and correlation

Description

Distance variance, covariance and correlation.

Usage

```
dvar(x, bc = FALSE)
dcov(x, y, bc = FALSE)
dcor(x, y, bc = FALSE)
bcdcor(x, y)
```

Arguments

x	A numerical matrix or a vector.
y	A numerical matrix or a vector.
bc	If you want the bias-corrected distance correlation set this equal to TRUE.

Details

The distance variance of a matrix/vector, the distance covariance or distance correlation of two matrices is calculated. For the dcov() and dcor(), if x and y are matrices, they must have the same dinmensions. We have optimized the code, using the formulas provided in Szekely and Rizzo (2023), but only for the case that both matrices are of the same dimensionality.

Value

The distance covariance or the distance variance.

For the bias corrected distance correlation its value only.

For the distance correlation a list including:

dcov	The distance covariance.
dvarX	The distance variance of x.
dvarY	The distance variance of Y.
dcor	The distance correlation.

Author(s)

Michail Tsagris and Manos Papadakis.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Szekely G.J., Rizzo M.L. and Bakirov N.K.(2007). Measuring and Testing Independence by Correlation of Distances. Annals of Statistics, 35(6):2769–2794.

Szekely G. J. and Rizzo M. L. (2023). The Energy of Data and Distance Correlation. Chapman and Hall/CRC.

Tsagris M. and Papadakis M. (2025). Fast and light-weight energy statistics using the R package Rfast. https://arxiv.org/abs/2501.02849

See Also

pdcor, dcor.ttest, edist

Examples

```
x <- as.matrix(iris[1:50, 1:4])
y <- as.matrix(iris[51:100, 1:4])
res <- dvar(x[, 1])
#dcor(x, y)
```

Eigenvalues and eigenvectors in high dimensional principal component analysis

Eigenvalues in high dimensional principal component analysis

Description

Eigenvalues in high dimensional (n«p) principal component analysis.

Usage

```
hd.eigen(x, center = TRUE, scale = FALSE, k = NULL, vectors = FALSE, large = FALSE)
```

Arguments

x	A numerical $n \times p$ matrix with data where the rows are the observations and the columns are the variables.
center	Do you want your data centered? TRUE or FALSE.
scale	Do you want each of your variables scaled, i.e. to have unit variance? TRUE or FALSE.
k	If you want a specific number of eigenvalues and eigenvectors set it here, otherwise all eigenvalues (and eigenvectors if requested) will be returned.
vectors	Do you want the eigenvectors be returned? By dafault this is FALSE.
large	If you have large matrices, with thousands of rows and or many tens or hundreds of columns set this equal to TRUE in order to use Rfast's Crossprod or Tcrossprod functions. These functions are twice or up to 3 times faster than the correpsonding built-in functions.

Details

When $n << p$, at most the first n eigenvalues are non zero. Hence, there is no need to calculate the other p-n zero eigenvalues. When center is TRUE, the eigenvalues of the covariance matrix are calculated. When both the center and scale is TRUE the eigenvalues of the correlation matrix are calculated. One or more eigenvectors (towards the end) will be 0. In general the signs might be the opposite than R's, but this makes no difference. We use the Crossprod instead of the relevant built-in function. The higher the dimensions of the matrix are the faster this function becomes.

Value

A list including:

values	A vector with the n (or first k) eigenvalues. The divisor in the crossproduc matrix is n-1 and not n.
vectors	A matrix of $p \times n$ or $p \times k$ eigenvectors.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

See Also

rmdp

Examples

```
x <- matrnorm(20, 50)
#a <- hd.eigen(x, FALSE, FALSE)
#b <- prcomp(x, center = FALSE, scale = FALSE)
#a
#b$sdev^2
#x <- NULL
```

Empirical and exponential empirical likelihood tests for one sample

Empirical and exponential empirical likelihood tests for one sample

---

Description

Empirical and exponential empirical likelihood tests for one sample.

Usage

```
eel.test1(x, mu, tol = 1e-09, logged = FALSE)
el.test1(x, mu, tol = 1e-07, logged = FALSE)
```

Arguments

x	A numerical vector.
mu	The hypothesised mean value.
tol	The tolerance value to stop the iterations of the Newton-Raphson.
logged	Should the logarithm of the p-value be returned? TRUE or FALSE.

Details

Exponential empirical likelihood is a non parametric method. In this case we use it as the non parametric alternative to the t-test. Newton-Raphson is used to maximise the log-likelihood ratio test statistic. In the case of no solution, NULL is returned. Despite the function having beeen written in R, it is pretty fast. As for the empirical likelihood ratio test, there is a condition for the range of possible values of mu. If mu is outside this range it is rejected immediately.

Value

iters	The number of iterations required by the Newton-Raphson algorithm. If no covnergence occured this is NULL. This is not returned for the empircial likelihood ratio test.
info	A vector with three elements, the value of the λ, the likelihood ratio test statistic and the relevant p-value. If no convergence occured, the value of the λ before is becomes NA, the value of test statistic is 10^5 and the p-value is 0. No convergence can be interpreted as rejection of the hypothesis test.
p	The estimated probabilities, one for each observation. If no covnergence occured this is NULL.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Owen A. B. (2001). Empirical likelihood. Chapman and Hall/CRC Press.

See Also

ftest, ttest1

Examples

```
x <- rnorm(500)
a1 <- eel.test1(x, 0)
a2 <- el.test1(x, 0)
```

`Empirical and exponential empirical likelihood tests for two samples`

Empirical and exponential empirical likelihood tests for two samples

---

Description

Empirical and exponential empirical likelihood tests for two samples.

Usage

```
eel.test2(x, y, tol = 1e-09, logged = FALSE)
el.test2(x, y, tol = 1e-07, logged = FALSE)
```

Arguments

x	A numerical vector.
y	Another numerical vector.
tol	The tolerance value to stop the iterations of the Newton-Raphson.
logged	Should the logarithm of the p-value be returned? TRUE or FALSE.

Details

Empirical and exponential empirical likelihood are two non parametric hypothesis testing methods. We can use them as non parametric alternatives to the t-test. Newton-Raphson is used to maximise the log-likelihood ratio test statistic. In the case of no solution, NULL is returned.

Value

iters	The number of iterations required by the Newton-Raphson algorithm. If no covnergence occured this is NULL.
info	A vector with three elements, the value of the λ, the likelihood ratio test statistic and the relevant p-value. If no convergence occured, the value of the λ before is becomes NA, the value of test statistic is 10^5 and the p-value is 0. No convergence can be interpreted as rejection of the hypothesis test.
p1	The estimated probabilities, one for each observation for the first sample. If no covnergence occured this is NULL.
p2	The estimated probabilities, one for each observation for the second sample. If no covnergence occured this is NULL.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Owen A. B. (2001). Empirical likelihood. Chapman and Hall/CRC Press.

See Also

ftests, ttests, ttest

Examples

```
x <- rnorm(200)
y <- rnorm(300)
eel.test2(x, y)
el.test2(x, y)
```

`Energy distance between matrices`
Energy distance between matrices

Description

Energy distance between matrices.

Usage

```
edist(x, y = NULL)
```

Arguments

x	A matrix with numbers or a list with matrices.
y	A second matrix with data. The number of columns of x and y must match. The number of rows can be different.

Details

This calculates the energy distance between two matrices. It will work even for tens of thousands of rows, it will just take some time. See the references for more information. If you have many matrices and want to calculate the distance matrix, then put them in a list and use the function.

Value

If "x" is matrix, a numerical value, the energy distance. If "x" is list, a matrix with all pairwsie distances of the matrices.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Szekely G. J. and Rizzo M. L. (2004) Testing for Equal Distributions in High Dimension, InterStat, November (5).

Szekely G. J. (2000) Technical Report 03-05, E-statistics: Energy of Statistical Samples, Department of Mathematics and Statistics, Bowling Green State University.

Sejdinovic D., Sriperumbudur B., Gretton A. and Fukumizu, K. (2013). Equivalence of distance-based and RKHS-based statistics in hypothesis testing. The Annals of Statistics, 41(5): 2263–2291.

Szekely G. J. and Rizzo M. L. (2023). The Energy of Data and Distance Correlation. Chapman and Hall/CRC.

Tsagris M. and Papadakis M. (2025). Fast and light-weight energy statistics using the R package Rfast. https://arxiv.org/abs/2501.02849

See Also

dcov, Dist, dista

Examples

```
x <- as.matrix( iris[1:50, 1:4] )
y <- as.matrix( iris[51:100, 1:4] )
res<-edist(x, y)
z <- as.matrix(iris[101:150, 1:4])
a <- list()
a[[ 1 ]] <- x
a[[ 2 ]] <- y
a[[ 3 ]] <- z
res<-edist(a)

x<-y<-z<-a<-NULL
```

`Estimation of an AR(1) model`

Estimation of an AR(1) model

Description

Estimation of an AR(1) model.

Usage

```
ar1(y, method = "cmle")
colar1(y, method = "cmle")
```

Arguments

`y`	For the case of **ar1** this is a vector of time series. For the case of **colar1** this is a matrix where weach column represents a time series.
`method`	This can be either "cmle" for conditional maximum likelihood or "yw" for the Yule-Walker equations.

Details

Instead of the classical MLE for the AR(1) model which requires numerical optimsation (Newton-Raphson for example) we estimate the parameters of the AR(1) model using conditional maximum likelihood. This procedure is described in Chapter 17 in Lee (2006). In some, it assumes that the first observation is deterministic and hence conditioning on that observation, there is a closed form solution for the parameters. The second alternative is to use the method of moments and hence the Yule-Walker equations.

Value

`param` For the case of **ar1** this is a vector with three elements, the constant term, the ϕ term (lag coefficient) and the variance. For the case of **colar1** this is a matrix with three columns, eahc of which carries the same aforementioned elements.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

http://econ.nsysu.edu.tw/ezfiles/124/1124/img/Chapter17_MaximumLikelihoodEstimation.pdf

See Also

`rm.lines`, `varcomps.mle`, `rm.anovas`

Examples

```
y <- as.vector(lh)
ar1(y)
ar(y, FALSE, 1, "ols")

ar1(y, method = "yw")
ar(y, FALSE, 1, "yw")

a1 <- colar1(cbind(y, y) )
b1 <- colar1(cbind(y, y), method = "yw")
```

`Estimation of the Box-Cox transformation`

Estimation of the Box-Cox transformation

Description

Estimation of the Box-Cox transformation.

Usage

```
bc(x, low = -1, up = 1)
```

Arguments

`x`	A numerical vector with strictly positive values.
`low`	The lowest value to search for the best λ parameter.
`up`	The highest value to search for the best λ parameter.

Details

The functions estimates the best λ in the Box-Cox power transformation.

Value

The optimal value of λ.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Box George E. P. and Cox D. R. (1964). An analysis of transformations. Journal of the Royal Statistical Society, Series B, 26 (2):211-252.

See Also

correls, auc

Examples

```
x <- exp(rnorm(1000))
res<-bc(x)
```

Exact t-test for 2 independent samples

Exact t-test for 2 independent samples

Description

Exact t-test for 2 independent samples.

Usage

```
exact.ttest2(x, y)
```

Arguments

x	A numerical vector with the data.
y	A numerical vector with the data.

Details

This function performs an exact t-test. With few observations, permutation or bootstrap calculation of the p-value is advisable. However, with even fewer observations, one can perform all possible permutations and calculate the exact p-value. This is what this function does. BUT, pay attention, as this works with few samples. If for example each sample contains 15 numbers, you will need a lot of memory (more than 17 GB) for this function to work. the reason is that we create the matrix with all possible permutations first and then perform the two-sample t-test.

Value

A vector with the number of permutations, test statistic and the permutation based p-value.

Author(s)

Michail Tsagris and Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

B.L. Welch (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

See Also

boot.ttest2, ttest2, ftest

Examples

```
x <- rnorm(7)
y <- rnorm(7)
res<-exact.ttest2(x, y)
```

`Exponential empirical likelihood for a one sample mean vector hypothesis testing`

Exponential empirical likelihood for a one sample mean vector hypothesis testing

---

Description

Exponential empirical likelihood for a one sample mean vector hypothesis testing.

Usage

```
mv.eeltest1(x, mu, tol = 1e-06)
```

Arguments

`x`	A matrix containing Euclidean data.
`mu`	The hypothesized mean vector.
`tol`	The tolerance value used to stop the Newton-Raphson algorithm.

Details

Multivariate hypothesis test for a one sample mean vector. This is a non parametric test and it works for univariate and multivariate data. The p-value is currently computed only asymptotically (no bootstrap calibration at the moment).

Value

A list including:

`p`	The estimated probabiities.
`lambda`	The value of the Lagrangian parameter λ.
`iters`	The number of iterations required by the newton-Raphson algorithm.
`info`	The value of the log-likelihood ratio test statistic along with its corresponding p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Jing Bing-Yi and Andrew TA Wood (1996). Exponential empirical likelihood is not Bartlett correctable. Annals of Statistics 24(1): 365-369.

Owen A. B. (2001). Empirical likelihood. Chapman and Hall/CRC Press.

See Also

`james`, `mv.eeltest2`

Examples

```
x <- Rfast::rmvnorm(100, numeric(10), diag( rexp(10, 0.5) ) )
res<-mv.eeltest1(x, numeric(10) )
```

Exponential empirical likelihood hypothesis testing for two mean vectors

Exponential empirical likelihood hypothesis testing for two mean vectors

Description

Exponential empirical likelihood hypothesis testing for two mean vectors.

Usage

```
mv.eeltest2(y1, y2, tol = 1e-07, R = 0)
```

Arguments

y1	A matrix containing the Euclidean data of the first group.
y2	A matrix containing the Euclidean data of the second group.
tol	The tolerance level used to terminate the Newton-Raphson algorithm.
R	If R is 0, the classical chi-sqaure distribution is used, if R = 1, the corrected chi-square distribution (James, 1954) is used and if R = 2, the modified F distribution (Krishnamoorthy and Yanping, 2006) is used.

Details

Exponential empirical likelihood is a non parametric hypothesis testing procedure for one sample. The generalisation to two (or more samples) is via searching for the mean vector that minimises the sum of the two test statistics.

Value

A list including:

test	The empirical likelihood test statistic value.
modif.test	The modified test statistic, either via the chi-square or the F distribution.
pvalue	The p-value.
iters	The number of iterations required by the newton-Raphson algorithm.
mu	The estimated common mean vector.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Jing Bing-Yi and Andrew TA Wood (1996). Exponential empirical likelihood is not Bartlett correctable. Annals of Statistics 24(1): 365-369.

G.S. James (1954). Tests of Linear Hypothese in Univariate and Multivariate Analysis when the Ratios of the Population Variances are Unknown. Biometrika, 41(1/2): 19-43.

Krishnamoorthy K. and Yanping Xia (2006). On Selecting Tests for Equality of Two Normal Mean Vectors. Multivariate Behavioral Research 41(4): 533-548.

Owen A. B. (2001). Empirical likelihood. Chapman and Hall/CRC Press.

Amaral G.J.A., Dryden I.L. and Wood A.T.A. (2007). Pivotal bootstrap methods for k-sample problems in directional statistics and shape analysis. Journal of the American Statistical Association 102(478): 695-707.

Preston S.P. and Wood A.T.A. (2010). Two-Sample Bootstrap Hypothesis Tests for Three-Dimensional Labelled Landmark Data. Scandinavian Journal of Statistics 37(4): 568-587.

Tsagris M., Preston S. and Wood A.T.A. (2017). Nonparametric hypothesis testing for equality of means on the simplex. Journal of Statistical Computation and Simulation, 87(2): 406-422.

See Also

`james`, `mv.eeltest1`

Examples

```
res<-mv.eeltest2( as.matrix(iris[1:25, 1:4]), as.matrix(iris[26:50, 1:4]), R = 0 )
res<-mv.eeltest2( as.matrix(iris[1:25, 1:4]), as.matrix(iris[26:50, 1:4]), R = 1 )
```

`Fast and general - untyped represantation of a factor variable`

Fast and general represantation of a factor variable

Description

Fast and general represantation of a factor variable.

Usage

```
ufactor(x)
## S3 method for class 'ufactor'
x[i]
## S3 method for class 'ufactor'
print(x,...)
```

Arguments

`x`	A vector with data.
`i`	An integer value/vector which is the index/indices to the element you want to access.
`...`	Anything the user want.

Details

This is a general implementation of factor structure. For access the fields of a "ufactor" use the "$" operator.

Value

An object of class "ufactor". This object holds 2 fields:

levels: the levels of the variable in his initial type values: the values of the variable in his initial type

Author(s)

Manos Papadakis

R implementation and documentation: and Manos Papadakis <papadakm95@gmail.com>.

See Also

colVars, factor

Examples

```
x <- rnorm(10)
R.factor<- as.factor(x)
Rfast.factor <- ufactor(x)

identical(levels(R.factor),Rfast.factor$levels) # TRUE
identical(as.numeric(R.factor),Rfast.factor$values) # TRUE
x<-R.factor<-Rfast.factor<-NULL
```

FBED variable selection method using the correlation

FBED variable selection method using the correlation

Description

FBED variable selection method using the correlation.

Usage

```
cor.fbed(y, x, ystand = TRUE, xstand = TRUE, alpha = 0.05, K = 0)
```

Arguments

y	The response variable, a numeric vector.
x	A matrix with the data, where the rows denote the samples and the columns are the variables.
ystand	If this is TRUE the response variable is centered. The mean is subtracted from every value.

`xstand`	If this is TRUE the independent variables are standardised.
`alpha`	The significance level, set to 0.05 by default.
`K`	The number of times to repeat the process. The default value is 0.

Details

FBED stands for Forward Backward with Earcly Dropping. It is a variation of the classical forward selection, where at each step, only the statistically significant variables carry on. The rest are dropped. The process stops when no other variables can be selected. If K = 1, the process is repeated testing sequentially again all those that have not been selected. If K > 1, then this is repeated.

In the end, the backward selection is performed to remove any falsely included variables. This backward phase has not been implemented yet.

Value

A list including:

`runtime`	The duration of the process.
`res`	A matrix with the index of the selected variable, their test statistic value and the associated p-value.
`info`	A matrix with two columns. The cumulative number of variables selected and the number of tests for each value of K.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Borboudakis G. and Tsamardinos I. (2019). Forward-backward selection with early dropping. Journal of Machine Learning Research, 20(8): 1-39.

See Also

`cor.fsreg`, `ompr`, `correls`, `fs.reg`

Examples

```
x <- matrnorm(100, 100)
y <- rnorm(100)
a <- cor.fbed(y, x)
a
x <- NULL
```

Find element *Find element*

Description

Search a value in an unordered vector.

Usage

```
is_element(x, key)
```

Arguments

x	A vector or matrix with the data.
key	A value to check if exists in the vector x.

Details

Find if the key exists in the vector and return returns TRUE/FALSE if the value is been found. If the vector is unordered it is fast but if the vector is ordered then use binary_search. The functions is written in C++ in order to be as fast as possible.

Value

TRUE/FALSE if the value is been found.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

binary_search (buit-in R function)

Examples

```
x <- rnorm(500)
key <- x[50]
b <- is_element(x, key)
```

`Find the given value in a hash table`
Find the given value in a hash table

Description

Find the given value in a hash table or list.

Usage

```
hash.find(x,key)
```

Arguments

`x`	A hash table or list.
`key`	The key for searching the table.

Details

This function search the given key.

Value

If the given key exists return its value else returns 0.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

`hash.list`

Examples

```
x <- hash.list(letters,c(1:26))
value <- hash.find(x,"a")
x[["a"]]==value
```

`Fitted probabilities of the Terry-Bradley model`
Fitted probabilities of the Terry-Bradley model

Description

Fitted probabilities of the Terry-Bradley model.

Usage

```
btmprobs(x, tol = 1e-09)
```

Arguments

`x`	A numerical square, usually not symmetric, matrix with discrete valued data. Each entry is a frequency, to give an example, the number of wins. x[i, j] is the number of wins of home team i against guest team j. x[j, i] is the number of wins of home team j against guest team i.
`tol`	The tolerance level to terminate the iterative algorithm.

Details

It fits a Bradley-Terry model to the given matrix and returns the fitted probabilities only.

Value

A list including:

`iters`	The numbetr of iterations required.
`probs`	A vector with probabilities which sum to 1. This is the probability of win for each item (or team in our hypothetical example).

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Bradley R.A. and Terry M.E. (1952). Rank Analysis of Incomplete Block Designs: I. The Method of Paired Comparisons. Biometrika, 39(3/4):324-345.

Huang Tzu-Kuo, Ruby C. Weng and Chih-Jen Lin (2006). Generalized Bradley-Terry models and multi-class probability estimates. Journal of Machine Learning Research, 7:85-115.

Agresti A. (2002). Categorical Data Analysis (2nd ed). New York: Wiley.

See Also

g2tests, poisson.anova, anova, poisson_only, poisson.mle

Examples

```
x <- matrix( rpois(10 * 10, 10), ncol = 10) ## not the best example though
res<-btmprobs(x)
```

`Fitting a Dirichlet distribution via Newton-Rapshon`

Fitting a Dirichlet distribution via Newton-Rapshon

Description

Fitting a Dirichlet distribution via Newton-Rapshon.

Usage

```
diri.nr2(x, type = 1, tol = 1e-07)
```

Arguments

`x`	A matrix containing the compositional data. Zeros are not allowed.
`type`	Type 1 uses a vectorised version of the Newton-Raphson (Minka, 2012). In high dimensions this is to be preferred. If the data are too concentrated, regardless of the dimensions, this is also to be preferrred. Type 2 uses the regular Newton-Raphson, with matrix multiplications. In small dimensions this can be considerably faster.
`tol`	The tolerance level idicating no further increase in the log-likelihood.

Details

Maximum likelihood estimation of the parameters of a Dirichlet distribution is performed via Newton-Raphson. Initial values suggested by Minka (2012) are used.

Value

A list including:

`loglik`	The value of the log-likelihood.
`param`	The estimated parameters.

Author(s)

Michail Tsagris and Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

Minka Thomas (2012). Estimating a Dirichlet distribution. Technical report.

Ng Kai Wang, Guo-Liang Tian, and Man-Lai Tang (2011). Dirichlet and related distributions: Theory, methods and applications. John Wiley & Sons.

See Also

beta.mle

Examples

```
x <- matrix( rgamma(100 * 4, c(5, 6, 7, 8), 1), ncol = 4)
x <- x / rowsums(x)
res<-diri.nr2(x)
```

Floyd-Warshall algorithm

Floyd-Warshall algorithm for shortest paths in a directed graph

---

Description

Floyd-Warshall algorithm for shortest paths in a directed graph.

Usage

```
floyd(x)
```

Arguments

x	The adjacency matrix of a directed graph. A positive number (including) in x[i, j] indicates that there is an arrow from i to j and it also shows the cost of going from i to j. Hence, the algorithm will find not only the shortest path but also the with the smallest cost. A value of NA means that there is no path. Put positive number only, as negative will cause problems.

Details

The Floyd-Warshall algorithm is designed to find the shortest path (if it exists) between two nodes in a graph.

Value

A matrix, say z, with 0 and positive numbers. The elements denote the length of the shortest path between each pair of points. If z[i, j] is zero it means that there is no cost from i to j. If z[i, j] has a positive value it means that the length of going from i to j is equal to that value.

Author(s)

John Burkardt (C++ code)

Ported into R and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Floyd, Robert W. (1962). Algorithm 97: Shortest Path. Communications of the ACM. 5(6): 345.

Warshall, Stephen (1962). A theorem on Boolean matrices. Journal of the ACM. 9 (1): 11-12.

https://en.wikipedia.org/wiki/Floyd

See Also

`colSort`, `rowSort`

Examples

```
x <- matrix(NA, 10, 10)
x[sample(1:100, 10)] <- rpois(10, 3)
res<-floyd(x)
```

Forward selection with generalised linear regression models

Variable selection in generalised linear regression models with forward selection

---

Description

Variable selection in generalised linear regression models with forward selection

Usage

```
fs.reg(y, ds, sig = 0.05, tol = 2, type = "logistic")
```

Arguments

`y`	The dependent variable. This can either be a binary numeric (0, 1) or a vector with integers (numeric or integer class), count data. The first case is for the binary logistic regression and the second for the Poisson regression.
`ds`	The dataset; provide a matrix where columns denote the variables and the rows the observations. The variables must be continuous, no categorical variables are accepted.
`sig`	Significance level for assessing the p-values significance. Default value is 0.05.
`tol`	The difference bewtween two successive values of the stopping rule. By default this is is set to 2. If for example, the BIC difference between two succesive models is less than 2, the process stops and the last variable, even though significant does not enter the model.

type — If you have a binary dependent variable, put "logistic" or "quasibinomial". If you have percentages, values between 0 and 1, including 0 and or 1, use "quasibinomial" as well. If you have count data put "poisson".

Details

The classical forward regression is implemented. The difference is that we have an extra step of check. Even if a variable is significant, the BIC of the model (with that variable) is calculated. If the decrease from the previous BIC (of the model without this variable) is less thatn a prespecified by the user value (default is 2) the variable wil enter. This way, we guard somehow against over-fitting.

Value

A matrix with for columns, the selected variables, the logarithm of their p-value, their test statistic and the BIC of the model with these variables included. If no variable is selected, the matrix is empty.

Author(s)

Marios Dimitriadis

Documentation: Marios Dimitriadis <kmdimitriadis@gmail.com>.

See Also

cor.fsreg, logistic_only, poisson_only, glm_logistic, glm_poisson

Examples

```
set.seed(123)

#simulate a dataset with continuous data
x <- matrnorm(100, 50)
y <- rpois(100, 10)
a <- fs.reg(y, x, sig = 0.05, tol = 2, type = "poisson")
x <- NULL
```

G-square and Chi-square test of conditional indepdence

G-square test of conditional indepdence

Description

G-square test of conditional indepdence with and without permutations.

Usage

```
g2Test(data, x, y, cs, dc)
g2Test_perm(data, x, y, cs, dc, nperm)
chi2Test(data, x, y, cs, dc)
```

Arguments

`data`	A numerical matrix with the data. **The minimum must be 0, otherwise the function can crash or will produce wrong results**. The data must be consecutive numbers.
`x`	A number between 1 and the number of columns of data. This indicates which variable to take.
`y`	A number between 1 and the number of columns of data (other than x). This indicates the other variable whose independence with x is to be tested.
`cs`	A vector with the indices of the variables to condition upon. It must be non zero and between 1 and the number of variables. If you want unconditional independence test see `g2Test_univariate` and `g2Test_univariate_perm`. If there is an overlap between x, y and cs you will get 0 as the value of the test statistic.
`dc`	A numerical value equal to the number of variables (or columns of the data matrix) indicating the number of distinct, unique values (or levels) of each variable. Make sure you give the correct numbers here, otherwise the degrees of freedom will be wrong.
`nperm`	The number of permutations. The permutations test is slower than without permutations and should be used with small sample sizes or when the contigency tables have zeros. When there are few variables, R's "chisq.test" function is faster, but as the number of variables increase the time difference with R's procedure becomes larger and larger.

Details

The functions calculates the test statistic of the G^2 test of conditional independence between x and y conditional on a set of variable(s) cs.

Value

A list including:

`statistic`	The G^2 or chi^2 test statistic.
`df`	The degrees of freedom of the test statistic.
`x`	The row or variable of the data.
`y`	The column or variable of the data.

Author(s)

Giorgos Borboudakis. The permutation version used a C++ code by John Burkardt.

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Tsamardinos, I., & Borboudakis, G. (2010). Permutation testing improves Bayesian network learning. In Joint European Conference on Machine Learning and Knowledge Discovery in Databases (pp. 322-337). Springer Berlin Heidelberg

See Also

g2Test_univariate, g2Test_univariate_perm, correls, univglms

Examples

```
nvalues <- 3
nvars <- 10
nsamples <- 5000
data <- matrix( sample( 0:(nvalues - 1), nvars * nsamples, replace = TRUE ), nsamples, nvars )
dc <- rep(nvalues, nvars)

res<-g2Test( data, 1, 2, 3, c(3, 3, 3) )
res<-g2Test_perm( data, 1, 2, 3, c(3, 3, 3), 1000 )

dc<-data<-NULL
```

Gamma regression with a log-link

Gamma regression with a log-link

Description

Gamma regression with a log-link.

Usage

```
gammareg(y, x, tol = 1e-07, maxiters = 100)
gammacon(y, tol = 1e-08, maxiters =50)
```

Arguments

y	The dependent variable, a numerical variable with non negative numbers.
x	A matrix or data.frame with the indendent variables.
tol	The tolerance value to terminate the Newton-Raphson algorithm.
maxiters	The maximum number of iterations that can take place in the regression.

Details

The gamma.reg fits a Gamma regression with a log-link. The gamma.con fits a Gamma regression with a log link with the intercept only (glm(y ~ 1, Gamma(log))).

Value

A list including:

`deviance`	The deviance value.
`phi`	The dispersion parameter (ϕ) of the regression. This is necessary if you want to perform an F hypothesis test for the significance of one or more independent variables.
`be`	The regression coefficient(s).
`info`	The number of iterations, the deviance and the dispersion parameter.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

gammaregs, normlog.reg, invgauss.reg

Examples

```
y <- abs( rnorm(100) )
x <- matrix( rnorm(100 * 2), ncol = 2)
mod <- glm(y ~ x, family = Gamma(log) )
res<-summary(mod)

res<-gammareg(y, x)

mod <- glm(y ~ 1, family = Gamma(log) )
res<-summary(mod)
res<-gammacon(y)
```

Gaussian regression with a log-link

Gaussian regression with a log-link

Description

Gaussian regression with a log-link.

Usage

```
normlog.reg(y, x, tol = 1e-07, maxiters = 100)
```

Arguments

y	The dependent variable, a numerical variable with non negative numbers.
x	A matrix or data.frame with the indendent variables.
tol	The tolerance value to terminate the Newton-Raphson algorithm.
maxiters	The maximum number of iterations that can take place in the regression.

Details

A Gaussian regression with a log-link is fitted.

Value

A list including:

i	The number of iterations required by the Newton-Raphson
loglik	The log-likelihood value.
deviance	The deviance value.
be	The regression coefficients

Author(s)

Stefanos Fafalios

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com>

See Also

normlog.regs, score.glms, prop.regs, allbetas

Examples

```
y <- abs( rnorm(100) )
x <- matrix( rnorm(100 * 2), ncol = 2)
a <- normlog.reg(y, x)
b <- glm(y ~ x, family = gaussian(log) )
summary(b)
a
```

`Generates random values from a normal and puts them in a matrix`
Generates random values from a normal and puts them in a matrix

Description

Generates random values from a normal and puts them in a matrix.

Usage

```
matrnorm(n, p, seed = NULL)
```

Arguments

`n`	The sample size, the number of rows the matrix will have.
`p`	The dimensionality of the data, the nubmer of columns of the matrix.
`seed`	If you want the same to be generated again use a seed for the generator, an integer number.

Details

How many times did you have to simulated data from a (standard) normal distribution in order to test something? For example, in order to see the speed of `logistic_only`, one needs to generate a matrix with predictor variables. The same is true for other similar functions. In `sftests`, one would like to examine the typer I error of this test under the null hypothesis.

By using the Ziggurat method of generating standard normal variates, this function is really fast when you want to generate big matrices.

Value

An n x p matrix with data simulated from a standard normal distribution.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

See Also

`rvmf`, `Rnorm`, `rmvnorm`, `rvonmises`

Examples

```
x <- matrnorm(100, 100)
```

Get specific columns/rows fo a matrix
Get specific columns/rows fo a matrix

Description

Get specific columns/rows of a matrix.

Usage

```
columns(x,indices)
rows(x,indices)
```

Arguments

x	A matrix with data.
indices	An integer vector with the indices.

Value

A matrix with the specific columns/rows of argumment indices.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, rowFalse, nth, colrange, colMedians, colVars, colSort, rowSort, rowTrue

Examples

```
x <- matrix(runif(100*100),100,100)
indices = sample(1:100,50)
all.equal(x[,indices],columns(x,indices))
all.equal(x[indices,],rows(x,indices))

x<-indices<-NULL
```

`Hash - Pair function` *Hash - Pair function*

Description

Hash - Pair function.

Usage

```
hash.list(key,x)
```

Arguments

`key`	The keys of the given values.
`x`	The values.

Details

This function pairs each item of of key and value make a unique hash table.

Value

Returns the hash-list table.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

`hash.find`

Examples

```
x <- hash.list(letters,c(1:26))
x[["a"]]==1
```

Hash object *Hash object*

Description

Hash object.

Usage

```
Hash(keys=NULL,values=NULL)
Hash.key.multi(x,...,sep = " ")
## S3 replacement method for class 'Hash'
x[...,sep = " "] <- value
## S3 method for class 'Hash'
x[...,sep = " "]
## S3 method for class 'Hash'
print(x,...)
## S3 method for class 'Hash'
length(x)
```

Arguments

x	A Hash object, using Hash function.
values	A vector with the values you want to store.
value	The values you want to store.
keys	A vector with keys for each values.
sep	A character value using to separate the multiple keys for each value.
...	One or more values for access or find elements.

Details

If you want to delete a key just insert the global variable "Rfast:::delete".

Hash: Create Hash object where every key has a value. Specify the type from the beggining (for speed). Use the argument "type" with one of the values "new.env, logical, character, integer, numeric". Hash.key.multi: search if key exists. If the keys are multiple, then use the argument "substr" to search inside each multiple for the specific key.

Value

A Hash object.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

hash.list, hash.find

Examples

```
x <- Hash(rnorm(10),sample(1:10))

x[1,2,13] <- 0.1234 # insert value using multi key. the same as x["1 2 13"] <- 0.1234
x[1,2,3] <- 15 # insert value using multi key. the same as x["1 2 3"] <- 15

Hash.key.multi(x,"1")
x # print Hash object using S3 generic
#x[1,2,3] <- Rfast:::delete # delete multi key. the same as x["1 2 3"] <- NULL
length(x)
```

Hash object to a list object

Hash object to a list object

Description

Hash object to a list object.

Usage

```
hash2list(x, sorting = FALSE)
```

Arguments

x	A hash table with two parts, the keys (number(s) as string) and the key values (a single number).
sorting	This is if you you want the numbers in the keys sorted. The default value is FALSE.

Details

For every key, there is a key value. This function creates a list and puts every pair of keys and value in a component of a list.

Value

A list whose length is equal to the size of the hash table.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

hash.list, hash.find

Examples

```
x=list("1 2 4 3"=2.56,"2.34 1.05"=2)
res<-hash2list(x)
res<-hash2list(x,TRUE)
```

`High dimensional MCD based detection of outliers`

High dimensional MCD based detection of outliers

Description

High dimensional MCD based detection of outliers.

Usage

```
rmdp(y, alpha = 0.05, itertime = 100, parallel = FALSE)
```

Arguments

y	A matrix with numerical data with more columns (p) than rows (n), i.e. n<p.
alpha	The significance level, i.e. used to decide whether an observation is said to be considered a possible outlier. The default value is 0.05.
itertime	The number of iterations the algorithm will be ran. The higher the sample size, the larger this number must be. With 50 observations in R^1000 maybe this has to be 1000 in order to produce stable results.
parallel	A logical value for parallel version.

Details

High dimensional outliers (n«p) are detected using a properly constructed MCD. The variances of the variables are used and the determinant is simply their product.

Value

A list including: runtime = runtime, dis = dis, wei = wei

runtime	The duration of the process.
dis	The final estimated Mahalanobis type normalised distances.
wei	A bollean variable vector specifying whether an observation is "clean" (TRUE) or a possible outlier (FALSE).
cova	The estimated covatriance matrix.

Author(s)

Initial R code: Changliang Zou <nk.chlzou@gmail.com> R code modifications: Michail Tsagris <mtsagris@uoc.gr> C++ implementation: Manos Papadakis <papadakm95@gmail.com> Documentation: Michail Tsagris <mtsagris@uoc.gr> and Changliang Zhou <nk.chlzou@gmail.com>

References

Ro K., Zou C., Wang Z. and Yin G. (2015). Outlier detection for high-dimensional data. Biometrika, 102(3): 589–599.

Tsagris M., Papadakis M., Alenazi A. and Alzeley O. (2024). Computationally Efficient Outlier Detection for High-Dimensional Data Using the MDP Algorithm. Computation, 12(9): 185.

See Also

`colmeans`, `colVars`, `colMedians`

Examples

```
x <- matrix(rnorm(30 * 100), ncol = 100)
#a <- rmdp(x, itertime = 5)

x<-a<-NULL
```

Hypothesis test for the distance correlation

Hypothesis test for the distance correlation

Description

Hypothesis test for the distance correlation.

Usage

```
dcor.ttest(x, y, logged = FALSE)
```

Arguments

x	A numerical matrix.
y	A numerical matrix.
logged	Do you want the logarithm of the p-value to be returned? If yes, set this to TRUE.

Details

The bias corrected distance correlation is used. The hypothesis test is whether the two matrices are independent or not. Note, that this test is size correct as both the sample size and the dimensionality goes to infinity. It will not have the correct type I error for univariate data or for matrices with just a couple of variables.

Value

A vector with 4 elements, the bias corrected distance correlation, the degrees of freedom, the test statistic and its associated p-value.

Author(s)

Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

G.J. Szekely, M.L. Rizzo and N. K. Bakirov (2007). Measuring and Testing Independence by Correlation of Distances. Annals of Statistics, 35(6): 2769–2794.

Szekely G. J. and Rizzo M. L. (2023). The Energy of Data and Distance Correlation. Chapman and Hall/CRC.

See Also

dcov, edist

Examples

```
x <- as.matrix(iris[1:50, 1:4])
y <- as.matrix(iris[51:100, 1:4])
#res<-dcor.ttest(x, y)
```

Hypothesis test for two means of percentages

Hypothesis test for two means of percentages

Description

Hypothesis test for two means of percentages.

Usage

```
percent.ttest(x, y, logged = FALSE)
```

Arguments

x	A numerical vector with the percentages of the first sample. Any value between 0 and 1 (inclusive) is allowed.
y	A numerical vector with the percentages of the first sample. Any value between 0 and 1 (inclusive) is allowed.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

This is the prop.reg but with a single categorical predictor which has two levels only. It is like a t-test for the means of two samples haivng percentages.

Value

A vector with three elements, the phi parameter, the test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Papke L. E. & Wooldridge J. (1996). Econometric methods for fractional response variables with an application to 401(K) plan participation rates. Journal of Applied Econometrics, 11(6): 619-632.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

link{percent.ttests}, prop.reg, ttest2, ftest

Examples

```
x <- rbeta(100, 3, 1)
y <- rbeta(100, 7.5, 2.5)
res<-percent.ttest(x, y)
```

Hypothesis test for von Mises-Fisher distribution over Kent distribution

Hypothesis test for von Mises-Fisher distribution over Kent distribution

---

Description

The null hypothesis is whether a von Mises-Fisher distribution fits the data well, and the altenrative is that the Kent distribution is more suitable.

Usage

```
fish.kent(x, logged = FALSE)
```

Arguments

x	A numeric matrix containing the data as unit vectors in Euclidean coordinates.
logged	If you want the logarithm of the p-value ot be returned set this to TRUE.

Details

Essentially it is a test of rotational symmetry, whether Kent's ovalness parameter (beta) is equal to zero. This works for spherical data only.

Value

A vector with two elements, the value of the test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Rivest, L. P. (1986). Modified Kent's statistics for testing goodness of fit for the Fisher distribution in small concentrated samples. Statistics & probability letters, 4(1): 1-4.

See Also

vmf.mle, iag.mle

Examples

```
#x <- rvmf(100, rnorm(3), 15)
#res<-fish.kent(x)
x <- NULL
```

Hypothesis testing between two skewness or kurtosis coefficients

Hypothesis testing between two skewness or kurtosis coefficients

---

Description

Hypothesis testing between two skewness or kurtosis coefficients.

Usage

```
skew.test2(x, y)

kurt.test2(x, y)
```

Arguments

x	A numerical vector with data.
y	A numerical vector with data, not necessarily of the same size.

Details

The skewness of kurtosis coefficients between two samples are being compared.

Value

A vector with the test statistic and its associated p-value.

Author(s)

Klio Lakiotaki

R implementation and documentation: Klio Lakiotaki <kliolak@gmail.com>.

References

https://en.wikipedia.org/wiki/Skewness

https://en.wikipedia.org/wiki/Kurtosis

See Also

skew, colskewness, colmeans, colVars, colMedians

Examples

```
x <- rgamma(150,1, 4)
y <- rgamma(100, 1, 4)
res<-skew.test2(x, y)
res<-kurt.test2(x, y)
```

Index of the columns of a data.frame which are a specific type

Index of the columns of a data.frame which are a specific type

---

Description

Index of the columns of a data.frame which are a specific type.

Usage

```
which.is(x,method="factor")
```

Arguments

x	A data.frame where some columns are expected to be factor variables.
method	A character value about the type. One of, "numeric","factor","integer","logical".

Details

The function is written in C++ and this is why it is very fast.

Value

A vector with the column indices which are factor variables. If there are no factor variables it will return an empty vector.

Author(s)

Manos Papadakis <papadakm95@gmail.com>

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

nth, Match

Examples

```
res<-which.is(iris)
```

Insert/remove function names in/from the NAMESPACE file

Insert/remove function names in/from the NAMESPACE file

Description

Insert/remove function names in/from the NAMESPACE file.

Usage

```
AddToNamespace(path.namespace,path.rfolder,paths.full = FALSE)
RemoveFromNamespace(path.namespace,files.to.remove)
```

Arguments

path.namespace	An full path to the NAMESPACE file.
path.rfolder	An full path to the directory the new files to be added are stored.
files.to.remove	An character with the names of the functions to be removed from file NAMESPACE.
paths.full	Print or return the full paths.

Details

AddToNameSpace: Reads the files that are exported in NAMESPACE and the functions that are inside rfolder (where R files are) and insert every function that is not exported. For that you must add the attribute "#[export]" above every function you wish to export. Also you can use the attribute "#[export s3]" for exporting S3methods. Finally, if you don't want the program to read a file just add at the top of the file the attribute "#[dont read]".

RemoveFromNamespace: Remove every function, from argument "files.to.remove", from NAMESPACE.

Value

AddToNameSpace:

`without export` A character vector with the names of the R functions that don't have te "#[export]" attribute.

`hidden functions`
A character vector with the names of the R functions that are hidden.

RemoveFromNamespace: Return the files that could not be removed.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`colShuffle`, `colVars`, `colmeans`

Examples

```
## Not run:
 #for example: path.namespace="C:\some_file\NAMESPACE" where is NAMESPACE file
 #path.rfolder="C:\some_file\R\" where is R files are
 #system.time( a<-AddToNamespace(path.namespace,path.rfolder) )
 #if(length(a)==0){
 # print("all the files are inserted")
 #}else{
 # print("The new files that inserted are: \n")
 # a
 #}
 #system.time( a<-RemoveFromNamespace(path.namespace,c("a","b")) )
 #if(length(a)==0){
 # print("all the files are inserted")
 #}else{
 # print("The files thatcould not be deleted are: \n")
 # a
 #}

## End(Not run)
```

`Inverse Gaussian regression with a log-link`
Inverese Gaussian regression with a log-link

Description

Inverse Gaussian regression with a log-link.

Usage

```
invgauss.reg(y, x, tol = 1e-07, maxiters = 100)
```

Arguments

`y`	The dependent variable, a numerical variable with non negative numbers.
`x`	A matrix or data.frame with the indendent variables.
`tol`	The tolerance value to terminate the Newton-Raphson algorithm.
`maxiters`	The maximum number of iterations that can take place in the regression.

Details

An inverse Gaussian regression with a log-link is fitted.

Value

A list including:

`i`	The number of iterations required by the Newton-Raphson
`loglik`	The log-likelihood value.
`deviance`	The deviance value.
`phi`	The dispersion parameter (ϕ) of the regression. This is necessary if you want to perform an F hypothesis test for the significance of one or more independent variables.
`be`	The regression coefficients

Author(s)

Michail Tsagris

R implementation and documentation: Stefanos Fafalios <mtsagris@uoc.gr>

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

Zakariya Yahya Algamal and Intisar Ibrahim Allyas (2017). Prediction of blood lead level in maternal and fetal using generalized linear model. International Journal of Advanced Statistics and Probability, 5(2): 65-69.

See Also

invgauss.regs, normlog.reg, score.glms

Examples

```
y <- abs( rnorm(100) )
x <- matrix( rnorm(100 * 2), ncol = 2)
a <- invgauss.reg(y, x)
a
```

`Inverse of a symmetric positive definite matrix`
Inverse of a symmetric positive definite matrix

Description

Inverse of a symmetric positive definite matrix.

Usage

```
spdinv(A)
```

Arguments

A	A square positive definite matrix.

Details

After calculating the Cholesky decomposition of the matrix we use this upper triangular matrix to invert the original matrix.

Value

The inverse of the input matrix.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

http://econ.nsysu.edu.tw/ezfiles/124/1124/img/Chapter17_MaximumLikelihoodEstimation.pdf

See Also

cholesky, cova

Examples

```
s <- cova( as.matrix(iris[, 1:4]) )
res<-spdinv(s)
res<-solve(s)
```

Iterator *Iterator*

Description

A way to traverse a list, data.frame, matrix or vector.

Usage

```
iterator(x,method="ceil",type="vector",by=1)
## S3 method for class 'iterator'
print(x,...)
## S3 replacement method for class 'iterator'
Elem(x) <- value
Elem(x)
Elem(x) <- value
## S3 method for class 'iterator'
Elem(x)
## S3 method for class 'iterator'
x == y
## S3 method for class 'iterator'
x != y
```

Arguments

x	A variable with any type, or iterator object.
value	An value depending the method of the iterator.
y	An iterator.
method	Method of the iterator class. One of "ceil","col","row".
type	One of "vector","matrix","data.frame","list".
by	An integer value to iterate through element.
...	Anything the user want.

Details

iterator: is an object that helps a programmer to traverse the given object.

print.iterator: print an object of class iterator.

"Elem<-": access to element and change the value.

Elem: access to element.

Value

An object of class "iterator". This object holds 4 fields:

copy: deep copy of iterator. end: get iterator tha have access to points to the last element. equals: equality of iterators nextElem: move iterator to point to the next element using argument "by". prevElem: move iterator to point to the previous element using argument "by".

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colShuffle, colVars, colmeans

Examples

```
y<-rnorm(100)
x<-iterator(y,method="ceil",type="vector",by=1)

s<-0
while(x != x$end()){
 s <- s + Elem(x)
 x$nextElem()
}

all.equal(s,sum(y))
```

`James multivariate version of the t-test`

James multivariate version of the t-test

Description

James test for testing the equality of two population mean vectors without assuming equality of the covariance matrices.

Usage

```
james(y1, y2, a = 0.05, R = 1)
```

Arguments

y1	A matrix containing the Euclidean data of the first group.
y2	A matrix containing the Euclidean data of the second group.
a	The significance level, set to 0.05 by default.
R	If R is 1 the classical James test is returned. If R is 2 the MNV modficiation is implemented.

Details

Multivariate analysis of variance without assuming equality of the covariance matrices. The p-value can be calculated either asymptotically or via bootstrap. The James test (1954) or a modification proposed by Krishnamoorthy and Yanping (2006) is implemented. The James test uses a corected chi-square distribution, whereas the modified version uses an F distribution.

Value

A list including:

note	A message informing the user about the test used.
mesoi	The two mean vectors.
info	The test statistic, the p-value, the correction factor and the corrected critical value of the chi-square distribution if the James test has been used or, the test statistic, the p-value, the critical value and the degrees of freedom (numerator and denominator) of the F distribution if the modified James test has been used.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

G.S. James (1954). Tests of Linear Hypothese in Univariate and Multivariate Analysis when the Ratios of the Population Variances are Unknown. Biometrika, 41(1/2): 19-43

Krishnamoorthy K. and Yanping Xia. On Selecting Tests for Equality of Two Normal Mean Vectors (2006). Multivariate Behavioral Research 41(4): 533-548

See Also

mv.eeltest2

Examples

```
james( as.matrix(iris[1:25, 1:4]), as.matrix(iris[26:50, 1:4]), R = 1 )
james( as.matrix(iris[1:25, 1:4]), as.matrix(iris[26:50, 1:4]), R = 2 )
```

k nearest neighbours algorithm (k-NN)

k nearest neighbours algorithm (k-NN)

Description

k nearest neighbours algorithm (k-NN).

Usage

```
knn(xnew, y, x, k, dist.type = "euclidean", type = "C", method = "average",
freq.option = 0, mem.eff = FALSE)
```

Arguments

xnew	The new data, new predictor variable values. A matrix with numerical data.
y	A vector with the response variable, whose values for the new data we wish to predict. This can be numerical data, factor or discrete, 0, 1, ... The latter two cases are for classification.
x	The dataset. A matrix with numerical data.
k	The number of nearest neighbours to use. The number can either be a single value or a vector with multiple values.
dist.type	The type of distance to be used. Either \"euclidean\" or \"manhattan\".
type	If your response variable \"y\" is numerical data, then this should be \"R\" (regression). If \"y\" is in general categorical, factor or discrete set this argument to \"C\" (classification).
method	In case you have regression (type = \"R\") you want a way to summarise the prediction. If you want to take the average of the reponses of the k closest observations, type \"average\". For the median, type \"median\" and for the harmonic mean, type \"harmonic\".
freq.option	If classification (type = \"C\") and ties occur in the prediction, more than one class has the same number of k nearest neighbours, in which case there are two strategies available: Option 0 selects the first most frequent encountered. Option 1 randomly selects the most frequent value, in the case that there are duplicates.
mem.eff	Boolean value indicating a conservative or not use of memory. Lower usage of memory/Having this option on will lead to a slight decrease in execution speed and should ideally be on when the amount of memory in demand might be a concern.

Details

The concept behind k-NN is simple. Suppose we have a matrix with predictor variables and a vector with the response variable (numerical or categorical). When a new vector with observations (predictor variables) is available, its corresponding response value, numerical or category is to be predicted. Instead of using a model, parametric or not, one can use this ad hoc algorithm.

The k smallest distances between the new predictor variables and the existing ones are calculated. In the case of regression, the average, median or harmonic mean of the corresponding respone values of these closest predictor values are calculated. In the case of classification, i.e. categorical response value, a voting rule is applied. The most frequent group (response value) is where the new observation is to be allocated.

Value

A matrix whose number of columns is equal to the size of k. If in the input you provided there is just one value of k, then a matrix with one column is returned containing the predicted values. If more than one value was supplied, the matrix will contain the predicted values for every value of k.

Author(s)

Marios Dimitriadis

R implementation and documentation: Marios Dimitriadis <kmdimitriadis@gmail.com>

References

Cover TM and Hart PE (1967). Nearest neighbor pattern classification. IEEE Transactions on Information Theory. 13(1):21-27.

Friedman J., Hastie T. and Tibshirani R. (2017). The elements of statistical learning. New York: Springer.

http://web.stanford.edu/~hastie/ElemStatLearn/printings/ESLII_print12.pdf

http://statlink.tripod.com/id3.html

See Also

knn.cv, dirknn, logistic_only, fs.reg, cor.fsreg

Examples

```
# Simulate a dataset with continuous data
x <- as.matrix(iris[, 1:4])
y <- as.numeric(iris[, 5])
id <- sample(1:150, 120)
mod <- knn(x[-id, ], y[id], x[id, ], k = c(4, 5, 6), type = "C", mem.eff = FALSE)
mod # Predicted values of y for 3 values of k.
res<-table(mod[, 1], y[-id] )  # Confusion matrix for k = 4
res<-table(mod[, 2], y[-id] )  # Confusion matrix for k = 5
res<-table(mod[, 3], y[-id] )  # Confusion matrix for k = 6
```

k-NN algorithm using the arc cosinus distance

k-NN algorithm using the arc cosinus distance

Description

It classifies new observations to some known groups via the k-NN algorithm.

Usage

```
dirknn(xnew, x, y, k, type = "C", parallel = FALSE)
```

Arguments

xnew	The new data whose membership is to be predicted, a numeric matrix with unit vectors. In case you have one vector only make it a row vector (i.e. matrix with one row).
x	The data, a numeric matrix with unit vectors.
k	The number of nearest neighbours. It can also be a vector with many values.
y	A numerical vector representing the class or label of each vector of x. 1, 2, 3, and so on. It can also be a numerical vector with data in order to perform regression.
type	If your response variable y is numerical data, then this should be "R" (regression) or "WR" for distance weighted based nearest neighbours. If y is in general categorical set this argument to "C" (classification) or to "WC" for distance weighted based nearest neighbours.
parallel	Do you want th ecalculations to take place in parallel? The default value is FALSE.

Details

The standard algorithm is to keep the k nearest observations and see the groups of these observations. The new observation is allocated to the most frequent seen group. The non standard algorithm is to calculate the classical mean or the harmonic mean of the k nearest observations for each group. The new observation is allocated to the group with the smallest mean distance.

If you want regression, the predicted value is calculated as the average of the responses of the k nearest observations.

Value

A matrix with the predicted group(s). It has as many columns as the values of k.

Author(s)

Stefanos Fafalios

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com>

See Also

dirknn.cv, knn, vmf.mle, spml.mle

Examples

```
x <- as.matrix(iris[, 1:4])
x <- x/sqrt( rowSums(x^2) )
y<- as.numeric( iris[, 5] )
a <- dirknn(x, x, y, k = 2:10)
```

`Limited number of eigenvalues and eigenvectors of a symmetric matrix`

Limited number of eigenvalues and eigenvectors of a symmetric matrix

---

Description

Limited number of eigenvalues and eigenvectors of a symmetric matrix.

Usage

```
eigen.sym(A, k, vectors = TRUE)
```

Arguments

A	A symmetric matrix.
k	The number of eigenvalues and eigenvectors to extract.
vectors	A flag that indicates if the eigenvectors will be returned (default: vectors = True)

Details

The function calls the same function from the Armadillo library in C++. It is quite faster than R's built in function "eigen" if the number of eigenvalues and eigenvectors (argument k) is small.

The k largest, in magnitude, eigenvalues are returned. Hence, if the matrix is not positive definite you may get negative eigenvalues as well. So, it is advised to use it with positive definite matrices.

Value

A list including:

values	The eigenvalues.
vectors	The eigenvectors.

Author(s)

Armadillo library in C++ and Stefanos Fafalios and Manos Papadakis.

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com> and Manos Papadakis <papadakm95@gmail.com>.

See Also

hd.eigen

Examples

```
x <- matrnorm(500, 100 )
s <- Rfast::cova(x)
res<-eigen.sym(s, 5)
x <- s <- NULL
```

`Linear models for large scale data`

Linear models for large scale data

Description

Linear models for large scale data.

Usage

```
lmfit(x, y, w = NULL)
```

Arguments

x	The design matrix with the data, where each column refers to a different sample of subjects. You must supply the design matrix, with the column of 1s. This function is the analogue of lm.fit and .lm.fit.
y	A numerical vector or a numerical matrix.
w	An optional numerical vector with weights. Note that if you supply this, the function does not make them sum to 1. So, you should do it.

Details

We have simply exploitted R's powerful function and managed to do better than .lm.fit which is a really powerful function as well. This is a bare bones function as it returns only two things, the coefficients and the residuals. .lm.fit returns more and lm.fit even more and finally lm returns too much. The motivatrion came form this site https://m-clark.github.io/docs/fastr.html . We changed the function a bit.

Value

A list including:

be	The beta coefficients.
residuals	The residuals of the linear model(s).

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

See Also

regression, allbetas, correls, mvbetas, cor.fsreg

Examples

```
n <- 200  ;  p <- 5
X <- matrnorm(n, p)
y <- rnorm(n)
a1 <- .lm.fit(X, y)
a2 <- lmfit(X, y)
x <- NULL
```

Logistic and Poisson regression models

Logistic and Poisson regression models

Description

Logistic and Poisson regression models.

Usage

```
glm_logistic(x, y, full = FALSE,tol = 1e-09, maxiters = 100)
glm_poisson(x, y, full = FALSE,tol = 1e-09)
```

Arguments

x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. This can be a matrix or a data.frame (with factors).
y	The dependent variable; a numerical vector with two values (0 and 1) for the logistic regression or integer values, 0, 1, 2,... for the Poisson regression.
full	If this is FALSE, the coefficients and the deviance will be returned only. If this is TRUE, more information is returned.
tol	The tolerance value to terminate the Newton-Raphson algorithm.
maxiters	The max number of iterations that can take place in each regression.

Details

The function is written in C++ and this is why it is very fast.

Value

When full is FALSE a list including:

`be`	The regression coefficients.
`devi`	The deviance of the model.

When full is TRUE a list including:

`info`	The regression coefficients, their standard error, their Wald test statistic and their p-value.
`devi`	The deviance.

Author(s)

Manos Papadakis <papadakm95@gmail.com>

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

`poisson_only`, `logistic_only`, `univglms`, `regression`

Examples

```
x <- matrix(rnorm(100 * 3), ncol = 3)
y <- rbinom(100, 1, 0.6)   ## binary logistic regression
a1 <- glm_logistic(x, y, full = TRUE)
a2 <- glm(y ~ x, binomial)

x <- matrix(rnorm(100 * 3), ncol = 3)
y <- rpois(100, 10)   ## binary logistic regression
b1 <- glm_poisson(x, y, full = TRUE)
b2 <- glm(y ~ x, poisson)

x<-y<-a1<-a2<-b1<-b2<-NULL
```

`Logistic or Poisson regression with a single categorical predictor`
Logistic or Poisson regression with a single categorical predictor

Description

Logistic or Poisson regression with a single categorical predictor.

Usage

```
logistic.cat1(y, x, logged = FALSE)
poisson.cat1(y, x, logged = FALSE)
```

Arguments

`y`	A numerical vector with values 0 or 1.
`x`	A numerical vector with discrete numbers or a factor variable. This is suppose to be a categorical predictor. If you supply a continuous valued vector the function will obviously provide wrong results. **Note:** For the "binomial.anova" if this is a numerical vector it must contain strictly positive numbers, i.e. 1, 2, 3, 4, ..., no zeros are allowed.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

There is a closed form solution for the logistic regression in the case of a single predictor variable. See the references for more information.

Value

`info`	A matrix similar to the one produced by the glm command. The estimates, their standard error, the Wald value and the relevant p-value.
`devs`	For the logistic regression case a vector with the null and the residual deviances, their difference and the significance of this difference.
`res`	For the Poisson regression case a vector with the log likelihood ratio test statistic value and its significance.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Stan Lipovetsky (2015). Analytical closed-form solution for binary logit regression by categorical predictors. Journal of Applied Statistics, 42(1): 37–49.

See Also

poisson.anova, poisson.anovas, anova, logistic_only, poisson_only

Examples

```
y <- rbinom(20000, 1, 0.6)
x <- as.factor( rbinom(20000, 3, 0.5) )
a1 <- logistic.cat1(y, x)
#a2 <- glm(y ~ x, binomial)

y <- rpois(20000, 10)
x <- as.factor( rbinom(20000, 3, 0.5) )
a1 <- poisson.cat1(y, x)
#a2 <- glm(y ~ x, poisson)

x<-y<-a1<-a2<-NULL
```

`Lower and Upper triangular of a matrix`

Lower and Upper triangular of a matrix

Description

Lower/upper triangular matrix.

Usage

```
lower_tri(x, suma = FALSE, diag = FALSE)
upper_tri(x, suma = FALSE, diag = FALSE)
lower_tri.assign(x, v, diag = FALSE)
upper_tri.assign(x, v, diag = FALSE)
```

Arguments

x	A matrix with data **or** a vector with 2 values which is the dimension of the logical matrix to be returned with the upper or lower triangular filled with "TRUE".
v	A numeric vector for assign to the lower/upper triangular.
suma	A logical value for returning the sum of the upper or lower triangular. By default is "FALSE". Works only **if** argument "x" is matrix.
diag	A logical value include the diagonal to the result.

Value

Get a lower/upper triangular logical matrix with values **TRUE/FALSE**, a vector with the values of a lower/upper triangular, the sum of the upper/lower triangular if suma is set **TRUE** or assign to the lower/upper (only for large matrices) triangular. You can also include diagonal with any operation if argument diag is set to "TRUE".

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, colFalse, nth, rowrange, rowMedians, rowVars, colTrue

Examples

```
x <- matrix(runif(10*10),10,10)

all.equal(lower_tri(c(10,10)),lower.tri(x))

all.equal(lower_tri(x),x[lower.tri(x)])

#all.equal(upper_tri(c(10,10)),upper.tri(x))

#all.equal(upper_tri(x),x[upper.tri(x)])


#all.equal(lower_tri(c(10,10),diag = TRUE),lower.tri(x,diag = TRUE))

#all.equal(lower_tri(x,diag = TRUE),x[lower.tri(x,diag = TRUE)])

#all.equal(upper_tri(c(10,10),diag = TRUE),upper.tri(x,diag = TRUE))

#all.equal(upper_tri(x,diag = TRUE),x[upper.tri(x,diag = TRUE)])

all.equal(lower_tri.assign(x,diag = TRUE,v=rep(1,1000)),x[lower.tri(x,diag = TRUE)]<-1)

all.equal(upper_tri.assign(x,diag = TRUE,v=rep(1,1000)),x[upper.tri(x,diag = TRUE)]<-1)

x<-NULL
```

Mahalanobis distance *Mahalanobis distance*

Description

Mahalanobis distance.

Usage

```
mahala(x, mu, sigma, ischol = FALSE)
```

Arguments

x	A matrix with the data, where rows denotes observations (vectors) and the columns contain the variables.
mu	The mean vector.
sigma	The covariance or any square symmetric matrix.
ischol	A boolean variable set to true if the Cholesky decomposition of the covariance matrix is supplied in the argument \"sigma\".

Value

A vector with the Mahalanobis distances.

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>,

C++ and R implementation and documentation: Matteo Fasiolo <matteo.fasiolo@gmail.com>.

See Also

dista, colmeans

Examples

```
x <- matrix( rnorm(100 * 50), ncol = 50 )
m <- colmeans(x)
s <- cov(x)
#a1 <- mahala(x, m, s)
```

Many (and one) area under the curve values

Many area under the curve values

Description

Many area under the curve values.

Usage

```
colaucs(group, preds)
auc(group, preds)
```

Arguments

group	A numerical vector with two values, one of which must be strictly 1.
preds	A numerical matrix with scores, probabilities or any other measure. In the case of auc this is a vector.

Details

The AUCs are calculated column-wise or just an AUC if the vector function is used.

Value

A vector with length equal to the number of columns of the "preds" argument, with the AUC values for each column. If the "auc" function is used then a signle number is returned.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`ttests`, `ttest`, `ftests`

Examples

```
## 200 variables, hence 200 AUCs will be calculated
x <- matrix( rnorm(100 * 200), ncol = 200 )
ina <- rbinom(100, 1, 0.6)
colaucs(ina, x)
a <- colaucs(ina, x)
b <- auc(ina, x[, 1])
x <- NULL
```

Many 2 sample proportions tests

Many 2 sample proportions tests

Description

It performs very many 2 sample proportions tests.

Usage

```
proptests(x1, x2, n1, n2)
```

Arguments

x1	A vector with the successes of the one group.
x2	A vector with the successes of the one group.
n1	A vector with the number of trials of the one group.
n2	A vector with the number of trials of the one group.

Details

The 2-sample proportions test is performed for each pair of proportions of teh two groups.

Value

A matrix with the proportions of each group (two columns), the test statistic and the p-value of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

B. L. Welch (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

See Also

`ttests`, `ftests`, `colVars`

Examples

```
## 10000 variables, hence 10000 t-tests will be performed
set.seed(12345)
x1 <- rpois(500, 5)
x2 <- rpois(500, 5)
n1 <- rpois(1000, 40)
n2 <- rpois(1000, 40)
a <- proptests(x1, x2, n1, n2)
mean(a[, 4]<0.05)

x1 <- rbinom(500, 500, 0.6)
x2 <- rbinom(500, 500, 0.6)
b <- proptests(x1, x2, 500, 500)
mean(b[, 4]<0.05)
```

Many 2 sample tests *Many 2 sample tests tests*

Description

It performs very many 2 sample tests.

Usage

```
ttests(x, y = NULL, ina, alternative = "unequal", paired = FALSE,
logged = FALSE, parallel = FALSE)
mcnemars(x, y = NULL, ina, logged = FALSE)
var2tests(x, y = NULL, ina, alternative = "unequal", logged = FALSE)
```

Arguments

x	A matrix with the data, where the rows denote the samples and the columns are the variables.
y	A second matrix with the data of the second group. If this is NULL (default value) then the argument ina must be supplied. Notice that when you supply the two matrices the procedure is two times faster.
ina	A numerical vector with 1s and 2s indicating the two groups. Be careful, the function is designed to accept only these two numbers. In addition, if your "y" is NULL, you must specify "ina".
alternative	The type of hypothesis to be checked, "equal", "greater", "less".
paired	If the groups are not independent paired t-tests should be performed and this must be TRUE, otherwise, leave it FALSE. In this case, the two groups must have equal smaple sizes, otherwise no test will be performed.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?
parallel	Should parallel implentations take place in C++? The default value is FALSE.

Details

For the ttests, if the groups are independent, the Welch's t-test (without assuming equal variances) is performed. Otherwise many paired t-tests are performed. The McNemar's test requires a number of observations, at least 30 would be good in order for the test to have some power and be size corect.

Value

A matrix with the test statistic, the degrees of freedom (if the groups are independent) and the p-value (or their logarithm) of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

B. L. Welch (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

McNemar Q. (1947). Note on the sampling error of the difference between correlated proportions or percentages. Psychometrika. 12(2):153-157.

See Also

ftests, anovas, ttest

Examples

```
## 1000 variables, hence 1000 t-tests will be performed
x = matrnorm(100, 100)
## 100 observations in total
ina = rbinom(100, 1, 0.6) + 1   ## independent samples t-test
ttests(x, ina = ina)
x1 = x[ina == 1, ]
x2 = x[ina == 2, ]
ttests(x1, x2)
x <- NULL
```

Many analysis of variance tests with a discrete variable

Many analysis of variance tests with a discrete variable

Description

Many analysis of variance tests with a discrete variable.

Usage

```
poisson.anovas(y, ina, logged = FALSE)
quasipoisson.anovas(y, ina, logged = FALSE)
geom.anovas(y, ina, type = 1, logged = FALSE)
```

Arguments

y	A numerical matrix with discrete valued data, i.e. counts for the case of the Poisson, or with 0s and 1s for the case of the Bernoulli distribution. Each column represents a variable.
ina	A numerical vector with discrete numbers starting from 1, i.e. 1, 2, 3, 4,... or a factor variable. This is suppose to be a categorical predictor. If you supply a continuous valued vector the function will obviously provide wrong results.
type	This rgument is for the geometric distribution. Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

This is the analysis of variance with count data. What we do is many log-likelihood ratio tests. For the quasi Poisson case we scale the difference in the deviances.

Value

A matrix with two values, the difference in the deviances (test statistic) and the relevant p-value. For the case of quasi Poisson the estimated ϕ parameter is also returned.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

g2tests, poisson.anova, anova, poisson_only, poisson.mle

Examples

```
ina <- rbinom(500, 3, 0.5) + 1
## Poisson example
y <- matrix( rpois(500 * 100, 10), ncol= 100 )
a1 <- poisson.anovas(y, ina)
y <- NULL
```

Many ANCOVAs *Many ANCOVAs*

Description

Many ANCOVAs.

Usage

```
ancovas(y, ina, x, logged = FALSE)
```

Arguments

y	A matrix with the data, where the rows denote the observations and the columns are the variables.
ina	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Be careful, the function is desinged to accept numbers greater than zero.
x	A numerical vector whose length is equal to the number of rows of y. This is the covariate.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

Many Analysis of covariance tests are performed. No interaction between the factor and the covariate is tested. Only the main effects. The design need not be balanced. The values of ina need not have the same frequency. The sums of squares have been adjusted to accept balanced and unbalanced designs.

Value

A matrix with the test statistic and the p-value for the factor variable and the covariate.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

D.C. Montgomery (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons

See Also

ftests, ttests, anovas

Examples

```
## 100 variables, hence 100 F-tests will be performed
y <- matrix( rnorm(90 * 100), ncol = 100 )
ina <- rbinom(90, 2, 0.5) + 1
x <- rnorm(90)
a <- ancovas(y, ina, x)

m1 <- lm(y[, 15] ~ factor(ina) + x)
m2 <- lm(y[, 15] ~ x + factor(ina))
res<-anova(m1)
res<-anova(m2)
y <- NULL
a[15, ]  ## the same with the m2 model, but not the m1
```

Many ANOVAS for count data with Poisson or quasi Poisson models

Many ANOVAS for count data with Poisson or quasi Poisson models

---

Description

Many ANOVAS for count data with Poisson or quasi Poisson models.

Usage

```
colpoisson.anovas(y, x, logged = FALSE)
colquasipoisson.anovas(y, x, logged = FALSE)
```

Arguments

y	A numerical vector with the data.
x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. This must be a matrix with the categorical variables as numbers, starting from 1. Poisson or quassi Poisson ANOVA takes place for each column.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.

Details

Poisson or quassi Poisson ANOVA takes place at each column.

Value

A matrix with the test statistic and the (logged) p-value for each predictor variable. In the case of the quasi Poisson, the ϕ is returned as well.

Author(s)

Michail Tsagris and Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

See Also

poisson.anova boot.ttest2, ttest2, ftest

Examples

```
y <- rpois(200, 10)
x <- matrix(rbinom(200 * 10, 3, 0.5 ), ncol = 10)
```

Many exponential regressions

Many exponential regressions

Description

Many exponential regressions.

Usage

```
expregs(y, x, di, tol = 1e-09, logged = FALSE)
```

Arguments

y	A vector with positive data (including zeros).
x	A numerical matrix with the predictor variables.
di	A vector of size equal to that of y with 0s and 1s indicating censoring or not respectively.
tol	The tolerance value to stop the newton-Raphson iterations. It is set to 1e-09 by default.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.

Details

We have implemented the newton-Raphson in order to avoid unnecessary calculations.

Value

A matrix with three columns, the test statistic, its associated (logged) p-value and the BIC of each model.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

univglms, score.glms, logistic_only, poisson_only, regression

Examples

```
## 200 variables, hence 200 univariate regressions are to be fitted
x <- matrnorm(100, 100)
y <- rexp(100, 4)
expregs(y, x, di = rep(1, length(y)))
x <- NULL
```

Many F-tests with really huge matrices

Many F-tests with really huge matrices

Description

Many F-tests with really huge matrices.

Usage

```
list.ftests(x, logged = FALSE)
```

Arguments

x	A list with many big size matrices. Each element of the list contains a matrix. This is the ftests function but with really huge matrices, which cannot be loaded into R as a single matrix.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The Welch's F-test (without assuming equal variances) is performed just like in the "ftests" function. The difference is that you have a really huge matrix which you cannot load into R. In the "ftests" function, the argument "ina" denotes the different groups. Here, you "cut" the matrix into smaller ones, each of which denotes a different group and put them in a list.

Value

A matrix with the test statistic and the p-value of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

B.L. Welch (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

See Also

ftests, ttests

Examples

```
x <- matrnorm(300, 500)
ina <- rbinom(300, 2, 0.6) + 1
a <- list()
a[[ 1 ]] <- x[ina == 1, ]
a[[ 2 ]] <- x[ina == 2, ]
a[[ 3 ]] <- x[ina == 3, ]
mod <- list.ftests(a)
z <- NULL
a <- NULL
```

`Many G-square and Chi-square tests of indepedence`
Many G-square tests of indepedence

Description

Many G-square tests of indepdence with and without permutations.

Usage

```
g2tests(data, x, y, dc)
g2tests_perm(data, x, y, dc, nperm)
chi2tests(data, x, y, dc)
```

Arguments

`data`	A numerical matrix with the data. **The minimum must be 0, otherwise the function can crash or will produce wrong results**. The data must be consecutive numbers.
`x`	An integer number or a vector of integer numbers showing the other variable(s) to be used for the G^2 test of independence.
`y`	An integer number showing which column of data to be used.
`dc`	A numerical value equal to the number of variables (or columns of the data matrix) indicating the number of distinct, unique values (or levels) of each variable. Make sure you give the correct numbers here, otherwise the degrees of freedom will be wrong.
`nperm`	The number of permutations. The permutations test is slower than without permutations and should be used with small sample sizes or when the contigency tables have zeros. When there are few variables, R's "chisq.test" function is faster, but as the number of variables increase the time difference with R's procedure becomes larger and larger.

Details

The function does all the pairwise G^2 test of independence and gives the position inside the matrix. The user must build the associations matrix now, similarly to the correlation matrix. See the examples of how to do that. The p-value is not returned, we leave this to the user. See the examples of how to obtain it.

Value

A list including:

`statistic`	The G^2 or χ^2 test statistic for each pair of variables.
`pvalue`	This is returned when you have selected the permutation based G^2 test.
`x`	The row or variable of the data.
`y`	The column or variable of the data.
`df`	The degrees of freedom of each test.

Author(s)

Giorgos Borboudakis. The permutation version used a C++ code by John Burkardt.

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Tsagris M. (2017). Conditional independence test for categorical data using Poisson log-linear model. Journal of Data Science, 15(2):347-356.

Tsamardinos, I., & Borboudakis, G. (2010). Permutation testing improves Bayesian network learning. In Joint European Conference on Machine Learning and Knowledge Discovery in Databases (pp. 322-337). Springer Berlin Heidelberg.

See Also

`g2Test`, `g2Test_perm`, `correls`, `univglms`

Examples

```
nvalues <- 3
nvars <- 10
nsamples <- 2000
data <- matrix( sample( 0:(nvalues - 1), nvars * nsamples, replace = TRUE ), nsamples, nvars )
dc <- rep(nvalues, nvars)
a <- g2tests(data = data, x = 2:9, y = 1, dc = dc)
pval <- pchisq(a$statistic, a$df, lower.tail = FALSE)  ## p-value
b <- g2tests_perm(data = data, x = 2:9, y = 1, dc = dc, nperm = 1000)
a<-b<-data<-NULL
```

`Many hypothesis tests for two means of percentages`
Many hypothesis tests for two means of percentages

Description

Many hypothesis tests for two means of percentages.

Usage

```
percent.ttests(x, y, logged = FALSE)
```

Arguments

`x`	A numericalmatrix with the percentages of the first sample. Any value between 0 and 1 (inclusive) is allowed.
`y`	A numerical matrix with the percentages of the first sample. Any value between 0 and 1 (inclusive) is allowed.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

This is the `prop.reg` but with a single categorical predictor which has two levels only. It is like a t-test for the means of two samples haivng percentages.

Value

A matrix with three columns, the phi parameter, the test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Papke L. E. & Wooldridge J. (1996). Econometric methods for fractional response variables with an application to 401(K) plan participation rates. Journal of Applied Econometrics, 11(6): 619-632.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

`link{percent.ttest}`, `prop.reg`, `ttest2`, `ftest`

Examples

```
x <- matrix( rbeta(100 * 10, 3, 1), ncol = 10)
y <- matrix( rbeta(50 * 10, 7.5, 2.5), ncol = 10)
res<-percent.ttests(x, y)
```

Many moment and maximum likelihood estimations of variance components

Many moment and maximum likelihood estimations of variance components

---

Description

Many moment and maximum likelihood estimations of variance components.

Usage

```
colvarcomps.mom(x, id, parallel = FALSE)
colvarcomps.mle(x, id, ranef = FALSE, tol= 1e-08, maxiters = 100,
parallel = FALSE)
```

Arguments

x	A matrix with the data, where each column refers to a different sample of subjects.
id	A numerical vector indicating the subject. You must put consecutive numbers and no zero values. Alternatively this can be a factor variable.
ranef	Do you also want the random effects to be returned? TRUE or FALSE.
tol	The tolerance level to terminate the golden ratio search.
maxiters	The maximum number of iterations to perform.
parallel	Should the computations run in parallel? TRUE or FALSE.

Details

Note that the "colvarcomp.mom" works for **balanced designs only**, i.e. for each subject the same number of measurements have been taken. The "colvarcomps.mle" works for unbalanced as well.

The variance components, the variance of the between measurements and the variance of the within are estimated using moment estimators. The "colvarcomps.mom" is the moment analogue of a random effects model which uses likelihood estimation ("colvarcomps.mle"). It is much faster, but can give negative variance of the random effects, in which case it becomes zero.

The maximum likelihood version is a bit slower (try youselves to see the difference), but statistically speaking is to be preferred when small samples are available. The reason why it is only a little bit slower and not a lot slower as one would imagine is because we are using a closed formula to calculate the two variance components (Demidenko, 2013, pg. 67-69). Yes, there are closed formulas for linear mixed models.

Value

For the "colvarcomps.mom": A matrix with 5 columns, The MSE, the estimate of the between variance, the variance components ratio and a 95% confidence for the ratio.

For the "colvarcomps.mle": **If ranef = FALSE** a list with a single component called "info". That is a matrix with 3 columns, The MSE, the estimate of the between variance and the log-likelihood value. **If ranef = TRUE** a list including "info" and an extra component called "ranef" containing the random effects. It is a matrix with the same number of columns as the data. Each column contains the randome effects of each variable.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

D.C. Montgomery (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons.

Charles S. Davis (2002). Statistical methods for the analysis of repeated measures. New York: Springer-Verlag.

Demidenko E. (2013). Mixed Models: Thoery and Applications with R 2nd Edition). New Jersey: John Wiley & Sons (Excellent book).

See Also

varcomps.mle, colrint.regbx

Examples

```
## example taken from Montgomery, page 514-517.
y <- c(98, 97, 99, 96, 91, 90, 93, 92,
96, 95, 97, 95, 95, 96, 99, 98)
y <- matrix(y)
id <- rep(1:4, each = 4)

x <- rmvnorm(100, numeric(20), diag(rexp(20)) )
id <- rep(1:25, each = 4)
n <- 25  ;  d <- 4
a <- colvarcomps.mom(x, id)
mean(a[, 4]<0 & a[, 5]>0)
b <- colvarcomps.mle(x, id)
x <- NULL
```

Many multi-sample tests

Many multi-sample tests

Description

Many multi-sample tests.

Usage

```
ftests(x, ina, logged = FALSE)
anovas(x, ina, logged = FALSE)
vartests(x, ina, type = "levene", logged = FALSE)
block.anovas(x, treat, block, logged = FALSE)
```

Arguments

x	A matrix with the data, where the rows denote the observations (and the two groups) and the columns are the variables.
ina	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Be careful, the function is desinged to accept numbers greater than zero. Alternatively it can be a factor variable.
type	This is for the variances test and can be either "levene" or "bf" corresponding to Levene's or Brown-Forsythe's testing procedure.
treat	In the case of the blocking ANOVA this argument plays the role of the "ina" argument.
block	This item, in the blocking ANOVA denotes the subjects which are the same. Similarly to "ina" a numeric vector with 1s, 2s, 3s and so on.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The Welch's F-test (without assuming equal variances) is performed with the "ftests" function. The "anovas" function perform the classical (Fisher's) one-way analysis of variance (ANOVA) which assumes equal variance across the groups.

The "vartests" perform hypothesis test for the equality of the variances in two ways, either via the Levene or via the Brown-Forshythe procedure. Levene's test employs the means, whereas the Brown-Forsythe procedure employs the medians and is therefore more robust to outliers. The "var2tests" implement the classical F test.

The "block.anova" is the ANOVA with blocking, randomised complete block design (RCBD). In this case, for every combination of the block and treatment values, there is only one observation. The mathematics are the same as in the case of two way ANOVA, but the assumptions different and the testing procedure also different. In addition, no interaction is present.

Value

A matrix with the test statistic and the p-value of each test.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Welch B.L. (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

Montgomery D.C. (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons.

See Also

ttests

Examples

```
x <- matrix( rnorm(300 * 50), ncol = 50 )
## 300 observations in total
ina <- rbinom(300, 3, 0.6) + 1
a1 <- ftests(x, ina)
a2 <- anovas(x, ina)
a3 <- vartests(x, ina)
x <- NULL
```

Many multivariate simple linear regressions coefficients

Many multivariate simple linear regressions coefficients

Description

Many multivariate simple linear regressions coefficients.

Usage

```
mvbetas(y, x, pvalue = FALSE)
```

Arguments

y	A matrix with the data, where rows denotes the observations and the columns contain the dependent variables.
x	A numerical vector with one continuous independent variable only.
pvalue	If you want a hypothesis test that each slope (beta coefficient) is equal to zero set this equal to TRUE. It will also produce all the correlations between y and x.

Details

It is a function somehow opposite to the allbetas. Instead of having one y and many xs we have many ys and one x.

Value

A matrix with the constant (alpha) and the slope (beta) for each simple linear regression. If the p-value is set to TRUE, the correlation of each y with the x is calculated along with the relevant p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

allbetas, correls, univglms

Examples

```
y <- matrnorm(100, 100)
x <- rnorm(100)
a <- mvbetas(y, x, pvalue = FALSE)
b <- matrix(nrow = 100, ncol = 2)
z <- cbind(1, x)

a <- mvbetas(y, x)
b[2, ] <- coef( lm.fit( z, y[, 1] ) )
b[2, ] <- coef( lm.fit( z, y[, 2] ) )
x <- NULL
```

Many non parametric multi-sample tests

Many multi-sample tests

Description

Many multi-sample tests.

Usage

```
kruskaltests(x, ina, logged = FALSE)
cqtests(x, treat, block, logged = FALSE)
```

Arguments

x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables.
ina	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Be careful, the function is desinged to accept numbers greater than zero.
treat	In the case of the Cochran's Q test, this argument plays the role of the "ina" argument.
block	This item denotes the subjects which are the same. Similarly to "ina" a numeric vector with 1s, 2s, 3s and so on.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The "kruskaltests" performs the Kruskal-Wallis non parametric alternative to analysis of variance test. The "cqtests" performs the Cocrhan's Q test for the equality of more than two groups whose values are strictly binary (0 or 1). This is a generalisation of the McNemar's test in the multi-sample case.

Value

A matrix with the test statistic and the p-value of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

block.anovas, ftests

Examples

```
x <- matrix( rexp(300 * 200), ncol = 200 )
ina <- rbinom(300, 3, 0.6) + 1
kruskaltests(x, ina)
x <- matrix( rbinom(300 * 200, 1, 0.6), ncol = 200 )
treat <- rep(1:3, each = 100)
block <- rep(1:3, 100)
cqtests(x, treat, block)
x <- NULL
```

`Many odds ratio tests` *Many odds ratio tests*

Description

It performs very many odds ratio tests.

Usage

```
odds(x, y = NULL, ina, logged = FALSE)
```

Arguments

`x`	A matrix with the data, where the rows denote the observations and the columns are the variables. They must be 0s and 1s only.
`y`	A second matrix with the data of the second group. If this is NULL (default value) then the argument ina must be supplied. Notice that when you supply the two matrices the procedure is two times faster. They must be 0s and 1s only.
`ina`	A numerical vector with 1s and 2s indicating the two groups. Be careful, the function is designed to accept only these two numbers. In addition, if your "y" is NULL, you must specify "ina".
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

Many odds ratio tests are performed.

Value

A matrix with the test statistic and the p-value (or their logarithm) of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Mosteller Frederick (1968). Association and Estimation in Contingency Tables. Journal of the American Statistical Association. 63(321):1-28.

Edwards A.W.F. (1963). The measure of association in a 2x2 table. Journal of the Royal Statistical Society, Series A. 126(1):109-114.

See Also

`odds.ratio`, `g2Test_univariate`

Examples

```
x <- matrix( rbinom(100 * 100, 1, 0.5), ncol = 100 )
ina <- rep(1:2, each = 50)
a <- odds(x, ina = ina)
```

`Many one sample goodness of fit tests for categorical data`

Many one sample goodness of fit tests for categorical data

Description

Many one sample goodness of fit tests for categorical data.

Usage

```
cat.goftests(x, props, type = "gsquare", logged = FALSE)
```

Arguments

`x`	A matrix with the data, where the rows denote the samples and the columns are the variables. The data must be integers and be of the form 1, 2, 3, and so on. The minimum must be 1, and not zero.
`props`	The assumed distribution of the data. A vector or percentages summing to 1.
`type`	Either Pearson's χ^2 test ("chisquare") is used or the G^2 test ("qsquare", default value).
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

Given a matrix of integers, where each column refers to a sample, the values of a categorical variable the function tests wether these values can be assumed to fit a specific distribution.

Value

A matrix with the test statistic and the p-value of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`ttests`, `ttest`, `ftests`

Examples

```
x <- matrix( rbinom(300 * 100, 4, 0.6), ncol = 100 ) + 1
props <- dbinom(0:4, 4, 0.6)
## can we assume that each column comes from a distribution  whose mass is given by props?
cat.goftests(x, props)
a1 <- cat.goftests(x, props)  ## G-square test
a2 <- cat.goftests(x, props, type = "chisq")  ## Chi-square test
cor(a1, a2)
mean( abs(a1 - a2) )
x <- NULL
```

Many one sample tests *Many one sample tests*

Description

Many one sample tests.

Usage

```
proptest(x, n, p, alternative = "unequal", logged = FALSE)
ttest(x, m, alternative = "unequal", logged = FALSE, conf = NULL)
vartest(x, sigma, alternative = "unequal", logged = FALSE, conf = NULL)
```

Arguments

x	A matrix with numerical data. Each column of the matrix corresponds to a sample, or a group. In the case of the "proptest" this is a vector integers ranging from 0 up to n. It is the number of "successes".
n	This is for the "proptest" only and is a vector with integer numbers specifying the number of tries for the proptest. Its size is equal to the size of x.
p	A vector with the assumed probabilities of success in the "proptest". Its size is equal to the number of colums of the matrix x.
m	A vector with the assumed means. Its size is equal to the number of colums of the matrix x.
sigma	A vector with assumed variances. Its size is equal to the number of colums of the matrix x.
alternative	The type of hypothesis to be checked. Equal to ("unequal"), grater than("greater") or less than ("less") the assumed parameter.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?
conf	If you want confidence intervals to be returned specify the confidence level, otherwise leave it NULL.

Details

Despite the functions having been written in R, they are very fast.

Value

For all tests except for the "sftests" a matrix with two colums, the test statistic and the p-value respectively.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

ftests, ttests

Examples

```
R <- 100
## protest
x <- rbinom(R, 50, 0.6)
n <- rep(50, R)
p <- rep(0.6, R)
a1 <- proptest(x, n, p, "unequal", logged = FALSE)
res<-sum( a1[, 2] < 0.05 ) / R

## vartest
x <- matrnorm(100, 100)
a2 <- vartest(x, rep(1, R) )
res<-sum( a2[, 2] < 0.05 )

## ttest
a4 <- ttest(x, numeric(R) )
res<-sum(a4[, 2] < 0.05) / R
x <- NULL
```

`Many random intercepts LMMs for balanced data with a single identical covariate.`

Many random intercepts LMMs for balanced data with a single identical covariate

---

Description

Many random intercepts LMMs for balanced data with a single identical covariate.

Usage

```
colrint.regbx(y, x, id)
```

Arguments

y	A numerical matrix with the data. The subject values.
x	A numerical vector with the same length as the number of rows of y indicating the fixed predictor variable. Its values are the same for all levels of y. An example of this x is time which is the same for all subjects.
id	A numerical variable with 1, 2, ... indicating the subject.

Details

This is a special case of a balanced random intercepts model with a compound symmetric covariance matrix and one single covariate which is constant for all replicates. An example, is time, which is the same for all subjects. Maximum likelihood estimation has been performed. In this case the mathematics exist in a closed formula (Demidenko, 2013, pg. 67-69).

This is the generalistion of `rint.regbx` to matrices. Assume you have many observations, gene expressions over time for example, and you want to calculate the random effects or something else for each expression. Instead of using a "for" loop with `rint.regbx` function we have used amtrix operations to make it even faster.

Value

A list including:

info	A matrix with the random intercepts variance (between), the variance of the errors (within), the log-likelihood, the deviance (twice the log-likelihood) and the BIC. In the case of "rint.reg" it also includes the number of iterations required by the generalised least squares.
be	The estimated regression coefficients, which in the case of "rint.regbx" are simply two: the constant and the slope (time effect).
ranef	A matrix with random intercepts effects. Each row corresponds to a column in y. Instead of having a matrix with the same number of columns as y we return a transposed matrix.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Eugene Demidenko (2013). Mixed Models: Theory and Applications with R, 2nd Edition. New Jersey: Wiley & Sons (excellent book).

See Also

`colvarcomps.mle`, `rint.regbx`, `rm.lines`, `varcomps.mom`, `rint.reg`

Examples

```
y <- matrix( rnorm(100 * 50), ncol = 50)
id <- rep(1:20, each = 5)
x <- rep(1:10, 10)
a<- colrint.regbx(y, x, id)
```

`Many regression based tests for single sample repeated measures`
Many regression based tests for single sample repeated measures

---

Description

Many regression based tests for single sample repeated measures.

Usage

```
rm.lines(y, x, logged = FALSE)
rm.anovas(y, x, logged = FALSE)
```

Arguments

`y`	A matrix with the data, where each column refers to a different sample of subjects. For example, the first column is the repeated measurements of a sample of subjects, the second column contains repeated measurements of a second sample of subjects and so on. Within each column, the measurements of each subjects are stacked one upon the other. Say for examples there are n subjects and each of them has been measured d times (in time or at different experimental conditions). We put these in a matrix with just one column. The first d rows are the measurements of subject 1, the next d rows are the measurements of subject 2 and so on.
`x`	A numerical vector with time (usually) or the the predictor variable. For example the temperature, or the pressure. See the details for more information. Its length is equal to the time points for example, i.e. it must not have the same length as the number of rows of y. For the "rm.lines" this is a continuous variable. For the "rm.anovas" this is treated as a categorical variable, indicating say the type of experimental condition, but no difference between the points is important. Hence, for this function only, x can also be a facto variable.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

In order to see whether the repeated measurements are associated with a single covariate, e.g. time we perform many regressions and each time calculate the slope. For each subject, its regression slope with the covariate is calculated. In the end a t-test for the hypothesis that the average slopes is zero is performed. The regression slopes ignore that the measurements are not independent, but

note that the slopes are independent, because they come from different subjects. This is a simple, summary statistics based approach found in Davis (2002), yet it can provide satisfactory results.

The second approach ("rm.anovas") found in Davis (2002) is the usual repeated measures ANOVA. In this case, suppose you have taken measurements on one or more variables from the same group of people. See the example below on how to put such data.

Value

A matrix with the test statistic (t-test) and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Charles S. Davis (2002). Statistical methods for the analysis of repeated measures. Springer-Verlag, New York.

See Also

rint.regbx, rint.reg, varcomps.mle

Examples

```
y <- c(74.5,81.5,83.6,68.6,73.1,79.4,
75.5,84.6,70.6,87.3,73.0,75.0,
68.9,71.6,55.9,61.9,60.5,61.8,
57.0,61.3,54.1,59.2,56.6,58.8,
78.3,84.9,64.0,62.2,60.1,78.7,
54.0,62.8,63.0,58.0,56.0,51.5,
72.5,68.3,67.8,71.5,65.0,67.7,
80.8,89.9,83.2,83.0,85.7,79.6)
y <- as.matrix(y)
### the first 6 measurements are from subject 1, measurments 7-12 are from subject 2,
## measurements 13-18 are from subject 3 and so on.
x <- c(-10, 25, 37, 50, 65, 80) ## all subjects were measured at the same time points
res<-rm.lines(y, x) ## Is linear trend between the measurements and the temperature?
res<-rm.anovas(y, x)  ## Tests whether the means of the individuals are the same
## the temperature is treated as categorical variable here.

## fake example
y <- matrnorm(10, 4)
## the y matrix contains 4 repeated measurements for each of the 10 persons.
x <- 1:4
## we stack the measurements of each subject, one under the other in a matrix form.
y1 <- matrix( t(y) )
res<-rm.anovas(y1, x)  ## perform the test
z <- matrix( rnorm(20 * 8), ncol = 2) ## same example, but with 2 sets of measurements.
```

```
res<-rm.anovas(z, x)
```

Many score based regressions

Many score based regressions

Description

Many score based GLM regressions.

Usage

```
score.glms(y, x, oiko = NULL, logged = FALSE)
score.multinomregs(y, x, logged = FALSE)
score.negbinregs(y, x, type = 1, logged = FALSE)
score.weibregs(y, x, logged = FALSE)
score.betaregs(y, x, logged = FALSE)
score.gammaregs(y, x, logged = FALSE)
score.expregs(y, x, logged = FALSE)
score.invgaussregs(y, x, logged = FALSE)
score.ztpregs(y, x, logged = FALSE)
score.geomregs(y, x, logged = FALSE)
```

Arguments

y	A vector with either discrete or binary data for the Poisson, geometric, or negative binomial and binary logistic regressions, respectively. A vector with discrete values or factor values for the multinomial regression. If the vector is binary and choose multinomial regression the function checks and transfers to the binary logistic regression. For the Weibull, gamma, inverse Gaussian and exponential regressions they must be strictly positive data, lifetimes or durations for example. For the beta regression they must be numbers between 0 and 1. For the zero truncated Poisson regression (score.ztpregs) they must be integer valued data strictly greater than 0.
x	A matrix with data, the predictor variables.
oiko	This can be either "poisson" or "binomial". If you are not sure leave it NULL and the function will check internally.
type	This argument is for the negative binomial distribution. In the negative binomial you can choose which way your prefer. Type 1 is for smal sample sizes, whereas type 2 is for larger ones as is faster.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.

Details

Instead of maximising the log-likelihood via the Newton-Raphson algorithm in order to perform the hypothesis testing that $\beta_i = 0$ we use the score test. This is dramatcially faster as no model needs to be fitted. The first derivative (score) of the log-likelihood is known and in closed form and under the null hypothesis the fitted values are all equal to the mean of the response variable y. The variance of the score is also known in closed form. The test is not the same as the likelihood ratio test. It is size correct nonetheless but it is a bit less efficient and less powerful. For big sample sizes though (5000 or more) the results are the same. We have seen via simulation studies is that it is size correct to large sample sizes, at elast a few thousands. You can try for yourselves and see that even with 500 the results are pretty close. The score test is pretty faster than the classical log-likelihood ratio test.

Value

A matrix with two columns, the test statistic and its associated p-value. For the Poisson and logistic regression the p-value is derived via the t distribution, whereas for the multinomial regressions via the χ^2 distribution.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Tsagris M., Alenazi A. and Fafalios S. (2020). Computationally efficient univariate filtering for massive data. Electronic Journal of Applied Statistical Analysis, 13(2):390-412.

Hosmer DW. JR, Lemeshow S. and Sturdivant R.X. (2013). Applied Logistic Regression. New Jersey ,Wiley, 3rd Edition.

Campbell M.J. (2001). Statistics at Square Two: Understand Modern Statistical Applications in Medicine, pg. 112. London, BMJ Books.

Draper N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

McCullagh Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

Agresti Alan (1996). An introduction to categorical data analysis. New York: Wiley.

Joseph M.H. (2011). Negative Binomial Regression. Cambridge University Press, 2nd edition.

See Also

univglms, logistic_only, poisson_only, regression

Examples

```
#x <- matrnorm(500, 500)
#y <- rbinom(500, 1, 0.6)   ## binary logistic regression
#a2 <- score.glms(y, x)
```

```
#y <- rweibull(500, 2, 3)
#a <- score.weibregs(y, x)
#mean(a[, 2] < 0.05)
#x <- NULL
```

`Many Shapiro-Francia normality tests`
Many Shapiro-Francia normality tests

Description

Many Shapiro-Francia normality tests.

Usage

```
sftests(x, logged = FALSE)
sftest(x, logged = FALSE)
```

Arguments

`x`	A matrix with the data, where the rows denote the observations and the columns are the variables. In the case of a single sample, then this must be a vector and "sftest" is to be used.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The Shapiro-Francia univariate normality test is performed for each column (variable) of the matrix x.

Value

A matrix with the squared correlation between the ordered values and the standard normal ordered statistics, the test statistic and the p-value of each test. If the "sftest" has been used, the output is a vector with these three elements.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Royston J. P. (1983). A simple method for evaluating the Shapiro-Francia W' test of non-normality. The Statistician, 32(3): 297-300.

Mbah A. K. & Paothong A. (2015). Shapiro-Francia test compared to other normality test using expected p-value. Journal of Statistical Computation and Simulation, 85(15): 3002-3016.

See Also

ttests, ttest, ftests

Examples

```
x <- matrnorm(200, 100)
sftests(x)
a <- sftests(x)
mean(a[, 3]<0.05)
x <- rnorm(100)
res<-sftest(x)
```

Many simple geometric regressions

Many simple geometric regressions

Description

Many simple geometric regressions.

Usage

```
geom.regs(y, x, tol = 1e-07, type = 1, logged = FALSE, parallel = FALSE, maxiters = 100)
```

Arguments

y	The dependent variable, count data.
x	A matrix with the indendent variables.
tol	The tolerance value to terminate the Newton-Raphson algorithm.
type	Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.
parallel	Do you want this to be executed in parallel or not. The parallel takes place in C++, and the number of threads is defined by each system's availiable cores.
maxiters	The max number of iterations that can take place in each regression.

Details

Many simple geometric regressions are fitted.

Value

A matrix with the test statistic values, their relevant (logged) p-values and the BIC values.

Author(s)

Stefanos Fafalios

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com>

See Also

poisson_only, prop.regs, score.geomregs

Examples

```
y <- rgeom(100, 0.6)
x <- matrix( rnorm(100 * 50), ncol = 50)
a <- geom.regs(y, x)
x <- NULL
```

`Many simple linear mixed model regressions`

Many simple linear mixed model regressions

Description

Many simple linear mixed model regressions with random intercepts only.

Usage

```
rint.regs(y, x, id, tol = 1e-08, logged = FALSE, parallel = FALSE, maxiters = 100)
```

Arguments

y	A numerical vector with the data. The subject values, the clustered data.
x	A numerical matrix with data ,the independent variables.
id	A numerical variable with 1, 2, ... indicating the subject. Unbalanced design is of course welcome.
tol	The tolerance value to terminate the Newton-Raphson algorithm. This is set to 10^{-9} by default.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?
parallel	Do you want this to be executed in parallel or not. The parallel takes place in C++, and the number of threads is defined by each system's availiable cores.
maxiters	The max number of iterations that can take place in each regression.

Details

Many linear mixed models with a single covariate are fitted. We use Newton-Raphson as described in Demidenko (2013). The test statistic is the usual F-test. This model allows for random intercepts only.

Value

A two-column matrix with the test statistics (Wald statistic) and the associated p-values (or their loggarithm).

Author(s)

Stefanos Fafalios.

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com>.

References

Eugene Demidenko (2013). Mixed Models: Theory and Applications with R, 2nd Edition. New Jersey: Wiley & Sons (excellent book).

See Also

rint.reg, allbetas univglms, score.glms, logistic_only

Examples

```
## not a so good example
y <- rnorm(100)
id <- sample(1:10, 100, replace = TRUE)
x <- matrix( rnorm(100 * 100), ncol = 100)
a <- rint.regs(y, x, id)
x <- NULL
```

Many simple linear regressions coefficients

Simple linear regressions coefficients

Description

Simple linear regressions coefficients.

Usage

```
allbetas(y, x, pvalue = FALSE, logged = FALSE)
```

Arguments

y	A numerical vector with the response variable.
x	A matrix with the data, where rows denotes the observations and the columns contain the independent variables.
pvalue	If you want a hypothesis test that each slope (beta coefficient) is equal to zero set this equal to TRUE. It will also produce all the correlations between y and x.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.

Value

A matrix with the constant (alpha) and the slope (beta) for each simple linear regression. If the p-value is set to TRUE, the correlation of each y with the x is calculated along with the relevant test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

mvbetas, correls, univglms, colsums, colVars

Examples

```
x <- matrix( rnorm(100 * 50), ncol = 50 )
y <- rnorm(100)
r <- cor(y, x)  ## correlation of y with each of the xs
a <- allbetas(y, x)  ## the coefficients of each simple linear regression of y with x
x <- NULL
```

Many simple multinomial regressions

Many simple multinomial regressions

Description

Many simple multinomial regressions.

Usage

```
multinom.regs(y, x, tol = 1e-08, logged = FALSE, parallel = FALSE, maxiters = 100)
```

Arguments

y	The dependent variable, either a numerical variable or a factor variable.
x	A matrix with the indendent variables.
tol	The tolerance value to terminate the Newton-Raphson algorithm.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.
parallel	Do you want this to be executed in parallel or not. The parallel takes place in C++, and the number of threads is defined by each system's availiable cores.
maxiters	The maximum number of iterations that can take place in each regression.

Details

Many simple multinomial regressions are fitted.

Value

A matrix with the test statistic values, their relevant (logged) p-values and the BIC values.

Author(s)

Stefanos Fafalios

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com>

See Also

poisson_only, prop.regs, score.geomregs

Examples

```
y <- rbinom(100, 2, 0.5)
x <- matrnorm(100, 100)
a <- multinom.regs(y, x)
x <- NULL
```

`Many simple regressions for positive valued data`

Many simple regressions for positive valued data

Description

Many simple regressions for positive valued data.

Usage

```
normlog.regs(y, x, tol = 1e-08, logged = FALSE, parallel = FALSE, maxiters = 100)
gammaregs(y, x, tol = 1e-07, logged = FALSE, maxiters = 100)
invgauss.regs(y, x, tol = 1e-08, logged = FALSE, maxiters = 100)
```

Arguments

y	The dependent variable, a numerical variable with non negative numbers for the Gamma and inverse Gaussian regressions. For the Gaussian with a log-link zero values are allowed.
x	A matrix with the indendent variables.
tol	The tolerance value to terminate the Newton-Raphson algorithm.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.
parallel	Do you want this to be executed in parallel or not. The parallel takes place in C++, therefore you do not have the option to set the number of cores.
maxiters	The maximum number of iterations that can take place in each regression.

Details

Many simple Gamma, inverse Gaussian or Gaussian regressions with a log-link are fitted.

Value

A matrix with the test statistic values and their relevant (logged) p-values.

Author(s)

Stefanos Fafalios and and Michail Tsagris

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

Zakariya Yahya Algamal and Intisar Ibrahim Allyas (2017). Prediction of blood lead level in maternal and fetal using generalized linear model. International Journal of Advanced Statistics and Probability, 5(2): 65-69.

See Also

`normlog.reg`, `score.glms`, `prop.regs`, `allbetas`

Examples

```
y <- abs( rnorm(100) )
x <- matrnorm(100, 100)
a <- normlog.regs(y, x)
b <- glm(y ~ x[, 1], family = gaussian(log) )
anova(b, test= "F")
a[1, ]
a2 <- gammaregs(y, x)
a3 <- invgauss.regs(y, x)
x <- NULL
```

`Many tests for the dispersion parameter in Poisson distribution`

Many tests for the dispersion parameter in Poisson distribution

---

Description

Many tests for the dispersion parameter in Poisson distribution.

Usage

```
colpoisdisp.tests(y, alternative = "either", logged = FALSE)
colpois.tests(y, logged = FALSE)
```

Arguments

y	A numerical matrix with count data, 0, 1,...
alternative	Do you want to test specifically for either over or underspirsion ("either"), overdispersion ("over") or undersispersion ("under")?
logged	Set to TRUE if you want the logarithm of the p-value.

Value

A matrix with two columns, the test statistic and the (logged) p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Yang Zhao, James W. Hardin, and Cheryl L. Addy. (2009). A score test for overdispersion in Poisson regression based on the generalized Poisson-2 model. Journal of statistical planning and inference 139(4):1514-1521.

Dimitris Karlis and Evdokia Xekalaki (2000). A Simulation Comparison of Several Procedures for Testing the Poisson Assumption. Journal of the Royal Statistical Society. Series D (The Statistician), 49(3): 355-382.

Bohning, D., Dietz, E., Schaub, R., Schlattmann, P. and Lindsay, B. (1994) The distribution of the likelihood ratio for mixtures of densities from the one-parameter exponential family. Annals of the Institute of Statistical Mathematics, 46(): 373-388.

See Also

poisson.mle, negbin.mle, poisson.anova, poisson.anovas, poisson_only

Examples

```
y <- matrix(rnbinom(100* 50, 10, 0.6), ncol = 50)
a1 <- colpoisdisp.tests(y, "over")
b1 <- colpois.tests(y)

y <- matrix(rpois(100* 50, 10), ncol = 50)
a2 <- colpoisdisp.tests(y, "either")
b2 <- colpois.tests(y)
y <- NULL
```

`Many two-way ANOVAs` *Many two-way ANOVAs*

Description

Many two-way ANOVAs.

Usage

```
twoway.anovas(y, x1, x2, interact = FALSE, logged = FALSE)
```

Arguments

`y`	A matrix with the data, where the rows denote the observations (and the two groups) and the columns are the variables.
`x1`	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Alternatively it can be a factor variable. This is the one factor.
`x2`	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Alternatively it can be a factor variable. This is the other factor.
`interact`	A boolean variable specifying whether you want to test for interaction.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The classical two-way ANOVA design is performed. Note that the design must be balanced. For every combination of values of the two factors, x1 and x2 the same number of observations must exist. If that's not the case, regression models must be used.

Value

A matrix with the test statistic and the p-value of each test.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

D.C. Montgomery (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons.

See Also

`ancovas`, `ftests`, `ttests`

Examples

```
y <- as.matrix( rnorm(125) )
x1 <- rep(1:5, 25)
x2 <- rep(1:5, each = 25)
x1 <- factor(x1)
x2 <- factor(x2)
res<-anova( lm(y ~ x1 + x2) )
res<-twoway.anovas(y, x1, x2)
res<-anova( lm(y ~ x1*x2) )
res<-twoway.anovas(y, x1, x2, interact = TRUE)
y <- matrnorm(125, 100)
a1 <- twoway.anovas(y, x1, x2)
a2 <- twoway.anovas(y, x1, x2, interact = TRUE)
y <- NULL
```

Many univariate generalised linear models

Many univariate generalised linear regressions

Description

It performs very many univariate generalised linear regressions.

Usage

```
univglms(y, x, oiko = NULL, logged = FALSE)

univglms2(y, x, oiko = NULL, logged = FALSE)
```

Arguments

y	The dependent variable. It can be a factor or a numerical variable with two values only (binary logistic regression), a discrete valued vector (count data) corresponding to a poisson regression or a numerical vector with continuous values (normal regression).
x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. For the "univglms" only continuous variables are allowed. You are advised to standardise the data before hand to avoid numerical overflow or similar issues. If you see NaN in the outcome, this might be the case. For the "univglms2" categorical variables are allowed and hence this accepts data.frames. In this case, the categorical variables must be given as factor variables, otherwise you might get wrong results.
oiko	This can be either "normal", "poisson", "quasipoisson" or "binomial". If you are not sure leave it NULL and the function will check internally. However, you might have discrete data (e.g. years of age) and want to perform many simple linear regressions. In this case you should specify the family.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.

Details

If you specify no family of distributions the function internally checkes the type of your data and decides on the type of regression to perform. The function is written in C++ and this is why it is very fast. It can accept thousands of predictor variables. It is usefull for univariate screening. We provide no p-value correction (such as fdr or q-values); this is up to the user.

Value

A matrix with the test statistic and the p-value for each predictor variable.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

logistic_only, poisson_only, allbetas, correls, regression

Examples

```
x <- matrnorm(100, 50)
y <- rbinom(100, 1, 0.6)   ## binary logistic regression
a1 <- univglms(y, x)
a2 <- glm(y ~ x[, 1], binomial)$deviance
a2 <- glm(y ~ 1, binomial)$null.dev - a2
x <- NULL
```

Many univariate simple linear regressions

Many univariate simple linear regressions

Description

It performs very many univariate simple linear regressions with or without categorical variables.

Usage

```
regression(x, y, poia = NULL, logged = FALSE)
```

Arguments

x	A data.frame or a matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. A data frame is expected if you have categorical predictor variables. If you only have continuous predictor variables you should the function allbetas instead as it is faster.
y	The dependent variable; a numerical vector.
poia	If the "x" is a data.frame and you know the indices of the columns which are categorical variables supply it here.
logged	Do you want the logarithm of the p-values be returned? The default value is FALSE.

Details

Some parts of the function will be transferred in C++. It can accept thousands of predictor variables. It is usefull for univariate screening. We provide no p-value correction (such as fdr or q-values); this is up to the user.

Value

A matrix with two columns, the test statistic value and its corresponding (logged) p-value.

Author(s)

Manos Papadakis <papadakm95@gmail.com>

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

univglms, allbetas, correls, univglms, mvbetas

Examples

```
y <- rnorm(150)
a <- regression(iris, y)
a
summary(lm(y ~ iris[, 5]) )  ## check the F-test
```

`Many univariate simple logistic and Poisson regressions`
Many univariate simple binary logistic regressions

Description

It performs very many univariate simple binary logistic regressions.

Usage

```
logistic_only(x, y, tol = 1e-09, b_values = FALSE)
poisson_only(x, y, tol = 1e-09, b_values = FALSE)
```

Arguments

`x`	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. Currently only continuous variables are allowed.
`y`	The dependent variable; a numerical vector with two values (0 and 1) for the logistic regressions and a vector with many discrete values (count data) for the Poisson regressions.
`tol`	The tolerance value to terminate the Newton-Raphson algorithm.
`b_values`	Do you want the values of the coefficients returned? If yes, set this to TRUE.

Details

The function is written in C++ and this is why it is very fast. It can accept thousands of predictor variables. It is usefull for univariate screening. We provide no p-value correction (such as fdr or q-values); this is up to the user.

Value

A vector with the deviance of each simple binayr logistic regression model for each predictor variable.

Author(s)

Manos Papadakis <papadakm95@gmail.com>

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

univglms, score.glms, prop.regs, quasi.poisson_only, allbetas, correls, regression

Examples

```
## 300 variables, hence 300 univariate regressions are to be fitted
x <- matrix( rnorm(100 * 300), ncol = 300 )

## 100 observations in total
y <- rbinom(100, 1, 0.6)   ## binary logistic regression
a1 <- logistic_only(x, y)

a2 <- glm(y ~ x[, 1], binomial)$deviance
a2 <- as.vector(a2)

y <- rpois(100, 10)
a1 <- poisson_only(x, y)

a1 <- x <- NULL
```

Many univariate simple quasi poisson regressions

Many univariate simple poisson regressions

Description

It performs very many univariate simple poisson regressions.

Usage

```
quasi.poisson_only(x, y, tol = 1e-09, maxiters = 100)
```

Arguments

x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. Currently only continuous variables are allowed.
y	The dependent variable; a numerical vector with many discrete values (count data).
maxiters	The maximum number of iterations after which the Newton-Raphson algorithm is terminated.
tol	The tolerance value to terminate the Newton-Raphson algorithm.

Details

The function is written in C++ and this is why it is very fast. It can accept thousands of predictor variables. It is usefull for univariate screening. We provide no p-value correction (such as fdr or q-values); this is up to the user.

Value

A matrix with the deviance and the estimated phi parameter (dispersion parameter) of each simple poisson regression model for each predictor variable.

Author(s)

Manos Papadakis <papadakm95@gmail.com> and Stefanos Fafalios <stefanosfafalios@gmail.com>

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>, Manos Papadakis <papadakm95@gmail.com> and Stefanos Fafalios <stefanosfafalios@gmail.com>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

poisson_only univglms, logistic_only, allbetas, regression

Examples

```
## 200 variables, hence 200 univariate regressions are to be fitted
x <- matrix( rnorm(100 * 200), ncol = 200 )
y <- rpois(100, 10)
poisson_only(x, y)
b1 <- poisson_only(x, y)
b2 <- quasi.poisson_only(x, y)

b1<-b2<-x<-y<-NULL
```

Many Welch's F-tests *Many Welch's F-tests*

Description

Many Welch's F-tests.

Usage

```
colanovas(y, x, logged = FALSE)
```

Arguments

y	A numerical vector with the dependent variable.
x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. This must be a matrix with the categorical variables as numbers, starting from 1. Welch's F-test is performed for each variable.
logged	A boolean variable; it will return the logarithm of the pvalue if set to TRUE.

Details

For each categorical variable in the x matrix Welch's F test is performed. This is the opposie of ftests,where there are many dependent variables and one categorical variable.

Value

A matrix with the test statistic and the p-value for each predictor variable.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Draper, N.R. and Smith H. (1988). Applied regression analysis. New York, Wiley, 3rd edition.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

regression, ftests, allbetas, correls

Examples

```
y <-  rnorm(100)
x <- matrix( rbinom(100 * 50, 2, 0.5) + 1 , ncol = 50)
a <- colanovas(y, x)
x <- NULL
```

Match *Match*

Description

Return the positions of its first argument that matches in its second.

Usage

```
Match(x,key=NULL)
```

Arguments

x	A numeric vector.
key	The value/vector for searching in vector x. For now let it NULL. **dont't use it!**.

Details

This function implements the R's \"match\" function. This version basicaly calculates the match(x,sort(unique(x))) for now. Do not use the argument key!

Value

Returns the position/positions of the given key/keys in the x vector.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

`match`

Examples

```
y <- rnorm(100)
a <- Match(y)
b <-50
all.equal(as.vector(a),as.vector(b))
```

`Matrix multiplication` *Matrix multiplication, Cross and Tcross product*

Description

Matrix multiplication, Cross and Tcross product.

Usage

```
mat.mult(x, y)
Crossprod(x,y)
Tcrossprod(x,y)
```

Arguments

`x`	A numerical matrix.
`y`	A numerical matrix.

Details

The functions performs matrix multiplication, croos product and transpose cross product. There are faster(!) than R's function for large matrices. Depending on the computer, maybe higher dimensions are required for the function to make a difference. The function runs in parallel in C++.

Value

A matrix, the result of the matrix multiplication.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

transpose, colsums

Examples

```
x <- matrnorm(100, 100)
y <- matrnorm(100, 100)
#a <- x %*% y
#b <- mat.mult(x, y) #Always execute in parallel
#b <- Crossprod(x, y) #Always execute in parallel
#b <- Tcrossprod(x, y) #Always execute in parallel
x <- NULL
y <- NULL
b <- NULL
```

`Matrix with all pairs of t-tests`

Matrix with all pairs of t-tests

Description

Matrix with all pairs of t-tests.

Usage

```
alltttests(x, y = NULL, ina, logged = FALSE)
ttests.pairs(x, logged = FALSE)
```

Arguments

x	A numerical matrix with the data.
y	For the case of "all.tests", if you have the second group or sample provide it here, otherwise leave it NULL. For the case of "ttests.pairs" this is not required.
ina	If you have the data in one matric then provide this indicator variable separating the samples. This numerical vector must contain 1s and 2s only as values. For the case of "ttests.pairs" this is not required.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The function does all the pairwise t-tests assuming unequal variances (Welch's t-test). The "all.ttests" does all the pairs formed by "cutting" the matrices x and y in two and everything between them. The "ttests.pairs" accepts a matrix x and does all the pairs of t-tests. This is similar to the correlation matrix style.

Value

A list including:

`stat`	A matrix with t-test statistic for each pair of variables.
`pvalue`	A matrix with the corresponding p-values.
`dof`	A matrix with the relevant degrees of freedom.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`ttests`, `ftests`, `ttest`, `g2Test_univariate`

Examples

```
x <- as.matrix( iris[1:100, 1:4] )
ina <- as.numeric(iris[1:100, 5])
a <- allttests(x, ina = ina)
b <- ttests.pairs(x)  ## less tests
```

`Matrix with G-square tests of indepedence`

Matrix with G-square tests of indepdence

Description

Matrix with G-square tests of indepdence with and without permutations.

Usage

```
g2Test_univariate(data, dc)
g2Test_univariate_perm(data, dc, nperm)
chi2Test_univariate(data, dc)
```

Arguments

data	A numerical matrix with the data. **The minimum must be 0, otherwise the function can crash or will produce wrong results**. The data must be consecutive numbers.
dc	A numerical value equal to the number of variables (or columns of the data matrix) indicating the number of distinct, unique values (or levels) of each variable. Make sure you give the correct numbers here, otherwise the degrees of freedom will be wrong.
nperm	The number of permutations. The permutations test is slower than without permutations and should be used with small sample sizes or when the contigency tables have zeros. When there are few variables, R's "chisq.test" function is faster, but as the number of variables increase the time difference with R's procedure becomes larger and larger.

Details

The function does all the pairwise G^2 test of independence and gives the position inside the matrix. The user must build the associations matrix now, similarly to the correlation matrix. See the examples of how to do that. The p-value is not returned, we live this to the user. See the examples of how to obtain it.

Value

A list including:

statistic	The G^2 or chi^2 test statistic for each pair of variables.
pvalue	This is returned when you have selected the permutation based G^2 test.
x	The row or variable of the data.
y	The column or variable of the data.
df	The degrees of freedom of each test.

Author(s)

Giorgos Borboudakis. The permutation version used a C++ code by John Burkardt.

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Tsagris M. (2017). Conditional independence test for categorical data using Poisson log-linear model. Journal of Data Science, 15(2):347-356.

Tsamardinos, I., & Borboudakis, G. (2010). Permutation testing improves Bayesian network learning. In Joint European Conference on Machine Learning and Knowledge Discovery in Databases (pp. 322-337). Springer Berlin Heidelberg

See Also

g2Test, g2Test_perm, correls, univglms

Examples

```
nvalues <- 3
nvars <- 10
nsamples <- 2000
data <- matrix( sample( 0:(nvalues - 1), nvars * nsamples, replace = TRUE ), nsamples, nvars )
dc <- rep(nvalues, nvars)
g2Test_univariate(data = data, dc = dc)
a <- g2Test_univariate(data = data, dc = dc)
pval <- pchisq(a$statistic, a$df, lower.tail = FALSE)

g <- matrix(0, nvars, nvars)
g[ cbind(a$x, a$y) ] <- a$statistic
g <- g + t(g)
diag(g) <- 0
## g ## matrix of G^2 test statistics

g<-a<-dc<-data<-NULL
```

`Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices`

Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices

---

Description

Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices.

Usage

```
colPmax(x, y)
colPmin(x, y)
Pmax(x, y,na.rm = FALSE)
Pmin(x, y,na.rm = FALSE)
Pmin_Pmax(x, y,na.rm = FALSE)
```

Arguments

x	A numerical vector or matrix with numbers.
y	A numerical vector with numbers.
na.rm	TRUE or FAlSE for remove NAs if exists.

Details

The parallel minima or maxima are returned. This are the same as the base functions pmax and pmin.

Value

A numerical vector/matrix with numbers, whose length is equal to the length of the initital matrices containing the maximum or minimum between each pair.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Sort, colMins, colMaxs, colMedians

Examples

```
x <- matrix(rnorm(100),10,10)
y <- matrix(rnorm(100),10,10)
res<-colPmax(x, y)
res<-colPmin(x, y)
x<-y<-NULL
```

Minimum and maximum *Minimum and maximum of a vector*

Description

Minimum and maximum of a vector.

Usage

```
min_max(x,index=FALSE, percent = FALSE)
```

Arguments

x	A numerical vector with data. NAs are handled naturally.
index	A boolean value for the indices of the minimum and the maximum value.
percent	A boolean value for the percent of the positive and negative numbers.

Value

A vector with the relevant values, min and max.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, rowMaxs, nth, colrange, colMedians,colSort, rowSort

Examples

```
x <- rnorm(100 * 500)
s1 <- min_max(x)
s2 <- c(min(x), max(x))
```

`Minimum and maximum frequencies`

Minimum and maximum frequencies of a vector

Description

Minimum and maximum frequencies of a vector.

Usage

```
freq.min(x,na.rm = FALSE)
freq.max(x,na.rm = FALSE)
```

Arguments

`x`	A numerical/integer vector with data but without NAs.
`na.rm`	TRUE or FAlSE for remove NAs if exists.

Details

Those functions are the same with max(table(x) or min(table(x)) but with one exception. freq.min and freq.max will return also which value has the minimum/maximum frequency. More Efficient than max(table(x) or min(table(x)).

Value

A vector with 2 values, the value with minimum/maximum frequency and the frequency.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Marios Dimitriadis <kmdimitriadis@gmail.com>.

See Also

rowMins, rowMaxs, nth, colrange, colMedians,colSort, rowSort

Examples

```
x <- rnorm(100)
f1 <- freq.min(x)
f2 <- freq.max(x)
# f1r <- min(table(x))
# f2r <- max(table(x))
# f1[2]==f1r ## the frequencies are the same
# f2[2]==f2r ## the frequencies are the same
```

`MLE for multivariate discrete data`

MLE for multivariate discrete data

Description

MLE for multivariate discrete data.

Usage

```
multinom.mle(x)
dirimultinom.mle(x, tol = 1e-07)
colpoisson.mle(x)
colgeom.mle(x, type = 1)
```

Arguments

`x`	A matrix with discrete valued non negative data.
`tol`	the tolerance level to terminate the Newton-Raphson algorithm for the Dirichlet multinomial distribution.
`type`	This is for the geometric distribution only. Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1.

Details

For the Poisson and geometric distributions we simply fit independent Poisson and geometric distributions respectively.

Value

A list including:

`loglik`	A vector with the value of the maximised log-likelihood.
`param`	A vector of the parameters.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Johnson Norman L., Kotz Samuel and Balakrishnan (1997). Discrete Multivariate Distributions. Wiley

Minka Thomas (2012). Estimating a Dirichlet distribution. Technical report.

See Also

poisson.mle, zip.mle, ztp.mle, negbin.mle, poisson.nb

Examples

```
x <- t( rmultinom(1000, 20, c(0.4, 0.5, 0.1) ) )
res<-multinom.mle(x)
res<-colpoisson.mle(x)
x <- NULL
```

`MLE of (hyper-)spherical distributions`

MLE of (hyper-)spherical distributions

Description

MLE of (hyper-)spherical distributions.

Usage

```
vmf.mle(x, tol = 1e-07)
multivmf.mle(x, ina, tol = 1e-07, ell = FALSE)
acg.mle(x, tol = 1e-07)
iag.mle(x, tol = 1e-07)
```

Arguments

x	A matrix with directional data, i.e. unit vectors.
ina	A numerical vector with discrete numbers starting from 1, i.e. 1, 2, 3, 4,... or a factor variable. Each number denotes a sample or group. If you supply a continuous valued vector the function will obviously provide wrong results.
ell	This is for the multivmf.mle only. Do you want the log-likelihood returned? The default value is TRUE.
tol	The tolerance value at which to terminate the iterations.

Details

For the von Mises-Fisher, the normalised mean is the mean direction. For the concentration parameter, a Newton-Raphson is implemented. For the angular central Gaussian distribution there is a constraint on the estimated covariance matrix; its trace is equal to the number of variables. An iterative algorithm takes place and convergence is guaranteed. Newton-Raphson for the projected normal distribution, on the sphere, is implemented as well. Finally, the von Mises-Fisher distribution for groups of data is also implemented.

Value

For the von Mises-Fisher a list including:

`loglik`	The maximum log-likelihood value.
`mu`	The mean direction.
`kappa`	The concentration parameter.

For the multi von Mises-Fisher a list including:

`loglik`	A vector with the maximum log-likelihood values if ell is set to TRUE. Otherwise NULL is returned.
`mi`	A matrix with the group mean directions.
`ki`	A vector with the group concentration parameters.

For the angular central Gaussian a list including:

`iter`	The number if iterations required by the algorithm to converge to the solution.
`cova`	The estimated covariance matrix.

For the spherical projected normal a list including:

`iters`	The number of iteration required by the Newton-Raphson.
`mesi`	A matrix with two rows. The first row is the mean direction and the second is the mean vector. The first comes from the second by normalising to have unit length.
`param`	A vector with the elements, the norm of mean vector, the log-likelihood and the log-likelihood of the spherical uniform distribution. The third value helps in case you want to do a log-likleihood ratio test for uniformity.

Author(s)

Michail Tsagris R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Mardia, K. V. and Jupp, P. E. (2000). Directional statistics. Chicester: John Wiley & Sons.

Sra, S. (2012). A short note on parameter approximation for von Mises-Fisher distributions: and a fast implementation of Is(x). Computational Statistics, 27(1): 177–190.

Tyler D. E. (1987). Statistical analysis for the angular central Gaussian distribution on the sphere. Biometrika 74(3): 579-589.

Paine P.J., Preston S.P., Tsagris M and Wood A.T.A. (2017). An Elliptically Symmetric Angular Gaussian Distribution. Statistics and Computing (To appear).

See Also

racg, vm.mle, rvmf

Examples

```
m <- c(0, 0, 0, 0)
s <- cov(iris[, 1:4])
#x <- racg(100, s)
#mod <- acg.mle(x)
#res<-cov2cor(mod$cova)  ## estimated covariance matrix turned into a correlation matrix
#res<-cov2cor(s)  ## true covariance matrix turned into a correlation matrix
#res<-vmf.mle(x)
#x <- rbind( rvmf(100,rnorm(4), 10), rvmf(100,rnorm(4), 20) )
#a <- multivmf.mle(x, rep(1:2, each = 100) )
```

MLE of continuous univariate distributions defined on the positive line

MLE of continuous univariate distributions defined on the positive line

---

Description

MLE of continuous univariate distributions defined on the positive line.

Usage

```
gammamle(x, tol = 1e-09)
chisq.mle(x, tol = 1e-09)
weibull.mle(x, tol = 1e-09, maxiters = 100)
lomax.mle(x, tol = 1e-09)
foldnorm.mle(x, tol = 1e-09)
betaprime.mle(x, tol = 1e-09)
logcauchy.mle(x, tol = 1e-09)
loglogistic.mle(x, tol = 1e-09)
halfnorm.mle(x)
invgauss.mle(x)
lognorm.mle(x)
pareto.mle(x)
expmle(x)
exp2.mle(x)
maxboltz.mle(x)
rayleigh.mle(x)
normlog.mle(x)
lindley.mle(x)
```

Arguments

x	A vector with positive valued data (zeros are not allowed).
tol	The tolerance level up to which the maximisation stops; set to 1e-09 by default.
maxiters	The maximum number of iterations the Newton-Raphson will perform.

Details

Instead of maximising the log-likelihood via a numerical optimiser we have used a Newton-Raphson algorithm which is faster. See wikipedia for the equations to be solved. For the t distribution we need the degrees of freedom and estimate the location and scatter parameters. If you want to to fit an inverse gamma distribution simply do "gamma.mle(1/x)". The log-likelihood and the parameters are for the inverse gamma.

The "normlog.mle" is simply the normal distribution where all values are positive. Note, this is not log-normal. It is the normal with a log link. Similarly to the inverse gaussian distribution where the mean is an exponentiated. This comes from the GLM theory.

Value

Usually a list with three elements, but this is not for all cases.

iters	The number of iterations required for the Newton-Raphson to converge.
loglik	The value of the maximised log-likelihood.
param	The vector of the parameters.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Kalimuthu Krishnamoorthy, Meesook Lee and Wang Xiao (2015). Likelihood ratio tests for comparing several gamma distributions. Environmetrics, 26(8):571-583.

N.L. Johnson, S. Kotz and N. Balakrishnan (1994). Continuous Univariate Distributions, Volume 1 (2nd Edition).

N.L. Johnson, S. Kotz a nd N. Balakrishnan (1970). Distributions in statistics: continuous univariate distributions, Volume 2.

Tsagris M., Beneki C. and Hassani H. (2014). On the folded normal distribution. Mathematics, 2(1):12-28.

Sharma V. K., Singh S. K., Singh U. and Agiwal V. (2015). The inverse Lindley distribution: a stress-strength reliability model with application to head and neck cancer data. Journal of Industrial and Production Engineering, 32(3): 162-173.

You can also check the relevant wikipedia pages for these distributions.

See Also

zip.mle, normal.mle, beta.mle

Examples

```
x <- rgamma(100, 3, 4)
for (i in 1:20) gammamle(x)
## for (i in 1:20) fitdistr(x,"gamma")
#a <- glm(x ~ 1, gaussian(log) )
res<-normlog.mle(x)
```

MLE of continuous univariate distributions defined on the real line

MLE of continuous univariate distributions defined on the real line

---

Description

MLE of continuous univariate distributions defined on the real line.

Usage

```
normal.mle(x)
gumbel.mle(x, tol = 1e-09)
cauchy.mle(x, tol = 1e-09)
logistic.mle(x, tol = 1e-07)
ct.mle(x, tol = 1e-09)
tmle(x, v = 5, tol = 1e-08)
wigner.mle(x, tol = 1e-09)
laplace.mle(x)
```

Arguments

x	A numerical vector with data.
v	The degrees of freedom of the t distribution.
tol	The tolerance level up to which the maximisation stops set to 1e-09 by default.

Details

Instead of maximising the log-likelihood via a numerical optimiser we have used a Newton-Raphson algorithm which is faster. See wikipedia for the equation to be solved. For the t distribution we need the degrees of freedom and estimate the location and scatter parameters.

The Cauchy is the t distribution with 1 degree of freedom. If you want to fit such a distribution used the cauchy.mle and not the t.mle with 1 degree of freedom as it's faster. The Laplace distribution is also called double exponential distribution.

The wigner.mle refers to the wigner semicircle distribution.

Value

Usually a list with three elements, but this is not for all cases.

`iters`	The number of iterations required for the Newton-Raphson to converge.
`loglik`	The value of the maximised log-likelihood.
`param`	The vector of the parameters.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Johnson, Norman L. Kemp, Adrianne W. Kotz, Samuel (2005). Univariate Discrete Distributions (third edition). Hoboken, NJ: Wiley-Interscience.

https://en.wikipedia.org/wiki/Wigner_semicircle_distribution

See Also

`zip.mle`, `gammamle`, `vm.mle`

Examples

```
x <- rt(1000,10)
a <- ct.mle(x)
res<-tmle(x, v = a$nu)
res<-cauchy.mle(x)
res<-normal.mle(x)
res<-logistic.mle(x)
res<-gumbel.mle(x)
```

`MLE of count data (univariate discrete distributions)`

MLE of count data

Description

MLE of count data.

Usage

```
zip.mle(x, tol = 1e-09)
ztp.mle(x, tol = 1e-09)
negbin.mle(x, type = 1, tol = 1e-09)
binom.mle(x, N = NULL, tol = 1e-07)
borel.mle(x)
geom.mle(x, type = 1)
logseries.mle(x, tol = 1e-09)
poisson.mle(x)
betageom.mle(x, tol = 1e-07)
betabinom.mle(x, N, tol = 1e-07)
```

Arguments

x	A vector with discrete valued data.
type	This argument is for the negative binomial and the geometric distribution. In the negative binomial you can choose which way your prefer. Type 1 is for smal sample sizes, whereas type 2 is for larger ones as is faster. For the geometric it is related to its two forms. Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1.
N	This is for the binomial distribution only, specifying the total number of successes. If NULL, it is sestimated by the data. It can also be a vector of successes.
tol	The tolerance level up to which the maximisation stops set to 1e-09 by default.

Details

Instead of maximising the log-likelihood via a numerical optimiser we used a Newton-Raphson algorithm which is faster.

See wikipedia for the equation to be solved in the case of the zero inflated distribution. https://en.wikipedia.org/wiki/Zero-inflated_model. In order to avoid negative values we have used link functions, log for the $lambda$ and logit for the π as suggested by Lambert (1992). As for the zero truncated Poisson see https://en.wikipedia.org/wiki/Zero-truncated_Poisson_distribution.

zip.mle is for the zero inflated Poisson, whereas ztp.mle is for the zero truncated Poisson distribution.

Value

The following list is not inclusive of all cases. Different functions have different names. In general a list including:

mess	This is for the negbin.mle only. If there is no reason to use the negative binomial distribution a message will appear, otherwise this is NULL.
iters	The number of iterations required for the Newton-Raphson to converge.
loglik	The value of the maximised log-likelihood.
prob	The probability parameter of the distribution. In some distributions this argument might have a different name. For example, param in the zero inflated Poisson.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Lambert Diane (1992). Zero-Inflated Poisson Regression, with an Application to Defects in Manufacturing. Technometrics. 34 (1): 1-14

Johnson Norman L., Kotz Samuel and Kemp Adrienne W. (1992). Univariate Discrete Distributions (2nd ed.). Wiley

See Also

poisson_only, colrange

Examples

```
x <- rpois(100, 2)
res<-zip.mle(x)
res<-poisson.mle(x)
## small difference in the two log-likelihoods as expected.

x <- rpois(100, 10)
x[x == 0 ] <- 1
res<-ztp.mle(x)
res<-poisson.mle(x)
## significant difference in the two log-likelihoods.

x <- rnbinom(100, 10, 0.6)
res<-poisson.mle(x)
res<-negbin.mle(x)
```

MLE of distributions defined in the (0, 1) interval

MLE of distributions defined in the (0, 1) interval

Description

MLE of distributions defined in the (0, 1) interval.

Usage

```
beta.mle(x, tol = 1e-09)
ibeta.mle(x, tol = 1e-09)
logitnorm.mle(x)
hsecant01.mle(x, tol = 1e-09)
```

Arguments

x	A numerical vector with proportions, i.e. numbers in (0, 1) (zeros and ones are not allowed).
tol	The tolerance level up to which the maximisation stops.

Details

Maximum likelihood estimation of the parameters of the beta distribution is performed via Newton-Raphson. The distributions and hence the functions does not accept zeros. "logitnorm.mle" fits the logistic normal, hence no nwewton-Raphson is required and the "hypersecant01.mle" uses the golden ratio search as is it faster than the Newton-Raphson (less calculations)

Value

A list including:

iters	The number of iterations required by the Newton-Raphson.
loglik	The value of the log-likelihood.
param	The estimated parameters. In the case of "hypersecant01.mle" this is called "theta" as there is only one parameter.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

See Also

diri.nr2,

Examples

```
x <- rbeta(100, 1, 4)
res<-beta.mle(x)
res<-hsecant01.mle(x)
res<-logitnorm.mle(x)

x[sample(1:100, 5)] <- 0
res<-ibeta.mle(x)
```

MLE of some circular distributions
MLE of some circular distributions

Description

MLE of some circular distributions.

Usage

```
vm.mle(x, tol = 1e-09)
spml.mle(x, tol = 1e-09, maxiters = 100)
wrapcauchy.mle(x, tol = 1e-09)
```

Arguments

x	A numerical vector with the circular data. They must be expressed in radians. For the "spml.mle" this can also be a matrix with two columns, the cosinus and the sinus of the circular data.
tol	The tolerance level to stop the iterative process of finding the MLEs.
maxiters	The maximum number of iterations to implement.

Details

The parameters of the von Mises, the bivariate angular Gaussian and wrapped Cauchy distributions are estimated. For the Wrapped Cauchy, the iterative procedure described by Kent and Tyler (1988) is used. As for the von Mises distribution, we use a Newton-Raphson to estimate the concentration parameter. The angular Gaussian is described, in the regression setting in Presnell et al. (1998).

Value

A list including:

iters	The iterations required until convergence. This is returned in the wrapped Cauchy distribution only.
loglik	The value of the maximised log-likelihood.
param	A vector consisting of the estimates of the two parameters, the mean direction for both distributions and the concentration parameter kappa and the rho for the von Mises and wrapped Cauchy respectively.
gamma	The norm of the mean vector of the angualr Gaussian distribution.
mu	The mean vector of the angular Gaussian distribution.

Author(s)

Michail Tsagris and Stefanos Fafalios

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Stefanos Fafalios <stefanosfafalios@gmail.com>

References

Mardia K. V. and Jupp P. E. (2000). Directional statistics. Chicester: John Wiley & Sons.

Sra S. (2012). A short note on parameter approximation for von Mises-Fisher distributions: and a fast implementation of Is(x). Computational Statistics, 27(1): 177-190.

Presnell Brett, Morrison Scott P. and Littell Ramon C. (1998). Projected multivariate linear models for directional data. Journal of the American Statistical Association, 93(443): 1068-1077.

Kent J. and Tyler D. (1988). Maximum likelihood estimation for the wrapped Cauchy distribution. Journal of Applied Statistics, 15(2): 247–254.

See Also

`vmf.mle`, `rvonmises`, `rvmf`

Examples

```
y <- rcauchy(100, 3, 1)
x <- y
res<-vm.mle(x)
res<-spml.mle(x)
res<-wrapcauchy.mle(x)
x <- NULL
```

`MLE of the inverted Dirichlet distribution`

MLE of the inverted Dirichlet distribution

Description

MLE of the inverted Dirichlet distribution.

Usage

```
invdir.mle(x, tol = 1e-07)
```

Arguments

`x`	A matrix with strictly positive data (no zeros are allowed).
`tol`	The tolerance level up to which the maximisation stops.

Details

Maximum likelihood estimation of the parameters of the inverted is performed via Newton-Raphson. We took the initial values suggested by Bdiri T. and Bouguila N. (2012) and modified them a bit.

Value

A list including:

`iters`	The number of iterations required by the Newton Raphson.
`loglik`	The value of the log-likelihood.
`param`	The estimated parameters.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

Bdiri T. and Bouguila N. (2012). Positive vectors clustering using inverted Dirichlet finite mixture models. Expert Systems with Applications, 39(2): 1869-1882.

See Also

`diri.nr2`, `multinom.mle`

Examples

```
x <- as.matrix(iris[, 1:4])
for(i in 1:10) invdir.mle(x)
res<-invdir.mle(x)
```

`MLE of the multivariate (log-) normal distribution`

MLE of the multivariate (log-) normal distribution

Description

MLE of the multivariate (log-) normal distribution.

Usage

```
mvnorm.mle(x)
mvlnorm.mle(x)
```

Arguments

`x`	A matrix with numerical data.

Details

The mean vector, covariance matrix and the value of the log-likelihood of the multivariate normal or log-normal distribution is calculated. For the log-normal distribution we also provide the expected value and the covariance matrix.

Value

A list including:

`loglik`	The log-likelihood multivariate distribution.
`mu`	The mean vector.
`sigma`	The covariance matrix.
`m`	The expected mean vector of the multivariate log-normal distribution.
`s`	The expected covariance matrix of the multivariate log-normal distribution.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Kotz, S., Balakrishnan, N., & Johnson, N. L. (2004). Continuous multivariate distributions, Volume 1: Models and applications (Vol. 1). John wiley & sons.

http://isi.cbs.nl/iamamember/CD2/pdf/329.PDF

https://en.wikipedia.org/wiki/Log-normal_distribution#Multivariate_log-normal

See Also

`multinom.mle`, `dmvnorm`, `gaussian.nb`

Examples

```
x <- matrnorm(100, 4)
res<-mvnorm.mle(x)
x <- NULL
```

`MLE of the multivariate t distribution`

MLE of the multivariate t distribution

Description

MLE of the multivariate t distribution.

Usage

```
mvt.mle(x, v = 5, tol = 1e-07)
```

Arguments

`x`	A matrix with numerical data.
`v`	The degrees of freedom. Must be a positive number, greater than zero.
`tol`	The tolerance value to terminate the EM algorithm.

Details

The location vector, scatter matrix and the value of the log-likelihood is calculated.

Value

A list including:

`iters`	The number of iterations required for the EM algorihm to converge.
`loglik`	The value of the maximised log-likelihood.
`location`	The location vector.
`scatter`	The scatter matrix.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Nadarajah S. and Kotz S. (2008). Estimation methods for the multivariate t distribution. Acta Applicandae Mathematicae, 102(1):99-118.

See Also

`mvnorm.mle`, `dmvnorm`, `gaussian.nb`

Examples

```
x <- matrnorm(100, 4)
#res<-mvnorm.mle(x)
#res<-mvt.mle(x, v = 5)
#res<-mvt.mle(x, v = 100)
```

`MLE of the ordinal model without covariates`

MLE of the ordinal model without covariates

Description

MLE of the ordinal model without covariates.

Usage

```
ordinal.mle(y, link = "logit")
```

Arguments

`y`	A numerical vector with values 1, 2, 3,..., not zeros, or an ordered factor.
`link`	This can either be "logit" or "probit". It is the link function to be used.

Details

Maximum likelihood of the ordinal model (proportional odds) is implemented. See for example the "polr" command in R or the examples.

Value

A list including:

`loglik`	The log-likelihood of the model.
`a`	The intercepts (threshold coefficients) of the model.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Agresti, A. (2002) Categorical Data. Second edition. Wiley.

See Also

`beta.mle`, `diri.nr2`

Examples

```
y <- factor( rbinom(100,3,0.5), ordered = TRUE )
res<-ordinal.mle(y)
res<-ordinal.mle(y, link = "probit")
```

MLE of the tobit model

MLE of the tobit model

Description

MLE of the tobit model.

Usage

```
tobit.mle(y, tol = 1e-09)
```

Arguments

y	A vector with positive valued data and zero values. If there are no zero values, a simple normal model is fitted in the end.
tol	The tolerance level up to which the maximisation stops; set to 1e-09 by default.

Details

The tobin model is useful for (univariate) positive data with left censoring at zero. There is the assumption of a latent variable. Tthe values of that variable which are positive concide with the observed values. If some values are negative, they are left censored and the observed values are zero. Instead of maximising the log-likelihood via a numerical optimiser we have used a Newton-Raphson algorithm which is faster.

Value

A list with three elements including

iters	The number of iterations required for the Newton-Raphson to converge.
loglik	The value of the maximised log-likelihood.
param	The vector of the parameters.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Tobin James (1958). Estimation of relationships for limited dependent variables. Econometrica. 26(1):24–36.

https://en.wikipedia.org/wiki/Tobit_model

See Also

gammamle, normal.mle

Examples

```
x <- rnorm(300, 3, 5)
x[ x < 0 ] <- 0   ## left censoring. Values below zero become zero
for (i in 1:50) tobit.mle(x)
```

`Moment and maximum likelihood estimation of variance components`
Moment and maximum likelihood estimation of variance components

---

Description

Moment and maximum likelihood estimation of variance components.

Usage

```
rint.mle(x, ina, ranef = FALSE, tol = 1e-09, maxiters = 100)
varcomps.mom(x, ina)
varcomps.mle(x, ina, tol = 1e-09)
```

Arguments

x	A numerical vector with the data.
ranef	Should the random effects be returned as well? The default value is FALSE.
ina	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Be careful, the function is desinged to accept numbers greater than zero. Alternatively it can be a factor variable.
tol	The tolerance level to terminate the golden ratio search. the default value is 10^(-9).
maxiters	The maximum number of iterations Newton-Raphson will implement.

Details

Note that the "varcomps.mle" and "varcomp.mom" work for **balanced designs only**, i.e. for each subject the same number of measurements have been taken. The "rint.mle" works for both the balanced and unbalanced designs.

The variance components, the variance of the between measurements and the variance of the within are estimated using moment estimators. The "colvarcomsp.mom" is the moment analogue of a random effects model which uses likelihood estimation ("colvarcomps.mle"). It is much faster, but can give negative variance of the random effects, in which case it becomes zero.

The maximum likelihood version is a bit slower (try youselves to see the difference), but statistically speaking is to be preferred when small samples are available. The reason why it is only a little bit slower and not a lot slower as one would imagine is because we are using a closed formula to calculate the two variance components (Demidenko, 2013, pg. 67-69). Yes, there are closed formulas for linear mixed models.

Value

For the "varcomps.mom": A vector with 5 elemets, The MSE, the estimate of the between variance, the variance components ratio and a 95% confidence for the ratio.

For the "varcomps.mle": a list with a single component called "info". That is a matrix with 3 columns, The MSE, the estimate of the between variance and the log-likelihood value. **If ranef = TRUE** a list including "info" and an extra component called "ranef" containing the random effects. It is a matrix with the same number of columns as the data. Each column contains the randome effects of each variable.

Author(s)

Michail Tsagris and Manos Papadakis.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Montgomery D.C. (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons.

Davis C.S. (2002). Statistical methods for the analysis of repeated measures. New York: Springer-Verlag.

Demidenko E. (2013). Mixed Models: Theory and Applications with R 2nd Edition). New Jersey: John Wiley & Sons (Excellent book).

See Also

`colvarcomps.mle`, `rint.reg`, `rint.regbx`

Examples

```
## example from Montgomery, pages 514-517
x <- c(98,97,99,96,91,90,93,92,96,95,97,95,95,96,99,98)
ina <- rep(1:4, each = 4)
res<-varcomps.mom(x, ina)
res<-varcomps.mle(x, ina)
```

`Multi-sample tests for vectors`

Multi-sample tests for vectors

Description

Multi-sample tests for vectors.

Usage

```
ftest(x, ina, logged = FALSE)
anova1(x, ina, logged = FALSE)
kruskaltest(x, ina, logged = FALSE)
var2test(x, y, alternative = "unequal", logged = FALSE)
mcnemar(x, y, logged = FALSE)
ttest2(x, y, alternative = "unequal", paired = FALSE, logged = FALSE)
cqtest(x, treat, block, logged = FALSE)
block.anova(x, treat, block, logged = FALSE)
twoway.anova(y, x1, x2, interact = FALSE, logged = FALSE)
```

Arguments

`x`	A numerical vector with the data.
`y`	A numerical vector with the data.
`ina`	A numerical vector with 1s, 2s, 3s and so one indicating the two groups. Be careful, the function is desinged to accept numbers greater than zero. Alternatively it can be a factor variable.
`paired`	This is for the two sample t-test only and is TRUE or FALSE specifying whether the two samples are paired or not.
`alternative`	This can either be "unequal", "greater" or "less".
`treat`	In the case of the blocking ANOVA and Cochran's Q test, this argument plays the role of the "ina" argument.
`block`	This item (in the blocking ANOVA and Cochran's Q test) denotes the subjects which are the same. Similarly to "ina" a numeric vector with 1s, 2s, 3s and so on.
`x1`	The first factor in the two way ANOVA.
`x2`	The second factor in the two way ANOVA. The orderis not important.
`interact`	Should interaction in the two way ANOVA be included? The default value is FALSE (no interaction).
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The Welch's F-test (without assuming equal variances) is performed with the "ftest" function. The "anova" function perform the classical (Fisher's) one-way analysis of variance (ANOVA) which assumes equal variance across the groups. The "kruskaltest" performs the Kruskal-Wallis non parametric alternative to analysis of variance test. The "var2tests" implement the classical F test for the equality of two sample variances. The "cqtest" performs the Cocrhan's Q test for the equality of more than two groups whose values are strictly binary (0 or 1). This is a generalisation of the McNemar's test in the multi-sample case. The "block.anova" is the ANOVA with blocking, randomised complete block design (RCBD). In this case, for every combination of the block and treatment values, there is only one observation. The mathematics are the same as in the case of "twoway.anova", but the assumptions different and the testing procedure also different. In addition, no interaction is present.

Value

A vector with the test statistic and the p-value of each test. For the case of t-test, an extra column with the degrees of freedom is given. For the two way ANOVA there can can be either 2 or three F test statistics and hence the same number of p-values.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

B.L. Welch (1951). On the comparison of several mean values: an alternative approach. Biometrika, 38(3/4), 330-336.

D.C. Montgomery (2001). Design and analysis of experiments (5th Edition). New York: John Wiley & Sons.

McNemar Q. (1947). Note on the sampling error of the difference between correlated proportions or percentages. Psychometrika. 12(2):153-157.

See Also

ttests, ftests

Examples

```
x <- rnorm(200)
ina <- rbinom(200, 3, 0.5) + 1
res<-anova1(x, ina)
res<-ftest(x, ina)
ina <- rbinom(200, 1, 0.5) + 1
x1 <- x[ ina == 1 ]   ; x2 <- x[ ina == 2 ]
res<-ttest2(x1, x2)
res<-var2test(x1, x2)
```

```
## RCBD example 4.1 from Montgomery (2001), page 131-132
x <- c(9.3, 9.4, 9.2, 9.7, 9.4, 9.3, 9.4, 9.6, 9.6, 9.8, 9.5, 10,
10, 9.9, 9.7, 10.2)
tr <- rep(1:4, 4)
bl <- rep(1:4, each = 4)
res<-block.anova(x, tr, bl)
```

`Multinomial regression` *Multinomial regression*

Description

Multinomial regression.

Usage

```
multinom.reg(y, x, tol = 1e-07, maxiters = 50)
```

Arguments

`y`	The response variable. A numerical or a factor type vector.
`x`	A matrix or a data.frame with the predictor variables.
`tol`	This tolerance value to terminate the Newton-Raphson algorithm.
`maxiters`	The maximum number of iterations Newton-Raphson will perform.

Value

A list including:

`iters`	The number of iterations required by the Newton-Raphson.
`loglik`	The value of the maximised log-likelihood.
`be`	A matrix with the estimated regression coefficients.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Bohning, D. (1992). Multinomial logistic regression algorithm. Annals of the Institute of Statistical Mathematics, 44(1): 197-200.

See Also

`glm_logistic`, `score.multinomregs` `logistic_only`

Examples

```
y <- iris[, 5]
x <- matrnorm(150, 3)
res <- multinom.reg(y, x)
```

`Multivariate kurtosis` *Multivariate kurtosis*

Description

Multivariate kurtosis.

Usage

```
mvkurtosis(x)
```

Arguments

`x`	A numerical matrix.

Details

The multivariate kurtosis is calcualted.

Value

A number, the multivariate kurtosis.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

K. V. Mardia (1970). Measures of Multivariate Skewness and Kurtosis with Applications Biometrika, 57(3):519-530.

See Also

`colskewness`, `skew.test2`, `colmeans`, `colVars`, `colMedians`

Examples

```
x <- as.matrix(iris[, 1:4])
#res<-mvkurtosis(x)
```

`Multivariate Laplace random values simulation`
Multivariate Laplace random values simulation

Description

Multivariate Laplace random values simulation.

Usage

```
rmvlaplace(n, lam, mu, G, seed = NULL)
```

Arguments

`n`	The sample size, a numerical value.
`lam`	The the parameter of the exponential distribution, a positive number.
`mu`	The mean vector.
`G`	A $d \times d$ covariance matrix with determinant 1.
`seed`	If you want the same to be generated again use a seed for the generator, an integer number.

Details

The algorithm uses univariate normal random values and transforms them to multivariate via a spectral decomposition.

Value

A matrix with the simulated data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Eltoft T., Kim T., and Lee T.W. (2006). On the multivariate laplace distribution. Signal Processing Letters, IEEE, 13(5):300-303.

See Also

`rmvnorm`, `racg`, `rmvt`

Examples

```
m <- colmeans( as.matrix( iris[, 1:4] ) )
s <- cov(iris[,1:4])
s <- s / det(s)^0.25
lam <- 3
x <- rmvlaplace(100, lam, m, s)
```

`Multivariate normal and t random values simulation`

Multivariate normal and t random values simulation

Description

Multivariate normal and t random values simulation.

Usage

```
rmvnorm(n, mu, sigma, seed = NULL)
rmvt(n, mu, sigma, v, seed = NULL)
```

Arguments

`n`	The sample size, a numerical value.
`mu`	The mean vector in R^d.
`sigma`	The covariance matrix in R^d.
`v`	The degrees of freedom.
`seed`	If you want the same to be generated again use a seed for the generator, an integer number.

Details

The algorithm uses univariate normal random values and transforms them to multivariate via a spectral decomposition. It is faster than the command "mvrnorm" available from MASS, and it allows for singular covariance matrices.

Value

A matrix with the simulated data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Aitchison J. (1986). The statistical analysis of compositional data. Chapman & Hall.

See Also

racg, rmvlaplace, rmvt

Examples

```
x <- as.matrix(iris[, 1:4])
m <- colmeans(x)
s <- cov(x)
y <- rmvnorm(1000, m, s)
res<-colmeans(y)
res<-cov(y)
y <- NULL
```

Naive Bayes classifiers

Naive Bayes classifiers

Description

Gaussian, Poisson, geometric and multinomial naive Bayes classifiers.

Usage

```
gaussian.nb(xnew = NULL, x, ina, parallel = FALSE)
poisson.nb(xnew, x, ina)
multinom.nb(xnew, x, ina)
geom.nb(xnew, x, ina, type = 1)
gammanb(xnew = NULL, x, ina, tol = 1e-07)
```

Arguments

xnew	A numerical matrix with new predictor variables whose group is to be predicted. For the Gaussian naive Bayes, this is set to NUUL, as you might want just the model and not to predict the membership of new observations. For the Gaussian case this contains any numbers, but for the multinomial and Poisson cases, the matrix must contain integer valued numbers only.
x	A numerical matrix with the observed predictor variable values. For the Gaussian case this contains any numbers, but for the multinomial and Poisson cases, the matrix must contain integer valued numbers only.
ina	A numerical vector with strictly positive numbers, i.e. 1,2,3 indicating the groups of the dataset. Alternatively this can be a factor variable.
type	Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1. This is for the geometric distribution. This argument is for the geometric distribution. Type 1 refers to the case where the minimum is zero and type 2 for the case of the minimum being 1.
tol	The tolerance value to terminate the Newton-Raphson algorithm in the gamma distribution.
parallel	If you want parallel computations set this equal to TRUE.

Value

For the Poisson and Multinomial naive Bayes classifiers the estimated group, a numerical vector with 1, 2, 3 and so on. For the Gaussian naive Bayes classifier a list including:

`mu`	A matrix with the mean vector of each group based on the dataset.
`sigma`	A matrix with the variance of each group and variable based on the dataset.
`ni`	The sample size of each group in the dataset.
`est`	The estimated group of the xnew observations. It returns a numerical value back regardless of the target variable being numerical as well or factor. Hence, it is suggested that you do \"as.numeric(target)\" in order to see what is the predicted class of the new data.

For the Gamma classifier a list including:

`a`	A matrix with the shape parameters.
`b`	A matrix with the scale parameters.
`est`	The estimated group of the xnew observations. It returns a numerical value back regardless of the target variable being numerical as well or factor. Hence, it is suggested that you do \"as.numeric(target)\" in order to see what is the predicted class of the new data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`gaussiannb.pred`, `colmeans`, `colVars`

Examples

```
x <- as.matrix(iris[, 1:4])
a <- gaussian.nb(x, x, iris[, 5])
x1 <- matrix( rpois(100 * 4, 5), ncol = 4)
x2 <- matrix( rpois(50 * 4, 10), ncol = 4)
x <- rbind(x1, x2)
ina <- c( rep(1, 100), rep(2, 50) )
res<-poisson.nb(x, x, ina)
res<-geom.nb(x, x, ina)
res<-multinom.nb(x, x, ina)
```

`Natural Logarithm each element of a matrix`
Natural Logarithm each element of a matrix

Description

Natural Logarithm each element of a matrix.

Usage

```
Log(x, na.rm = FALSE)
```

Arguments

`x`	A matrix with data.
`na.rm`	A boolean value (TRUE/FALSE) for removing NA.

Details

The argument must be a matrix. For vector the time was the same as R's "log" function so we did not add it.

Value

A matrix where each element is the natural logarithm of the given argument.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`Lbeta`, `Lchoose`, `Choose`

Examples

```
x <-matrix( runif( 100 * 100), ncol = 100 )
a <- log(x)
b <- Log(x)
all.equal(a, b) # true

x<-a<-b<-NULL
```

Natural logarithm of the beta function

Natural logarithm of the beta function

Description

Natural logarithm of the beta function.

Usage

```
Lbeta(x, y)
```

Arguments

x	A numerical matrix, or a vector or just a number with positive numbers in either case.
y	A numerical matrix, or a vector or just a number with positive numbers in either case. The dimensions of y must match those of x.

Details

The function is faster than R's lbeta when the dimensions of x any are large. If you have only two numbers, then lbeta is faster. But if you have for example two vectors of 1000 values each, Lbeta becomes two times faster than lbeta.

Value

The matrix, vector or number with the resulting values.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Abramowitz, M. and Stegun, I. A. (1972) Handbook of Mathematical Functions. New York: Dover. https://en.wikipedia.org/wiki/Abramowitz_and_Stegun provides links to the full text which is in public domain. Chapter 6: Gamma and Related Functions.

See Also

Lgamma, beta.mle, diri.nr2

Examples

```
x <- rexp(1000)
y <- rexp(1000)
a1 <- Lbeta(x, y)

x<-y<-a1<-NULL
```

`Natural logarithm of the gamma function and its derivatives`
Natural logarithm of the gamma function and its derivatives

Description

Natural logarithm of the gamma function and its derivatives.

Usage

```
Lgamma(x)
Digamma(x)
Trigamma(x)
```

Arguments

x	A numerical matrix or vector with positive numbers in either case.

Details

We have spotted that the time savings come when there are more than 50 elements, with vector or matrix.

Value

The matrix or the vector with the resulting values.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Abramowitz, M. and Stegun, I. A. (1972) Handbook of Mathematical Functions. New York: Dover. https://en.wikipedia.org/wiki/Abramowitz_and_Stegun provides links to the full text which is in public domain. Chapter 6: Gamma and Related Functions.

See Also

`beta.mle`, `diri.nr2`

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
 a1 <- Lgamma(x)
a2 <- lgamma(x)
all.equal(as.vector(a1), as.vector(a2))

a1 <- Digamma(x)
a2 <- digamma(x)
all.equal(as.vector(a1), as.vector(a2))

x<-a1<-a2<-NULL
```

Norm of a matrix *Norm of a matrix*

Description

Norm of a matrix.

Usage

```
Norm(x, type = "F")
```

Arguments

x	A matrix with numbers.
type	The type of norm to be calculated. The default is "F" standing for Frobenius norm ("f" in R's norm). The other options are "C" standing for the one norm ("o" in R's norm), "R" for the identiy norm ("I" in R's norm) and "M" for the maximum modulus among elements of a matrix ("M" in R's norm)

Value

A number, the norm of the matrix.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Dist, dista, colmeans

Examples

```
x <- matrix( rnorm(10 * 10), ncol = 10 )
res<-Norm(x, "F")
res<-norm(x, "F")
res<-Norm(x, "M")
res<-norm(x, "M")
```

`Number of equal columns between two matrices`
Number of equal columns between two matrices

Description

Number of equal columns between two matrices.

Usage

```
mat.mat(x, y)
```

Arguments

x	A numerical matrix. See details for more information. It must have the same number of rows as y.
y	A numerical matrix. See details for more information. It must have the same number of rows as x.

Details

The function takes each column of x and checks the number of times it matches a column of y. In the example below, we take the first 3 columns of iris as the x matrix. The y matrix is the whole of iris. We will see how many times, each column of x appears in the y matrix. The answer is 1 for each column.

Value

A numerical vector of size equal to the number of columns of x.

Author(s)

Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`Match`, `colmeans`, `colMedians`

Examples

```
x <- as.matrix(iris[, 1:3])
y <- iris
y[, 5] <- as.numeric(y[, 5])
y <- as.matrix(y)
res<-mat.mat(x, y)

x<-y<-NULL
```

`Odds ratio and relative risk`

Odds ratio and relative risk

Description

Odds ratio and relative risk.

Usage

```
odds.ratio(x, a = 0.05, logged = FALSE)
rel.risk(x, a = 0.05, logged = FALSE)
```

Arguments

`x`	A 2 x 2 matrix or a vector with 4 elements. In the case of the vector make sure it corresponds to the correct table.
`a`	The significance level, set to 0.05 by default.
`logged`	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

The odds ratio and the confidence interval are calculated.

Value

A list including:

`res`	The estimated odds ratio and the p-value for the null hypothesis test that it is equal to 1.
`ci`	The (1-a)% confidence interval for the true value of the odds ratio.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Mosteller Frederick (1968). Association and Estimation in Contingency Tables. Journal of the American Statistical Association. 63(321):1-28.

Edwards A.W.F. (1963). The measure of association in a 2x2 table. Journal of the Royal Statistical Society, Series A. 126(1):109-114.

See Also

odds, g2Test

Examples

```
x <- rpois(4, 30)+2
res<-odds.ratio(x)
res<-odds.ratio( matrix(x, ncol = 2) )
```

`One and many Gini coefficients`

One and many Gini coefficients

Description

Many Gini coefficients.

Usage

```
gini(x)
ginis(x)
```

Arguments

x	Either a vector or a matrix with non negative data. The rows are observations and the columns denote the variables.

Details

We have implemented the fast version of the Gini coefficient. See wikipedia for more details.

Value

A value with the Gini coefficient or a vector with the Gini coefficient, one for each variable.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

colskewness, colmeans, corpairs

Examples

```
x <- matrix( rpois(300 * 100, 100), ncol = 100 )
a <- ginis(x)
```

One sample t-test for a vector

One sample t-test for a vector

Description

One sample t-test for a vector.

Usage

```
ttest1(x, m, alternative = "unequal", logged = FALSE, conf = NULL)
```

Arguments

x	A numerical vector with the data.
m	The mean value under the null hypothesis.
alternative	The alternative hypothesis, "unequal", "greater" or "less".
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?
conf	If you want a confidence interval supply the confidence level.

Details

The usual one sample t-test is implemented, only faster.

Value

A list including:

res	A two valued vector with the test statistic and its (logged) p-value.
ci	In the case you supplied a number in the input argument "conf" the relevant confidence interval will be returned as well.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

See Also

ttest, anova1, ttests

Examples

```
x = rnorm(500)
res<-t.test(x, mu = 0)
res<-ttest1(x, 0, conf = 0.95)
```

`Operations between two matrices or matrix and vector`

Operations between two matrices or matrix and vector

Description

Operations between two matrices or matrix and vector.

Usage

```
XopY.sum(x, y = NULL, oper = "*")
eachrow(x,y,oper = "*",method = NULL)
eachcol.apply(x,y,indices = NULL,oper = "*",apply = "sum", parallel = FALSE)
```

Arguments

x	A numerical matrix.
y	A second numerical matrix for "XopY.sum" whose dimensions must match the ones of x, or vector for "eachrow","eachcol.apply" whose length must match with the rows of x.
oper	The operation to be performed, either "*", "/", "+", "-" or "==".
method	A character value for choosing option to apply in the result. Options: 1) sum 2) max 3) min Does not work for oper="==".
indices	An integer vector with indices to specific columns. Only for "eachcol.apply".
apply	A character value with the function to be applied in the columns of the matrix. Only for "eachcol.apply". Options: 1) sum 2) median 3) max 4) min
parallel	A boolean value for parallel version.

Details

XopY.sum: sum(X op Y) where op can be on of "+,-,*,/".

eachrow: X op Y **by row** or **FUNCTION**(X op Y) where "x" is matrix, "y" is vector with length as much an the columns of x and "op" is one of "+,-,*,/,==", and "FUNCTION" is a specific method for applying in the result matrix (see argument method).

eachcol.apply: **FUNCTION**(X op Y) **by column** where "x" is matrix, "y" is vector with length as much an the rows of x, "op" is one of "+,-,*,/" and "FUNCTION" is a specific method (see argument apply).

NOTE: Arguments "method" does not work for oper="==" and this operation works only in "eachrow".

Value

XopY.sum: sum(X op Y) where "op" can be on of "+,-,*,/".

eachrow: operation by row between a matrix and a vector."op" can be on of "+,-,*,/". If "suma=TRUE" then returns the sum of this operation.

eachcol.apply: operation by column between a matrix and a vector and applied a specific function."op" can be on of "+,-,*,/".

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Dist, dista, colmeans, Diag.fill,colMads, rowMads

Examples

```
x <- matrix( rnorm(5 * 5), ncol = 5 )
y <- matrix( rnorm(5 * 5), ncol = 5 )
res<-XopY.sum(x, y, oper = "*")
y <- x[,1]
res<-eachrow(x,y)

all.equal(eachcol.apply(x,y),colsums(x*y))


x<-y<-NULL
```

`Orthogonal matching pursuit variable selection`

Orthogonal matching pursuit variable selection

Description

Orthogonal matching pursuit variable selection.

Usage

```
ompr(y, x, ystand = TRUE, xstand = TRUE, method = "BIC", tol = 2 )
omp(y, x, xstand = TRUE, tol = qchisq(0.95, 1) + log( length(y) ), type = "logistic" )
```

Arguments

`y`	The response variable, a numeric vector. For "ompr" this is a continuous variable. For "omp" this can be either a vector with discrete (count) data, 0 and 1, non negative values, strictly positive or proportions including 0 and 1.
`x`	A matrix with the data, where the rows denote the observations and the columns are the variables.
`ystand`	If this is TRUE the response variable is centered. The mean is subtracted from every value.
`xstand`	If this is TRUE the independent variables are standardised.
`method`	You can choose between the change in the BIC ("BIC"), the adjusted R^2 ("ar2"), the SSE ("SSE") or the classical p-value based ("pvalue").
`tol`	The tolerance value to terminate the algorithm. This is the change in the criterion value between two successive steps. For "ompr" the default value is 2 because the default method is "BIC". For "omp" the default value is the 95% quantile of the χ^2 distribution with 1 degree of freedom plus the logarithm of the sample size.
`type`	This denotes the parametric model to be used each time. It depends upon the nature of y. The possible values are "logistic", "poisson", "quasipoisson", "quasibinomial", "normlog", "gamma", "weibull", "mv" (for multivariate response variable) or "multinomial".

Value

For "ompr" a list including:

`runtime`	The runtime of the algorithm.
`info`	A matrix with two columns. The selected variable(s) and the criterion value at every step.

For "omp" a list including:

`runtime`	The runtime of the algorithm.
`phi`	The ϕ parameter. In the cases of "quasipoisson", "quasibinomial" and "normlog" this is useful. For all other cases this is NULL.
`info`	A matrix with two columns. The selected variable(s) and the criterion value at every step.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Pati Y. C., Rezaiifar R. & Krishnaprasad P. S. (1993). Orthogonal matching pursuit: Recursive function approximation with applications to wavelet decomposition. In Signals, Systems and Computers. 1993 Conference Record of The Twenty-Seventh Asilomar Conference on. IEEE.

Mazin Abdulrasool Hameed (2012). Comparative analysis of orthogonal matching pursuit and least angle regression. MSc thesis, Michigan State University. https://www.google.gr/url?sa=t&rct=j&q=&esrc=s&source=web&c

Lozano A., Swirszcz G., & Abe N. (2011). Group orthogonal matching pursuit for logistic regression. In Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics.

The γ-OMP algorithm for feature selection with application to gene expression data. IEEE/ACM Transactions on Computational Biology and Bioinformatics (Accepted for publication) https://arxiv.org/pdf/2004.00281.pdf

See Also

cor.fbed, cor.fsreg, correls, fs.reg

Examples

```
x <- matrnorm(200, 100)
y <- rnorm(200)
a <- ompr(y, x)
a
x <- NULL
```

`Outer function` *Outer function*

Description

The outer function.

Usage

```
Outer(x, y, oper = "*")
```

Arguments

x	A numerical vector.
y	A numerical vector.
oper	The available options are "*" (multiplication), "/" (division), "+" (sum), "-" (substraction), "^" (power raise), and "

Details

The function is the same as R's "outer", but works with vectors only and probably has less capabilities, but faster.

Value

A matrix with all the combinations.

Author(s)

Manos Papadakis and Michail Tsagris

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>.

See Also

`mat.mult`, `vecdist`

Examples

```
x <- rnorm(10)
y <- rnorm(10)
res<-Outer(x, y)
```

Partial distance correlation

Partial distance correlation

Description

Partial distance correlation.

Usage

```
pdcor(x, y, z)
```

Arguments

x	A numerical matrix.
y	A numerical matrix.
z	A numerical matrix.

Details

The partial distance correlation between x and y conditioning on z is computed.

Value

The partial distance correlation

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Szekely G.J. and Rizzo M.L. (2014). Partial Distance Correlation with Methods for Dissimilarities. Annals of Statistics, 42(6): 2382–2412.

Szekely G. J. and Rizzo M. L. (2023). The Energy of Data and Distance Correlation. Chapman and Hall/CRC.

Tsagris M. and Papadakis M. (2025). Fast and light-weight energy statistics using the R package Rfast. https://arxiv.org/abs/2501.02849

See Also

dcov, dcor.ttest

Examples

```
x <- as.matrix(iris[1:50, 1:4])
y <- as.matrix(iris[51:100, 1:4])
z <- as.matrix(iris[101:150, 1:4])
#pdcor(x, y, z)
x <- y <- NULL
```

Permutation *Permutation*

Description

Permute the given vector.

Usage

```
permutation(x, nperm = gamma(length(x)+1))
permutation.next(x, nperm = gamma(length(x)+1))
permutation.prev(x, nperm = gamma(length(x)+1))
bincomb(n)
```

Arguments

x	A numeric vector with data.
nperm	An integer value for returning specific number of combinations. By defualt is set to all combinations. Must be between **0<=nperm<=gamma(length(x)+1)**
n	An integer value for the length of the binary number.

Details

This function implements "Permutation", which means all the possible combinations. In the permutation.next and permutation.prev if there aren't possible combinations it returns the same vector. "Binary Combinations" for "bincomb", means all the possible combinations for the binary number with length "n".

Value

Returns a matrix with all possible combinations of the given vector or a matrix row with one possible combinations.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

combn,comb_n

Examples

```
y <- rnorm(3)
b <- permutation(y)
b <- permutation.next(y)
b <- permutation.prev(y)
g <- bincomb(3)
```

Permutation based p-value for the Pearson correlation coefficient

Permutation based p-value for the Pearson correlation coefficient

---

Description

Permutation based p-value for the Pearson correlation coefficient.

Usage

```
permcor(x, y, R = 999)
```

Arguments

x	A numerical vector with the first variable.
y	A numerical vector with the second variable.
R	The number of permutations to be conducted; set to 999 by default.

Details

This is a very low computational calculation of the p-value. Try it yourselves.

Value

A vector consisting of two values, the Pearson correlation and the permutation based p-value.

Author(s)

Marios Dimitriadis and Michail Tsagris

R implementation and documentation: Marios Dimitriadis and Michail Tsagris <kmdimitriadis@gmail.com> and <mtsagris@csd.uoc.gr>

References

Chatzipantsiou C., Dimitriadis M., Papadakis M. and Tsagris M. (2019). Extremely efficient permutation and bootstrap hypothesis tests using R. To appear in the Journal of Modern Applied Statistical Methods.

https://arxiv.org/ftp/arxiv/papers/1806/1806.10947.pdf

See Also

pc.skel

Examples

```
x <- iris[, 1]
y <- iris[, 2]
permcor(x, y, R = 499)
```

Polyserial correlation

Polyserial correlation

Description

Polyserial correlation.

Usage

```
poly.cor(x, y)
```

Arguments

x	The continuous variable.
y	The ordinal variable, a numeric vector with numbers starting from 1.

Details

The polyserial correlation between a continuous and an ordinal variable is calculated. The function is not super fast, yet is faster than other implementations we found.

Value

A list including:

`est`	A vector with the polyserial correlation and its estimated variance.
`test`	A vector with the test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Olsson U., Drasgow F. and Dorans N. J. (1982). The polyserial correlation coefficient. Psychometrika, 47(3):337-347.

See Also

`correls`, `Table`

Examples

```
x <- rnorm(100)
y <- rpois(100, 10) + 1
res<-poly.cor(x, y)
```

Pooled covariance matrix

Pooled covariance matrix

Description

Pooled covariance matrix.

Usage

```
pooled.cov(x, ina)
```

Arguments

`x`	A matrix with continuous data.
`ina`	A numerical vector indicating the groups. **The nubmers must be consecutive and start from 1**.

Details

The spatial median is at first computed (if not supplied) and then the covariance matrix.

Value

The spatial sign covariance matrix.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Durre A, Vogel D. and D.E. Tyler D.E.(2014). The spatial sign covariance matrix with unknown location. Journal of Multivariate Analysis, 130: 107-117. http://arxiv.org/pdf/1307.5706v2.pdf

See Also

spat.med, spatmed.reg

Examples

```
res<-sscov( as.matrix(iris[, 1:4]) )
```

`Prediction with some naive Bayes classifiers`

Prediction with some naive Bayes classifiers

Description

Prediction with some naive Bayes classifiers.

Usage

```
gaussiannb.pred(xnew, m, s, ni)
poissonnb.pred(xnew, m)
multinomnb.pred(xnew, m)
gammanb.pred(xnew, a, b)
geomnb.pred(xnew, prob)
```

Arguments

xnew	A numerical matrix with new predictor variables whose group is to be predicted. For the Gaussian case this contains any numbers, but for the multinomial and Poisson cases, the matrix must contain integer valued numbers only.
m	A matrix with the group means. Each row corresponds to a group.
s	A matrix with the group colum-wise variances. Each row corresponds to a group.
ni	A vector with the frequencies of each group.
a	A vector with the shape parameters of each group.
b	A vector with the scale parameters of each group.
prob	A vector with the sprobability parameters of each group.

Value

A numerical vector with 1, 2, ... denoting the predicted group.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

gaussian.nb, colpoisson.mle colVars

Examples

```
ina <- sample(1:150, 100)
x <- as.matrix(iris[, 1:4])
id <- as.numeric(iris[, 5])
a <- gaussian.nb(xnew = NULL, x[ina, ], id[ina])
est <- gaussiannb.pred(x[-ina, ], a$mu, a$sigma, a$ni)
res<-table(id[-ina], est)
```

Quasi binomial regression for proportions

Quasi binomial regression for proportions

Description

Quasi binomial regression for proportions.

Usage

```
prop.reg(y, x, varb = "quasi", tol = 1e-09, maxiters = 100)
prop.regs(y, x, varb = "quasi", tol = 1e-09, logged = FALSE, maxiters = 100)
```

Arguments

y	A numerical vector proportions. 0s and 1s are allowed.
x	For the "prop.reg" a matrix with data, the predictor variables. This can be a matrix or a data frame. For the "prop.regs" this must be a numerical matrix, where each columns denotes a variable.
tol	The tolerance value to terminate the Newton-Raphson algorithm. This is set to 10^{-9} by default.
varb	The type of estimate to be used in order to estimate the covariance matrix of the regression coefficients. There are two options, either "quasi" (default value) or "glm". See the references for more information.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?
maxiters	The maximum number of iterations before the Newton-Raphson is terminated automatically.

Details

We are using the Newton-Raphson, but unlike R's built-in function "glm" we do no checks and no extra calculations, or whatever. Simply the model. The "prop.regs" is to be used for very many univariate regressions. The "x" is a matrix in this case and the significance of each variable (column of the matrix) is tested. The function accepts binary responses as well (0 or 1).

Value

For the "prop.reg" function a list including:

iters	The number of iterations required by the Newton-Raphson.
varb	The covariance matrix of the regression coefficients.
phi	The phi parameter is returned if the input argument "varb" was set to "glm", othwerise this is NULL.
info	A table similar to the one produced by "glm" with the estimated regression coefficients, their standard error, Wald test statistic and p-values.

For the "prop.regs" a two-column matrix with the test statistics (Wald statistic) and the associated p-values (or their loggarithm).

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Papke L. E. & Wooldridge J. (1996). Econometric methods for fractional response variables with an application to 401(K) plan participation rates. Journal of Applied Econometrics, 11(6): 619–632.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

anova_propreg univglms, score.glms, logistic_only

Examples

```
y <- rbeta(100, 1, 4)
x <- matrix(rnorm(100 * 3), ncol = 3)
a <- prop.reg(y, x)
y <- rbeta(100, 1, 4)
x <- matrix(rnorm(400 * 100), ncol = 400)
b <- prop.regs(y, x)
res<-mean(b[, 2] < 0.05)
```

Quasi Poisson regression for count data

Quasi Poisson regression

Description

Quasi Poisson regression.

Usage

```
qpois.reg(x, y, full = FALSE, tol = 1e-09,maxiters = 100)
qpois.regs(x, y, tol = 1e-09, logged = FALSE)
```

Arguments

x	For the "qpois.reg" a matrix with data, the predictor variables. This can be a matrix or a data frame. For the "qpois.regs" this must be a numerical matrix, where each columns denotes a variable.
y	A numerical vector with positive discrete data.
full	If this is FALSE, the coefficients, the deviance and the estimated phi parameter will be returned only. If this is TRUE, more information is returned.
tol	The tolerance value to terminate the Newton-Raphson algorithm. This is set to 10^{-9} by default.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?
maxiters	The maximum number of iterations before the Newton-Raphson is terminated automatically.

Details

We are using the Newton-Raphson, but unlike R's built-in function "glm" we do no checks and no extra calculations, or whatever. Simply the model, unless the user requests for the Wald tests of the coefficients. The "qpois.regs" is to be used for very many univariate regressions. The "x" is a matrix in this case and the significance of each variable (column of the matrix) is tested.

Value

For the "prop.reg" a list including: When full is FALSE

`be`	The regression coefficients.
`devi`	The deviance of the model.
`varb`	The covariance matrix of the beta coefficients.
`phi`	The phi parameter, the estimate of dispersion.

When full is TRUE, the additional item is:

`info`	The regression coefficients, their standard error, their Wald test statistic and their p-value.

For the "prop.regs" a two-column matrix with the test statistics (Wald statistic) and the associated p-values (or their loggarithm).

Author(s)

Manos Papadakis and Marios Dimitriadis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Marios Dimitriadis <kmdimitriadis@gmail.com>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

`prop.reg` `univglms`, `score.glms`, `poisson_only`

Examples

```
y <- rnbinom(100, 10, 0.6)
x <- matrix(rnorm(100*3), ncol = 3)
mod1 <- glm(y ~ x, quasipoisson)
res<-summary(mod1)
res<-qpois.reg(x, y, full = TRUE)
res<-qpois.regs(x, y)
```

`Random intercepts linear mixed models`
Random intercepts linear mixed models

Description

Random intercepts linear mixed models (for balanced data with a single identical covariate).

Usage

```
rint.reg(y, x, id ,tol = 1e-08, ranef = FALSE, maxiters = 100)
rint.regbx(y, x, id)
```

Arguments

`y`	A numerical vector with the data. The subject values.
`x`	For the case of "rint.reg" this can be a vector or a numerical matrix with data. In the case of "rint.regbx" this is a numerical vector with the same length as y indicating the fixed predictor variable. Its values are the same for all levels of y. An example of this x is time which is the same for all subjects.
`id`	A numerical variable with 1, 2, ... indicating the subject.
`tol`	The tolerance level to terminate the generalised elast squares algorithm.
`ranef`	If you want to obtain the random effects (random intercepts) set this equal to TRUE.
`maxiters`	The max number of iterations that can take place in a regression.

Details

Random intercepts linear mixed models with compound covariance structure is fitted in both functions. The "rint.reg" allows any numerical matrix, with balanced or unbalanced data. See Demidenko (2013, pg. 65-67) for more information.

The "rint.regbx" is a special case of a balanced random intercepts model with a compound symmetric covariance matrix and one single covariate which is constant for all replicates. An example, is time, which is the same for all subjects. Maximum likelihood estimation has been performed. In this case the mathematics exist in a closed formula (Demidenko, 2013, pg. 67-69).

Value

A list including:

`info`	A vector with the random intercepts variance (between), the variance of the errors (within), the log-likelihood, the deviance (twice the log-likelihood) and the BIC. In the case of "rint.reg" it also includes the number of iterations required by the generalised least squares.
`be`	The estimated regression coefficients, which in the case of "rint.regbx" are simply two: the constant and the slope (time effect).
`ranef`	The random intercepts effects.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Eugene Demidenko (2013). Mixed Models: Theory and Applications with R, 2nd Edition. New Jersey: Wiley & Sons (excellent book).

See Also

rm.lines, varcomps.mom, colvarcomps.mom

Examples

```
y <- rnorm(100)
x <- rnorm(10)
x <- rep(x, 10)
id <- rep(1:10, each = 10)
for (i in 1:20) a <- rint.reg(y, x, id)
```

Random values simulation from a von Mises distribution

Random values simulation from a von Mises distribution

Description

It generates random vectors following the von Mises distribution. The data can be spherical or hyper-spherical.

Usage

```
rvonmises(n, m, k, rads = TRUE)
```

Arguments

n	The sample size.
m	The mean angle expressed in radians or degrees.
k	The concentration parameter. If k is zero the sample will be generated from the uniform distribution over $(0, 2\pi)$.
rads	If the mean angle is expressed in radians, this should be TRUE and FALSE otherwise. The simulated data will be expressed in radians or degrees depending on what the mean angle is expressed.

Details

The mean direction is transformed to the Euclidean coordinates (i.e. unit vector) and then the fvmf function is employed. It uses a rejection smapling as suggested by Andrew Wood in 1994. I have mentioned the description of the algorithm as I found it in Dhillon and Sra in 2003. Finally, the data are transformed to radians or degrees.

Value

A vector with the simulated data.

Author(s)

Michail Tsagris and Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm85@gmail.com>

References

Wood, A. T. (1994). Simulation of the von Mises Fisher distribution. Communications in statistics-simulation and computation, 23(1): 157-164.

Dhillon, I. S., & Sra, S. (2003). Modeling data using directional distributions. Technical Report TR-03-06, Department of Computer Sciences, The University of Texas at Austin. http://citeseerx.ist.psu.edu/viewdoc/download?d

See Also

vm.mle, rvmf

Examples

```
#x <- rvonmises(1000, 2, 25, rads = TRUE)
#res<-vm.mle(x)
```

`Reading the files of a directory`

Reading the files of a directory

Description

Reading the files of a directory.

Usage

```
read.examples(path.man,paths.full = FALSE)
read.directory(path.directory)
```

Arguments

path.man	The full path to the directory with the Rd files in it. For example: \"C:\Users\username\Documents\R\Rfas
paths.full	Print or return the full paths.
path.directory	The full path to the directory.

Details

For function \"read.examples\": Takes as an argument a full path to the directory of the Rd files. If you don't want the program to read any file add at the top of the file the attribute "%[dont read]".

Value

For function \"read.examples\": a list with 2 fields

examples	A character vector with the examples of each Rd file.
files	A character vector with the name of the file that each examples belongs.
long_lines	A character vector with the name of the file that has large examples.

You can choose which files not to read for both R and Rd. You must add in the first line of the file in comment the "attribute" "%[dont read]". Finally, that function wil return in the result a list of which files had this attribute.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

AddToNamespace, sourceR, sourceRd, checkRd, checkExamples

Examples

```
# for example: path.man="C:\some_file\man\"
# system.time( read.examples(path.man) )
# system.time( read.examples(path.man,dont.read=c("somef_1.Rd",...,"somef_n.Rd") ) )
```

Repeated measures anova

Repeated measures anova

Description

Repeated measures anova.

Usage

```
rm.anova(y, logged = FALSE)
```

Arguments

y	A matrix with the data, where each column refers to a different measurement. The rows denote the subjects.
logged	Should the p-values be returned (FALSE) or their logarithm (TRUE)?

Details

Found in Davis (2002) is the usual repeated measures ANOVA. In this case, suppose you have taken measurements on one or more variables from the same group of people. See the example below on how to put such data.

Value

A vector with the test statistic (t-test) and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Charles S. Davis (2002). Statistical methods for the analysis of repeated measures. Springer-Verlag, New York.

See Also

rm.anovas, rint.reg, varcomps.mle

Examples

```
y <- c(74.5,81.5,83.6,68.6,73.1,79.4,
75.5,84.6,70.6,87.3,73.0,75.0,
68.9,71.6,55.9,61.9,60.5,61.8,
57.0,61.3,54.1,59.2,56.6,58.8,
78.3,84.9,64.0,62.2,60.1,78.7,
54.0,62.8,63.0,58.0,56.0,51.5,
72.5,68.3,67.8,71.5,65.0,67.7,
80.8,89.9,83.2,83.0,85.7,79.6)
y <- matrix(y, ncol = 6, byrow = TRUE)
res<-rm.anova(y)
```

Replicate columns/rows *Replicate columns/rows*

Description

Replicate columns/rows.

Usage

```
rep_col(x,n)
rep_row(x,n)
```

Arguments

x	A vector with data.
n	Number of new columns/rows.

Value

A matrix where each column/row is equal to "x".

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, rowFalse, nth, colrange, colMedians, colVars, colSort, rowSort, rowTrue

Examples

```
x <- runif(10)
all.equal(rep_col(x,10),matrix(x,nrow=length(x),ncol=10))
all.equal(rep_row(x,10),matrix(x,ncol=length(x),nrow=10,byrow=TRUE))
```

`Represantation of Stack`
Represantation of Stack

Description

Represantation of Stack.

Usage

```
Stack(x,type=NULL)
```

Arguments

`x`	Any type that could be convert to vector or an integer value.
`type`	A type for the Stack, "integer", "numeric" or any other that accepts one argument.

Details

Stack is an abstract data type - data structure based on the principle of last in first out. To access the 3 fields, use operator "$".

Value

An object of class "Stack". This object holds 3 fields:

pop: remove the first element (from the top). top: access the first element (from the top). push: add an element to the top of the Stack.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`colShuffle`, `colVars`, `colmeans`

Examples

```
x<-Stack(10,type=integer)

x$push(5)
x$push(10)
x$top()  == 10
x$pop()
x$top() == 5

y<-rnorm(10)
```

```
x<-Stack(x)

x$push(5) # length increased to 11
x$top() # access the last element that pushed, 5
x$pop() # pop the last element that pushed
```

Round each element of a matrix/vector

Round each element of a matrix/vector

Description

Round each element of a matrix/vector.

Usage

```
Round(x,digit=0,na.rm = FALSE)
```

Arguments

x	A numeric matrix/vector with data or NA. NOT integer values.
digit	An integer value for 0...N-1 where N is the number of the digits. By default is 0.
na.rm	TRUE or FAlSE for remove NAs if exists.

Details

Round is a very fast C++ implementation. Especially for large data. It handles NA.

Value

A vector/matrix where each element is been rounded in the given digit.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Lchoose, Log, Choose

Examples

```
x <-matrix( rnorm( 50 * 10), ncol = 10 )
a <- Round(x,5)
b <- round(x,5)
all.equal(a,b) #true
x <-rnorm( 1000)
a <- Round(x,5)
b <- round(x,5)
all.equal(a,b) # true
```

`Row - Wise matrix/vector count the frequency of a value`

Row - Wise matrix/vector count the frequency of a value

Description

Row - Wise matrix/vector count the frequency of a value.

Usage

```
count_value(x, value)
colCountValues(x, values, parallel = FALSE,cores = 0)
rowCountValues(x, values, parallel = FALSE,cores = 0)
```

Arguments

`x`	A vector with the data (numeric or character) or a numeric matrix.
`value`	The value, numeric or character, to check its frequency in the vector "x".
`values`	a vector with the values to check its frequency in the matrix "x" by row or column.
`parallel`	Do you want to do it in parallel in C++? TRUE or FALSE. Works with every other argument.
`cores`	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Details

The functions is written in C++ in order to be as fast as possible. The "x" and "value" must have the same type. The type can be numeric or character.

Value

The frequency of a value/values in a vector in linear time or by row/column in a matrix.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Median, binary_search, Order, nth

Examples

```
x <- rnorm(100)
value <- x[50]
count_value(x,value)
y <- sample(letters,replace=TRUE)
value <- "r"
count_value(y,value)
values <- sample(x,100,replace=TRUE)
x <- matrix(x,100,100)
res<-colCountValues(x,values)
res<-rowCountValues(x,values)
x<-value<-values<-y<-NULL
```

Row-wise minimum and maximum

Row-wise minimum and maximum of a matrix

Description

Row-wise minimum and maximum of a matrix.

Usage

```
rowMins(x, value = FALSE)
rowMaxs(x, value = FALSE)
rowMinsMaxs(x)
```

Arguments

x	A numerical matrix with data.
value	If the value is FALSE it returns the indices of the minimum/maximum, otherwise it returns the minimum and maximum values.

Value

A vector with the relevant values.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`colMins`, `colMaxs`, `nth`, `rowrange` `colMedians`, `colVars`, `colSort`, `rowSort`

Examples

```
x <- matrix( rnorm(10 * 10), ncol = 10 )

s1 <- rowMins(x)
#s2 <- apply(x, 1, min)

s1 <- rowMaxs(x)
#s2 <- apply(x, 1, max)

#s1 <- c(apply(x, 1, min),apply(x, 1, max) )
s2 <- rowMinsMaxs(x)

x<-s1<-s2<-NULL
```

Row-wise true value *Row-wise true value of a matrix*

Description

Row-wise true value of a matrix.

Usage

```
rowTrue(x)
rowFalse(x)
rowTrueFalse(x)
```

Arguments

x	A logical matrix with data.

Value

An integer vector where item "i" is the number of the true/false values of "i" row.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

rowMins, colFalse, nth, rowrange, rowMedians, rowVars, colTrue

Examples

```
x <- matrix(as.logical(rbinom(100*100,1,0.5)),100,100)

s1 <- rowTrue(x)

s1 <- rowFalse(x)

s1 <- rowTrueFalse(x)

x<-s1<-NULL
```

Search for variables with zero range in a matrix

Search for variables with zero range in a matrix

Description

Search for variables with zero range in a matrix.

Usage

```
check_data(x, ina = NULL)
```

Arguments

x	A matrix or a data.frame with the data, where rows denotes the observations and the columns contain the dependent variables.
ina	If your data are grouped, for example there is a factor or numerical variable indicating the groups of the data supply it here, otherwise leave it NULL.

Details

The function identifies the variabels with zero range, instead of a zero variance as this is faster. It will work with matrices and data.frames.

Value

A numerical vector of length zero if no zero ranged variable exists, or of length at least one with the index (or indices) of the variable(s) that need attention or need to be removed.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

colrange, colVars

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
res<-check_data(x)

## some variables have a constant value
x[, c(1,10, 50, 70)] <- 1
res<-check_data(x)
id <- rep(1:4, each = 25 )
x[1:25, 2] <- 0
res<-check_data(x)  ## did not use the id variable
res<-check_data(x, id)  ## see now
x <- NULL
```

`Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression`

Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression

---

Description

Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression.

Usage

```
anova_propreg(mod, poia = NULL)
anova_qpois.reg(mod, poia = NULL)
```

Arguments

`mod`	An object as returned by the "prop.reg" or the "qpois.reg" function.
`poia`	If you want to test the significance of a single coefficient this must be a number. In this case, the "prop.reg" or the "qpois.reg" function contains this information. If you want more coefficients to be testes simultaneously, e.g. for a categorical predictor, then this must contain the positions of the coefficients. If you want to see if all coefficients are zero, like an overall F-test, leave this NULL.

Details

Even though the name of this function starts with anova it is not an ANOVA type significance testing, but a Wald type.

Value

A vector with three elements, the test statistic value, its associated p-value and the relevant degrees of freedom.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Papke L. E. & Wooldridge J. (1996). Econometric methods for fractional response variables with an application to 401(K) plan participation rates. Journal of Applied Econometrics, 11(6): 619-632.

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

prop.reg, qpois.reg, univglms, score.glms, logistic_only

Examples

```
y <- rbeta(1000, 1, 4)
x <- matrix(rnorm(1000 * 3), ncol = 3)
a <- prop.reg(y, x)
## all coefficients are tested
res<-anova_propreg(a)
## the first predictor variable is tested
res<-anova_propreg(a, 2)
a  ## this information is already included in the model output
## the first and the second predictor variables are tested
res<-anova_propreg(a, 2:3)
```

Simulation of random values from a Bingham distribution

Simulating from a Bingham distribution

Description

Simulation from a Bingham distribution using the code suggested by Kent et al. (2013).

Usage

```
rbing(n, lam)
```

Arguments

`n`	Sample size.
`lam`	Eigenvalues of the diagonal symmetric matrix of the Bingham distribution. See details for more information on this.

Details

The user must have calculated the eigenvalues of the diagonal symmetric matrix of the Bingham distribution. The function accepts the q-1 eigenvalues only. This means, that the user must have subtracted the lowest eigenvalue from the rest and give the non zero ones. The function uses rejection sampling.

Value

A matrix with the simulated data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

Kent J.T., Ganeiber A.M. and Mardia K.V. (2013). A new method to simulate the Bingham and related distributions in directional data analysis with applications. http://arxiv.org/pdf/1310.8110v1.pdf

C.J. Fallaize and T. Kypraios (2014). Exact Bayesian Inference for the Bingham Distribution. Statistics and Computing (No volum assigned yet). http://arxiv.org/pdf/1401.2894v1.pdf

See Also

`rvmf`

Examples

```
x <- rbing( 100, c(1, 0.6, 0.1) )
x
```

`Simulation of random values from a Bingham distribution with any symmetric matrix`

Simulation of random values from a Bingham distribution with any symmetric matrix

---

Description

Simulation of random values from a Bingham distribution with any symmetric matrix.

Usage

```
rbingham(n, A)
```

Arguments

n	Sample size.
A	A symmetric matrix.

Details

The eigenvalues of the q x q symmetric matrix A are calculated and the smallest of them is subtracted from the rest. The q - 1 non zero eiqenvalues are then passed to rbing. The generated data are then right multiplied by V^T, where V is the matrix of eigenvectors of the matrix A.

Value

A matrix with the simulated data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

Kent J.T., Ganeiber A.M. and Mardia K.V. (2013). A new method to simulate the Bingham and related distributions in directional data analysis with applications. http://arxiv.org/pdf/1310.8110v1.pdf

C.J. Fallaize and T. Kypraios (2014). Exact Bayesian Inference for the Bingham Distribution. Statistics and Computing (No volum assigned yet). http://arxiv.org/pdf/1401.2894v1.pdf

See Also

rvmf

Examples

```
A <- cov( iris[, 1:4] )
x <- rbingham(100, A)
x
```

`Simulation of random values from a normal distribution`
Simulation of random values from a normal distribution

Description

Simulation of random values from a normal distribution.

Usage

```
Rnorm(n, m = 0, s = 1, seed = NULL)
```

Arguments

`n`	The sample size.
`m`	The mean, set to 0 by default.
`s`	The standard devation, set to 1 by default.
`seed`	If you want the same to be generated again use a seed for the generator, an integer number.

Details

By using the Ziggurat method of generating standard normal variates, this function is really fast when you want to generate large vectors. For less than 2,000 this might make no difference when compared with R's "rnorm", but for 10,000 this will be 6-7 times faster.

Value

A vector with n values.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

See Also

`matrnorm`, `rvonmises`, `rvmf`, `rmvnorm`

Examples

```
x <- Rnorm(500)
```

`Simulation of random values from a von Mises-Fisher distribution`
Random values simulation from a von Mises-Fisher distribution

Description

It generates random vectors following the von Mises-Fisher distribution. The data can be spherical or hyper-spherical.

Usage

```
rvmf(n, mu, k, parallel = FALSE)
```

Arguments

`n`	The sample size.
`mu`	The mean direction, a unit vector.
`k`	The concentration parameter. If k = 0, random values from the spherical uniform will be drwan. Values from a multivariate normal distribution with zero mean vector and the identity matrix as the covariance matrix. Then each vector becomes a unit vector.
`parallel`	Run the algorithm in parallel. The parallel algorithm needs memory.

Details

It uses a rejection smapling as suggested by Andrew Wood (1994).

Value

A matrix with the simulated data.

Author(s)

Michail Tsagris and Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm85@gmail.com>

References

Wood A. T. A. (1994). Simulation of the von Mises Fisher distribution. Communications in statistics-simulation and computation, 23(1): 157–164.

Dhillon I. S. & Sra S. (2003). Modeling data using directional distributions. Technical Report TR-03-06, Department of Computer Sciences, The University of Texas at Austin. http://citeseerx.ist.psu.edu/viewdoc/download?

See Also

`vmf.mle`, `rvonmises`, `iag.mle`

Examples

```
m <- rnorm(4)
m <- m/sqrt(sum(m^2))
#x <- rvmf(1000, m, 25)
#res<-vmf.mle(x)
```

Skeleton of the PC algorithm

The skeleton of a Bayesian network produced by the PC algorithm

---

Description

The skeleton of a Bayesian network produced by the PC algorithm.

Usage

```
pc.skel(dataset, method = "pearson", alpha = 0.01, R = 1, stat = NULL, ini.pvalue = NULL)
```

Arguments

`dataset`	A numerical matrix with the variables. If you have a data.frame (i.e. categorical data) turn them into a matrix using `data.frame.to_matrix`. Note, that for the categorical case data, the numbers must start from 0. No missing data are allowed.
`method`	If you have continuous data, you can choose either "pearson" or "spearman". If you have categorical data though, this must be "cat". In this case, make sure the minimum value of each variable is zero. The `g2Test` and the relevant functions work that way.
`alpha`	The significance level (suitable values in (0, 1)) for assessing the p-values. Default (preferred) value is 0.01.
`R`	The number of permutations to be conducted. The p-values are assessed via permutations. Use the default value if you want no permutation based assessment.
`stat`	If the initial test statistics (univariate associations) are available, pass them through this parameter.
`ini.pvalue`	if the initial p-values of the univariate associations are available, pass them through this parameter.

Details

The PC algorithm as proposed by Spirtes et al. (2000) is implemented. The variables must be either continuous or categorical, only. The skeleton of the PC algorithm is order independent, since we are using the third heuristic (Spirte et al., 2000, pg. 90). At every stage of the algorithm use the pairs which are least statistically associated. The conditioning set consists of variables which are most statistically associated with each other of the pair of variables.

For example, for the pair (X, Y) there can be two conditioning sets for example (Z1, Z2) and (W1, W2). All p-values and test statistics and degrees of freedom have been computed at the first step

of the algorithm. Take the p-values between (Z1, Z2) and (X, Y) and between (Z1, Z2) and (X, Y). The conditioning set with the minimum p-value is used first. If the minimum p-values are the same, use the second lowest p-value. If the unlikely, but not impossible, event of all p-values being the same, the test statistic divided by the degrees of freedom is used as a means of choosing which conditioning set is to be used first.

If two or more p-values are below the machine epsilon (.Machine$double.eps which is equal to 2.220446e-16), all of them are set to 0. To make the comparison or the ordering feasible we use the logarithm of p-value. Hence, the logarithm of the p-values is always calculated and used.

In the case of the G^2 test of independence (for categorical data) with no permutations, we have incorporated a rule of thumb. If the number of samples is at least 5 times the number of the parameters to be estimated, the test is performed, otherwise, independence is not rejected according to Tsamardinos et al. (2006). We have modified it so that it calculates the p-value using permutations.

Value

A list including:

`stat`	The test statistics of the univariate associations.
`ini.pvalue`	The initial p-values univariate associations.
`pvalue`	The logarithm of the p-values of the univariate associations.
`runtime`	The amount of time it took to run the algorithm.
`kappa`	The maximum value of k, the maximum cardinality of the conditioning set at which the algorithm stopped.
`n.tests`	The number of tests conducted during each k.
`G`	The adjancency matrix. A value of 1 in G[i, j] appears in G[j, i] also, indicating that i and j have an edge between them.
`sepset`	A list with the separating sets for every value of k.

Author(s)

Marios Dimitriadis.

R implementation and documentation: Marios Dimitriadis <kmdimitriadis@gmail.com>.

References

Spirtes P., Glymour C. and Scheines R. (2001). Causation, Prediction, and Search. The MIT Press, Cambridge, MA, USA, 3nd edition.

Tsamardinos I., Borboudakis G. (2010) Permutation Testing Improves Bayesian Network Learning. In Machine Learning and Knowledge Discovery in Databases. ECML PKDD 2010. 322-337.

Tsamardinos I., Brown E.L. and Aliferis F.C. (2006). The max-min hill-climbing Bayesian network structure learning algorithm. Machine learning 65(1):31-78.

See Also

`g2Test`, `g2Test_univariate`, `cora`, `correls`

Examples

```
# simulate a dataset with continuous data
dataset <- matrnorm(100, 10)
a <- pc.skel(dataset, method = "pearson", alpha = 0.05)
```

`Skewness and kurtosis coefficients`
Skewness and kurtosis coefficients

Description

Skewness and kurtosis coefficients.

Usage

```
skew(x, pvalue = FALSE)

kurt(x, pvalue = FALSE)
```

Arguments

`x`	A numerical vector with data.
`pvalue`	If you want a hypothesis test that the skewness or kurtosis are significant set this to TRUE. This checks whether the skewness is significantly different from 0 and whether the kurtosis is significantly different from 3.

Details

The sample skewness and kurtosis coefficient are calculated. For the kurtosis we do not subtract 3.

Value

If "pvalue" is FALSE (default value) the skewness or kurtosis coefficients are returned. Otherwise, the p-value of the significance of the coefficient is returned.

Author(s)

Klio Lakiotaki

R implementation and documentation: Klio Lakiotaki <kliolak@gmail.com>.

References

https://en.wikipedia.org/wiki/Skewness

https://en.wikipedia.org/wiki/Kurtosis

See Also

`colskewness`, `skew.test2`, `colmeans`, `colVars`, `colMedians`

Examples

```
x <- rgamma(500,1, 4)
res<-skew(x)
res<-kurt(x, TRUE)
```

Some summary statistics of a vector for each level of a grouping variable

Some summary statistics of a vector for each level of a grouping variable

---

Description

Some summary statistics of a vector for each level of a grouping variable.

Usage

```
group(x,ina,method="sum",ina.min=NULL,ina.max = NULL,
 ina.length.unique=NULL,mad.method="median", std = FALSE, sorted = TRUE)
group.sum(x, ina,ina.max = NULL,ina.min = NULL)
```

Arguments

x	A numerical vector with data.
ina	A numerical vector with numbers. Note that zero and negative values are not allowed as this can cause R to run forever or crash.
ina.length.unique	Length of the unique numerical values of ina argument.
method	A character vector with values "sum", "var", "all", "any", "mad", "mean", "med", "min", "max", "min.max".
ina.max	Maximum number for vector ina.
ina.min	Minimum number for vector ina.
mad.method	A character vector with values "median", for median absolute deviation or "mean", for mean absolute deviation. This works only with method="mad".
std	A boolean value for method **var** for using standard deviation.
sorted	A boolean value for getting the results sorted based on ina.

Details

This command works only for vectors. Median absolute deviation, mean, median, minimum, maximum are some of the options offered.

Value

A vector with the variance, or standard deviation, or mean, or minimum, or maximum, or median, or minimum-maximum of x for each distinct value of ina.

Author(s)

Manos Papadakis and Michail Tsagris

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com> and Michail Tsagris <mtsagris@uoc.gr>.

See Also

colmeans, colVars, colMedians

Examples

```
x <- rgamma(100,1, 4)
ina <- sample(1:5, 100, TRUE)
res<-group(x, ina,method="var")
```

Sort - Integer Sort - Sort a vector coresponding to another

Sort - Integer Sort - Sort a vector coresponding to another

Description

Fast sorting a vector.

Usage

```
Sort(x,descending=FALSE,partial=NULL,stable=FALSE,na.last=NULL,parallel = FALSE)
Sort.int(x)
sort_cor_vectors(x, base, stable = FALSE, descending = FALSE)
```

Arguments

x	A numerical/integer/character vector with data.
base	A numerical/character vector to help sorting the x.
descending	A boolean value (TRUE/FALSE) for sorting the vector in descending order. By default sorts the vector in ascending.
partial	This argument has two usages. The first is an index number for sorting partial the vector. The second is a vector with 2 values, start and end c(start,end). Gives you a vector where the elements between start and end will be sorted only. Not character vector.
stable	A boolean value (TRUE/FALSE) for choosing a stable sort algorithm. Stable means that discriminates on the same elements. Not character vector.
na.last	Accept 4 values. TRUE, FALSE, NA, NULL. TRUE/FALSE: for put NAs last or first. NA: for remove NAs completely from vector. NULL: by default. Leave it like that if there is no NA values.

`parallel` Do you want to do it in parallel, in C++? TRUE or FALSE. (Supported on Windows and most of the unix)

Details

This function uses the sorting algorithm from C++. The implementation is very fast and highly optimised. Especially for large data.

Value

Sort and Sort.int: The sorted vector.

sort_cor_vectors: The first argument but sorted acording to the second.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`nth`, `colnth`, `rownth`,`sort_unique`, `Round`

Examples

```
x <- rnorm(1000)
s1 <- Sort(x)
s2 <- sort(x)
all.equal(s1,s2) #true  but not if many duplicates.

s1 <- Sort(x,partial=100)
s2 <- sort(x,partial=100)
all.equal(s1,s2) #true


s1 <- Sort(x,stable=TRUE)
s2 <- sort(x)
all.equal(s1,s2) #true

x <- as.character(x)
s1 <- Sort(x)
s2 <- sort(x)
all.equal(s1,s2) #true

y <- runif(1000)
b <- sort_cor_vectors(x,y)

x<-rpois(100,100)
all.equal(Sort.int(x),sort.int(x))

x<-y<-y<-s1<-s2<-NULL
```

`Sort and unique numbers` *Sort and unique*

Description

Sort and unique numbers.

Usage

```
sort_unique(x)
sort_unique.length(x)
Unique(x, fromLast = FALSE)
```

Arguments

`x`	A numeric vector.
`fromLast`	logical indicating if duplication should be considered from the last, i.e., the last (or rightmost) of identical elements will be kept. This only matters for names or dimnames.

Details

The "sort_unique" function implements R's "unique" function using C++'s function but also sort the result. The "sort_unique.length" returns the length of the unique numbers only for **itegers**.

Value

Returns the discrete values or sorted or their length (depending on the function you do).

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>

See Also

`colSort`, `rowSort`, `sort_cor_vectors`

Examples

```
y <- rnorm(100)
a <- sort_unique(y)
b <- sort.int(unique(y))
all.equal(as.vector(a),as.vector(b))
x <- rpois(1000,10)
sort_unique.length(x)
length(sort_unique(x))
```

```
x<-a<-b<-NULL
```

Sorting of the columns-rows of a matrix

Sorting of the columns-rows of a matrix

Description

Fast sorting of the columns-rows of a matrix.

Usage

```
colSort(x, descending = FALSE, stable = FALSE, parallel=FALSE, cores = 0)
rowSort(x, descending = FALSE, stable = FALSE, parallel=FALSE, cores = 0)
sort_mat(x,by.row=FALSE,descending=FALSE,stable=FALSE,parallel=FALSE)
```

Arguments

x	A numerical matrix or data.frame with data.
descending	If you want the sorting in descending order, set this to TRUE.
stable	If you the stable version, so that the results are the same as R's (in the case of ties) set this to TRUE. If this is TRUE, the algorithm is a bit slower.
parallel	Do you want to do it in parallel in C++? TRUE or FALSE. Works with every other argument.
by.row	TRUE or FALSE for applying sort in rows or column.
cores	Number of cores to use for parallelism. Valid only when argument parallel is set to TRUE. Default value is 0 and it means the maximum supported cores.

Value

The matrix with its columns-rows (or rows) independently sorted.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

nth, colMaxs, colMins, colrange, sort_cor_vectors,sort_unique

Examples

```
x <- matrix( rnorm(100 * 200), ncol = 200 )
s1 <- colSort(x)
#s2 <- apply(x, 2, sort)
#all.equal(as.vector(s1), as.vector(s2))

x<-NULL
```

Source many R files *Source many R files*

Description

Source many R/Rd files.

Usage

```
sourceR(path,local=FALSE,encode = "UTF-8",print.errors=FALSE)
sourceRd(path,print.errors=FALSE, macros = NULL)
```

Arguments

path	An full path to the directory where R file are.
local	TRUE, FALSE or an environment, determining where the parsed expressions are evaluated. FALSE (the default) corresponds to the user's workspace (the global environment) and TRUE to the environment from which source is called.
encode	Character vector. The encoding(s) to be assumed when file is a character string: see file. A possible value is "unknown" when the encoding is guessed: see the "Encodings" section.
print.errors	A boolean value (TRUE/FALSE) for printing the errors, if exists, for every file.
macros	A full or relative path to the macros file.

Details

Reads many R files and source them.

Value

Returns the files that had produced errors during source.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

AddToNamespace

Examples

```
# for example: path="C:\some_file\R\" where is R files are
# system.time( a<-sourceR(path) )
# for example: path="C:\some_file\man\" where is Rd files are
# system.time( a<-sourceRd(path) )
```

`Spatial median for Euclidean data`

Spatial median for Euclidean data

Description

Spatial median for Euclidean data.

Usage

```
spat.med(x, tol = 1e-09)
```

Arguments

`x`	A matrix with Euclidean data, continuous variables.
`tol`	A tolerance level to terminate the process. This is set to 1e-09 by default.

Details

The spatial median, using a fixed point iterative algorithm, for Euclidean data is calculated. It is a robust location estimate.

Value

A vector with the spatial median.

Author(s)

Manos Papadakis and Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

Jyrki Mottonen, Klaus Nordhausen and Hannu Oja (2010). Asymptotic theory of the spatial median. In Nonparametrics and Robustness in Modern Statistical Inference and Time Series Analysis: A Festschrift in honor of Professor Jana Jureckova.

T. Karkkaminen and S. Ayramo (2005). On computation of spatial median for robust data mining. Evolutionary and Deterministic Methods for Design, Optimization and Control with Applications to Industrial and Societal Problems, EUROGEN 2005, R. Schilling, W.Haase, J. Periaux, H. Baier, G. Bugeda (Eds) FLM, Munich. http://users.jyu.fi/~samiayr/pdf/ayramo_eurogen05.pdf

See Also

colMedians

Examples

```
res<-spat.med( as.matrix( iris[, 1:4] ) )
res<-colMeans( as.matrix(iris[, 1:4]) )
res<-colMedians( as.matrix(iris[, 1:4]) )
```

Spatial median regression

Spatial median regression

Description

Spatial median regression with Euclidean data.

Usage

```
spatmed.reg(y, x, tol = 1e-07)
```

Arguments

y	A matrix with the response variable.
x	The predictor variable(s), they have to be continuous.
tol	The threshold upon which to stop the iterations of the Newton-Rapshon algorithm.

Details

The objective function is the minimization of the sum of the absolute residuals. It is the multivariate generalisation of the median regression.

Value

A list including:

iters	The number of iterations that were required.
be	The beta coefficients.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Biman Chakraborty (2003) On multivariate quantile regression. Journal of Statistical Planning and Inference http://www.stat.nus.edu.sg/export/sites/dsap/research/documents/tr01_2000.pdf

See Also

spat.med, sscov, lmfit

Examples

```
x <- as.matrix(iris[, 3:4])
y <- as.matrix(iris[, 1:2])
mod1 <- spatmed.reg(y, x)
```

`Spatial sign covariance matrix`

Spatial sign covariance matrix

Description

Spatial sign covariance matrix.

Usage

```
sscov(x, me = NULL, tol = 1e-09)
```

Arguments

x	A matrix with continuous data.
me	If you have already computed the spatial median plug it in here.
tol	A tolerance level to terminate the process of finding the spatial median. This is set to 1e-09 by default.

Details

The spatial median is at first computed (if not supplied) and then the covariance matrix.

Value

The spatial sign covariance matrix.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Durre A, Vogel D. and D.E. Tyler D.E.(2014). The spatial sign covariance matrix with unknown location. Journal of Multivariate Analysis, 130: 107-117. http://arxiv.org/pdf/1307.5706v2.pdf

See Also

spat.med, spatmed.reg

Examples

```
res<-sscov( as.matrix(iris[, 1:4]) )
```

Spherical and hyperspherical median

Fast calculation of the spherical and hyperspherical median

Description

It calculates, very fast, the (hyper-)spherical median of a sample.

Usage

```
mediandir(x)
```

Arguments

x	The data, a numeric matrix with unit vectors.

Details

The "mediandir" employes a fixed poit iterative algorithm stemming from the first derivative (Cabrera and Watson, 1990) to find the median direction as described in Fisher (1985) and Fisher, Lewis and Embleton (1987).

Value

The median direction.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Fisher N. I. (1985). Spherical medians. Journal of the Royal Statistical Society. Series B, 47(2): 342-348.

Fisher N. I., Lewis T. and Embleton B. J. (1987). Statistical analysis of spherical data. Cambridge university press.

Cabrera J. and Watson G. S. (1990). On a spherical median related distribution. Communications in Statistics-Theory and Methods, 19(6): 1973-1986.

See Also

vmf.mle

Examples

```
m <- rnorm(3)
m <- m / sqrt( sum(m^2) )
#x <- rvmf(100, m, 10)
#res<-mediandir(x)
x <- NULL
```

`Standardisation` *Standardisation*

Description

Standardisation.

Usage

```
standardise(x, center = TRUE, scale = TRUE)
```

Arguments

`x`	A matrix with data. It has to be matrix, if it is data.frame for example the function does not turn it into a matrix.
`center`	Should the data be centred as well? TRUE or FALSE.
`scale`	Should the columns have unit variance, yes (TRUE) or no (FALSE)?

Details

Similar to R's built in functions "scale" there is the option for centering or scaling only or both (default).

Value

A matrix with the standardised data.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

`colVars`, `colmeans`, `colMads`

Examples

```
x <- matrnorm( 100, 100 )
a1 <- scale(x)[1:100, ]
a2 <- standardise(x)
all.equal(as.vector(a1), as.vector(a2))
x <- NULL
```

Sub-matrix *Sub-matrix*

Description

Sub-matrix.

Usage

```
submatrix(x,rowStart=1,rowEnd=1,colStart=1,colEnd=1)
```

Arguments

`x`	A Matrix, List, Dataframe or Vector.
`rowStart`	Start of the row.
`rowEnd`	End of the row.
`colStart`	Start of the col.
`colEnd`	End of the col.

Value

sub matrix like R's, x[startrow:endrow,startcol:endcol]. Fast especially for big sub matrices.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

Match, mvbetas, correls, univglms, colsums, colVars

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100 )
res<-submatrix(x,1,50,1,25) # x[1:50,1:25]

x<-NULL
```

Table Creation - Frequency of each value

Table Creation - Frequency of each value

Description

Table Creation - Frequency of each value.

Usage

```
Table(x,y=NULL,names = TRUE,useNA = FALSE,rm.zeros = FALSE)
Table.sign(x,names = TRUE,useNA = FALSE)
```

Arguments

x	A vector with numeric/character data.
names	A logical value (TRUE/FALSE) for add names.
y	A vector with numeric/character data. Doesn't work with "useNA".
rm.zeros	A logical value for removing zero columns/rows. Only for integer vectors for now.
useNA	Table: Integer/logical value: FALSE: not NA values in vector. TRUE: count NAs and add the value in the last position of the returned vector. any other integer except 0,1: for just removing NAs. Table.sign: Logical value, TRUE, for count NAs. Otherwise FALSE. Doesn't work character data.

Details

Like R's "table":

for giving one argument,"x": If "names" is FALSE then, if "useNA" is TRUE then the NAs will be count, if is FALSE it means there are no NAs and for any other integer value the NAs will be ignored.

for giving two arguments,"x","y": If "names" is FALSE then, creates the contigency table, otherwise sets the col-row names with discrete values. If "rm.zeros" is FALSE then it won't remove the zero

columns/rows from the result but it will work only for positive integers for now. For this if "names" is TRUE then the col-row names will be the seq(min(),max()) for "x","y". In future updates it will be changed.

for both algorithms: You can't use "useNA" with "names" for now. It is much faster to get the result without names (names = FALSE) but all the algorithms are more efficient than R's.

Like R's "table(sign())" but more efficient. Count the frequencies of positives, negatives, zeros and NAs values. If argument "names" is FALSE then the returned vector doesn't have names. Otherwise "-1,0,+1,NA". If "useNA" is TRUE then the NAs will be count, otherwise not. You can use "useNA" with "names".

Value

Table:

for giving one argument,"x": if "names" is TRUE then return a vector with names the discrete values of "x" and values there frequencies, otherwise only the frequencies

for giving two arguments,"x","y": if "names" is TRUE then return a contigency matrix with row-names the discrete values of "x", colnames the dicrete values of "y" and values the freuquencies of the pairs, otherwise only the freuquencies of the pairs.

Table.sign: A vector with 4 values/frequencies: index 1: negatives index 2: zeros index 3: postives if "names" is TRUE then the returned vector have names "-1,0,+1". if "useNA" is TRUE then 4th value has the frequencies of NAs and the returned vector will have one more name, "-1,0,+1,NA", if "names" is also TRUE.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

colShuffle, colVars, colmeans, is_integer, as_integer

Examples

```
x<-runif(10)
y1<-Table(x)
y2<-as.vector(table(x)) # Neads a lot of time.
all.equal(y1,y2)
y1<-Table(x,names=FALSE)
all.equal(y1,y2) # the name attribute of y1 is null

y1<-Table.sign(x)
y2<-table(sign(x))
all.equal(y1,y2)

x<-y1<-y2<-NULL
```

`Tests for the dispersion parameter in Poisson distribution`
Tests for the dispersion parameter in Poisson distribution

Description

Tests for the dispersion parameter in Poisson distribution.

Usage

```
poisdisp.test(y, alternative = "either", logged = FALSE)
pois.test(y, logged = FALSE)
```

Arguments

`y`	A numerical vector with count data, 0, 1,...
`alternative`	Do you want to test specifically for either over or underspirsion ("either"), overdispersion ("over") or undersispersion ("under")?
`logged`	Set to TRUE if you want the logarithm of the p-value.

Value

A vector with two elements, the test statistic and the (logged) p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

References

Yang Zhao, James W. Hardin, and Cheryl L. Addy. (2009). A score test for overdispersion in Poisson regression based on the generalized Poisson-2 model. Journal of statistical planning and inference 139(4): 1514-1521.

Dimitris Karlis and Evdokia Xekalaki (2000). A Simulation Comparison of Several Procedures for Testing the Poisson Assumption. Journal of the Royal Statistical Society. Series D (The Statistician), 49(3): 355-382.

Bohning, D., Dietz, E., Schaub, R., Schlattmann, P. and Lindsay, B. (1994) The distribution of the likelihood ratio for mixtures of densities from the one-parameter exponential family. Annals of the Institute of Statistical Mathematics, 46(): 373-388.

See Also

`poisson.mle`, `negbin.mle`, `poisson.anova`, `poisson.anovas`, `poisson_only`

Examples

```
y <- rnbinom(500, 10, 0.6)
res<-poisdisp.test(y, "either")
res<-poisdisp.test(y, "over")
res<-pois.test(y)

y <- rpois(500, 10)
res<-poisdisp.test(y, "either")
res<-poisdisp.test(y, "over")
res<-pois.test(y)
```

`Topological sort of a DAG`

Topological sort of a DAG

Description

Topological sort of a DAG.

Usage

```
topological_sort(dag)
```

Arguments

`dag`	A square matrix representing a directed graph which contains 0s and 1s. If G[i, j] = 1 it means there is an arrow from node i to node j. When there is no edge between nodes i and j if G[i, j] = 0.

Details

The function is an R translation from an old matlab code.

Value

A vector with numbers indicating the sorting. If the dag is not a Directed acyclic Graph, NA will be returned.

Author(s)

Michail Tsagris and Manos Papadakis

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>

References

Chickering, D.M. (1995). A transformational characterization of equivalent Bayesian network structures. Proceedings of the 11th Conference on Uncertainty in Artificial Intelligence, Montreal, Canada, 87-98.

See Also

floyd, pc.skel

Examples

```
G <- matrix(0, 5, 5)
G[2, 1] <- 1
G[3, 1] <- 1
G[4, 2] <- 1
G[5, 4] <- 1
res<-topological_sort(G)
G[2, 4] <- 1
res<-topological_sort(G)
```

Transpose of a matrix *Transpose of a matrix*

Description

Transpose of a matrix.

Usage

```
transpose(x)
```

Arguments

x	A numerical **square** matrix with data.

Value

The transposed matrix.

Author(s)

Manos Papadakis

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

References

Gilbert Strang (2006). Linear Algebra and its Applications (4th edition).

See Also

nth, colMaxs, colMins, colrange

Examples

```
x <- matrix( rnorm(100 * 100), ncol = 100, nrow=100 )
transpose(x) #t(x)

x<-NULL
```

`Uniformity test for circular data`
Uniformity tests for circular data

Description

Hypothesis tests of uniformity for circular data.

Usage

```
kuiper(u)

watson(u)
```

Arguments

`u`	A numeric vector containing the circular data which are expressed in radians.

Details

These tests are used to test the hypothesis that the data come from a circular uniform distribution.

Value

A vector with two elements, the value of the test statistic and its associated p-value.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Jammalamadaka, S. Rao and SenGupta, A. (2001). Topics in Circular Statistics, pg. 153-55 (Kuiper's test) & 156-157 (Watson's test).

See Also

`vmf.mle`, `rvonmises`

Examples

```
#x <- rvonmises(n = 50, m = 2, k = 10)
#res<-kuiper(x)
#res<-watson(x)
x <- runif(50, 0, 2 * pi)
#res<-kuiper(x)
#res<-watson(x)
```

Variance of a vector *Variance (and standard deviation) of a vector*

Description

Variance (and standard deviation) of a vector.

Usage

```
Var(x, std = FALSE,na.rm = FALSE)
```

Arguments

x	A vector with data.
std	If you want the standard deviation set this to TRUE, otherwise leave it FALSE.
na.rm	TRUE or FAlSE for remove NAs if exists.

Details

This is a faster calculation of the usual variance of a matrix.

Value

The variance of the vector.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Manos Papadakis <papadakm95@gmail.com>.

See Also

colVars, cova

Examples

```
x <- rnorm(100)
a1 <- Var(x)
a2 <- var(x)
x<-NULL
```

`Vector allocation in a symmetric matrix`
Vector allocation in a symmetric matrix

Description

Vector allocation in a symmetric matrix.

Usage

```
squareform(x)
```

Arguments

x	An numverical vector whose size must be the one that matches the dimensions of the final matrix. See examples.

Details

The functions is written in C++ in order to be as fast as possible.

Value

A symmetric matrix. The vector is allocated in the upper and in the lower part of the matrix. The diagonal is filled with zeros.

Author(s)

R implementation and documentation: Manos Papadakis <papadakm95@gmail.com>.

See Also

`colShuffle`, `colVars`, `colmeans`

Examples

```
x <- rnorm(1)
res<-squareform(x)  ## OK
x <- rnorm(3)
res<-squareform(x)  ## OK
x <- rnorm(4)
res<-squareform(x)  ## not OK
```

Weibull regression model
Weibull regression model

Description

Weibull regression model.

Usage

```
weib.reg(y, x, tol = 1e-07, maxiters = 100)
```

Arguments

y	The dependent variable; a numerical vector with strictly positive data, i.e. greater than zero.
x	A matrix with the data, where the rows denote the samples (and the two groups) and the columns are the variables. This can be a matrix or a data.frame (with factors).
tol	The tolerance value to terminate the Newton-Raphson algorithm.
maxiters	The max number of iterations that can take place in each regression.

Details

The function is written in C++ and this is why it is very fast. No standard errors are returned as they are not corectly estimated. We focused on speed.

Value

When full is FALSE a list including:

iters	The iterations required by the Newton-Raphson.
loglik	The log-likelihood of the model.
shape	The shape parameter of the Weibull regression.
be	The regression coefficients.

Author(s)

Stefanos Fafalios

R implementation and documentation: Stefanos Fafalios <stefanosfafalios@gmail.com>.

References

McCullagh, Peter, and John A. Nelder. Generalized linear models. CRC press, USA, 2nd edition, 1989.

See Also

poisson_only, logistic_only, univglms, regression

Examples

```
x <- matrix(rnorm(100 * 2), ncol = 2)
y <- rexp(100, 1)
res<-weib.reg(y, x)
```

`Yule's Y (coefficient of colligation)`

Yule's Y (coefficient of colligation)

Description

Yule's Y (coefficient of colligation).

Usage

```
yule(x)
```

Arguments

x	A 2 x 2 matrix or a vector with 4 elements. In the case of the vector make sure it corresponds to the correct table.

Details

Yule's coefficient of colligation is calculated.

Value

Yule's Y is returned.

Author(s)

Michail Tsagris

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>

References

Yule G. Udny (1912). On the Methods of Measuring Association Between Two Attributes. Journal of the Royal Statistical Society, 75(6):579-652.

See Also

col.yule, odds.ratio

Examples

```
x <- rpois(4, 30) + 2
res<-yule(x)
res<-yule( matrix(x, ncol = 2) )
```

Index

!=.iterator *(Iterator)*, 122
* **2 sample proportions tests**
    Many 2 sample proportions tests, 136
* **2 variances test**
    Many 2 sample tests, 137
* **AR(1) model**
    Estimation of an AR(1) model, 87
* **All possibe combinations**
    All k possible combinations from n elements, 8
* **Analysis of covariance**
    Analysis of covariance, 9
    Many ANCOVAs, 140
* **Analysis of variance**
    Analysis of variance with a count variable, 11
* **Angular central Gaussian distribution**
    Angular central Gaussian random values simulation, 12
* **Area aunder the curve**
    Many (and one) area under the curve values, 135
* **BIC**
    BIC (using partial correlation) forward regression, 17
    BIC forward regression with generalised linear models, 18
* **Beta distribution**
    MLE of distributions defined in the (0, 1) interval, 194
* **Beta function**
    Natural logarithm of the beta function, 214
* **Binary search Algorithm**
    Binary search algorithm, 20
* **Bradley-Terry model**
    Fitted probabilities of the Terry-Bradley model, 98
* **Canberra distance**
    Distance matrix - Sum of all pairwise distances in a distance matrix, 78
* **Cauchy**
    MLE of continuous univariate distributions defined on the real line, 191
* **Checking Alias**
    Check Namespace and Rd files, 25
* **Checking Examples**
    Check Namespace and Rd files, 25
* **Checking Rd**
    Check Namespace and Rd files, 25
* **Checking R**
    Check Namespace and Rd files, 25
* **Checking Usage section**
    Check Namespace and Rd files, 25
* **Checking for FALSE**
    Check Namespace and Rd files, 25
* **Checking for TRUE**
    Check Namespace and Rd files, 25
* **Cholesky decomposition**
    Cholesky decomposition of a square matrix, 30
* **Circular data**
    Column-wise uniformity Watson test for circular data, 58
    Uniformity test for circular data, 273
* **Circular regression**
    Circular or angular regression(s), 31
* **Circular-linear correlation**
    Circular-linear correlation, 33
* **Cochran's Q test**
    Many non parametric multi-sample tests, 152
* **Coefficient matrices**

Coefficient matrices, 34
* **Column means**
Column and row-wise means of a matrix, 38
* **Column sums**
Column and row-wise sums of a matrix, 47
* **Column-Row wise checking**
Check if any column or row is fill with values, 23
* **Column-wise Any**
Column and row-wise Any/All, 37
* **Column-wise Shuffle**
Column and row-wise Shuffle, 46
* **Column-wise median absolute deviations**
Column and rows-wise mean absolute deviations, 50
* **Column-wise medians**
Column and row-wise medians of a matrix or median of a vector., 39
* **Column-wise minimum**
Column-wise minimum and maximum, 54
* **Column-wise nth**
Column and row-wise nth smallest value of a matrix/vector, 40
* **Column-wise ranges**
Column and row-wise range of values of a matrix, 44
* **Column-wise tabulate**
Column and row-wise tabulate, 48
* **Column-wise true**
Column-wise true/false value, 57
* **Column-wise variances**
Column and row-wise variances and standard deviations, 49
* **Column-wise**
Column-wise MLE of some univariate distributions, 55
* **Combinatorics**
All k possible combinations from n elements, 8
* **Continuous distributions**
MLE of continuous univariate distributions defined on the positive line, 189
MLE of continuous univariate distributions defined on the real line, 191
* **Correlations**
Correlation between pairs of variables, 63
Correlations, 65
* **Covariance matrix**
Covariance and correlation matrix, 66
* **Create - Fill**
Diagonal Matrix, 75
* **DAG**
Topological sort of a DAG, 271
* **Data Frame**
Index of the columns of a data.frame which are a specific type, 117
* **Dataframe to Matrix**
Convert a dataframe to matrix, 60
* **Deep copy**
Deep copy, 72
* **Design Matrix**
Design Matrix, 74
* **Determinant**
Check if any column or row is fill with values, 23
* **Diagonal Matrix**
Diagonal Matrix, 75
* **Differences**
Column-wise differences, 51
* **Directional k-NN algorithm**
k-NN algorithm using the arc cosinus distance, 127
* **Dirichlet distribution**
Fitting a Dirichlet distribution via Newton-Rapshon, 99
* **Discrimination**
Prediction with some naive Bayes classifiers, 230
* **Distance covariance**
Distance variance, covariance and correlation, 80
* **Distance matrix - Sum of all pairwise distances in a distance matrix**
Distance matrix - Sum of all pairwise distances in a distance matrix, 78
* **Distance variance**
Distance variance, covariance and

correlation, 80
* **Distances**
Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix., 76
* **Divide and Qonquer**
Binary search algorithm, 20
Find element, 96
* **Eigenvalues**
Eigenvalues and eigenvectors in high dimensional principal component analysis, 82
* **Energy distances**
Energy distance between matrices, 86
* **Environment**
Deep copy, 72
Iterator, 122
Represantation of Stack, 241
* **Euclidean distance**
Distance matrix - Sum of all pairwise distances in a distance matrix, 78
* **Exponential regressions**
Many exponential regressions, 142
* **Export functions**
Insert/remove function names in/from the NAMESPACE file, 118
Source many R files, 261
* **Extract columns/rows**
Get specific columns/rows fo a matrix, 108
* **F-tests**
Many F-tests with really huge matrices, 144
Many multi-sample tests, 150
* **F-test**
Multi-sample tests for vectors, 205
* **Factor variables**
Index of the columns of a data.frame which are a specific type, 117
* **Factorials**
Binomial coefficient and its logarithm, 21
* **Factor**
Fast and general - untyped represantation of a factor variable, 93
* **Find Value**
Find the given value in a hash table, 97
* **Find element**
Find element, 96
* **Floyd-Warshall algorithm**
Floyd-Warshall algorithm, 100
* **Forward regression**
BIC (using partial correlation) forward regression, 17
BIC forward regression with generalised linear models, 18
Correlation based forward regression, 62
Forward selection with generalised linear regression models, 101
* **GLMS**
Many score based regressions, 161
* **GLMs**
Quasi binomial regression for proportions, 231
Quasi Poisson regression for count data, 233
Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression, 247
* **G^2 test of conditional independence**
Chi-square and G-square tests of (unconditional) indepdence, 29
G-square and Chi-square test of conditional indepdence, 102
* **G^2 test of independence**
Matrix with G-square tests of indepedence, 181
* **G^2 tests of independence**
Many G-square and Chi-square tests of indepedence, 145
* **G^2 test**
Rfast-package, 7
* **Gini coefficient**
One and many Gini coefficients, 219
* **Goodness of fit test**
Hypothesis test for von Mises-Fisher distribution over Kent distribution, 115

∗ **Gumbel distribution**
MLE of continuous univariate distributions defined on the real line, 191
∗ **Hash Function**
Find the given value in a hash table, 97
Hash - Pair function, 109
∗ **Hash tables**
Hash object, 110
Hash object to a list object, 111
∗ **Hellinger distance**
Distance matrix - Sum of all pairwise distances in a distance matrix, 78
∗ **High dimensional data**
High dimensional MCD based detection of outliers, 112
∗ **Hypothesis testing**
Empirical and exponential empirical likelihood tests for one sample, 83
Empirical and exponential empirical likelihood tests for two samples, 84
Many one sample tests, 156
∗ **Hypothesis test**
Exponential empirical likelihood for a one sample mean vector hypothesis testing, 90
∗ **Integer variables**
Index of the columns of a data.frame which are a specific type, 117
∗ **Inverse matrix**
Inverse of a symmetric positive definite matrix, 121
∗ **Inverted Dirichlet distribution**
MLE of the inverted Dirichlet distribution, 197
∗ **James test**
Multi-sample tests for vectors, 205
∗ **Kent distribution**
Hypothesis test for von Mises-Fisher distribution over Kent distribution, 115
∗ **Laplace distribution**
MLE of continuous univariate distributions defined on the real line, 191
∗ **Linear mixed models**
Column and row wise coefficients of variation, 36
Many random intercepts LMMs for balanced data with a single identical covariate., 157
Random intercepts linear mixed models, 235
∗ **Linear models**
Linear models for large scale data, 129
∗ **Linear time**
Find element, 96
∗ **Log matrix**
Natural Logarithm each element of a matrix, 213
∗ **Logarithm of gamma function**
Natural logarithm of the gamma function and its derivatives, 215
∗ **Logical variables**
Index of the columns of a data.frame which are a specific type, 117
∗ **Logistic distribution**
MLE of continuous univariate distributions defined on the real line, 191
∗ **Logistic regressions**
Many univariate simple logistic and Poisson regressions, 175
∗ **Logistic regression**
Logistic and Poisson regression models, 130
Logistic or Poisson regression with a single categorical predictor, 132
∗ **Lower and Upper triangular of a matrix**
Lower and Upper triangular of a matrix, 133
∗ **MCD estimation**
High dimensional MCD based detection of outliers, 112
∗ **Mahalanobis distance**
Mahalanobis distance, 134
∗ **Manhattan distance**

Distance matrix - Sum of all pairwise distances in a distance matrix, 78
* **Many betas in regression**
Many multivariate simple linear regressions coefficients, 151
Many simple linear regressions coefficients, 166
* **Match Function**
Match, 178
* **Matrices**
Number of equal columns between two matrices, 217
* **McNemar's test**
Many 2 sample tests, 137
* **Median direction**
Spherical and hyperspherical median, 265
* **Multinomial distribution**
MLE for multivariate discrete data, 186
Multinomial regression, 207
* **Multivariate analysis of variance**
James multivariate version of the t-test, 123
* **Multivariate data**
Multivariate kurtosis, 208
* **Multivariate hypothesis testing**
Exponential empirical likelihood hypothesis testing for two mean vectors, 92
* **Multivariate normal distribution**
Density of the multivariate normal and t distributions, 73
MLE of the multivariate (log-) normal distribution, 198
* **Namespace file**
Check Namespace and Rd files, 25
Insert/remove function names in/from the NAMESPACE file, 118
Source many R files, 261
* **Newton-Raphson**
Fitting a Dirichlet distribution via Newton-Rapshon, 99
MLE of distributions defined in the (0, 1) interval, 194
* **Norm of a matrix**
Norm of a matrix, 216
* **Numeric variables**
Index of the columns of a data.frame which are a specific type, 117
* **Odds ratios**
Many odds ratio tests, 154
* **Odds ratio**
Odds ratio and relative risk, 218
* **One sample t-test**
One sample t-test for a vector, 220
* **Orderings**
Column and row-wise Order - Sort Indices, 41
* **Ordinal model**
MLE of the ordinal model without covariates, 201
* **PC algorithm**
Skeleton of the PC algorithm, 253
* **Pair Function**
Hash - Pair function, 109
* **Pairs of vectors**
Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices, 183
* **Pareto**
MLE of continuous univariate distributions defined on the positive line, 189
* **Pearson correlation**
Correlation based forward regression, 62
* **Permutation Function**
Permutation, 226
* **Poisson distribution**
Analysis of variance with a count variable, 11
Many analysis of variance tests with a discrete variable, 139
Many tests for the dispersion parameter in Poisson distribution, 169
MLE of count data (univariate discrete distributions), 192
Prediction with some naive Bayes classifiers, 230
Tests for the dispersion parameter in Poisson distribution, 270

* **Poisson regressions**
  Many univariate simple quasi poisson regressions, 176
* **Poisson regression**
  Logistic or Poisson regression with a single categorical predictor, 132
* **Poisson**
  Forward selection with generalised linear regression models, 101
* **Products**
  Column and row-wise products, 43
* **Quasi Poisson regression**
  Quasi Poisson regression for count data, 233
* **Quasi regression**
  Quasi binomial regression for proportions, 231
  Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression, 247
* **Random values simulation**
  Random values simulation from a von Mises distribution, 236
  Simulation of random values from a von Mises-Fisher distribution, 252
* **Read Examples**
  Reading the files of a directory, 237
* **Read directory**
  Reading the files of a directory, 237
* **Remove functions**
  Insert/remove function names in/from the NAMESPACE file, 118
* **Repeated measures**
  Many regression based tests for single sample repeated measures, 159
  Repeated measures anova, 238
* **Replicate in columns/rows**
  Replicate columns/rows, 240
* **Round vector/matrix**
  Round each element of a matrix/vector, 242
* **Row - Wise matrix/vector count the frequency of a value**
  Row - Wise matrix/vector count the frequency of a value, 243
* **Row sums**
  Column and row-wise sums of a matrix, 47
* **Row-wise Any**
  Column and row-wise Any/All, 37
* **Row-wise Shuffle**
  Column and row-wise Shuffle, 46
* **Row-wise false**
  Row-wise true value, 245
* **Row-wise medians**
  Column and row-wise medians of a matrix or median of a vector., 39
* **Row-wise minimum**
  Row-wise minimum and maximum, 244
* **Row-wise nth**
  Column and row-wise nth smallest value of a matrix/vector, 40
* **Row-wise tabulate**
  Column and row-wise tabulate, 48
* **Row-wise true-false**
  Row-wise true value, 245
* **Row-wise true**
  Row-wise true value, 245
* **Shapiro-Francia**
  Many Shapiro-Francia normality tests, 163
* **Significance testing**
  Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression, 247
* **Simple linear regressions**
  Many univariate simple linear regressions, 173
* **Skewness coefficient**
  Column-wise kurtosis and skewness coefficients, 52
* **Skewness**
  Hypothesis testing between two skewness or kurtosis coefficients, 116
  Skewness and kurtosis coefficients, 255
* **Sort 2 vectors**

Sort - Integer Sort - Sort a vector coresponding to another, 257
* **Sort function**
Sort and unique numbers, 259
* **Sorting**
Sorting of the columns-rows of a matrix, 260
* **Sort**
Sort - Integer Sort - Sort a vector coresponding to another, 257
* **Stable Sort**
Sort - Integer Sort - Sort a vector coresponding to another, 257
* **Stack**
Represantation of Stack, 241
* **Standardisation**
Standardisation, 266
* **Sub-matrix**
Sub-matrix, 267
* **Sum**
Operations between two matrices or matrix and vector, 221
* **Supervised classification**
k-NN algorithm using the arc cosinus distance, 127
* **Symmetric matrix**
Check whether a square matrix is symmetric, 28
* **Table Creation**
Table Creation - Frequency of each value, 268
* **Time series**
Estimation of an AR(1) model, 87
* **Tobit model**
MLE of the tobit model, 202
* **Topological sort**
Topological sort of a DAG, 271
* **Transpose**
Transpose of a matrix, 272
* **Two-way ANOVA**
Many two-way ANOVAs, 171
* **Unequality of the covariance matrices**
James multivariate version of the t-test, 123
* **Univariate normality test**
Many Shapiro-Francia normality tests, 163
* **Variance components**
Moment and maximum likelihood estimation of variance components, 203
* **Variance**
Some summary statistics of a vector for each level of a grouping variable, 256
Variance of a vector, 274
* **Weibull**
MLE of continuous univariate distributions defined on the positive line, 189
* **Wigner semicircle distribution**
MLE of continuous univariate distributions defined on the real line, 191
* **Zero range**
Search for variables with zero range in a matrix, 246
* **analysis of variance**
Logistic or Poisson regression with a single categorical predictor, 132
Many analysis of variance tests with a discrete variable, 139
Many F-tests with really huge matrices, 144
Many multi-sample tests, 150
Many non parametric multi-sample tests, 152
Multi-sample tests for vectors, 205
* **balanced design**
Column and row wise coefficients of variation, 36
Many random intercepts LMMs for balanced data with a single identical covariate., 157
Random intercepts linear mixed models, 235
* **beta prime**
MLE of continuous univariate distributions defined on the positive line, 189
* **binary data**
Forward selection with generalised

linear regression models, 101
* **binomial distribution**
MLE of count data (univariate discrete distributions), 192
* **bivariate angular Gaussian**
MLE of some circular distributions, 196
* **blocking ANOVA**
Many multi-sample tests, 150
Multi-sample tests for vectors, 205
* **categorical variables**
Many univariate simple linear regressions, 173
* **censored observations**
MLE of the tobit model, 202
* **central angular Gaussian distribution**
MLE of (hyper-)spherical distributions, 187
* **circular data**
MLE of some circular distributions, 196
* **column-wise false**
Column-wise true/false value, 57
* **column-wise maximum**
Column-wise minimum and maximum, 54
* **column-wise minimum-maximum**
Column-wise minimum and maximum, 54
* **column-wise true-false**
Column-wise true/false value, 57
* **combinatorics**
Binomial coefficient and its logarithm, 21
* **conditional MLE**
Estimation of an AR(1) model, 87
* **continuous distributions**
Column-wise MLE of some univariate distributions, 55
* **covariance matrix**
Pooled covariance matrix, 229
Spatial sign covariance matrix, 264
* **cross-validation**
Cross-Validation for the k-NN algorithm, 68
* **data check**
Search for variables with zero range in a matrix, 246
* **density values**
Density of the multivariate normal and t distributions, 73
* **dependent binary data**
Multi-sample tests for vectors, 205
* **derivatives**
Natural logarithm of the gamma function and its derivatives, 215
* **digamma function**
Natural logarithm of the gamma function and its derivatives, 215
* **directed graph**
Floyd-Warshall algorithm, 100
* **directional data**
Angular central Gaussian random values simulation, 12
MLE of (hyper-)spherical distributions, 187
* **discrete distributions**
Column-wise MLE of some univariate distributions, 55
* **dispersion parameter**
Many tests for the dispersion parameter in Poisson distribution, 169
Tests for the dispersion parameter in Poisson distribution, 270
* **distance**
Rfast-package, 7
* **energy distance**
Rfast-package, 7
* **equality of variances**
Many multi-sample tests, 150
Multi-sample tests for vectors, 205
* **excessive zeros**
MLE of count data (univariate discrete distributions), 192
* **fitted probabilities**
Fitted probabilities of the Terry-Bradley model, 98
* **folded normal**
MLE of continuous univariate distributions defined on the positive line, 189
* **fractional response**
Quasi binomial regression for proportions, 231
Significance testing for the

coefficients of Quasi binomial or the quasi Poisson regression, 247
* **gamma distribution**
MLE of continuous univariate distributions defined on the positive line, 189
* **generalised linear models**
Logistic and Poisson regression models, 130
Many univariate simple logistic and Poisson regressions, 175
Many univariate simple quasi poisson regressions, 176
* **geometric distribution**
Analysis of variance with a count variable, 11
Many analysis of variance tests with a discrete variable, 139
MLE of count data (univariate discrete distributions), 192
* **grouppings**
Some summary statistics of a vector for each level of a grouping variable, 256
* **half normal**
MLE of continuous univariate distributions defined on the positive line, 189
* **harmonic means**
Column and row-wise means of a matrix, 38
* **high dimensional data**
Eigenvalues and eigenvectors in high dimensional principal component analysis, 82
* **huge datasets**
Many F-tests with really huge matrices, 144
* **hypersecant distribution for proportions**
MLE of distributions defined in the (0, 1) interval, 194
* **hypothesis testing**
Column-wise uniformity Watson test for circular data, 58
Hypothesis testing between two skewness or kurtosis coefficients, 116
Uniformity test for circular data, 273
* **inflated beta distribution**
MLE of distributions defined in the (0, 1) interval, 194
* **interaction**
Many two-way ANOVAs, 171
* **is_integer Creation**
Check if values are integers and convert to integer, 24
* **iterator**
Iterator, 122
* **k-NN algorithm**
Cross-Validation for the k-NN algorithm, 68
k nearest neighbours algorithm (k-NN), 125
* **kurtosis coefficient**
Column-wise kurtosis and skewness coefficients, 52
* **kurtosis**
Hypothesis testing between two skewness or kurtosis coefficients, 116
Multivariate kurtosis, 208
Skewness and kurtosis coefficients, 255
* **large scale data**
Linear models for large scale data, 129
* **left censoring**
MLE of the tobit model, 202
* **list**
Hash object, 110
Hash object to a list object, 111
* **logarithm**
Natural logarithm of the beta function, 214
* **logistic normal distribution**
MLE of distributions defined in the (0, 1) interval, 194
* **matrix**
Column and row-wise Order - Sort Indices, 41
Column and row-wise products, 43
Column-wise differences, 51
Transpose of a matrix, 272
* **maximum frequency**

Minimum and maximum frequencies, 185
* **maximum likelihood estimation**
Column and row wise coefficients of variation, 36
Fitting a Dirichlet distribution via Newton-Rapshon, 99
Many random intercepts LMMs for balanced data with a single identical covariate., 157
MLE of (hyper-)spherical distributions, 187
MLE of distributions defined in the (0, 1) interval, 194
Moment and maximum likelihood estimation of variance components, 203
Random intercepts linear mixed models, 235
* **maximum**
Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices, 183
Minimum and maximum, 184
* **mean vector**
Exponential empirical likelihood for a one sample mean vector hypothesis testing, 90
* **medians**
Column and row-wise medians of a matrix or median of a vector., 39
* **minimum frequency**
Minimum and maximum frequencies, 185
* **minimum or maximum of negative**
Apply method to Positive and Negative number, 14
* **minimum or maximum of positive**
Apply method to Positive and Negative number, 14
* **minimum**
Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices, 183
Minimum and maximum, 184
* **moments estimation**
Moment and maximum likelihood estimation of variance components, 203
* **multinomial distribution**
Prediction with some naive Bayes classifiers, 230
* **multinomial regressions**
Many score based regressions, 161
* **multivariate Laplace distribution**
Multivariate Laplace random values simulation, 209
* **multivariate discrete data**
MLE for multivariate discrete data, 186
* **multivariate normal distribution**
Multivariate normal and t random values simulation, 210
* **multivariate t distribution**
Density of the multivariate normal and t distributions, 73
* **naive Bayes**
Prediction with some naive Bayes classifiers, 230
* **negative binomial**
MLE of count data (univariate discrete distributions), 192
* **negative numbers**
Apply method to Positive and Negative number, 14
* **non parametric statistics**
Many non parametric multi-sample tests, 152
* **non parametric test**
Empirical and exponential empirical likelihood tests for one sample, 83
Empirical and exponential empirical likelihood tests for two samples, 84
Exponential empirical likelihood hypothesis testing for two mean vectors, 92
* **normal distribution**
Prediction with some naive Bayes classifiers, 230
* **nth elements**
Column and row-wise nth smallest

value of a matrix/vector, 40
* **one sample**
Empirical and exponential empirical likelihood tests for one sample, 83
Many one sample tests, 156
* **operations**
Operations between two matrices or matrix and vector, 221
* **outliers**
High dimensional MCD based detection of outliers, 112
* **partial correlation**
BIC (using partial correlation) forward regression, 17
Correlation based forward regression, 62
* **percentages**
Hypothesis test for two means of percentages, 114
Many hypothesis tests for two means of percentages, 147
* **poisson regression**
Logistic and Poisson regression models, 130
* **positive definite**
Inverse of a symmetric positive definite matrix, 121
* **positive multivariate data**
MLE of the inverted Dirichlet distribution, 197
* **positive numbers**
Apply method to Positive and Negative number, 14
* **projected normal distribution**
MLE of (hyper-)spherical distributions, 187
* **projected normal**
Circular or angular regression(s), 31
* **proportion test**
Many one sample tests, 156
* **proportional odds**
MLE of the ordinal model without covariates, 201
* **proportions**
Forward selection with generalised linear regression models, 101
MLE of distributions defined in the (0, 1) interval, 194
* **random values simulation**
Angular central Gaussian random values simulation, 12
Multivariate Laplace random values simulation, 209
Multivariate normal and t random values simulation, 210
* **regression**
Many regression based tests for single sample repeated measures, 159
Multinomial regression, 207
Repeated measures anova, 238
* **robust statistics**
Pooled covariance matrix, 229
Spatial median for Euclidean data, 262
Spatial sign covariance matrix, 264
* **row means**
Column and row-wise means of a matrix, 38
* **row-wise maximum**
Row-wise minimum and maximum, 244
* **row-wise variances**
Column and row-wise variances and standard deviations, 49
* **score based tests**
Many score based regressions, 161
* **shortest paths**
Floyd-Warshall algorithm, 100
* **single categorical predictor**
Logistic or Poisson regression with a single categorical predictor, 132
* **spatial median**
Spatial median for Euclidean data, 262
* **spherical data**
MLE of (hyper-)spherical distributions, 187
* **summary statistics**
Many regression based tests for single sample repeated measures, 159
Repeated measures anova, 238
* **symmetric matrix**

Inverse of a symmetric positive definite matrix, 121
Vector allocation in a symmetric matrix, 275
∗ **t distribution**
MLE of continuous univariate distributions defined on the real line, 191
∗ **t-tests**
Many 2 sample tests, 137
Many hypothesis tests for two means of percentages, 147
Matrix with all pairs of t-tests, 180
Rfast-package, 7
∗ **t-test**
Hypothesis test for two means of percentages, 114
Many one sample tests, 156
∗ **total sum**
Energy distance between matrices, 86
∗ **trigamma function**
Natural logarithm of the gamma function and its derivatives, 215
∗ **two samples**
Empirical and exponential empirical likelihood tests for two samples, 84
∗ **uniformity tests**
Column-wise uniformity Watson test for circular data, 58
∗ **uniformity test**
Uniformity test for circular data, 273
∗ **unique numbers**
Sort and unique numbers, 259
∗ **univariate approach**
Many regression based tests for single sample repeated measures, 159
Repeated measures anova, 238
∗ **univariate regressions**
Rfast-package, 7
∗ **variable selection**
Forward selection with generalised linear regression models, 101
∗ **variance test**
Many one sample tests, 156
∗ **variances of many samples**
Column and row-wise variances and standard deviations, 49
∗ **variances**
Rfast-package, 7
∗ **von Mises distribution**
MLE of some circular distributions, 196
∗ **von Mises-Fisher distribution**
Hypothesis test for von Mises-Fisher distribution over Kent distribution, 115
MLE of (hyper-)spherical distributions, 187
Random values simulation from a von Mises distribution, 236
Simulation of random values from a von Mises-Fisher distribution, 252
∗ **wrapped Cauchy distribution**
MLE of some circular distributions, 196
∗ **zero inflated Poisson**
MLE of count data (univariate discrete distributions), 192
∗ **zero truncated Poisson**
MLE of count data (univariate discrete distributions), 192
.lm.fit, *129*
==.iterator *(*Iterator*)*, 122
[.Hash *(*Hash object*)*, 110
[.ufactor *(*Fast and general - untyped represantation of a factor variable*)*, 93
[<-.Hash *(*Hash object*)*, 110

acg.mle, *13*, *32*
acg.mle *(*MLE of (hyper-)spherical distributions*)*, 187
AddToNamespace, *27*, *238*, *261*
AddToNamespace *(*Insert/remove function names in/from the NAMESPACE file*)*, 118
All k possible combinations from n elements, 8
allbetas, *64*, *65*, *106*, *130*, *152*, *166*, *169*, *173*, *174*, *176–178*

allbetas (Many simple linear regressions coefficients), 166
alltests (Matrix with all pairs of t-tests), 180
Analysis of covariance, 9
Analysis of variance with a count variable, 11
ancova1 (Analysis of covariance), 9
ancovas, *10*, *171*
ancovas (Many ANCOVAs), 140
Angular central Gaussian random values simulation, 12
anova, *12*, *99*, *133*, *140*
ANOVA for two quasi Poisson regression models, 13
anova1, *10*, *221*
anova1 (Multi-sample tests for vectors), 205
anova_propreg, *233*
anova_propreg (Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression), 247
anova_qpois.reg, *14*
anova_qpois.reg (Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression), 247
anova_quasipois.reg (ANOVA for two quasi Poisson regression models), 13
anovas, *139*, *141*
anovas (Many multi-sample tests), 150
Apply method to Positive and Negative number, 14
Apply to each column a method under condition, 15
apply.condition (Apply to each column a method under condition), 15
ar1 (Estimation of an AR(1) model), 87
as.Rfast.function (Convert R function to the Rfast's coresponding), 61
as_integer, *25*, *269*
as_integer (Check if values are integers and convert to integer), 24
auc, *89*
auc (Many (and one) area under the curve values), 135

Backward selection regression, 16
bc (Estimation of the Box-Cox transformation), 88
bcdcor (Distance variance, covariance and correlation), 80
beta.mle, *100*, *191*, *201*, *214*, *215*
beta.mle (MLE of distributions defined in the (0, 1) interval), 194
betabinom.mle (MLE of count data (univariate discrete distributions)), 192
betageom.mle (MLE of count data (univariate discrete distributions)), 192
betaprime.mle (MLE of continuous univariate distributions defined on the positive line), 189
BIC (using partial correlation) forward regression, 17
BIC forward regression with generalised linear models, 18
bic.corfsreg, *19*
bic.corfsreg (BIC (using partial correlation) forward regression), 17
bic.fs.reg (BIC forward regression with generalised linear models), 18
Binary search algorithm, 20
binary_search, *96*, *244*
binary_search (Binary search algorithm), 20
bincomb (Permutation), 226
binom.mle (MLE of count data (univariate discrete distributions)), 192
Binomial coefficient and its logarithm, 21
block.anova (Multi-sample tests for vectors), 205
block.anovas, *153*
block.anovas (Many multi-sample tests), 150
boot.ttest2, *90*, *142*
boot.ttest2 (Bootstrap t-test for 2 independent samples), 22

Bootstrap t-test for 2 independent samples, 22
borel.mle *(*MLE of count data (univariate discrete distributions)*)*, 192
bs.reg *(*Backward selection regression*)*, 16
btmprobs *(*Fitted probabilities of the Terry-Bradley model*)*, 98

cat.goftests *(*Many one sample goodness of fit tests for categorical data*)*, 155
cauchy.mle *(*MLE of continuous univariate distributions defined on the real line*)*, 191
Check if any column or row is fill with values, 23
Check if values are integers and convert to integer, 24
Check Namespace and Rd files, 25
Check whether a square matrix is symmetric, 28
check_data *(*Search for variables with zero range in a matrix*)*, 246
checkAliases, *26*
checkAliases *(*Check Namespace and Rd files*)*, 25
checkExamples, *26*, *238*
checkExamples *(*Check Namespace and Rd files*)*, 25
checkNamespace, *26*
checkNamespace *(*Check Namespace and Rd files*)*, 25
checkRd, *238*
checkTF, *26, 27*
checkTF *(*Check Namespace and Rd files*)*, 25
checkUsage, *26, 27*
checkUsage *(*Check Namespace and Rd files*)*, 25
Chi-square and G-square tests of (unconditional) indepdence, 29
chi2Test *(*G-square and Chi-square test of conditional indepdence*)*, 102
chi2Test_univariate *(*Matrix with G-square tests of indepedence*)*, 181
chi2tests *(*Many G-square and Chi-square tests of indepedence*)*, 145
chisq.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
cholesky, *28*, *122*
cholesky *(*Cholesky decomposition of a square matrix*)*, 30
Cholesky decomposition of a square matrix, 30
Choose, *213*, *242*
Choose *(*Binomial coefficient and its logarithm*)*, 21
circlin.cor *(*Circular-linear correlation*)*, 33
Circular or angular regression(s), 31
Circular-linear correlation, 33
coeff *(*Coefficient matrices*)*, 34
Coefficient matrices, 34
col.coxpoisrat *(*Cox confidence interval for the ratio of two Poisson variables*)*, 67
col.yule, *277*
col.yule *(*Column-wise Yule's Y (coefficient of colligation)*)*, 59
colAll *(*Column and row-wise Any/All*)*, 37
colanovas *(*Many Welch's F-tests*)*, 177
colAny *(*Column and row-wise Any/All*)*, 37
colar1 *(*Estimation of an AR(1) model*)*, 87
colaucs *(*Many (and one) area under the curve values*)*, 135
colCountValues *(*Row - Wise matrix/vector count the frequency of a value*)*, 243
colCumMaxs *(*Colum-wise cumulative operations (sum, prod, min, max)*)*, 35
colCumMins *(*Colum-wise cumulative operations (sum, prod, min, max)*)*, 35
colCumProds *(*Colum-wise cumulative operations (sum, prod, min, max)*)*, 35
colCumSums *(*Colum-wise cumulative operations (sum, prod, min, max)*)*, 35

colcvs (Column and row wise coefficients of variation), 36
coldiffs, *42*, *43*
coldiffs (Column-wise differences), 51
colexp2.mle (Column-wise MLE of some univariate distributions), 55
colexpmle (Column-wise MLE of some univariate distributions), 55
colFalse, *76*, *134*, *246*
colFalse (Column-wise true/false value), 57
colgammamle (Column-wise MLE of some univariate distributions), 55
colgeom.mle (MLE for multivariate discrete data), 186
colhameans (Column and row-wise means of a matrix), 38
colinvgauss.mle (Column-wise MLE of some univariate distributions), 55
colkurtosis (Column-wise kurtosis and skewness coefficients), 52
collaplace.mle (Column-wise MLE of some univariate distributions), 55
collindley.mle (Column-wise MLE of some univariate distributions), 55
colMads, *38*, *222*, *267*
colMads (Column and rows-wise mean absolute deviations), 50
colmaxboltz.mle (Column-wise MLE of some univariate distributions), 55
colMaxs, *9*, *44*, *184*, *245*, *260*, *272*
colMaxs (Column-wise minimum and maximum), 54
colMeans, *37*, *40*, *41*, *47*, *51*
colmeans, *25*, *47*, *48*, *50–52*, *73*, *113*, *117*, *119*, *123*, *135*, *208*, *212*, *216*, *217*, *220*, *222*, *241*, *255*, *257*, *267*, *269*, *275*
colmeans (Column and row-wise means of a matrix), 38
colMedians, *16*, *23*, *35*, *37*, *38*, *41–44*, *47*, *50–52*, *55*, *57*, *61*, *80*, *108*, *113*, *117*, *184*, *185*, *208*, *217*, *240*, *245*, *255*, *257*, *263*
colMedians (Column and row-wise medians of a matrix or median of a vector.), 39
colMins, *9*, *38*, *44*, *184*, *245*, *260*, *272*
colMins (Column-wise minimum and maximum), 54
colMinsMaxs (Column-wise minimum and maximum), 54
colnormal.mle (Column-wise MLE of some univariate distributions), 55
colnormlog.mle (Column-wise MLE of some univariate distributions), 55
colnth, *15*, *258*
colnth (Column and row-wise nth smallest value of a matrix/vector), 40
colOrder (Column and row-wise Order - Sort Indices), 41
colpareto.mle (Column-wise MLE of some univariate distributions), 55
colPmax (Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices), 183
colPmin (Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices), 183
colpois.tests (Many tests for the dispersion parameter in Poisson distribution), 169
colpoisdisp.tests (Many tests for the dispersion parameter in Poisson distribution), 169
colpoisson.anovas (Many ANOVAS for count data with Poisson or quasi Poisson models), 141
colpoisson.mle, *231*
colpoisson.mle (MLE for multivariate discrete data), 186
colprods, *42*
colprods (Column and row-wise products), 43
colquasipoisson.anovas (Many ANOVAS for count data with Poisson or quasi Poisson models), 141
colrange, *9*, *23*, *50*, *55*, *57*, *108*, *185*, *194*, *240*, *247*, *260*, *272*
colrange (Column and row-wise range of values of a matrix), 44

colRanks (Column and row-wise ranks), 45
colrayleigh.mle (Column-wise MLE of some univariate distributions), 55
colrint.regbx, *149*
colrint.regbx (Many random intercepts LMMs for balanced data with a single identical covariate.), 157
colrow.value (Check if any column or row is fill with values), 23
colShuffle, *48*, *73*, *119*, *123*, *241*, *269*, *275*
colShuffle (Column and row-wise Shuffle), 46
colskewness, *117*, *208*, *220*, *255*
colskewness (Column-wise kurtosis and skewness coefficients), 52
colSort, *23*, *44*, *55*, *57*, *76*, *101*, *108*, *185*, *240*, *245*, *259*
colSort (Sorting of the columns-rows of a matrix), 260
colsums, *16*, *35*, *36*, *38*, *42*, *43*, *61*, *167*, *180*, *268*
colsums (Column and row-wise sums of a matrix), 47
colTabulate, *54*
colTabulate (Column and row-wise tabulate), 48
colTrue, *76*, *134*, *246*
colTrue (Column-wise true/false value), 57
colTrueFalse (Column-wise true/false value), 57
Colum-wise cumulative operations (sum, prod, min, max), 35
Column and row wise coefficients of variation, 36
Column and row-wise Any/All, 37
Column and row-wise means of a matrix, 38
Column and row-wise medians of a matrix or median of a vector., 39
Column and row-wise nth smallest value of a matrix/vector, 40
Column and row-wise Order - Sort Indices, 41
Column and row-wise products, 43
Column and row-wise range of values of a matrix, 44
Column and row-wise ranks, 45
Column and row-wise Shuffle, 46
Column and row-wise sums of a matrix, 47
Column and row-wise tabulate, 48
Column and row-wise variances and standard deviations, 49
Column and rows-wise mean absolute deviations, 50
Column-wise differences, 51
Column-wise kurtosis and skewness coefficients, 52
Column-wise matching coefficients, 53
Column-wise minimum and maximum, 54
Column-wise MLE of some univariate distributions, 55
Column-wise true/false value, 57
Column-wise uniformity Watson test for circular data, 58
Column-wise Yule's Y (coefficient of colligation), 59
columns (Get specific columns/rows fo a matrix), 108
colvarcomps.mle, *158*, *204*
colvarcomps.mle (Many moment and maximum likelihood estimations of variance components), 148
colvarcomps.mom, *236*
colvarcomps.mom (Many moment and maximum likelihood estimations of variance components), 148
colVars, *16*, *23*, *25*, *35*, *36*, *40*, *44*, *47*, *48*, *51*, *52*, *55*, *57*, *61*, *67*, *73*, *94*, *108*, *113*, *117*, *119*, *123*, *137*, *167*, *208*, *212*, *231*, *240*, *241*, *245*, *247*, *255*, *257*, *267–269*, *274*, *275*
colVars (Column and row-wise variances and standard deviations), 49
colvm.mle (Column-wise MLE of some univariate distributions), 55
colwatsons (Column-wise uniformity Watson test for circular data), 58
colweibull.mle (Column-wise MLE of some univariate distributions), 55
comb_n, *21*, *227*

comb_n (All k possible combinations from n elements), 8
combn, *227*
Convert a dataframe to matrix, 60
Convert R function to the Rfast's coresponding, 61
cor, *66*, *67*
cor.fbed, *224*
cor.fbed (FBED variable selection method using the correlation), 94
cor.fsreg, *17–19*, *95*, *102*, *126*, *130*, *224*
cor.fsreg (Correlation based forward regression), 62
cora, *28*, *254*
cora (Covariance and correlation matrix), 66
corpairs, *220*
corpairs (Correlation between pairs of variables), 63
Correlation based forward regression, 62
Correlation between pairs of variables, 63
Correlations, 65
correls, *46*, *64*, *68*, *89*, *95*, *104*, *130*, *146*, *152*, *167*, *173*, *174*, *176*, *178*, *182*, *224*, *229*, *254*, *268*
correls (Correlations), 65
count_value (Row - Wise matrix/vector count the frequency of a value), 243
cov, *67*
cova, *28*, *122*, *274*
cova (Covariance and correlation matrix), 66
Covariance and correlation matrix, 66
Cox confidence interval for the ratio of two Poisson variables, 67
cox.poisrat (Cox confidence interval for the ratio of two Poisson variables), 67
cqtest (Multi-sample tests for vectors), 205
cqtests (Many non parametric multi-sample tests), 152
Cross-Validation for the k-NN algorithm, 68
Cross-Validation for the k-NN algorithm using the arc cosinus distance, 70
Crossprod, *66*, *82*
Crossprod (Matrix multiplication), 179
ct.mle (MLE of continuous univariate distributions defined on the real line), 191

data.frame.to_matrix, *253*
data.frame.to_matrix (Convert a dataframe to matrix), 60
dcor (Distance variance, covariance and correlation), 80
dcor.ttest, *81*, *226*
dcor.ttest (Hypothesis test for the distance correlation), 113
dcov, *87*, *114*, *226*
dcov (Distance variance, covariance and correlation), 80
Deep copy, 72
Density of the multivariate normal and t distributions, 73
Design Matrix, 74
design_matrix (Design Matrix), 74
Diag.fill, *222*
Diag.fill (Diagonal Matrix), 75
Diag.matrix (Diagonal Matrix), 75
Diagonal Matrix, 75
Digamma (Natural logarithm of the gamma function and its derivatives), 215
diri.nr2, *195*, *198*, *201*, *214*, *215*
diri.nr2 (Fitting a Dirichlet distribution via Newton-Rapshon), 99
dirimultinom.mle (MLE for multivariate discrete data), 186
dirknn, *72*, *126*
dirknn (k-NN algorithm using the arc cosinus distance), 127
dirknn.cv, *70*, *128*
dirknn.cv (Cross-Validation for the k-NN algorithm using the arc cosinus distance), 70
Dist, *34*, *51*, *70*, *78*, *87*, *216*, *222*
Dist (Distance matrix - Sum of all pairwise distances in a distance matrix), 78

dista, *34*, *51*, *70*, *80*, *87*, *135*, *216*, *222*
dista *(*Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix.*)*, 76
Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix., 76
Distance matrix - Sum of all pairwise distances in a distance matrix, 78
Distance variance, covariance and correlation, 80
dmvnorm, *199*, *200*
dmvnorm *(*Density of the multivariate normal and t distributions*)*, 73
dmvt *(*Density of the multivariate normal and t distributions*)*, 73
dvar *(*Distance variance, covariance and correlation*)*, 80

eachcol.apply *(*Operations between two matrices or matrix and vector*)*, 221
eachrow *(*Operations between two matrices or matrix and vector*)*, 221
edist, *81*, *114*
edist *(*Energy distance between matrices*)*, 86
eel.test1 *(*Empirical and exponential empirical likelihood tests for one sample*)*, 83
eel.test2 *(*Empirical and exponential empirical likelihood tests for two samples*)*, 84
eigen.sym *(*Limited number of eigenvalues and eigenvectors of a symmetric matrix*)*, 128
Eigenvalues and eigenvectors in high dimensional principal component analysis, 82
el.test1 *(*Empirical and exponential empirical likelihood tests for one sample*)*, 83
el.test2 *(*Empirical and exponential empirical likelihood tests for two samples*)*, 84
Elem *(*Iterator*)*, 122
Elem<- *(*Iterator*)*, 122
Empirical and exponential empirical likelihood tests for one sample, 83
Empirical and exponential empirical likelihood tests for two samples, 84
Energy distance between matrices, 86
env.copy *(*Deep copy*)*, 72
Estimation of an AR(1) model, 87
Estimation of the Box-Cox transformation, 88
Exact t-test for 2 independent samples, 89
exact.ttest2, *22*
exact.ttest2 *(*Exact t-test for 2 independent samples*)*, 89
exp2.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
expmle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
Exponential empirical likelihood for a one sample mean vector hypothesis testing, 90
Exponential empirical likelihood hypothesis testing for two mean vectors, 92
expregs *(*Many exponential regressions*)*, 142

factor, *94*
Fast and general - untyped represantation of a factor variable, 93
FBED variable selection method using the correlation, 94
Find element, 96
Find the given value in a hash table, 97
fish.kent *(*Hypothesis test for von Mises-Fisher distribution over Kent distribution*)*, 115
Fitted probabilities of the Terry-Bradley model, 98
Fitting a Dirichlet distribution via Newton-Rapshon, 99

floyd, *272*
floyd *(*Floyd-Warshall algorithm*)*, 100
Floyd-Warshall algorithm, 100
foldnorm.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
Forward selection with generalised linear regression models, 101
freq.max *(*Minimum and maximum frequencies*)*, 185
freq.min *(*Minimum and maximum frequencies*)*, 185
fs.reg, *17*, *19*, *95*, *126*, *224*
fs.reg *(*Forward selection with generalised linear regression models*)*, 101
ftest, *22*, *84*, *90*, *115*, *142*, *147*
ftest *(*Multi-sample tests for vectors*)*, 205
ftests, *10*, *85*, *136, 137*, *139*, *141*, *144*, *153*, *155*, *157*, *164*, *171*, *178*, *181*, *206*
ftests *(*Many multi-sample tests*)*, 150

G-square and Chi-square test of conditional indepdence, 102
g2Test, *11, 12*, *29, 30*, *146*, *182*, *219*, *253, 254*
g2Test *(*G-square and Chi-square test of conditional indepdence*)*, 102
g2Test_perm, *146*, *182*
g2Test_perm *(*G-square and Chi-square test of conditional indepdence*)*, 102
g2Test_univariate, *30*, *103, 104*, *154*, *181*, *254*
g2Test_univariate *(*Matrix with G-square tests of indepedence*)*, 181
g2Test_univariate_perm, *30*, *103, 104*
g2Test_univariate_perm *(*Matrix with G-square tests of indepedence*)*, 181
g2tests, *99*, *140*
g2tests *(*Many G-square and Chi-square tests of indepedence*)*, 145
g2tests_perm *(*Many G-square and Chi-square tests of indepedence*)*, 145
Gamma regression with a log-link, 104
gammacon *(*Gamma regression with a log-link*)*, 104
gammamle, *56*, *192*, *203*
gammamle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
gammanb *(*Naive Bayes classifiers*)*, 211
gammanb.pred *(*Prediction with some naive Bayes classifiers*)*, 230
gammareg *(*Gamma regression with a log-link*)*, 104
gammaregs, *105*
gammaregs *(*Many simple regressions for positive valued data*)*, 168
Gaussian regression with a log-link, 105
gaussian.nb, *199, 200*, *231*
gaussian.nb *(*Naive Bayes classifiers*)*, 211
gaussiannb.pred, *212*
gaussiannb.pred *(*Prediction with some naive Bayes classifiers*)*, 230
gchi2Test *(*Chi-square and G-square tests of (unconditional) indepdence*)*, 29
Generates random values from a normal and puts them in a matrix, 107
geom.anova *(*Analysis of variance with a count variable*)*, 11
geom.anovas *(*Many analysis of variance tests with a discrete variable*)*, 139
geom.mle *(*MLE of count data (univariate discrete distributions)*)*, 192
geom.nb *(*Naive Bayes classifiers*)*, 211
geom.regs *(*Many simple geometric regressions*)*, 164
geomnb.pred *(*Prediction with some naive Bayes classifiers*)*, 230
Get specific columns/rows fo a matrix, 108
gini *(*One and many Gini coefficients*)*, 219
ginis *(*One and many Gini coefficients*)*, 219
glm_logistic, *102*, *207*
glm_logistic *(*Logistic and Poisson regression models*)*, 130

glm_poisson, *102*
glm_poisson *(*Logistic and Poisson regression models*)*, 130
group *(*Some summary statistics of a vector for each level of a grouping variable*)*, 256
groupcorrels *(*Correlations*)*, 65
gumbel.mle *(*MLE of continuous univariate distributions defined on the real line*)*, 191

halfnorm.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
Hash *(*Hash object*)*, 110
Hash - Pair function, 109
Hash object, 110
Hash object to a list object, 111
hash.find, *109*, *111*, *112*
hash.find *(*Find the given value in a hash table*)*, 97
hash.list, *97*, *111*, *112*
hash.list *(*Hash - Pair function*)*, 109
hash2list *(*Hash object to a list object*)*, 111
hd.eigen, *129*
hd.eigen *(*Eigenvalues and eigenvectors in high dimensional principal component analysis*)*, 82
High dimensional MCD based detection of outliers, 112
hsecant01.mle *(*MLE of distributions defined in the (0, 1) interval*)*, 194
Hypothesis test for the distance correlation, 113
Hypothesis test for two means of percentages, 114
Hypothesis test for von Mises-Fisher distribution over Kent distribution, 115
Hypothesis testing between two skewness or kurtosis coefficients, 116

iag.mle, *32*, *74*, *116*, *252*
iag.mle *(*MLE of (hyper-)spherical distributions*)*, 187
ibeta.mle *(*MLE of distributions defined in the (0, 1) interval*)*, 194
Index of the columns of a data.frame which are a specific type, 117
Insert/remove function names in/from the NAMESPACE file, 118
invdir.mle *(*MLE of the inverted Dirichlet distribution*)*, 197
Inverse Gaussian regression with a log-link, 120
Inverse of a symmetric positive definite matrix, 121
invgauss.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
invgauss.reg, *105*
invgauss.reg *(*Inverse Gaussian regression with a log-link*)*, 120
invgauss.regs, *121*
invgauss.regs *(*Many simple regressions for positive valued data*)*, 168
is.symmetric, *31*, *60*
is.symmetric *(*Check whether a square matrix is symmetric*)*, 28
is_element, *20*
is_element *(*Find element*)*, 96
is_integer, *269*
is_integer *(*Check if values are integers and convert to integer*)*, 24
Iterator, 122
iterator *(*Iterator*)*, 122

james, *91*, *93*
james *(*James multivariate version of the t-test*)*, 123
James multivariate version of the t-test, 123

k nearest neighbours algorithm (k-NN), 125
k-NN algorithm using the arc cosinus distance, 127
knn, *70*, *72*, *128*
knn *(*k nearest neighbours algorithm (k-NN)*)*, 125
knn.cv, *72*, *126*

knn.cv (Cross-Validation for the k-NN algorithm), 68
kruskaltest (Multi-sample tests for vectors), 205
kruskaltests (Many non parametric multi-sample tests), 152
kuiper (Uniformity test for circular data), 273
kurt (Skewness and kurtosis coefficients), 255
kurt.test2 (Hypothesis testing between two skewness or kurtosis coefficients), 116

laplace.mle (MLE of continuous univariate distributions defined on the real line), 191
Lbeta, *21*, *213*
Lbeta (Natural logarithm of the beta function), 214
Lchoose, *213*, *242*
Lchoose (Binomial coefficient and its logarithm), 21
length.Hash (Hash object), 110
Lgamma, *21*, *214*
Lgamma (Natural logarithm of the gamma function and its derivatives), 215
Limited number of eigenvalues and eigenvectors of a symmetric matrix, 128
lindley.mle (MLE of continuous univariate distributions defined on the positive line), 189
Linear models for large scale data, 129
list.ftests (Many F-tests with really huge matrices), 144
lm, *129*
lm.fit, *129*
lmfit, *264*
lmfit (Linear models for large scale data), 129
Log, *242*
Log (Natural Logarithm each element of a matrix), 213
logcauchy.mle (MLE of continuous univariate distributions defined on the positive line), 189
Logistic and Poisson regression models, 130
Logistic or Poisson regression with a single categorical predictor, 132
logistic.cat1, *12*
logistic.cat1 (Logistic or Poisson regression with a single categorical predictor), 132
logistic.mle (MLE of continuous univariate distributions defined on the real line), 191
logistic_only, *18*, *19*, *63*, *102*, *107*, *126*, *131*, *133*, *143*, *162*, *166*, *173*, *177*, *207*, *233*, *248*, *277*
logistic_only (Many univariate simple logistic and Poisson regressions), 175
logitnorm.mle (MLE of distributions defined in the (0, 1) interval), 194
loglogistic.mle (MLE of continuous univariate distributions defined on the positive line), 189
lognorm.mle (MLE of continuous univariate distributions defined on the positive line), 189
logseries.mle (MLE of count data (univariate discrete distributions)), 192
lomax.mle (MLE of continuous univariate distributions defined on the positive line), 189
Lower and Upper triangular of a matrix, 133
lower_tri (Lower and Upper triangular of a matrix), 133

Mad (Column and rows-wise mean absolute deviations), 50
mahala, *78*
mahala (Mahalanobis distance), 134
Mahalanobis distance, 134
Many (and one) area under the curve values, 135

Many 2 sample proportions tests, 136
Many 2 sample tests, 137
Many analysis of variance tests with a discrete variable, 139
Many ANCOVAs, 140
Many ANOVAS for count data with Poisson or quasi Poisson models, 141
Many exponential regressions, 142
Many F-tests with really huge matrices, 144
Many G-square and Chi-square tests of indepedence, 145
Many hypothesis tests for two means of percentages, 147
Many moment and maximum likelihood estimations of variance components, 148
Many multi-sample tests, 150
Many multivariate simple linear regressions coefficients, 151
Many non parametric multi-sample tests, 152
Many odds ratio tests, 154
Many one sample goodness of fit tests for categorical data, 155
Many one sample tests, 156
Many random intercepts LMMs for balanced data with a single identical covariate., 157
Many regression based tests for single sample repeated measures, 159
Many score based regressions, 161
Many Shapiro-Francia normality tests, 163
Many simple geometric regressions, 164
Many simple linear mixed model regressions, 165
Many simple linear regressions coefficients, 166
Many simple multinomial regressions, 167
Many simple regressions for positive valued data, 168
Many tests for the dispersion parameter in Poisson distribution, 169
Many two-way ANOVAs, 171
Many univariate generalised linear models, 172
Many univariate simple linear regressions, 173
Many univariate simple logistic and Poisson regressions, 175
Many univariate simple quasi poisson regressions, 176
Many Welch's F-tests, 177
mat.mat *(Number of equal columns between two matrices)*, 217
mat.mult, *225*
mat.mult *(Matrix multiplication)*, 179
Match, *60*, *118*, 178, *217*, *268*
match, *179*
match.coefs *(Column-wise matching coefficients)*, 53
Matrix multiplication, 179
Matrix with all pairs of t-tests, 180
Matrix with G-square tests of indepedence, 181
matrnorm, *251*
matrnorm *(Generates random values from a normal and puts them in a matrix)*, 107
maxboltz.mle *(MLE of continuous univariate distributions defined on the positive line)*, 189
mcnemar *(Multi-sample tests for vectors)*, 205
mcnemars *(Many 2 sample tests)*, 137
med *(Column and row-wise medians of a matrix or median of a vector.)*, 39
Median, *37*, *40*, *41*, *47*, *244*
Median *(Column and row-wise medians of a matrix or median of a vector.)*, 39
mediandir *(Spherical and hyperspherical median)*, 265
min_max *(Minimum and maximum)*, 184
Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices, 183
Minimum and maximum, 184
Minimum and maximum frequencies, 185

MLE for multivariate discrete data, 186
MLE of (hyper-)spherical distributions, 187
MLE of continuous univariate distributions defined on the positive line, 189
MLE of continuous univariate distributions defined on the real line, 191
MLE of count data (univariate discrete distributions), 192
MLE of distributions defined in the (0, 1) interval, 194
MLE of some circular distributions, 196
MLE of the inverted Dirichlet distribution, 197
MLE of the multivariate (log-) normal distribution, 198
MLE of the multivariate t distribution, 200
MLE of the ordinal model without covariates, 201
MLE of the tobit model, 202
model.matrix, *75*
Moment and maximum likelihood estimation of variance components, 203
Multi-sample tests for vectors, 205
multinom.mle, *198*, *199*
multinom.mle *(*MLE for multivariate discrete data*)*, 186
multinom.nb *(*Naive Bayes classifiers*)*, 211
multinom.reg *(*Multinomial regression*)*, 207
multinom.regs *(*Many simple multinomial regressions*)*, 167
Multinomial regression, 207
multinomnb.pred *(*Prediction with some naive Bayes classifiers*)*, 230
Multivariate kurtosis, 208
Multivariate Laplace random values simulation, 209
Multivariate normal and t random values simulation, 210
multivmf.mle *(*MLE of (hyper-)spherical distributions*)*, 187
mv.eeltest1, *93*
mv.eeltest1 *(*Exponential empirical likelihood for a one sample mean vector hypothesis testing*)*, 90
mv.eeltest2, *91*, *124*
mv.eeltest2 *(*Exponential empirical likelihood hypothesis testing for two mean vectors*)*, 92
mvbetas, *64*, *130*, *167*, *174*, *268*
mvbetas *(*Many multivariate simple linear regressions coefficients*)*, 151
mvkurtosis *(*Multivariate kurtosis*)*, 208
mvlnorm.mle *(*MLE of the multivariate (log-) normal distribution*)*, 198
mvnorm.mle, *74*, *200*
mvnorm.mle *(*MLE of the multivariate (log-) normal distribution*)*, 198
mvt.mle *(*MLE of the multivariate t distribution*)*, 200

Naive Bayes classifiers, 211
Natural Logarithm each element of a matrix, 213
Natural logarithm of the beta function, 214
Natural logarithm of the gamma function and its derivatives, 215
negative *(*Apply method to Positive and Negative number*)*, 14
negbin.mle, *170*, *187*, *270*
negbin.mle *(*MLE of count data (univariate discrete distributions)*)*, 192
Norm *(*Norm of a matrix*)*, 216
Norm of a matrix, 216
normal.mle, *56*, *191*, *203*
normal.mle *(*MLE of continuous univariate distributions defined on the real line*)*, 191
normlog.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
normlog.reg, *105*, *121*, *169*

normlog.reg (Gaussian regression with a log-link), 105
normlog.regs, *106*
normlog.regs (Many simple regressions for positive valued data), 168
nth, *9*, *15*, *23*, *44*, *55*, *57*, *76*, *108*, *118*, *134*, *185*, *240*, *244–246*, *258*, *260*, *272*
nth (Column and row-wise nth smallest value of a matrix/vector), 40
Number of equal columns between two matrices, 217

odds, *54*, *59*, *219*
odds (Many odds ratio tests), 154
Odds ratio and relative risk, 218
odds.ratio, *154*, *277*
odds.ratio (Odds ratio and relative risk), 218
omp (Orthogonal matching pursuit variable selection), 222
ompr, *95*
ompr (Orthogonal matching pursuit variable selection), 222
One and many Gini coefficients, 219
One sample t-test for a vector, 220
Operations between two matrices or matrix and vector, 221
Order, *244*
Order (Column and row-wise Order - Sort Indices), 41
ordinal.mle (MLE of the ordinal model without covariates), 201
Orthogonal matching pursuit variable selection, 222
Outer (Outer function), 224
Outer function, 224

pareto.mle (MLE of continuous univariate distributions defined on the positive line), 189
Partial distance correlation, 225
pc.skel, *228*, *272*
pc.skel (Skeleton of the PC algorithm), 253
pdcor, *81*
pdcor (Partial distance correlation), 225
percent.ttest (Hypothesis test for two means of percentages), 114
percent.ttests (Many hypothesis tests for two means of percentages), 147
permcor (Permutation based p-value for the Pearson correlation coefficient), 227
Permutation, 226
permutation, *60*
permutation (Permutation), 226
Permutation based p-value for the Pearson correlation coefficient, 227
Pmax (Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices), 183
Pmin (Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices), 183
Pmin_Pmax (Minima and maxima of two vectors/matrices and Column-row wise minima and maxima of two matrices), 183
pois.test (Tests for the dispersion parameter in Poisson distribution), 270
poisdisp.test (Tests for the dispersion parameter in Poisson distribution), 270
poisson.anova, *99*, *133*, *140*, *142*, *170*, *270*
poisson.anova (Analysis of variance with a count variable), 11
poisson.anovas, *12*, *133*, *170*, *270*
poisson.anovas (Many analysis of variance tests with a discrete variable), 139
poisson.cat1 (Logistic or Poisson regression with a single categorical predictor), 132
poisson.mle, *12*, *56*, *99*, *140*, *170*, *187*, *270*
poisson.mle (MLE of count data (univariate discrete distributions)), 192
poisson.nb, *187*
poisson.nb (Naive Bayes classifiers),

211
poisson_only, *12*, *18*, *19*, *63*, *99*, *102*, *131*, *133*, *140*, *143*, *162*, *165*, *168*, *170*, *173*, *177*, *194*, *234*, *270*, *277*
poisson_only *(*Many univariate simple logistic and Poisson regressions*)*, 175
poissonnb.pred *(*Prediction with some naive Bayes classifiers*)*, 230
poly.cor *(*Polyserial correlation*)*, 228
Polyserial correlation, 228
Pooled covariance matrix, 229
pooled.cov *(*Pooled covariance matrix*)*, 229
positive *(*Apply method to Positive and Negative number*)*, 14
Prediction with some naive Bayes classifiers, 230
print.Hash *(*Hash object*)*, 110
print.iterator *(*Iterator*)*, 122
print.ufactor *(*Fast and general - untyped represantation of a factor variable*)*, 93
prop.reg, *115*, *147*, *234*, *248*
prop.reg *(*Quasi binomial regression for proportions*)*, 231
prop.regs, *106*, *165*, *168*, *169*, *176*
prop.regs *(*Quasi binomial regression for proportions*)*, 231
proptest *(*Many one sample tests*)*, 156
proptests *(*Many 2 sample proportions tests*)*, 136

qpois.reg, *14*, *248*
qpois.reg *(*Quasi Poisson regression for count data*)*, 233
qpois.regs *(*Quasi Poisson regression for count data*)*, 233
Quasi binomial regression for proportions, 231
Quasi Poisson regression for count data, 233
quasi.poisson_only, *176*
quasi.poisson_only *(*Many univariate simple quasi poisson regressions*)*, 176
quasipoisson.anova, *14*
quasipoisson.anova *(*Analysis of variance with a count variable*)*, 11
quasipoisson.anovas *(*Many analysis of variance tests with a discrete variable*)*, 139

racg, *189*, *209*, *211*
racg *(*Angular central Gaussian random values simulation*)*, 12
Random intercepts linear mixed models, 235
Random values simulation from a von Mises distribution, 236
Rank, *46*
Rank *(*Column and row-wise ranks*)*, 45
rayleigh.mle *(*MLE of continuous univariate distributions defined on the positive line*)*, 189
rbing, *250*
rbing *(*Simulation of random values from a Bingham distribution*)*, 248
rbingham *(*Simulation of random values from a Bingham distribution with any symmetric matrix*)*, 249
read.directory *(*Reading the files of a directory*)*, 237
read.examples, *27*
read.examples *(*Reading the files of a directory*)*, 237
Reading the files of a directory, 237
regression, *18*, *19*, *63*, *130*, *131*, *143*, *162*, *173*, *176–178*, *277*
regression *(*Many univariate simple linear regressions*)*, 173
rel.risk *(*Odds ratio and relative risk*)*, 218
RemoveFromNamespace *(*Insert/remove function names in/from the NAMESPACE file*)*, 118
rep_col *(*Replicate columns/rows*)*, 240
rep_row *(*Replicate columns/rows*)*, 240
Repeated measures anova, 238
Replicate columns/rows, 240
Represantation of Stack, 241
Rfast-package, 7
rint.mle *(*Moment and maximum likelihood estimation of variance components*)*, 203
rint.reg, *158*, *160*, *166*, *204*, *239*

rint.reg (Random intercepts linear mixed models), 235
rint.regbx, *158*, *160*, *204*
rint.regbx (Random intercepts linear mixed models), 235
rint.regs (Many simple linear mixed model regressions), 165
rm.anova (Repeated measures anova), 238
rm.anovas, *88*, *239*
rm.anovas (Many regression based tests for single sample repeated measures), 159
rm.lines, *88*, *158*, *236*
rm.lines (Many regression based tests for single sample repeated measures), 159
rmdp, *83*
rmdp (High dimensional MCD based detection of outliers), 112
rmvlaplace, *13*, *211*
rmvlaplace (Multivariate Laplace random values simulation), 209
rmvnorm, *13*, *74*, *107*, *209*, *251*
rmvnorm (Multivariate normal and t random values simulation), 210
rmvt, *13*, *74*, *209*, *211*
rmvt (Multivariate normal and t random values simulation), 210
Rnorm, *107*
Rnorm (Simulation of random values from a normal distribution), 251
Round, *15*, *258*
Round (Round each element of a matrix/vector), 242
Round each element of a matrix/vector, 242
Row - Wise matrix/vector count the frequency of a value, 243
Row-wise minimum and maximum, 244
Row-wise true value, 245
rowAll (Column and row-wise Any/All), 37
rowAny (Column and row-wise Any/All), 37
rowCountValues (Row - Wise matrix/vector count the frequency of a value), 243
rowcvs (Column and row wise coefficients of variation), 36
rowFalse, *23*, *57*, *108*, *240*
rowFalse (Row-wise true value), 245
rowhameans (Column and row-wise means of a matrix), 38
rowMads, *222*
rowMads (Column and rows-wise mean absolute deviations), 50
rowMaxs, *44*, *55*, *185*
rowMaxs (Row-wise minimum and maximum), 244
rowmeans (Column and row-wise means of a matrix), 38
rowMedians, *51*, *76*, *134*, *246*
rowMedians (Column and row-wise medians of a matrix or median of a vector.), 39
rowMins, *23*, *44*, *55*, *57*, *76*, *108*, *134*, *185*, *240*, *246*
rowMins (Row-wise minimum and maximum), 244
rowMinsMaxs (Row-wise minimum and maximum), 244
rownth, *15*, *258*
rownth (Column and row-wise nth smallest value of a matrix/vector), 40
rowOrder (Column and row-wise Order - Sort Indices), 41
rowprods (Column and row-wise products), 43
rowrange, *76*, *134*, *245*, *246*
rowrange (Column and row-wise range of values of a matrix), 44
rowRanks (Column and row-wise ranks), 45
rows (Get specific columns/rows fo a matrix), 108
rowShuffle (Column and row-wise Shuffle), 46
rowSort, *23*, *44*, *55*, *57*, *76*, *101*, *108*, *185*, *240*, *245*, *259*
rowSort (Sorting of the columns-rows of a matrix), 260
rowsums, *38*
rowsums (Column and row-wise sums of a matrix), 47
rowTabulate (Column and row-wise tabulate), 48
rowTrue, *23*, *57*, *108*, *240*
rowTrue (Row-wise true value), 245

rowTrueFalse (Row-wise true value), 245
rowVars, *76*, *134*, *246*
rowVars (Column and row-wise variances and standard deviations), 49
rvmf, *107*, *189*, *197*, *237*, *249–251*
rvmf (Simulation of random values from a von Mises-Fisher distribution), 252
rvonmises, *58*, *107*, *197*, *251*, *252*, *273*
rvonmises (Random values simulation from a von Mises distribution), 236

score.betaregs (Many score based regressions), 161
score.expregs (Many score based regressions), 161
score.gammaregs (Many score based regressions), 161
score.geomregs, *165*, *168*
score.geomregs (Many score based regressions), 161
score.glms, *18*, *19*, *63*, *106*, *121*, *143*, *166*, *169*, *176*, *233*, *234*, *248*
score.glms (Many score based regressions), 161
score.invgaussregs (Many score based regressions), 161
score.multinomregs, *207*
score.multinomregs (Many score based regressions), 161
score.negbinregs (Many score based regressions), 161
score.weibregs (Many score based regressions), 161
score.ztpregs (Many score based regressions), 161
Search for variables with zero range in a matrix, 246
sftest (Many Shapiro-Francia normality tests), 163
sftests, *52*, *107*
sftests (Many Shapiro-Francia normality tests), 163
Significance testing for the coefficients of Quasi binomial or the quasi Poisson regression, 247
Simulation of random values from a Bingham distribution, 248
Simulation of random values from a Bingham distribution with any symmetric matrix, 249
Simulation of random values from a normal distribution, 251
Simulation of random values from a von Mises-Fisher distribution, 252
Skeleton of the PC algorithm, 253
skew, *52*, *117*
skew (Skewness and kurtosis coefficients), 255
skew.test2, *52*, *208*, *255*
skew.test2 (Hypothesis testing between two skewness or kurtosis coefficients), 116
Skewness and kurtosis coefficients, 255
Some summary statistics of a vector for each level of a grouping variable, 256
Sort, *184*
Sort (Sort - Integer Sort - Sort a vector coresponding to another), 257
Sort - Integer Sort - Sort a vector coresponding to another, 257
Sort and unique numbers, 259
Sort.int (Sort - Integer Sort - Sort a vector coresponding to another), 257
sort_cor_vectors, *259*, *260*
sort_cor_vectors (Sort - Integer Sort - Sort a vector coresponding to another), 257
sort_mat (Sorting of the columns-rows of a matrix), 260
sort_unique, *15*, *258*, *260*
sort_unique (Sort and unique numbers), 259
Sorting of the columns-rows of a matrix, 260
Source many R files, 261
sourceR, *27*, *238*
sourceR (Source many R files), 261
sourceRd, *27*, *238*
sourceRd (Source many R files), 261
spat.med, *230*, *264*, *265*

spat.med (Spatial median for Euclidean data), 262
Spatial median for Euclidean data, 262
Spatial median regression, 263
Spatial sign covariance matrix, 264
spatmed.reg, *230*, *265*
spatmed.reg (Spatial median regression), 263
spdinv (Inverse of a symmetric positive definite matrix), 121
Spherical and hyperspherical median, 265
spml.mle, *32*, *128*
spml.mle (MLE of some circular distributions), 196
spml.reg, *33*
spml.reg (Circular or angular regression(s)), 31
spml.regs (Circular or angular regression(s)), 31
squareform (Vector allocation in a symmetric matrix), 275
sscov, *264*
sscov (Spatial sign covariance matrix), 264
Stack (Represantation of Stack), 241
Standardisation, 266
standardise (Standardisation), 266
Sub-matrix, 267
submatrix (Sub-matrix), 267

Table, *68*, *229*
Table (Table Creation - Frequency of each value), 268
Table Creation - Frequency of each value, 268
Tcrossprod, *66*, *82*
Tcrossprod (Matrix multiplication), 179
Tests for the dispersion parameter in Poisson distribution, 270
tmle (MLE of continuous univariate distributions defined on the real line), 191
tobit.mle (MLE of the tobit model), 202
Topological sort of a DAG, 271
topological_sort (Topological sort of a DAG), 271
total.dist, *78*
total.dist (Distance matrix - Sum of all pairwise distances in a distance matrix), 78
total.dista, *78*
total.dista (Distance between vectors and a matrix - Sum of all pairwise distances in a distance matrix.), 76
transpose, *180*
transpose (Transpose of a matrix), 272
Transpose of a matrix, 272
Trigamma (Natural logarithm of the gamma function and its derivatives), 215
ttest, *85*, *136*, *139*, *155*, *164*, *181*, *221*
ttest (Many one sample tests), 156
ttest1, *84*
ttest1 (One sample t-test for a vector), 220
ttest2, *22*, *90*, *115*, *142*, *147*
ttest2 (Multi-sample tests for vectors), 205
ttests, *10*, *85*, *136*, *137*, *141*, *144*, *151*, *155*, *157*, *164*, *171*, *181*, *206*, *221*
ttests (Many 2 sample tests), 137
ttests.pairs (Matrix with all pairs of t-tests), 180
twoway.anova (Multi-sample tests for vectors), 205
twoway.anovas (Many two-way ANOVAs), 171

ufactor (Fast and general - untyped represantation of a factor variable), 93
Uniformity test for circular data, 273
Unique (Sort and unique numbers), 259
univglms, *14*, *17–19*, *63*, *65*, *104*, *131*, *143*, *146*, *152*, *162*, *166*, *167*, *174*, *176*, *177*, *182*, *233*, *234*, *248*, *268*, *277*
univglms (Many univariate generalised linear models), 172
univglms2 (Many univariate generalised linear models), 172
upper_tri (Lower and Upper triangular of a matrix), 133

Var (Variance of a vector), 274
var2test (Multi-sample tests for vectors), 205

var2tests (Many 2 sample tests), 137
varcomps.mle, *88*, *149*, *160*, *239*
varcomps.mle (Moment and maximum likelihood estimation of variance components), 203
varcomps.mom, *158*, *236*
varcomps.mom (Moment and maximum likelihood estimation of variance components), 203
Variance of a vector, 274
vartest (Many one sample tests), 156
vartests (Many multi-sample tests), 150
vecdist, *225*
vecdist (Distance matrix - Sum of all pairwise distances in a distance matrix), 78
Vector allocation in a symmetric matrix, 275
vm.mle, *56*, *189*, *192*, *237*
vm.mle (MLE of some circular distributions), 196
vmf.mle, *58*, *116*, *128*, *197*, *252*, *266*, *273*
vmf.mle (MLE of (hyper-)spherical distributions), 187

watson, *58*
watson (Uniformity test for circular data), 273
weib.reg (Weibull regression model), 276
Weibull regression model, 276
weibull.mle (MLE of continuous univariate distributions defined on the positive line), 189
which.is (Index of the columns of a data.frame which are a specific type), 117
wigner.mle (MLE of continuous univariate distributions defined on the real line), 191
wrapcauchy.mle (MLE of some circular distributions), 196

XopY.sum (Operations between two matrices or matrix and vector), 221

yule, *59*
yule (Yule's Y (coefficient of colligation)), 277
Yule's Y (coefficient of colligation), 277

zip.mle, *187*, *191*, *192*
zip.mle (MLE of count data (univariate discrete distributions)), 192
ztp.mle, *187*
ztp.mle (MLE of count data (univariate discrete distributions)), 192