

Package: Rmpfr (via r-universe)

October 26, 2024

Title R MPFR - Multiple Precision Floating-Point Reliable

Version 0.9-5

Date 2024-01-20

DateNote Previous CRAN version 0.9-4 on 2023-12-04

Type Package

Description Arithmetic (via S4 classes and methods) for arbitrary precision floating point numbers, including transcendental ("special") functions. To this end, the package interfaces to the 'LGPL' licensed 'MPFR' (Multiple Precision Floating-Point Reliable) Library which itself is based on the 'GMP' (GNU Multiple Precision) Library.

SystemRequirements gmp (>= 4.2.3), mpfr (>= 3.0.0), pdfcrop (part of TexLive) is required to rebuild the vignettes.

SystemRequirementsNote 'MPFR' (MP Floating-Point Reliable Library, <https://www.mpfr.org/>) and 'GMP' (GNU Multiple Precision library, <https://gmplib.org/>), see >> README.md

Depends gmp (>= 0.6-1), R (>= 3.6.0)

Imports stats, utils, methods

Suggests MASS, Bessel, polynom, sfsmisc (>= 1.1-14)

SuggestsNote MASS, polynom, sfsmisc: only for vignette;

Enhances dfoptim, pracma, DPQ

EnhancesNote mentioned in Rd xrefs | used in example

URL <https://rmpfr.r-forge.r-project.org/>

BugReports https://r-forge.r-project.org/tracker/?group_id=386

License GPL (>= 2)

Encoding UTF-8

NeedsCompilation yes

Author Martin Maechler [aut, cre]
 (<<https://orcid.org/0000-0002-8685-9910>>), Richard M. Heiberger
 [ctb] (formatHex(), *Bin, *Dec), John C. Nash [ctb] (hjkMpfr()),
 origin of unirootR()), Hans W. Borchers [ctb] (optimizeR(*,
 ``GoldenRatio"); origin of hjkMpfr())

Maintainer Martin Maechler <maechler@stat.math.ethz.ch>

Repository CRAN

Date/Publication 2024-01-21 12:22:45 UTC

Contents

Rmpfr-package	3
array_or_vector-class	6
asNumeric-methods	7
atomicVector-class	8
Bernoulli	9
Bessel_mpfr	10
bind-methods	11
chooseMpfr	12
factorialMpfr	14
formatHex	16
formatMpfr	18
frexpMpfr	21
gmp-conversions	23
hjkMpfr	24
igamma	26
integrateR	28
is.whole	30
log1mexp	31
matmult	33
Mnumber-class	35
mpfr	36
mpfr-class	38
mpfr-distr-etc	43
mpfr-special-functions	45
mpfr-utils	47
mpfr.utils	52
mpfrArray	53
mpfrMatrix	55
mpfrMatrix-utils	58
optimizeR	59
pbetaI	62
pmax	64
qnormI	65
Rmpfr-workarounds	68
roundMpfr	69
sapplyMpfr	69

seqMpfr 71
 str.mpfr 72
 sumBinomMpfr 73
 unirootR 75

Index 80

Rmpfr-package *R MPFR - Multiple Precision Floating-Point Reliable*

Description

Rmpfr provides S4 classes and methods for arithmetic including transcendental ("special") functions for arbitrary precision floating point numbers, here often called "mpfr - numbers". To this end, it interfaces to the LGPL'ed MPFR (Multiple Precision Floating-Point Reliable) Library which itself is based on the GMP (GNU Multiple Precision) Library.

Details

Package: Rmpfr
 Title: R MPFR - Multiple Precision Floating-Point Reliable
 Version: 0.9-5
 Date: 2024-01-20
 DateNote: Previous CRAN version 0.9-4 on 2023-12-04
 Type: Package
 Authors@R: c(person("Martin", "Maechler", role = c("aut", "cre"), email = "maechler@stat.math.ethz.ch", com
 Description: Arithmetic (via S4 classes and methods) for arbitrary precision floating point numbers, including
 SystemRequirements: gmp (>= 4.2.3), mpfr (>= 3.0.0), pdfcrop (part of TexLive) is required to rebuild the vignettes.
 SystemRequirementsNote: 'MPFR' (MP Floating-Point Reliable Library, <https://www.mpfr.org/>) and 'GMP' (GNU Multipl
 Depends: gmp (>= 0.6-1), R (>= 3.6.0)
 Imports: stats, utils, methods
 Suggests: MASS, Bessel, polynom, sfsmisc (>= 1.1-14)
 SuggestsNote: MASS, polynom, sfsmisc: only for vignette;
 Enhances: dfoptim, pracma, DPQ
 EnhancesNote: mentioned in Rd xrefs | used in example
 URL: <https://rmpfr.r-forge.r-project.org/>
 BugReports: https://r-forge.r-project.org/tracker/?group_id=386
 License: GPL (>= 2)
 Encoding: UTF-8
 Author: Martin Maechler [aut, cre] (<<https://orcid.org/0000-0002-8685-9910>>), Richard M. Heiberger [c
 Maintainer: Martin Maechler <maechler@stat.math.ethz.ch>

Index of help topics:

.bigq2mpfr Conversion Utilities gmp <-> Rmpfr
 Bernoulli Bernoulli Numbers in Arbitrary Precision

Bessel_mpfr	Bessel functions of Integer Order in multiple precisions
Mnumber-class	Class "Mnumber" and "mNumber" of "mpfr" and regular numbers and arrays from them
Rmpfr-package	R MPFR - Multiple Precision Floating-Point Reliable
array_or_vector-class	Auxiliary Class "array_or_vector"
asNumeric-methods	Methods for 'asNumeric(<mpfr>)'
atomicVector-class	Virtual Class "atomicVector" of Atomic Vectors
c.mpfr	MPFR Number Utilities
cbind	"mpfr" '...' - Methods for Functions cbind(), rbind()
chooseMpfr	Binomial Coefficients and Pochhammer Symbol aka Rising Factorial
determinant.mpfrMatrix	Functions for mpfrMatrix Objects
factorialMpfr	Factorial 'n!' in Arbitrary Precision
formatHex	Flexibly Format Numbers in Binary, Hex and Decimal Format
formatMpfr	Formatting MPFR (multiprecision) Numbers
frexpMpfr	Base-2 Representation and Multiplication of Mpfr Numbers
getPrec	Rmpfr - Utilities for Precision Setting, Printing, etc
hjkMpfr	Hooke-Jeeves Derivative-Free Minimization R (working for MPFR)
igamma	Incomplete Gamma Function
integrateR	One-Dimensional Numerical Integration - in pure R
is.whole.mpfr	Whole ("Integer") Numbers
log1mexp	Compute $f(a) = \log(1 \pm \exp(-a))$ Numerically Optimally
matmult	(MPFR) Matrix (Vector) Multiplication
mpfr	Create "mpfr" Numbers (Objects)
mpfr-class	Class "mpfr" of Multiple Precision Floating Point Numbers
mpfrArray	Construct "mpfrArray" almost as by 'array()'
mpfrMatrix-class	Classes "mpfrMatrix" and "mpfrArray"
optimizeR	High Precision One-Dimensional Optimization
outer	Base Functions etc, as an Rmpfr version
pbetaI	Accurate Incomplete Beta / Beta Probabilities For Integer Shapes
pmax	Parallel Maxima and Minima
pnorm	Distribution Functions with MPFR Arithmetic
qnormI	Gaussian / Normal Quantiles 'qnorm()' via Inversion
roundMpfr	Rounding to Binary bits, "mpfr-internally"
sapplyMpfr	Apply a Function over a "mpfr" Vector

<code>seqMpfr</code>	"mpfr" Sequence Generation
<code>str.mpfr</code>	Compactly Show STRucture of Rmpfr Number Object
<code>sumBinomMpfr</code>	(Alternating) Binomial Sums via Rmpfr
<code>unirootR</code>	One Dimensional Root (Zero) Finding - in pure R
<code>zeta</code>	Special Mathematical Functions (MPFR)

Further information is available in the following vignettes:

<code>Maechler_userR_2011-abstr</code>	<code>useR-2011-abstract</code> (source)
<code>Rmpfr-pkg</code>	Arbitrarily Accurate Computation with R Package Rmpfr (source)
<code>log1mexp-note</code>	Accurately Computing $\log(1 - \exp(\cdot))$ – Assessed by Rmpfr (source)

The following (help pages) index does not really mention that we provide *many* methods for mathematical functions, including `gamma`, `digamma`, etc, namely, all of R's (S4) Math group (with the only exception of `trigamma`), see the list in the examples. Additionally also `pnorm`, the "error function", and more, see the list in `zeta`, and further note the first vignette (below).

Partial index:

<code>mpfr</code>	Create "mpfr" Numbers (Objects)
<code>mpfrArray</code>	Construct "mpfrArray" almost as by <code>array()</code>
<code>mpfr-class</code>	Class "mpfr" of Multiple Precision Floating Point Numbers
<code>mpfrMatrix-class</code>	Classes "mpfrMatrix" and "mpfrArray"
<code>Bernoulli</code>	Bernoulli Numbers in Arbitrary Precision
<code>Bessel_mpfr</code>	Bessel functions of Integer Order in multiple precisions
<code>c.mpfr</code>	MPFR Number Utilities
<code>cbind</code>	"mpfr" . . . - Methods for Functions <code>cbind()</code> , <code>rbind()</code>
<code>chooseMpfr</code>	Binomial Coefficients and Pochhammer Symbol aka Rising Factorial
<code>factorialMpfr</code>	Factorial 'n!' in Arbitrary Precision
<code>formatMpfr</code>	Formatting MPFR (multiprecision) Numbers
<code>getPrec</code>	Rmpfr - Utilities for Precision Setting, Printing, etc
<code>roundMpfr</code>	Rounding to Binary bits, "mpfr-internally"
<code>seqMpfr</code>	"mpfr" Sequence Generation
<code>sumBinomMpfr</code>	(Alternating) Binomial Sums via Rmpfr
<code>zeta</code>	Special Mathematical Functions (MPFR)
<code>integrateR</code>	One-Dimensional Numerical Integration - in pure R
<code>unirootR</code>	One Dimensional Root (Zero) Finding - in pure R
<code>optimizeR</code>	High Precision One-Dimensional Optimization
<code>hjkMpfr</code>	Hooke-Jeeves Derivative-Free Minimization R (working for MPFR)

Further information is available in the following vignettes:

Rmpfr-pkg Arbitrarily Accurate Computation with R: The 'Rmpfr' package (source, pdf)
 log1mexp-note Accurately Computing $\log(1 - \exp(\cdot))$ – Assessed by Rmpfr (source, pdf)

Author(s)

Martin Maechler

References

MPFR (MP Floating-Point Reliable Library), <https://www.mpfr.org/>
 GMP (GNU Multiple Precision library), <https://gmplib.org/>
 and see the vignettes mentioned above.

See Also

The R package **gmp** for big integer **gmp** and rational numbers (**bigrational**) on which **Rmpfr** depends.

Examples

```
## Using "mpfr" numbers instead of regular numbers...
n1.25 <- mpfr(5, precBits = 256)/4
n1.25

## and then "everything" just works with the desired chosen precision:hig
n1.25 ^ c(1:7, 20, 30) ## fully precise; compare with
print(1.25 ^ 30, digits=19)

exp(n1.25)

## Show all math functions which work with "MPFR" numbers (1 exception: trigamma)
getGroupMembers("Math")

## We provide *many* arithmetic, special function, and other methods:
showMethods(classes = "mpfr")
showMethods(classes = "mpfrArray")
```

array_or_vector-class *Auxiliary Class "array_or_vector"*

Description

"array_or_vector" is the class union of `c("array", "matrix", "vector")` and exists for its use in signatures of method definitions.

Details

Using "array_or_vector" instead of just "vector" in a signature makes an important difference: E.g., if we had `setMethod(crossprod, c(x="mpfr", y="vector"), function(x,y) CPR(x,y))`, a call `crossprod(x, matrix(1:6, 2, 3))` would extend into a call of `CPR(x, as(y, "vector"))` such that `CPR()`'s second argument would simply be a vector instead of the desired 2×3 matrix.

Objects from the Class

A virtual Class: No objects may be created from it.

Examples

```
showClass("array_or_vector")
```

asNumeric-methods *Methods for asNumeric(<mpfr>)*

Description

Methods for function `asNumeric` (in package **gmp**).

Usage

```
## S4 method for signature 'mpfrArray'
asNumeric(x)
```

Arguments

`x` a "number-like" object, here, a `mpfr` or typically `mpfrArray`one.

Value

an R object of type (`typeof`) "numeric", a `matrix` or `array` if `x` had non-NULL dimension `dim()`.

Methods

signature(`x = "mpfrArray"`) this method also dispatches for `mpfrMatrix` and returns a numeric array.

signature(`x = "mpfr"`) for non-array/matrix, `asNumeric(x)` is basically the same as `as.numeric(x)`.

Author(s)

Martin Maechler

See Also

our lower level (non-generic) `toNum()`. Further, `asNumeric` (package **gmp**), standard R's `as.numeric()`.

Examples

```
x <- (0:7)/8 # (exact)
X <- mpfr(x, 99)
stopifnot(identical(asNumeric(x), x),
           identical(asNumeric(X), x))

m <- matrix(1:6, 3,2)
(M <- mpfr(m, 99) / 5) ##-> "mpfrMatrix"
asNumeric(M) # numeric matrix
stopifnot(all.equal(asNumeric(M), m/5),
           identical(asNumeric(m), m))# remains matrix
```

atomicVector-class *Virtual Class "atomicVector" of Atomic Vectors*

Description

The `class` "atomicVector" is a *virtual* class containing all atomic vector classes of base `R`, as also implicitly defined via `is.atomic`.

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

In the `Matrix` package, the "atomicVector" is used in signatures where typically "old-style" "matrix" objects can be used and can be substituted by simple vectors.

Extends

The atomic classes "logical", "integer", "double", "numeric", "complex", "raw" and "character" are extended directly. Note that "numeric" already contains "integer" and "double", but we want all of them to be direct subclasses of "atomicVector".

Author(s)

Martin Maechler

See Also

`is.atomic`, `integer`, `numeric`, `complex`, etc.

Examples

```
showClass("atomicVector")
```


Description

Computes the Bernoulli numbers in the desired (binary) precision. The computation happens via the `zeta` function and the formula

$$B_k = -k\zeta(1 - k),$$

and hence the only non-zero odd Bernoulli number is $B_1 = +1/2$. (Another tradition defines it, equally sensibly, as $-1/2$.)

Usage

```
Bernoulli(k, precBits = 128)
```

Arguments

<code>k</code>	non-negative integer vector
<code>precBits</code>	the precision in <i>bits</i> desired.

Value

an `mpfr` class vector of the same length as `k`, with *i*-th component the `k[i]`-th Bernoulli number.

Author(s)

Martin Maechler

References

https://en.wikipedia.org/wiki/Bernoulli_number

See Also

`zeta` is used to compute them.

The next version of package `gmp` is to contain `BernoulliQ()`, providing exact Bernoulli numbers as big rationals (class "bigq").

Examples

```
Bernoulli(0:10)
plot(as.numeric(Bernoulli(0:15)), type = "h")

curve(-x*zeta(1-x), -.2, 15.03, n=300,
      main = expression(-x %% zeta(1-x)))
legend("top", paste(c("even", "odd "), "Bernoulli numbers"),
      pch=c(1,3), col=2, pt.cex=2, inset=1/64)
abline(h=0,v=0, lty=3, col="gray")
```

```

k <- 0:15; k[1] <- 1e-4
points(k, -k*zeta(1-k), col=2, cex=2, pch=1+2*(k%%2))

## They pretty much explode for larger k :
k2 <- 2*(1:120)
plot(k2, abs(as.numeric(Bernoulli(k2))), log = "y")
title("Bernoulli numbers exponential growth")

Bernoulli(10000)# - 9.0494239636 * 10^27677

```

Bessel_mpfr

Bessel functions of Integer Order in multiple precisions

Description

Bessel functions of integer orders, provided via arbitrary precision algorithms from the MPFR library.

Note that the computation can be very slow when n and x are large (and of similar magnitude).

Usage

```

Ai(x)
j0(x)
j1(x)
jn(n, x, rnd.mode = c("N", "D", "U", "Z", "A"))
y0(x)
y1(x)
yn(n, x, rnd.mode = c("N", "D", "U", "Z", "A"))

```

Arguments

<code>x</code>	a numeric or mpfr vector.
<code>n</code>	non-negative integer (vector).
<code>rnd.mode</code>	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see mpfr .

Value

Computes multiple precision versions of the Bessel functions of *integer order*, $J_n(x)$ and $Y_n(x)$, and—when using MPFR library 3.0.0 or newer—also of the Airy function $Ai(x)$. Note that currently $Ai(x)$ is very slow to compute for large x .

See Also

[besselJ](#), and [bessely](#) compute the same bessel functions but for arbitrary *real* order and only precision of a bit more than ten digits.

Examples

```

x <- (0:100)/8 # (have exact binary representation)
stopifnot(exprs = {
  all.equal(bessely(x, 0), bY0 <- y0(x))
  all.equal(besselJ(x, 1), bJ1 <- j1(x))
  all.equal(yn(0,x), bY0)
  all.equal(jn(1,x), bJ1)
})

mpfrVersion() # now typically 4.1.0
if(mpfrVersion() >= "3.0.0") { ## Ai() not available previously
  print( aix <- Ai(x) )
  plot(x, aix, log="y", type="l", col=2)
  stopifnot(
    all.equal(Ai(0) , 1/(3^(2/3) * gamma(2/3)))
    , # see https://dlmf.nist.gov/9.2.ii
    all.equal(Ai(100), mpfr("2.6344821520881844895505525695264981561e-291"), tol=1e-37)
  )
  two3rd <- 2/mpfr(3, 144)
  print( all.equal(Ai(0), 1/(3^two3rd * gamma(two3rd)), tol=0) ) # 1.7...e-40
  if(Rmpfr::doExtras()) withAutoprint({ # slowish:
    system.time(ai1k <- Ai(1000)) # 1.4 sec (on 2017 lynne)
    stopifnot(all.equal(print(log10(ai1k)),
      -9157.031193409585185582, tol=2e-16)) # seen 8.8..e-17 | 1.1..e-16
  })
} # ver >= 3.0

```

bind-methods

*"mpfr" '...' - Methods for Functions cbind(), rbind()***Description**

`cbind` and `rbind` methods for signature `...` (see [dotsMethods](#) are provided for class `Mnumber`, i.e., for binding numeric vectors and class `"mpfr"` vectors and matrices (`"mpfrMatrix"`) together.

Usage

```

cbind(..., deparse.level = 1)
rbind(..., deparse.level = 1)

```

Arguments

`...` matrix-/vector-like R objects to be bound together, see the **base** documentation, [cbind](#).

`deparse.level` integer determining under which circumstances column and row names are built from the actual arguments' 'expression', see [cbind](#).

Value

typically a ‘matrix-like’ object, here typically of class `"mpfrMatrix"`.

Methods

`... = "Mnumber"` is used to `(clr)bind` multiprecision “numbers” (inheriting from class `"mpfr"`) together, maybe combined with simple numeric vectors.

`... = "ANY"` reverts to `cbind` and `rbind` from package **base**.

Author(s)

Martin Maechler

See Also

`cbind2`, `cbind`, Documentation in base R’s **methods** package

Examples

```
cbind(1, mpfr(6:3, 70)/7, 3:0)
```

chooseMpfr

Binomial Coefficients and Pochhammer Symbol aka Rising Factorial

Description

Compute binomial coefficients, `chooseMpfr(a, n)` being mathematically the same as `choose(a, n)`, but using high precision (MPFR) arithmetic.

`chooseMpfr.all(n)` means the vector `choose(n, 1:n)`, using enough bits for exact computation via MPFR. However, `chooseMpfr.all()` is now **deprecated** in favor of `chooseZ` from package **gmp**, as that is now vectorized.

`pochMpfr()` computes the Pochhammer symbol or “rising factorial”, also called the “Pochhammer function”, “Pochhammer polynomial”, “ascending factorial”, “rising sequential product” or “upper factorial”,

$$x^{(n)} = x(x+1)(x+2)\cdots(x+n-1) = \frac{(x+n-1)!}{(x-1)!} = \frac{\Gamma(x+n)}{\Gamma(x)}.$$

Usage

```
chooseMpfr(a, n, rnd.mode = c("N", "D", "U", "Z", "A"))
chooseMpfr.all(n, precBits=NULL, k0=1, alternating=FALSE)
pochMpfr(a, n, rnd.mode = c("N", "D", "U", "Z", "A"))
```

Arguments

a	a numeric or <code>mpfr</code> vector.
n	an <code>integer</code> vector; if not of length one, n and a are recycled to the same length.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see <code>mpfr</code> .
precBits	integer or NULL for increasing the default precision of the result.
k0	integer scalar
alternating	logical, for <code>chooseMpfr.all()</code> , indicating if <i>alternating sign</i> coefficients should be returned, see below.

Value

For

`chooseMpfr()`, `pochMpfr()`: an `mpfr` vector of length $\max(\text{length}(a), \text{length}(n))$;

`chooseMpfr.all(n, k0)`: a `mpfr` vector of length $n - k0 + 1$, of binomial coefficients $C_{n,m}$ or, if `alternating` is true, $(-1)^m \cdot C_{n,m}$ for $m \in k0:n$.

Note

Currently this works via a (C level) for(`i` in 1:n)-loop which really slow for large n, say 10^6 , with computational cost $O(n^2)$. In such cases, if you need high precision `choose(a, n)` (or `Pochhammer(a, n)`) for large n, preferably work with the corresponding `factorial(mpfr(...))`, or `gamma(mpfr(...))` terms.

See Also

`choose(n, m)` (**base R**) computes the binomial coefficient $C_{n,m}$ which can also be expressed via Pochhammer symbol as $C_{n,m} = (n - m + 1)^{(m)} / m!$.

`chooseZ` from package **gmp**; for now, `factorialMpfr`.

For (alternating) binomial sums, directly use `sumBinomMpfr`, as that is potentially more efficient.

Examples

```
pochMpfr(100, 4) == 100*101*102*103 # TRUE
a <- 100:110
pochMpfr(a, 10) # exact (but too high precision)
x <- mpfr(a, 70) # should be enough
(px <- pochMpfr(x, 10)) # the same as above (needing only 70 bits)
stopifnot(pochMpfr(a, 10) == px,
          px[1] == prod(mpfr(100:109, 100))) # used to fail

(c1 <- chooseMpfr(1000:997, 60)) # -> automatic "correct" precision
stopifnot(all.equal(c1, choose(1000:997, 60), tolerance=1e-12))

## --- Experimenting & Checking
n.set <- c(1:10, 20, 50:55, 100:105, 200:203, 300:303, 500:503,
          699:702, 999:1001)
```

```

if(!Rmpfr:::doExtras()) { ## speed up: smaller set
  n. <- n.set[-(1:10)]
  n.set <- c(1:10, n.[ c(TRUE, diff(n.) > 1)])
}
C1 <- C2 <- numeric(length(n.set))
for(i.n in seq_along(n.set)) {
  cat(n <- n.set[i.n],":")
  C1[i.n] <- system.time(c.c <- chooseMpfr.all(n) )[1]
  C2[i.n] <- system.time(c.2 <- chooseMpfr(n, 1:n))[1]
  stopifnot(is.whole(c.c), c.c == c.2,
    if(n > 60) TRUE else all.equal(c.c, choose(n, 1:n), tolerance = 1e-15))
  cat(" [0k]\n")
}
matplot(n.set, cbind(C1,C2), type="b", log="xy",
  xlab = "n", ylab = "system.time(.) [s]")
legend("topleft", c("chooseMpfr.all(n)", "chooseMpfr(n, 1:n)"),
  pch=as.character(1:2), col=1:2, lty=1:2, bty="n")

## Currently, chooseMpfr.all() is faster only for large n (>= 300)
## That would change if we used C-code for the *.all() version

## If you want to measure more:
measureMore <- TRUE
measureMore <- FALSE
if(measureMore) { ## takes ~ 2 minutes (on "lynne", Intel i7-7700T, ~2019)
  n.s <- 2^(5:20)
  r <- lapply(n.s, function(n) {
    N <- ceiling(10000/n)
    cat(sprintf("n=%9g => N=%d: ",n,N))
    ct <- system.time(C <- replicate(N, chooseMpfr(n, n/2)))
    cat("[0k]\n")
    list(C=C, ct=ct/N)
  })
  print(ct.n <- t(sapply(r, `[`, "ct")))
  hasSfS <- requireNamespace("sfsmisc")
  plot(ct.n[, "user.self"] ~ n.s, xlab=quote(n), ylab="system.time(.) [s]",
    main = "CPU Time for chooseMpfr(n, n/2)",
    log = "xy", type = "b", axes = !hasSfS)
  if(hasSfS) for(side in 1:2) sfsmisc::eaxis(side)
  summary(fm <- lm(log(ct.n[, "user.self"]) ~ log(n.s), subset = n.s >= 10^4))
  ## --> slope ~ 2 ==> It's O(n^2)
  nn <- 2^seq(11,21, by=1/16) ; Lcol <- adjustcolor(2, 1/2)
  bet <- coef(fm)
  lines(nn, exp(predict(fm, list(n.s = nn))), col=Lcol, lwd=3)
  text(500000,1, substitute(AA %*% n^EE,
    list(AA = signif(exp(bet[1]),3),
      EE = signif( bet[2], 3))), col=2)
} # measure more

```


formatHex

*Flexibly Format Numbers in Binary, Hex and Decimal Format***Description**

Show numbers in binary, hex and decimal format. The resulting character-like objects can be back-transformed to "mpfr" numbers via `mpfr()`.

Usage

```
formatHex(x, precBits = min(getPrec(x)), style = "+", expAlign = TRUE)

formatBin(x, precBits = min(getPrec(x)), scientific = TRUE,
          left.pad = "_", right.pad = left.pad, style = "+", expAlign = TRUE)
formatDec(x, precBits = min(getPrec(x)), digits = decdigits,
          nsmall = NULL, scientific = FALSE, style = "+",
          decimalPointAlign = TRUE, ...)
```

Arguments

<code>x</code>	a numeric or <code>mpfr</code> R object.
<code>precBits</code>	integer, the number of bits of precision, typically derived from <code>x</code> , see <code>getPrec</code> . Numeric, i.e., double precision numbers have 53 bits. For more detail, see <code>mpfr</code> .
<code>style</code>	a single character, to be used in <code>sprintf</code> 's format (<code>fmt</code>), immediately after the <code>"</code> sets a sign in the output, i.e., <code>"+"</code> or <code>"-"</code> , where as <code>style = " "</code> may seem more standard.
<code>expAlign</code>	logical indicating if for scientific ("exponential") representations the exponents should be aligned to the same width, i.e., zero-padded to the same number of digits.
<code>scientific</code>	logical indicating that <code>formatBin</code> should display the binary representation in scientific notation (<code>mpfr(3, 5)</code> is displayed as <code>+0b1.1000p+1</code>). When <code>FALSE</code> , <code>formatBin</code> will display the binary representation in regular format shifted to align binary points (<code>mpfr(3, 5)</code> is displayed <code>+0b11.000</code>).
<code>...</code>	additional optional arguments. <code>formatHex</code> , <code>formatBin</code> : <code>precBits</code> is the only <code>...</code> argument acted on. Other <code>...</code> arguments are ignored. <code>formatDec</code> : <code>precBits</code> is acted on. Any argument accepted by <code>format</code> (except <code>nsmall</code>) is acted on. Other <code>...</code> arguments are ignored.
<code>left.pad</code> , <code>right.pad</code>	characters (one-character strings) that will be used for left- and right-padding of the formatted string when <code>scientific=FALSE</code> . <i>Do not change these unless for display-only purpose !!</i>
<code>nsmall</code>	only used when <code>scientific</code> is false, then passed to <code>format()</code> . If <code>NULL</code> , the default is computed from the range of the non-zero values of <code>x</code> .

digits	integer; the number of decimal digits displayed is the larger of this argument and the internally generated value that is a function of precBits. This is related to but different than digits in <code>format</code> .
decimalPointAlign	logical indicating if padding should be used to ensure that the resulting strings align on the decimal point (".").

Details

For the hexadecimal representation, when the precision is not larger than double precision, `sprintf()` is used directly, otherwise `formatMpfr()` is used and post processed. For the binary representation, the hexadecimal value is calculated and then edited by substitution of the binary representation of the hex characters coded in the `HextoBin` vector. For binary with `scientific=FALSE`, the result of the `scientific=TRUE` version is edited to align binary points. For the decimal representation, the hexadecimal value is calculated with the specified precision and then sent to the `format` function for `scientific=FALSE` or to the `sprintf` function for `scientific=TRUE`.

Value

a character vector (or matrix) like `x`, say `r`, containing the formatted representation of `x`, with a `class` (unless `left.pad` or `right.pad` were not `"_"`). In that case, `formatHex()` and `formatBin()` return class `"Ncharacter"`; for that, `mpfr(.)` has a method and will basically return `x`, i.e., work as *inverse* function.

Since **Rmpfr** version 0.6-2, the S3 class `"Ncharacter"` extends `"character"`. (`class(.)` is now of length two and `class(.)[2]` is `"character"`). There are simple `[` and `print` methods; modifying or setting `dim` works as well.

Author(s)

Richard M. Heiberger <rmh@temple.edu>, with minor tweaking by Martin M.

References

R FAQ 7.31: Why doesn't R think these numbers are equal? `system.file("../../doc/FAQ")`

See Also

`mpfr`, `sprintf`

Examples

```
FourBits <- mpfr(matrix(0:31, 8, 4, dimnames = list(0:7, c(0,8,16,24))),
                 precBits=4) ## 4 significant bits

FourBits

formatHex(FourBits)
formatBin(FourBits, style = " ")
formatBin(FourBits, scientific=FALSE)
formatDec(FourBits)
```

```

## as "Ncharacter" 'inherits from' "character", this now works too :
data.frame(Dec = c( formatDec(FourBits) ), formatHex(FourBits),
           Bin = formatBin(FourBits, style = " "))

FBB <- formatBin(FourBits) ; clB <- class(FBB)
(nFBB <- mpfr(FBB))
stopifnot(class(FBB)[1] == "Ncharacter",
          all.equal(nFBB, FourBits, tol=0))

FBH <- formatHex(FourBits) ; clH <- class(FBH)
(nFBH <- mpfr(FBH))
stopifnot(class(FBH)[1] == "Ncharacter",
          all.equal(nFBH, FourBits, tol=0))

## Compare the different "formattings" (details will change, i.e. improve!)%% FIXME
M <- mpfr(c(-Inf, -1.25, 1/(-Inf), NA, 0, .5, 1:2, Inf), 3)
data.frame(fH = formatHex(M), f16 = format(M, base=16),
           fB = formatBin(M), f2 = format(M, base= 2),
           fD = formatDec(M), f10 = format(M), # base = 10 is default
           fSci= format(M, scientific=TRUE),
           fFix= format(M, scientific=FALSE))

## Other methods ("[" , t()) also work :
stopifnot(dim(F1 <- FBB[, 1, drop=FALSE]) == c(8,1), identical(class( F1), clB),
          dim(t(F1)) == c(1,8), identical(class(t(F1)),clB),
          is.null(dim(F.2 <- FBB[,2])), identical(class( F.2), clB),
          dim(F22 <- FBH[1:2, 3:4]) == c(2,2), identical(class(F22), clH),
          identical(class(FBH[2,3]), clH), is.null(dim(FBH[2,3])),
          identical(FBH[2,3:4], F22[2,]),
          identical(FBH[2,3], unname(FBH[,3][2])),
          TRUE)

TenFrac <- matrix((1:10)/10, dimnames=list(1:10, expression(1/x)))
TenFrac9 <- mpfr(TenFrac, precBits=9) ## 9 significant bits
TenFrac9
formatHex(TenFrac9)
formatBin(TenFrac9)
formatBin(TenFrac9, scientific=FALSE)
formatDec(TenFrac9)
formatDec(TenFrac9, precBits=10)

```

formatMpfr

Formatting MPFR (multiprecision) Numbers

Description

Flexible formatting of “multiprecision numbers”, i.e., objects of class `mpfr`. `formatMpfr()` is also the `mpfr` method of the generic `format` function.

The `formatN()` methods for `mpfr` numbers renders them differently than their double precision equivalents, by appending “_M”.

Function `.mpfr2str()` is the low level work horse for `formatMpfr()` and hence all `print()`ing of "mpfr" objects.

Usage

```
formatMpfr(x, digits = NULL, trim = FALSE, scientific = NA,
  maybe.full = (!is.null(digits) && is.na(scientific)) || isFALSE(scientific),
  base = 10, showNeg0 = TRUE, max.digits = Inf,
  big.mark = "", big.interval = 3L,
  small.mark = "", small.interval = 5L,
  decimal.mark = ".",
  exponent.char = if(base <= 14) "e" else if(base <= 36) "E" else "|e",
  exponent.plus = TRUE,
  zero.print = NULL, drop0trailing = FALSE, ...)

## S3 method for class 'mpfr'
formatN(x, drop0trailing = TRUE, ...)

.mpfr2str(x, digits = NULL, maybe.full = !is.null(digits), base = 10L)
```

Arguments

<code>x</code>	an MPFR number (vector or array).
<code>digits</code>	how many significant digits (in the base chosen!) are to be used in the result. The default, <code>NULL</code> , uses enough digits to represent the full precision, often one or two digits more than “you” would expect. For bases 2,4,8,16, or 32, MPFR requires digits at least 2. For such bases, <code>digits = 1</code> is changed into 2, with a message.
<code>trim</code>	logical; if <code>FALSE</code> , numbers are right-justified to a common width: if <code>TRUE</code> the leading blanks for justification are suppressed.
<code>scientific</code>	either a logical specifying whether MPFR numbers should be encoded in scientific format (“exponential representation”), or an integer penalty (see <code>options("scipen")</code>). Missing values correspond to the current default penalty.
<code>maybe.full</code>	logical, passed to <code>.mpfr2str()</code> .
<code>base</code>	an integer in 2, 3, ..., 62; the base (“basis”) in which the numbers should be represented. Apart from the default base 10, binary (base = 2) or hexadecimal (base = 16) are particularly interesting.
<code>showNeg0</code>	logical indicating if “negative” zeros should be shown with a “-”. The default, <code>TRUE</code> is intentionally different from <code>format(<numeric>)</code> .
<code>exponent.char</code>	the “exponent” character to be used in scientific notation. The default takes into account that for base $B \geq 15$, “e” is part of the (mantissa) digits and the same is true for “E” when $B \geq 37$.
<code>exponent.plus</code>	logical indicating if “+” should be for positive exponents in exponential (aka “scientific”) representation. This used to be hardcoded to <code>FALSE</code> ; the new default is compatible to R’s <code>format()</code> ing of numbers and helps to note visually when exponents are in use.

max.digits a (large) positive number to limit the number of (mantissa) digits, notably when digits is NULL (as by default). Otherwise, a numeric digits is *preferred* to setting max.digits (which should not be smaller than digits).

big.mark, big.interval, small.mark, small.interval, decimal.mark, zero.print, drop0trailing used for prettying decimal sequences, these are passed to `prettyNum` and that help page explains the details.

... further arguments passed to or from other methods.

Value

a character vector or array, say `cx`, of the same length as `x`. Since Rmpfr version 0.5-3 (2013-09), if `x` is an `mpfrArray`, then `cx` is a character `array` with the same `dim` and `dimnames` as `x`.

Note that in scientific notation, the integer exponent is always in *decimal*, i.e., base 10 (even when base is not 10), but of course meaning base powers, e.g., in base 32, "u.giE3" is the same as "ugi0" which is 32^3 times "u.gi". This is in contrast, e.g., with `sprintf("%a", x)` where the powers after "p" are powers of 2.

Note

Currently, `formatMpfr(x, scientific = FALSE)` does *not work correctly*, e.g., for `x <- Const("pi", 128) * 2^c(-200, 200)`, i.e., it uses the scientific / exponential-style format. This is considered bogus and hopefully will change.

Author(s)

Martin Maechler

References

The MPFR manual's description of 'mpfr_get_str()' which is the C-internal workhorse for `.mpfr2str()` (on which `formatMpfr()` builds).

See Also

`mpfr` for creation and the `mpfr` class description with its many methods. The `format` generic, and the `prettyNum` utility on which `formatMpfr` is based as well. The S3 generic function `formatN` from package `gmp`.

`.mpfr_formatinfo(x)` provides the (cheap) non-string parts of `.mpfr2str(x)`; the (base 2) exponents are also available via `.mpfr2exp(x)`.

Examples

```
## Printing of MPFR numbers uses formatMpfr() internally.
## Note how each components uses the "necessary" number of digits:
( x3 <- c(Const("pi", 168), mpfr(pi, 140), 3.14) )
format(x3[3], 15)
format(x3[3], 15, drop0 = TRUE)# "3.14" .. dropping the trailing zeros
x3[4] <- 2^30
```

```

x3[4] # automatically drops trailing zeros
format(x3[1], dig = 41, small.mark = "'') # (41 - 1 = ) 40 digits after "."

rbind(formatN(x3, digits = 15),
      formatN(as.numeric(x3), digits = 15))

(Zero <- mpfr(c(0,1/-Inf), 20)) # 0 and "-0"
xx <- c(Zero, 1:2, Const("pi", 120), -100*pi, -.00987)
format(xx, digits = 2)
format(xx, digits = 1, showNeg0 = FALSE)# "-0" no longer shown

## Output in other bases :
formatMpfr(mpfr(10^6, 40), base=32, drop0trailing=TRUE)
## "ugi0"
mpfr("ugi0", base=32) #-> 1'000'000

## This now works: The large number shows "as" large integer:
x <- Const("pi", 128) * 2^c(-200,200)
formatMpfr(x, scientific = FALSE) # was 1.955...e-60 5.048...e+60

i32 <- mpfr(1:32, precBits = 64)
format(i32, base= 2, drop0trailing=TRUE)
format(i32, base= 16, drop0trailing=TRUE)
format(1/i32, base= 2, drop0trailing=TRUE)# using scientific notation for [17..32]
format(1/i32, base= 32)
format(1/i32, base= 62, drop0trailing=TRUE)
format(mpfr(2, 64)^(1:16), base=16, drop0trailing=TRUE)

```

fexpMpfr

Base-2 Representation and Multiplication of Mpfr Numbers

Description

MPFR - versions of the C99 (and POSIX) standard C (and C++) mathlib functions `fexp()` and `ldexp()`.

`fexpMpfr(x)` computes base-2 exponent e and “mantissa”, or *fraction* r , such that $x = r * 2^e$, where $r \in [0.5, 1)$ (unless when x is in $c(0, -\text{Inf}, \text{Inf}, \text{NaN})$ where $r == x$ and e is 0), and e is integer valued.

`ldexpMpfr(f, E)` is the *inverse* of `fexpMpfr()`: Given fraction or mantissa f and integer exponent E , it returns $x = f * 2^E$. Viewed differently, it's the fastest way to multiply or divide MPFR numbers with 2^E .

Usage

```

fexpMpfr(x, rnd.mode = c("N", "D", "U", "Z", "A"))
ldexpMpfr(f, E, rnd.mode = c("N", "D", "U", "Z", "A"))

```

Arguments

x	numeric (coerced to double) vector.
f	numeric fraction (vector), in $[0.5, 1)$.
E	integer valued, exponent of 2, i.e., typically in $(-1024-50):1024$, otherwise the result will underflow to 0 or overflow to $\pm \text{Inf}$.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see mpfr .

Value

frexpMpfr returns a [list](#) with named components r (of class mpfr) and e (integer valued, of type integer is small enough, "double" otherwise).

Author(s)

Martin Maechler

References

On unix-alikes, typically `man frexp` and `man ldexp`

See Also

Somewhat related, `.mpfr2exp()`, `frexp()` and `ldexp()` in package [DPQ](#).

Examples

```
set.seed(47)
x <- c(0, 2^(-3:3), (-1:1)/0,
      sort(rlnorm(2^12, 10, 20) * sample(c(-1,1), 512, replace=TRUE)))
head(xM <- mpfr(x, 128), 11)
str(rFM <- frexpMpfr(xM))
d.fr <- with(rFM, data.frame(x=x, r=asNumeric(r), e=e))
head(d.fr , 16)
tail(d.fr)
ar <- abs(rFM$r)
stopifnot(0.5 <= ar[is.finite(x) & x != 0], ar[is.finite(x)] < 1,
          is.integer(rFM$e))
ldx <- with(rFM, ldexpMpfr(r, e))
(iN <- which(is.na(x))) # 10
stopifnot(exprs = {
  all.equal(xM, ldx, tol = 2^-124) # allow 4 bits loss, but apart from the NA, even:
  identical(xM[-iN], ldx[-iN])
  is.na(xM [iN])
  is.na(ldx[iN])
})
```

gmp-conversions *Conversion Utilities gmp <-> Rmpfr*

Description

Coerce from and to big integers ([bigz](#)) and [mpfr](#) numbers.
 Further, coerce from big rationals ([bigq](#)) to [mpfr](#) numbers.

Usage

```
.bigz2mpfr(x, precB = NULL, rnd.mode = c('N', 'D', 'U', 'Z', 'A'))
.bigq2mpfr(x, precB = NULL, rnd.mode = c('N', 'D', 'U', 'Z', 'A'))
.mpfr2bigz(x, mod = NA)
.mpfr2bigq(x)
```

Arguments

x	an R object of class bigz , bigq or mpfr respectively.
precB	precision in bits for the result. The default, NULL, means to use the <i>minimal</i> precision necessary for correct representation.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see details of mpfr .
mod	a possible modulus, see as.bigz in package gmp .

Details

Note that we also provide the natural (S4) coercions, `as(x, "mpfr")` for x inheriting from class "bigz" or "bigq".

Value

a numeric vector of the same length as x, of the desired class.

See Also

[mpfr\(\)](#), [as.bigz](#) and [as.bigq](#) in package **gmp**.

Examples

```
S <- gmp::Stirling2(50,10)
show(S)
SS <- S * as.bigz(1:3)^128
stopifnot(all.equal(log2(SS[2]) - log2(S), 128, tolerance=1e-15),
           identical(SS, .mpfr2bigz(.bigz2mpfr(SS))))

.bigz2mpfr(S)            # 148 bit precision
```

```
.bigz2mpfr(S, precB=256) # 256 bit

## rational --> mpfr:
sq <- SS / as.bigz(2)^100
MP <- as(sq, "mpfr")
stopifnot(identical(MP, .bigq2mpfr(sq)),
           SS == MP * as(2, "mpfr")^100)

## New since 2024-01-20: mpfr --> big rational "bigq"
Pi <- Const("pi", 128)
m <- Pi * 2^(-5:5)
(m <- c(m, mpfr(2, 128)^(-5:5)))

getDenom <- Rmpfr::getDenom
stopifnot(is.whole(m * (d.m <- getDenom(m))))
stopifnot(all.equal(m, mpfr(.mpfr2bigq(m), 130), tolerance = 2^-130)) # I see even
all.equal(m, mpfr(.mpfr2bigq(m), 130), tolerance = 0) # TRUE

m <- m * mpfr(2, 128)^200 # quite a bit larger
stopifnot(is.whole(m * (d.m <- getDenom(m))))
stopifnot(all.equal(m, mpfr(.mpfr2bigq(m), 130), tolerance = 2^-130)) # I see even
all.equal(m, mpfr(.mpfr2bigq(m), 130), tolerance = 0) # TRUE

m2 <- m * mpfr(2, 128)^20000 ## really huge
stopifnot(is.whole(m2 * (d.m2 <- getDenom(m2))))
stopifnot(all.equal(m2, mpfr(.mpfr2bigq(m2), 130), tolerance = 2^-130)) # I see even
all.equal(m2, mpfr(.mpfr2bigq(m2), 130), tolerance = 0) # TRUE
```

hjkMpfr

Hooke-Jeeves Derivative-Free Minimization R (working for MPFR)

Description

An implementation of the Hooke-Jeeves algorithm for derivative-free optimization.

This is a slight adaption `hjk()` from package **dfoptim**.

Usage

```
hjkMpfr(par, fn, control = list(), ...)
```

Arguments

<code>par</code>	Starting vector of parameter values. The initial vector may lie on the boundary. If <code>lower[i]=upper[i]</code> for some <code>i</code> , the <code>i</code> -th component of the solution vector will simply be kept fixed.
<code>fn</code>	Nonlinear objective function that is to be optimized. A scalar function that takes a real vector as argument and returns a scalar that is the value of the function at that point.
<code>control</code>	list of control parameters. See Details for more information.
<code>...</code>	Additional arguments passed to <code>fn</code> .

Details

Argument `control` is a list specifying changes to default values of algorithm control parameters. Note that parameter names may be abbreviated as long as they are unique.

The list items are as follows:

`tol` Convergence tolerance. Iteration is terminated when the step length of the main loop becomes smaller than `tol`. This does *not* imply that the optimum is found with the same accuracy. Default is `1.e-06`.

`maxfeval` Maximum number of objective function evaluations allowed. Default is `Inf`, that is no restriction at all.

`maximize` A logical indicating whether the objective function is to be maximized (`TRUE`) or minimized (`FALSE`). Default is `FALSE`.

`target` A real number restricting the absolute function value. The procedure stops if this value is exceeded. Default is `Inf`, that is no restriction.

`info` A logical variable indicating whether the step number, number of function calls, best function value, and the first component of the solution vector will be printed to the console. Default is `FALSE`.

If the minimization process threatens to go into an infinite loop, set either `maxfeval` or `target`.

Value

A `list` with the following components:

<code>par</code>	Best estimate of the parameter vector found by the algorithm.
<code>value</code>	value of the objective function at termination.
<code>convergence</code>	indicates convergence (<code>TRUE</code>) or not (<code>FALSE</code>).
<code>feval</code>	number of times the objective fn was evaluated.
<code>niter</code>	number of iterations (“steps”) in the main loop.

Note

This algorithm is based on the Matlab code of Prof. C. T. Kelley, given in his book “Iterative methods for optimization”. It has been implemented for package **dfoptim** with the permission of Prof. Kelley.

This version does not (yet) implement a cache for storing function values that have already been computed as searching the cache makes it slower.

Author(s)

Hans W Borchers <hwborchers@googlemail.com>; for **Rmpfr**: John Nash, June 2012. Modifications by Martin Maechler.

References

- C.T. Kelley (1999), Iterative Methods for Optimization, SIAM.
 Quarteroni, Sacco, and Saleri (2007), Numerical Mathematics, Springer.

See Also

Standard R's `optim`; `optimizeR` provides *one*-dimensional minimization methods that work with `mpfr`-class numbers.

Examples

```
## simple smooth example:
ff <- function(x) sum((x - c(2:4))^2)
str(rr <- hjkMpfr(rep(mpfr(0,128), 3), ff, control=list(info=TRUE)))

doX <- Rmpfr:::doExtras(); cat("doExtras: ", doX, "\n") # slow parts only if(doX)

## Hooke-Jeeves solves high-dim. Rosenbrock function {but slowly!}
rosenbrock <- function(x) {
  n <- length(x)
  sum (100*((x1 <- x[1:(n-1)])^2 - x[2:n])^2 + (x1 - 1)^2)
}
par0 <- rep(0, 10)
str(rb.db <- hjkMpfr(rep(0, 10), rosenbrock, control=list(info=TRUE)))
if(doX) {
## rosenbrock() is quite slow with mpfr-numbers:
str(rb.M. <- hjkMpfr(mpfr(numeric(10), prec=128), rosenbrock,
  control = list(tol = 1e-8, info=TRUE)))
}

## Hooke-Jeeves does not work well on non-smooth functions
nsf <- function(x) {
  f1 <- x[1]^2 + x[2]^2
  f2 <- x[1]^2 + x[2]^2 + 10 * (-4*x[1] - x[2] + 4)
  f3 <- x[1]^2 + x[2]^2 + 10 * (-x[1] - 2*x[2] + 6)
  max(f1, f2, f3)
}
par0 <- c(1, 1) # true min 7.2 at (1.2, 2.4)
h.d <- hjkMpfr(par0, nsf) # fmin=8 at xmin=(2,2)
if(doX) {
## and this is not at all better (but slower!)
h.M <- hjkMpfr(mpfr(c(1,1), 128), nsf, control = list(tol = 1e-15))
}
## --> demo(hjkMpfr) # -> Fletcher's chebyquad function m = n -- residuals
```

igamma

*Incomplete Gamma Function***Description**

For MPFR version $\geq 3.2.0$, the following MPFR library function is provided: `mpfr_gamma_inc(a, x)`, the R interface of which is `igamma(a, x)`, where `igamma(a, x)` is the “upper” incomplete gamma function

$$\Gamma(a, x) := \Gamma(a) - \gamma(a, x),$$

where

$$\gamma(a, x) := \int_0^x t^{a-1} e^{-t} dt,$$

and hence

$$\Gamma(a, x) := \int_x^\infty t^{a-1} e^{-t} dt,$$

and

$$\Gamma(a) := \gamma(a, \infty).$$

As R's `pgamma(x, a)` is

$$\text{pgamma}(x, a) := \gamma(a, x) / \Gamma(a),$$

we get

$$\text{igamma}(a, x) == \text{gamma}(a) * \text{pgamma}(x, a, \text{lower.tail}=\text{FALSE})$$

Usage

```
igamma(a, x, rnd.mode = c("N", "D", "U", "Z", "A"))
```

Arguments

<code>a, x</code>	an object of class <code>mpfr</code> or <code>numeric</code> .
<code>rnd.mode</code>	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see <code>mpfr</code> .

Value

a numeric vector of “common length”, recycling along `a` and `x`.

Author(s)

R interface: Martin Maechler

References

NIST Digital Library of Mathematical Functions, section 8.2. <https://dlmf.nist.gov/8.2.i>
 Wikipedia (2019). *Incomplete gamma function*; https://en.wikipedia.org/wiki/Incomplete_gamma_function

See Also

R's `gamma` (function) and `pgamma` (probability distribution).

Examples

```
## show how close pgamma() is :
x <- c(seq(0,20, by=1/4), 21:50, seq(55, 100, by=5))
if(mpfrVersion() >= "3.2.0") { print(
  all.equal(igamma(Const("pi", 80), x),
            pgamma(x, pi, lower.tail=FALSE) * gamma(pi),
            tol=0, formatFUN = function(., ...) format(., digits = 7)) #-> 2.75e-16 (was 3.13e-16)
  )
## and ensure *some* closeness:
stopifnot(exprs = {
  all.equal(igamma(Const("pi", 80), x),
            pgamma(x, pi, lower.tail=FALSE) * gamma(pi),
            tol = 1e-15)
  })
} # only if MPFR version >= 3.2.0
```

integrateR

One-Dimensional Numerical Integration - in pure R

Description

Numerical integration of one-dimensional functions in pure R, with care so it also works for "mpfr"-numbers.

Currently, only classical Romberg integration of order `ord` is available.

Usage

```
integrateR(f, lower, upper, ..., ord = NULL,
           rel.tol = .Machine$double.eps^0.25, abs.tol = rel.tol,
           max.ord = 19, verbose = FALSE)
```

Arguments

<code>f</code>	an R function taking a numeric or "mpfr" first argument and returning a numeric (or "mpfr") vector of the same length. Returning a non-finite element will generate an error.
<code>lower, upper</code>	the limits of integration. Currently <i>must</i> be finite. Do use "mpfr"-numbers to get higher than double precision, see the examples.
<code>...</code>	additional arguments to be passed to <code>f</code> .
<code>ord</code>	integer, the order of Romberg integration to be used. If this is NULL, as per default, and either <code>rel.tol</code> or <code>abs.tol</code> are specified, the order is increased until convergence.
<code>rel.tol</code>	relative accuracy requested. The default is 1.2e-4, about 4 digits only, see the Note.
<code>abs.tol</code>	absolute accuracy requested.

max.ord	only used, when neither ord or one of rel.tol, abs.tol are specified: Stop Romberg iterations after the order reaches max.ord; may prevent infinite loops or memory explosion.
verbose	logical or integer, indicating if and how much information should be printed during computation.

Details

Note that arguments after . . . must be matched exactly.

For convergence, *both* relative and absolute changes must be smaller than rel.tol and abs.tol, respectively.

rel.tol cannot be less than $\max(50 * \text{Machine}\$double.eps, 0.5e-28)$ if abs.tol ≤ 0 .

Value

A list of class "integrateR" (as from standard R's `integrate()`) with a `print` method and components

value	the final estimate of the integral.
abs.error	estimate of the modulus of the absolute error.
subdivisions	for Romberg, the number of function evaluations.
message	"OK" or a character string giving the error message.
call	the matched call.

Note

f must accept a vector of inputs and produce a vector of function evaluations at those points. The `Vectorize` function may be helpful to convert f to this form.

If you want to use higher accuracy, you *must* set lower or upper to "mpfr" numbers (and typically lower the relative tolerance, rel.tol), see also the examples.

Note that the default tolerances (rel.tol, abs.tol) are not very accurate, but the same as for `integrate`, which however often returns considerably more accurate results than requested. This is typically *not* the case for `integrateR()`.

Note

We use practically the same print S3 method as `print.integrate`, provided by R, with a difference when the message component is not "Ok".

Author(s)

Martin Maechler

References

Bauer, F.L. (1961) Algorithm 60 – Romberg Integration, *Communications of the ACM* **4**(6), p.255.

See Also

R's standard, `integrate`, is much more adaptive, also allowing infinite integration boundaries, and typically considerably faster for a given accuracy.

Examples

```
## See more from ?integrate
## this is in the region where integrate() can get problems:
integrateR(dnorm,0,2000)
integrateR(dnorm,0,2000, rel.tol=1e-15)
(Id <- integrateR(dnorm,0,2000, rel.tol=1e-15, verbose=TRUE))
Id$value == 0.5 # exactly

## Demonstrating that 'subdivisions' is correct:
Exp <- function(x) { .N <<- .N+ length(x); exp(x) }
.N <- 0; str(integrateR(Exp, 0,1, rel.tol=1e-10), digits=15); .N

### Using high-precision functions -----

## Polynomials are very nice:
integrateR(function(x) (x-2)^4 - 3*(x-3)^2, 0, 5, verbose=TRUE)
# n= 1, 2^n=      2 | I =          46.04, abs.err =      98.9583
# n= 2, 2^n=      4 | I =           20, abs.err =       26.0417
# n= 3, 2^n=      8 | I =           20, abs.err =  7.10543e-15
## 20 with absolute error < 7.1e-15
## Now, using higher accuracy:
I <- integrateR(function(x) (x-2)^4 - 3*(x-3)^2, 0, mpfr(5,128),
                rel.tol = 1e-20, verbose=TRUE)
I ; I$value ## all fine

## with floats:
integrateR(exp,      0      , 1, rel.tol=1e-15, verbose=TRUE)
## with "mpfr":
(I <- integrateR(exp, mpfr(0,200), 1, rel.tol=1e-25, verbose=TRUE))
(I.true <- exp(mpfr(1, 200)) - 1)
## true absolute error:
stopifnot(print(as.numeric(I.true - I$value)) < 4e-25)

## Want absolute tolerance check only (=> set 'rel.tol' very high, e.g. 1):
(Ia <- integrateR(exp, mpfr(0,200), 1, abs.tol = 1e-6, rel.tol=1, verbose=TRUE))

## Set 'ord' (but no '*tol') --> Using 'ord'; no convergence checking
(I <- integrateR(exp, mpfr(0,200), 1, ord = 13, verbose=TRUE))
```

Description

Check which elements of `x[]` are integer valued aka “whole” numbers, including MPFR numbers (class `mpfr`).

Usage

```
## S3 method for class 'mpfr'
is.whole(x)
```

Arguments

`x` any R vector, here of class `mpfr`.

Value

logical vector of the same length as `x`, indicating where `x[.]` is integer valued.

Author(s)

Martin Maechler

See Also

`is.integer(x)` (**base** package) checks for the *internal* mode or class, not if `x[i]` are integer valued. The `is.whole()` methods in package **gmp**.

Examples

```
is.integer(3) # FALSE, it's internally a double
is.whole(3)   # TRUE
x <- c(as(2,"mpfr") ^ 100, 3, 3.2, 1000000, 2^40)
is.whole(x) # one FALSE, only
```

log1mexp

Compute $f(a) = \log(1 \pm \exp(-a))$ Numerically Optimally

Description

Compute $f(a) = \log(1 - \exp(-a))$, respectively $g(x) = \log(1 + \exp(x))$ quickly numerically accurately.

Usage

```
log1mexp(a, cutoff = log(2))
log1pexp(x, c0 = -37, c1 = 18, c2 = 33.3)
```

Arguments

a	numeric (or <code>mpfr</code>) vector of positive values.
x	numeric vector, may also be an " <code>mpfr</code> " object.
cutoff	positive number; <code>log(2)</code> is "optimal", but the exact value is unimportant, and anything in <code>[0.5, 1]</code> is fine.
<code>c0, c1, c2</code>	cutoffs for <code>log1pexp</code> ; see below.

Value

$$\text{log1mexp}(a) := f(a) = \log(1 - \exp(-a)) = \log_1\text{p}(-\exp(-a)) = \log(-\text{expm1}(-a))$$

or, respectively,

$$\text{log1pexp}(x) := g(x) = \log(1 + \exp(x)) = \log_1\text{p}(\exp(x))$$

computed accurately and quickly.

Author(s)

Martin Maechler, May 2002; `log1pexp()` in 2012

References

Martin Mächler (2012). Accurately Computing $\log(1 - \exp(-|a|))$; <https://CRAN.R-project.org/package=Rmpfr/vignettes/log1mexp-note.pdf>.

Examples

```
fExpr <- expression(
  DEF = log(1 - exp(-a)),
  expm1 = log(-expm1(-a)),
  log1p = log1p(-exp(-a)),
  F = log1mexp(a))
a. <- 2^seq(-58, 10, length = 256)
a <- a. ; str(fa <- do.call(cbind, as.list(fExpr)))
head(fa)# expm1() works here
tail(fa)# log1p() works here

## graphically:
lwd <- 1.5*(5:2); col <- adjustcolor(1:4, 0.4)
op <- par(mfcol=c(1,2), mgp = c(1.25, .6, 0), mar = .1+c(3,2,1,1))
matplot(a, fa, type = "l", log = "x", col=col, lwd=lwd)
legend("topleft", fExpr, col=col, lwd=lwd, lty=1:4, bty="n")
# expm1() & log1mexp() work here

matplot(a, -fa, type = "l", log = "xy", col=col, lwd=lwd)
legend("left", paste("-",fExpr), col=col, lwd=lwd, lty=1:4, bty="n")
# log1p() & log1mexp() work here
```



```

par(op)

aM <- 2^seqMpfr(-58, 10, length=length(a.)) # => default prec = 128
a <- aM; dim(faM <- do.call(cbind, as.list(fExpr))) # 256 x 4, "same" as 'fa'
## Here, for small 'a' log1p() and even 'DEF' is still good enough
l_f <- asNumeric(log(-faM))
all.equal(l_f[, "F"], l_f[, "log1p"], tol=0) # see TRUE (Lnx 64-bit)
io <- a. < 80 # for these, the differences are small
all.equal(l_f[io, "F"], l_f[io, "expm1"], tol=0) # see 6.662e-9
all.equal(l_f[io, "F"], l_f[io, "DEF" ], tol=0)
stopifnot(exprs = {
  all.equal(l_f[, "F"], l_f[, "log1p"],      tol= 1e-15)
  all.equal(l_f[io, "F"], l_f[io, "expm1"],  tol= 1e-7)
  all.equal(l_f[io, "F"], l_f[io, "DEF" ],  tol= 1e-7)
})
## For 128-bit prec, if we go down to 2^-130, "log1p" is no longer ok:
aM2 <- 2^seqMpfr(-130, 10, by = 1/2)
a <- aM2; fa2 <- do.call(cbind, as.list(fExpr))
head(asNumeric(fa2), 12)
tail(asNumeric(fa2), 12)

matplot(a, log(-fa2[,1:3]) -log(-fa2[, "F"]), type="l", log="x",
        lty=1:3, lwd=2*(3:1)-1, col=adjustcolor(2:4, 1/3))
legend("top", colnames(fa2)[1:3], lty=1:3, lwd=2*(3:1)-1, col=adjustcolor(2:4, 1/3))

cols <- adjustcolor(2:4, 1/3); lwd <- 2*(3:1)-1
matplot(a, 1e-40+abs(log(-fa2[,1:3]) -log(-fa2[, "F"])), type="o", log="xy",
        main = "log1mexp(a) -- approximation rel.errors, mpfr(*, prec=128)",
        pch=21:23, cex=.6, bg=5:7, lty=1:2, lwd=lwd, col=cols)
legend("top", colnames(fa2)[1:3], bty="n", lty=1:2, lwd=lwd, col=cols,
        pch=21:23, pt.cex=.6, pt.bg=5:7)

## ----- log1pexp() [simpler] -----

curve(log1pexp, -10, 10, asp=1)
abline(0,1, h=0,v=0, lty=3, col="gray")

## Cutoff c1 for log1pexp() -- not often "needed":
curve(log1p(exp(x)) - log1pexp(x), 16, 20, n=2049)
## need for *some* cutoff:
x <- seq(700, 720, by=2)
cbind(x, log1p(exp(x)), log1pexp(x))

## Cutoff c2 for log1pexp():
curve((x+exp(-x)) - x, 20, 40, n=1025)
curve((x+exp(-x)) - x, 33.1, 33.5, n=1025)

```

Description

Matrix / vector multiplication of `mpfr` (and “simple” `numeric`) matrices and vectors.

`matmult(x,y, fPrec = 2)` or `crossprod(x,y, fPrec = 2)` use higher precision in underlying computations.

Usage

```
matmult(x, y, ...)
```

Arguments

`x, y` `numeric` or `mpfrMatrix`-classed `R` objects, i.e. semantically numeric matrices or vectors.

`...` arguments passed to the hidden underlying `.matmult.R()` work horse which is also underlying the `%*%`, `crossprod()`, and `tcrossprod()` methods, see the `mpfrMatrix` class documentation:

fPrec a multiplication factor, a positive number determining the number of bits `precBits` used for the underlying multiplication and summation arithmetic. The default is `fPrec = 1`. Setting `fPrec = 2` doubles the precision which has been recommended, e.g., by John Nash.

precBits the number of bits used for the underlying multiplication and summation arithmetic; by default `precBits = fPrec * max(getPrec(x), getPrec(y))` which typically uses the same accuracy as regular `mpfr`-arithmetic would use.

Value

a (base `R`) `matrix` or `mpfrMatrix`, depending on the classes of `x` and `y`.

Note

Using `matmult(x,y)` instead of `x %*% y`, makes sense mainly *if* you use non-default `fPrec` or `precBits` arguments.

The `crossprod()`, and `tcrossprod()` function have the *identical* optional arguments `fPrec` or `precBits`.

Author(s)

Martin Maechler

See Also

`%*%`, `crossprod`, `tcrossprod`.

Examples

```
## FIXME: add example

## 1) matmult() <--> %*%

## 2) crossprod() , tcrossprod() %<--> ./mpfrMatrix-class.Rd examples (!)
```

Mnumber-class	<i>Class "Mnumber" and "mNumber" of "mpfr" and regular numbers and arrays from them</i>
---------------	---

Description

Classes "Mnumber" "mNumber" are class unions of "mpfr" and regular numbers and arrays from them.

Its purpose is for method dispatch, notably defining a `cbind(...)` method where ... contains objects of one of the member classes of "Mnumber".

Classes "mNumber" is considerably smaller as it does *not* contain "matrix" and "array" since these also extend "character" which is not really desirable for generalized numbers. It extends the simple "numericVector" class by `mpfr*` classes.

Methods

```
%*% signature(x = "mpfrMatrix", y = "Mnumber"): ...
crossprod signature(x = "mpfr", y = "Mnumber"): ...
tcrossprod signature(x = "Mnumber", y = "mpfr"): ...
etc. These are documented with the classes mpfr and or mpfrMatrix.
```

See Also

the [array_or_vector](#) sub class; [cbind-methods](#).

Examples

```
## "Mnumber" encompasses (i.e., "extends") quite a few
## "vector / array - like" classes:
showClass("Mnumber")
stopifnot(extends("mpfrMatrix", "Mnumber"),
          extends("array", "Mnumber"))

Mnsub <- names(getClass("Mnumber")@subclasses)
(mNsub <- names(getClass("mNumber")@subclasses))
## mNumber has *one* subclass which is not in Mnumber:
setdiff(mNsub, Mnsub) # namely "numericVector"
## The following are only subclasses of "Mnumber", but not of "mNumber":
setdiff(Mnsub, mNsub)
```

 mpfr *Create "mpfr" Numbers (Objects)*

Description

Create multiple (i.e. typically *high*) precision numbers, to be used in arithmetic and mathematical computations with R.

Usage

```
mpfr(x, precBits, ...)
## Default S3 method:
mpfr(x, precBits, base = 10,
      rnd.mode = c("N","D","U","Z","A"), scientific = NA, ...)

Const(name = c("pi", "gamma", "catalan", "log2"), prec = 120L,
      rnd.mode = c("N","D","U","Z","A"))

is.mpfr(x)
```

Arguments

x	a numeric , mpfr , bigz , bigq , or character vector or array .
precBits, prec	a number, the maximal precision to be used, in <i>bits</i> ; i.e. 53 corresponds to double precision. Must be at least 2. If missing , getPrec(x) determines a default precision.
base	(only when x is character) the base with respect to which x[i] represent numbers; base <i>b</i> must fulfill $2 \leq b \leq 62$.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see details.
scientific	(used only when x is the result of formatBin() , i.e., of class "Bcharacter") logical indicating that the binary representation of x is in scientific notation. When TRUE, mpfr() will substitute 0 for _; when NA, mpfr() will guess, and use TRUE when finding a "p" in x; see also formatBin .
name	a string specifying the mpfrlib - internal constant computation. "gamma" is Euler's gamma (γ), and "catalan" Catalan's constant.
...	potentially further arguments passed to and from methods.

Details

The "mpfr" method of [mpfr\(\)](#) is a simple wrapper around [roundMpfr\(\)](#).

MPFR supports the following rounding modes,

GMP_RNDN: round to nearest (roundTiesToEven in IEEE 754-2008).

GMP_RNDZ: round toward zero (roundTowardZero in IEEE 754-2008).

GMP_RNDU: round toward plus infinity (“Up”, roundTowardPositive in IEEE 754-2008).

GMP_RNDD: round toward minus infinity (“Down”, roundTowardNegative in IEEE 754-2008).

GMP_RNDA: round away from zero (new since MPFR 3.0.0).

The ‘round to nearest’ (“N”) mode, the default here, works as in the IEEE 754 standard: in case the number to be rounded lies exactly in the middle of two representable numbers, it is rounded to the one with the least significant bit set to zero. For example, the number $5/2$, which is represented by (10.1) in binary, is rounded to (10.0)=2 with a precision of two bits, and not to (11.0)=3. This rule avoids the “drift” phenomenon mentioned by Knuth in volume 2 of *The Art of Computer Programming* (Section 4.2.2).

When x is `character`, `mpfr()` will detect the precision of the input object.

Value

an object of (S4) class `mpfr`, or for `mpfr(x)` when x is an array, `mpfrMatrix`, or `mpfrArray` which the user should just as a normal numeric vector or array.

`is.mprfr()` returns TRUE or FALSE.

Author(s)

Martin Maechler

References

The MPFR team. (202x). *GNU MPFR – The Multiple Precision Floating-Point Reliable Library*; see <https://www.mpfr.org/mpfr-current/#doc> or directly <https://www.mpfr.org/mpfr-current/mpfr.pdf>.

See Also

The class documentation `mpfr` contains more details. Use `asNumeric` to transform back to double precision (“numeric”).

Examples

```
mpfr(pi, 120) ## the double-precision pi "translated" to 120-bit precision

pi. <- Const("pi", prec = 260) # pi "computed" to correct 260-bit precision
pi. # nicely prints 80 digits [260 * log10(2) ~= 78.3 ~ 80]

Const("gamma", 128L) # 0.5772...
Const("catalan", 128L) # 0.9159...

x <- mpfr(0:7, 100)/7 # a more precise version of k/7, k=0,...,7
x
1 / x

## character input :
mpfr("2.718281828459045235360287471352662497757") - exp(mpfr(1, 150))
## ~= -4 * 10^-40
```

```

## Also works for NA, NaN, ... :
cx <- c("1234567890123456", 345, "NA", "NaN", "Inf", "-Inf")
mpfr(cx)

## with some 'base' choices :
print(mpfr("111.1111", base=2)) * 2^4

mpfr("af21.01020300a0b0c", base=16)
## 68 bit prec. 44833.00393694653820642

mpfr("ugi0", base = 32) == 10^6 ## TRUE

## --- Large integers from package 'gmp':
Z <- as.bigz(7)^(1:200)
head(Z, 40)
## mpfr(Z) by default chooses the correct *maximal* default precision:
mZ. <- mpfr(Z)
## more efficiently chooses precision individually
m.Z <- mpfr(Z, precBits = frexpZ(Z)$exp)
## the precBits chosen are large enough to keep full precision:
stopifnot(identical(cZ <- as.character(Z),
                    as(mZ., "character")),
           identical(cZ, as(m.Z, "character")))

## compare mpfr-arithmetic with exact rational one:
stopifnot(all.equal(mpfr(as.bigq(355,113), 99),
                    mpfr(355, 99) / 113, tol = 2^-98))

## look at different "rounding modes":
sapply(c("N", "D", "U", "Z", "A"), function(RND)
       mpfr(c(-1,1)/5, 20, rnd.mode = RND), simplify=FALSE)

symnum(sapply(c("N", "D", "U", "Z", "A"),
              function(RND) mpfr(0.2, prec = 5:15, rnd.mode = RND) < 0.2 ))

```

mpfr-class

Class "mpfr" of Multiple Precision Floating Point Numbers

Description

"mpfr" is the class of **M**ultiple **P**recision **F**loatingpoint numbers with **R**eliable arithmetic.

sFor the high-level user, "mpfr" objects should behave as standard R's `numeric` vectors. They would just print differently and use the prespecified (typically high) precision instead of the double precision of 'traditional' R numbers (with `class(.) == "numeric"` and `typeof(.) == "double"`).

`hypot(x,y)` computes the hypotenuse length z in a rectangular triangle with "leg" side lengths x and y , i.e.,

$$z = \text{hypot}(x, y) = \sqrt{x^2 + y^2},$$

in a numerically stable way.

Usage

```
hypot(x,y, rnd.mode = c("N", "D", "U", "Z", "A"))
```

Arguments

`x, y` an object of class `mpfr`.
`rnd.mode` a 1-letter string specifying how *rounding* should happen at C-level conversion to MPFR, see [mpfr](#).

Objects from the Class

Objects are typically created by `mpfr(<number>, precBits)`.
`summary(<mpfr>)` returns an object of class `"summaryMpfr"` which contains `"mpfr"` but has its own `print` method.

Slots

Internally, `"mpfr"` objects just contain standard **R lists** where each list element is of class `"mpfr1"`, representing *one* MPFR number, in a structure with four slots, very much parallelizing the C `struc` in the `mpfr` C library to which the **Rmpfr** package interfaces.

An object of class `"mpfr1"` has slots

`prec`: "integer" specifying the maximal precision in **bits**.
`exp`: "integer" specifying the base-2 exponent of the number.
`sign`: "integer", typically -1 or 1, specifying the sign (i.e. `sign(.)`) of the number.
`d`: an "integer" vector (of 32-bit "limbs") which corresponds to the full mantissa of the number.

Methods

abs signature(`x = "mpfr"`): ...
atan2 signature(`y = "mpfr"`, `x = "ANY"`), and
atan2 signature(`x = "ANY"`, `y = "mpfr"`): compute the arc-tangent of two arguments: `atan2(y, x)` returns the angle between the x-axis and the vector from the origin to (x, y) , i.e., for positive arguments `atan2(y, x) == atan(y/x)`.
lbeta signature(`a = "ANY"`, `b = "mpfrArray"`), is $\log(|B(a, b)|)$ where $B(a, b)$ is the Beta function, `beta(a, b)`.
beta signature(`a = "mpfr"`, `b = "ANY"`),
beta signature(`a = "mpfr"`, `b = "mpfr"`), ..., etc: Compute the beta function $B(a, b)$, using high precision, building on internal `gamma` or `lgamma`. See the help for R's base function `beta` for more. Currently, there, $a, b \geq 0$ is required. Here, we provide (non-**NaN**) for all numeric `a, b`.

When either a, b , or $a + b$ is a negative *integer*, $\Gamma(\cdot)$ has a pole there and is undefined (**NaN**). However the Beta function can be defined there as "limit", in some cases. Following other software such as SAGE, Maple or Mathematica, we provide finite values in these cases. However, note that these are not proper limits (two-dimensional in (a, b)), but useful for some applications. E.g., $B(a, b)$ is defined as zero when $a + b$ is a negative integer, but neither a nor b is. Further, if $a > b > 0$ are integers, $B(-a, b) = B(b, -a)$ can be seen as $(-1)^b * B(a - b + 1, b)$.

dim<- signature(x = "mpfr"): Setting a dimension `dim` on an "mpfr" object makes it into an object of class "mpfrArray" or (more specifically) "mpfrMatrix" for a length-2 dimension, see their help page; note that `t(x)` (below) is a special case of this.

Ops signature(e1 = "mpfr", e2 = "ANY"): ...

Ops signature(e1 = "ANY", e2 = "mpfr"): ...

Arith signature(e1 = "mpfr", e2 = "missing"): ...

Arith signature(e1 = "mpfr", e2 = "mpfr"): ...

Arith signature(e1 = "mpfr", e2 = "integer"): ...

Arith signature(e1 = "mpfr", e2 = "numeric"): ...

Arith signature(e1 = "integer", e2 = "mpfr"): ...

Arith signature(e1 = "numeric", e2 = "mpfr"): ...

Compare signature(e1 = "mpfr", e2 = "mpfr"): ...

Compare signature(e1 = "mpfr", e2 = "integer"): ...

Compare signature(e1 = "mpfr", e2 = "numeric"): ...

Compare signature(e1 = "integer", e2 = "mpfr"): ...

Compare signature(e1 = "numeric", e2 = "mpfr"): ...

Logic signature(e1 = "mpfr", e2 = "mpfr"): ...

Summary signature(x = "mpfr"): The S4 `Summary` group functions, `max`, `min`, `range`, `prod`, `sum`, `any`, and `all` are all defined for MPFR numbers. `mean(x, trim)` for non-0 `trim` works analogously to `mean.default`.

median signature(x = "mpfr"): works via

quantile signature(x = "mpfr"): a simple wrapper of the `quantile.default` method from `stats`.

summary signature(object = "mpfr"): modeled after `summary.default`, ensuring to provide the full "mpfr" range of numbers.

Math signature(x = "mpfr"): All the S4 `Math` group functions are defined, using multiple precision (MPFR) arithmetic, from `getGroupMembers("Math")`, these are (in alphabetical order): `abs`, `sign`, `sqrt`, `ceiling`, `floor`, `trunc`, `cummax`, `cummin`, `cumprod`, `cumsum`, `exp`, `expm1`, `log`, `log10`, `log2`, `log1p`, `cos`, `cosh`, `sin`, `sinh`, `tan`, `tanh`, `acos`, `acosh`, `asin`, `asinh`, `atan`, `atanh`, `cospi`, `sinpi`, `tanpi`, `gamma`, `lgamma`, `digamma`, and `trigamma`.

Currently, `trigamma` is not provided by the MPFR library and hence not yet implemented. Further, the `cum*()` methods are *not yet* implemented.

factorial signature(x = "mpfr"): this will `round` the result when `x` is integer valued. Note however that `factorialMpfr(n)` for integer `n` is slightly more efficient, using the MPFR function 'mpfr_fac_ui'.

Math2 signature(x = "mpfr"): `round(x, digits)` and `signif(x, digits)` methods. Note that these do not change the formal precision ('prec' slot), and you may often want to apply `roundMpfr()` in addition or preference.

as.numeric signature(x = "mpfr"): ...

as.vector signature(x = "mpfrArray"): as for standard `arrays`, this "drops" the `dim` (and `dimnames`), i.e., transforms `x` into an 'MPFR' number vector, i.e., class `mpfr`.

`[[` signature(x = "mpfr", i = "ANY"), and

- [signature(x = "mpfr", i = "ANY", j = "missing", drop = "missing"): subsetting aka “indexing” happens as for numeric vectors.
- format** signature(x = "mpfr"), further arguments digits = NULL, scientific = NA, etc: returns [character](#) vector of same length as x; when digits is NULL, with *enough* digits to recreate x accurately. For details, see [formatMpfr](#).
- is.finite** signature(x = "mpfr"): ...
- is.infinite** signature(x = "mpfr"): ...
- is.na** signature(x = "mpfr"): ...
- is.nan** signature(x = "mpfr"): ...
- log** signature(x = "mpfr"): ...
- show** signature(object = "mpfr"): ...
- sign** signature(x = "mpfr"): ...
- Re, Im** signature(z = "mpfr"): simply return z or 0 (as "mpfr" numbers of correct precision), as mpfr numbers are ‘real’ numbers.
- Arg, Mod, Conj** signature(z = "mpfr"): these are trivial for our ‘real’ mpfr numbers, but defined to work correctly when used in R code that also allows complex number input.
- all.equal** signature(target = "mpfr", current = "mpfr"),
- all.equal** signature(target = "mpfr", current = "ANY"), and
- all.equal** signature(target = "ANY", current = "mpfr"): methods for numerical (approximate) equality, [all.equal](#) of multiple precision numbers. Note that the default tolerance (argument) is taken to correspond to the (smaller of the two) precisions when both main arguments are of class "mpfr", and hence can be considerably less than double precision machine epsilon [.Machine\\$double.eps](#).
- coerce** signature(from = "numeric", to = "mpfr"): [as\(. , "mpfr"\)](#) coercion methods are available for [character](#) strings, [numeric](#), [integer](#), [logical](#), and even [raw](#). Note however, that [mpfr\(. , precBits, base\)](#) is more flexible.
- coerce** signature(from = "mpfr", to = "bigz"): coerces to biginteger, see [bigz](#) in package **gmp**.
- coerce** signature(from = "mpfr", to = "numeric"): ...
- coerce** signature(from = "mpfr", to = "character"): ...
- unique** signature(x = "mpfr"), and corresponding S3 method (such that [unique\(<mpfr>\)](#) works inside **base** functions), see [unique](#).
- Note that [duplicated\(\)](#) works for "mpfr" objects without the need for a specific method.
- t** signature(x = "mpfr"): makes x into an $n \times 1$ [mpfrMatrix](#).
- which.min** signature(x = "mpfr"): gives the index of the first minimum, see [which.min](#).
- which.max** signature(x = "mpfr"): gives the index of the first maximum, see [which.max](#).

Note

Many more methods (“functions”) automagically work for "mpfr" number vectors (and matrices, see the [mpfrMatrix](#) class doc), notably [sort](#), [order](#), [quantile](#), [rank](#).

Author(s)

Martin Maechler

See Also

The `"mpfrMatrix"` class, which extends the `"mpfr"` one.

`roundMpfr` to *change* precision of an `"mpfr"` object which is typically desirable *instead* of or in addition to `signif()` or `round()`; `is.whole()` etc.

Special mathematical functions such as some Bessel ones, e.g., `jn`; further, `zeta(.)` ($= \zeta(.)$), `Ei()` etc. `Bernoulli` numbers and the Pochhammer function `pochMpfr`.

Examples

```
## 30 digit precision
(x <- mpfr(c(2:3, pi), prec = 30 * log2(10)))
str(x) # str() displays *compact*ly => not full precision
x^2
x[1] / x[2] # 0.66666... ~ 30 digits

## indexing - as with numeric vectors
stopifnot(exprs = {
  identical(x[2], x[[2]])
  ## indexing "outside" gives NA (well: "mpfr-NaN" for now):
  is.na(x[5])
  ## whereas "[[" cannot index outside:
  inherits(tryCatch(x[[5]], error=identity), "error")
  ## and only select *one* element:
  inherits(tryCatch(x[[2:3]], error=identity), "error")
})

## factorial() & lfactorial would work automagically via [l]gamma(),
## but factorial() additionally has an "mpfr" method which rounds
f200 <- factorial(mpfr(200, prec = 1500)) # need high prec.!
f200
as.numeric(log2(f200))# 1245.38 -- need precBits >~ 1246 for full precision

##--> see factorialMpfr() for more such computations.

##--- "Underflow" **much** later -- exponents have 30(+1) bits themselves:

mpfr.min.exp2 <- - (2^30 + 1)
two <- mpfr(2, 55)
stopifnot(two ^ mpfr.min.exp2 == 0)
## whereas
two ^ (mpfr.min.exp2 * (1 - 1e-15))
## 2.38256490488795107e-323228497 ["typically"]

##--- "Assert" that {sort}, {order}, {quantile}, {rank}, all work :

p <- mpfr(rpois(32, lambda=500), precBits=128)^10
np <- as.numeric(log(p))
```

```

(sp <- summary(p))# using the print.summaryMpfr() method
stopifnot(all(diff(sort(p)) >= 0),
  identical(order(p), order(np)),
  identical(rank(p), rank(np)),
  all.equal(sapply(1:9, function(Typ) quantile(np, type=Typ, names=FALSE)),
    sapply(lapply(1:9, function(Typ) quantile(p, type=Typ, names=FALSE)),
      function(x) as.numeric(log(x))),
    tol = 1e-3),# quantiles: interpolated in orig. <--> log scale
  TRUE)

m0 <- mpfr(numeric(), 99)
xy <- expand.grid(x = -2:2, y = -2:2) ; x <- xy[,"x"] ; y <- xy[,"y"]
a2. <- atan2(y,x)

stopifnot(identical(which.min(m0), integer(0)),
  identical(which.max(m0), integer(0)),
  all.equal(a2., atan2(as(y,"mpfr"), x)),
  max(m0) == mpfr(-Inf, 53), # (53 is not a feature, but ok)
  min(m0) == mpfr(+Inf, 53),
  sum(m0) == 0, prod(m0) == 1)

## unique(), now even base::factor() "works" on <mpfr> :
set.seed(17)
p <- rlnorm(20) * mpfr(10, 100)^-999
pp <- sample(p, 50, replace=TRUE)
str(unique(pp)) # length 18 .. (from originally 20)
## Class 'mpfr' [package "Rmpfr"] of length 18 and precision 100
## 5.56520587824e-999 4.41636588227e-1000 ..
facp <- factor(pp)
str(facp) # the factor *levels* are a bit verbose :
# Factor w/ 18 levels "new(\"mpfr1\", ....." ...
# At least *some* factor methods work :
stopifnot(exprs = {
  is.factor(facp)
  identical(unnname(table(facp)),
    unnname(table(asNumeric(pp * mpfr(10,100)^1000))))
})

## ((unfortunately, the expressions are wrong; should integer "L"))
#
## More useful: levels with which to *invert* factor() :
## -- this is not quite ok:
## simplified from 'utils' :
deparse1 <- function(x, ...) paste(deparse(x, 500L, ...), collapse = " ")
if(FALSE) {
  str(pp.levs <- vapply(unclass(sort(unique(pp))), deparse1, ""))
  facp2 <- factor(pp, levels = pp.levs)
}

```

Description

For some R standard (probability) density, distribution or quantile functions, we provide MPFR versions.

Usage

```
dpois(x, lambda, log = FALSE, useLog = )
dbinom(x, size, prob, log = FALSE, useLog = )
dnbinom(x, size, prob, mu, log = FALSE, useLog = any(x > 1e6))
dnorm(x, mean = 0, sd = 1, log = FALSE)
dgamma(x, shape, rate = 1, scale = 1/rate, log = FALSE)
dt(x, df, ncp, log = FALSE)

pnorm(q, mean = 0, sd = 1, lower.tail = TRUE, log.p = FALSE)
```

Arguments

`x`, `q`, `lambda`, `size`, `prob`, `mu`, `mean`, `sd`, `shape`, `rate`, `scale`, `df`, `ncp`
 numeric or mpfr vectors. All of these are “recycled” to the length of the longest one. For their meaning/definition, see the corresponding standard R (**stats** package) function.

`log`, `log.p`, `lower.tail`
 logical, see `pnorm`, `dpois`, etc.

`useLog`
 logical with default depending on `x` etc, indicating if log-scale computation should be used even when `log = FALSE`, for performance or against overflow / underflow.

Details

`pnorm()` is based on `erf()` and `erfc()` which have direct MPFR counter parts and are both reparametrizations of `pnorm`, $\text{erf}(x) = 2 * \text{pnorm}(\sqrt{2} * x)$ and $\text{erfc}(x) = 2 * \text{pnorm}(\sqrt{2} * x, \text{lower} = \text{FALSE})$.

Value

A vector of the same length as the longest of `x`, `q`, `...`, of class `mpfr` with the high accuracy results of the corresponding standard R function.

Note

E.g., for `pnorm(*, log.p = TRUE)` to be useful, i.e., not to underflow or overflow, you may want to extend the exponential range of MPFR numbers, using `.mpfr_erange_set()`, see the examples.

See Also

`pnorm`, `dt`, `dbinom`, `dnbinom`, `dgamma`, `dpois` in standard package **stats**.
`pbetaI(x, a, b)` is a `mpfr` version of `pbeta` only for *integer* `a` and `b`.

Examples

```

x <- 1400+ 0:10
print(dpois(x, 1000), digits =18) ## standard R's double precision
(px <- dpois(mpfr(x, 120), 1000))## more accuracy for the same
px. <- dpois(mpfr(x, 120), 1000, useLog=TRUE)# {failed in 0.8-8}
stopifnot(all.equal(px, px., tol = 1e-31))
dpois(0:5, mpfr(10000, 80)) ## very small exponents (underflowing in dbl.prec.)

print(dbinom(0:8, 8, pr = 4 / 5), digits=18)
      dbinom(0:8, 8, pr = 4/mpfr(5, 99)) -> dB; dB

print(dnorm(      -5:5), digits=18)
      dnorm(mpfr(-5:5, prec=99))

## For pnorm() in the extreme tails, need an exponent range
## larger than the (MPFR and Rmpfr) default:
(old_eranges <- .mpfr_erange()) # typically +/- 2^30:
log2(abs(old_eranges)) # 30 30
.mpfr_erange_set(value = (1-2^-52)*.mpfr_erange(c("min.emin", "max.emax")))
log2(abs(.mpfr_erange()))# 62 62 *if* setup -- 2023-01: *not* on Winbuilder, nor
## other Windows where long is 4 bytes (32 bit) and the erange typically cannot be extended.
tens <- mpfr(10^(4:7), 128)
pnorm(tens, lower.tail=FALSE, log.p=TRUE) # "works" (iff ...)
## "the" boundary:
pnorm(mpfr(- 38581.371, 128), log.p=TRUE) # still does not underflow {but *.372 does}
## -744261105.599283824811986753129188937418 (iff ...)
.mpfr_erange()*log(2) # the boundary
##      Emin      Emax
## -3.196577e+18  3.196577e+18 (iff ...)

## reset to previous
.mpfr_erange_set( , old_eranges)
pnorm(tens, lower.tail=FALSE, log.p=TRUE) # all but first underflow to -Inf

```

mpfr-special-functions

Special Mathematical Functions (MPFR)

Description

Special Mathematical Functions, supported by the MPFR Library.

Note that additionally, all the [Math](#) and [Math2](#) group member functions are “mpfr-ified”, too; ditto, for many more standard R functions. See see the methods listed in [mpfr](#) (aka `?`mpfr-class``).

Usage

```

zeta(x)
Ei(x)
Li2(x)

```

erf(x)
erfc(x)

Arguments

x a numeric or mpfr vector.

Details

zeta(x) computes Riemann's Zeta function $\zeta(x)$ important in analytical number theory and related fields. The traditional definition is

$$\zeta(x) = \sum_{n=1}^{\infty} \frac{1}{n^x}.$$

Ei(x) computes the exponential integral,

$$\int_{-\infty}^x \frac{e^t}{t} dt.$$

Li2(x) computes the dilogarithm,

$$\int_0^x \frac{-\log(1-t)}{t} dt.$$

erf(x) and erfc(x) are the error, respectively complementary error function which are both reparametrizations of `pnorm`, $\text{erf}(x) = 2 \cdot \text{pnorm}(\sqrt{2} \cdot x)$ and $\text{erfc}(x) = 2 \cdot \text{pnorm}(\sqrt{2} \cdot x, \text{lower}=\text{FALSE})$, and hence **Rmpfr** provides its own version of `pnorm`.

Value

A vector of the same length as x, of class `mpfr`.

See Also

`pnorm` in standard package **stats**; the class description `mpfr` mentioning the generic arithmetic and mathematical functions (`sin`, `log`, ..., etc) for which "mpfr" methods are available.

Note the (integer order, non modified) Bessel functions $j_0()$, $y_n()$, etc, named `j0`, `yn` etc, and Airy function $Ai()$ in `Bessel_mpfr`.

Examples

```
curve(Ei, 0, 5, n=2001)

## As we now require (mpfrVersion() >= "2.4.0"):
curve(Li2, 0, 5, n=2001)
curve(Li2, -2, 13, n=2000); abline(h=0,v=0, lty=3)
curve(Li2, -200,400, n=2000); abline(h=0,v=0, lty=3)

curve(erf, -3,3, col = "red", ylim = c(-1,2))
```

```

curve(erfc, add = TRUE, col = "blue")
abline(h=0, v=0, lty=3)
legend(-3,1, c("erf(x)", "erfc(x)"), col = c("red","blue"), lty=1)

```

mpfr-utils

Rmpfr – Utilities for Precision Setting, Printing, etc

Description

This page documents utilities from package **Rmpfr** which are typically not called by the user, but may come handy in some situations.

Notably, the (base-2) maximal (and minimal) precision and the “erange”, the range of possible (base-2) exponents of `mpfr`-numbers can be queried and partly extended.

Usage

```

getPrec(x, base = 10, doNumeric = TRUE, is.mpfr = NA, bigq. = 128L)
.getPrec(x)
getD(x)
mpfr_default_prec(prec)
## S3 method for class 'mpfrArray'
print(x, digits = NULL, drop0trailing = FALSE,
      right = TRUE,
      max.digits = getOption("Rmpfr.print.max.digits", 999L),
      exponent.plus = getOption("Rmpfr.print.exponent.plus", TRUE),
      ...)
## S3 method for class 'mpfr'
print(x, digits = NULL, drop0trailing = TRUE,
      right = TRUE,
      max.digits = getOption("Rmpfr.print.max.digits", 999L),
      exponent.plus = getOption("Rmpfr.print.exponent.plus", TRUE),
      ...)
toNum(from, rnd.mode = c('N','D','U','Z','A'))
.mpfr2d(from)
.mpfr2i(from)

mpfr2array(x, dim, dimnames = NULL, check = FALSE)

.mpfr2list(x, names = FALSE)

mpfrXport(x, names = FALSE)
mpfrImport(mxp)

.mpfr_formatinfo(x)
.mpfr2exp(x)

.mpfr_erange(kind = c("Emin", "Emax"), names = TRUE)

```

```

.mpfr_erange_set(kind = c("Emin", "Emax"), value)
.mpfr_erange_kinds
.mpfr_erange_is_int()
.mpfr_maxPrec()
.mpfr_minPrec()

.mpfr_gmp_numbbits()
.mpfrVersion()

## Really Internal and low level, no error checking (for when you know ..)
.mpfr(x, precBits)
.mpfr(x, precBits, rnd.mode)
.getSign(x)

.mpfr_negative(x)
.mpfr_sign(x)

..bigq2mpfr(x, precB = NULL, rnd.mode = c("N", "D", "U", "Z", "A"))
..bigz2mpfr(x, precB = NULL, rnd.mode = c("N", "D", "U", "Z", "A"))

```

Arguments

x, from	typically, an R object of class "mpfr", or "mpfrArray", respectively. For getPrec(), any number-like R object, or NULL.
base	(only when x is <code>character</code>) the base with respect to which x[i] represent numbers; base b must fulfill $2 \leq b \leq 62$.
doNumeric	logical indicating <code>integer</code> or <code>double</code> typed x should be accepted and a default precision be returned. Should typically be kept at default TRUE.
is.mpfr	logical indicating if <code>class(x)</code> is already known to be "mpfr"; typically should be kept at default, NA.
bigq.	for getPrec(), the precision to use for a big rational (class "bigq"); if not specified gives warning when used.
prec, precB, precBits	a positive integer, or missing.
drop0trailing	logical indicating if trailing "0"s should be omitted.
right	logical indicating print()ing should right justify the strings; see <code>print.default()</code> to which it is passed.
digits, ...	further arguments to print methods.
max.digits	a number (possibly Inf) to limit the number of (mantissa) digits to be printed, simply passed to <code>formatMpfr()</code> . The default is finite to protect from printing very long strings which is often undesirable, notably in <code>interactive</code> use.
exponent.plus	logical, simply passed to <code>formatMpfr()</code> . Was FALSE hardwired in Rmpfr versions before 0.8-0, and hence is allowed to be tweaked by an <code>options()</code> setting.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see details of <code>mpfr</code> .

dim, dimnames	for "mpfrArray" construction.
check	logical indicating if the mpfrArray construction should happen with internal safety check. Previously, the implicit default used to be true.
names	(for .mpfr2list()) logical or character vector, indicating if the list returned should have names . If character, it specifies the names; if true, the names are set to format(x).
mxp	an "mpfrXport" object, as resulting from mpfrXport().
kind	a character string or vector, specifying the kind of "erange" value; must be an element of .mpfr_erange_kinds, i.e., one of "Emin", "Emax", "min.emin", "max.emin", "min.emax", "max.emax".
value	numeric , for .mpfr_erange_set() one number per kind. Must be in range specified by the *. "emin" and *. "emax" erange values.

Details

The print method is currently built on the **format** method for class **mpfr**. This, currently does *not* format columns jointly which leads to suboptimally looking output. There are plans to change this.

Note that **formatMpfr()** which is called by **print()** (or **show()** or R's implicit printing) uses `max.digits = Inf`, differing from our **print()**'s default on purpose. If you do want to see the full accuracy even in cases it is large, use **options(Rmpfr.print.max.digits = Inf)** or `(. = 1e7)`, say.

The `.mpfr_erange*` functions (and variable) allow to query and set the allowed range of values for the base-2 *exponents* of "mpfr" numbers. See the examples below and GNU MPFR library documentation on the C functions `mpfr_get_emin()`, `mpfr_set_emin(.)`, `mpfr_get_emin_min()`, and `mpfr_get_emin_max()`, (and those four with `'_emin'` replaced by `'_emax'` above).

Value

getPrec(x) returns a **integer** vector of length one or the same length as `x` when that is positive, whereas **getPrec(NULL)** returns `mpfr_default_prec()`, see below. If you need to *change* the precision of `x`, i.e., need something like "setPrec", use **roundMpfr()**.

`.getPrec(x)` is a simplified version of **getPrec()** which only works for "mpfr" objects `x`.

getD(x) is intended to be a fast version of `x@.Data`, and should not be used outside of lower level functions.

`mpfr_default_prec()` returns the current MPFR default precision, an **integer**. This is currently not made use of much in package **Rmpfr**, where functions have their own default precision where needed, and otherwise we'd rather not be dependent of such a *global* setting.

`mpfr_default_prec(prec)` *sets* the current MPFR default precision and returns the previous one; see above.

`.mpfr_maxPrec()` and (less interestingly) `.mpfr_minPrec()` give the maximal and minimal base-2 precision allowed in the current version of the MPFR library linked to by R package **Rmpfr**. The maximal precision is typically 2^{63} , i.e.,

```
all.equal(.mpfr_maxPrec(), 2^63)
```

is typically true.

toNum(m) returns a numeric `array` or `matrix`, when m is of class "mpfrArray" or "mpfrMatrix", respectively. It should be equivalent to as(m, "array") or ... "matrix". Note that the slightly more general `asNumeric()` is preferred now. `.mpfr2d()` is similar to but simpler than `toNum()`, whereas `.mpfr2i()` is an analogue low level utility for `as.integer(<mpfr>)`.

`mpfr2array()` a slightly more flexible alternative to `dim(.) <- dd`.

`.mpfr2exp(x)` returns the base-2 (integer valued) exponents of x, i.e., it is the R interface to MPFR C's `mpfr_get_exp()`. The result is `integer` iff `.mpfr_erange_is_int()` is true, otherwise `double`. Note that the MPFR (4.0.1) manual says about `mpfr_get_exp()`: *The behavior for NaN, infinity or zero is undefined.*

`.mpfr_erange_is_int()` returns TRUE iff the `.mpfr_erange(c("Emin", "Emax"))` range lies inside the range of R's `integer` limits, i.e., has absolute values not larger than `.Machine$integer.max` ($= 2^{31} - 1$).

`.mpfr_erange_set()` *invisibly* (see `invisible()`) returns TRUE iff the change was successful.

`.mpfr_gmp_numbbits()` returns the 'GMP' library "numb" size, which is either 32 or 64 bit (as `integer`, i.e., 64L or 32L). If it is *not* 64, you typically cannot enlarge the exponential range of mpfr numbers via `.mpfr_erange()`, see above.

`.mpfrVersion()` returns a string, the version of the 'MPFR' library we are linking to.

`.mpfr_formatinfo(x)` returns conceptually a subset of `.mpfr2str()`'s result, a list with three components

exp the base-2 exponents of x, identical to `.mpfr2exp(x)`.

finite `logical` identical to `is.finite(x)`.

is.0 `logical` indicating if the corresponding `x[i]` is zero; identical to `mpfrIs0(x)`.

(Note that `.mpfr2str(x, ..., base)$exp` is wrt base *and* is not undefined but ...)

`.mpfr_sign(x)` only works for mpfr objects, then identical to `sign(x)`. Analogously, `.mpfr_negative(x)` is `-x` in that case. `.getSign(x)` is a low-level version of `sign(x)` returning -1 or +1, but not 0.

Finally, `..bigq2mpfr(x, ..)` and `..bigz2mpfr(x, ..)` are fast ways to coerce bigz and bigq number objects (created by package `gmp`'s functionality) to our "mpfr" class.

Note

`mpfrXport()` and `mpfrImport()` are **experimental** and used to explore reported platform incompatibilities of `save()`d and `load()`ed "mpfr" objects between Windows and non-Windows platforms.

In other words, the format of the result of `mpfrXport()` and hence the `mxf` argument to `mpfrImport()` are considered internal, not part of the API and subject to change.

See Also

Start using `mpfr(...)`, and compute with these numbers.

`mpfrArray(x)` is for numeric ("non-mpfr") x, whereas `mpfr2array(x)` is for "mpfr" classed x, only.

Examples

```

getPrec(as(c(1,pi), "mpfr")) # 128 for both

(opr <- mpfr_default_prec()) ## typically 53, the MPFR system default
stopifnot(opr == (oprec <- mpfr_default_prec(70)),
          70 == mpfr_default_prec())
## and reset it:
mpfr_default_prec(opr)

## Explore behavior of rounding modes 'rnd.mode':
x <- mpfr(10,99)^512 # too large for regular (double prec. / numeric):
sapply(c("N", "D", "U", "Z", "A"), function(RM)
       sapply(list(-x,x), function(.) toNum(., RM)))
##      N          D          U          Z          A
## -Inf          -Inf -1.797693e+308 -1.797693e+308 -Inf
##  Inf 1.797693e+308          Inf 1.797693e+308  Inf

## Printing of "MPFR" matrices is less nice than R's usual matrix printing:
m <- outer(c(1, 3.14, -1024.5678), c(1, 1e-3, 10,100))
m[3,3] <- round(m[3,3])
m
mpfr(m, 50)

B6 <- mpfr2array(Bernoulli(1:6, 60), c(2,3),
                 dimnames = list(LETTERS[1:2], letters[1:3]))
B6

## Ranges of (base 2) exponents of MPFR numbers:
.mpfr_erange() # the currently active range of possible base 2 exponents:

## A factory fresh setting fulfills
.mpfr_erange(c("Emin","Emax")) == c(-1,1) * (2^30 - 1)

## There are more 'kind's, the latter 4 showing how you could change the first two :
.mpfr_erange_kinds
.mpfr_erange(.mpfr_erange_kinds)
eLimits <- .mpfr_erange(c("min.emin", "max.emin", "min.emax", "max.emax"))
## Typically true in MPFR versions *iff* long is 64-bit, i.e. *not* on Windows
if(.Machine$sizeof.long == 8L) {
  eLimits == c(-1,1, -1,1) * (2^62 - 1)
} else if(.Machine$sizeof.long == 4L) # on Windows
  eLimits == c(-1,1, -1,1) * (2^30 - 1)

## Looking at internal representation [for power users only!]:

i8 <- mpfr(-2:5, 32)
x4 <- mpfr(c(NA, NaN, -Inf, Inf), 32)
stopifnot(exprs = {
  identical(x4[1], x4[2])
  is.na(x4[1]) == x4[2] # <- was *wrong* in Rmpfr <= 0.9-4
  is.na(x4[1]) != x4[2] # (ditto)
})

```

```

    identical(x4 < i8[1:4], c(NA,NA, TRUE,FALSE))
    !is.finite(x4)
    identical(is.infinite(x4), c(FALSE,FALSE, TRUE,TRUE))
  })
## The output of the following depends on the GMP "numb" size
## (32 bit vs. 64 bit), *and* additionally
## on sizeof.long (mostly non-Windows <-> Windows, see above):
str( .mpfr2list(i8) )
str( .mpfr2list(x4, names = TRUE) )

str(xp4 <- mpfrXport(x4, names = TRUE))
stopifnot(identical(x4, mpfrImport(mpfrXport(x4))),
           identical(i8, mpfrImport(mpfrXport(i8))))
## FIXME, need c(.), as dim(.) "get lost":
stopifnot(identical(c(B6), mpfrImport(mpfrXport(B6))))

```

mpfr.utils

MPFR Number Utilities

Description

`mpfrVersion()` returns the version of the MPFR library which **Rmpfr** is currently linked to.

`c(x,y,...)` can be used to combine MPFR numbers in the same way as regular numbers **IFF** the first argument `x` is of class `mpfr`.

`mpfrIs0(.)` uses the MPFR library in the documented way to check if (a vector of) MPFR numbers are zero. It was called `mpfr.is.0` which is strongly deprecated now.

`.mpfr.is.whole(x)` uses the MPFR library in the documented way to check if (a vector of) MPFR numbers is integer *valued*. This is equivalent to `x == round(x)`, but *not* at all to `is.integer(as(x, "numeric"))`.

You should typically rather use (the "mpfr" method of the generic function) `is.whole(x)` instead. The former name `mpfr.is.integer` is deprecated now.

Usage

```

mpfrVersion()
mpfrIs0(x)
## S3 method for class 'mpfr'
c(...)
## S3 method for class 'mpfr'
diff(x, lag = 1L, differences = 1L, ...)

```

Arguments

`x` an object of class `mpfr`.

`...` for `diff`, further `mpfr` class objects or simple numbers (`numeric` vectors) which are coerced to `mpfr` with default precision of 128 bits.

`lag, differences` for `diff()`: exact same meaning as in `diff()`'s default method, `diff.default`.

Value

`mpfrIs0` returns a logical vector of length `length(x)` with values `TRUE` iff the corresponding `x[i]` is an MPFR representation of zero (0).

Similarly, `.mpfr.is.whole` and `is.whole` return a logical vector of length `length(x)`.

`mpfrVersion` returns an object of S3 class `"numeric_version"`, so it can be used in comparisons.

The other functions return MPFR number (vectors), i.e., extending class `mpfr`.

See Also

[str.mpfr](#) for the `str` method. [erf](#) for special mathematical functions on MPFR.

The class description [mpfr](#) page mentions many generic arithmetic and mathematical functions for which "mpfr" methods are available.

Examples

```
mpfrVersion()

(x <- c(Const("pi", 64), mpfr(-2:2, 64)))
mpfrIs0(x) # one of them is
x[mpfrIs0(x)] # but it may not have been obvious..
str(x)

x <- rep(-2:2, 5)
stopifnot(is.whole(mpfr(2, 500) ^ (1:200)),
          all.equal(diff(x), diff(as.numeric(x))))
```

<code>mpfrArray</code>	<i>Construct "mpfrArray" almost as by 'array()'</i>
------------------------	---

Description

Utility to construct an R object of class `mpfrArray`, very analogously to the numeric `array` function.

Usage

```
mpfrArray(x, precBits, dim = length(x), dimnames = NULL,
          rnd.mode = c("N", "D", "U", "Z", "A"))
```

Arguments

<code>x</code>	numeric(like) vector, typically of length <code>prod(dim)</code> or shorter in which case it is recycled.
<code>precBits</code>	a number, the maximal precision to be used, in <i>bits</i> ; i.e., 53 corresponds to double precision. Must be at least 2.
<code>dim</code>	the dimension of the array to be created, that is a vector of length one or more giving the maximal indices in each dimension.

dimnames	either NULL or the names for the dimensions. This is a list with one component for each dimension, either NULL or a character vector of the length given by dim for that dimension.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see details of <code>mpfr</code> .

Value

an object of class "`mpfrArray`", specifically "`mpfrMatrix`" when `length(dim) == 2`.

See Also

`mpfr`, `array`; `asNumeric()` as “inverse” of `mpfrArray()`, to get back a numeric array.

`mpfr2array(x)` is for “mpfr” classed `x`, only, whereas `mpfrArray(x)` is for numeric (“non-mpfr”) `x`.

Examples

```
## preallocating is possible here too
ma <- mpfrArray(NA, prec = 80, dim = 2:4)
validObject(A2 <- mpfrArray(1:24, prec = 64, dim = 2:4))

## recycles, gives an "mpfrMatrix" and dimnames :
mat <- mpfrArray(1:5, 64, dim = c(5,3), dimnames=list(NULL, letters[1:3]))
mat
asNumeric(mat)
stopifnot(identical(asNumeric(mat),
                    matrix(1:5 +0, 5,3, dimnames=dimnames(mat))))

## Testing the apply() method :
apply(mat, 2, range)
apply(A2, 1:2, range)
apply(A2, 2:3, max)
(fA2 <- apply(A2, 2, fivenum))
a2 <- as(A2, "array")
stopifnot(as(apply(A2, 2, range), "matrix") ==
          apply(a2, 2, range)
          , all.equal(fA2, apply(a2, 2, fivenum))
          , all.equal(apply(A2, 2, quantile),
                      apply(a2, 2, quantile))
          , all.equal(A2, apply(A2, 2:3, identity) -> aA2, check.attributes=FALSE)
          , dim(A2) == dim(aA2)
          )
)
```

mpfrMatrix

Classes "mpfrMatrix" and "mpfrArray"

Description

The classes "mpfrMatrix" and "mpfrArray" are, analogously to the **base** `matrix` and `array` functions and classes simply "numbers" of class `mpfr` with an additional `Dim` and `Dimnames` slot.

Objects from the Class

Objects should typically be created by `mpfrArray()`, but can also be created by `new("mpfrMatrix", ...)` or `new("mpfrArray", ...)`, or also by `t(x)`, `dim(x) <- dd`, or `mpfr2array(x, dim=dd)` where `x` is a an `mpfr` "number vector".

A (slightly more flexible) alternative to `dim(x) <- dd` is `mpfr2array(x, dd, dimnames)`.

Slots

.Data: as for the `mpfr` class, a "list" of `mpfr1` numbers.

Dim: of class "integer", specifying the array dimension.

Dimnames: of class "list" and the same length as `Dim`, each list component either `NULL` or a `character` vector of length `Dim[j]`.

Extends

Class "mpfrMatrix" extends "mpfrArray", directly.

Class "mpfrArray" extends class "`mpfr`", by class "mpfrArray", distance 2; class "`list`", by class "mpfrArray", distance 3; class "`vector`", by class "mpfrArray", distance 4.

Methods

Arith signature(e1 = "mpfr", e2 = "mpfrArray"): ...

Arith signature(e1 = "numeric", e2 = "mpfrArray"): ...

Arith signature(e1 = "mpfrArray", e2 = "mpfrArray"): ...

Arith signature(e1 = "mpfrArray", e2 = "mpfr"): ...

Arith signature(e1 = "mpfrArray", e2 = "numeric"): ...

as.vector signature(x = "mpfrArray", mode = "missing"): drops the dimension 'attribute', i.e., transforms `x` into a simple `mpfr` vector. This is an inverse of `t(.)` or `dim(.) <- *` on such a vector.

atan2 signature(y = "ANY", x = "mpfrArray"): ...

atan2 signature(y = "mpfrArray", x = "mpfrArray"): ...

atan2 signature(y = "mpfrArray", x = "ANY"): ...

[<- signature(x = "mpfrArray", i = "ANY", j = "ANY", value = "ANY"): ...

[signature(x = "mpfrArray", i = "ANY", j = "ANY", drop = "ANY"): ...

[signature(x = "mpfrArray", i = "ANY", j = "missing", drop = "missing"): "mpfrArray"s can be subset ("indexed") as regular R arrays.

%% signature(x = "mpfr", y = "mpfrMatrix"): Compute the matrix/vector product xy when the dimensions (`dim`) of x and y match. If x is not a matrix, it is treated as a 1-row or 1-column matrix (aka "row vector" or "column vector") depending on which one makes sense, see the documentation of the `base` function `%*%`.

%% signature(x = "mpfr", y = "Mnumber"): method definition for cases with one `mpfr` and any "number-like" argument are to use MPFR arithmetic as well.

%% signature(x = "mpfrMatrix", y = "mpfrMatrix"),

%% signature(x = "mpfrMatrix", y = "mpfr"), etc. Further method definitions with identical semantic.

crossprod signature(x = "mpfr", y = "missing"): Computes $x'x$, i.e., `t(x) %*% x`, typically more efficiently.

crossprod signature(x = "mpfr", y = "mpfrMatrix"): Computes $x'y$, i.e., `t(x) %*% y`, typically more efficiently.

crossprod signature(x = "mpfrMatrix", y = "mpfrMatrix"): ...

crossprod signature(x = "mpfrMatrix", y = "mpfr"): ...

tcrossprod signature(x = "mpfr", y = "missing"): Computes xx' , i.e., `x %*% t(x)`, typically more efficiently.

tcrossprod signature(x = "mpfrMatrix", y = "mpfrMatrix"): Computes xy' , i.e., `x %*% t(y)`, typically more efficiently.

tcrossprod signature(x = "mpfrMatrix", y = "mpfr"): ...

tcrossprod signature(x = "mpfr", y = "mpfrMatrix"): ...

coerce signature(from = "mpfrArray", to = "array"): coerces from to a *numeric* array of the same dimension.

coerce signature(from = "mpfrArray", to = "vector"): as for standard arrays, this "drops" the `dim` (and `dimnames`), i.e., returns an `mpfr` vector.

Compare signature(e1 = "mpfr", e2 = "mpfrArray"): ...

Compare signature(e1 = "numeric", e2 = "mpfrArray"): ...

Compare signature(e1 = "mpfrArray", e2 = "mpfr"): ...

Compare signature(e1 = "mpfrArray", e2 = "numeric"): ...

dim signature(x = "mpfrArray"): ...

dimnames<- signature(x = "mpfrArray"): ...

dimnames signature(x = "mpfrArray"): ...

show signature(object = "mpfrArray"): ...

sign signature(x = "mpfrArray"): ...

norm signature(x = "mpfrMatrix", type = "character"): computes the matrix norm of x , see `norm` or the one in package `Matrix`.

t signature(x = "mpfrMatrix"): transpose the `mpfrMatrix`.

aperm signature(a = "mpfrArray"): `aperm(a, perm)` is a generalization of `t(.)` to *permute* the dimensions of an `mpfrArray`; it has the same semantics as the standard `aperm()` method for simple R arrays.

Author(s)

Martin Maechler

See Also[mpfrArray](#), also for more examples.**Examples**

```

showClass("mpfrMatrix")

validObject(mm <- new("mpfrMatrix"))
validObject(aa <- new("mpfrArray"))

v6 <- mpfr(1:6, 128)
m6 <- new("mpfrMatrix", v6, Dim = c(2L, 3L))
validObject(m6)
m6
which(m6 == 3, arr.ind = TRUE) # |--> (1, 2)
## Coercion back to "vector": Both of these work:
stopifnot(identical(as(m6, "mpfr"), v6),
  identical(as.vector(m6), v6)) # < but this is a "coincidence"

S2 <- m6[,-3] # 2 x 2
S3 <- rbind(m6, c(1:2,10)) ; s3 <- asNumeric(S3)
det(S2)
str(determinant(S2))
det(S3)
stopifnot(all.equal(det(S2), det(asNumeric(S2))), tol=1e-15),
  all.equal(det(S3), det(s3), tol=1e-15))

## 2-column matrix indexing and replacement:
(sS <- S3[i2 <- cbind(1:2, 2:3)])
stopifnot(identical(asNumeric(sS), s3[i2]))
C3 <- S3; c3 <- s3
C3[i2] <- 10:11
c3[i2] <- 10:11
stopifnot(identical(asNumeric(C3), c3))

AA <- new("mpfrArray", as.vector(cbind(S3, -S3)), Dim=c(3L,3:2))
stopifnot(identical(AA[,1] , S3), identical(AA[,2] , -S3))
aa <- asNumeric(AA)

i3 <- cbind(3:1, 1:3, c(2L, 1:2))
ii3 <- Rmpfr:::mat2ind(i3, dim(AA), dimnames(AA))
stopifnot(aa[i3] == new("mpfr", getD(AA)[ii3]))
stopifnot(identical(aa[i3], asNumeric(AA[i3])))
CA <- AA; ca <- aa
ca[i3] <- ca[i3] ^ 3
CA[i3] <- CA[i3] ^ 3

## scale():

```

```

S2. <- scale(S2)
stopifnot(all.equal(abs(as.vector(S2.)), rep(sqrt(1/mpfr(2, 128)), 4),
  tol = 1e-30))

## norm() :
norm(S2)
stopifnot(identical(norm(S2), norm(S2, "1")),
  norm(S2, "I") == 6,
  norm(S2, "M") == 4,
  abs(norm(S2, "F") - 5.477225575051661) < 1e-15)

```

mpfrMatrix-utils

Functions for mpfrMatrix Objects

Description

`determinant(x, ...)` computes the determinant of the mpfr square matrix `x`. May work via coercion to "numeric", i.e., compute `determinant(asNumeric(x), logarithm)`, if `asNumeric` is true, by default, if the dimension is larger than three. Otherwise, use precision `precBits` for the "accumulator" of the result, and use the recursive mathematical definition of the determinant (with computational complexity $n!$, where n is the matrix dimension, i.e., **very** inefficient for all but small matrices!)

Usage

```

## S3 method for class 'mpfrMatrix'
determinant(x, logarithm = TRUE,
  asNumeric = (d[1] > 3), precBits = max(.getPrec(x)), ...)

```

Arguments

<code>x</code>	an <code>mpfrMatrix</code> object of <i>square</i> dimension.
<code>logarithm</code>	logical indicating if the <code>log</code> of the absolute determinant should be returned.
<code>asNumeric</code>	logical ... if rather <code>determinant(asNumeric(x), ...)</code> should be computed.
<code>precBits</code>	the number of binary digits for the result (and the intermediate accumulations).
<code>...</code>	unused (potentially further arguments passed to methods).

Value

as `determinant()`, an object of S3 class "det", a `list` with components

<code>modulus</code>	the (logarithm of) the absolute value (<code>abs</code>) of the determinant of <code>x</code> .
<code>sign</code>	the sign of the determinant.

Author(s)

Martin Maechler

See Also

[determinant](#) in base R, which relies on a fast LU decomposition. [mpfrMatrix](#)

Examples

```
m6 <- mpfrArray(1:6, prec=128, dim = c(2L, 3L))
m6
S2 <- m6[,-3] # 2 x 2
S3 <- rbind(m6, c(1:2,10))
det(S2)
str(determinant(S2))
det(S3)
stopifnot(all.equal(det(S2), det(asNumeric(S2)), tolerance=1e-15),
          all.equal(det(S3), det(asNumeric(S3)), tolerance=1e-15))
```

optimizeR

*High Precision One-Dimensional Optimization***Description**

optimizeR searches the interval from lower to upper for a minimum of the function f with respect to its first argument.

Usage

```
optimizeR(f, lower, upper, ..., tol = 1e-20,
          method = c("Brent", "GoldenRatio"),
          maximum = FALSE,
          precFactor = 2.0, precBits = -log2(tol) * precFactor,
          maxiter = 1000, trace = FALSE)
```

Arguments

f	the function to be optimized. $f(x)$ must work “in Rmpfr arithmetic” for optimizer() to make sense. The function is either minimized or maximized over its first argument depending on the value of maximum.
...	additional named or unnamed arguments to be passed to f.
lower	the lower end point of the interval to be searched.
upper	the upper end point of the interval to be searched.
tol	the desired accuracy, typically higher than double precision, i.e., $tol < 2e-16$.
method	character string specifying the optimization method.
maximum	logical indicating if $f()$ should be maximized or minimized (the default).
precFactor	only for default precBits construction: a factor to multiply with the number of bits directly needed for tol.
precBits	number of bits to be used for mpfr numbers used internally.

maxiter	maximal number of iterations to be used.
trace	integer or logical indicating if and how iterations should be monitored; if an integer k , print every k -th iteration.

Details

"Brent": Brent(1973)'s simple and robust algorithm is a hybrid, using a combination of the golden ratio and local quadratic ("parabolic") interpolation. This is the same algorithm as standard R's `optimize()`, adapted to high precision numbers.

In smooth cases, the convergence is considerably faster than the golden section or Fibonacci ratio algorithms.

"GoldenRatio": The golden ratio method, aka 'golden-section search' works as follows: from a given interval containing the solution, it constructs the next point in the golden ratio between the interval boundaries.

Value

A `list` with components `minimum` (or `maximum`) and `objective` which give the location of the minimum (or maximum) and the value of the function at that point; `iter` specifying the number of iterations, the logical `convergence` indicating if the iterations converged and `estim.prec` which is an estimate or an upper bound of the final precision (in x). `method` the string of the method used.

Author(s)

"GoldenRatio" is based on Hans Werner Borchers' `golden_ratio` (package `pracma`); modifications and "Brent" by Martin Maechler.

See Also

R's standard `optimize`; for multivariate optimization, `Rmpfr`'s `hjkMpfr()`; for root finding, `Rmpfr`'s `unirootR`.

Examples

```
## The minimum of the Gamma (and lgamma) function (for x > 0):
Gmin <- optimizeR(gamma, .1, 3, tol = 1e-50)
str(Gmin, digits = 8)
## high precision chosen for "objective"; minimum has "estim.prec" = 1.79e-50
Gmin[c("minimum", "objective")]
## it is however more accurate to 59 digits:
asNumeric(optimizeR(gamma, 1, 2, tol = 1e-100)$minimum - Gmin$minimum)
```

```
iG5 <- function(x) -exp(-(x-5)^2/2)
curve(iG5, 0, 10, 200)
o.dp <- optimize(iG5, c(0, 10)) #-> 5 of course
oM.gs <- optimizeR(iG5, 0, 10, method="Golden")
oM.Br <- optimizeR(iG5, 0, 10, method="Brent", trace=TRUE)
oM.gs$min ; oM.gs$iter
oM.Br$min ; oM.Br$iter
```

```

(doExtras <- Rmpfr::doExtras())
if(doExtras) {## more accuracy {takes a few seconds}
  oM.gs <- optimizeR(iG5, 0, 10, method="Golden", tol = 1e-70)
  oM.Br <- optimizeR(iG5, 0, 10, tol = 1e-70)
}
rbind(Golden = c(err = as.numeric(oM.gs$min -5), iter = oM.gs$iter),
      Brent = c(err = as.numeric(oM.Br$min -5), iter = oM.Br$iter))

## ==> Brent is orders of magnitude more efficient !

## Testing on the sine curve with 40 correct digits:
sol <- optimizeR(sin, 2, 6, tol = 1e-40)
str(sol)
sol <- optimizeR(sin, 2, 6, tol = 1e-50,
                 precFactor = 3.0, trace = TRUE)
pi.. <- 2*sol$min/3
print(pi.., digits=51)
stopifnot(all.equal(pi.., Const("pi", 256), tolerance = 10*1e-50))

if(doExtras) { # considerably more expensive

## a harder one:
f.sq <- function(x) sin(x-2)^4 + sqrt(pmax(0,(x-1)*(x-4)))*(x-2)^2
curve(f.sq, 0, 4.5, n=1000)
msq <- optimizeR(f.sq, 0, 5, tol = 1e-50, trace=5)
str(msq) # ok
stopifnot(abs(msq$minimum - 2) < 1e-49)

## find the other local minimum: -- non-smooth ==> Golden ratio -section is used
msq2 <- optimizeR(f.sq, 3.5, 5, tol = 1e-50, trace=10)
stopifnot(abs(msq2$minimum - 4) < 1e-49)

## and a local maximum:
msq3 <- optimizeR(f.sq, 3, 4, maximum=TRUE, trace=2)
stopifnot(abs(msq3$maximum - 3.57) < 1e-2)

}#end {doExtras}

##----- "impossible" one to get precisely -----

ff <- function(x) exp(-1/(x-8)^2)
curve(exp(-1/(x-8)^2), -3, 13, n=1001)
(opt. <- optimizeR(function(x) exp(-1/(x-8)^2), -3, 13, trace = 5))
## -> close to 8 {but not very close!}
ff(opt.$minimum) # gives 0
if(doExtras) {
  ## try harder ... in vain ..
  str(opt1 <- optimizeR(ff, -3,13, tol = 1e-60, precFactor = 4))
  print(opt1$minimum, digits=20)
  ## still just 7.99998038 or 8.000036655 {depending on method}
}

```

pbetaI

Accurate Incomplete Beta / Beta Probabilities For Integer Shapes

Description

For integers a, b , $I_x(a, b)$ aka $\text{pbeta}(x, a, b)$ is a polynomial in x with rational coefficients, and hence arbitrarily accurately computable.

TODO (*not yet*): It's sufficient for *one* of a, b to be integer such that the result is a *finite sum* (but the coefficients will no longer be rational, see Abramowitz and Stegun, 26.5.6 and *.7, p.944).

Usage

```
pbetaI(q, shape1, shape2, ncp = 0, lower.tail = TRUE, log.p = FALSE,
       precBits = NULL,
       useRational = !log.p && !is.mpfr(q) && is.null(precBits) && int2,
       rnd.mode = c("N", "D", "U", "Z", "A"))
```

Arguments

q	called x , above; vector of quantiles, in $[0, 1]$; can be <code>numeric</code> , or of class <code>"mpfr"</code> or also <code>"bigq"</code> ("big rational" from package <code>gmp</code>); in the latter case, if <code>log.p = FALSE</code> as by default, <i>all computations</i> are exact, using big rational arithmetic.
shape1, shape2	the positive Beta "shape" parameters, called a, b , above. Must be integer valued for this function.
ncp	unused, only for compatibility with <code>pbeta</code> , must be kept at its default, 0.
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.
log.p	logical; if TRUE, probabilities p are given as $\log(p)$.
precBits	the precision (in number of bits) to be used in <code>sumBinomMpfr()</code> .
useRational	optional <code>logical</code> , specifying if we should try to do everything in exact <i>rational arithmetic</i> , i.e., using package <code>gmp</code> functionality only, and return <code>bigq</code> numbers instead of <code>mpfr</code> numbers.
rnd.mode	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see <code>mpfr</code> .

Value

an `"mpfr"` vector of the same length as `q`.

Note

For upper tail probabilities, i.e., when `lower.tail=FALSE`, we may need large `precBits`, because the implicit or explicit $1 - P$ computation suffers from severe cancellation.

Author(s)

Martin Maechler

References

Abramowitz, M. and Stegun, I. A. (1972) *Handbook of Mathematical Functions*. New York: Dover.
https://en.wikipedia.org/wiki/Abramowitz_and_Stegun provides links to the full text which is in public domain.

See Also

[pbeta](#), [sumBinomMpfr](#) [chooseZ](#).

Examples

```
x <- (0:12)/16 # not all the way up ..
a <- 7; b <- 788

p. <- pbetaI(x, a, b) ## a bit slower:
system.time(
pp <- pbetaI(x, a, b, precBits = 2048)
) # 0.23 -- 0.50 sec
## Currently, the lower.tail=FALSE are computed "badly":
lp <- log(pp)    ## = pbetaI(x, a, b, log.p=TRUE)
lIp <- log1p(-pp) ## = pbetaI(x, a, b, lower.tail=FALSE, log.p=TRUE)
Ip <- 1 - pp     ## = pbetaI(x, a, b, lower.tail=FALSE)

if(Rmpfr:::doExtras()) { ## somewhat slow
  stopifnot(
    all.equal(lp, pbetaI(x, a, b, precBits = 2048, log.p=TRUE)),
    all.equal(lIp, pbetaI(x, a, b, precBits = 2048, lower.tail=FALSE, log.p=TRUE),
              tol = 1e-230),
    all.equal( Ip, pbetaI(x, a, b, precBits = 2048, lower.tail=FALSE))
  )
}

rErr <- function(approx, true, eps = 1e-200) {
  true <- as.numeric(true) # for "mpfr"
  ifelse(Mod(true) >= eps,
         ## relative error, catching '-Inf' etc :
         ifelse(true == approx, 0, 1 - approx / true),
         ## else: absolute error (e.g. when true=0)
         true - approx)
}

rErr(pbeta(x, a, b), pp)
rErr(pbeta(x, a, b, lower=FALSE), Ip)
rErr(pbeta(x, a, b, log = TRUE), lp)
rErr(pbeta(x, a, b, lower=FALSE, log = TRUE), lIp)

a.EQ <- function(..., tol=1e-15) all.equal(..., tolerance=tol)
stopifnot(
  a.EQ(pp, pbeta(x, a, b)),
  a.EQ(lp, pbeta(x, a, b, log.p=TRUE)),
  a.EQ(lIp, pbeta(x, a, b, lower.tail=FALSE, log.p=TRUE)),
  a.EQ( Ip, pbeta(x, a, b, lower.tail=FALSE))
)
```

```

)

## When 'q' is a bigrational (i.e., class "bigq", package 'gmp'), everything
## is computed *exactly* with bigrational arithmetic:
(q4 <- as.bigq(1, 2^(0:4)))
pb4 <- pbetaI(q4, 10, 288, lower.tail=FALSE)
stopifnot( is.bigq(pb4) )
mpb4 <- as(pb4, "mpfr")
mpb4[1:2]
getPrec(mpb4) # 128 349 1100 1746 2362
(pb. <- pbeta(asNumeric(q4), 10, 288, lower.tail=FALSE))
stopifnot(mpb4[1] == 0,
          all.equal(mpb4, pb., tol=4e-15))

qbetaI. <- function(p, shape1, shape2, ncp = 0, lower.tail = TRUE, log.p = FALSE,
  precBits = NULL, rnd.mode = c("N", "D", "U", "Z", "A"),
  tolerance = 1e-20, ...)
{
  if(is.na(a <- as.integer(shape1))) stop("a = shape1 is not coercable to finite integer")
  if(is.na(b <- as.integer(shape2))) stop("b = shape2 is not coercable to finite integer")
  unirootR(function(q) pbetaI(q, a, b, lower.tail=lower.tail, log.p=log.p,
    precBits=precBits, rnd.mode=rnd.mode) - p,
    interval = if(log.p) c(-double.xmax, 0) else 0:1,
    tol = tolerance, ...)
} # end{qbetaI}

(p <- 1 - mpfr(1,128)/20) # 'p' must be high precision
q95.1.3 <- qbetaI.(p, 1,3, tolerance = 1e-29) # -> ~29 digits accuracy
str(q95.1.3) ; roundMpfr(q95.1.3$root, precBits = 29 * log2(10))
## relative error is really small:
(relE <- asNumeric(1 - pbetaI(q95.1.3$root, 1,3) / p))
stopifnot(abs(relE) < 1e-28)

```

pmax

Parallel Maxima and Minima

Description

Returns the parallel maxima and minima of the input values.

The functions `pmin` and `pmax` have been made S4 generics, and this page documents the "... method for class `"mNumber"`", i.e., for arguments that are numeric or from [class "mpfr"](#).

Usage

```

pmax(..., na.rm = FALSE)
pmin(..., na.rm = FALSE)

```

Arguments

...	numeric or arbitrary precision numbers (class mpfr).
na.rm	a logical indicating whether missing values should be removed.

Details

See [pmax](#), the documentation of the base functions, i.e., default methods.

Value

vector-like, of length the longest of the input vectors; typically of class [mpfr](#), for the methods here.

Methods

... = "ANY" the default method, really just [base::pmin](#) or [base::pmax](#), respectively.

... = "mNumber" the method for [mpfr](#) arguments, mixed with numbers; designed to follow the same semantic as the default method.

See Also

The documentation of the **base** functions, [pmin](#) and [pmax](#); also [min](#) and [max](#); further, [range](#) (both [min](#) and [max](#)).

Examples

```
(pm <- pmin(1.35, mpfr(0:10, 77)))
stopifnot(pm == pmin(1.35, 0:10))
```

qnormI

Gaussian / Normal Quantiles qnorm() via Inversion

Description

Compute Gaussian or Normal Quantiles [qnorm\(p, *\)](#) via inversion of our “mpfr-ified” arbitrary accurate [pnorm\(\)](#), using our [unirootR\(\)](#) root finder.

Usage

```
qnormI(p, mean = 0, sd = 1, lower.tail = TRUE, log.p = FALSE,
       trace = 0, verbose = as.logical(trace),
       tol,
       useMpfr = any(prec > 53),
       give.full = FALSE,
       ...)
```

Arguments

<code>p</code>	vector of probabilities.
<code>mean</code>	vector of means.
<code>sd</code>	vector of standard deviations.
<code>log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$ otherwise, $P[X > x]$.
<code>trace</code>	integer passed to <code>unirootR()</code> . If positive, information about a search interval extension will be printed to the console.
<code>verbose</code>	logical indicating if progress details should be printed to the console.
<code>tol</code>	optionally the desired accuracy (convergence tolerance); if missing or not finite, it is computed as $2^{-pr} + 2$ where the precision pr is basically $\max(\text{getPrec}(p+\text{mean}+\text{sd}))$.
<code>useMpfr</code>	logical indicating if <code>mpfr</code> arithmetic should be used.
<code>give.full</code>	logical indicating if the <i>full</i> result of <code>unirootR()</code> should be returned (when applicable).
<code>...</code>	optional further arguments passed to <code>unirootR()</code> such as <code>maxiter</code> , <code>verbDigits</code> , <code>check.conv</code> , <code>warn.no.convergence</code> , and <code>epsC</code> .

Value

If `give.full` is true, return a `list`, say `r`, of `unirootR(.)` results, with `length(r) == length(p)`. Otherwise, return a “numeric vector” like `p`, e.g., of class “`mpfr`” when `p` is.

Author(s)

Martin Maechler

See Also

Standard R’s `qnorm`.

Examples

```
doX <- Rmpfr:::doExtras() # slow parts only if(doX)
cat("doExtras: ", doX, "\n")
p <- (0:32)/32
lp <- -c(1000, 500, 200, 100, 50, 20:1, 2^{-(1:8)})
if(doX) {
  tol1 <- 2.3e-16
  tolM <- 1e-20
  tolRIlog <- 4e-14
} else { # use one more than a third of the points:
  ip <- c(TRUE,FALSE, rep_len(c(TRUE,FALSE,FALSE), length(p)-2L))
  p <- p[ip]
  lp <- lp[ip]
  tol1 <- 1e-9
  tolM <- 1e-12
  tolRIlog <- 25*tolM
```

```

}

f.all.eq <- function(a,b)
  sub("^Mean relative difference:", '', format(all.equal(a, b, tol=0)))
for(logp in c(FALSE,TRUE)) {
  pp <- if(logp) lp else p
  mp <- mpfr(pp, precBits = if(doX) 80 else 64) # precBits = 128 gave "the same" as 80
  for(l.tail in c(FALSE,TRUE)) {
    qn <- qnorm(pp, lower.tail = l.tail, log.p = logp)
    qnI <- qnormI(pp, lower.tail = l.tail, log.p = logp, tol = tolI)
    qnM <- qnormI(mp, lower.tail = l.tail, log.p = logp, tol = tolM)
    cat(sprintf("Accuracy of qnorm(*, lower.t=%-5s, log.p=%-5s): %s || qnI: %s\n",
              l.tail, logp, f.all.eq(qnM, qn ),
              f.all.eq(qnM, qnI)))
    stopifnot(exprs = {
      all.equal(qn, qnI, tol = if(logp) tolRIlog else 4*tolI)
      all.equal(qnM, qnI, tol = tolI)
    })
  }
}

## useMpfr, using mpfr() :
if(doX) {
  p2 <- 2^-c(1:27, 5*(6:20), 20*(6:15))
  e2 <- 88
} else {
  p2 <- 2^-c(1:2, 7, 77, 177, 307)
  e2 <- 60
}
system.time( pn2 <- pnorm(qnormI(mpfr(p2, e2))) ) # 4.1 or 0.68
  all.equal(p2, pn2, tol = 0) # 5.48e-29 // 5.2e-18
2^-e2
stopifnot(all.equal(p2, pn2, tol = 6 * 2^-e2)) # '4 *' needed

## Boundary -- from limits in mpfr maximal exponent range!
## 1) Use maximal ranges:
(old_eranges <- .mpfr_erange()) # typically +/- 2^30
(myERng <- (1-2^-52) * .mpfr_erange(c("min.emin", "max.emax")))
(doIncr <- !isTRUE(all.equal(unname(myERng), unname(old_eranges)))) # ==>
## TRUE only if long is 64-bit, i.e., *not* on Windows
if(doIncr) .mpfr_erange_set(value = myERng)

log2(abs(.mpfr_erange()))# 62 62 if(doIncr) i.e. not on Windows
(lrgOK <- all(log2(abs(.mpfr_erange())) >= 62)) # FALSE on Windows
## The largest quantile for which our mpfr-sized qnorm() does *NOT* underflow :
cM <- if(doX) { "2528468770.343293436810768159197281514373932815851856314908753969469064"
  } else "2528468770.34329343681"
##          1 3 5 7 9 1 3 5 7 9 1 3 5 7 9 1 3 5 7 9 1 3 5 7 9 1 3 5 7 9 1 3
##          10      20      30      40      50      60      70
(qM <- mpfr(cM))
(pM <- pnorm(-qM)) # precision if(doX) 233 else 70 bits of precision ;
## |--> 0 on Windows {limited erange}; otherwise and if(doX) :
```

```
## 7.64890682545699845135633468495894619457903458325606933043966616334460003e-1388255822130839040
log(pM) # 233 bits: -3196577161300663205.8575919621115614148120323933633827052786873078552904

if(lrgOK) withAutoprint({

  try( qnormI(pM) ) ## Error: lower < upper not fulfilled (evt. TODO)
  ## but this works
  print(qnI <- qnormI(log(pM), log.p=TRUE)) # -2528468770.343293436
  all.equal(-qM, qnI, tol = 0) # << show how close; seen 1.084202e-19
  stopifnot( all.equal(-qM, qnI, tol = 1e-18) )
})

if(FALSE) # this (*SLOW*) gives 21 x the *same* (wrong) result --- FIXME!
  qnormI(log(pM) * (2:22), log.p=TRUE)
if(doX) ## Show how bad it is (currently ca. 220 iterations, and then *wrong*)
  str(qnormI(round(log(pM)), log.p=TRUE, trace=1, give.full = TRUE))
if(requireNamespace("DPQ"))
  new("mpfr", as(DPQ::qnormR(pM, trace=1), "mpfr")) # as(*, "mpfr") also works for +/- Inf
  # qnormR1(p=          0, m=0, s=1, l.t.= 1, log= 0): q = -0.5
  # somewhat close to 0 or 1: r := sqrt(-lp) = 1.7879e+09
  # r > 5, using rational form R_3(t), for t=1.787897e+09 -- that is *not* accurate
  # [1] -94658744.369295865460462720.....

## reset to previous status if needed
if(doIncr) .mpfr_erange_set( , old_eranges)
```

Rmpfr-workarounds

Base Functions etc, as an Rmpfr version

Description

Functions from **base** etc which need a *copy* in the **Rmpfr** namespace so they correctly dispatch.

Usage

```
outer(X, Y, FUN = "*", ...)
```

Arguments

X, Y, FUN, ... See **base** package help: [outer](#).

See Also

[outer](#).

Examples

```
outer(1/mpfr(1:10, 70), 0:2)
```

roundMpfr	<i>Rounding to Binary bits, "mpfr-internally"</i>
-----------	---

Description

Rounding to binary bits, not decimal digits. Closer to the number representation, this also allows to *increase* or decrease a number's `precBits`. In other words, it acts as `setPrec()`, see `getPrec()`.

Usage

```
roundMpfr(x, precBits, rnd.mode = c("N", "D", "U", "Z", "A"))
```

Arguments

<code>x</code>	an mpfr number (vector)
<code>precBits</code>	integer specifying the desired precision in bits.
<code>rnd.mode</code>	a 1-letter string specifying how <i>rounding</i> should happen at C-level conversion to MPFR, see <code>mpfr</code> .

Value

an mpfr number as `x` but with the new '`precBits`' precision

See Also

The `mpfr` class group method `Math2` implements a method for `round(x, digits)` which rounds to *decimal* digits.

Examples

```
(p1 <- Const("pi", 100)) # 100 bit prec
roundMpfr(p1, 120) # 20 bits more, but "random noise"
Const("pi", 120) # same "precision", but really precise
```

sapplyMpfr	<i>Apply a Function over a "mpfr" Vector</i>
------------	--

Description

Users may be disappointed to note that `sapply()` or `vapply()` typically do not work with "mpfr" numbers.

This is a simple (but strong) approach to work around the problem, based on `lapply()`.

Usage

```
sapplyMpfr(X, FUN, ..., drop_1_ = TRUE)
```

Arguments

X a vector, possibly of class "mpfr".

FUN a [function](#) returning an "mpfr" vector or even an "mpfrArray". May also be a function returning a [numeric](#) vector or array for numeric X, *and* which returns "mpfr(Array)" for an X argument inheriting from "mpfr".

... further arguments passed to [lapply](#), typically further arguments to FUN.

drop_1_ logical (with unusual name on purpose!) indicating if 1-column matrices ("mpfrMatrix") should be "dropped" to vectors ("mpfr"), the same as in base R's own [sapply](#). This has been implicitly FALSE in **Rmpfr** versions 0.8-5 to 0.8-9 (Oct 2021 to June 2022), accidentally. Since **Rmpfr** 0.9-0, this has been made an argument with default TRUE to be compatible by default with R's [sapply](#).

Details

In the case FUN(<length-1>) returns an [array](#) or "mpfrArray", i.e., with two or more dimensions, sapplyMpfr() returns an "mpfrArray"; this is analogous to [sapply\(X, FUN, simplify = "array"\)](#) (rather than the default sapply() behaviour which returns a matrix also when a higher array would be more "logical".)

Value

an "mpfr" vector, typically of the same length as X.

Note

This may still not always work as well as [sapply\(\)](#) does for atomic vectors. The examples seem to indicate that it typically does work as desired, since **Rmpfr** version 0.9-0.

If you want to transform back to regular numbers anyway, it maybe simpler and more efficient to use

```
res <- lapply(...)
sapply(res, asNumeric, simplify = "array")
```

instead of sapplyMpfr().

Author(s)

Martin Maechler

See Also

[sapply](#), [lapply](#), etc.

Examples

```

sapplyMpfr0 <- ## Originally, the function was simply defined as
  function (X, FUN, ...) new("mpfr", unlist(lapply(X, FUN, ...), recursive = FALSE))

(m1 <- sapply ( 3, function(k) (1:3)^k)) # 3 x 1 matrix (numeric)
(p1 <- sapplyMpfr(mpfr(3, 64), function(k) (1:3)^k))
stopifnot(m1 == p1, is(p1, "mpfrMatrix"), dim(p1) == c(3,1), dim(p1) == dim(m1))
k.s <- c(2, 5, 10, 20)
(mk <- sapply ( k.s, function(k) (1:3)^k)) # 3 x 4 " "
(pm <- sapplyMpfr(mpfr(k.s, 64), function(k) (1:3)^k))
stopifnot(mk == pm, is(pm, "mpfrMatrix"), dim(pm) == 3:4, 3:4 == dim(mk))
## was *wrongly* 4x3 in Rmpfr 0.8-x
f5k <- function(k) outer(1:5, k+0:2, `^^`)# matrix-valued
(mk5 <- sapply ( k.s, f5k)) # sapply()'s default; not "ideal"
(ak5 <- sapply ( k.s, f5k, simplify = "array")) # what we want
(pm5 <- sapplyMpfr(mpfr(k.s, 64), f5k))
stopifnot(c(mk5) == c(ak5), ak5 == pm5, is(pm5, "mpfrArray"), is.array(ak5),
  dim(pm5) == dim(ak5), dim(pm5) == c(5,3, 4))
if(require("Bessel")) { # here X, is simple
  bI1 <- function(k) besselI.nuAsym(mpfr(1.31e9, 128), 10, expon.scaled=TRUE, k.max=k)
  bImp1 <- sapplyMpfr (0:4, bI1, drop_1_ = FALSE) # 1x5 mpfrMatrix -- as in DPQ 0.8-8
  bImp <- sapplyMpfr (0:4, bI1, drop_1_ = TRUE ) # 5 "mpfr" vector {by default}
  bImp0 <- sapplyMpfr0(0:4, bI1) # 5-vector
  stopifnot(identical(bImp, bImp0), bImp == bImp1,
    is(bImp, "mpfr"), is(bImp1, "mpfrMatrix"), dim(bImp1) == c(1, 5))
}# {Bessel}

```

seqMpfr

"mpfr" Sequence Generation

Description

Generate 'regular', i.e., arithmetic sequences. This is in lieu of methods for [seq](#) (dispatching on all three of from, to, and by).

Usage

```

seqMpfr(from = 1, to = 1, by = ((to - from)/(length.out - 1)),
  length.out = NULL, along.with = NULL, ...)

```

Arguments

from, to	the starting and (maximal) end value (numeric or "mpfr") of the sequence.
by	number (numeric or "mpfr"): increment of the sequence.
length.out	desired length of the sequence. A non-negative number, which will be rounded up if fractional.
along.with	take the length from the length of this argument.
...	arguments passed to or from methods.

Details

see [seq](#) (default method in package **base**), whose semantic we want to replicate (almost).

Value

a ‘vector’ of class `"mpfr"`, when one of the first three arguments was.

Author(s)

Martin Maechler

See Also

The documentation of the **base** function [seq](#); [mpfr](#)

Examples

```
seqMpfr(0, 1, by = mpfr(0.25, prec=88))
```

```
seqMpfr(7, 3) # -> default prec.
```

```
str.mpfr
```

Compactly Show STRucture of Rmpfr Number Object

Description

The `str` method for objects of class `mpfr` produces a bit more useful output than the default method `str.default`.

Usage

```
## S3 method for class 'mpfr'
str(object, nest.lev, internal = FALSE,
     give.head = TRUE, digits.d = 12, vec.len = NULL, drop0trailing=TRUE,
     width = getOption("width"), ...)
```

Arguments

<code>object</code>	an object of class <code>mpfr</code> .
<code>nest.lev</code>	for <code>str()</code> , typically only used when called by a higher level <code>str()</code> .
<code>internal</code>	logical indicating if the low-level internal structure should be shown; if true (not by default), uses <code>str(object@.Data)</code> .
<code>give.head</code>	logical indicating if the “header” should be printed.

digits.d	the number of digits to be used, will be passed <code>formatMpfr()</code> and hence NULL will use “as many as needed”, i.e. often too many. If this is a number, as per default, less digits will be used in case the precision (<code>getPrec(object)</code>) is smaller.
vec.len	the number of <i>elements</i> that will be shown. The default depends on the precision of object and width (since Rmpfr 0.6-0, it was 3 previously).
drop0trailing	logical, passed to <code>formatMpfr()</code> (with a different default here).
width	the (approximately) desired width of output, see <code>options(width = .)</code> .
...	further arguments, passed to <code>formatMpfr()</code> .

See Also

`.mpfr2list()` puts the internal structure into a `list`, and its help page documents many more (low level) utilities.

Examples

```
(x <- c(Const("pi", 64), mpfr(-2:2, 64)))
str(x)
str(list(pi = pi, x.mpfr = x))
str(x ^ 1000)
str(x ^ -1e4, digits=NULL) # full precision

str(x, internal = TRUE) # internal low-level (for experts)

uu <- Const("pi", 16) # unaccurate
str(uu) # very similar to just 'uu'
```

sumBinomMpfr

*(Alternating) Binomial Sums via Rmpfr***Description**

Compute (alternating) binomial sums via high-precision arithmetic. If $sBn(f, n) := \text{sumBinomMpfr}(n, f)$, (default `alternating` is true, and `n0 = 0`),

$$sBn(f, n) = \sum_{k=n0}^n (-1)^{(n-k)} \binom{n}{k} \cdot f(k) = \Delta^n f,$$

see Details for the n -th forward difference operator $\Delta^n f$. If `alternating` is false, the $(-1)^{(n-k)}$ factor is dropped (or replaced by 1) above.

Such sums appear in different contexts and are typically challenging, i.e., currently impossible, to evaluate reliably as soon as n is larger than around 50 – 70.

Usage

```
sumBinomMpfr(n, f, n0 = 0, alternating = TRUE, precBits = 256,
             f.k = f(mpfr(k, precBits=precBits)))
```

Arguments

n	upper summation index (integer).
f	function to be evaluated at k for k in $n0:n$ (and which must return <i>one</i> value per k).
n0	lower summation index, typically 0 (= default) or 1.
alternating	logical indicating if the sum is alternating, see below.
precBits	the number of bits for MPFR precision, see mpfr .
f.k	can be specified instead of f and $precBits$, and must contain the equivalent of its default, $f(\text{mpfr}(k, \text{precBits}=\text{precBits}))$.

Details

The alternating binomial sum $sB(f, n) := \text{sumBinom}(n, f, n0 = 0)$ is equal to the n -th forward difference operator $\Delta^n f$,

$$sB(f, n) = \Delta^n f,$$

where

$$\Delta^n f = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot f(k),$$

is the n -fold iterated forward difference $\Delta f(x) = f(x+1) - f(x)$ (for $x = 0$).

The current implementation might be improved in the future, notably for the case where $sB(f, n) = \text{sumBinomMpfr}(n, f, *)$ is to be computed for a whole sequence $n = 1, \dots, N$.

Value

an **mpfr** number of precision $precBits$. s . If **alternating** is true (as per default),

$$s = \sum_{k=n0}^n (-1)^k \binom{n}{k} \cdot f(k),$$

if **alternating** is false, the $(-1)^k$ factor is dropped (or replaced by 1) above.

Author(s)

Martin Maechler, after conversations with Christophe Dutang.

References

- Wikipedia (2012) The N"orlund-Rice integral, https://en.wikipedia.org/wiki/Rice_integral
- Flajolet, P. and Sedgewick, R. (1995) Mellin Transforms and Asymptotics: Finite Differences and Rice's Integrals, *Theoretical Computer Science* **144**, 101–124.

See Also

chooseMpfr, **chooseZ** from package **gmp**.

Examples

```

## "naive" R implementation:
sumBinom <- function(n, f, n0=0, ...) {
  k <- n0:n
  sum( choose(n, k) * (-1)^(n-k) * f(k, ...) )
}

## compute sumBinomMpfr(.) for a whole set of 'n' values:
sumBin.all <- function(n, f, n0=0, precBits = 256, ...)
{
  N <- length(n)
  precBits <- rep(precBits, length = N)
  ll <- lapply(seq_len(N), function(i)
    sumBinomMpfr(n[i], f, n0=n0, precBits=precBits[i], ...))
  sapply(ll, as, "double")
}
sumBin.all.R <- function(n, f, n0=0, ...)
  sapply(n, sumBinom, f=f, n0=n0, ...)

n.set <- 5:80
system.time(res.R <- sumBin.all.R(n.set, f = sqrt)) ## instantaneous..
system.time(resMpfr <- sumBin.all (n.set, f = sqrt)) ## ~ 0.6 seconds

matplot(n.set, cbind(res.R, resMpfr), type = "l", lty=1,
  ylim = extendrange(resMpfr, f = 0.25), xlab = "n",
  main = "sumBinomMpfr(n, f = sqrt) vs. R double precision")
legend("topleft", leg=c("double prec.", "mpfr"), lty=1, col=1:2, bty = "n")

```

unirootR

*One Dimensional Root (Zero) Finding – in pure R***Description**

The function `unirootR` searches the interval from lower to upper for a root (i.e., zero) of the function `f` with respect to its first argument.

`unirootR()` is “clone” of `uniroot()`, written entirely in R, in a way that it works with `mpfr`-numbers as well.

Usage

```

unirootR(f, interval, ...,
  lower = min(interval), upper = max(interval),
  f.lower = f(lower, ...), f.upper = f(upper, ...),
  extendInt = c("no", "yes", "downX", "upX"),
  trace = 0, verbose = as.logical(trace),
  verbDigits = max(3, min(20, -log10(tol)/2)),
  tol = .Machine$double.eps^0.25, maxiter = 1000L,
  check.conv = FALSE,
  warn.no.convergence = !check.conv,
  epsC = NULL)

```

Arguments

f	the function for which the root is sought.
interval	a vector containing the end-points of the interval to be searched for the root.
...	additional named or unnamed arguments to be passed to f
lower, upper	the lower and upper end points of the interval to be searched.
f.lower, f.upper	the same as f(upper) and f(lower), respectively. Passing these values from the caller where they are often known is more economical as soon as f() contains non-trivial computations.
extendInt	character string specifying if the interval c(lower, upper) should be extended or directly produce an error when f() does not have differing signs at the end-points. The default, "no", keeps the search interval and hence produces an error. Can be abbreviated.
trace	integer number; if positive, tracing information is produced. Higher values giving more details.
verbose	logical (or integer) indicating if (and how much) verbose output should be produced during the iterations.
verbDigits	used only if verbose is true, indicates the number of digits numbers should be printed with, using <code>format(., digits=verbDigits)</code> .
tol	the desired accuracy (convergence tolerance).
maxiter	the maximum number of iterations.
check.conv	logical indicating whether non convergence should be caught as an error, notably non-convergence in maxiter iterations should be an error instead of a warning.
warn.no.convergence	if set to FALSE there's no warning about non-convergence. Useful to just run a few iterations.
epsC	positive number or NULL in which case a smart default is sought. This should specify the "achievable machine precision" for the given numbers and their arithmetic. The default will set this to <code>.Machine\$double.eps</code> for double precision numbers, and will basically use $2^{-\min(\text{getPrec}(f.lower), \text{getPrec}(f.upper))}$ when that works (as, e.g., for <code>mpfr</code> -numbers) otherwise. This is factually a lower bound for the achievable lower bound, and hence, setting <code>tol</code> smaller than <code>epsC</code> is typically non-sensical and produces a warning.

Details

Note that arguments after ... must be matched exactly.

Either `interval` or both `lower` and `upper` must be specified: the upper endpoint must be strictly larger than the lower endpoint. The function values at the endpoints must be of opposite signs (or zero), for `extendInt="no"`, the default. Otherwise, if `extendInt="yes"`, the interval is extended on both sides, in search of a sign change, i.e., until the search interval $[l, u]$ satisfies $f(l) \cdot f(u) \leq 0$.

If it is *known how* f changes sign at the root x_0 , that is, if the function is increasing or decreasing there, `extendInt` can (and typically should) be specified as "upX" (for "upward crossing") or

"downX", respectively. Equivalently, define $S := \pm 1$, to require $S = \text{sign}(f(x_0 + \epsilon))$ at the solution. In that case, the search interval $[l, u]$ possibly is extended to be such that $S \cdot f(l) \leq 0$ and $S \cdot f(u) \geq 0$.

The function only uses R code with basic arithmetic, such that it should also work with "generalized" numbers (such as `mpfr`-numbers) as long the necessary `Ops` methods are defined for those.

The underlying algorithm assumes a continuous function (which then is known to have at least one root in the interval).

Convergence is declared either if $f(x) == 0$ or the change in x for one step of the algorithm is less than `tol` (plus an allowance for representation error in x).

If the algorithm does not converge in `maxiter` steps, a warning is printed and the current approximation is returned.

`f` will be called as `f(x, ...)` for a (generalized) numeric value of x .

Value

A list with four components: `root` and `f.root` give the location of the root and the value of the function evaluated at that point. `iter` and `estim.prec` give the number of iterations used and an approximate estimated precision for `root`. (If the root occurs at one of the endpoints, the estimated precision is NA.)

Source

Based on `zeroin()` (in package **rootoned**) by John Nash who manually translated the C code in R's `zeroin.c` and on `uniroot()` in R's sources.

References

Brent, R. (1973), see `uniroot`.

See Also

R's own (**stats** package) `uniroot`. `polyroot` for all complex roots of a polynomial; `optimize`, `nlm`.

Examples

```
require(utils) # for str

## some platforms hit zero exactly on the first step:
## if so the estimated precision is 2/3.
f <- function(x,a) x - a
str(xmin <- unirootR(f, c(0, 1), tol = 0.0001, a = 1/3))

## handheld calculator example: fixpoint of cos(.):
rc <- unirootR(function(x) cos(x) - x, lower=-pi, upper=pi, tol = 1e-9)
rc$root

## the same with much higher precision:
rcM <- unirootR(function(x) cos(x) - x,
                 interval= mpfr(c(-3,3), 300), tol = 1e-40)
```

```

rcM
x0 <- rcM$root
stopifnot(all.equal(cos(x0), x0,
                    tol = 1e-40))## 40 digits accurate!

str(unirootR(function(x) x*(x^2-1) + .5, lower = -2, upper = 2,
            tol = 0.0001), digits.d = 10)
str(unirootR(function(x) x*(x^2-1) + .5, lower = -2, upper = 2,
            tol = 1e-10 ), digits.d = 10)

## A sign change of f(.), but not a zero but rather a "pole":
tan. <- function(x) tan(x * (Const("pi",200)/180))# == tan( <angle> )
(rtan <- unirootR(tan., interval = mpfr(c(80,100), 200), tol = 1e-40))
## finds 90 {"ok"}, and now gives a warning

## Find the smallest value x for which exp(x) > 0 (numerically):
r <- unirootR(function(x) 1e80*exp(x)-1e-300, c(-1000,0), tol = 1e-15)
str(r, digits.d = 15) ##> around -745, depending on the platform.

exp(r$root)      # = 0, but not for r$root * 0.999...
minexp <- r$root * (1 - 10*.Machine$double.eps)
exp(minexp)      # typically denormalized

## --- using mpfr-numbers :

## Find the smallest value x for which exp(x) > 0 ("numerically");
## Note that mpfr-numbers underflow *MUCH* later than doubles:
## one of the smallest mpfr-numbers {see also ?mpfr-class } :
(ep.M <- mpfr(2, 55) ^ - ((2^30 + 1) * (1 - 1e-15)))
r <- unirootR(function(x) 1e99* exp(x) - ep.M, mpfr(c(-1e20, 0), 200))
r # 97 iterations; f.root is very similar to ep.M

## interval extension 'extendInt' -----

f1 <- function(x) (121 - x^2)/(x^2+1)
f2 <- function(x) exp(-x)*(x - 12)
tools::assertError(unirootR(f1, c(0,10)), verbose=TRUE)
##-> error: f() .. end points not of opposite sign

## where as 'extendInt="yes"' simply first enlarges the search interval:
u1 <- unirootR(f1, c(0,10),extendInt="yes", trace=1)
u2 <- unirootR(f2, mpfr(c(0,2), 128), extendInt="yes", trace=2, verbose=FALSE, tol = 1e-25)
stopifnot(all.equal(u1$root, 11, tolerance = 1e-5),
          all.equal(u2$root, 12, tolerance = 1e-23))

## The *danger* of interval extension:
## No way to find a zero of a positive function, but
## numerically, f(-|M|) becomes zero :
u3 <- unirootR(exp, c(0,2), extendInt="yes", trace=TRUE)

## Nonsense example (must give an error):
tools::assertCondition( unirootR(function(x) 1, 0:1, extendInt="yes"),

```

"error", verbose=TRUE)

Index

- * **Forward Difference**
 - sumBinomMpfr, 73
- * **Rice integral**
 - sumBinomMpfr, 73
- * **arithmetic**
 - frexpMpfr, 21
- * **arith**
 - Bernoulli, 9
 - chooseMpfr, 12
 - factorialMpfr, 14
 - formatHex, 16
 - gmp-conversions, 23
 - matmult, 33
 - mpfr.utils, 52
 - pbetaI, 62
 - pmax, 64
 - roundMpfr, 69
 - sumBinomMpfr, 73
- * **array**
 - mpfrArray, 53
 - mpfrMatrix-utils, 58
- * **character**
 - formatMpfr, 18
- * **classes**
 - array_or_vector-class, 6
 - atomicVector-class, 8
 - Mnumber-class, 35
 - mpfr, 36
 - mpfr-class, 38
 - mpfrMatrix, 55
- * **distribution**
 - mpfr-distr-etc, 43
 - pbetaI, 62
 - qnormI, 65
- * **manip**
 - sapplyMpfr, 69
 - seqMpfr, 71
- * **math**
 - Bessel_mpfr, 10
 - igamma, 26
 - integrateR, 28
 - is.whole, 30
 - log1mexp, 31
 - mpfr-special-functions, 45
 - qnormI, 65
- * **methods**
 - asNumeric-methods, 7
 - bind-methods, 11
 - pmax, 64
- * **misc**
 - Rmpfr-workarounds, 68
- * **optimize**
 - hjkMpfr, 24
 - optimizeR, 59
 - unirootR, 75
- * **package**
 - Rmpfr-package, 3
- * **print**
 - formatMpfr, 18
- * **univar**
 - pmax, 64
- * **utilities**
 - frexpMpfr, 21
 - integrateR, 28
 - mpfr-utils, 47
 - str.mpfr, 72
 - ..bigq2mpfr (mpfr-utils), 47
 - ..bigz2mpfr (mpfr-utils), 47
 - .Machine, 41, 50, 76
 - .bigq2mpfr (gmp-conversions), 23
 - .bigz2mpfr (gmp-conversions), 23
 - .getPrec (mpfr-utils), 47
 - .getSign (mpfr-utils), 47
 - .matmult.R (matmult), 33
 - .mpfr (mpfr-utils), 47
 - .mpfr.is.whole (mpfr.utils), 52
 - .mpfr2bigq (gmp-conversions), 23
 - .mpfr2bigz (gmp-conversions), 23

- .mpfr2d (mpfr-utils), 47
- .mpfr2exp, 20, 22
- .mpfr2exp (mpfr-utils), 47
- .mpfr2i (mpfr-utils), 47
- .mpfr2list, 73
- .mpfr2list (mpfr-utils), 47
- .mpfr2str, 19, 50
- .mpfr2str (formatMpfr), 18
- .mpfrVersion (mpfr-utils), 47
- .mpfr_erange (mpfr-utils), 47
- .mpfr_erange_is_int (mpfr-utils), 47
- .mpfr_erange_kinds (mpfr-utils), 47
- .mpfr_erange_set, 44
- .mpfr_erange_set (mpfr-utils), 47
- .mpfr_formatinfo, 20
- .mpfr_formatinfo (mpfr-utils), 47
- .mpfr_gmp_numbbits (mpfr-utils), 47
- .mpfr_maxPrec (mpfr-utils), 47
- .mpfr_minPrec (mpfr-utils), 47
- .mpfr_negative (mpfr-utils), 47
- .mpfr_sign (mpfr-utils), 47
- [,mpfr, ANY, missing, missing-method (mpfr-class), 38
- [,mpfrArray, ANY, ANY, ANY-method (mpfrMatrix), 55
- [,mpfrArray, ANY, missing, missing-method (mpfrMatrix), 55
- [,mpfrArray, matrix, missing, missing-method (mpfrMatrix), 55
- [<-,mpfr, ANY, missing, ANY-method (mpfr-class), 38
- [<-,mpfr, ANY, missing, mpfr-method (mpfr-class), 38
- [<-,mpfr, missing, missing, ANY-method (mpfr-class), 38
- [<-,mpfrArray, ANY, ANY, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, ANY, ANY, mpfr-method (mpfrMatrix), 55
- [<-,mpfrArray, ANY, missing, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, ANY, missing, mpfr-method (mpfrMatrix), 55
- [<-,mpfrArray, matrix, missing, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, matrix, missing, mpfr-method (mpfrMatrix), 55
- [<-,mpfrArray, missing, ANY, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, missing, ANY, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, missing, missing, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, missing, missing, mpfr-method (mpfrMatrix), 55
- [<-,mpfr, Mnumber, mpfr-method (mpfrMatrix), 55
- [<-,mpfrArray, missing, missing, ANY-method (mpfrMatrix), 55
- [<-,mpfrArray, missing, missing, mpfr-method (mpfrMatrix), 55
- [[,mpfr-method (mpfr-class), 38
- %*%, Mnumber, mpfr-method (mpfrMatrix), 55
- %*%, array_or_vector, mpfr-method (mpfr-class), 38
- %*%, mpfr, Mnumber-method (mpfrMatrix), 55
- %*%, mpfr, array_or_vector-method (mpfr-class), 38
- %*%, mpfr, mpfr-method (mpfrMatrix), 55
- %*%, mpfr, mpfrMatrix-method (mpfrMatrix), 55
- %*%, mpfrMatrix, mpfr-method (mpfrMatrix), 55
- %*%, mpfrMatrix, mpfrMatrix-method (mpfrMatrix), 55
- %*%, 34, 56
- abs, 40, 58
- abs,mpfr-method (mpfr-class), 38
- acos, 40
- acosh, 40
- Ai (Bessel_mpfr), 10
- all, 40
- all.equal, 41
- all.equal, ANY, mpfr-method (mpfr-class), 38
- all.equal, mpfr, ANY-method (mpfr-class), 38
- all.equal, mpfr, mpfr-method (mpfr-class), 38
- any, 40
- aperm, 56
- aperm,mpfrArray-method (mpfrMatrix), 55
- apply,mpfrArray-method (mpfrMatrix), 55
- Arg,mpfr-method (mpfr-class), 38
- Arith, array, mpfr-method (mpfr-class), 38
- Arith, integer, mpfr-method (mpfr-class), 38
- Arith,mpfr, array-method (mpfr-class), 38
- Arith,mpfr, integer-method (mpfr-class), 38
- Arith,mpfr, missing-method (mpfr-class), 38

- coerce, bigq, mpfr-method
(gmp-conversions), 23
- coerce, bigz, mpfr-method
(gmp-conversions), 23
- coerce, character, mpfr-method
(mpfr-class), 38
- coerce, integer, mpfr-method
(mpfr-class), 38
- coerce, logical, mpfr-method
(mpfr-class), 38
- coerce, matrix, mpfrMatrix-method
(mpfrMatrix), 55
- coerce, mpfr, bigz-method (mpfr-class), 38
- coerce, mpfr, character-method
(mpfr-class), 38
- coerce, mpfr, integer-method
(mpfr-class), 38
- coerce, mpfr, mpfr1-method (mpfr-class),
38
- coerce, mpfr, numeric-method
(mpfr-class), 38
- coerce, mpfr1, mpfr-method (mpfr-class),
38
- coerce, mpfr1, numeric-method
(mpfr-class), 38
- coerce, mpfrArray, array-method
(mpfrMatrix), 55
- coerce, mpfrArray, matrix-method
(mpfrMatrix), 55
- coerce, mpfrArray, vector-method
(mpfrMatrix), 55
- coerce, mpfrMatrix, matrix-method
(mpfrMatrix), 55
- coerce, numeric, mpfr-method
(mpfr-class), 38
- coerce, numeric, mpfr1-method
(mpfr-class), 38
- coerce, raw, mpfr-method (mpfr-class), 38
- coerce<-, mpfrArray, vector-method
(mpfrMatrix), 55
- colMeans, mpfrArray-method (mpfrMatrix),
55
- colSums, mpfrArray-method (mpfrMatrix),
55
- Compare, array, mpfr-method (mpfr-class),
38
- Compare, integer, mpfr-method
(mpfr-class), 38
- Compare, mpfr, array-method (mpfr-class),
38
- Compare, mpfr, integer-method
(mpfr-class), 38
- Compare, mpfr, mpfr-method (mpfr-class),
38
- Compare, mpfr, mpfrArray-method
(mpfrMatrix), 55
- Compare, mpfr, numeric-method
(mpfr-class), 38
- Compare, mpfrArray, mpfr-method
(mpfrMatrix), 55
- Compare, mpfrArray, numeric-method
(mpfrMatrix), 55
- Compare, numeric, mpfr-method
(mpfr-class), 38
- Compare, numeric, mpfrArray-method
(mpfrMatrix), 55
- complex, 8
- Conj, mpfr-method (mpfr-class), 38
- Const (mpfr), 36
- cos, 40
- cosh, 40
- cospi, 40
- crossprod, 34
- crossprod, array_or_vector, mpfr-method
(mpfr-class), 38
- crossprod, Mnumber, mpfr-method
(mpfrMatrix), 55
- crossprod, mpfr, array_or_vector-method
(mpfr-class), 38
- crossprod, mpfr, missing-method
(mpfrMatrix), 55
- crossprod, mpfr, Mnumber-method
(mpfrMatrix), 55
- crossprod, mpfr, mpfr-method
(mpfrMatrix), 55
- crossprod, mpfr, mpfrMatrix-method
(mpfrMatrix), 55
- crossprod, mpfrMatrix, mpfr-method
(mpfrMatrix), 55
- crossprod, mpfrMatrix, mpfrMatrix-method
(mpfrMatrix), 55
- cummax, 40
- cummin, 40
- cumprod, 40
- cumsum, 40
- dbinom, 44

- dbinom (mpfr-distr-etc), 43
- determinant, 58, 59
- determinant.mpfrMatrix
(mpfrMatrix-utils), 58
- dgamma, 44
- dgamma (mpfr-distr-etc), 43
- diag, mpfrMatrix-method (mpfrMatrix), 55
- diag<-, mpfrMatrix-method (mpfrMatrix),
55
- diff, 52
- diff.default, 52
- diff.mpfr (mpfr.utils), 52
- digamma, 5, 40
- dim, 7, 20, 40, 56
- dim, mpfrArray-method (mpfrMatrix), 55
- dim<-, mpfr-method (mpfr-class), 38
- dimnames, 20
- dimnames, mpfrArray-method (mpfrMatrix),
55
- dimnames<-, mpfrArray-method
(mpfrMatrix), 55
- dnbinom, 44
- dnbinom (mpfr-distr-etc), 43
- dnorm (mpfr-distr-etc), 43
- dotsMethods, 11
- double, 48, 50
- dpois, 44
- dpois (mpfr-distr-etc), 43
- dt, 44
- dt (mpfr-distr-etc), 43
- duplicated, 41

- Ei (mpfr-special-functions), 45
- erf, 44, 53
- erf (mpfr-special-functions), 45
- erfc (mpfr-special-functions), 45
- exp, 40
- expm1, 40

- factorial, 13, 15
- factorial, mpfr-method (mpfr-class), 38
- factorialMpfr, 5, 13, 14, 40
- factorialZ, 15
- floor, 40
- format, 16–20, 49, 76
- format, mpfr-method (mpfr-class), 38
- formatBin, 36
- formatBin (formatHex), 16
- formatDec (formatHex), 16

- formatHex, 16
- formatMpfr, 5, 17, 18, 41, 48, 49, 73
- formatN, 20
- formatN.mpfr (formatMpfr), 18
- frexp, 22
- frexpMpfr, 21
- function, 70, 74

- gamma, 5, 13, 15, 27, 39, 40
- getD (mpfr-utils), 47
- getGroupMembers, 40
- getPrec, 5, 16, 36, 66, 69, 73
- getPrec (mpfr-utils), 47
- gmp, 6
- gmp-conversions, 23
- golden_ratio, 60

- hjk, 24
- hjkMpfr, 5, 24, 60
- hypot (mpfr-class), 38

- igamma, 26
- Im, mpfr-method (mpfr-class), 38
- integer, 8, 13, 41, 48–50
- integrate, 29, 30
- integrateR, 5, 28
- interactive, 48
- invisible, 50
- is.atomic, 8
- is.finite, 50
- is.finite, mpfr-method (mpfr-class), 38
- is.finite, mpfrArray-method
(mpfr-class), 38
- is.infinite, mpfr-method (mpfr-class), 38
- is.infinite, mpfrArray-method
(mpfr-class), 38
- is.integer, 31
- is.mpfr (mpfr), 36
- is.na, mpfr-method (mpfr-class), 38
- is.na, mpfrArray-method (mpfr-class), 38
- is.nan, mpfr-method (mpfr-class), 38
- is.nan, mpfrArray-method (mpfr-class), 38
- is.whole, 30, 31, 42, 52

- j0, 46
- j0 (Bessel_mpfr), 10
- j1 (Bessel_mpfr), 10
- jn, 42
- jn (Bessel_mpfr), 10

- lapply, [69, 70](#)
- lbeta, ANY, mpfr-method (mpfr-class), [38](#)
- lbeta, ANY, mpfrArray-method (mpfr-class), [38](#)
- lbeta, mpfr, ANY-method (mpfr-class), [38](#)
- lbeta, mpfr, mpfr-method (mpfr-class), [38](#)
- lbeta, mpfr, numeric-method (mpfr-class), [38](#)
- lbeta, mpfrArray, ANY-method (mpfr-class), [38](#)
- lbeta, mpfrArray, mpfrArray-method (mpfr-class), [38](#)
- lbeta, numeric, mpfr-method (mpfr-class), [38](#)
- ldexpMpfr (frexpMpfr), [21](#)
- lgamma, [39, 40](#)
- Li2 (mpfr-special-functions), [45](#)
- list, [22, 24, 25, 39, 55, 58, 60, 66, 73](#)
- load, [50](#)
- log, [40, 58](#)
- log, mpfr-method (mpfr-class), [38](#)
- log10, [40](#)
- log1mexp, [31](#)
- log1p, [40](#)
- log1pexp (log1mexp), [31](#)
- log2, [40](#)
- Logic, mpfr, mpfr-method (mpfr-class), [38](#)
- Logic, mpfr, numeric-method (mpfr-class), [38](#)
- Logic, numeric, mpfr-method (mpfr-class), [38](#)
- logical, [16, 19, 41, 44, 49, 50, 62](#)
- Math, [40, 45](#)
- Math, mpfr-method (mpfr-class), [38](#)
- Math2, [45](#)
- Math2, mpfr-method (mpfr-class), [38](#)
- matmult, [33](#)
- matrix, [7, 34, 50, 55](#)
- max, [40](#)
- mean, [40](#)
- mean, mpfr-method (mpfr-class), [38](#)
- mean.default, [40](#)
- median, mpfr-method (mpfr-class), [38](#)
- min, [40, 65](#)
- missing, [36](#)
- Mnumber, [11](#)
- Mnumber-class, [35](#)
- mNumber-class (Mnumber-class), [35](#)
- Mod, mpfr-method (mpfr-class), [38](#)
- mpfr, [5, 7, 9–13, 15–20, 22, 23, 26, 27, 29, 31, 32, 34–36, 36, 37, 39–41, 44–50, 52–56, 59, 62, 64–66, 69–72, 74–77](#)
- mpfr-class, [5, 38](#)
- mpfr-distr (mpfr-distr-etc), [43](#)
- mpfr-distr-etc, [43](#)
- mpfr-special-functions, [45](#)
- mpfr-utils, [47](#)
- mpfr.is.0 (mpfr.utils), [52](#)
- mpfr.is.integer (mpfr.utils), [52](#)
- mpfr.utils, [52](#)
- mpfr1, [55](#)
- mpfr1-class (mpfr-class), [38](#)
- mpfr2array, [54, 55](#)
- mpfr2array (mpfr-utils), [47](#)
- mpfr_default_prec (mpfr-utils), [47](#)
- mpfrArray, [5, 7, 20, 37, 40, 48–50, 53, 53, 54, 55, 57, 70](#)
- mpfrArray-class (mpfrMatrix), [55](#)
- mpfrImport (mpfr-utils), [47](#)
- mpfrIs0, [50](#)
- mpfrIs0 (mpfr.utils), [52](#)
- mpfrMatrix, [7, 11, 12, 34, 35, 37, 41, 42, 50, 54, 55, 58, 59](#)
- mpfrMatrix-class, [5](#)
- mpfrMatrix-class (mpfrMatrix), [55](#)
- mpfrMatrix-utils, [58](#)
- mpfrVersion (mpfr.utils), [52](#)
- mpfrXport (mpfr-utils), [47](#)
- names, [49](#)
- NaN, [39](#)
- nlm, [77](#)
- norm, [56](#)
- norm, ANY, missing-method (mpfrMatrix), [55](#)
- norm, mpfrMatrix, character-method (mpfrMatrix), [55](#)
- NULL, [48, 55](#)
- numeric, [8, 10, 27, 34, 36–38, 41, 44, 46, 49, 52, 62, 70](#)
- numeric_version, [53](#)
- numericVector-class (Mnumber-class), [35](#)
- Ops, [77](#)
- Ops, ANY, mpfr-method (mpfr-class), [38](#)
- Ops, array, mpfr-method (mpfr-class), [38](#)
- Ops, bigq, mpfr-method (mpfr-class), [38](#)
- Ops, bigz, mpfr-method (mpfr-class), [38](#)

- Ops, mpfr, ANY-method (mpfr-class), 38
- Ops, mpfr, array-method (mpfr-class), 38
- Ops, mpfr, bigq-method (mpfr-class), 38
- Ops, mpfr, bigz-method (mpfr-class), 38
- Ops, mpfr, vector-method (mpfr-class), 38
- Ops, vector, mpfr-method (mpfr-class), 38
- optim, 26
- optimize, 60, 77
- optimizeR, 5, 26, 59
- options, 19, 48, 49, 73
- order, 41
- outer, 68
- outer (Rmpfr-workarounds), 68
- pbeta, 44, 62, 63
- pbetaI, 44, 62
- pgamma, 27
- pmax, 64, 65
- pmax, ANY-method (pmax), 64
- pmax, mNumber-method (pmax), 64
- pmax-methods (pmax), 64
- pmin, 65
- pmin (pmax), 64
- pmin, ANY-method (pmax), 64
- pmin, mNumber-method (pmax), 64
- pmin-methods (pmax), 64
- pnorm, 5, 44, 46, 65
- pnorm (mpfr-distr-etc), 43
- pochMpfr, 15, 42
- pochMpfr (chooseMpfr), 12
- polyroot, 77
- prettyNum, 20
- print, 17, 19, 29, 39
- print.default, 48
- print.integrate, 29
- print.integrateR (integrateR), 28
- print.mpfr (mpfr-utils), 47
- print.mpfr1 (mpfr-class), 38
- print.mpfrArray (mpfr-utils), 47
- print.Ncharacter (formatHex), 16
- print.summaryMpfr (mpfr-class), 38
- prod, 40
- qnorm, 65, 66
- qnormI, 65
- quantile, 41
- quantile, mpfr-method (mpfr-class), 38
- range, 40, 65
- rank, 41
- raw, 41
- rbind, 11
- rbind (bind-methods), 11
- rbind, ANY-method (bind-methods), 11
- rbind, Mnumber-method (bind-methods), 11
- rbind-methods (bind-methods), 11
- Re, mpfr-method (mpfr-class), 38
- Rmpfr (Rmpfr-package), 3
- Rmpfr-package, 3
- Rmpfr-workarounds, 68
- round, 40, 69
- roundMpfr, 5, 36, 40, 42, 49, 69
- rowMeans, mpfrArray-method (mpfrMatrix), 55
- rowSums, mpfrArray-method (mpfrMatrix), 55
- sapply, 69, 70
- sapplyMpfr, 69
- save, 50
- seq, 71, 72
- seqMpfr, 5, 71
- setPrec (roundMpfr), 69
- show, integrateR-method (integrateR), 28
- show, mpfr-method (mpfr-class), 38
- show, mpfr1-method (mpfr-class), 38
- show, mpfrArray-method (mpfrMatrix), 55
- show, summaryMpfr-method (mpfr-class), 38
- sign, 39, 40, 50
- sign, mpfr-method (mpfr-class), 38
- sign, mpfrArray-method (mpfrMatrix), 55
- signif, 40
- sin, 40
- sinh, 40
- sinpi, 40
- sort, 41
- sprintf, 16, 17, 20
- sqrt, 40
- str, 53, 72
- str.default, 72
- str.mpfr, 53, 72
- sum, 40
- sumBinomMpfr, 5, 13, 62, 63, 73
- Summary, 40
- Summary, mpfr-method (mpfr-class), 38
- summary, mpfr-method (mpfr-class), 38
- summary.default, 40
- summaryMpfr-class (mpfr-class), 38

t, mpfr-method (mpfr-class), 38
t, mpfrMatrix-method (mpfrMatrix), 55
tan, 40
tanh, 40
tanpi, 40
tcrossprod, 34
tcrossprod, array_or_vector, mpfr-method (mpfr-class), 38
tcrossprod, Mnumber, mpfr-method (mpfrMatrix), 55
tcrossprod, mpfr, array_or_vector-method (mpfr-class), 38
tcrossprod, mpfr, missing-method (mpfrMatrix), 55
tcrossprod, mpfr, Mnumber-method (mpfrMatrix), 55
tcrossprod, mpfr, mpfr-method (mpfrMatrix), 55
tcrossprod, mpfr, mpfrMatrix-method (mpfrMatrix), 55
tcrossprod, mpfrMatrix, mpfr-method (mpfrMatrix), 55
tcrossprod, mpfrMatrix, mpfrMatrix-method (mpfrMatrix), 55
toNum, 7
toNum (mpfr-utils), 47
trigamma, 5, 40
trunc, 40
typeof, 7, 38

unique, 41
unique, mpfr, ANY-method (mpfr-class), 38
unique, mpfr-method (mpfr-class), 38
unique.mpfr (mpfr-class), 38
uniroot, 75, 77
unirootR, 5, 60, 65, 66, 75

vapply, 69
vector, 55
Vectorize, 29

which.max, 41
which.max, mpfr-method (mpfr-class), 38
which.min, 41
which.min, mpfr-method (mpfr-class), 38

y0 (Bessel_mpfr), 10
y1 (Bessel_mpfr), 10
yn, 46
yn (Bessel_mpfr), 10
zeta, 5, 9, 42
zeta (mpfr-special-functions), 45