

Package: Rwbo (via r-universe)

May 21, 2026

Title Run the 'Open-WBO' MaxSAT Solver

Version 0.1.2

Description Provides a wrapper for running the bundled 'Open-WBO' Maximum Satisfiability (MaxSAT) solver (<https://github.com/sat-group/open-wbo>). Users can pass command-line arguments to the solver and capture its output as a character string or file.

License GPL (>= 3)

RoxygenNote 7.3.2

Encoding UTF-8

Depends R (>= 4.0)

Suggests testthat (>= 3.0)

Config/testthat/edition 3

NeedsCompilation yes

Author Matthias Ollech [aut, cre], Ruben Martins, Vasco Manquinho, Ines Lynce [cph] (Copyright holders of included Open-WBO code)

Maintainer Matthias Ollech <ollech@gmx.com>

Repository <https://cran.r-universe.dev>

Date/Publication 2026-01-21 07:40:09 UTC

RemoteUrl <https://github.com/cran/Rwbo>

RemoteRef HEAD

RemoteSha 354333fb61e354e0db53c17dd3b8b95f79065e49

Contents

run_open_wbo	2
Index	3

run_open_wbo

Run open-wbo_static

Description

Run the bundled ‘open-wbo_static’ binary with user-supplied parameters.

Usage

```
run_open_wbo(args = character())
```

Arguments

`args` Character vector of arguments passed to ‘open-wbo_static’.

Details

‘args’ is passed directly to the ‘open-wbo_static’ command-line tool, so supply the path to a WCNF file along with any solver flags you want to enable. To see the full list of supported options for your bundled binary, run ‘run_open_wbo(“-help”)’. The help text is emitted on stderr, so it appears in your console but is not returned by ‘run_open_wbo()’.

Common solver options include toggles such as ‘-forceunsat’/‘-no-forceunsat’, ‘-adapt’/‘-no-adapt’, ‘-print-model’/‘-no-print-model’, and parameter settings like ‘-algorithm <int>’, ‘-cpu-lim <int>’, ‘-mem-lim <int>’, and ‘-verbosity <int>’.

Value

Character string containing the output from ‘open-wbo_static’.

Examples

```
wcnf_file <- tempfile(fileext = ".wcnf")
writeLines(c(
  "p wcnf 1 2 2",
  "2 1 0",
  "1 -1 0"
), wcnf_file)
run_open_wbo(args = wcnf_file)
```

Index

run_open_wbo, [2](#)