

Package: SCMA (via r-universe)

August 22, 2024

Type Package

Title Single-Case Meta-Analysis

Version 1.3.1

Date 2019-12-20

Author Isis Bulte, Tamal Kumar De, Patrick Onghena

Maintainer Tamal Kumar De <tamalkumar.de@kuleuven.be>

Depends R (>= 2.11.1)

Description Perform meta-analysis of single-case experiments, including calculating various effect size measures (SMD, PND, PEM and NAP) and probability combining (additive and multiplicative method), as discussed in Bulte and Onghena (2013) <[doi:10.22237/jmasm/1383280020](https://doi.org/10.22237/jmasm/1383280020)>.

License GPL (>= 2)

Imports stats, utils

Repository CRAN

NeedsCompilation no

Date/Publication 2020-01-09 05:40:11 UTC

Contents

SCMA-package	2
AB	2
combine	3
ES	4
P	5

Index	6
--------------	----------

SCMA-package

Single-Case Meta-Analysis

Description

Perform meta-analysis of single-case experiments, including calculating various effect size measures (SMD, PND, PEM and NAP) and probability combining (additive and multiplicative method).

Details

Package: SCMA
Type: Package
Version: 1.3.1
Date: 2019-12-20
License: GPL version 2 or newer

Author(s)

Isis Bulte, Tamal Kumar De, Patrick Onghena

Maintainer: Tamal Kumar De <tamalkumar.de@kuleuven.be>

AB

Hypothetical AB data

Description

Hypothetical data collected in an AB phase design with 27 measurement times.

Usage

```
data(AB)
```

Format

A data frame with 27 observations.

- The first column contains the condition/phase labels ("A" and "B").
- The second column contains the obtained scores.
- The rows and columns are not labeled.

References

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

Examples

```
data(AB)
```

combine	<i>Statistical combination of p-values</i>
---------	--

Description

Calculates a general p-value by statistically combining the p-values of a number of independent studies, to determine whether a general significant result is obtained.

Usage

```
combine(method, pvalues = read.table(file.choose(new = FALSE)))
```

Arguments

method	Indicates which combining function should be used: "x" (multiplicative) or "+" (additive)
pvalues	File in which the p-values can be found. Default: a window pops up in which the appropriate file can be selected.

Details

When using the default 'pvalues' argument, a window will pop up to ask in what file the pvalues can be found. This text file containing the pvalues should consist of 1 column with all the obtained pvalues.

Author(s)

Isis Bulte

References

Bulte, I., & Onghena, P. (2008). An R package for single-case randomization tests. *Behavior Research Methods*, 40, 467-478.

Bulte, I., & Onghena, P. (2009). Randomization tests for multiple baseline designs: An extension of the SCRT-R package. *Behavior Research Methods*, 41, 477-485.

<http://ppw.kuleuven.be/cmcs/SCRT-R.html>

Examples

```
data(P)
combine(method="+", pvalues=P)
```

ES *measure of effect size*

Description

Calculates the specified effect size measure.

Usage

```
ES(design, ES, data = read.table(file.choose(new = FALSE)))
```

Arguments

design	Type of single-case design: "AB", "ABA", "ABAB", "CRD"(completely randomized design), "RBD" (randomized block design), "ATD" (alternating treatments design), "MBD" (multiple-baseline AB design) or "Custom" (user specified design).
ES	Type of effect size that has to be calculated: "SMD" (standardized mean difference), "SMDpool" (pooled standardized mean difference), "PND+" / "PND-" (percentage of nonoverlapping data, depending on the expected direction of the treatment effect), "PEM+" / "PEM-" (percentage of data points exceeding the median, depending on the expected direction of the treatment effect), or "NAP+" / "NAP-" (nonoverlap of all pairs, depending on the expected direction of the treatment effect).
data	File in which the data can be found. Default: a window pops up in which the appropriate file can be selected.

Details

When using the default 'data' argument, a window will pop up to ask in what file the data can be found. This text file containing the data should consist of two columns for single-case phase and alternation designs: the first with the condition labels and the second with the obtained scores.

For multiple-baseline designs, it should consist of these two columns for EACH unit. This way, each row represents one measurement occasion. It is important not to label the rows or columns.

Missing data should be indicated as NA. For calculations, missing data are omitted.

Author(s)

Isis Bulte

References

Bulte, I., & Onghena, P. (2008). An R package for single-case randomization tests. *Behavior Research Methods*, 40, 467-478.

Bulte, I., & Onghena, P. (2009). Randomization tests for multiple baseline designs: An extension of the SCRT-R package. *Behavior Research Methods*, 41, 477-485.

<http://ppw.kuleuven.be/cmcs/SCRT-R.html>

Examples

```
data(AB)
ES(design = "AB", ES = "SMD", data = AB)
```

P	<i>P-values</i>
---	-----------------

Description

Each p-value (i.e., each row) corresponds to one participant in the study.

Usage

```
data(P)
```

Format

A data frame with 7 observations on the following variable.

V1 P-value

Examples

```
data(P)
```

Index

- * **datasets**

- AB, [2](#)

- P, [5](#)

- * **meta-analysis**

- combine, [3](#)

- ES, [4](#)

- * **package**

- SCMA-package, [2](#)

- * **single-case designs**

- combine, [3](#)

- ES, [4](#)

AB, [2](#)

combine, [3](#)

ES, [4](#)

P, [5](#)

SCMA-package, [2](#)