Package: SIMplyBee (via r-universe)

October 20, 2026

Type Package

Title 'AlphaSimR' Extension for Simulating Honeybee Populations and Breeding Programmes

Version 0.4.1

Description An extension of the 'AlphaSimR' package (<https://cran.r-project.org/package=AlphaSimR>) for stochastic simulations of honeybee populations and breeding programmes. 'SIMplyBee' enables simulation of individual bees that form a colony, which includes a queen, fathers (drones the queen mated with), virgin queens, workers, and drones. Multiple colony can be merged into a population of colonies, such as an apiary or a whole country of colonies. Functions enable operations on castes, colony, or colonies, to ease 'R' scripting of whole populations. All 'AlphaSimR' functionality with respect to genomes and genetic and phenotype values is available and further extended for honeybees, including haplo-diploidy, complementary sex determiner locus, colony events (swarming, supersedure, etc.), and colony phenotype values.

URL https://github.com/HighlanderLab/SIMplyBee

License MIT + file LICENSE

Encoding UTF-8

Imports methods, R6, stats, utils, extraDistr (>= 1.9.1), RANN, Rcpp (>= 0.12.7)

Depends R (>= 3.3.0), AlphaSimR (>= 1.5.3)

LinkingTo Rcpp, RcppArmadillo (>= 0.7.500.0.0), BH

RoxygenNote 7.3.2

Suggests rmarkdown, knitr, ggplot2, testthat (>= 3.0.0), Matrix

Config/testthat/edition 3

Config/Needs/website tidyverse/tidytemplate

VignetteBuilder knitr

NeedsCompilation yes

Author Jana Obšteter [aut, cre]
(<https://orcid.org/0000-0003-1511-3916>), Laura Strachan [aut]
(<https://orcid.org/0000-0002-2569-0250>), Jernej Bubnič [aut]
(<https://orcid.org/0000-0003-1362-3736>), Gregor Gorjanc [aut]
(<https://orcid.org/0000-0001-8008-2787>)

Maintainer Jana Obšteter <obsteter.jana@gmail.com>

Repository https://cran.r-universe.dev

Date/Publication 2024-09-21 02:54:07 UTC

RemoteUrl https://github.com/cran/SIMplyBee

RemoteRef HEAD

RemoteSha e445fd722b99e832b714136cfbe867e9988bd28c

Contents

addCastePop 4
buildUp 6
c,NULLOrPop-method 9
calcBeeGRMIbd 9
calcBeeGRMIbs 11
calcColonyValue 13
calcInheritanceCriterion 15
calcPerformanceCriterion 17
calcQueensPHomBrood 19
calcSelectionCriterion 20
collapse 22
Colony-class 23
combine 25
combineBeeGametes 26
combineBeeGametesHaploDiploid 27
createCastePop 28
createColony 31
createCrossPlan 32
createDCA 34
createMatingStationDCA 36
createMultiColony 37
cross 38
downsize 42
downsizePUnif 43
editCsdLocus 44
getAa 45
getBv 46
getCaste 47
getCasteId 49
getCastePop 50
getCasteSex 53
getCsdAlleles 55

getCsdGeno . . . 58
getDd . . . 60
getEvents . . . 61
getGv . . . 62
getIbdHaplo . . . 64
getId . . . 68
getLocation . . . 69
getMisc . . . 70
getPheno . . . 71
getPooledGeno . . . 73
getQtlGeno . . . 74
getQtlHaplo . . . 77
getQueenAge . . . 80
getQueenYearOfBirth . . . 82
getSegSiteGeno . . . 83
getSegSiteHaplo . . . 85
getSnpGeno . . . 88
getSnpHaplo . . . 91
hasCollapsed . . . 95
hasSplit . . . 96
hasSuperseded . . . 97
hasSwarmed . . . 98
isCaste . . . 99
isCsdActive . . . 101
isCsdHeterozygous . . . 101
isDronesPresent . . . 102
isEmpty . . . 103
isFathersPresent . . . 104
isGenoHeterozygous . . . 105
isNULLColonies . . . 106
isProductive . . . 107
isQueenPresent . . . 108
isSimParamBee . . . 109
isVirginQueensPresent . . . 109
isWorkersPresent . . . 110
mapCasteToColonyValue . . . 111
mapLoci . . . 114
MultiColony-class . . . 115
nCaste . . . 118
nColonies . . . 120
nCsdAlleles . . . 121
nDronesPoisson . . . 123
nFathersPoisson . . . 125
nVirginQueensPoisson . . . 126
nWorkersPoisson . . . 128
pullCastePop . . . 130
pullColonies . . . 133
pullDroneGroupsFromDCA . . . 134

pullInd . . . 136
rcircle . . . 136
reduceDroneGeno . . . 137
reduceDroneHaplo . . . 138
removeCastePop . . . 139
removeColonies . . . 141
replaceCastePop . . . 142
reQueen . . . 144
resetEvents . . . 146
selectColonies . . . 148
setLocation . . . 150
setMisc . . . 151
setQueensYearOfBirth . . . 151
SimParamBee . . . 152
simulateHoneyBeeGenomes . . . 159
split . . . 161
splitPUnif . . . 162
supersede . . . 164
swarm . . . 166
swarmPUnif . . . 167

Index **169**

`addCastePop` *Add caste individuals to the colony*

Description

Level 2 function that adds (raises) the specified number of a specific caste individuals to a Colony or MultiColony object by producing offspring from a mated queen. If there are already some individuals present in the caste, new and present individuals are combined.

Usage

```
addCastePop(
  x,
  caste = NULL,
  nInd = NULL,
  new = FALSE,
  exact = FALSE,
  year = NULL,
  simParamBee = NULL,
  ...
)

addWorkers(x, nInd = NULL, new = FALSE, exact = FALSE, simParamBee = NULL, ...)

addDrones(x, nInd = NULL, new = FALSE, simParamBee = NULL, ...)
```

```
addVirginQueens(
  x,
  nInd = NULL,
  new = FALSE,
  year = NULL,
  simParamBee = NULL,
  ...
)
```

Arguments

x	Colony-class or MultiColony-class
caste	character, "workers", "drones", or "virginQueens"
nInd	numeric or function, number of workers to be added, but see new; if NULL then SimParamBee$nWorkers is used. If input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be used for all the colonies.
new	logical, should the number of individuals be added to the caste population anew or should we only top-up the existing number of individuals to nInd
exact	logical, only relevant when adding workers - if the csd locus is turned on and exact is TRUE, we add the exact specified number of viable workers (heterozygous at the csd locus)
year	numeric, only relevant when adding virgin queens - year of birth for virgin queens
simParamBee	SimParamBee, global simulation parameters
...	additional arguments passed to nInd when this argument is a function

Details

This function increases queen's nWorkers and nHomBrood counters.

Value

Colony-class or MultiColony-class with workers added

Functions

- addWorkers(): Add workers to a colony
- addDrones(): Add drones to a colony
- addVirginQueens(): Add virgin queens to a colony

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 5, nDrones = nFathersPoisson)

# Create and cross Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[4:5], n = 2)
apiary <- cross(apiary, drones = droneGroups[3:4])

#Here we show an example for workers, but same holds for drones and virgin queens!
# Add workers
addCastePop(colony, caste = "workers", nInd = 20)
# Or use a alias function
addWorkers(colony, nInd = 20)
# Same aliases exist for drones and virgin queens!

# If nInd is NULL, the functions uses the default in SP$nWorkers
# We can change this default
SP$nWorkers <- 15
nWorkers(addWorkers(colony))
# nVirginQueens/nWorkers/nDrones will NOT vary between function calls when a constant is used

# Specify a function that will give a number
nWorkers(addWorkers(colony, nInd = nWorkersPoisson))
nWorkers(addWorkers(colony, nInd = nWorkersPoisson))
# nVirginQueens/nWorkers/nDrones will vary between function calls when a function is used

# Store a function or a value in the SP object
SP$nWorkers <- nWorkersPoisson
(addWorkers(colony))
# nVirginQueens/nWorkers/nDrones will vary between function calls when a function is used

# Queen's counters
getMisc(getQueen(addWorkers(colony)))

# Add individuals to a MultiColony object
apiary <- addWorkers(apiary)
# Add different number of workers to colonies
nWorkers(addWorkers(apiary, nInd = c(50, 100)))
```

`buildUp` *Build up Colony or MultiColony object by adding (raising) workers and drones*

Description

Level 2 function that builds up a Colony or MultiColony object by adding (raising) workers and drones usually in spring or after events such as split or swarming.

Usage

```
buildUp(
  x,
  nWorkers = NULL,
  nDrones = NULL,
  new = TRUE,
  exact = FALSE,
  resetEvents = FALSE,
  simParamBee = NULL,
  ...
)
```

Arguments

x	Colony-class or MultiColony-class
nWorkers	numeric or function, number of worker to add to the colony, but see new; if NULL then SimParamBee$nWorkers is used. If input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies.
nDrones	numeric or function, number of drones to add to the colony, but see new; if NULL then SimParamBee$nDrones is used. If input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies.
new	logical, should the number of workers and drones be added anew or should we only top-up the existing number of workers and drones to nWorkers and nDrones (see details)
exact	logical, if the csd locus is turned on and exact is TRUE, create the exact specified number of only viable workers (heterozygous on the csd locus)
resetEvents	logical, call resetEvents as part of the build up
simParamBee	SimParamBee, global simulation parameters
...	additional arguments passed to nWorkers or nDrones when these arguments are a function

Details

This function increases queen's nWorkers, nHomBrood, and nDrones counters. It also turns production on.

Argument new enables simulation of two common cases. First, if you are modelling year-to-year cycle, you will likely want new = TRUE, so that, say, in spring you will replace old (from last year) workers and drones with the new ones. This is the case that we are targeting and hence new = TRUE is default. Second, if you are modelling shorter period cycles, you will likely want new = FALSE to

just top up the current workers and drones - you might also want to look at replaceWorkers and replaceDrones.

TODO: Discuss on how to model day-to-day variation with new = FALSE. We are not sure this is easy to achieve with current implementation just now, but could be expanded. https://github.com/HighlanderLab/SIMplyBee/issue

Value

Colony-class or MultiColony-class with workers and drones replaced or added

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
isProductive(colony)
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
isProductive(apiary)

# Build up
# Using defaults in SP$nWorkers & SP$nDrones
(colony <- buildUp(colony))
isProductive(colony)
# Build-up a MultiColony class
(apiary <- buildUp(apiary))
isProductive(apiary)

# The user can also specify a function that will give a number
colony <- removeWorkers(colony) # Remove workers to start from fresh
colony <- removeDrones(colony) # Remove drones to start from fresh
buildUp(colony, nWorkers = nWorkersPoisson, nDrones = nDronesPoisson)
buildUp(colony, nWorkers = nWorkersPoisson, nDrones = nDronesPoisson)
# nWorkers and nDrones will vary between function calls when a function is used
# You can store these functions or a values in the SP object
SP$nWorkers <- nWorkersPoisson
SP$nDrones <- nDronesPoisson

# Specifying own number
colony <- buildUp(colony, nWorkers = 100)
# Build up a MultiColony class
apiary <- buildUp(apiary, nWorkers = 250)
# Build up with different numbers
apiary <- buildUp(apiary, nWorkers = c(1000, 2000), nDrones = c(100, 150))
nWorkers(apiary)
```

```
nDrones(apiary)

# Queen's counters
getMisc(getQueen(buildUp(colony)))
```

`c,NULLOrPop-method` *Combine a NULL and AlphaSimR population*

Description

This combine `c()` method is a hack to combine NULL and an AlphaSimR population object `c(NULL, pop)` (`c(pop, NULL)` works already with AlphaSimR package code).

Usage

```
## S4 method for signature 'NULLOrPop'
c(x, ...)
```

Arguments

`x`	NULL or `Pop-class`
`...`	list of NULL or `Pop-class` objects

`calcBeeGRMIbd` *Calculate Genomic Relatedness Matrix (GRM) for honeybees from Identical By Descent genomic data*

Description

Level 0 function that returns Genomic Relatedness Matrix (GRM) for honeybees from Identical By Descent genomic data (tracked alleles since the founders) - see references on the background theory.

Usage

```
calcBeeGRMIbd(x)
```

Arguments

`x`	`matrix` of haplotypes/genomes with allele indicators for the founders coded as 1, 2, ... Haplotypes/genome are in rows and sites are in columns; no missing values are allowed (this is not checked!). Row names are essential (formated as ind_genome as returned by AlphaSimR IBD functions) to infer the individual and their ploidy (see examples)!

Value

a list with a matrix of gametic relatedness coefficients (genome) and a matrix of individual relatedness coefficients (indiv)

References

Grossman and Eisen (1989) Inbreeding, coancestry, and covariance between relatives for X-chromosomal loci. The Journal of Heredity, doi:10.1093/oxfordjournals.jhered.a110812

Fernando and Grossman (1989) Covariance between relatives for X-chromosomal loci in a population in disequilibrium. Theoretical and Applied Genetics, doi:10.1007/bf00305821

Fernando and Grossman (1990) Genetic evaluation with autosomal and X-chromosomal inheritance. Theoretical and Applied Genetics, doi:10.1007/bf00224018

Van Arendonk, Tier, and Kinghorn (1994) Use of multiple genetic markers in prediction of breeding values. Genetics, doi:10.1093/genetics/137.1.319

Hill and Weir (2011) Variation in actual relationship as a consequence of Mendelian sampling and linkage. Genetics Research, doi:10.1017/s0016672310000480

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

SP$setTrackRec(TRUE)
SP$setTrackPed(isTrackPed = TRUE)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 1, nDrones = nFathersPoisson)
colony <- createColony(basePop[2])
colony <- cross(x = colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)

haploQ <- getQueenIbdHaplo(colony)
haploW <- getWorkersIbdHaplo(colony)
haploD <- getDronesIbdHaplo(colony)
SP$pedigree

haplo <- rbind(haploQ, haploW, haploD)

GRMs <- calcBeeGRMIbd(x = haplo)
# You can visualise this matrix with the image() functions from the "Matrix" package

# Inspect the diagonal of the relationship matrix between individuals
x <- diag(GRMs$indiv)
hist(x)
summary(x)

 # Inspect the off-diagonal of the relationship matrix between individuals
x <- GRMs$indiv[lower.tri(x = GRMs$indiv, diag = FALSE)]
hist(x)
```

```
summary(x)

ids <- getCasteId(colony)
qI <- ids$queen
wI <- sort(ids$workers)
dI <- sort(ids$drones)

qG <- c(t(outer(X = qI, Y = 1:2, FUN = paste, sep = "_")))
wG <- c(t(outer(X = wI, Y = 1:2, FUN = paste, sep = "_")))
dG <- paste(dI, 1, sep = "_")

# Queen vs workers
GRMs$genome[wG, qG]
GRMs$indiv[wI, qI]

# Queen vs drones
GRMs$genome[dG, qG]
GRMs$indiv[dI, qI]

# Workers vs workers
GRMs$genome[wG, wG]
GRMs$indiv[wI, wI]

# Workers vs drones
GRMs$genome[dG, wG]
GRMs$indiv[dI, wI]
```

`calcBeeGRMIbs` *Calculate Genomic Relatedness Matrix (GRM) for honeybees from Identical By State genomic data*

Description

Level 0 function that returns Genomic Relatedness Matrix (GRM) for honeybees from Identical By State genomic data (bi-allelic SNP represented as allele dosages) following the method for the sex X chromosome (Druet and Legarra, 2020)

Usage

```
calcBeeGRMIbs(x, sex, alleleFreq = NULL)

calcBeeAlleleFreq(x, sex)
```

Arguments

x	matrix of genotypes represented as allele dosage coded as 0, 1, or 2 in females (queens or workers) and as 0 or 1 in males (fathers or drones); individuals are in rows and sites are in columns; no missing values are allowed (this is not checked - you will get NAs!)

sex	character vector denoting sex for individuals with genotypes in x - "F" for female and "M" for male
alleleFreq	numeric, vector of allele frequencies for the sites in x; if NULL, then calcBeeAlleleFreq is used

Value

matrix of genomic relatedness coefficients

Functions

- calcBeeAlleleFreq(): Calculate allele frequencies from honeybee genotypes

References

Druet and Legarra (2020) Theoretical and empirical comparisons of expected and realized relationships for the X-chromosome. Genetics Selection Evolution, 52:50 doi:10.1186/s12711020005706

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

SP$setTrackRec(TRUE)
SP$setTrackPed(isTrackPed = TRUE)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 1, nDrones = nFathersPoisson)
colony <- createColony(basePop[2])
colony <- cross(x = colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)

geno <- getSegSiteGeno(colony, collapse = TRUE)
sex <- getCasteSex(x = colony, collapse = TRUE)

GRM <- calcBeeGRMIbs(x = geno, sex = sex)
# You can visualise this matrix with the function image() from the package 'Matrix'

#Look at the diagonal at the relationship matrix
x <- diag(GRM)
hist(x)
summary(x)

#Look at the off-diagonal at the relationship matrix
x <- GRM[lower.tri(x = GRM, diag = FALSE)]
hist(x)
summary(x)

# Compare relationship between castes
ids <- getCasteId(colony)
idQueen <- ids$queen
```

```
idWorkers <- ids$workers
idDrones <- ids$drones

# Queen vs others
GRM[idQueen, idWorkers]
GRM[idQueen, idDrones]

# Workers vs worker
GRM[idWorkers, idWorkers]

# Workers vs drones
GRM[idWorkers, idDrones]

# Calculating allele frequencies ourselves (say, to "shift" base population)
aF <- calcBeeAlleleFreq(x = geno, sex = sex)
hist(aF)
GRM2 <- calcBeeGRMIbs(x = geno, sex = sex, alleleFreq = aF)
stopifnot(identical(GRM2, GRM))

# You can also create relationships with pooled genomes
pooledGenoW <- getPooledGeno(getWorkersSegSiteGeno(colony),
                             type = "mean",
                             sex = getCasteSex(colony, caste="workers"))
queenGeno <- getQueenSegSiteGeno(colony)
# Compute relationship between pooled workers genotype and the queen
calcBeeGRMIbs(x = rbind(queenGeno, pooledGenoW), sex = c("F","F"))
# You can now compare how this compare to relationships between the queen
# individual workers!
```

`calcColonyValue` *Calculate colony value(s)*

Description

Level 0 function that calculate value(s) of a colony.

Usage

```
calcColonyValue(x, FUN = NULL, simParamBee = NULL, ...)

calcColonyPheno(x, FUN = mapCasteToColonyPheno, simParamBee = NULL, ...)

calcColonyGv(x, FUN = mapCasteToColonyGv, simParamBee = NULL, ...)

calcColonyBv(x, FUN = mapCasteToColonyBv, simParamBee = NULL, ...)

calcColonyDd(x, FUN = mapCasteToColonyDd, simParamBee = NULL, ...)

calcColonyAa(x, FUN = mapCasteToColonyAa, simParamBee = NULL, ...)
```

Arguments

x	Colony-class or MultiColony-class
FUN	function, that calculates colony value from values of colony members
simParamBee	SimParamBee, global simulation parameters
...	other arguments of FUN

Value

a matrix with one value or a row of values when x is Colony-class and a row-named matrix when x is MultiColony-class, where names are colony IDs

Functions

- calcColonyPheno(): Calculate colony phenotype value from caste individuals' phenotype values
- calcColonyGv(): Calculate colony genetic value from caste individuals' genetic values
- calcColonyBv(): Calculate colony breeding value from caste individuals' breeding values
- calcColonyDd(): Calculate colony dominance value from caste individuals' dominance values
- calcColonyAa(): Calculate colony epistasis value from caste individuals' epistasis value

See Also

mapCasteToColonyValue as an example of FUN, selectColonies for example for to select colonies based on these values, and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)


# Define two traits that collectively affect colony honey yield:
# 1) queen's effect on colony honey yield, say via pheromone secretion phenotype
# 2) workers' effect on colony honey yield, say via foraging ability phenotype
# The traits will have a negative genetic correlation of -0.5 and heritability
# of 0.25 (on an individual level)
nWorkers <- 10
mean <- c(10, 10 / nWorkers)
varA <- c(1, 1 / nWorkers)
corA <- matrix(data = c(
  1.0, -0.5,
  -0.5, 1.0
), nrow = 2, byrow = TRUE)
varE <- c(3, 3 / nWorkers)
varA / (varA + varE)
SP$addTraitADE(nQtlPerChr = 100,
               mean = mean,
```

```
                var = varA, corA = corA,
                meanDD = 0.1, varDD = 0.2, corD = corA,
                relAA = 0.1, corAA = corA)
SP$setVarE(varE = varE)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 200)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create and cross Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(colony, nWorkers = nWorkers, nDrones = 3)
apiary <- createMultiColony(basePop[3:5], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(apiary, nWorkers = nWorkers, nDrones = 3)

# Colony value - shorthand version
# (using the default mapCasteToColony*() functions - you can provide yours instead!)
# Phenotype value
calcColonyPheno(colony)
calcColonyPheno(apiary)
# Genetic value
calcColonyGv(colony)
calcColonyGv(apiary)

# Colony value - long version
# (using the default mapCasteToColony*() function - you can provide yours instead!)
calcColonyValue(colony, FUN = mapCasteToColonyPheno)
calcColonyValue(apiary, FUN = mapCasteToColonyPheno)

# Colony value - long version - using a function stored in SimParamBee (SP)
# (using the default mapCasteToColony*() function - you can provide yours instead!)
SP$colonyValueFUN <- mapCasteToColonyPheno
calcColonyValue(colony)
calcColonyValue(apiary)
```

`calcInheritanceCriterion` *Calculate the inheritance criterion*

Description

Level 0 function that calculates the inheritance criterion as the sum of the queen (maternal) and workers (direct) effect from the queen, as defined by Du et al. (2021). This can be seen as the expected value of drones from the queen or half the expected value of virgin queens from the queen.

Usage

```
calcInheritanceCriterion(
  x,
  queenTrait = 1,
  workersTrait = 2,
  use = "gv",
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class or MultiColony-class
queenTrait	numeric (column position) or character (column name), trait that represents queen's effect on the colony value; if NULL then this effect is 0
workersTrait	numeric (column position) or character (column name), trait that represents workers' effect on the colony value; if NULL then this effect is 0
use	character, the measure to use for the calculation, being either "gv" (genetic value), "ebv" (estimated breeding value), or "pheno" (phenotypic value)
simParamBee	SimParamBee, global simulation parameters

Value

integer when x is Colony-class and a named list when x is MultiColony-class, where names are colony IDs

References

Du, M., et al. (2021) Short-term effects of controlled mating and selection on the genetic variance of honeybee populations. Heredity 126, 733–747. doi:10.1038/s41437021004112

See Also

calcSelectionCriterion and calcPerformanceCriterion and as well as vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

meanA <- c(10, 10 / SP$nWorkers)
varA <- c(1, 1 / SP$nWorkers)
corA <- matrix(data = c( 1.0, -0.5,
                        -0.5,  1.0), nrow = 2, byrow = TRUE)
SP$addTraitA(nQtlPerChr = 100, mean = meanA, var = varA, corA = corA,
name = c("queenTrait", "workersTrait"))
varE <- c(3, 3 / SP$nWorkers)
corE <- matrix(data = c(1.0, 0.3,
                        0.3, 1.0), nrow = 2, byrow = TRUE)
```

```
SP$setVarE(varE = varE, corE = corE)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

calcInheritanceCriterion(colony, queenTrait = 1, workersTrait = 2)
calcInheritanceCriterion(apiary, queenTrait = 1, workersTrait = 2)

apiary[[2]] <- removeQueen(apiary[[2]])
calcInheritanceCriterion(apiary, queenTrait = 1, workersTrait = 2)
```

`calcPerformanceCriterion` *Calculate the performance criterion*

Description

Level 0 function that calculates the performance criterion as the sum of the queen (maternal) effect from the queen and the workers (direct) effect from her workers, as defined by Du et al. (2021). This can be seen as the expected value of the colony.

Usage

```
calcPerformanceCriterion(
  x,
  queenTrait = 1,
  workersTrait = 2,
  workersTraitFUN = sum,
  use = "gv",
  simParamBee = NULL
)
```

Arguments

x	Colony-class or MultiColony-class
queenTrait	numeric (column position) or character (column name), trait that represents queen's effect on the colony value; if NULL then this effect is 0
workersTrait	numeric (column position) or character (column name), trait that represents workers' effect on the colony value; if NULL then this effect is 0

workersTraitFUN
: function, that will be applied to the workers effect values of workers, default is sum (see examples), but note that the correct function will depend on how you will setup simulation!

use
: character, the measure to use for the calculation, being either "gv" (genetic value),"ebv" (estimated breeding value), or "pheno" (phenotypic value)

simParamBee
: SimParamBee, global simulation parameters

Value

integer when x is Colony-class and a named list when x is MultiColony-class, where names are colony IDs

References

Du, M., et al. (2021) Short-term effects of controlled mating and selection on the genetic variance of honeybee populations. Heredity 126, 733–747. doi:10.1038/s41437021004112

See Also

calcSelectionCriterion and calcInheritanceCriterion and as well as vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

meanA <- c(10, 10 / SP$nWorkers)
varA <- c(1, 1 / SP$nWorkers)
corA <- matrix(data = c( 1.0, -0.5,
                        -0.5,  1.0), nrow = 2, byrow = TRUE)
SP$addTraitA(nQtlPerChr = 100, mean = meanA, var = varA, corA = corA,
name = c("queenTrait", "workersTrait"))
varE <- c(3, 3 / SP$nWorkers)
corE <- matrix(data = c(1.0, 0.3,
                        0.3, 1.0), nrow = 2, byrow = TRUE)
SP$setVarE(varE = varE, corE = corE)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(colony)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(apiary)
```

```
calcPerformanceCriterion(colony, queenTrait = 1, workersTrait = 2, workersTraitFUN = sum)
calcPerformanceCriterion(apiary, queenTrait = 1, workersTrait = 2, workersTraitFUN = sum)

apiary[[2]] <- removeQueen(apiary[[2]])
calcPerformanceCriterion(apiary, queenTrait = 1,
                         workersTrait = 2, workersTraitFUN = sum)
```

`calcQueensPHomBrood` *The expected proportion and a realised number of csd homozygous brood*

Description

Level 0 functions that calculate or report the proportion of csd homozygous brood of a queen or a colony. The csd locus determines viability of fertilised eggs (brood) - homozygous brood is removed by workers. These functions 1) calculate the expected proportion of homozygous brood from the csd allele of the queen and fathers, 2) report the expected proportion of homozygous brood, or 3) report a realised number of homozygous brood due to inheritance process. See `vignette(package = "SIMplyBee")` for more details.

Usage

```
calcQueensPHomBrood(x, simParamBee = NULL)

pHomBrood(x, simParamBee = NULL)

nHomBrood(x, simParamBee = NULL)
```

Arguments

`x`	`Pop-class`, `Colony-class`, or `MultiColony-class`
`simParamBee`	`SimParamBee`, global simulation parameters

Value

numeric, expected csd homozygosity named by colony id when `x` is `MultiColony-class`

Functions

- `pHomBrood()`: Expected percentage of csd homozygous brood of a queen / colony
- `nHomBrood()`: Realised number of csd homozygous brood produced by a queen

See Also

Demo in the introductory vignette `vignette("Honeybee_biology", package="SIMplyBee")`

Examples

```
# This is a bit long example - the key is at the end!
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 120, nDrones = 20)
colony <- addVirginQueens(x = colony, nInd = 1)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10)

# Virgin queen
try(calcQueensPHomBrood(basePop[5]))

# Queens of colony
calcQueensPHomBrood(colony)

# Queens of apiary
calcQueensPHomBrood(apiary)

# Inbreed virgin queen with her brothers to generate csd homozygous brood
colony2 <- createColony(x = getVirginQueens(colony))
colony2 <- cross(x = colony2, drones = pullDrones(x = colony, nInd = nFathersPoisson())[[1]])

# Calculate the expected csd homozygosity
calcQueensPHomBrood(getQueen(colony2))
pHomBrood(colony2)

# Evaluate a realised csd homozygosity
nHomBrood(addWorkers(colony2, nInd = 100))
nHomBrood(addWorkers(colony2, nInd = 100))
# nHomBrood will vary between function calls due to inheritance process
```

`calcSelectionCriterion` *Calculate the selection criterion*

Description

Level 0 function that calculates the selection criterion as the sum of workers (direct) and queen (maternal) effects of workers, as defined by Du et al. (2021). This can be seen as the expected value of virgin queens from the queen (as well as workers, but we would not be selecting workers).

Usage

```
calcSelectionCriterion(
  x,
  queenTrait = 1,
  queenTraitFUN = sum,
  workersTrait = 2,
  workersTraitFUN = sum,
  use = "gv",
  simParamBee = NULL
)
```

Arguments

x	Colony-class or MultiColony-class
queenTrait	numeric (column position) or character (column name), trait that represents queen's effect on the colony value; if NULL then this contribution is 0
queenTraitFUN	function, that will be applied to the queen effect values of workers, default is sum (see examples), but note that the correct function will depend on how you will setup simulation!
workersTrait	numeric (column position) or character (column name), trait that represents workers' effect on the colony value; if NULL then this contribution is 0
workersTraitFUN	function, that will be applied to the workers effect values of workers, default is sum (see examples), but note that the correct function will depend on how you will setup simulation!
use	character, the measure to use for the calculation, being either "gv" (genetic value), "ebv" (estimated breeding value), or "pheno" (phenotypic value)
simParamBee	SimParamBee, global simulation parameters

Value

integer when x is Colony-class and a named list when x is MultiColony-class, where names are colony IDs

References

Du, M., et al. (2021) Short-term effects of controlled mating and selection on the genetic variance of honeybee populations. Heredity 126, 733–747. doi:10.1038/s41437021004112

See Also

calcInheritanceCriterion and calcPerformanceCriterion and as well as

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)
```

```
meanA <- c(10, 10 / SP$nWorkers)
varA <- c(1, 1 / SP$nWorkers)
corA <- matrix(data = c( 1.0, -0.5,
                         -0.5,  1.0), nrow = 2, byrow = TRUE)
SP$addTraitA(nQtlPerChr = 100, mean = meanA, var = varA, corA = corA,
name = c("queenTrait", "workersTrait"))
varE <- c(3, 3 / SP$nWorkers)
corE <- matrix(data = c(1.0, 0.3,
                         0.3, 1.0), nrow = 2, byrow = TRUE)
SP$setVarE(varE = varE, corE = corE)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(colony)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(apiary)

calcSelectionCriterion(colony,
                       queenTrait = 1, queenTraitFUN = sum,
                       workersTrait = 2, workersTraitFUN = sum)
calcSelectionCriterion(apiary,
                       queenTrait = 1, queenTraitFUN = sum,
                       workersTrait = 2, workersTraitFUN = sum)

apiary[[2]] <- removeQueen(apiary[[2]])
calcSelectionCriterion(apiary, queenTrait = 1,
                       workersTrait = 2, workersTraitFUN = sum)
```

`collapse` *Collapse*

Description

Level 2 function that collapses a Colony or MultiColony object by setting the collapse event slot to `TRUE`. The production status slot is also changed (to `FALSE`).

Usage

```
collapse(x)
```

Arguments

x	Colony-class or MultiColony-class

Details

You should use this function in an edge-case when you want to indicate that the colony has collapsed, but you still want to collect some values from the colony for a retrospective analysis. It resembles a situation where the colony has collapsed, but dead bees are still in the hive.

Value

Colony-class or MultiColony-class with the collapse event set to TRUE

Examples

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)

# Create Colony and MultiColony class
colony <- createColony(x = basePop[1])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(x = basePop[2:10], n = 9)
apiary <- cross(apiary, drones = droneGroups[2:10])

# Collapse
hasCollapsed(colony)
colony <- collapse(colony)
hasCollapsed(colony)

hasCollapsed(apiary)
tmp <- pullColonies(apiary, n = 2)
tmp
apiaryLost <- collapse(tmp$pulled)
hasCollapsed(apiaryLost)
apiaryLeft <- tmp$remnant
hasCollapsed(apiaryLeft)
```

Colony-class *Honeybee colony*

Description

An object holding honeybee colony

Usage

```
isColony(x)

## S4 method for signature 'Colony'
show(object)

## S4 method for signature 'ColonyOrNULL'
c(x, ...)
```

Arguments

x	Colony-class
object	Colony-class
...	NULL, Colony-class, or MultiColony-class

Value

Colony-class or MultiColony-class

Functions

- isColony(): Test if x is a Colony class object
- show(Colony): Show colony object
- c(ColonyOrNULL): Combine multiple colony objects

Slots

id integer, unique ID of the colony

location numeric, location of the colony (x, y)

queen Pop-class, the queen of the colony (we use its misc slot for queen's age and drones (fathers) she mated with)

virginQueens Pop-class, virgin queens of the colony

drones Pop-class, drones of the colony

workers Pop-class, workers of the colony

split logical, has colony split

swarm logical, has colony swarmed

supersedure logical, has colony superseded

collapse logical, has colony collapsed

production logical, is colony productive

misc list, available for storing extra information about the colony

See Also

createColony

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)
colony1 <- createColony(x = basePop[2])
colony1 <- cross(colony1, drones = droneGroups[[1]])
colony2 <- createColony(x = basePop[3])
colony2 <- cross(colony2, drones = droneGroups[[2]])
colony3 <- createColony(x = basePop[4])
colony3 <- cross(colony3, drones = droneGroups[[3]])

colony1
show(colony1)
is(colony1)
isColony(colony1)

apiary <- c(colony1, colony2)
is(apiary)
isMultiColony(apiary)

c(apiary, colony3)
c(colony3, apiary)
```

---

combine *Combine two colony objects*

Description

Level 2 function that combines two Colony or MultiColony objects into one or two colonies objects of the same length to one. For example, to combine a weak and a strong colony (or MultiColony). Workers and drones of the weak colony are added to the strong. User has to remove the weak colony (or MultiColony) from the workspace.

Usage

```
combine(strong, weak)
```

Arguments

strong	Colony-class or MultiColony-class
weak	Colony-class or MultiColony-class

Value

a combined Colony-class or MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)

# Create weak and strong Colony and MultiColony class
colony1 <- createColony(x = basePop[2])
colony1 <- cross(colony1, drones = droneGroups[[1]])
colony2 <- createColony(x = basePop[3])
colony2 <- cross(colony2, drones = droneGroups[[2]])
apiary1 <- createMultiColony(basePop[4:6], n = 3)
apiary1 <- cross(apiary1, drones = droneGroups[3:5])
apiary2 <- createMultiColony(basePop[7:9], n = 3)
apiary2 <- cross(apiary2, drones = droneGroups[6:8])

# Build-up
colony1 <- buildUp(x = colony1, nWorkers = 100, nDrones = 20)
colony2 <- buildUp(x = colony2, nWorkers = 20, nDrones = 5)
apiary1 <- buildUp(x = apiary1, nWorkers = 100, nDrones = 20)
apiary2 <- buildUp(x = apiary2, nWorkers = 20, nDrones = 5)

# Combine
nWorkers(colony1); nWorkers(colony2)
nDrones(colony1); nDrones(colony2)
colony1 <- combine(strong = colony1, weak = colony2)
nWorkers(colony1); nWorkers(colony2)
nDrones(colony1); nDrones(colony2)
rm(colony2)

nWorkers(apiary1); nWorkers(apiary2)
nDrones(apiary1); nDrones(apiary2)
apiary1 <- combine(strong = apiary1, weak = apiary2)
nWorkers(apiary1); nWorkers(apiary2)
nDrones(apiary1); nDrones(apiary2)
rm(apiary2)
```

`combineBeeGametes` *Create diploid gametes from a mated queen*

Description

Level 1 function that produces diploid offspring from a mated queen. Queen is diploid, while drones are double haploids so we use AlphaSimR diploid functionality to make this cross, but since drones are double haploids we get the desired outcome. This is an utility function, and you most likely want to use the `cross` functions.

Usage

```
combineBeeGametes(queen, drones, nProgeny = 1, simParamBee = NULL)
```

Arguments

queen	Pop-class, with a single diploid individual
drones	Pop-class, with one or more diploid (double haploid) individual(s)
nProgeny	integer, number of progeny to create per cross
simParamBee	SimParamBee, global simulation parameters

Value

Pop-class with diploid individuals

Not exporting this function, since its just a helper

---

combineBeeGametesHaploDiploid

Create diploid gametes from a mated queen

Description

Level 1 function that produces diploid offspring from a mated queen. Drones are haploid, while the queen is diploid, so we first generate gametes (with recombination) from her and merge them with drone genomes (=gametes), where we randomly re-sample drones to get the desired number of progeny. This is an utility function, and you most likely want to use the cross function.

Usage

```
combineBeeGametesHaploDiploid(queen, drones, nProgeny = 1, simParamBee = NULL)
```

Arguments

queen	Pop-class, with a single diploid individual
drones	Pop-class, with one or more haploid individual(s)
nProgeny	integer, number of progeny to create per cross
simParamBee	SimParamBee, global simulation parameters

Details

This would be the right approach to handle haplo-diploid inheritance in bees, but it causes a raft of downstream issues, since AlphaSimR assumes that individuals have the same ploidy. Hence, we don't use this function.

Value

Pop-class with diploid individuals

createCastePop *Creates caste population individuals from the colony*

Description

Level 1 function that creates the specified number of caste individuals from the colony with a mated queens. If csd locus is active, it takes it into account and any csd homozygotes are removed and counted towards homozygous brood.

Usage

```
createCastePop(
  x,
  caste = NULL,
  nInd = NULL,
  exact = TRUE,
  year = NULL,
  editCsd = TRUE,
  csdAlleles = NULL,
  simParamBee = NULL,
  ...
)

createWorkers(x, nInd = NULL, exact = FALSE, simParamBee = NULL, ...)

createDrones(x, nInd = NULL, simParamBee = NULL, ...)

createVirginQueens(
  x,
  nInd = NULL,
  year = NULL,
  editCsd = TRUE,
  csdAlleles = NULL,
  simParamBee = NULL,
  ...
)
```

Arguments

x	link[AlphaSimR]{MapPop-class} (only if caste is "virginQueens"), or Pop (only if caste is "drones") or Colony-class or MultiColony-class
caste	character, "workers", "drones", or "virginQueens"
nInd	numeric or function, number of caste individuals; if NULL then SimParamBee$nWorkers, SimParamBee$nDrones or SimParamBee$nVirginQueens is used depending on the caste; only used when x is Colony-class or MultiColony-class, when x is link[AlphaSimR]{MapPop-class} all individuals in x are converted into virgin queens

exact	logical, only relevant when creating workers, if the csd locus is active and exact is TRUE, create the exactly specified number of viable workers (heterozygous on the csd locus)
year	numeric, year of birth for virgin queens
editCsd	logical (only active when x is link[AlphaSimR]{MapPop-class}), whether the csd locus should be edited to ensure heterozygosity at the csd locus (to get viable virgin queens); see csdAlleles
csdAlleles	NULL or list (only active when x is link[AlphaSimR]{MapPop-class}); If NULL, then the function samples a heterozygous csd genotype for each virgin queen from all possible csd alleles. If not NULL, the user provides a list of length nInd with each node holding a matrix or a data.frame, each having two rows and n columns. Each row must hold one csd haplotype (allele) that will be assigned to a virgin queen. The n columns span the length of the csd locus as specified in SimParamBee. The two csd alleles must be different to ensure heterozygosity at the csd locus.
simParamBee	SimParamBee, global simulation parameters
...	additional arguments passed to nInd when this argument is a function

Value

when x is MapPop-class returns virginQueens (a Pop-class); when x is Colony-class returns virginQueens (a Pop-class); when x is MultiColony-class return is a named list of virginQueens (a Pop-class); named by colony ID

Functions

- createWorkers(): Create workers from a colony
- createDrones(): Create drones from a colony
- createVirginQueens(): Create virgin queens from a colony

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$setTrackRec(TRUE)
SP$setTrackPed(isTrackPed = TRUE)

# Create virgin queens on a MapPop
basePop <- createCastePop(founderGenomes, caste = "virginQueens")
# Or alias
createVirginQueens(founderGenomes)
# Same aliases exist for all the castes!!!

# Create drones on a Pop
drones <- createDrones(x = basePop[1],  nInd = 200)
# Or create unequal number of drones from multiple virgin queens
drones <- createDrones(basePop[1:2], nInd = c(100, 200))
```

```
droneGroups <- pullDroneGroupsFromDCA(drones, n = 3, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

# Using default nInd in SP
colony@virginQueens <- createVirginQueens(colony)
colony@workers <- createWorkers(colony)$workers
colony@drones <- createDrones(colony)
# Usually, you would use functions buildUp() or addCastePop()

# These populations hold individual information
# Example on the virgin queens (same holds for all castes!)
virginQueens <- colony@virginQueens
virginQueens@id
virginQueens@sex
virginQueens@mother
virginQueens@father

# Specify own number
SP$nVirginQueens <- 15
SP$nWorkers <- 100
SP$nDrones <- 10
createVirginQueens(colony)
createVirginQueens(apiary)
# Or creating unequal numbers
createVirginQueens(apiary, nInd = c(5, 10))
# nVirginQueens will NOT vary between function calls when a constant is used

# Specify a function that will give a number
createVirginQueens(colony, nInd = nVirginQueensPoisson)
createVirginQueens(apiary, nInd = nVirginQueensPoisson)
# No. of individuals will vary between function calls when a function is used

# Store a function or a value in the SP object
SP$nVirginQueens <- nVirginQueensPoisson
createVirginQueens(colony)
createVirginQueens(colony)
createVirginQueens(apiary)
createVirginQueens(apiary)
# No. of individuals will vary between function calls when a function is used

# csd homozygosity - relevant when creating virgin queens
SP <- SimParamBee$new(founderGenomes, csdChr = 1, nCsdAlleles = 8)

basePop <- createVirginQueens(founderGenomes, editCsd = FALSE)
all(isCsdHeterozygous(basePop))

basePop <- createVirginQueens(founderGenomes, editCsd = TRUE)
all(isCsdHeterozygous(basePop))
```

createColony *Create a new Colony*

Description

Level 2 function that creates a new Colony-class to initiate simulations.

Usage

```
createColony(x = NULL, simParamBee = NULL)
```

Arguments

x	Pop-class, one queen or virgin queen(s)
simParamBee	SimParamBee, global simulation parameters

Value

new Colony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 15)

# Create an empty Colony class
colony <- createColony()

# Create Colony class with one or multiple virgin queens
colony1 <- createColony(x = basePop[2])
colony1
colony2 <- createColony(x = basePop[3:4])
colony2

# Create a mated Colony
colony1 <- cross(colony1, drones = drones)
colony1
```

createCrossPlan *Create a plan for crossing virgin queens*

Description

Level 0 function that creates a plan for crossing virgin queens or virgin colonies by sampling drones or drone producing colonies to mate with a the virgin queens/colonies either at random (`spatial = FALSE`) or according to the distance between colonies (`spatial = TRUE`).

Usage

```
createCrossPlan(
  x,
  drones = NULL,
  droneColonies = NULL,
  nDrones = NULL,
  spatial = FALSE,
  radius,
  simParamBee = NULL,
  ...
)
```

Arguments

x	Pop-class or Colony-class or MultiColony-class, the object with the virgin queens that need to be crossed. When `spatial = TRUE`, the argument needs to be a Colony-class or MultiColony-class with the location set
drones	Pop-class, a population of drones (resembling a drone congregation area) available for mating. When `spatial = TRUE`, the user can not provide drones, but needs to provide drone producing colonies instead (see argument `droneColonies`)
droneColonies	MultiColony-class, drone producing colonies available for mating. When `spatial = TRUE`, the object needs to have the location set
nDrones	integer or function, number of drones to sample for each crossing. You need to provide this to provide this argument even when sampling drone producing colonies (otherwise, the default value will be used)
spatial	logical, whether the drone producing colonies should be sampled according to their distance from the virgin colony (that is, in a radius)
radius	numeric, the radius from the virgin colony in which to sample mating partners, only needed when `spatial = TRUE`
simParamBee	SimParamBee, global simulation parameters
...	other arguments for `nDrones`, when `nDrones` is a function

Value

named list with names being virgin queens/colonies IDs with each list element holding the IDs of selected drones or drone producing colonies

Examples

```
founderGenomes <- quickHaplo(nInd = 1000, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

# Create three virgin MultiColony objects with locations
virginColonies1 <- createMultiColony(basePop[1:30])
virginColonies1 <- setLocation(virginColonies1,
                               location = Map(c, runif(30, 0, 2*pi),
                                              runif(30, 0, 2*pi)))
virginColonies2 <- createMultiColony(basePop[31:60])
virginColonies2 <- setLocation(virginColonies2,
                               location = Map(c, runif(30, 0, 2*pi),
                                              runif(30, 0, 2*pi)))
virginColonies3 <- createMultiColony(basePop[61:90])
virginColonies3 <- setLocation(virginColonies3,
                               location = Map(c, runif(30, 0, 2*pi),
                                              runif(30, 0, 2*pi)))

# Create drone colonies
droneColonies <- createMultiColony(basePop[121:200])
droneColonies <- setLocation(droneColonies,
                             location = Map(c, runif(80, 0, 2*pi),
                                            runif(80, 0, 2*pi)))

# Create some drones to mate initial drone colonies with
DCA <- createDrones(basePop[201:300], nInd = 20)
# Cross initial virgin drone colonies to the DCA with a random cross plan
randomCrossPlan <- createCrossPlan(x = droneColonies,
                                   drones = DCA,
                                   nDrones = nFathersPoisson,
                                   spatial = FALSE)
droneColonies <- cross(droneColonies,
                       drones = DCA,
                       nDrones = nFathersPoisson,
                       crossPlan = randomCrossPlan)

# Plot the colonies in space
virginLocations <- as.data.frame(getLocation(c(virginColonies1, virginColonies2, virginColonies3),
                                             collapse= TRUE))
virginLocations$Type <- "Virgin"
droneLocations <- as.data.frame(getLocation(droneColonies, collapse= TRUE))
droneLocations$Type <- "Drone"
locations <- rbind(virginLocations, droneLocations)

plot(x = locations$V1, y = locations$V2,
     col = c("red", "blue")[as.numeric(as.factor(locations$Type))])

# Cross according to a spatial cross plan according to the colonies' locations
crossPlanSpatial <- createCrossPlan(x = virginColonies1,
                                   droneColonies = droneColonies,
```

```
                                    nDrones = nFathersPoisson,
                                    spatial = TRUE,
                                    radius = 1.5)

# Plot the crossing for the first colony in the crossPlan
virginLocations1 <- as.data.frame(getLocation(virginColonies1, collapse= TRUE))
virginLocations1$Type <- "Virgin"
droneLocations <- as.data.frame(getLocation(droneColonies, collapse= TRUE))
droneLocations$Type <- "Drone"
locations1 <- rbind(virginLocations1, droneLocations)

# Blue marks the target virgin colony and blue marks the drone colonies in the chosen radius
plot(x = locations1$V1, y = locations1$V2, pch = c(1, 2)[as.numeric(as.factor(locations1$Type))],
  col = ifelse(rownames(locations1) %in% crossPlanSpatial[[1]],
                              "red",
                             ifelse(rownames(locations1) == names(crossPlanSpatial)[[1]],
                              "blue", "black")))

colonies1 <- cross(x = virginColonies1,
                   crossPlan = crossPlanSpatial,
                   droneColonies = droneColonies,
                   nDrones = nFathersPoisson)
nFathers(colonies1)

# Cross according to a cross plan that is created internally within the cross function
# The cross plan is created at random, regardless the location of the colonies
colonies2 <- cross(x = virginColonies2,
                   droneColonies = droneColonies,
                   nDrones = nFathersPoisson,
                   crossPlan = "create")

# Mate spatially with cross plan created internally by the cross function
colonies3 <- cross(x = virginColonies3,
                   droneColonies = droneColonies,
                   crossPlan = "create",
                   checkCross = "warning",
                   spatial = TRUE,
                   radius = 1)
```

`createDCA` *Create a drone congregation area (DCA)*

Description

Level 1 function that creates a population of drones from a Colony or MultiColony. Such a population is often referred to as a drone congregation area (DCA).

Usage

```
createDCA(x, nInd = NULL, removeFathers = TRUE, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
nInd	numeric, number of random drones to pull from each colony, if NULL all drones in a colony are pulled
removeFathers	logical, removes drones that have already mated; set to FALSE if you would like to get drones for mating with multiple virgin queens, say via insemination
simParamBee	SimParamBee, global simulation parameters

Details

In reality, drones leave the colony to mate. They die after that. In this function we only get a copy of drones from x, for computational efficiency and ease of use. However, any mating will change the caste of drones to fathers, and they won't be available for future matings (see cross). Not unless removeFathers = FALSE.

Value

Pop-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

colony <- addDrones(colony, nInd = 10)
createDCA(colony)
createDCA(colony, nInd = 10)@id

apiary <- addDrones(apiary)
createDCA(apiary)
createDCA(apiary, nInd = 10)
```

createMatingStationDCA *Create a DCA of drones at a mating stations*

Description

Level 1 function that creates a DCA at a classical honeybee mating station of several sister drone producing queens. The functions first creates multiple drone producing queens (DPQs) from one colony; and second, produces drones from the DPQs. All the created drones form a DCA at a mating station.

Usage

```
createMatingStationDCA(
  colony,
  nDPQs = 20,
  nDronePerDPQ = NULL,
  simParamBee = NULL
)
```

Arguments

colony	Colony-class to produce drone producing queens from
nDPQs	integer, the number of drone producing queens
nDronePerDPQ	integer, number of drones each DPQ contributed to the DCA
simParamBee	SimParamBee, global simulation parameters

Value

Pop-class with created drones resembling a DCA at a mating station

Examples

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)

# Create a colony and cross it
colony1 <- createColony(x = basePop[2])
colony1 <- cross(colony1, drones = droneGroups[[1]])

# Create a empty colony
colony2 <- createColony(x = basePop[3])

# Create a mating station from colony1
```

```
matingStation <- createMatingStationDCA(colony1, nDPQs = 20, nDronePerDPQ = 10)

# Cross colony2 on the mating station
fathers <- pullDroneGroupsFromDCA(matingStation, n = 1, nDrones = 15)
colony2 <- cross(colony2, drones = fathers[[1]])
nFathers(colony2)
```

`createMultiColony` *Create MultiColony object*

Description

Level 3 function that creates a set of colonies. Usually to start a simulation.

Usage

```
createMultiColony(x = NULL, n = NULL, simParamBee = NULL)
```

Arguments

x	Pop-class, virgin queens or queens for the colonies (selected at random if there are more than n in Pop, while all are used when n is NULL)
n	integer, number of colonies to create (if only n is given then MultiColony-class is created with n NULL) individual colony - this is mostly useful for programming)
simParamBee	SimParamBee, global simulation parameters

Details

When both x and n are NULL, then a MultiColony-class with 0 colonies is created.

Value

MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

# Create 2 empty (NULL) colonies
apiary <- createMultiColony(n = 2)
apiary
apiary[[1]]
apiary[[2]]
```

```
# Create 3 virgin colonies
apiary <- createMultiColony(x = basePop, n = 3) # specify n
apiary <- createMultiColony(x = basePop[1:3]) # take all provided
apiary
apiary[[1]]
apiary[[2]]

# Create mated colonies by crossing
apiary <- createMultiColony(x = basePop[1:2], n = 2)
drones <- createDrones(x = basePop[3], n = 30)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 2, nDrones = 15)
apiary <- cross(apiary, drones = droneGroups)
apiary
apiary[[1]]
apiary[[2]]
```

`cross` *Cross (mate) virgin queen(s) as a population, of a colony, or of all given colonies*

Description

Level 1 function that crosses (mates) a virgin queen to a group of drones. The virgin queen(s) could be within a population (`Pop-class`), in a colony (`Colony-class`), or multi-colony (`MultiColony-class`). This function does not create any progeny, it only stores the mated drones (fathers) so we can later create progeny as needed. When input is a (`Colony-class`) or (`MultiColony-class`), one virgin queens is selected at random, mated, and promoted to the queen of the colony. Other virgin queens are destroyed. Mated drones (fathers) are stored for producing progeny at a later stage. For a better understanding of crossing and the functions have a look at the "Crossing" vignette.

Usage

```
cross(
  x,
  crossPlan = NULL,
  drones = NULL,
  droneColonies = NULL,
  nDrones = NULL,
  spatial = FALSE,
  radius = NULL,
  checkCross = "error",
  simParamBee = NULL,
  ...
)
```

Arguments

x	Pop-class or Colony-class or MultiColony-class, one or more virgin queens / colonies to be mated;
crossPlan	named list with names being virgin queen or colony IDs with each list element holding the IDs of either selected drones or selected drone producing colonies, OR a string "create" if you want the cross plan to be created internally. The function can create a random (spatial = FALSE) or spatial (spatial = TRUE) cross plan internally. Also see createCrossPlan.
drones	a Pop-class or a list of Pop-class, group(s) of drones that will be mated with virgin queen(s). See pullDroneGroupsFromDCA) to create a list of drone "packages". A single Pop-class is only allowed when mating a single virgin queen or colony, or when mating according to a cross plan that includes drones' IDs. When creating a spatial cross plan internally, males can not be provided through the drones argument as a Pop-class, but should be provided through the droneColonies argument as or MultiColony-class
droneColonies	MultiColony-class with all available drone producing colonies. Provided when drones is not provided (NULL). When providing drone producing colonies, the cross function uses a cross plan, that can either be provided by the user through (crossPlan) argument or created internally (when crossPlan is "create")
nDrones	numeric of function, the number of drones to sample to mate with each virgin queen when using a cross plan
spatial	logical, whether the drone producing colonies should be sampled according to their distance from the virgin colony (that is, in a radius)
radius	numeric, the radius around the virgin colony in which to sample mating partners, only needed when spatial = TRUE
checkCross	character, throw a warning (when checkCross = "warning"),
simParamBee	SimParamBee, global simulation parameters
...	other arguments for nDrones, when nDrones is a function

Details

This function changes caste for the mated drones to fathers, and mated virgin queens to queens. See examples. This means that you can not use these individuals in matings any more!

If the supplied drone population is empty (has 0 individuals), which can happen in edge cases or when nFathersPoisson is used instead of nFathersTruncPoisson, or when performing spatially-aware mating and no drone producing colonies are found in the vicinity, then mating of a virgin queen will fail and she will stay virgin. This can happen for just a few of many virgin queens, which can be annoying to track down, but you can use isQueen or isVirginQueen to find such virgin queens. You can use checkCross to alert you about this situation.

Value

Pop-class with mated queen(s). The misc slot of the queens contains additional information about the number of workers, drones, and homozygous brood produced, and the expected percentage of csd homozygous brood.

See Also

Colony-class on how we store the fathers along the queen. For more examples for mating with either externally or internally created cross plan, please see createCrossPlan

For crossing virgin queens according to a cross plan, see createCrossPlan. For crossing virgin queens on a mating stations, see createMatingStationDCA

Examples

```
founderGenomes <- quickHaplo(nInd = 30, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 20, nDrones = nFathersPoisson)

# If input is a Pop class of virgin queen(s)
virginQueen <- basePop[2]
isQueen(virginQueen)
(matedQueen <- cross(
  x = virginQueen,
  drones = droneGroups[1]
))

isQueen(virginQueen)
isQueen(matedQueen)
nFathers(matedQueen)
isDrone(getFathers(matedQueen))
isFather(getFathers(matedQueen))

virginQueens <- basePop[4:5]
matedQueens <- cross(
  x = virginQueens,
  drones = droneGroups[c(3, 4)]
)

isQueen(matedQueens)
nFathers(matedQueens)
getFathers(matedQueens)

# Inbred mated queen (mated with her own sons)
matedQueen2 <- cross(
  x = basePop[1],
  drones = droneGroups[5]
)
# Check the expected csd homozygosity
pHomBrood(matedQueen2)

# If input is a Colony or MultiColony class
# Create Colony and MultiColony class
colony <- createColony(basePop[6])
```

```
isVirginQueen(getVirginQueens(colony))
apiary <- createMultiColony(basePop[7:8])
all(isVirginQueen(mergePops(getVirginQueens(apiary))))

# Cross
colony <- cross(colony, drones = droneGroups[[6]])
isQueenPresent(colony)
apiary <- cross(apiary, drones = droneGroups[c(7, 8)])
all(isQueenPresent(apiary))
nFathers(apiary)

# Try mating with drones that were already used for mating
colony <- createColony(basePop[9])
try((matedColony <- cross(x = colony, drones = droneGroups[[1]])))
# Create new drones and mate the colony with them
drones <- createDrones(x = basePop[1], nInd = 15)
all(isDrone(drones))
any(isFather(drones))
(matedColony <- cross(x = colony, drones = drones))
isQueenPresent(matedColony)

# Mate with drone producing colonies and a given cross plan
droneColonies <- createMultiColony(basePop[10:15])
droneColonies <- cross(droneColonies, drones = droneGroups[10:15])
nFathers(droneColonies)
apiary2 <- createMultiColony(basePop[16:20])
apiary3 <- createMultiColony(basePop[21:25])
apiary4 <- createMultiColony(basePop[26:30])

# Create a random cross plan
randomCrossPlan <- createCrossPlan(x = apiary2,
                                   droneColonies = droneColonies,
                                   nDrones = nFathersPoisson,
                                   spatial = FALSE)
apiary2 <- cross(x = apiary2,
                 droneColonies = droneColonies,
                 crossPlan = randomCrossPlan,
                 nDrones = 15)
nFathers(apiary2)

# Mate colonies according to a cross plan that is created internally within the cross function
apiary3 <- cross(x = apiary3,
                 droneColonies = droneColonies,
                 crossPlan = "create",
                 nDrones = 15)
nFathers(apiary3)

# Mate colonies according to a cross plan that is created internally within the cross function
# For this, all the colonies have to have a set location
droneColonies <- setLocation(droneColonies,
                             location = Map(c, runif(6, 0, 2*pi), runif(6, 0, 2*pi)))
apiary4 <- setLocation(apiary4,
                       location = Map(c, runif(5, 0, 2*pi), runif(5, 0, 2*pi)))
```

```
apiary4 <- cross(x = apiary4,
                 droneColonies = droneColonies,
                 crossPlan = "create",
                 nDrones = nFathersPoisson,
                 spatial = TRUE,
                 checkCross = "warning",
                 radius = 3)
nFathers(apiary4)
```

`downsize` *Reduce number of workers and remove all drones and virgin queens from a Colony or MultiColony object*

Description

Level 2 function that downsizes a Colony or MultiColony object by removing a proportion of workers, all drones and all virgin queens. Usually in the autumn, such an event occurs in preparation for the winter months.

Usage

```
downsize(x, p = NULL, use = "rand", new = FALSE, simParamBee = NULL, ...)
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`p`	numeric, proportion of workers to be removed from the colony; if `NULL` then `SimParamBee$downsizeP` is used. If input is `MultiColony-class`, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies
`use`	character, all the options provided by `selectInd`; it guides the selection of workers that will be removed
`new`	logical, should we remove all current workers and add a targeted proportion anew (say, create winter workers)
`simParamBee`	`SimParamBee`, global simulation parameters
`...`	additional arguments passed to `p` when this argument is a function

Value

`Colony-class` or `MultiColony-class` with workers reduced and drones/virgin queens removed

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 3, nDrones = 12)

# Create and cross Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(colony)
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(apiary)

# Downsize
colony <- downsize(x = colony, new = TRUE, use = "rand")
colony
apiary <- downsize(x = apiary, new = TRUE, use = "rand")
apiary[[1]]

# Downsize with different numbers
nWorkers(apiary); nDrones(apiary)
apiary <- downsize(x = apiary, p = c(0.5, 0.1), new = TRUE, use = "rand")
nWorkers(apiary); nDrones(apiary)
```

---

downsizePUnif *Sample the downsize proportion - proportion of removed workers in downsizing*

Description

Sample the downsize proportion - proportion of removed workers in downsizing - used when p = NULL (see SimParamBee$downsizeP).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
downsizePUnif(colony, n = 1, min = 0.8, max = 0.9)
```

Arguments

colony	Colony-class
n	integer, number of samples
min	numeric, lower limit for downsizePUnif
max	numeric, upper limit for downsizePUnif

Value

numeric, downsize proportion

See Also

SimParamBee field downsizeP

Examples

```
downsizePUnif()
downsizePUnif()
p <- downsizePUnif(n = 1000)
hist(p, breaks = seq(from = 0, to = 1, by = 0.01), xlim = c(0, 1))
```

---

editCsdLocus *Edit the csd locus*

Description

Edits the csd locus in an entire population of individuals to ensure heterozygosity. The user can provide a list of csd alleles for each individual or, alternatively, the function samples a heterozygous genotype for each individual from all possible csd alleles. The gv slot is recalculated to reflect the any changes due to editing, but other slots remain the same.

Usage

```
editCsdLocus(pop, alleles = NULL, simParamBee = NULL)
```

Arguments

pop	Pop-class
alleles	NULL or list; If NULL, then the function samples a heterozygous csd genotype for each virgin queen from all possible csd alleles. If not NULL, the user provides a list of length nInd with each node holding a matrix or a data.frame, each having two rows and n columns. Each row must hold one csd haplotype (allele) that will be assigned to a virgin queen. The n columns span the length of the csd locus as specified in SimParamBee. The two csd alleles must be different to ensure heterozygosity at the csd locus.
simParamBee	global simulation parameters.

Value

Returns an object of Pop-class

getAa *Access epistasis values of individuals in a caste*

Description

Level 0 function that returns epistasis values of individuals in a caste.

Usage

```
getAa(x, caste = NULL, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getQueenAa(x, collapse = FALSE, simParamBee = NULL)

getFathersAa(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getVirginQueensAa(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getWorkersAa(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getDronesAa(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
collapse	logical, if the return value should be a single matrix with epistatic values of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

vector of epistasis values when x is Colony-class and list of vectors of epistasis values when x is MultiColony-class, named by colony id when x is MultiColony-class

Not exporting this function, since the theory behind it is not fully developed

Functions

- getQueenAa(): Access epistasis value of the queen
- getFathersAa(): Access epistasis values of fathers
- getVirginQueensAa(): Access epistasis values of virgin queens
- getWorkersAa(): Access epistasis values of workers
- getDronesAa(): Access epistasis values of drones

See Also

dd and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

---

getBv *Access breeding values of individuals in a caste*

Description

Level 0 function that returns breeding values of individuals in a caste.

Usage

```
getBv(x, caste = NULL, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getQueenBv(x, collapse = FALSE, simParamBee = NULL)

getFathersBv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getVirginQueensBv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getWorkersBv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getDronesBv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
collapse	logical, if the return value should be a single matrix with breeding valued of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

vector of breeding values when x is Colony-class and list of vectors of breeding values when x is MultiColony-class, named by colony id when x is MultiColony-class

Not exporting this function, since the theory behind it is not fully developed

Functions

- `getQueenBv()`: Access breeding value of the queen
- `getFathersBv()`: Access breeding values of fathers
- `getVirginQueensBv()`: Access breeding values of virgin queens
- `getWorkersBv()`: Access breeding values of workers
- `getDronesBv()`: Access breeding values of drones

See Also

`bv` and `vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")`

`getCaste` *Report caste of an individual*

Description

Level 0 function that reports caste of an individual

Usage

```
getCaste(x, collapse = FALSE, simParamBee = NULL)
```

Arguments

`x`	`Pop-class`, `Colony-class`, or `MultiColony-class`
`collapse`	logical, if `TRUE`, the function will return a single vector with caste information
`simParamBee`	`SimParamBee`, global simulation parameters

Value

When x is `Pop-class`, character of caste status; if you get `NA` note that this is not supposed to happen. When x is `Colony-class`, list with character vectors (list is named with caste). When x is `MultiColony-class`, list of lists with character vectors (list is named with colony id).

See Also

`getCastePop` and `getCasteId`

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 20, nDrones = 5)
colony <- addVirginQueens(colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 10, nDrones = 2)
apiary <- addVirginQueens(apiary, nInd = 4)

getCaste(getQueen(colony))
getCaste(getFathers(colony))
getCaste(getWorkers(colony))
getCaste(getDrones(colony))
getCaste(getVirginQueens(colony))

bees <- c(
  getQueen(colony),
  getFathers(colony, nInd = 2),
  getWorkers(colony, nInd = 2),
  getDrones(colony, nInd = 2),
  getVirginQueens(colony, nInd = 2)
)
getCaste(bees)

getCaste(colony)
# Collapse information into a single vector
getCaste(colony, collapse = TRUE)
getCaste(apiary)

# Create a data.frame with id, colony, and caste information
(tmpC <- getCaste(apiary[[1]]))
(tmpI <- getCasteId(apiary[[1]]))
tmp <- data.frame(caste = unlist(tmpC), id = unlist(tmpI))
head(tmp)
tail(tmp)

(tmpC <- getCaste(apiary))
(tmpI <- getCasteId(apiary))
(tmp <- data.frame(caste = unlist(tmpC), id = unlist(tmpI)))
tmp$colony <- sapply(
  X = strsplit(
```

```
    x = rownames(tmp), split = ".",
    fixed = TRUE
  ),
  FUN = function(z) z[[1]]
)
head(tmp)
tail(tmp)
```

`getCasteId` *Get IDs of individuals of a caste, or ID of all members of colony*

Description

Level 0 function that returns the ID individuals of a caste. To get the individuals, use `getCastePop`. To get individuals' caste, use `getCaste`.

Usage

```
getCasteId(x, caste = "all", collapse = FALSE, simParamBee = NULL)
```

Arguments

`x`	`Pop-class`, `Colony-class`, or `MultiColony-class`
`caste`	character, "queen", "fathers", "workers", "drones", "virginQueens", or "all"
`collapse`	logical, if all IDs should be returned as a single vector
`simParamBee`	`SimParamBee`, global simulation parameters

Value

when `x` is `Pop-class` for `caste != "all"` or list for `caste == "all"` with ID nodes named by caste; when `x` is `Colony-class` return is a named list of `Pop-class` for `caste != "all"` or named list for `caste == "all"` indluding caste members IDs; when `x` is `MultiColony-class` return is a named list of `Pop-class` for `caste != "all"` or named list of lists of `Pop-class` for `caste == "all"` indluding caste members IDs

See Also

`getCaste`

`getCastePop` and `getCaste`

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
```

```
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 20, nDrones = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 10, nDrones = 2)
apiary <- addVirginQueens(apiary, nInd = 4)

getCasteId(x = drones)
getCasteId(x = colony)
getCasteId(x = apiary, caste = "workers")
getCasteId(x = apiary)
getCasteId(x = apiary, caste = "virginQueens")
# Get all IDs as a single vector
getCasteId(x = colony, caste = "all", collapse = TRUE)
getCasteId(x = apiary, caste = "workers", collapse = TRUE)
getCasteId(x = apiary, caste = "drones", collapse = TRUE)
getCasteId(x = apiary, caste = "all", collapse = TRUE)

# Create a data.frame with id, colony, and caste information
(tmpC <- getCaste(apiary[[1]]))
(tmpI <- getCasteId(apiary[[1]]))
tmp <- data.frame(caste = unlist(tmpC), id = unlist(tmpI))
head(tmp)
tail(tmp)

(tmpC <- getCaste(apiary))
(tmpI <- getCasteId(apiary))
(tmp <- data.frame(caste = unlist(tmpC), id = unlist(tmpI)))
tmp$colony <- sapply(
  X = strsplit(
    x = rownames(tmp), split = ".",
    fixed = TRUE
  ),
  FUN = function(z) z[[1]]
)
head(tmp)
tail(tmp)
```

`getCastePop` *Access individuals of a caste*

Description

Level 1 function that returns individuals of a caste. These individuals stay in the colony (compared to `pullCastePop`).

Usage

```
getCastePop(
  x,
  caste = "all",
  nInd = NULL,
  use = "rand",
  removeFathers = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueen(x, collapse = FALSE, simParamBee = NULL)

getFathers(x, nInd = NULL, use = "rand", collapse = FALSE, simParamBee = NULL)

getWorkers(x, nInd = NULL, use = "rand", collapse = FALSE, simParamBee = NULL)

getDrones(
  x,
  nInd = NULL,
  use = "rand",
  removeFathers = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueens(
  x,
  nInd = NULL,
  use = "rand",
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Colony-class or MultiColony-class, exceptionally Pop-class for calling getFathers on a queen population
caste	character, "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed; if there are less individuals than requested, we return the ones available - this can return NULL. If input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies.
use	character, all options provided by selectInd and "order" that selects 1:nInd individuals (meaning it always returns at least one individual, even if nInd = 0)

removeFathers	logical, removes drones that have already mated; set to FALSE if you would like to get drones for mating with multiple virgin queens, say via insemination
collapse	logical, whether to return a single merged population
simParamBee	SimParamBee, global simulation parameters

Value

when x is Colony-class return is Pop-class for caste != "all" or list for caste == "all" with nodes named by caste; when x is MultiColony-class return is a named list of Pop-class for caste != "all" or named list of lists of Pop-class for caste == "all". You can merge all the populations in the list with mergePops function.

Functions

- getQueen(): Access the queen
- getFathers(): Access fathers (drones the queen mated with)
- getWorkers(): Access workers
- getDrones(): Access drones
- getVirginQueens(): Access virgin queens

See Also

getQueen, getFathers, getVirginQueens, getWorkers, and getDrones

getCasteId and getCaste

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

# Build-up and add virgin queens
colony <- buildUp(x = colony)
apiary <- buildUp(x = apiary)
colony <- addVirginQueens(x = colony)
apiary <- addVirginQueens(x = apiary)

# Get the queen of the colony
getCastePop(colony, caste = "queen")
```

```
getQueen(colony)

# Comparison of getCastePop() and getWorkers()
getCastePop(colony, caste = "workers")
getCastePop(colony, caste = "workers")
getCastePop(colony, caste = "workers", nInd = 2)
# Or aliases
getWorkers(colony)
# Same aliases exist for all the castes!

# Input is a MultiColony class - same behaviour as for the Colony!
getCastePop(apiary, caste = "queen")
# Or alias
getQueen(apiary)

# Sample individuals from all the castes
getCastePop(colony, nInd = 5, caste = "all")

# Get different number of workers per colony
getCastePop(apiary, caste = "workers", nInd = c(10, 20))
# Or alias
getWorkers(apiary, nInd = c(10, 20))

# Obtain individuals from MultiColony as a single population
getCastePop(apiary, caste = "queen", collapse = TRUE)
getQueen(apiary, collapse = TRUE)
getWorkers(apiary, nInd = 10, collapse = TRUE)
getDrones(apiary, nInd = 3, collapse = TRUE)
```

`getCasteSex` *Get sex of individuals of a caste, or sex of all members of colony*

Description

Level 0 function that returns the sex individuals of a caste. To get the individuals, use `getCastePop`. To get individuals' caste, use `getCaste`.

Usage

```
getCasteSex(x, caste = "all", collapse = FALSE, simParamBee = NULL)
```

Arguments

`x`	`Pop-class`, `Colony-class`, or `MultiColony-class`
`caste`	character, "queen", "fathers", "workers", "drones", "virginQueens", or "all"
`collapse`	logical, if `TRUE`, the function will return a single vector with sex information
`simParamBee`	`SimParamBee`, global simulation parameters

Value

when x is Pop-class for caste != "all" or list for caste == "all" with sex nodes named by caste; when x is Colony-class return is a named list of Pop-class for caste != "all" or named list for caste == "all" indluding caste members sexes; when x is MultiColony-class return is a named list of Pop-class for caste != "all" or named list of lists of Pop-class for caste == "all" indluding caste members sexes

See Also

getCaste

getCastePop and getCaste

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 20, nDrones = 5)
colony <- addVirginQueens(colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 10, nDrones = 2)
apiary <- addVirginQueens(apiary, nInd = 4)

getCasteSex(x = drones)
getCasteSex(x = colony)
getCasteSex(x = apiary, caste = "workers")
getCasteSex(x = apiary)
getCasteSex(x = apiary, caste = "virginQueens")
# Collapse information into a single vector
getCasteSex(colony, caste = "all", collapse = TRUE)

# Create a data.frame with sex, colony, and caste information
(tmpC <- getCaste(apiary[[1]]))
(tmpS <- getCasteSex(apiary[[1]]))
(tmpI <- getCasteId(apiary[[1]]))
tmp <- data.frame(caste = unlist(tmpC), sex = unlist(tmpS), id = unlist(tmpI))
head(tmp)
tail(tmp)

(tmpC <- getCaste(apiary))
(tmpS <- getCasteSex(apiary))
```

```
(tmpI <- getCasteId(apiary))
tmp <- data.frame(caste = unlist(tmpC), sex = unlist(tmpS), id = unlist(tmpI))
tmp$colony <- sapply(
  X = strsplit(
    x = rownames(tmp), split = ".",
    fixed = TRUE
  ),
  FUN = function(z) z[[1]]
)
head(tmp)
tail(tmp)
```

`getCsdAlleles` *Get csd alleles*

Description

Level 0 function that returns alleles from the csd locus. See `SimParamBee` for more information about the csd locus.

Usage

```
getCsdAlleles(
  x,
  caste = NULL,
  nInd = NULL,
  allele = "all",
  dronesHaploid = TRUE,
  collapse = FALSE,
  unique = FALSE,
  simParamBee = NULL
)

getQueenCsdAlleles(
  x,
  allele = "all",
  unique = FALSE,
  collapse = FALSE,
  simParamBee = NULL
)

getFathersCsdAlleles(
  x,
  nInd = NULL,
  allele = "all",
  dronesHaploid = TRUE,
  unique = FALSE,
  collapse = FALSE,
```

```
  simParamBee = NULL
)

getVirginQueensCsdAlleles(
  x,
  nInd = NULL,
  allele = "all",
  unique = FALSE,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersCsdAlleles(
  x,
  nInd = NULL,
  allele = "all",
  unique = FALSE,
  collapse = FALSE,
  simParamBee = NULL
)

getDronesCsdAlleles(
  x,
  nInd = NULL,
  allele = "all",
  dronesHaploid = TRUE,
  unique = FALSE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, for how many individuals; if NULL all individuals are taken; this can be useful as a test of sampling individuals
allele	character, either "all" for both alleles or an integer for a single allele, use a value of 1 for female allele and a value of 2 for male allele
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if TRUE, the function will return a set of csd alleles across the entire population, colony, or multicolony (not separately for each caste when x is a colony or each caste of each colony when x is a multicolony. This is a way to get one single object as an output across castes or colonies. Note this has nothing to do with the colony collapse. It's like paste(..., collapse = TRUE). Default is FALSE. See examples about this behaviour.

unique	logical, return only the unique set of csd alleles. This argument interacts with collapse. Default is FALSE. See examples about this behaviour.
simParamBee	SimParamBee, global simulation parameters

Details

If both collapse and unique are TRUE, the function returns a unique set of csd alleles in the entire population, colony, or multicolony

Value

matrix with haplotypes when x is Pop-class, list of matrices with haplotypes when x is Colony-class (list nodes named by caste) and list of a list of matrices with haplotypes when x is MultiColony-class, outer list is named by colony id when x is MultiColony-class; NULL when x is NULL

Functions

- getQueenCsdAlleles(): Access csd alleles of the queen
- getFathersCsdAlleles(): Access csd alleles of the fathers
- getVirginQueensCsdAlleles(): Access csd alleles of the virgin queens
- getWorkersCsdAlleles(): Access csd alleles of the workers
- getDronesCsdAlleles(): Access csd alleles of the drones

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 5)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)

# Use getCsdAlleles on a Population
getCsdAlleles(getQueen(colony))
getCsdAlleles(getWorkers(colony))

# Use getCsdAlleles on a Colony
getCsdAlleles(colony)
getCsdAlleles(colony, caste = "queen")
getQueenCsdAlleles(colony)
```

```
getCsdAlleles(colony, caste = "workers")
getWorkersCsdAlleles(colony)
# Same aliases exist for all the castes!

getCsdAlleles(colony, unique = TRUE)
getCsdAlleles(colony, collapse = TRUE)
getCsdAlleles(colony, collapse = TRUE, unique = TRUE)

# Use getCsdAlleles on a MultiColony
getCsdAlleles(apiary)
getCsdAlleles(apiary, unique = TRUE)
getCsdAlleles(apiary, collapse = TRUE, unique = TRUE)
getCsdAlleles(apiary, nInd = 2)
```

`getCsdGeno` *Get genotypes from the csd locus*

Description

Level 0 function that returns genotypes from the csd locus. See `SimParamBee` for more information about the csd locus and how we have implemented it.

Usage

```
getCsdGeno(
  x,
  caste = NULL,
  nInd = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueenCsdGeno(x, collapse = FALSE, simParamBee = NULL)

getFathersCsdGeno(
  x,
  nInd = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensCsdGeno(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getWorkersCsdGeno(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getDronesCsdGeno(
```

```
  x,
  nInd = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, for how many individuals; if NULL all individuals are taken; this can be useful as a test of sampling individuals
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with haplotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Details

The returned genotypes are spanning multiple bi-allelic SNP of a non-recombining csd locus / haplotype. In most cases you will want to use getCsdAlleles.

Value

matrix with genotypes when x is Pop-class, list of matrices with genotypes when x is Colony-class (list nodes named by caste) and list of a list of matrices with genotypes when x is MultiColony-class, outer list is named by colony id when x is MultiColony-class; NULL when x is NULL

Functions

- getQueenCsdGeno(): Access csd genotypes of the queen
- getFathersCsdGeno(): Access csd genotypes of the fathers
- getVirginQueensCsdGeno(): Access csd genotypes of the virgin queens
- getWorkersCsdGeno(): Access csd genotypes of the virgin queens
- getDronesCsdGeno(): Access csd genotypes of the virgin queens

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
```

```
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 4)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Use getCsdGeno on a Population
getCsdGeno(getQueen(colony))
getCsdGeno(getWorkers(colony))

# Using dronesHaploid = TRUE returns drones as haploids instead of double haploids
getCsdGeno(getDrones(colony), nInd = 3, dronesHaploid = TRUE)
# Using dronesHaploid = FALSE returns drones as double haploids
getCsdGeno(getDrones(colony), nInd = 3, dronesHaploid = FALSE)

# Use getCsdGeno on a Colony
getCsdGeno(colony)
getCsdGeno(colony, caste = "queen")
getQueenCsdGeno(colony)
getCsdGeno(colony, caste = "workers")
getWorkersCsdGeno(colony)
# Same aliases exist for all the castes!

# Use getCsdGeno on a MultiColony - same behaviour as for the Colony!
getCsdGeno(apiary)
getCsdGeno(apiary, nInd = 2)
```

---

getDd *Access dominance values of individuals in a caste*

Description

Level 0 function that returns dominance values of individuals in a caste.

Usage

```
getDd(x, caste = NULL, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getQueenDd(x, collapse = FALSE, simParamBee = NULL)

getFathersDd(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getVirginQueensDd(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)
```

```
getWorkersDd(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getDronesDd(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
collapse	logical, if the return value should be a single matrix with dominance values of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

vector of dominance values when x is Colony-class and list of vectors of dominance values when x is MultiColony-class, named by colony id when x is MultiColony-class

Not exporting this function, since the theory behind it is not fully developed

Functions

- getQueenDd(): Access dominance value of the queen
- getFathersDd(): Access dominance values of fathers
- getVirginQueensDd(): Access dominance values of virgin queens
- getWorkersDd(): Access dominance values of workers
- getDronesDd(): Access dominance values of drones

See Also

dd and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

---

getEvents *Report which colony events have occurred*

Description

Level 0 function that returns a matrix of logicals reporting the status of the colony events. The events are: split, swarm, supersedure, collapse, and production. These events impact colony status, strength, and could also impact downstream phenotypes.

Usage

```
getEvents(x)
```

Arguments

x	Colony-class or MultiColony-class

Value

matrix of logicals, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(apiary, nInd = 4)

getEvents(colony)
getEvents(apiary)

tmp <- swarm(colony)
getEvents(tmp$swarm)
getEvents(tmp$remnant)

apiary <- supersede(apiary)
getEvents(apiary)
```

---

getGv *Access genetic values of individuals in a caste*

Description

Level 0 function that returns genetic values of individuals in a caste.

Usage

```
getGv(x, caste = NULL, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getQueenGv(x, collapse = FALSE, simParamBee = NULL)

getFathersGv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getVirginQueensGv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getWorkersGv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getDronesGv(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
collapse	logical, if the return value should be a single matrix with genetic values of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

vector of phenotype values when x is Colony-class and list of vectors of genetic values when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenGv(): Access genetic value of the queen
- getFathersGv(): Access genetic values of fathers
- getVirginQueensGv(): Access genetic values of virgin queens
- getWorkersGv(): Access genetic values of workers
- getDronesGv(): Access genetic values of drones

See Also

gv and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$addTraitA(nQtlPerChr = 10, var = 1)
SP$addSnpChip(5)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getGv(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getGv(queens)

# Input is a colony
getGv(colony, caste = "queen")
getQueenGv(colony)

getGv(colony, caste = "workers")
getWorkersGv(colony)
# Same aliases exist for all the castes!

# Get genetic values for all individuals
getGv(colony, caste = "all")
# Get all genetic values in a single matrix
getGv(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony!
getGv(apiary, caste = "queen")
getQueenGv(apiary)

# Get the genetic values of all individuals either by colony or in a single matrix
getGv(apiary, caste = "all")
getGv(apiary, caste = "all", collapse = TRUE)
```

`getIbdHaplo` *Access IBD haplotypes of individuals in a caste*

Description

Level 0 function that returns IBD (identity by descent) haplotypes of individuals in a caste.

Usage

```
getIbdHaplo(
  x,
  caste = NULL,
  nInd = NULL,
  chr = NULL,
  snpChip = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueenIbdHaplo(
  x,
  chr = NULL,
  snpChip = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getFathersIbdHaplo(
  x,
  nInd = NULL,
  chr = NULL,
  snpChip = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensIbdHaplo(
  x,
  nInd = NULL,
  chr = NULL,
  snpChip = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersIbdHaplo(
  x,
  nInd = NULL,
  chr = NULL,
  snpChip = NULL,
```

```
  collapse = FALSE,
  simParamBee = NULL
)

getDronesIbdHaplo(
  x,
  nInd = NULL,
  chr = NULL,
  snpChip = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
snpChip	integer, indicating which SNP array loci are to be retrieved, if NULL, all sites are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with haplotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with haplotypes when x is Colony-class and list of matrices with haplotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenIbdHaplo(): Access IBD haplotype data of the queen
- getFathersIbdHaplo(): Access IBD haplotype data of fathers
- getVirginQueensIbdHaplo(): Access IBD haplotype data of virgin queens
- getWorkersIbdHaplo(): Access IBD haplotype data of workers
- getDronesIbdHaplo(): Access IBD haplotype data of drones

See Also

getIbdHaplo and pullIbdHaplo

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$setTrackRec(TRUE)
SP$setTrackPed(isTrackPed = TRUE)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 200)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getIbdHaplo(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getIbdHaplo(queens)

# Input is a colony
getIbdHaplo(x = colony, caste = "queen")
getQueenIbdHaplo(colony)

getIbdHaplo(colony, caste = "workers", nInd = 3)
getWorkersIbdHaplo(colony)
# Same aliases exist for all castes!

# Get haplotypes for all individuals
getIbdHaplo(colony, caste = "all")
# Get all haplotypes in a single matrix
getIbdHaplo(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony
getIbdHaplo(x = apiary, caste = "queen")
getQueenIbdHaplo(apiary)
# Or collapse all the haplotypes into a single matrix
getQueenIbdHaplo(apiary, collapse = TRUE)

# Get the haplotypes of all individuals either by colony or in a single matrix
getIbdHaplo(apiary, caste = "all")
getIbdHaplo(apiary, caste = "all", collapse = TRUE)
```

getId *Get the colony ID*

Description

Level 0 function that returns the colony ID. This is by definition the ID of the queen.

Usage

```
getId(x)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class

Value

character, NA when queen not present

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

getId(getQueen(colony)) # Pop class
getId(colony) # Colony Class
getId(apiary) # MultiColony Class

colony2 <- removeQueen(colony)
getId(colony2)
```

`getLocation` *Get the colony location*

Description

Level 0 function that returns the colony location as (x, y) coordinates.

Usage

```
getLocation(x, collapse = FALSE)
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`collapse`	logical, if the return value should be a single matrix with locations of all the colonies; only applicable when input is a `MultiColony-class` object

Value

numeric with two values when `x` is `Colony-class` and a list of numeric with two values when `x` is `MultiColony-class` (list named after colonies); `c(NA, NA)` when location not set

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

getLocation(colony)
getLocation(apiary[[1]])
getLocation(apiary)
getLocation(apiary, collapse = TRUE)

loc <- c(123, 456)
colony <- setLocation(colony, location = loc)
getLocation(colony)

loc1 <- c(512, 722)
```

```
colony1 <- setLocation(apiary[[1]], location = loc1)
getLocation(colony1)

loc2 <- c(189, 357)
colony2 <- setLocation(apiary[[2]], location = loc2)
getLocation(colony2)

getLocation(c(colony1, colony2))

# Assuming one location (as in bringing colonies to an apiary at a location!)
apiary <- setLocation(apiary, location = loc1)
getLocation(apiary)

# Assuming different locations (so tmp is not an apiary in one location!)
tmp <- setLocation(c(colony1, colony2), location = list(loc1, loc2))
getLocation(tmp)
```

`getMisc` *Get miscellaneous information in a population*

Description

Get miscellaneous information in a population

Usage

```
getMisc(x, node = NULL)
```

Arguments

x	Pop-class
node	character, name of the node to get from the `x@misc` slot; if `NULL` the whole `x@misc` slot is returned

Value

The `x@misc` slot or its nodes `x@misc[[*]][[node]]`

getPheno *Access phenotype values of individuals in a caste*

Description

Level 0 function that returns phenotype values of individuals in a caste.

Usage

```
getPheno(x, caste = NULL, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getQueenPheno(x, collapse = FALSE, simParamBee = NULL)

getFathersPheno(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getVirginQueensPheno(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getWorkersPheno(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)

getDronesPheno(x, nInd = NULL, collapse = FALSE, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
collapse	logical, if the return value should be a single matrix with phenotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

vector of genetic values when x is Colony-class and list of vectors of genetic values when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenPheno(): Access phenotype value of the queen
- getFathersPheno(): Access phenotype values of fathers
- getVirginQueensPheno(): Access phenotype values of virgin queens
- getWorkersPheno(): Access phenotype values of workers
- getDronesPheno(): Access phenotype values of drones

See Also

pheno and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

SP$addTraitA(nQtlPerChr = 10, var = 1)
SP$setVarE(varE = 1)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getPheno(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getPheno(queens)

# Input is a colony
getPheno(colony, caste = "queen")
getQueenPheno(colony)

getPheno(colony, caste = "fathers")
getPheno(colony, caste = "fathers", nInd = 2)
getPheno(colony, caste = "fathers", nInd = 2) # random sample!
getFathersPheno(colony)
getFathersPheno(colony, nInd = 2)

getPheno(colony, caste = "workers")
getWorkersPheno(colony)
# Same aliases exist for all the castes!!!

# Get phenotypes for all individuals
getPheno(colony, caste = "all")
# Get all phenotypes in a single matrix
getPheno(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony!
```

```
getPheno(apiary, caste = "queen")
getQueenPheno(apiary)

# Get the phenotypes of all individuals either by colony or in a single matrix
getPheno(apiary, caste = "all")
getPheno(apiary, caste = "all", collapse = TRUE)
```

`getPooledGeno` *Get a pooled genotype from true genotypes*

Description

Level 0 function that returns a pooled genotype from true genotypes to mimic genotyping of a pool of colony members.

Usage

```
getPooledGeno(x, type = NULL, sex = NULL)
```

Arguments

`x`	matrix, true genotypes with individuals in rows and sites in columns
`type`	character, "mean" for average genotype or "count" for the counts of reference and alternative alleles
`sex`	character, vector of "F" and "M" to denote the sex of individuals in `x`

Value

a numeric vector with average allele dosage when `type = "mean"` and a two-row matrix with the counts of reference (1st row) and alternative (2nd row) alleles

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)


basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)
apiary <- createMultiColony(basePop[2:3], n = 2)
apiary <- cross(x = apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

genoQ <- getQueenSegSiteGeno(apiary[[1]])
genoF <- getFathersSegSiteGeno(apiary[[1]])
genoW <- getWorkersSegSiteGeno(apiary[[1]])
genoD <- getDronesSegSiteGeno(apiary[[1]])
```

```
genoV <- getVirginQueensSegSiteGeno(apiary[[1]])

# Pool of drones
sexD <- getCasteSex(apiary[[1]], caste = "drones")
getPooledGeno(x = genoD, type = "count", sex = sexD)[, 1:10]
(poolD <- getPooledGeno(x = genoD, type = "mean", sex = sexD))[, 1:10]
# ... compare to queen's genotype
genoQ[, 1:10]
plot(
  y = poolD, x = genoQ, ylim = c(0, 2), xlim = c(0, 2),
  ylab = "Average allele dosage in drones",
  xlab = "Allele dosage in the queen"
)

# As an exercise you could repeat the above with different numbers of drones!

# Pool of workers
getPooledGeno(x = genoW, type = "count")[, 1:10]
(poolW <- getPooledGeno(x = genoW, type = "mean"))[, 1:10]
# ... compare to fathers' and queen's avearage genotype
sexF <- getCasteSex(apiary[[1]], caste = "fathers")
sexQ <- rep(x = "F", times = nrow(genoF))
sexFQ <- c(sexF, sexQ)
genoFQ <- rbind(genoF, genoQ[rep(x = 1, times = nrow(genoF)), ])
(poolFQ <- getPooledGeno(x = genoFQ, type = "mean", sex = sexFQ))[, 1:10]
plot(
  y = poolW, x = poolFQ, ylim = c(0, 2), xlim = c(0, 2),
  ylab = "Average allele dosage in workers",
  xlab = "Average allele dosage in the queen and fathers"
)

# As an exercise you could repeat the above with different numbers of workers!
```

`getQtlGeno` *Access QTL genotypes of individuals in a caste*

Description

Level 0 function that returns QTL genotypes of individuals in a caste.

Usage

```
getQtlGeno(
  x,
  caste = NULL,
  nInd = NULL,
  trait = 1,
  chr = NULL,
  dronesHaploid = TRUE,
```

```
  collapse = FALSE,
  simParamBee = NULL
)

getQueenQtlGeno(x, trait = 1, chr = NULL, collapse = FALSE, simParamBee = NULL)

getFathersQtlGeno(
  x,
  nInd = NULL,
  trait = 1,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensQtlGeno(
  x,
  nInd = NULL,
  trait = 1,
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersQtlGeno(
  x,
  nInd = NULL,
  trait = 1,
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getDronesQtlGeno(
  x,
  nInd = NULL,
  trait = 1,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is

	a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
trait	numeric (trait position) or character (trait name), indicates which trait's QTL genotypes to retrieve
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with genotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with genotypes when x is Colony-class and list of matrices with genotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenQtlGeno(): Access QTL genotype data of the queen
- getFathersQtlGeno(): Access QTL genotype data of fathers
- getVirginQueensQtlGeno(): Access QTL genotype data of virgin queens
- getWorkersQtlGeno(): Access QTL genotype data of workers
- getDronesQtlGeno(): Access QTL genotype data of drones

See Also

getQtlGeno and pullQtlGeno as well as vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$addTraitA(nQtlPerChr = 10)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 200)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
```

```
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getQtlGeno(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getQtlGeno(queens)

# Input is a colony
getQtlGeno(colony, caste = "queen")
getQueenQtlGeno(colony)

getQtlGeno(colony, caste = "workers", nInd = 3)
getWorkersQtlGeno(colony)
# Same aliases exist for all the castes!

# Get genotypes for all individuals
getQtlGeno(colony, caste = "all")
# Get all haplotypes in a single matrix
getQtlGeno(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony!
getQtlGeno(apiary, caste = "queen")
getQueenQtlGeno(apiary)

# Get the genotypes of all individuals either by colony or in a single matrix
getQtlGeno(apiary, caste = "all")
getQtlGeno(apiary, caste = "all", collapse = TRUE)
```

`getQtlHaplo` *Access QTL haplotypes of individuals in a caste*

Description

Level 0 function that returns QTL haplotypes of individuals in a caste.

Usage

```
getQtlHaplo(
  x,
  caste = NULL,
  nInd = NULL,
  trait = 1,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
```

```
)

getQueenQtlHaplo(
  x,
  trait = 1,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getFathersQtlHaplo(
  x,
  nInd = NULL,
  trait = 1,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensQtlHaplo(
  x,
  nInd = NULL,
  trait = 1,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersQtlHaplo(
  x,
  nInd = NULL,
  trait = 1,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getDronesQtlHaplo(
  x,
  nInd = NULL,
  trait = 1,
  haplo = "all",
  chr = NULL,
```

```
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
trait	numeric (trait position) or character (trait name), indicates which trait's QTL haplotypes to retrieve
haplo	character, either "all" for all haplotypes or an integer for a single set of haplotypes, use a value of 1 for female haplotypes and a value of 2 for male haplotypes
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with haplotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with haplotypes when x is Colony-class and list of matrices with haplotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenQtlHaplo(): Access QTL haplotype data of the queen
- getFathersQtlHaplo(): Access QTL haplotype data of fathers
- getVirginQueensQtlHaplo(): Access QTL haplotype data of virgin queens
- getWorkersQtlHaplo(): Access QTL haplotype of workers
- getDronesQtlHaplo(): Access QTL haplotype data of drones

See Also

getQtlHaplo and pullQtlHaplo as well as vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$addTraitA(nQtlPerChr = 10)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 200)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getQtlHaplo(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getQtlHaplo(queens)

# Input is a Colony
getQtlHaplo(colony, caste = "queen")
getQueenQtlHaplo(colony)

getQtlHaplo(colony, caste = "workers", nInd = 3)
getWorkersQtlHaplo(colony)
# Same aliases exist for all the castes!

# Get haplotypes for all individuals
getQtlHaplo(colony, caste = "all")
# Get all haplotypes in a single matrix
getQtlHaplo(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony
getQtlHaplo(apiary, caste = "queen")
getQueenQtlHaplo(apiary)

# Get the haplotypes of all individuals either by colony or in a single matrix
getQtlHaplo(apiary, caste = "all")
getQtlHaplo(apiary, caste = "all", collapse = TRUE)
```

`getQueenAge` *Get (calculate) the queen's age*

Description

Level 0 function that returns the queen's age.

Usage

```
getQueenAge(x, currentYear, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
currentYear	integer, current year
simParamBee	SimParamBee, global simulation parameters

Value

numeric, the age of the queen(s); named when theres is more than one queen; NA if queen not present

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

queen <- getQueen(colony)
queen <- setQueensYearOfBirth(queen, year = 2020)
getQueenAge(queen, currentYear = 2022)

colony <- setQueensYearOfBirth(colony, year = 2021)
getQueenAge(colony, currentYear = 2022)

apiary <- setQueensYearOfBirth(apiary, year = 2018)
getQueenAge(apiary, currentYear = 2022)
```

`getQueenYearOfBirth` *Access the queen's year of birth*

Description

Level 0 function that returns the queen's year of birth.

Usage

```
getQueenYearOfBirth(x, simParamBee = NULL)
```

Arguments

x	Pop-class (one or more than one queen), Colony-class (one colony), or MultiColony-class (more colonies)
simParamBee	SimParamBee, global simulation parameters

Value

numeric, the year of birth of the queen(s); named when theres is more than one queen; NA if queen not present

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

queen <- getQueen(colony)
queen <- setQueensYearOfBirth(queen, year = 2022)
getQueenYearOfBirth(queen)

getQueenYearOfBirth(getQueen(colony))
colony <- setQueensYearOfBirth(colony, year = 2030)
getQueenYearOfBirth(colony)

apiary <- setQueensYearOfBirth(apiary, year = 2022)
getQueenYearOfBirth(apiary)
```

getSegSiteGeno *Access genotypes for all segregating sites of individuals in a caste*

Description

Level 0 function that returns genotypes for all segregating sites of individuals in a caste.

Usage

```
getSegSiteGeno(
  x,
  caste = NULL,
  nInd = NULL,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueenSegSiteGeno(x, chr = NULL, collapse = FALSE, simParamBee = NULL)

getFathersSegSiteGeno(
  x,
  nInd = NULL,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensSegSiteGeno(
  x,
  nInd = NULL,
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersSegSiteGeno(
  x,
  nInd = NULL,
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getDronesSegSiteGeno(
```

```
  x,
  nInd = NULL,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with genotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with genotypes when x is Colony-class and list of matrices with genotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenSegSiteGeno(): Access genotype data for all segregating sites of the queen
- getFathersSegSiteGeno(): Access genotype data for all segregating sites of fathers
- getVirginQueensSegSiteGeno(): Access genotype data for all segregating sites of virgin queens
- getWorkersSegSiteGeno(): Access genotype data for all segregating sites of workers
- getDronesSegSiteGeno(): Access genotype data for all segregating sites of drones

See Also

getSegSiteGeno and pullSegSiteGeno

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
```

```
drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getSegSiteGeno(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getSegSiteGeno(queens)

# Input is a colony
getSegSiteGeno(colony, caste = "queen")
getQueenSegSiteGeno(colony)

getSegSiteGeno(colony, caste = "workers", nInd = 3)
getWorkersSegSiteGeno(colony)
# same aliases exist for all the castes!

# Get genotypes for all individuals
getSegSiteGeno(colony, caste = "all")
# Get all genotypes in a single matrix
getSegSiteGeno(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony
getSegSiteGeno(apiary, caste = "queen")
getQueenSegSiteGeno(apiary)

# Get the genotypes of all individuals either by colony or in a single matrix
getSegSiteGeno(apiary, caste = "all")
getSegSiteGeno(apiary, caste = "all", collapse = TRUE)
```

`getSegSiteHaplo` *Access haplotypes for all segregating sites of individuals in a caste*

Description

Level 0 function that returns haplotypes for all segregating sites of individuals in a caste.

Usage

```
getSegSiteHaplo(
```

```
  x,
  caste = NULL,
  nInd = NULL,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueenSegSiteHaplo(
  x,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getFathersSegSiteHaplo(
  x,
  nInd = NULL,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensSegSiteHaplo(
  x,
  nInd = NULL,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersSegSiteHaplo(
  x,
  nInd = NULL,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getDronesSegSiteHaplo(
  x,
```

```
  nInd = NULL,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
haplo	character, either "all" for all haplotypes or an integer for a single set of haplotypes, use a value of 1 for female haplotypes and a value of 2 for male haplotypes
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with haplotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with haplotypes when x is Colony-class and list of matrices with haplotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenSegSiteHaplo(): Access haplotype data for all segregating sites of the queen
- getFathersSegSiteHaplo(): Access haplotype data for all segregating sites of fathers
- getVirginQueensSegSiteHaplo(): Access haplotype data for all segregating sites of virgin queens
- getWorkersSegSiteHaplo(): Access haplotype data for all segregating sites of workers
- getDronesSegSiteHaplo(): Access haplotype data for all segregating sites of drones

See Also

getSegSiteHaplo and pullSegSiteHaplo

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getSegSiteHaplo(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getSegSiteHaplo(queens)

# Input is a colony
getSegSiteHaplo(colony, caste = "queen")
getQueenSegSiteHaplo(colony)

getSegSiteHaplo(colony, caste = "workers", nInd = 3)
getWorkersSegSiteHaplo(colony)
#Same aliases exist for all the castes!

# Get haplotypes for all individuals
getSegSiteHaplo(colony, caste = "all")
# Get all haplotypes in a single matrix
getSegSiteHaplo(colony, caste = "all", collapse = TRUE)

#Input is a MultiColony - same behaviour as for the Colony!
getSegSiteHaplo(apiary, caste = "queen")
getQueenSegSiteHaplo(apiary)

# Get the haplotypes of all individuals either by colony or in a single matrix
getSegSiteHaplo(apiary, caste = "all")
getSegSiteHaplo(apiary, caste = "all", collapse = TRUE)
```

`getSnpGeno` *Access SNP array genotypes of individuals in a caste*

Description

Level 0 function that returns SNP array genotypes of individuals in a caste.

Usage

```
getSnpGeno(
  x,
  caste = NULL,
  nInd = NULL,
  snpChip = 1,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueenSnpGeno(
  x,
  snpChip = 1,
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getFathersSnpGeno(
  x,
  nInd = NULL,
  snpChip = 1,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensSnpGeno(
  x,
  nInd = NULL,
  snpChip = 1,
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersSnpGeno(
  x,
  nInd = NULL,
  snpChip = 1,
  chr = NULL,
```

```
  collapse = FALSE,
  simParamBee = NULL
)

getDronesSnpGeno(
  x,
  nInd = NULL,
  snpChip = 1,
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
snpChip	numeric, indicates which SNP array genotypes to retrieve
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with genotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with genotypes when x is Colony-class and list of matrices with genotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenSnpGeno(): Access SNP array genotype data of the queen
- getFathersSnpGeno(): Access SNP array genotype data of fathers
- getVirginQueensSnpGeno(): Access SNP array genotype data of virgin queens
- getWorkersSnpGeno(): Access SNP array genotype data of workers
- getDronesSnpGeno(): Access SNP array genotype data of drones

See Also

getSnpGeno and pullSnpGeno

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$addSnpChip(nSnpPerChr = 5)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getSnpGeno(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getSnpGeno(queens)

# Input is a colony
getSnpGeno(colony, caste = "queen")
getQueenSnpGeno(colony)

getSnpGeno(colony, caste = "workers", nInd = 3)
getWorkersSnpGeno(colony)
# Same aliases exist for all the castes!

# Get genotypes for all individuals
getSnpGeno(colony, caste = "all")
# Get all haplotypes in a single matrix
getSnpGeno(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony!
getSnpGeno(apiary, caste = "queen")
getQueenSnpGeno(apiary)

# Get the haplotypes of all individuals either by colony or in a single matrix
getSnpGeno(apiary, caste = "all")
getSnpGeno(apiary, caste = "all", collapse = TRUE)
```

`getSnpHaplo` *Access SNP array haplotypes of individuals in a caste*

Description

Level 0 function that returns SNP array haplotypes of individuals in a caste.

Usage

```
getSnpHaplo(
  x,
  caste = NULL,
  nInd = NULL,
  snpChip = 1,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getQueenSnpHaplo(
  x,
  snpChip = 1,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getFathersSnpHaplo(
  x,
  nInd = NULL,
  snpChip = 1,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

getVirginQueensSnpHaplo(
  x,
  nInd = NULL,
  snpChip = 1,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getWorkersSnpHaplo(
```

```
  x,
  nInd = NULL,
  snpChip = 1,
  haplo = "all",
  chr = NULL,
  collapse = FALSE,
  simParamBee = NULL
)

getDronesSnpHaplo(
  x,
  nInd = NULL,
  snpChip = 1,
  haplo = "all",
  chr = NULL,
  dronesHaploid = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
caste	NULL or character, NULL when x is a Pop-class, and character when x is a Colony-class or MultiColony-class with the possible values of "queen", "fathers", "workers", "drones", "virginQueens", or "all"
nInd	numeric, number of individuals to access, if NULL all individuals are accessed, otherwise a random sample
snpChip	numeric, indicates which SNP array haplotypes to retrieve
haplo	character, either "all" for all haplotypes or an integer for a single set of haplotypes, use a value of 1 for female haplotypes and a value of 2 for male haplotypes
chr	numeric, chromosomes to retrieve, if NULL, all chromosome are retrieved
dronesHaploid	logical, return haploid result for drones?
collapse	logical, if the return value should be a single matrix with haplotypes of all the individuals
simParamBee	SimParamBee, global simulation parameters

Value

matrix with haplotypes when x is Colony-class and list of matrices with haplotypes when x is MultiColony-class, named by colony id when x is MultiColony-class

Functions

- getQueenSnpHaplo(): Access SNP array haplotype data of the queen
- getFathersSnpHaplo(): Access SNP array haplotype data of fathers

- `getVirginQueensSnpHaplo()`: Access SNP array haplotype data of virgin queens
- `getWorkersSnpHaplo()`: Access SNP array haplotype of workers
- `getDronesSnpHaplo()`: Access SNP array haplotype data of drones

See Also

`getSnpHaplo` and `pullSnpHaplo`

Examples

```
founderGenomes <- quickHaplo(nInd = 4, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

SP$addSnpChip(nSnpPerChr = 5)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)

# Input is a population
getSnpHaplo(x = getQueen(colony))
queens <- getQueen(apiary, collapse = TRUE)
getSnpHaplo(queens)

# Input is a colony
getSnpHaplo(colony, caste = "queen")
getQueenSnpHaplo(colony)

getSnpHaplo(colony, caste = "workers", nInd = 3)
getWorkersSnpHaplo(colony)
# Same aliases exist for all the castes!

# Get haplotypes for all individuals
getSnpHaplo(colony, caste = "all")
# Get all haplotypes in a single matrix
getSnpHaplo(colony, caste = "all", collapse = TRUE)

# Input is a MultiColony - same behaviour as for the Colony!
getSnpHaplo(apiary, caste = "queen")
getQueenSnpHaplo(apiary)
```

```
# Get the haplotypes of all individuals either by colony or in a single matrix
getSnpHaplo(apiary, caste = "all")
getSnpHaplo(apiary, caste = "all", collapse = TRUE)
```

---

hasCollapsed *Test if colony has collapsed*

Description

Level 0 function that returns colony collapse status.

Usage

```
hasCollapsed(x)
```

Arguments

x	Colony-class or MultiColony-class

Value

logical, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(colony, nInd = 5)

hasCollapsed(colony)
colony <- collapse(colony)
hasCollapsed(colony)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)

hasCollapsed(apiary)
apiary <- collapse(apiary)
hasCollapsed(apiary)
```

hasSplit *Test if colony has split*

Description

Level 0 function that returns colony split status. This will obviously impact colony strength.

Usage

```
hasSplit(x)
```

Arguments

x	Colony-class or MultiColony-class

Value

logical, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)

hasSplit(colony)
tmp <- split(colony)
hasSplit(tmp$split)
hasSplit(tmp$remnant)

hasSplit(apiary)
tmp2 <- split(apiary)
hasSplit(tmp2$split)
hasSplit(tmp2$remnant)
```

hasSuperseded *Test if colony has superseded*

Description

Level 0 function that returns colony supersedure status.

Usage

```
hasSuperseded(x)
```

Arguments

x	Colony-class or MultiColony-class

Value

logical, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)

hasSuperseded(colony)
colony <- supersede(colony)
hasSuperseded(colony)

hasSuperseded(apiary)
apiary <- supersede(apiary)
hasSuperseded(apiary)
```

hasSwarmed *Test if colony has swarmed*

Description

Level 0 function that returns colony swarmed status. This will obviously have major impact on the colony and its downstream events.

Usage

```
hasSwarmed(x)
```

Arguments

x	Colony-class or MultiColony-class

Value

logical, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(colony, nInd = 5)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)

hasSwarmed(colony)
tmp <- swarm(colony)
hasSwarmed(tmp$swarm)
hasSwarmed(tmp$remnant)

hasSwarmed(apiary)
tmp2 <- swarm(apiary)
hasSwarmed(tmp2$swarm)
hasSwarmed(tmp2$remnant)
```

isCaste *Is individual a member of a specific caste*

Description

Level 0 function that tests if individuals are members of a specific caste

Usage

```
isCaste(x, caste, simParamBee = NULL)

isQueen(x, simParamBee = NULL)

isFather(x, simParamBee = NULL)

isWorker(x, simParamBee = NULL)

isDrone(x, simParamBee = NULL)

isVirginQueens(x, simParamBee = NULL)

isVirginQueen(x, simParamBee = NULL)
```

Arguments

x	Pop-class
caste	character, one of "queen", "fathers", "workers", "drones", or "virginQueens"; only single value is used
simParamBee	SimParamBee, global simulation parameters

Value

logical

Functions

- isQueen(): Is individual a queen
- isFather(): Is individual a father
- isWorker(): Is individual a worker
- isDrone(): Is individual a drone
- isVirginQueens(): Is individual a virgin queen
- isVirginQueen(): Is individual a virgin queen

See Also

isQueen, isFather, isVirginQueen, isWorker, and isDrone

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 120, nDrones = 20)
colony <- addVirginQueens(x = colony, nInd = 4)

isCaste(getQueen(colony), caste = "queen")
isCaste(getFathers(colony, nInd = 2), caste = "fathers")
isCaste(getWorkers(colony, nInd = 2), caste = "workers") # random sample!
isCaste(getDrones(colony, nInd = 2), caste = "drones")
isCaste(getVirginQueens(colony, nInd = 2), caste = "virginQueens")

bees <- c(
  getQueen(colony),
  getFathers(colony, nInd = 2),
  getWorkers(colony, nInd = 2),
  getDrones(colony, nInd = 2),
  getVirginQueens(colony, nInd = 2)
)
isCaste(bees, caste = "queen")
isCaste(bees, caste = "fathers")
isCaste(bees, caste = "workers")
isCaste(bees, caste = "drones")
isCaste(bees, caste = "virginQueens")

isQueen(getQueen(colony))
isQueen(getFathers(colony, nInd = 2))

isFather(getQueen(colony))
isFather(getFathers(colony, nInd = 2))

isWorker(getQueen(colony))
isWorker(getFathers(colony, nInd = 2))
isWorker(getWorkers(colony, nInd = 2))

isDrone(getQueen(colony))
isDrone(getFathers(colony, nInd = 2))
isDrone(getDrones(colony, nInd = 2))

isVirginQueen(getQueen(colony))
isVirginQueen(getFathers(colony, nInd = 2))
isVirginQueen(getVirginQueens(colony, nInd = 2))
```

isCsdActive *Is csd locus activated*

Description

Level 0 function that checks if the csd locus has been activated. See SimParamBee for more information about the csd locus.

Usage

```
isCsdActive(simParamBee = NULL)
```

Arguments

simParamBee	SimParamBee, global simulation parameters

Value

logical

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 3, segSites = 100)
SP <- SimParamBee$new(founderGenomes, csdChr = NULL)

isCsdActive()

SP <- SimParamBee$new(founderGenomes)

isCsdActive()
```

isCsdHeterozygous *Test if individuals are heterozygous at the csd locus*

Description

Level 0 function that returns if individuals of a population are heterozygous at the csd locus. See SimParamBee for more information about the csd locus.

Usage

```
isCsdHeterozygous(pop, simParamBee = NULL)
```

Arguments

pop	Pop-class
simParamBee	SimParamBee, global simulation parameters

Details

We could expand `isCsdHeterozygous` to work also with `Colony-class` and `MultiColony-class` if needed

Value

logical

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 4)

# Use isCsdHeterozygous on a Population
isCsdHeterozygous(getQueen(colony))
isCsdHeterozygous(getWorkers(colony))
```

---

isDronesPresent *Are drones present*

Description

Level 0 function that returns drones presence status (are they present or not).

Usage

```
isDronesPresent(x, simParamBee = NULL)
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`simParamBee`	`SimParamBee`, global simulation parameters

Value

logical, named by colony id when `x` is `MultiColony-class`

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 120, nDrones = 20)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10)

isDronesPresent(colony)
isDronesPresent(removeDrones(colony))
isDronesPresent(apiary)
isDronesPresent(removeDrones(apiary))
```

---

isEmpty *Check whether a population, colony or a multicolony object has no individuals within*

Description

Check whether a population, colony or a multicolony object has no individuals within.

Usage

```
isEmpty(x)
```

Arguments

x	Pop-class or Colony-class or MultiColony-class

Value

boolean when x is Pop-class or Colony-class, and named vector of boolean when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
```

```
isEmpty(new(Class = "Pop"))
isEmpty(basePop[0])
isEmpty(basePop)

emptyColony <- createColony()
nonEmptyColony <- createColony(basePop[1])
isEmpty(emptyColony)
isEmpty(nonEmptyColony)

emptyApiary <- createMultiColony(n = 3)
emptyApiary1 <- c(createColony(), createColony())
emptyApiary2 <- createMultiColony()
nonEmptyApiary <- createMultiColony(basePop[2:5], n = 4)

isEmpty(emptyApiary)
isEmpty(emptyApiary1)
isEmpty(nonEmptyApiary)
isNULLColonies(emptyApiary)
isNULLColonies(emptyApiary1)
isNULLColonies(nonEmptyApiary)

nEmptyColonies(emptyApiary)
nEmptyColonies(emptyApiary1)
nEmptyColonies(nonEmptyApiary)
nNULLColonies(emptyApiary)
nNULLColonies(emptyApiary1)
nNULLColonies(nonEmptyApiary)
```

`isFathersPresent` *Are fathers present (=queen mated)*

Description

Level 0 function that returns fathers presence status (are they present or not, which means the queen is mated).

Usage

```
isFathersPresent(x, simParamBee = NULL)

areFathersPresent(x, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
simParamBee	SimParamBee, global simulation parameters

Value

logical, named by colony id when x is MultiColony-class

Functions

- areFathersPresent(): Are fathers present

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
isFathersPresent(colony)
apiary <- createMultiColony(basePop[3:4], n = 2)
isFathersPresent(apiary)

colony <- cross(colony, drones = droneGroups[[1]])
isFathersPresent(removeDrones(colony))

apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
isFathersPresent(removeDrones(apiary))
```

---

isGenoHeterozygous *Test if a multilocus genotype is heterozygous*

Description

Level 0 function that returns heterozygote status for a multilocus genotype.

Usage

```
isGenoHeterozygous(x)
```

Arguments

x	integer or matrix, output from getCsdGeno

Value

logical # Not exporting this function, since its just a helper

`isNULLColonies` *Check which of the colonies in a multicolony are NULL*

Description

Check which of the colonies in a multicolony are NULL

Usage

```
isNULLColonies(multicolony)
```

Arguments

`multicolony`	`MultiColony-class`

Value

Named vector of boolean

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

emptyApiary <- createMultiColony(n = 3)
emptyApiary1 <- c(createColony(), createColony())
nonEmptyApiary <- createMultiColony(basePop[2:5], n = 4)

isEmpty(emptyApiary)
isEmpty(emptyApiary1)
isEmpty(nonEmptyApiary)
isNULLColonies(emptyApiary)
isNULLColonies(emptyApiary1)
isNULLColonies(nonEmptyApiary)

nEmptyColonies(emptyApiary)
nEmptyColonies(emptyApiary1)
nEmptyColonies(nonEmptyApiary)
nNULLColonies(emptyApiary)
nNULLColonies(emptyApiary1)
nNULLColonies(nonEmptyApiary)
```

isProductive *Test if colony is currently productive*

Description

Level 0 function that returns colony production status. This can be used to decided if colony production can be simulated.

Usage

```
isProductive(x)
```

Arguments

x	Colony-class or MultiColony-class

Value

logical, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])

isProductive(colony)
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
isProductive(colony)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

isProductive(apiary)
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
isProductive(apiary)
```

`isQueenPresent` *Is the queen present*

Description

Level 0 function that returns queen's presence status (is she present/alive or not).

Usage

```
isQueenPresent(x, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
simParamBee	SimParamBee, global simulation parameters

Value

logical, named by colony id when x is MultiColony-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 120, nDrones = 20)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10)

isQueenPresent(colony)
isQueenPresent(apiary)

colony <- removeQueen(colony)
isQueenPresent(colony)
```

isSimParamBee *Test if x is a SimParamBee class object*

Description

Test if x is a SimParamBee class object

Usage

```
isSimParamBee(x)
```

Arguments

x	SimParamBee

Value

logical

Examples

```
founderGenomes <- quickHaplo(nInd = 2, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

isSimParamBee(SP)
```

isVirginQueensPresent *Are virgin queen(s) present*

Description

Level 0 function that returns virgin queen(s) presence status.

Usage

```
isVirginQueensPresent(x, simParamBee = NULL)

isVirginQueenPresent(x, simParamBee = NULL)

areVirginQueensPresent(x, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
simParamBee	SimParamBee, global simulation parameters

Value

logical, named by colony id when x is MultiColony-class

Functions

- isVirginQueenPresent(): Are virgin queen(s) present
- areVirginQueensPresent(): Are virgin queen(s) present

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- addVirginQueens(x = colony, nInd = 4)
isVirginQueenPresent(colony)
isVirginQueenPresent(pullVirginQueens(colony)$remnant)
isVirginQueenPresent(removeQueen(colony))

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10)
isVirginQueenPresent(apiary)

tmp <- swarm(x = apiary)
isVirginQueenPresent(tmp$swarm)
isVirginQueenPresent(tmp$remnant)
```

---

isWorkersPresent *Are workers present*

Description

Level 0 function that returns workers presence status (are they present or not).

Usage

```
isWorkersPresent(x, simParamBee = NULL)

areWorkersPresent(x, simParamBee = NULL)

areDronesPresent(x, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
simParamBee	SimParamBee, global simulation parameters

Value

logical, named by colony id when x is MultiColony-class

Functions

- areWorkersPresent(): Are workers present
- areDronesPresent(): Are drones present

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 120, nDrones = 20)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10)

isWorkersPresent(colony)
isWorkersPresent(removeWorkers(colony))
isWorkersPresent(apiary)
isWorkersPresent(removeWorkers(apiary))
```

---

mapCasteToColonyValue *Map caste member (individual) values to a colony value*

Description

Maps caste member (individual) values to a colony value - for phenotype, genetic, breeding, dominance, and epistasis values. This function can be used as FUN argument in calcColonyValue function(s). It can also be saved in SimParamBee$colonyValueFUN as a default function called by calcColonyValue function(s).

This is just an example - quite a flexible one! You can provide your own "caste functions" that satisfy your needs within this mapping function (see queenFUN, workersFUN, and dronesFUN below) or

provide a complete replacement of this mapping function! For example, this mapping function does not cater for indirect (social) genetic effects where colony individuals value impacts value of other colony individuals. Note though that you can achieve this impact also via multiple correlated traits, such as a queen and a workers trait.

Usage

```
mapCasteToColonyValue(
  colony,
  value = "pheno",
  queenTrait = 1,
  queenFUN = function(x) x,
  workersTrait = 2,
  workersFUN = colSums,
  dronesTrait = NULL,
  dronesFUN = NULL,
  traitName = NULL,
  combineFUN = function(q, w, d) q + w,
  checkProduction = TRUE,
  notProductiveValue = 0,
  simParamBee = NULL
)

mapCasteToColonyPheno(colony, simParamBee = NULL, ...)

mapCasteToColonyGv(colony, simParamBee = NULL, ...)

mapCasteToColonyBv(colony, simParamBee = NULL, ...)

mapCasteToColonyDd(colony, simParamBee = NULL, ...)

mapCasteToColonyAa(colony, simParamBee = NULL, ...)
```

Arguments

colony	Colony-class
value	character, one of pheno or gv
queenTrait	numeric (column position) or character (column name), trait(s) that represents queen's contribution to colony value(s); if NULL then this contribution is 0; you can pass more than one trait here, but make sure that combineFUN works with these trait dimensions
queenFUN	function, function that will be applied to queen's value
workersTrait	numeric (column position) or character (column name), trait(s) that represents workers' contribution to colony value(s); if NULL then this contribution is 0; you can pass more than one trait here, but make sure that combineFUN works with these trait dimensions
workersFUN	function, function that will be applied to workers values

dronesTrait	numeric (column position) or character (column name), trait(s) that represents drones' contribution to colony value(s); if NULL then this contribution is 0; you can pass more than one trait here, but make sure that combineFUN works with these trait dimensions
dronesFUN	function, function that will be applied to drone values
traitName	the name of the colony trait(s), say, honeyYield; you can pass more than one trait name here, but make sure to match them with combineFUN trait dimensions
combineFUN	function that will combine the queen, worker, and drone contributions - this function should be defined as function(q, w, d) where q represents queen's, q represents workers', and d represents drones' contribution.
checkProduction	logical, does the value depend on the production status of colony; if yes and production is FALSE, the return is notProductiveValue - this will often make sense for colony phenotype value only; you can pass more than one logical value here (one per trait coming out of combineFUN)
notProductiveValue	numeric, returned value when colony is not productive; you can pass more than one logical value here (one per trait coming out of combineFUN)
simParamBee	SimParamBee, global simulation parameters
...	other arguments of mapCasteToColonyValue (for its aliases)

Details

This is a utility/mapping function meant to be called by calcColonyValue. It only works on a single colony - use calcColonyValue to get Colony or MultiColony values.

Value

numeric matrix with one value or a row of values

Functions

- mapCasteToColonyPheno(): Map caste member (individual) phenotype values to a colony phenotype value
- mapCasteToColonyGv(): Map caste member (individual) genetic values to a colony genetic value
- mapCasteToColonyBv(): Map caste member (individual) breeding values to a colony breeding value
- mapCasteToColonyDd(): Map caste member (individual) dominance values to a colony dominance value
- mapCasteToColonyAa(): Map caste member (individual) epistasis values to a colony epistasis value

See Also

SimParamBee field colonyValueFUN and functions calcColonyValue, calcColonyPheno, calcColonyGv, getEvents, pheno, and gv, as well as vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)


# Define two traits that collectively affect colony honey yield:
# 1) queen's effect on colony honey yield, say via pheromone secretion phenotype
# 2) workers' effect on colony honey yield, say via foraging ability phenotype
# The traits will have a negative genetic correlation of -0.5 and heritability
# of 0.25 (on an individual level)
nWorkers <- 10
mean <- c(10, 10 / nWorkers)
varA <- c(1, 1 / nWorkers)
corA <- matrix(data = c(
  1.0, -0.5,
  -0.5, 1.0
), nrow = 2, byrow = TRUE)
varE <- c(3, 3 / nWorkers)
varA / (varA + varE)
SP$addTraitADE(nQtlPerChr = 100,
               mean = mean,
               var = varA, corA = corA,
               meanDD = 0.1, varDD = 0.2, corD = corA,
               relAA = 0.1, corAA = corA)
SP$setVarE(varE = varE)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 10)
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = drones)
colony <- buildUp(colony, nWorkers = nWorkers, nDrones = 3)

# Colony value
mapCasteToColonyPheno(colony)
mapCasteToColonyGv(colony)

# To understand where the above values come from, study the contents of
# mapCasteToColonyValue() and the values below:

# Phenotype values
getQueenPheno(colony)
getWorkersPheno(colony)

# Genetic values
getQueenGv(colony)
getWorkersGv(colony)
```

`mapLoci` *Finds loci on a genetic map and return a list of positions*

Description

Finds loci on a genetic map and return a list of positions. This function is adopted from AlphaSimR (Gaynor et al., 2021)

Usage

```
mapLoci(markers, genMap)
```

Arguments

markers	character, vector of marker positions as "chr_position"
genMap	list, genetic map

Value

A list with number of loci per chromosome and genetic positions of the markers

---

MultiColony-class *Honeybee multicolony object*

Description

An object holding a collection of honeybee colonies. It behaves like a list.

Usage

```
isMultiColony(x)

## S4 method for signature 'MultiColony'
show(object)

## S4 method for signature 'MultiColony'
c(x, ...)

## S4 method for signature 'MultiColonyOrNULL'
c(x, ...)

## S4 method for signature 'MultiColony,integerOrNumericOrLogical'
x[i, j, drop]

## S4 method for signature 'MultiColony,character'
x[i, j, drop]

## S4 method for signature 'MultiColony,integerOrNumericOrLogical'
x[[i]]

## S4 method for signature 'MultiColony,character'
```

```
x[[i]]

## S4 replacement method for signature
## 'MultiColony,integerOrNumericOrLogicalOrCharacter,ANY,MultiColony'
x[i, j] <- value

## S4 replacement method for signature
## 'MultiColony,integerOrNumericOrLogicalOrCharacter,ANY,Colony'
x[[i, j]] <- value
```

Arguments

x	MultiColony-class
object	MultiColony-class
...	NULL, Colony-class, or MultiColony-class
i	integer, numeric, logical, or character, index or ID to select a colony (see examples)
j	not used
drop	not used
value	Colony-class or MultiColony-class to assign into x based on colony index or name i

Value

MultiColony-class or Colony-class

Functions

- isMultiColony(): Test if x is a MultiColony class object
- show(MultiColony): Show MultiColony object
- c(MultiColony): Combine multiple Colony and MultiColony objects
- c(MultiColonyOrNULL): Combine multiple Colony and MultiColony objects
- x[i: Extract a colony (one or more!) with an integer/numeric/logical index (position) (return MultiColony-class)
- x[i: Extract a colony (one or more!) with a character ID (name) (return MultiColony-class)
- x[[i: Extract a colony (just one!) with an integer/numeric/logical index (position) (return Colony-class)
- x[[i: Extract a colony (just one!) with a character ID (name) (return Colony-class)
- `[`(x = MultiColony, i = integerOrNumericOrLogicalOrCharacter, j = ANY) <- value: Assign colonies into MultiColony
- `[[`(x = MultiColony, i = integerOrNumericOrLogicalOrCharacter, j = ANY) <- value: Assign Colony into MultiColony

Slots

colonies list, a collection of Colony-class objects

See Also

createMultiColony

Examples

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)
apiary <- createMultiColony(basePop[1:6], n = 6)
apiary <- cross(apiary, drones = droneGroups[1:6])
apiary
show(apiary)
is(apiary)
isMultiColony(apiary)

getId(apiary)
apiary[1]
getId(apiary[1])
getId(apiary["2"])
getId(apiary[2])
getId(apiary[-1])
getId(apiary[5])

getId(apiary)
getId(apiary[c(1, 3)])
getId(apiary[c("2", "4")])
getId(apiary[c(TRUE, FALSE, TRUE, FALSE)])
getId(apiary[c(TRUE, FALSE)]) # beware of recycling!
getId(apiary[c(5, 6)])
getId(apiary[c("6", "7")])

apiary[[1]]
apiary[["2"]]
apiary[[3]]
apiary[["4"]]
try(apiary[[6]])
apiary[["7"]]

getId(c(apiary[c(1, 3)], apiary[2]))
getId(c(apiary[2], apiary[c(1, 3)]))

getId(c(apiary[2], apiary[0]))
getId(c(apiary[0], apiary[2]))

getId(c(apiary[2], NULL))
getId(c(NULL, apiary[2]))

apiary1 <- apiary[1:2]
```

```
apiary2 <- apiary[3:4]
getId(apiary1)
getId(apiary2)
apiary1[[1]] <- apiary2[[1]]
getId(apiary1)
try(apiary2[[1]] <- apiary2[[2]])

apiary1 <- apiary[1:2]
apiary2 <- apiary[3:5]
getId(apiary1)
getId(apiary2)
apiary2[1:2] <- apiary1
getId(apiary2)
try(apiary2[1] <- apiary1)
try(apiary2[1:3] <- apiary1)
try(apiary2[1:2] <- apiary1[[1]])

apiary2 <- apiary[3:5]
getId(apiary2)
try(apiary2[c("4", "5")] <- apiary1)
try(apiary2[c("4", "5")] <- apiary1)
```

`nCaste` *Level 0 function that returns the number of individuals of a caste in a colony*

Description

Returns the number of individuals of a caste in a colony

Usage

```
nCaste(x, caste = "all", simParamBee = NULL)

nQueens(x, simParamBee = NULL)

nFathers(x, simParamBee = NULL)

nWorkers(x, simParamBee = NULL)

nDrones(x, simParamBee = NULL)

nVirginQueens(x, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
caste	character, "queen", "fathers", "workers", "drones", "virginQueens", or "all"
simParamBee	SimParamBee, global simulation parameters

Value

when x is Colony-class return is integer for caste != "all" or list for caste == "all" with nodes named by caste; when x is MultiColony-class return is named integer for caste != "all" or named list of lists for caste == "all"

Functions

- nQueens(): Number of queens in a colony
- nFathers(): Number of fathers in a colony
- nWorkers(): Number of workers in a colony
- nDrones(): Number of drones in a colony
- nVirginQueens(): Number of virgin queens in a colony

See Also

nQueens, nFathers, nVirginQueens, nWorkers, and nDrones

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 100, nDrones = 10)
colony <- addVirginQueens(x = colony, nInd = 3)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10)
apiary <- addVirginQueens(x = apiary, nInd = 3)

# Check caste members
nCaste(colony, caste = "queen")
nCaste(colony, caste = "fathers")
nCaste(colony, caste = "virginQueens")
nCaste(colony, caste = "workers")
nCaste(colony, caste = "drones")
nCaste(colony, caste = "all")

nCaste(apiary, caste = "queen")
nCaste(apiary, caste = "fathers")
nCaste(apiary, caste = "virginQueens")
nCaste(apiary, caste = "workers")
```

```
nCaste(apiary, caste = "drones")
nCaste(apiary, caste = "all")

# Check number of queens
nQueens(colony)
nQueens(apiary)
apiary <- removeQueen(apiary)
nQueens(apiary)

# Check number of fathers
nFathers(colony)
nFathers(apiary)

# Check number of workers
nWorkers(colony)
nWorkers(apiary)

# Check number of drones
nDrones(colony)
nDrones(apiary)

# Check number of virgin queens
nVirginQueens(colony)
nVirginQueens(apiary)
```

`nColonies` *Number of colonies in a MultiColony object*

Description

Level 0 function that returns the number of colonies in a MultiColony object.

Usage

```
nColonies(multicolony)

nNULLColonies(multicolony)

nEmptyColonies(multicolony)
```

Arguments

`multicolony`	`MultiColony-class`

Value

integer

Functions

- nNULLColonies(): Number of NULL colonies in a MultiColony object
- nEmptyColonies(): Number of empty colonies in a MultiColony object

See Also

nNULLColonies and nEmptyColonies

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
emptyApiary <- createMultiColony(n = 3)
emptyApiary1 <- c(createColony(), createColony())
nonEmptyApiary <- createMultiColony(basePop[2:3], n = 2)

nColonies(nonEmptyApiary)
nColonies(emptyApiary)

isEmpty(emptyApiary)
isEmpty(emptyApiary1)
isEmpty(nonEmptyApiary)
isNULLColonies(emptyApiary)
isNULLColonies(emptyApiary1)
isNULLColonies(nonEmptyApiary)

nEmptyColonies(emptyApiary)
nEmptyColonies(emptyApiary1)
nEmptyColonies(nonEmptyApiary)
nNULLColonies(emptyApiary)
nNULLColonies(emptyApiary1)
nNULLColonies(nonEmptyApiary)
```

---

nCsdAlleles *Report the number of distinct csd alleles*

Description

Level 0 function that returns the number of distinct csd alleles in input. See SimParamBee for more information about the csd locus.

Usage

```
nCsdAlleles(x, collapse = FALSE, simParamBee = NULL)
```

Arguments

x	Pop-class, Colony-class, or MultiColony-class
collapse	logical, if TRUE, the function will return the number of distinct csd alleles in either the entire population, colony, or multicolony. Note this has nothing to do with the colony collapse. It's like paste(..., collapse = TRUE). Default is FALSE. See examples about this behaviour.Default is FALSE.
simParamBee	SimParamBee, global simulation parameters

Details

Queen has 2 distinct csd alleles, since she has to be heterozygous to be viable. The same holds for individual virgin queens and workers, but note that looking at csd genotypes of virgin queens or workers we are looking at a sample of 1 csd allele from the queen and 1 csd allele from their fathers, noting that homozygous genotypes are excluded. Therefore, nCsdAlleles() from virgin queens and workers is a noisy realisation of nCsdAlleles() from queens and fathers. For this reason, we also report nCsdAlleles() from queens and fathers combined (see the queenAndFathers list node) when x is Colony-class. This last measure is then the expected number of csd alleles in a colony as opposed to realised number of csd alleles in a sample of virgin queens and workers. Similarly as for virgin queens and workers, nCsdAlleles() from drones gives a noisy realisation of nCsdAlleles() from queens. The amount of noise will depend on the number of individuals, so in most cases with reasonable number of individuals there should be minimal amount of noise.

Value

integer representing the number of distinct csd alleles when x is Pop-class (or), list of integer when x is Colony-class (list nodes named by caste) and list of a list of integer when x is MultiColony-class, outer list is named by colony id when x is MultiColony-class; the integer rep

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 6, nDrones = 3)
colony <- addVirginQueens(x = colony, nInd = 4)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 6, nDrones = 3)
apiary <- addVirginQueens(x = apiary, nInd = 5)
```

```
nCsdAlleles(getQueen(colony))
nCsdAlleles(getWorkers(colony))

nCsdAlleles(colony)
nCsdAlleles(colony, collapse = TRUE)

nCsdAlleles(apiary)
nCsdAlleles(apiary, collapse = TRUE)
```

`nDronesPoisson` *Sample a number of drones*

Description

Sample a number of drones - used when `nDrones = NULL` (see `SimParamBee$nDrones`).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
nDronesPoisson(x, n = 1, average = 100)

nDronesTruncPoisson(x, n = 1, average = 100, lowerLimit = 0)

nDronesColonyPhenotype(
  x,
  queenTrait = 1,
  workersTrait = NULL,
  checkProduction = FALSE,
  lowerLimit = 0,
  simParamBee = NULL,
  ...
)
```

Arguments

`x`	`Pop-class` or `Colony-class`
`n`	integer, number of samples
`average`	numeric, average number of drones
`lowerLimit`	numeric, returned numbers will be above this value
`queenTrait`	numeric (column position) or character (column name), trait that represents queen's effect on the colony phenotype (defined in `SimParamBee` - see examples); if `0` then this effect is 0
`workersTrait`	numeric (column position) or character (column name), trait that represents workers's effect on the colony phenotype (defined in `SimParamBee` - see examples); if `0` then this effect is 0

checkProduction
: logical, does the phenotype depend on the production status of colony; if yes and production is not TRUE, the result is above lowerLimit

simParamBee
: SimParamBee, global simulation parameters

...
: other arguments of mapCasteToColonyPheno

Details

nDronesPoisson samples from a Poisson distribution with a given average, which can return a value 0.

nDronesTruncPoisson samples from a zero truncated Poisson distribution.

nDronesColonyPhenotype returns a number (above lowerLimit) as a function of colony phenotype, say queen's fecundity. Colony phenotype is provided by mapCasteToColonyPheno. You need to set up traits influencing the colony phenotype and their parameters (mean and variances) via SimParamBee (see examples).

When x is Pop-class, only workersTrait is not used, that is, only queenTrait is used.

Value

numeric, number of drones

Functions

- nDronesTruncPoisson(): Sample a non-zero number of drones
- nDronesColonyPhenotype(): Sample a non-zero number of drones based on colony phenotype, say queen's fecundity

See Also

SimParamBee field nDrones and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
nDronesPoisson()
nDronesPoisson()
n <- nDronesPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 200))
table(n)

nDronesTruncPoisson()
nDronesTruncPoisson()
n <- nDronesTruncPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 200))
table(n)

# Example for nDronesColonyPhenotype()
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)
```

```
average <- 100
h2 <- 0.1
SP$addTraitA(nQtlPerChr = 100, mean = average, var = average * h2)
SP$setVarE(varE = average * (1 - h2))
basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 50)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 2, nDrones = 15)
colony1 <- createColony(x = basePop[2])
colony2 <- createColony(x = basePop[3])
colony1 <- cross(colony1, drones = droneGroups[[1]])
colony2 <- cross(colony2, drones = droneGroups[[2]])
colony1@queen@pheno
colony2@queen@pheno
createDrones(colony1, nInd = nDronesColonyPhenotype)
createDrones(colony2, nInd = nDronesColonyPhenotype)
```

`nFathersPoisson` *Sample a number of fathers*

Description

Sample a number of fathers - use when `nFathers = NULL` (see `SimParamBee$nFathers`).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
nFathersPoisson(n = 1, average = 15)

nFathersTruncPoisson(n = 1, average = 15, lowerLimit = 0)
```

Arguments

`n`	integer, number of samples
`average`	numeric, average number of fathers
`lowerLimit`	numeric, returned numbers will be above this value

Details

`nFathersPoisson` samples from a Poisson distribution, which can return a value 0 (that would mean a failed queen mating).

`nFathersTruncPoisson` samples from a truncated Poisson distribution (truncated at zero) to avoid failed matings.

Value

numeric, number of fathers

Functions

- `nFathersTruncPoisson()`: Sample a non-zero number of fathers

See Also

`SimParamBee` field `nFathers`

Examples

```
nFathersPoisson()
nFathersPoisson()
n <- nFathersPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 40))
table(n)

nFathersTruncPoisson()
nFathersTruncPoisson()
n <- nFathersTruncPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 40))
table(n)
```

---

nVirginQueensPoisson *Sample a number of virgin queens*

Description

Sample a number of virgin queens - used when `nFathers = NULL` (see `SimParamBee$nVirginQueens`).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
nVirginQueensPoisson(colony, n = 1, average = 10)

nVirginQueensTruncPoisson(colony, n = 1, average = 10, lowerLimit = 0)

nVirginQueensColonyPhenotype(
  colony,
  queenTrait = 1,
  workersTrait = 2,
  checkProduction = FALSE,
  lowerLimit = 0,
  simParamBee = NULL,
  ...
)
```

Arguments

colony	Colony-class
n	integer, number of samples
average	numeric, average number of virgin queens
lowerLimit	numeric, returned numbers will be above this value
queenTrait	numeric (column position) or character (column name), trait that represents queen's effect on the colony phenotype (defined in SimParamBee - see examples); if NULL then this effect is 0
workersTrait	numeric (column position) or character (column name), trait that represents workers's effect on the colony phenotype (defined in SimParamBee - see examples); if NULL then this effect is 0
checkProduction	logical, does the phenotype depend on the production status of colony; if yes and production is not TRUE, the result is above lowerLimit
simParamBee	SimParamBee, global simulation parameters
...	other arguments of mapCasteToColonyPheno

Details

nVirginQueensPoisson samples from a Poisson distribution, which can return a value 0 (that would mean a colony will fail to raise a single virgin queen after the queen swarms or dies).

nVirginQueensTruncPoisson samples from a truncated Poisson distribution (truncated at zero) to avoid failure.

nVirginQueensColonyPhenotype returns a number (above lowerLimit) as a function of colony phenotype, say swarming tendency. Colony phenotype is provided by mapCasteToColonyPheno. You need to set up traits influencing the colony phenotype and their parameters (mean and variances) via SimParamBee (see examples).

Value

numeric, number of virgin queens

Functions

- nVirginQueensTruncPoisson(): Sample a non-zero number of virgin queens
- nVirginQueensColonyPhenotype(): Sample a non-zero number of virgin queens based on colony's phenotype, say, swarming tendency

See Also

SimParamBee field nVirginQueens and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
nVirginQueensPoisson()
nVirginQueensPoisson()
n <- nVirginQueensPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 30))
table(n)

nVirginQueensTruncPoisson()
nVirginQueensTruncPoisson()
n <- nVirginQueensTruncPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 30))
table(n)

# Example for nVirginQueensColonyPhenotype()
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

# Setting trait scale such that mean is 10 split into queen and workers effects
meanP <- c(5, 5 / SP$nWorkers)
# setup variances such that the total phenotype variance will match the mean
varA <- c(3 / 2, 3 / 2 / SP$nWorkers)
corA <- matrix(data = c(
  1.0, -0.5,
  -0.5, 1.0
), nrow = 2, byrow = TRUE)
varE <- c(7 / 2, 7 / 2 / SP$nWorkers)
varA / (varA + varE)
varP <- varA + varE
varP[1] + varP[2] * SP$nWorkers
SP$addTraitA(nQtlPerChr = 100, mean = meanP, var = varA, corA = corA)
SP$setVarE(varE = varE)
basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 50)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 2, nDrones = 15)
colony1 <- createColony(x = basePop[2])
colony2 <- createColony(x = basePop[3])
colony1 <- cross(colony1, drones = droneGroups[[1]])
colony2 <- cross(colony2, drones = droneGroups[[2]])
colony1 <- buildUp(colony1)
colony2 <- buildUp(colony2)
nVirginQueensColonyPhenotype(colony1)
nVirginQueensColonyPhenotype(colony2)
```

`nWorkersPoisson` *Sample a number of workers*

Description

Sample a number of workers - used when `nInd = NULL` (see `SimParamBee$nWorkers`).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
nWorkersPoisson(colony, n = 1, average = 100)

nWorkersTruncPoisson(colony, n = 1, average = 100, lowerLimit = 0)

nWorkersColonyPhenotype(
  colony,
  queenTrait = 1,
  workersTrait = NULL,
  checkProduction = FALSE,
  lowerLimit = 0,
  simParamBee = NULL,
  ...
)
```

Arguments

colony	Colony-class
n	integer, number of samples
average	numeric, average number of workers
lowerLimit	numeric, returned numbers will be above this value
queenTrait	numeric (column position) or character (column name), trait that represents queen's effect on the colony phenotype (defined in SimParamBee - see examples); if 0 then this effect is 0
workersTrait	numeric (column position) or character (column name), trait that represents workers's effect on the colony phenotype (defined in SimParamBee - see examples); if 0 then this effect is 0
checkProduction	logical, does the phenotype depend on the production status of colony; if yes and production is not TRUE, the result is above lowerLimit
simParamBee	SimParamBee, global simulation parameters
...	other arguments of mapCasteToColonyPheno

Details

nWorkersPoisson samples from a Poisson distribution with a given average, which can return a value 0. nDronesTruncPoisson samples from a zero truncated Poisson distribution.

nWorkersColonyPhenotype returns a number (above lowerLimit) as a function of colony phenotype, say queen's fecundity. Colony phenotype is provided by mapCasteToColonyPheno. You need to set up traits influencing the colony phenotype and their parameters (mean and variances) via SimParamBee (see examples).

Value

numeric, number of workers

Functions

- nWorkersTruncPoisson(): Sample a non-zero number of workers
- nWorkersColonyPhenotype(): Sample a non-zero number of workers based on colony phenotype, say queen's fecundity

See Also

SimParamBee field nWorkers and vignette(topic = "QuantitativeGenetics", package = "SIMplyBee")

Examples

```
nWorkersPoisson()
nWorkersPoisson()
n <- nWorkersPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 200))
table(n)

nWorkersTruncPoisson()
nWorkersTruncPoisson()
n <- nWorkersTruncPoisson(n = 1000)
hist(n, breaks = seq(from = min(n), to = max(n)), xlim = c(0, 200))
table(n)

# Example for nWorkersColonyPhenotype()
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

average <- 100
h2 <- 0.1
SP$addTraitA(nQtlPerChr = 100, mean = average, var = average * h2)
SP$setVarE(varE = average * (1 - h2))
basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 50)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 2, nDrones = 15)
colony1 <- createColony(x = basePop[2])
colony2 <- createColony(x = basePop[3])
colony1 <- cross(colony1, drones = droneGroups[[1]])
colony2 <- cross(colony2, drones = droneGroups[[2]])
colony1@queen@pheno
colony2@queen@pheno
createWorkers(colony1, nInd = nWorkersColonyPhenotype)
createWorkers(colony2, nInd = nWorkersColonyPhenotype)
```

---

pullCastePop *Pull individuals from a caste in a colony*

Description

Level 1 function that pulls individuals from a caste in a colony. These individuals are removed from the colony (compared to getCaste).

Usage

```
pullCastePop(
  x,
  caste,
  nInd = NULL,
  use = "rand",
  removeFathers = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

pullQueen(x, collapse = FALSE, simParamBee = NULL)

pullWorkers(x, nInd = NULL, use = "rand", collapse = FALSE, simParamBee = NULL)

pullDrones(
  x,
  nInd = NULL,
  use = "rand",
  removeFathers = TRUE,
  collapse = FALSE,
  simParamBee = NULL
)

pullVirginQueens(
  x,
  nInd = NULL,
  use = "rand",
  collapse = FALSE,
  simParamBee = NULL
)
```

Arguments

x	Colony-class or MultiColony-class
caste	character, "queen", "workers", "drones", or "virginQueens"
nInd	numeric, number of individuals to pull, if NULL all individuals are pulled. If input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies.
use	character, all options provided by selectInd
removeFathers	logical, removes drones that have already mated; set to FALSE if you would like to get drones for mating with multiple virgin queens, say via insemination
collapse	logical, whether to return a single merged population for the pulled individuals (does not affect the remnant colonies)
simParamBee	SimParamBee, global simulation parameters

Value

list of Pop-class and Colony-class when x is Colony-class and list of (a list of Pop-class named by colony id) and MultiColony-class when x is MultiColony-class

Functions

- pullQueen(): Pull queen from a colony
- pullWorkers(): Pull workers from a colony
- pullDrones(): Pull drones from a colony
- pullVirginQueens(): Pull virgin queens from a colony

See Also

pullQueen, pullVirginQueens, pullWorkers, and pullDrones

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(x = colony, nWorkers = 100, nDrones = 10, exact = TRUE)
colony <- addVirginQueens(x = colony, nInd = 3)

apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])
apiary <- buildUp(x = apiary, nWorkers = 100, nDrones = 10, exact = TRUE)
apiary <- addVirginQueens(x = apiary, nInd = 3)

# pullCastePop on Colony class
# We can't pull the queen and leave the colony queenless
pullCastePop(colony, caste = "virginQueens")
pullCastePop(colony, caste = "virginQueens", nInd = 2)
# Or use aliases
pullVirginQueens(colony)
pullVirginQueens(colony, nInd = 2)
# Same aliases exist for all the castes!!!

# pullCastePop on MultiColony class - same behaviour as for the Colony!
pullCastePop(apiary, caste = "workers")
# Or pull out unequal number of workers from colonies
pullCastePop(apiary, caste = "workers", nInd = c(10, 20))
pullWorkers(apiary)
```

```
nWorkers(apiary)
nWorkers(pullWorkers(apiary)$remnant)


# Merge all the pulled populations into a single population
pullCastePop(apiary, caste = "queen", collapse = TRUE)
pullCastePop(apiary, caste = "virginQueens", collapse = TRUE)
```

`pullColonies` *Pull out some colonies from the MultiColony object*

Description

Level 3 function that pulls out some colonies from the MultiColony based on colony ID or random selection.

Usage

```
pullColonies(
  multicolony,
  ID = NULL,
  n = NULL,
  p = NULL,
  by = NULL,
  pullTop = TRUE,
  simParamBee = NULL
)
```

Arguments

`multicolony`	`MultiColony-class`
`ID`	character or numeric, ID of a colony (one or more) to be pulled out
`n`	numeric, number of colonies to select
`p`	numeric, percentage of colonies pulled out (takes precedence over `n`)
`by`	matrix, matrix of values to select by with names being colony IDs (can be obtained with `calcColonyValue`. If NULL, the colonies are pulled at random. This parameter is used in combination with `n` or `p` to determine the number of pulled colonies, and `pullTop` to determine whether to pull the best or the worst colonies.
`pullTop`	logical, pull highest (lowest) values if `TRUE` (`FALSE`)
`simParamBee`	`SimParamBee`, global simulation parameters

Value

list with two `MultiColony-class`, the `pulled` and the `remnant`

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

mean <- c(10, 10 / SP$nWorkers)
varA <- c(1, 1 / SP$nWorkers)
corA <- matrix(data = c(
  1.0, -0.5,
  -0.5, 1.0
), nrow = 2, byrow = TRUE)
varE <- c(3, 3 / SP$nWorkers)
varA / (varA + varE)
SP$addTraitADE(nQtlPerChr = 100,
               mean = mean,
               var = varA, corA = corA,
               meanDD = 0.1, varDD = 0.2, corD = corA,
               relAA = 0.1, corAA = corA)
SP$setVarE(varE = varE)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1:4], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)
apiary <- createMultiColony(basePop[2:5], n = 4)
apiary <- cross(apiary, drones = droneGroups[1:4])
apiary <- buildUp(apiary)
getId(apiary)

tmp <- pullColonies(apiary, ID = c(1, 2))
getId(tmp$pulled)
getId(tmp$remnant)

tmp <- pullColonies(apiary, ID = c("3", "4"))
getId(tmp$pulled)
getId(tmp$remnant)

tmp <- pullColonies(apiary, n = 2)
getId(tmp$pulled)
getId(tmp$remnant)

tmp <- pullColonies(apiary, p = 0.75)
getId(tmp$pulled)
getId(tmp$remnant)

# How to pull out colonies based on colony values?
colonyGv <- calcColonyGv(apiary)
pullColonies(apiary, n = 1, by = colonyGv)
```

`pullDroneGroupsFromDCA` *Pulls drone groups from a Drone Congregation Area (DCA)*

Description

Level 1 function that pulls drone groups from a Drone Congregation Area (DCA) to use them later in mating. Within the function drones are pulled (removed) from the DCA to reflect the fact that drones die after mating, so they can't be present in the DCA anymore. Be careful what you do with the DCA object outside function to avoid drone "copies".

Usage

```
pullDroneGroupsFromDCA(DCA, n, nDrones = NULL, simParamBee = NULL, ...)
```

Arguments

DCA	Pop-class, population of drones
n	integer, number of drone groups to be created
nDrones	numeric of function, number of drones that a virgin queen mates with; if NULL then SimParamBee$nFathers is used
simParamBee	SimParamBee, global simulation parameters
...	additional arguments passed to nDrones when this argument is a function

Value

list of Pop-class

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- addDrones(colony, nInd = 100)

# Create colony DCA
DCA <- createDCA(colony)
pullDroneGroupsFromDCA(DCA, n = 4, nDrones = 5)
pullDroneGroupsFromDCA(DCA, n = 5, nDrones = nFathersPoisson)
```

pullInd *Pull individuals from a population*

Description

Level 1 function that pulls individuals from a population and update the population (these individuals don't stay in a population).

Usage

```
pullInd(pop, nInd = NULL, use = "rand", simParamBee = NULL)
```

Arguments

pop	Pop-class
nInd	numeric, number of individuals to pull, if NULL pull all individuals
use	character, all options provided by selectInd
simParamBee	SimParamBee, global simulation parameters

Value

list with a node pulled holding Pop-class of pulled individuals and a node remnant) holding Pop-class of remaining individuals

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 100)
SP <- SimParam$new(founderGenomes)

basePop <- newPop(founderGenomes)

pullInd(basePop, nInd = 2)
pullInd(basePop, nInd = 3)
pullInd(basePop)
```

rcircle *Sample random points within a circle*

Description

Level 0 function that samples random points (x, y) within a circle via rejection sampling.

Usage

```
rcircle(n = 1, radius = 1, uniform = TRUE, normScale = 1/3)
```

Arguments

n	integer, number of samples points
radius	numeric, radius of the sampled circle
uniform	logical, should sampling be uniform or according to a bi-variate spherical (uncorrelated) Gaussian distribution (see examples)
normScale	numeric, if uniform = FALSE, a factor to scale radius to standard deviation of the Gaussian density in x and in y (see examples)

Value

matrix with two columns for the x and y coordinates of the points.

References

nubDotDev (2021) The BEST Way to Find a Random Point in a Circle https://youtu.be/4y_nmpv-9lI

Wolfram MathWorld (2023) Disk Point Picking https://mathworld.wolfram.com/DiskPointPicking.html

Examples

```
x <- rcircle(n = 500)
lim <- range(x)
plot(x, xlim = lim, ylim = lim, main = "Uniform")

x <- rcircle(n = 500, uniform = FALSE)
lim <- range(x)
plot(x, xlim = lim, ylim = lim, main = "Gaussian")
```

---

reduceDroneGeno *Reduce drones' genotype to a single haplotype*

Description

Level 0 function that reduces drone's genotype to a single haplotype, because we internally simulate them as diploid (doubled haploid). This is an internal utility function that you likely don't need to use.

Usage

```
reduceDroneGeno(geno, pop)
```

Arguments

geno	matrix-class
pop	Pop-class

Value

matrix with genotype as one haplotype per drone instead of two - the order of individuals and the number of rows stays the same!

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 5)
SP <- SimParamBee$new(founderGenomes, csdChr = NULL)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 2)

(tmp <- getSegSiteGeno(drones))
reduceDroneGeno(geno = tmp, pop = drones)

(tmp <- getSegSiteGeno(c(basePop, drones)))
reduceDroneGeno(geno = tmp, pop = c(basePop, drones))
```

---

reduceDroneHaplo *Reduce drone's double haplotypes to a single haplotype*

Description

Level 0 function that returns one haplotype of drones, because we internally simulate them as diploid (doubled haploid). This is an internal utility function that you likely don't need to use.

Usage

```
reduceDroneHaplo(haplo, pop)
```

Arguments

haplo	matrix-class
pop	Pop-class

Details

While this function is meant to work on male (drone) haplotypes, we handle cases where the haplo matrix contains male and female haplotypes, which is why you need to provide pop. We only reduce haplotypes for males though.

Value

matrix with one haplotype per drone instead of two - the order of individuals stays the same, but there will be less rows!

Examples

```
founderGenomes <- quickHaplo(nInd = 3, nChr = 1, segSites = 5)
SP <- SimParamBee$new(founderGenomes, csdChr = NULL)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 2)

(tmp <- getSegSiteHaplo(drones, dronesHaploid = FALSE))
reduceDroneHaplo(haplo = tmp, pop = drones)

(tmp <- getSegSiteHaplo(c(basePop, drones), dronesHaploid = FALSE))
reduceDroneHaplo(haplo = tmp, pop = c(basePop, drones))
```

---

removeCastePop *Remove a proportion of caste individuals from a colony*

Description

Level 2 function that removes a proportion of virgin queens of a Colony or MultiColony object

Usage

```
removeCastePop(
  x,
  caste = NULL,
  p = 1,
  use = "rand",
  addVirginQueens = FALSE,
  nVirginQueens = NULL,
  year = NULL,
  simParamBee = NULL
)

removeQueen(
  x,
  addVirginQueens = FALSE,
  nVirginQueens = NULL,
  year = NULL,
  simParamBee = NULL
)

removeWorkers(x, p = 1, use = "rand", simParamBee = NULL)

removeDrones(x, p = 1, use = "rand", simParamBee = NULL)

removeVirginQueens(x, p = 1, use = "rand", simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
caste	character, "queen", "workers", "drones", or "virginQueens"
p	numeric, proportion to be removed; if input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies
use	character, all the options provided by selectInd - guides selection of virgins queens that will stay when p < 1
addVirginQueens	logical, whether virgin queens should be added; only used when removing the queen from the colony
nVirginQueens	integer, the number of virgin queens to be created in the colony; only used when removing the queen from the colony. If 0, no virgin queens are added; If NULL, the value from simParamBee$nVirginQueens is used
year	numeric, only relevant when adding virgin queens - year of birth for virgin queens
simParamBee	SimParamBee, global simulation parameters

Value

Colony-class or MultiColony-class without virgin queens

Functions

- removeQueen(): Remove queen from a colony
- removeWorkers(): Remove workers from a colony
- removeDrones(): Remove workers from a colony
- removeVirginQueens(): Remove virgin queens from a colony

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 5, nDrones = nFathersPoisson)

# Create and cross Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
colony <- buildUp(colony)
apiary <- createMultiColony(basePop[4:5], n = 2)
apiary <- cross(apiary, drones = droneGroups[3:4])
apiary <- buildUp(apiary)
```

```
# Remove workers
nWorkers(colony)
colony <- removeCastePop(colony, caste = "workers", p = 0.3)
# or alias:
colony <- removeWorkers(colony, p = 0.3)
# Same aliases exist for all the castes!!

nWorkers(apiary)
apiary <- removeCastePop(apiary, caste = "workers", p = 0.3)
nWorkers(apiary)

# Remove different proportions
apiary <- buildUp(apiary)
nWorkers(apiary)
nWorkers(removeWorkers(apiary, p = c(0.1, 0.5)))
```

`removeColonies` *Remove some colonies from the MultiColony object*

Description

Level 3 function that removes some colonies from the MultiColony object based on their ID.

Usage

```
removeColonies(
  multicolony,
  ID = NULL,
  n = NULL,
  p = NULL,
  by = NULL,
  removeTop = FALSE,
  simParamBee = NULL
)
```

Arguments

multicolony	MultiColony-class
ID	character or numeric, ID of a colony (one or more) to be removed
n	numeric, number of colonies to remove
p	numeric, percentage of colonies removed (takes precedence over n)
by	matrix, matrix of values to select by with names being colony IDs (can be obtained with calcColonyValue. If NULL, the colonies are removed at random. This parameter is used in combination with n or p to determine the number of removed colonies, and removeTop to determine whether to remove the best or the worst colonies.
removeTop	logical, remove highest (lowest) values if TRUE (FALSE)
simParamBee	SimParamBee, global simulation parameters

Value

MultiColony-class with some colonies removed

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

mean <- c(10, 10 / SP$nWorkers)
varA <- c(1, 1 / SP$nWorkers)
corA <- matrix(data = c(
  1.0, -0.5,
  -0.5, 1.0
), nrow = 2, byrow = TRUE)
varE <- c(3, 3 / SP$nWorkers)
varA / (varA + varE)
SP$addTraitADE(nQtlPerChr = 100,
               mean = mean,
               var = varA, corA = corA,
               meanDD = 0.1, varDD = 0.2, corD = corA,
               relAA = 0.1, corAA = corA)
SP$setVarE(varE = varE)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1:4], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)
apiary <- createMultiColony(basePop[2:5], n = 4)
apiary <- cross(apiary, drones = droneGroups[1:4])
apiary <- buildUp(apiary)
getId(apiary)

getId(removeColonies(apiary, ID = 1))
getId(removeColonies(apiary, ID = c("3", "4")))

nColonies(apiary)
apiary <- removeColonies(apiary, ID = "2")
nColonies(apiary)

# How to remove colonies based on colony values?
# Obtain colony phenotype
colonyPheno <- calcColonyPheno(apiary)
# Remove the worst colony
removeColonies(apiary, n = 1, by = colonyPheno)
```

---

replaceCastePop *Replace a proportion of caste individuals with new ones*

Description

Level 2 function that replaces a proportion of caste individuals with new individuals from a Colony or MultiColony object. Useful after events like season change, swarming, supersedure, etc. due to the short life span honeybees.

Usage

```
replaceCastePop(
  x,
  caste = NULL,
  p = 1,
  use = "rand",
  exact = TRUE,
  year = NULL,
  simParamBee = NULL
)

replaceWorkers(x, p = 1, use = "rand", exact = TRUE, simParamBee = NULL)

replaceDrones(x, p = 1, use = "rand", simParamBee = NULL)

replaceVirginQueens(x, p = 1, use = "rand", simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
caste	character, "workers", "drones", or "virginQueens"
p	numeric, proportion of caste individuals to be replaced with new ones; if input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies
use	character, all the options provided by selectInd - guides selection of caste individuals that stay when p < 1
exact	logical, only relevant when adding workers - if the csd locus is turned on and exact is TRUE, we replace the exact specified number of viable workers (heterozygous at the csd locus). You probably want this set to TRUE since you want to replace with the same number of workers.
year	numeric, only relevant when replacing virgin queens, year of birth for virgin queens
simParamBee	SimParamBee, global simulation parameters

Value

Colony-class or or MultiColony-class with replaced virgin queens

Functions

- `replaceWorkers()`: Replaces some workers in a colony
- `replaceDrones()`: Replaces some drones in a colony
- `replaceVirginQueens()`: Replaces some virgin queens in a colony

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 5, nDrones = nFathersPoisson)

# Create and cross Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[4:5], n = 2)
apiary <- cross(apiary, drones = droneGroups[3:4])

# Add individuals
colony <- buildUp(colony, nWorkers = 5, nDrones = 2)
apiary <- buildUp(apiary, nWorkers = 5, nDrones = 2)

# Replace workers in a colony
getCasteId(colony, caste = "workers")
colony <- replaceCastePop(colony, caste = "workers", p = 0.5)
# You can also use an alias
replaceWorkers(colony, p = 0.5)
# Same aliases exist for all the castes!!!
getCasteId(colony, caste = "workers")

getCasteId(apiary, caste="workers")
apiary <- replaceWorkers(apiary, p = 0.5)
getCasteId(apiary, caste="workers")
```

---

reQueen *Re-queen*

Description

Level 2 function that re-queens a Colony or MultiColony object by adding a mated or a virgin queen, removing the previous queen, and changing the colony id to the new mated queen.

Usage

```
reQueen(x, queen, removeVirginQueens = TRUE, simParamBee = NULL)
```

Arguments

x	Colony-class or MultiColony-class
queen	Pop-class with one individual that will be the queen of the colony; if she is not mated, she will be added as a virgin queen that will have to be mated later; test will be run if the individual isVirginQueen or isQueen
removeVirginQueens	logical, remove existing virgin queens, default is TRUE since bee-keepers tend to remove any virgin queen cells to ensure the provided queen prevails (see details)
simParamBee	SimParamBee, global simulation parameters

Details

If the provided queen is mated, then she is saved in the queen slot of the colony. If she is not mated, then she is saved in the virgin queen slot (replacing any existing virgin queens) and once she is mated will be promoted to the queen of the colony.

Value

Colony-class or MultiColony-class with new queen(s) (see details)

Examples

```
founderGenomes <- quickHaplo(nInd = 12, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 200)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 7, nDrones = nFathersPoisson)

# Create and cross Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[2:3])

# Check queen and virgin queens IDs
getCasteId(colony, caste = "queen")
getCasteId(colony, caste = "virginQueens")
getCasteId(apiary, caste = "queen")
getCasteId(apiary, caste = "virginQueens")

# Requeen with virgin queens
virginQueens <- basePop[5:8]
# Requeen a Colony class
colony <- reQueen(colony, queen = virginQueens[1])
# Check queen and virgin queens IDs
getCasteId(colony, caste = "queen")
getCasteId(colony, caste = "virginQueens")
```

```
#' # Requeen with mated queens
matedQueens <- cross(x = basePop[9:12], drones = droneGroups[4:7])
colony <- reQueen(colony, queen = matedQueens[1])
# Check queen and virgin queens IDs
getCasteId(colony, caste = "queen")
getCasteId(colony, caste = "virginQueens")

# Requeen a MultiColony class
apiary <- reQueen(apiary, queen = virginQueens[2:3])
# Check queen and virgin queens IDs
getCasteId(apiary, caste = "queen")
getCasteId(apiary, caste = "virginQueens")
```

`resetEvents` *Reset colony events*

Description

Level 2 function that resets the slots swarm, split, supersedure, collapsed, and production to FALSE in a Colony or MultiColony object. Useful at the end of a yearly cycle to reset the events, allowing the user to track new events in a new year.

Usage

```
resetEvents(x, collapse = NULL)
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`collapse`	logical, reset the collapse event (only sensible in setting up a new colony, which the default of `NULL` caters for; otherwise, a collapsed colony should be left collapsed forever, unless you force resetting this event with `collapse = TRUE`)

Value

`Colony-class` or `MultiColony-class` with events reset

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 5, nDrones = nFathersPoisson)

# Create and cross Colony and MultiColony class
```

```
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[4:5], n = 2)
apiary <- cross(apiary, drones = droneGroups[3:4])

# Build-up - this sets Productive to TRUE
(colony <- buildUp(colony, nWorkers = 100))
isProductive(colony)
resetEvents(colony)

apiary <- buildUp(apiary, nWorkers = 100)
isProductive(apiary)
resetEvents(apiary)

# Split - this sets Split to TRUE
tmp <- split(colony)
(split <- tmp$split)
hasSplit(split)
resetEvents(split)
(remnant <- tmp$remnant)
hasSplit(remnant)
resetEvents(remnant)

# Swarm - this sets Swarm to TRUE
tmp <- swarm(colony)
(swarm <- tmp$swarm)
hasSwarmed(swarm)
resetEvents(swarm)
(remnant <- tmp$remnant)
hasSwarmed(remnant)
resetEvents(remnant)

# Supersede - this sets Supersede to TRUE
(tmp <- supersede(colony))
hasSuperseded(tmp)
resetEvents(tmp)

# Collapse - this sets Collapse to TRUE
(tmp <- collapse(colony))
hasCollapsed(tmp)
resetEvents(tmp)
resetEvents(tmp, collapse = TRUE)

# Same behaviour for MultiColony (example for the split)
tmp <- split(apiary)
(splits <- tmp$split)
hasSplit(splits[[1]])
resetEvents(splits)[[1]]
(remnants <- tmp$remnant)
hasSplit(remnants[[1]])
resetEvents(remnants)[[1]]
```

selectColonies *Select colonies from MultiColony object*

Description

Level 3 function that selects colonies from MultiColony object based on colony ID or random selection. Whilst user can provide all three arguments ID, p and n, there is a priority list: ID takes first priority. If no ID is provided, p takes precedence over n.

Usage

```
selectColonies(
  multicolony,
  ID = NULL,
  n = NULL,
  p = NULL,
  by = NULL,
  selectTop = TRUE,
  simParamBee = NULL
)
```

Arguments

multicolony	MultiColony-class
ID	character or numeric, ID of a colony (one or more) to be selected
n	numeric, number of colonies to select
p	numeric, percentage of colonies selected (takes precedence over n)
by	matrix, matrix of values to select by with names being colony IDs (can be obtained with calcColonyValue. If NULL, the colonies are selected at random. This parameter is used in combination with n or p to determine the number of selected colonies, and selectTop to determine whether to select the best or the worst colonies.
selectTop	logical, selects highest (lowest) values if TRUE (FALSE)
simParamBee	SimParamBee, global simulation parameters

Value

MultiColony-class with selected colonies

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

mean <- c(10, 10 / SP$nWorkers)
varA <- c(1, 1 / SP$nWorkers)
```

```
corA <- matrix(data = c(
  1.0, -0.5,
  -0.5, 1.0
), nrow = 2, byrow = TRUE)
varE <- c(3, 3 / SP$nWorkers)
varA / (varA + varE)
SP$addTraitADE(nQtlPerChr = 100,
               mean = mean,
               var = varA, corA = corA,
               meanDD = 0.1, varDD = 0.2, corD = corA,
               relAA = 0.1, corAA = corA)
SP$setVarE(varE = varE)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1:4], nInd = 100)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)
apiary <- createMultiColony(basePop[2:5], n = 4)
apiary <- cross(apiary, drones = droneGroups[1:4])
apiary <- buildUp(apiary)
getId(apiary)

getId(selectColonies(apiary, ID = 1))
getId(selectColonies(apiary, ID = c("3", "4")))
# ... alternative
getId(apiary[1])
getId(apiary[["4"]])

# Select a random number of colonies
selectColonies(apiary, n = 3)
# Select a percentage of colonies
selectColonies(apiary, p = 0.2)

# Since selection is random, you would get a different set of colonies with
# each function call
getId(selectColonies(apiary, p = 0.5))
getId(selectColonies(apiary, p = 0.5))

# How to select colonies based on colony values?
# Obtain colony phenotype
colonyPheno <- calcColonyPheno(apiary)
# Select the best colony
selectColonies(apiary, n = 1, by = colonyPheno)

# Select the worst 2 colonies
selectColonies(apiary, n = 2, by = colonyPheno, selectTop = FALSE)

# Select best colony based on queen's genetic value for trait 1
queenGv <- calcColonyGv(apiary, FUN = mapCasteToColonyGv, workersTrait = NULL)
selectColonies(apiary, n = 1, by = queenGv)
```

`setLocation` *Set colony location*

Description

Level 2 function that to set a Colony or MultiColony object location to (x, y) coordinates.

Usage

```
setLocation(x, location = c(0, 0))
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`location`	numeric, list, or data.frame, x and y coordinates of colony locations as `c(x1, y1)` (the same location set to all colonies), `list(c(x1, y1), c(x2, y2))`, or `data.frame(x = c(x1, x2), y = c(y1, y2))`

Value

`Colony-class` or `MultiColony-class` with set location

Examples

```
founderGenomes <- quickHaplo(nInd = 5, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 4, nDrones = 10)

# Create Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:5])
apiary <- cross(apiary, drones = droneGroups[2:4])

getLocation(colony)
getLocation(apiary)

loc <- c(1, 1)
colony <- setLocation(colony, location = loc)
getLocation(colony)

# Assuming one location (as in bringing colonies to one place!)
apiary <- setLocation(apiary, location = loc)
getLocation(apiary)

# Assuming different locations
```

```
locList <- list(c(0, 0), c(1, 1), c(2, 2))
apiary <- setLocation(apiary, location = locList)
getLocation(apiary)

locDF <- data.frame(x = c(0, 1, 2), y = c(0, 1, 2))
apiary <- setLocation(apiary, location = locDF)
getLocation(apiary)
```

---

setMisc *Set miscellaneous information in a population*

Description

Set miscellaneous information in a population

Usage

```
setMisc(x, node = NULL, value = NULL)
```

Arguments

x	Pop-class
node	character, name of the node to set within the x@misc slot
value	value to be saved into x@misc[[*]][[node]]; length of value should be equal to nInd(x); if its length is 1, then it is repeated using rep (see examples)

Details

A NULL in value is ignored

Value

Pop-class

---

setQueensYearOfBirth *Set the queen's year of birth*

Description

Level 1 function that sets the queen's year of birth.

Usage

```
setQueensYearOfBirth(x, year, simParamBee = NULL)
```

Arguments

x	Pop-class (one or more than one queen), Colony-class (one colony), or MultiColony-class (more colonies)
year	integer, the year of the birth of the queen
simParamBee	SimParamBee, global simulation parameters

Value

Pop-class, Colony-class, or MultiColony-class with queens having the year of birth set

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = nFathersPoisson)

# Create a Colony and a MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(x = colony, drones = droneGroups[[1]])
apiary <- createMultiColony(basePop[3:4], n = 2)
apiary <- cross(apiary, drones = droneGroups[c(2, 3)])

# Example on Colony class
getQueenYearOfBirth(colony)
getQueenYearOfBirth(apiary)

queen1 <- getQueen(colony)
queen1 <- setQueensYearOfBirth(queen1, year = 2022)
getQueenYearOfBirth(queen1)

colony <- setQueensYearOfBirth(colony, year = 2022)
getQueenYearOfBirth(colony)

apiary <- setQueensYearOfBirth(apiary, year = 2022)
getQueenYearOfBirth(apiary)
```

SimParamBee *Honeybee simulation parameters*

Description

Container for global honeybee simulation parameters. Saving this object as SP will allow it to be accessed by SIMplyBee functions without repeatedly (and annoyingly!) typing out someFun(argument, simParamBee = SP). SimParamBee inherits from AlphaSimR SimParam, so all SimParam slots and functions are available in addition to SimParamBee-specific slots and functions. Some SimParam functions could have upgraded behaviour as documented in line with honeybee biology.

Details

This documentation shows details specific to SimParamBee. We suggest you also read all the options provided by the AlphaSimR SimParam. Below we show minimal usage cases for each SimParamBee function.

See also vignette(package = "SIMplyBee") for descriptions of how SIMplyBee implements the specific honeybee biology.

Super class

AlphaSimR::SimParam -> SimParamBee

Public fields

nWorkers numeric or function, a number of workers generated in a colony - used in createWorkers, addWorkers, buildUp.

The default value is 100, that is, queen generates 100 workers - this is for a down-scaled simulation (for efficiency) assuming that this represents ~60,000 workers in a full/strong colony (Seeley, 2019). This value is set in SimParamBee$new() to have a number to work with.

You can change this setting to your needs!

When nWorkers is a function, it should work with internals of other functions. Therefore, the function MUST be defined like function(colony, arg = default) someCode , that is, the first argument MUST be colony and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See nWorkersPoisson, nWorkersTruncPoisson, or nWorkersColonyPhenotype for examples.

You can provide your own functions that satisfy your needs!

nDrones numeric or function, a number of drones generated in a colony - used in createDrones, addDrones, buildUp.

The default value is 100, that is, queen generates 100 drones - this is for a down-scaled simulation (for efficiency) assuming that this represents ~1,000 drones in a full/strong colony (Seeley, 2019). This value is set in SimParamBee$new() to have a number to work with.

You can change this setting to your needs!

When nDrones is a function, it should work with internals of other functions. Therefore, the function MUST be defined like function(x, arg = default) someCode , that is, the first argument MUST be x and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See nDronesPoisson, nDronesTruncPoisson, or nDronesColonyPhenotype for examples.

You can provide your own functions that satisfy your needs!

nVirginQueens numeric or function, a number of virgin queens generated when a queen dies or other situations - used in createVirginQueens and addVirginQueens.

The default value is 10, that is, when the queen dies, workers generate 10 new virgin queens (Seeley, 2019). This value is set in SimParamBee$new() to have a number to work with.

You can change this setting to your needs!

When nVirginQueens is a function, it should work with internals of other functions. Therefore, the function MUST be defined like function(colony, arg = default) someCode , that is, the first argument MUST be colony and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See

nVirginQueensPoisson, nVirginQueensTruncPoisson, or nVirginQueensColonyPhenotype for examples.

You can provide your own functions that satisfy your needs!

nFathers numeric or function, a number of drones a queen mates with - used in pullDroneGroupsFromDCA, cross.

The default value is 15, that is, a virgin queen mates on average with 15 drones (Seeley, 2019). This value is set in SimParamBee$new() to have a number to work with.

You can change this setting to your needs!

When nFathers is a function, it should work with internals of other functions. Therefore, the function MUST be defined like function(arg = default) someCode , that is, any arguments MUST have a default value. We did not use the colony argument here, because nFathers likely does not depend on the colony. Let us know if we are wrong! For flexibility you can add ... argument to pass on any other argument. See nFathersPoisson or nFathersTruncPoisson for examples.

You can provide your own functions that satisfy your needs!

swarmP numeric or a function, the swarm proportion - the proportion of workers that leave with the old queen when the colony swarms - used in swarm.

The default value is 0.50, that is, about a half of workers leave colony in a swarm (Seeley, 2019). This value is set in SimParamBee$new() to have a proportion to work with.

You can change this setting to your needs!

When swarmP is a function, it should work with internals of other functions. Therefore, the function MUST be defined like function(colony, arg = default) someCode , that is, the first argument MUST be colony and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See swarmPUnif for examples.

You can provide your own functions that satisfy your needs!

swarmRadius numeric, radius within which to sample a location of of the swarm - used in swarm - see its radius argument.

The default value is 0, that is, swarm gets the same location as the original colony.

You can change this setting to your needs!

splitP numeric or a function, the split proportion - the proportion of workers removed in a managed split - used in split.

The default value is 0.30, that is, about a third of workers is put into a split colony from a strong colony (Seeley, 2019). This value is set in SimParamBee$new() to have a proportion to work with.

You can change this setting to your needs!

When splitP is a function, it should work with internals of other functions. Therefore, the function MUST be defined like function(colony, arg = default) someCode , that is, the first argument MUST be colony and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See splitPUnif or splitPColonyStrength for examples.

You can provide your own functions that satisfy your needs!

downsizeP numeric or a function, the downsize proportion - the proportion of workers removed from the colony when downsizing, usually in autumn - used in downsize.

The default value is 0.85, that is, a majority of workers die before autumn or all die but some winter workers are created (Seeley, 2019). This value is set in `SimParamBee$new()` to have a proportion to work with.

You can change this setting to your needs!

When `downsizeP` is a function, it should work with internals of other functions. Therefore, the function MUST be defined like `function(colony, arg = default) someCode` , that is, the first argument MUST be `colony` and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See `downsizePUnif` for example.

You can provide your own functions that satisfy your needs!

`colonyValueFUN` function, to calculate colony values - used in `calcColonyValue` - see also `calcColonyPheno` and `calcColonyGv`.

This function should work with internals of others functions - therefore the function MUST be defined like `function(colony, arg = default) someCode` , that is, the first argument MUST be `colony` and any following arguments MUST have a default value. For flexibility you can add ... argument to pass on any other argument. See `mapCasteToColonyValue` for an example.

You can provide your own functions that satisfy your needs!

Active bindings

`caste` character, caste information for every individual ever created

`lastColonyId` integer, ID of the last Colony object created with `createColony`

`csdChr` integer, chromosome of the csd locus

`csdPos` numeric, starting position of the csd locus on the `csdChr` chromosome (relative at the moment, but could be in base pairs in the future)

`nCsdAlleles` integer, number of possible csd alleles

`nCsdSites` integer, number of segregating sites representing the csd locus

`csdPosStart` integer, starting position of the csd locus

`csdPosStop` integer, ending position of the csd locus

`version` list, versions of AlphaSimR and SIMplyBee packages used to generate this object

Methods

Public methods:

- `SimParamBee$new()`
- `SimParamBee$addToCaste()`
- `SimParamBee$changeCaste()`
- `SimParamBee$updateLastColonyId()`
- `SimParamBee$clone()`

Method `new()`**:** Starts the process of building a new simulation by creating a new SimParamBee object and assigning a founder population of genomes to the this object.

Usage:

```
SimParamBee$new(
  founderPop,
  nWorkers = 100,
  nDrones = 100,
  nVirginQueens = 10,
  nFathers = 15,
  swarmP = 0.5,
  swarmRadius = 0,
  splitP = 0.3,
  downsizeP = 0.85,
  csdChr = 3,
  csdPos = 0.865,
  nCsdAlleles = 128,
  colonyValueFUN = NULL
)
```

Arguments:

`founderPop` MapPop-class, founder population of genomes

`nWorkers` see SimParamBee field `nWorkers`

`nDrones` see SimParamBee field `nDrones`

`nVirginQueens` see SimParamBee field `nVirginQueens`

`nFathers` see SimParamBee field `nFathers`

`swarmP` see SimParamBee field `swarmP`

`swarmRadius` see SimParamBee field `swarmRadius`

`splitP` see SimParamBee field `splitP`

`downsizeP` see SimParamBee field `downsizeP`

`csdChr` integer, chromosome that will carry the csd locus, by default 3, but if there are less chromosomes (for a simplified simulation), the locus is put on the last available chromosome (1 or 2); if `NULL` then csd locus is ignored in the simulation

`csdPos` numeric, starting position of the csd locus on the `csdChr` chromosome (relative at the moment, but could be in base pairs in future)

`nCsdAlleles` integer, number of possible csd alleles (this determines how many segregating sites will be needed to represent the csd locus from the underlying bi-allelic SNP; the minimum number of bi-allelic SNP needed is `log2(nCsdAlleles)`); if set to `0` then `csdChr=NULL` is triggered. By default we set `nCsdAlleles` to 128, which is at the upper end of the reported number of csd alleles (Lechner et al., 2014; Zareba et al., 2017; Bovo et al., 2021).

`colonyValueFUN` see SimParamBee field `colonyValueFUN`

Examples:

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 3, segSites = 10)
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 2)
\dontshow{SP$nThreads = 1L}

# We need enough segregating sites
try(SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 100))
\dontshow{SP$nThreads = 1L}
founderGenomes <- quickHaplo(nInd = 10, nChr = 3, segSites = 100)
```

```
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 100)
\dontshow{SP$nThreads = 1L}

# We can save the csd locus on chromosome 1 or 2, too, for quick simulations
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 100)
\dontshow{SP$nThreads = 1L}
```

Method `addToCaste()`**:** Store caste information (for internal use only!)

Usage:

```
SimParamBee$addToCaste(id, caste)
```

Arguments:

`id` character, individuals whose caste will be stored

`caste` character, single "Q" for queens, "W" for workers, "D" for drones, "V" for virgin queens, and "F" for fathers

Examples:

```
founderGenomes <- quickHaplo(nInd = 2, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)
\dontshow{SP$nThreads = 1L}
SP$setTrackPed(isTrackPed = TRUE)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 10)
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = drones)
colony <- addWorkers(colony, nInd = 5)
colony <- addDrones(colony, nInd = 5)
colony <- addVirginQueens(colony, nInd = 2)

SP$pedigree
SP$caste
```

Method `changeCaste()`**:** Change caste information (for internal use only!)

Usage:

```
SimParamBee$changeCaste(id, caste)
```

Arguments:

`id` character, individuals whose caste will be changed

`caste` character, single "Q" for queens, "W" for workers, "D" for drones, "V" for virgin queens, and "F" for fathers

Examples:

```
founderGenomes <- quickHaplo(nInd = 2, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)
\dontshow{SP$nThreads = 1L}
SP$setTrackPed(isTrackPed = TRUE)
basePop <- createVirginQueens(founderGenomes)
```

```
SP$pedigree
SP$caste

drones <- createDrones(x = basePop[1], nInd = 10)
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = drones)
SP$pedigree
SP$caste
```

Method `updateLastColonyId()`**:** A function to update the colony last ID everytime we create a Colony-class with createColony. For internal use only.

Usage:

```
SimParamBee$updateLastColonyId()
```

Arguments:

`lastColonyId` integer, last colony ID assigned

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
SimParamBee$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Bovo et al. (2021) Application of Next Generation Semiconductor-Based Sequencing for the Identification of Apis mellifera Complementary Sex Determiner (csd) Alleles from Honey DNA. Insects, 12(10), 868. doi:10.3390/insects12100868

Lechner et al. (2014) Nucleotide variability at its limit? Insights into the number and evolutionary dynamics of the sex-determining specificities of the honey bee Apis mellifera Molecular Biology and Evolution, 31, 272-287. doi:10.1093/molbev/mst207

Seeley (2019) The Lives of Bees: The Untold Story of the Honey Bee in the Wild. Princeton: Princeton University Press. doi:10.1515/9780691189383

Zareba et al. (2017) Uneven distribution of complementary sex determiner (csd) alleles in Apis mellifera population. Scientific Reports, 7, 2317. doi:10.1038/s41598017026299

Examples

```
## ------------------------------------------------
## Method `SimParamBee$new`
## ------------------------------------------------

founderGenomes <- quickHaplo(nInd = 10, nChr = 3, segSites = 10)
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 2)


# We need enough segregating sites
try(SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 100))
```

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 3, segSites = 100)
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 100)


# We can save the csd locus on chromosome 1 or 2, too, for quick simulations
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes, nCsdAlleles = 100)


## ------------------------------------------------
## Method `SimParamBee$addToCaste`
## ------------------------------------------------

founderGenomes <- quickHaplo(nInd = 2, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

SP$setTrackPed(isTrackPed = TRUE)
basePop <- createVirginQueens(founderGenomes)

drones <- createDrones(x = basePop[1], nInd = 10)
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = drones)
colony <- addWorkers(colony, nInd = 5)
colony <- addDrones(colony, nInd = 5)
colony <- addVirginQueens(colony, nInd = 2)

SP$pedigree
SP$caste

## ------------------------------------------------
## Method `SimParamBee$changeCaste`
## ------------------------------------------------

founderGenomes <- quickHaplo(nInd = 2, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

SP$setTrackPed(isTrackPed = TRUE)
basePop <- createVirginQueens(founderGenomes)
SP$pedigree
SP$caste

drones <- createDrones(x = basePop[1], nInd = 10)
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = drones)
SP$pedigree
SP$caste
```

`simulateHoneyBeeGenomes`

Simulate the Honey bee genome

Description

Level 0 function that returns simulated honeybee genomes

Usage

```
simulateHoneyBeeGenomes(
  nMelN = 0L,
  nMelS = 0L,
  nCar = 0L,
  nLig = 0L,
  Ne = 170000L,
  ploidy = 2L,
  nChr = 16L,
  nSegSites = 100L,
  nBp = 225200000/16,
  genLen = 3.199121,
  mutRate = 3.4e-09,
  recRate = 2.3e-07,
  nThreads = NULL
)
```

Arguments

nMelN	integer, number of Apis mellifera mellifera North individuals to simulate
nMelS	integer, number of Apis mellifera mellifera South individuals to simulate
nCar	integer, number of Apis mellifera carnica individuals to simulate
nLig	integer, number of Apis mellifera ligustica individuals to simulate
Ne	integer, effective size of the simulated population. Currently set to 170,000, according to Wallberg et al., 2014. Would discourage you to change it since it is linked to the parameters of the demographic model we use for the simulation. However, there might be some edge cases when using a different Ne is necessary, but proceed with caution.
ploidy	integer, the ploidy of the individuals
nChr	integer, number of chromosomes to simulate
nSegSites	integer, number of segregating sites to keep per chromosome
nBp	integer, base pair length of chromosome
genLen	numeric, genetic length of chromosome in Morgans
mutRate	numeric, per base pair mutation rate
recRate	numeric, per base pair recombination rate
nThreads	integer, if OpenMP is available, this will allow for simulating chromosomes in parallel. If NULL, the number of threads is automatically detected

Value

MapPop-class

References

Wallberg, A., Bunikis, I., Pettersson, O.V. et al. A hybrid de novo genome assembly of the honeybee, Apis mellifera, with chromosome-length scaffolds. 2019, BMC Genomics 20:275. doi:10.1186/s1286401956420

Beye M, Gattermeier I, Hasselmann M, et al. Exceptionally high levels of recombination across the honey bee genome. 2006, Genome Res 16(11):1339-1344. doi:10.1101/gr.5680406

Wallberg, A., Han, F., Wellhagen, G. et al. A worldwide survey of genome sequence variation provides insight into the evolutionary history of the honeybee Apis mellifera. 2014, Nat Genet 46:1081–1088. doi:10.1038/ng.3077

Yang S, Wang L, Huang J, Zhang X, Yuan Y, Chen JQ, Hurst LD, Tian D. Parent-progeny sequencing indicates higher mutation rates in heterozygotes. 2015, Nature 523(7561):463-7. doi:10.1038/nature14649.

See Also

Due to the computational time and resources required to run this function, we do not include an example here, but we demonstrate its use in the Honeybee biology vignette.

`split` *Split colony in two MultiColony*

Description

Level 2 function that splits a Colony or MultiColony object into two new colonies to prevent swarming (in managed situation). The remnant colony retains the queen and a proportion of the workers and all drones. The split colony gets the other part of the workers, which raise virgin queens, of which only one prevails. Location of the split is the same as for the remnant.

Usage

```
split(x, p = NULL, year = NULL, simParamBee = NULL, ...)
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`p`	numeric, proportion of workers that will go to the split colony; if `NULL` then `SimParamBee$splitP` is used. If input is `MultiColony-class`, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies
`year`	numeric, year of birth for virgin queens
`simParamBee`	`SimParamBee`, global simulation parameters
`...`	additional arguments passed to `p` when this argument is a function

Value

list with two Colony-class or MultiColony-class, the split and the remnant (see the description what each colony holds!); both outputs have the split even slot set do TRUE

Examples

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)

# Create Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
(colony <- buildUp(colony, nWorkers = 100))
apiary <- createMultiColony(basePop[3:8], n = 6)
apiary <- cross(apiary, drones = droneGroups[2:7])
apiary <- buildUp(apiary, nWorkers = 100)

# Split a colony
tmp <- split(colony)
tmp$split
tmp$remnant

# Split all colonies in the apiary with p = 0.5 (50% of workers in each split)
tmp <- split(apiary, p = 0.5)
tmp$split[[1]]
tmp$remnant[[1]]
# Split with different proportions
nWorkers(apiary)
tmp <- split(apiary, p = c(0.1, 0.2, 0.3, 0.4, 0.5, 0.6))
nWorkers(tmp$split)
nWorkers(tmp$remnant)

# Split only specific colonies in the apiary
tmp <- pullColonies(apiary, ID = c(4, 5))
# Split only the pulled colonies
(split(tmp$pulled, p = 0.5))
```

---

splitPUnif *Sample the split proportion - proportion of removed workers in a managed split*

Description

Sample the split proportion - proportion of removed workers in a managed split - used when p = NULL - (see SimParamBee$splitP).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
splitPUnif(colony, n = 1, min = 0.2, max = 0.4)

splitPColonyStrength(colony, n = 1, nWorkersFull = 100, scale = 1)
```

Arguments

colony	Colony-class
n	integer, number of samples
min	numeric, lower limit for splitPUnif
max	numeric, upper limit for splitPUnif
nWorkersFull	numeric, average number of workers in a full/strong colony for splitPColonyStrength (actual number can go beyond this value)
scale	numeric, scaling of numbers in splitPColonyStrength to avoid to narrow range when colonies have a large number of bees (in that case change nWorkersFull too!)

Details

splitPUnif samples from a uniform distribution between values 0.2 and 0.4 irrespective of colony strength.

splitPColonyStrength samples from a beta distribution with mean a / (a + b), where a = nWorkers + nWorkersFull and b = nWorkers. This beta sampling mimics larger splits for strong colonies and smaller splits for weak colonies - see examples. This is just an example - adapt to your needs!

The nWorkersFull default value used in this function is geared towards a situation where we simulate ~100 workers per colony (down-scaled simulation for efficiency). If you simulate more workers, you should change the default accordingly.

Value

numeric, split proportion

Functions

- splitPColonyStrength(): Sample the split proportion - the proportion of removed workers in a managed split based on the colony strength

See Also

SimParamBee field splitP

Examples

```
splitPUnif()
splitPUnif()
p <- splitPUnif(n = 1000)
hist(p, breaks = seq(from = 0, to = 1, by = 0.01), xlim = c(0, 1))
```

```
# Example for splitPColonyStrength()
founderGenomes <- quickHaplo(nInd = 2, nChr = 1, segSites = 100)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(x = basePop[1], nInd = 15)
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = drones)
colony <- addWorkers(colony, nInd = 10)
nWorkers(colony) # weak colony
splitPColonyStrength(colony)
splitPColonyStrength(colony)
colony <- addWorkers(colony, nInd = 100)
nWorkers(colony) # strong colony
splitPColonyStrength(colony)
splitPColonyStrength(colony)

# Logic behind splitPColonyStrength()
nWorkersFull <- 100
nWorkers <- 0:200
splitP <- 1 - rbeta(
  n = length(nWorkers),
  shape1 = nWorkers + nWorkersFull,
  shape2 = nWorkers
)
plot(splitP ~ nWorkers, ylim = c(0, 1))
abline(v = nWorkersFull)
pKeep <- 1 - splitP
plot(pKeep ~ nWorkers, ylim = c(0, 1))
abline(v = nWorkersFull)
```

`supersede` *Supersede*

Description

Level 2 function that supersedes a Colony or MultiColony object - an event where the queen dies. The workers and drones stay unchanged, but workers raise virgin queens, of which only one prevails.

Usage

```
supersede(x, year = NULL, nVirginQueens = NULL, simParamBee = NULL, ...)
```

Arguments

`x`	`Colony-class` or `MultiColony-class`
`year`	numeric, year of birth for virgin queens

nVirginQueens	integer, the number of virgin queens to be created in the colony; of these one is randomly selected as the new virgin queen of the remnant colony. If NULL, the value from simParamBee$nVirginQueens is used
simParamBee	SimParamBee, global simulation parameters
...	additional arguments passed to nVirginQueens when this argument is a function

Value

Colony-class or MultiColony-class with the supersede event set to TRUE

Examples

```
founderGenomes <- quickHaplo(nInd = 10, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)

# Create Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
(colony <- buildUp(colony, nWorkers = 100))
apiary <- createMultiColony(basePop[3:8], n = 6)
apiary <- cross(apiary, drones = droneGroups[2:7])
apiary <- buildUp(apiary, nWorkers = 100)

# Supersede a colony
isQueenPresent(colony)
isVirginQueenPresent(colony)
colony <- supersede(colony)
isQueenPresent(colony)
isVirginQueenPresent(colony)

# Supersede all colonies in the apiary
isQueenPresent(colony)
isVirginQueenPresent(colony)
apiary1 <- supersede(apiary)
isQueenPresent(colony)
isVirginQueenPresent(colony)

# Sample colonies from the apiary that will supersede (sample with probability of 0.2)
tmp <- pullColonies(apiary, p = 0.2)
# Swarm only the pulled colonies
(supersede(tmp$pulled))
```

swarm *Swarm*

Description

Level 2 function that swarms a Colony or MultiColony object - an event where the queen leaves with a proportion of workers to create a new colony (the swarm). The remnant colony retains the other proportion of workers and all drones, and the workers raise virgin queens, of which only one prevails. Location of the swarm is the same as for the remnant or sampled as deviation from the remnant.

Usage

```
swarm(
  x,
  p = NULL,
  year = NULL,
  nVirginQueens = NULL,
  sampleLocation = TRUE,
  radius = NULL,
  simParamBee = NULL,
  ...
)
```

Arguments

x	Colony-class or MultiColony-class
p	numeric, proportion of workers that will leave with the swarm colony; if NULL then SimParamBee$swarmP is used. If input is MultiColony-class, the input could also be a vector of the same length as the number of colonies. If a single value is provided, the same value will be applied to all the colonies
year	numeric, year of birth for virgin queens
nVirginQueens	integer, the number of virgin queens to be created in the colony; of these one is randomly selected as the new virgin queen of the remnant colony. If NULL, the value from simParamBee$nVirginQueens is used
sampleLocation	logical, sample location of the swarm by taking the current colony location and adding deviates to each coordinate using rcircle
radius	numeric, radius of a circle within which swarm will go; if NULL then SimParamBee$swarmRadius is used (which uses 0, so by default swarm does not fly far away)
simParamBee	SimParamBee, global simulation parameters
...	additional arguments passed to p or nVirginQueens when these arguments are functions

Value

list with two Colony-class or MultiColony-class, the swarm and the remnant (see the description what each colony holds!); both outputs have the swarm event set to TRUE

Examples

```
founderGenomes <- quickHaplo(nInd = 8, nChr = 1, segSites = 50)
SP <- SimParamBee$new(founderGenomes)

basePop <- createVirginQueens(founderGenomes)
drones <- createDrones(basePop[1], n = 1000)
droneGroups <- pullDroneGroupsFromDCA(drones, n = 10, nDrones = 10)

# Create Colony and MultiColony class
colony <- createColony(x = basePop[2])
colony <- cross(colony, drones = droneGroups[[1]])
(colony <- buildUp(colony, nWorkers = 100))
apiary <- createMultiColony(basePop[3:8], n = 6)
apiary <- cross(apiary, drones = droneGroups[2:7])
apiary <- buildUp(apiary, nWorkers = 100)

# Swarm a colony
tmp <- swarm(colony)
tmp$swarm
tmp$remnant

# Swarm all colonies in the apiary with p = 0.6 (60% of workers leave)
tmp <- swarm(apiary, p = 0.6)
nWorkers(tmp$swarm)
nWorkers(tmp$remnant)
# Swarm with different proportions
nWorkers(apiary)
tmp <- swarm(apiary, p = c(0.4, 0.6, 0.5, 0.5, 0.34, 0.56))
nWorkers(tmp$swarm)
nWorkers(tmp$remnant)

# Sample colonies from the apiary that will swarm (sample with probability of 0.2)
tmp <- pullColonies(apiary, p = 0.2)
# Swarm only the pulled colonies
(swarm(tmp$pulled, p = 0.6))
```

---

swarmPUnif *Sample the swarm proportion - the proportion of workers that swarm*

Description

Sample the swarm proportion - the proportion of workers that swarm - used when p = NULL (see SimParamBee$swarmP).

This is just an example. You can provide your own functions that satisfy your needs!

Usage

```
swarmPUnif(colony, n = 1, min = 0.4, max = 0.6)
```

Arguments

colony	Colony-class
n	integer, number of samples
min	numeric, lower limit for swarmPUnif
max	numeric, upper limit for swarmPUnif

Details

swarmPUnif samples from a uniform distribution between values 0.4 and 0.6 irrespective of colony strength.

The nWorkersFull default value used in this function is geared towards a situation where we simulate ~100 workers per colony (down-scaled simulation for efficiency). If you simulate more workers, you should change the default accordingly.

Value

numeric, swarm proportion

See Also

SimParamBee field swarmP

Examples

```
swarmPUnif()
swarmPUnif()
p <- swarmPUnif(n = 1000)
hist(p, breaks = seq(from = 0, to = 1, by = 0.01), xlim = c(0, 1))
```

Index

[,MultiColony,character-method
(MultiColony-class), 115
[,MultiColony,integerOrNumericOrLogical-method
(MultiColony-class), 115
[<-,MultiColony,integerOrNumericOrLogicalOrCharacter,ANY,MultiColony-method
(MultiColony-class), 115
[[,MultiColony,character-method
(MultiColony-class), 115
[[,MultiColony,integerOrNumericOrLogical-method
(MultiColony-class), 115
[[<-,MultiColony,integerOrNumericOrLogicalOrCharacter,ANY,MultiColony-method
(MultiColony-class), 115

addCastePop, 4
addDrones, *153*
addDrones (addCastePop), 4
addVirginQueens, *153*
addVirginQueens (addCastePop), 4
addWorkers, *153*
addWorkers (addCastePop), 4
AlphaSimR::SimParam, *153*
areDronesPresent (isWorkersPresent), 110
areFathersPresent (isFathersPresent), 104
areVirginQueensPresent
(isVirginQueensPresent), 109
areWorkersPresent (isWorkersPresent), 110

buildUp, 6, *153*
bv, *47*

c,ColonyOrNULL-method (Colony-class), 23
c,MultiColony-method
(MultiColony-class), 115
c,MultiColonyOrNULL-method
(MultiColony-class), 115
c,NULLOrPop-method, 9
calcBeeAlleleFreq, *12*
calcBeeAlleleFreq (calcBeeGRMIbs), 11
calcBeeGRMIbd, 9
calcBeeGRMIbs, 11
calcColonyAa (calcColonyValue), 13
calcColonyBv (calcColonyValue), 13
calcColonyD (calcColonyValue), 13
calcColonyGv, *113*, *155*
calcColonyGv (calcColonyValue), 13
calcColonyPheno, *113*, *155*
calcColonyPheno (calcColonyValue), 13
calcColonyValue, 13, *111*, *113*, *133*, *141*, *148*, *155*
calcInheritanceCriterion, 15, *18*, *21*
calcPerformanceCriterion, *16*, 17, *21*
calcQueensPHomBrood, 19
calcSelectionCriterion, *16*, *18*, 20
collapse, 22
Colony-class, 23
combine, 25
combineBeeGametes, 26
combineBeeGametesHaploDiploid, 27
createCastePop, 28
createColony, *24*, 31, *155*
createCrossPlan, 32, *39, 40*
createDCA, 34
createDrones, *153*
createDrones (createCastePop), 28
createMatingStationDCA, 36, *40*
createMultiColony, 37, *117*
createVirginQueens, *153*
createVirginQueens (createCastePop), 28
createWorkers, *153*
createWorkers (createCastePop), 28
cross, *26, 27*, *35*, 38, *154*

dd, *46*, *61*
downsize, 42, *154*
downsizePUnif, 43, *155*

editCsdLocus, 44

getAa, 45
getBv, 46
getCaste, 47, *49*, *52–54*, *130*
getCasteId, *47*, 49, *52*
getCastePop, *47*, *49*, 50, *53, 54*
getCasteSex, 53
getCsdAlleles, 55, *59*
getCsdGeno, 58, *105*
getDd, 60
getDrones, *52*
getDrones *(getCastePop)*, 50
getDronesAa *(getAa)*, 45
getDronesBv *(getBv)*, 46
getDronesCsdAlleles *(getCsdAlleles)*, 55
getDronesCsdGeno *(getCsdGeno)*, 58
getDronesDd *(getDd)*, 60
getDronesGv *(getGv)*, 62
getDronesIbdHaplo *(getIbdHaplo)*, 64
getDronesPheno *(getPheno)*, 71
getDronesQtlGeno *(getQtlGeno)*, 74
getDronesQtlHaplo *(getQtlHaplo)*, 77
getDronesSegSiteGeno *(getSegSiteGeno)*, 83
getDronesSegSiteHaplo *(getSegSiteHaplo)*, 85
getDronesSnpGeno *(getSnpGeno)*, 88
getDronesSnpHaplo *(getSnpHaplo)*, 91
getEvents, 61, *113*
getFathers, *52*
getFathers *(getCastePop)*, 50
getFathersAa *(getAa)*, 45
getFathersBv *(getBv)*, 46
getFathersCsdAlleles *(getCsdAlleles)*, 55
getFathersCsdGeno *(getCsdGeno)*, 58
getFathersDd *(getDd)*, 60
getFathersGv *(getGv)*, 62
getFathersIbdHaplo *(getIbdHaplo)*, 64
getFathersPheno *(getPheno)*, 71
getFathersQtlGeno *(getQtlGeno)*, 74
getFathersQtlHaplo *(getQtlHaplo)*, 77
getFathersSegSiteGeno *(getSegSiteGeno)*, 83
getFathersSegSiteHaplo *(getSegSiteHaplo)*, 85
getFathersSnpGeno *(getSnpGeno)*, 88
getFathersSnpHaplo *(getSnpHaplo)*, 91
getGv, 62
getIbdHaplo, 64, *66*
getId, 68
getLocation, 69
getMisc, 70
getPheno, 71
getPooledGeno, 73
getQtlGeno, 74, *76*
getQtlHaplo, 77, *79*
getQueen, *52*
getQueen *(getCastePop)*, 50
getQueenAa *(getAa)*, 45
getQueenAge, 80
getQueenBv *(getBv)*, 46
getQueenCsdAlleles *(getCsdAlleles)*, 55
getQueenCsdGeno *(getCsdGeno)*, 58
getQueenDd *(getDd)*, 60
getQueenGv *(getGv)*, 62
getQueenIbdHaplo *(getIbdHaplo)*, 64
getQueenPheno *(getPheno)*, 71
getQueenQtlGeno *(getQtlGeno)*, 74
getQueenQtlHaplo *(getQtlHaplo)*, 77
getQueenSegSiteGeno *(getSegSiteGeno)*, 83
getQueenSegSiteHaplo *(getSegSiteHaplo)*, 85
getQueenSnpGeno *(getSnpGeno)*, 88
getQueenSnpHaplo *(getSnpHaplo)*, 91
getQueenYearOfBirth, 82
getSegSiteGeno, 83, *84*
getSegSiteHaplo, 85, *87*
getSnpGeno, 88, *90*
getSnpHaplo, 91, *94*
getVirginQueens, *52*
getVirginQueens *(getCastePop)*, 50
getVirginQueensAa *(getAa)*, 45
getVirginQueensBv *(getBv)*, 46
getVirginQueensCsdAlleles *(getCsdAlleles)*, 55
getVirginQueensCsdGeno *(getCsdGeno)*, 58
getVirginQueensDd *(getDd)*, 60
getVirginQueensGv *(getGv)*, 62
getVirginQueensIbdHaplo *(getIbdHaplo)*, 64
getVirginQueensPheno *(getPheno)*, 71
getVirginQueensQtlGeno *(getQtlGeno)*, 74
getVirginQueensQtlHaplo *(getQtlHaplo)*, 77
getVirginQueensSegSiteGeno *(getSegSiteGeno)*, 83
getVirginQueensSegSiteHaplo

(getSegSiteHaplo), 85
getVirginQueensSnpGeno (getSnpGeno), 88
getVirginQueensSnpHaplo (getSnpHaplo), 91
getWorkers, *52*
getWorkers (getCastePop), 50
getWorkersAa (getAa), 45
getWorkersBv (getBv), 46
getWorkersCsdAlleles (getCsdAlleles), 55
getWorkersCsdGeno (getCsdGeno), 58
getWorkersDd (getDd), 60
getWorkersGv (getGv), 62
getWorkersIbdHaplo (getIbdHaplo), 64
getWorkersPheno (getPheno), 71
getWorkersQtlGeno (getQtlGeno), 74
getWorkersQtlHaplo (getQtlHaplo), 77
getWorkersSegSiteGeno (getSegSiteGeno), 83
getWorkersSegSiteHaplo (getSegSiteHaplo), 85
getWorkersSnpGeno (getSnpGeno), 88
getWorkersSnpHaplo (getSnpHaplo), 91
gv, *63*, *113*

hasCollapsed, 95
hasSplit, 96
hasSuperseded, 97
hasSwarmed, 98

isCaste, 99
isColony (Colony-class), 23
isCsdActive, 101
isCsdHeterozygous, 101
isDrone, *99*
isDrone (isCaste), 99
isDronesPresent, 102
isEmpty, 103
isFather, *99*
isFather (isCaste), 99
isFathersPresent, 104
isGenoHeterozygous, 105
isMultiColony (MultiColony-class), 115
isNULLColonies, 106
isProductive, 107
isQueen, *39*, *99*, *145*
isQueen (isCaste), 99
isQueenPresent, 108
isSimParamBee, 109
isVirginQueen, *39*, *99*, *145*
isVirginQueen (isCaste), 99
isVirginQueenPresent (isVirginQueensPresent), 109
isVirginQueens (isCaste), 99
isVirginQueensPresent, 109
isWorker, *99*
isWorker (isCaste), 99
isWorkersPresent, 110

mapCasteToColonyAa (mapCasteToColonyValue), 111
mapCasteToColonyBv (mapCasteToColonyValue), 111
mapCasteToColonyDd (mapCasteToColonyValue), 111
mapCasteToColonyGv (mapCasteToColonyValue), 111
mapCasteToColonyPheno, *124*, *127*, *129*
mapCasteToColonyPheno (mapCasteToColonyValue), 111
mapCasteToColonyValue, *14*, 111, *155*
mapLoci, 114
matrix, *9*, *11*
mergePops, *52*
MultiColony-class, 115

nCaste, 118
nColonies, 120
nCsdAlleles, 121
nDrones, *119*
nDrones (nCaste), 118
nDronesColonyPhenotype, *153*
nDronesColonyPhenotype (nDronesPoisson), 123
nDronesPoisson, 123, *153*
nDronesTruncPoisson, *153*
nDronesTruncPoisson (nDronesPoisson), 123
nEmptyColonies, *121*
nEmptyColonies (nColonies), 120
nFathers, *119*
nFathers (nCaste), 118
nFathersPoisson, *39*, 125, *154*
nFathersTruncPoisson, *39*, *154*
nFathersTruncPoisson (nFathersPoisson), 125
nHomBrood (calcQueensPHomBrood), 19
nNULLColonies, *121*
nNULLColonies (nColonies), 120

nQueens, *119*
nQueens *(nCaste)*, 118
nVirginQueens, *119*
nVirginQueens *(nCaste)*, 118
nVirginQueensColonyPhenotype, *154*
nVirginQueensColonyPhenotype *(nVirginQueensPoisson)*, 126
nVirginQueensPoisson, 126, *154*
nVirginQueensTruncPoisson, *154*
nVirginQueensTruncPoisson *(nVirginQueensPoisson)*, 126
nWorkers, *119*
nWorkers *(nCaste)*, 118
nWorkersColonyPhenotype, *153*
nWorkersColonyPhenotype *(nWorkersPoisson)*, 128
nWorkersPoisson, 128, *153*
nWorkersTruncPoisson, *153*
nWorkersTruncPoisson *(nWorkersPoisson)*, 128

pheno, *72*, *113*
pHomBrood *(calcQueensPHomBrood)*, 19
pullCastePop, *50*, 130
pullColonies, 133
pullDroneGroupsFromDCA, *39*, 134, *154*
pullDrones, *132*
pullDrones *(pullCastePop)*, 130
pullIbdHaplo, *66*
pullInd, 136
pullQtlGeno, *76*
pullQtlHaplo, *79*
pullQueen, *132*
pullQueen *(pullCastePop)*, 130
pullSegSiteGeno, *84*
pullSegSiteHaplo, *87*
pullSnpGeno, *90*
pullSnpHaplo, *94*
pullVirginQueens, *132*
pullVirginQueens *(pullCastePop)*, 130
pullWorkers, *132*
pullWorkers *(pullCastePop)*, 130

rcircle, 136, *166*
reduceDroneGeno, 137
reduceDroneHaplo, 138
removeCastePop, 139
removeColonies, 141
removeDrones *(removeCastePop)*, 139
removeQueen *(removeCastePop)*, 139
removeVirginQueens *(removeCastePop)*, 139
removeWorkers *(removeCastePop)*, 139
replaceCastePop, 142
replaceDrones, *8*
replaceDrones *(replaceCastePop)*, 142
replaceVirginQueens *(replaceCastePop)*, 142
replaceWorkers, *8*
replaceWorkers *(replaceCastePop)*, 142
reQueen, 144
resetEvents, *7*, 146

selectColonies, *14*, 148
selectInd, *42*, *51*, *131*, *136*, *140*, *143*
setLocation, 150
setMisc, 151
setQueensYearOfBirth, 151
show,Colony-method *(Colony-class)*, 23
show,MultiColony-method *(MultiColony-class)*, 115
SimParam, *152, 153*
SimParamBee, *5*, *7*, *14*, *16*, *18, 19*, *21*, *27–29*, *31, 32*, *35–37*, *39*, *42–47*, *49*, *52, 53*, *55*, *57–59*, *61*, *63*, *66*, *71*, *76*, *79*, *81, 82*, *84*, *87*, *90*, *93*, *99*, *101, 102*, *104*, *108, 109*, *111*, *113*, *118*, *121–131*, *133*, *135, 136*, *140, 141*, *143*, *145*, *148*, 152, *152*, *156*, *161–163*, *165–168*
simulateHoneyBeeGenomes, 159
split, *154*, 161
splitPColonyStrength, *154*
splitPColonyStrength *(splitPUnif)*, 162
splitPUnif, *154*, 162
supersede, 164
swarm, *154*, 166
swarmPUnif, *154*, 167