Package: VAJointSurv (via r-universe)

November 27, 2026

Type Package

Title Variational Approximation for Joint Survival and Marker Models

Version 0.1.2

Maintainer Benjamin Christoffersen <boennecd@gmail.com>

Description Estimates joint marker (longitudinal) and survival (time-to-event) outcomes using variational approximations. The package supports multivariate markers allowing for correlated error terms and multiple types of survival outcomes which may be left-truncated, right-censored, and recurrent. Time-varying fixed and random covariate effects are supported along with non-proportional hazards.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

URL https://github.com/boennecd/VAJointSurv

BugReports https://github.com/boennecd/VAJointSurv/issues

LinkingTo Rcpp, RcppArmadillo, RcppEigen, testthat, psqn (>= 0.3.0)

Imports Rcpp, splines, utils, stats, SimSurvNMarker, psqn, Matrix, methods, lme4

Suggests rmarkdown, knitr, testthat (>= 3.0.0), xml2, R.rsp

Depends R (>= 3.5.0), survival

VignetteBuilder R.rsp

SystemRequirements C++17

Config/testthat/edition 3

NeedsCompilation yes

Author Benjamin Christoffersen [cre, aut] (ORCID: <https://orcid.org/0000-0002-7182-1346>), Mark Clements [aut], Birzhan Akynkozhayev [aut], Antoine Savine [cph]

Repository https://cran.r-universe.dev

Date/Publication 2026-11-27 22:07:38 UTC

RemoteUrl https://github.com/cran/VAJointSurv

RemoteRef HEAD

RemoteSha 53f75b75ed5c732dab20fc19ddcf6bd801952df6

Contents

bs_term . . . 2
joint_ms_format . . . 3
joint_ms_hess . . . 5
joint_ms_lb . . . 7
joint_ms_opt . . . 8
joint_ms_profile . . . 11
joint_ms_ptr . . . 14
joint_ms_set_vcov . . . 15
joint_ms_start_val . . . 17
joint_ms_va_par . . . 19
marker_term . . . 20
ns_term . . . 22
plot_marker . . . 23
plot_surv . . . 24
poly_term . . . 26
stacked_term . . . 27
surv_term . . . 28
VAJointSurv-terms . . . 30
weighted_term . . . 30

Index **32**

`bs_term` *Term for a B-Spline Basis for Polynomial Splines*

Description

Term for a B-Spline Basis for Polynomial Splines

Usage

```
bs_term(
  x = numeric(),
  df = NULL,
  knots = NULL,
  degree = 3,
  intercept = FALSE,
  Boundary.knots = range(if (use_log) log(x) else x),
  use_log = FALSE
)
```

Arguments

x, df, knots, degree, intercept, Boundary.knots	same as bs.
use_log	TRUE if the polynomials should be in the log of the argument.

Value

A list like bs with an additional element called eval to evaluate the basis. See VAJointSurv-terms.

See Also

poly_term, ns_term, weighted_term, and stacked_term.

Examples

```
vals <- c(0.41, 0.29, 0.44, 0.1, 0.18, 0.65, 0.29, 0.85, 0.36, 0.47)
spline_basis <- bs_term(vals,df = 3)
# evaluate spline basis at 0.5
spline_basis$eval(0.5)
# evaluate first derivative of spline basis at 0.5
spline_basis$eval(0.5, der = 1)
```

---

joint_ms_format *Formats the Parameter Vector*

Description

Formats a parameter vector by putting the model parameters into a list with elements for each type of parameter.

Usage

```
joint_ms_format(object, par = object$start_val)
```

Arguments

object	a joint_ms object from joint_ms_ptr.
par	parameter vector to be formatted.

Value

A list with the following elements:

markers	list with an element for each marker. The lists contains an element called fixef for non-time-varying fixed effects and an element called fixef_vary time-varying fixed effects.

survival	list with an element for each survival outcome. The lists contains an element called fixef for non-time-varying fixed effects, an element called fixef_vary time-varying fixed effects, and an element called associations for the association parameters.
vcov	contains three covariance matrices called vcov_marker, vcov_vary and vcov_surv for the covariance matrix of the markers error term, the time-varying random effects, and the frailties, respectively.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# format the initial parameters stored in the model object
joint_ms_format(object = model_ptr)
```

joint_ms_hess *Computes the Hessian*

Description

Computes the Hessian

Usage

```
joint_ms_hess(
  object,
  par,
  quad_rule = object$quad_rule,
  cache_expansions = object$cache_expansions,
  eps = 1e-04,
  scale = 2,
  tol = .Machine$double.eps^(3/5),
  order = 4L,
  gh_quad_rule = object$gh_quad_rule
)
```

Arguments

object	a joint_ms object from joint_ms_ptr.
par	parameter vector for where the lower bound is evaluated at.
quad_rule	list with nodes and weights for a quadrature rule for the integral from zero to one.
cache_expansions	TRUE if the expansions in the numerical integration in the survival parts of the lower bound should be cached (not recomputed). This requires more memory and may be an advantage particularly with expansions that take longer to compute (like ns_term and bs_term). The computation time may be worse particularly if you use more threads as the CPU cache is not well utilized.
eps, scale, tol, order	parameter to pass to psqn. See psqn_hess.
gh_quad_rule	list with two numeric vectors called node and weight with Gauss–Hermite quadrature nodes and weights to handle delayed entry. A low number of quadrature nodes and weights is used when NULL is passed. This seems to work well when delayed entry happens at time with large marginal survival probabilities. The nodes and weights can be obtained e.g. from fastGHQuad::gaussHermiteData.

Value

A list with the following two Hessian matrices:

hessian	Hessian matrix of the model parameters with the variational parameters profiled out.
hessian_all	Hessian matrix of the model and variational parameters.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# find the starting values
start_vals <- joint_ms_start_val(model_ptr)

# optimize lower bound
fit <- joint_ms_opt(
  object = model_ptr, par = start_vals, gr_tol = .01,
  strong_wolfe = FALSE, cg_tol = .1, pre_method = 1L)

# compute the Hessian
hess <- joint_ms_hess(object = model_ptr,par = fit$par)

# standard errors of the parameters
library(Matrix)
sqrt(diag(solve(hess$hessian)))
```

joint_ms_lb *Evaluates the Lower Bound or the Gradient of the Lower Bound*

Description

Evaluates the Lower Bound or the Gradient of the Lower Bound

Usage

```
joint_ms_lb(
  object,
  par,
  n_threads = object$max_threads,
  quad_rule = object$quad_rule,
  cache_expansions = object$cache_expansions,
  gh_quad_rule = object$gh_quad_rule
)

joint_ms_lb_gr(
  object,
  par,
  n_threads = object$max_threads,
  quad_rule = object$quad_rule,
  cache_expansions = object$cache_expansions,
  gh_quad_rule = object$gh_quad_rule
)
```

Arguments

object	a joint_ms object from joint_ms_ptr.
par	parameter vector for where the lower bound is evaluated at.
n_threads	number of threads to use. This is not supported on Windows.
quad_rule	list with nodes and weights for a quadrature rule for the integral from zero to one.
cache_expansions	TRUE if the expansions in the numerical integration in the survival parts of the lower bound should be cached (not recomputed). This requires more memory and may be an advantage particularly with expansions that take longer to compute (like ns_term and bs_term). The computation time may be worse particularly if you use more threads as the CPU cache is not well utilized.
gh_quad_rule	list with two numeric vectors called node and weight with Gauss–Hermite quadrature nodes and weights to handle delayed entry. A low number of quadrature nodes and weights is used when NULL is passed. This seems to work well when delayed entry happens at time with large marginal survival probabilities. The nodes and weights can be obtained e.g. from fastGHQuad::gaussHermiteData.

Value

`joint_ms_lb` returns a number scalar with the lower bound.

`joint_ms_lb_gr` returns a numeric vector with the gradient.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# find the starting values
start_vals <- joint_ms_start_val(model_ptr)

# same lower bound
all.equal(attr(start_vals,"value"),joint_ms_lb(model_ptr,par = start_vals))
```

`joint_ms_opt` *Optimizes the Lower Bound*

Description

Optimizes the Lower Bound

Usage

```
joint_ms_opt(
  object,
  par = object$start_val,
  rel_eps = 1e-08,
  max_it = 1000L,
  n_threads = object$max_threads,
  c1 = 1e-04,
  c2 = 0.9,
  use_bfgs = TRUE,
  trace = 0L,
  cg_tol = 0.5,
  strong_wolfe = TRUE,
  max_cg = 0L,
  pre_method = 3L,
  quad_rule = object$quad_rule,
  mask = integer(),
  cache_expansions = object$cache_expansions,
  gr_tol = -1,
  gh_quad_rule = object$gh_quad_rule
)
```

Arguments

object	a joint_ms object from joint_ms_ptr.
par	starting value.
rel_eps, max_it, c1, c2, use_bfgs, trace, cg_tol, strong_wolfe, max_cg, pre_method, mask, gr_tol	arguments to pass to the C++ version of psqn.
n_threads	number of threads to use. This is not supported on Windows.
quad_rule	list with nodes and weights for a quadrature rule for the integral from zero to one.
cache_expansions	TRUE if the expansions in the numerical integration in the survival parts of the lower bound should be cached (not recomputed). This requires more memory and may be an advantage particularly with expansions that take longer to compute (like ns_term and bs_term). The computation time may be worse particularly if you use more threads as the CPU cache is not well utilized.
gh_quad_rule	list with two numeric vectors called node and weight with Gauss–Hermite quadrature nodes and weights to handle delayed entry. A low number of quadrature nodes and weights is used when NULL is passed. This seems to work well when delayed entry happens at time with large marginal survival probabilities. The nodes and weights can be obtained e.g. from fastGHQuad::gaussHermiteData.

Value

A list with the following elements:

par	numeric vector of estimated model parameters.
value	numeric scalar with the value of optimized lower bound.
counts	integer vector with the function counts and the number of conjugate gradient iterations. See psqn.
convergence	logical for whether the optimization converged.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# find the starting values
start_vals <- joint_ms_start_val(model_ptr)

# optimize lower bound
fit <- joint_ms_opt(
```

```
  object = model_ptr, par = start_vals, gr_tol = .01,
  strong_wolfe = FALSE, cg_tol = .1, pre_method = 1L)

# formatted maximum likelihood estimators
joint_ms_format(model_ptr, fit$par)
```

`joint_ms_profile` *Approximate Likelihood Ratio based Confidence Intervals*

Description

Approximate Likelihood Ratio based Confidence Intervals

Usage

```
joint_ms_profile(
  object,
  opt_out,
  which_prof,
  delta,
  level = 0.95,
  max_step = 15L,
  rel_eps = 1e-08,
  max_it = 1000L,
  n_threads = object$max_threads,
  c1 = 1e-04,
  c2 = 0.9,
  use_bfgs = TRUE,
  trace = 0L,
  cg_tol = 0.5,
  strong_wolfe = TRUE,
  max_cg = 0L,
  pre_method = 3L,
  quad_rule = object$quad_rule,
  verbose = TRUE,
  mask = integer(),
  cache_expansions = object$cache_expansions,
  gr_tol = -1,
  hess = NULL
)
```

Arguments

`object`	a joint_ms object from `joint_ms_ptr`.
`opt_out`	maximum lower bound estimator from `joint_ms_opt`.
`which_prof`	index of the parameter to profile.

delta — numeric scalar greater than zero for the initial step size. Steps are made of size `2^(iteration - 1) * delta`. A guess of the standard deviation is a good value.

level — confidence level.

max_step — maximum number of steps to take in each direction when constructing the approximate profile likelihood curve.

rel_eps, max_it, c1, c2, use_bfgs, trace, cg_tol, strong_wolfe, max_cg, pre_method, mask, gr_tol — arguments to pass to the C++ version of psqn.

n_threads — number of threads to use. This is not supported on Windows.

quad_rule — list with nodes and weights for a quadrature rule for the integral from zero to one.

verbose — logical for whether to print output during the construction of the approximate profile likelihood curve.

cache_expansions — TRUE if the expansions in the numerical integration in the survival parts of the lower bound should be cached (not recomputed). This requires more memory and may be an advantage particularly with expansions that take longer to compute (like ns_term and bs_term). The computation time may be worse particularly if you use more threads as the CPU cache is not well utilized.

hess — the Hessian from joint_ms_hess. It is used to get better starting values along the profile likelihood curve. Use NULL if it is not passed.

Value

A list with the following elements:

confs — profile likelihood based confidence interval.

xs — the value of the parameter at which the profile likelihood is evaluated at.

p_log_Lik — numeric scalar with the profile log-likelihood.

data — list of lists of the output of each point where the profile likelihood is evaluated with the optimal parameter values of the other parameters given the constrained value of the parameter that is being profiled and the optimal value of the lower bound.

Examples

```
 # load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
```

```
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))


# find the starting values
start_vals <- joint_ms_start_val(model_ptr)

# optimize lower bound
fit <- joint_ms_opt(
  object = model_ptr, par = start_vals, gr_tol = .01,
  strong_wolfe = FALSE, cg_tol = .1, pre_method = 1L)

# compute the Hessian
hess <- joint_ms_hess(object = model_ptr,par = fit$par)

# compute the standard errors
library(Matrix)
se <- sqrt(diag(solve(hess$hessian)))

# find index for the first association parameter
which_prof <- model_ptr$indices$survival[[1]]$associations[1]

# initial step size for finding the confidence interval limits
delta <- 2*se[which_prof]

# compute profile likelihood based confidence interval
# for the first association parameter
profile_CI <- joint_ms_profile(
  object = model_ptr, opt_out = fit, which_prof = which_prof,
  delta = delta, gr_tol = .01,
  strong_wolfe = FALSE, cg_tol = .1, pre_method = 1L)
```

```
# comparison of CIs
profile_CI$confs
fit$par[which_prof]+c(-1,1)*qnorm(0.975)*se[which_prof]
```

`joint_ms_ptr` *Creates a joint_ms Object to Estimate a Joint Survival and Marker Model*

Description

Creates a joint_ms Object to Estimate a Joint Survival and Marker Model

Usage

```
joint_ms_ptr(
  markers = list(),
  survival_terms = list(),
  max_threads = 1L,
  quad_rule = NULL,
  cache_expansions = TRUE,
  gh_quad_rule = NULL,
  ders = NULL
)
```

Arguments

`markers`	either an object from `marker_term` or a list of such objects.
`survival_terms`	either an object from `surv_term` or a list of such objects.
`max_threads`	maximum number of threads to use.
`quad_rule`	list with nodes and weights for a quadrature rule for the integral from zero to one.
`cache_expansions`	`TRUE` if the expansions in the numerical integration in the survival parts of the lower bound should be cached (not recomputed). This requires more memory and may be an advantage particularly with expansions that take longer to compute (like `ns_term` and `bs_term`). The computation time may be worse particularly if you use more threads as the CPU cache is not well utilized.
`gh_quad_rule`	list with two numeric vectors called node and weight with Gauss–Hermite quadrature nodes and weights to handle delayed entry. A low number of quadrature nodes and weights is used when `NULL` is passed. This seems to work well when delayed entry happens at time with large marginal survival probabilities. The nodes and weights can be obtained e.g. from `fastGHQuad::gaussHermiteData`.
`ders`	a `list` of `list`s with `integer` vectors for how the survival outcomes are linked to the markers. 0 implies present values, -1 is integral of, and 1 is the derivative. `NULL` implies the present value of the random effect for all markers. Note that the number of integer vectors should be equal to the number of markers.

Value

An object of `joint_ms` class with the needed C++ and R objects to estimate the model.

See Also

`joint_ms_opt`, `joint_ms_lb`, `joint_ms_hess`, and `joint_ms_start_val`.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L)
```

---

joint_ms_set_vcov *Sets the Covariance Parameters*

Description

Sets the covariance matrices to the passed values. The function also sets covariance matrices for the variational distributions to the same values.

Usage

```
joint_ms_set_vcov(
  object,
  vcov_vary,
  vcov_surv,
  par = object$start_val,
  va_mean = NULL
)
```

Arguments

object	a joint_ms object from joint_ms_ptr.
vcov_vary	the covariance matrix for the time-varying effects.
vcov_surv	the covariance matrix for the frailties.
par	parameter vector to be formatted.
va_mean	a matrix with the number of rows equal to the number of random effects per observation and the number of columns is the number of observations. The order for the observations needs to be the same as the id element of object.

Value

Numeric vector with model parameters.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])
```

```
# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# compute var-covar matrices with the first set of starting values
joint_ms_format(object = model_ptr)$vcov
joint_ms_va_par(object = model_ptr)[[1]]

# altering var-covar matrices
alter_pars <- joint_ms_set_vcov(
  object = model_ptr,
  vcov_vary = diag(1:4),
  vcov_surv = matrix(0,0,0))

# altered var-covar matrices
joint_ms_format(object = model_ptr, par = alter_pars)$vcov
joint_ms_va_par(object = model_ptr, par = alter_pars)[[1]]
```

`joint_ms_start_val` *Quick Heuristic for the Starting Values*

Description

Quick Heuristic for the Starting Values

Usage

```
joint_ms_start_val(
  object,
  par = object$start_val,
  rel_eps = 1e-08,
  max_it = 1000L,
  n_threads = object$max_threads,
  c1 = 1e-04,
  c2 = 0.9,
  use_bfgs = TRUE,
  trace = 0,
  cg_tol = 0.5,
  strong_wolfe = TRUE,
  max_cg = 0,
  pre_method = 3L,
  quad_rule = object$quad_rule,
```

```
  mask = integer(),
  cache_expansions = object$cache_expansions,
  gr_tol = -1,
  gh_quad_rule = object$gh_quad_rule
)
```

Arguments

object	a joint_ms object from joint_ms_ptr.
par	starting value.
rel_eps, max_it, c1, c2, use_bfgs, trace, cg_tol, strong_wolfe, max_cg, pre_method, mask, gr_tol	arguments to pass to the C++ version of psqn.
n_threads	number of threads to use. This is not supported on Windows.
quad_rule	list with nodes and weights for a quadrature rule for the integral from zero to one.
cache_expansions	TRUE if the expansions in the numerical integration in the survival parts of the lower bound should be cached (not recomputed). This requires more memory and may be an advantage particularly with expansions that take longer to compute (like ns_term and bs_term). The computation time may be worse particularly if you use more threads as the CPU cache is not well utilized.
gh_quad_rule	list with two numeric vectors called node and weight with Gauss–Hermite quadrature nodes and weights to handle delayed entry. A low number of quadrature nodes and weights is used when NULL is passed. This seems to work well when delayed entry happens at time with large marginal survival probabilities. The nodes and weights can be obtained e.g. from fastGHQuad::gaussHermiteData.

Value

Numeric vector of starting values for the model parameters.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
```

```
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# find the starting values
start_vals <- joint_ms_start_val(model_ptr)
```

`joint_ms_va_par` *Extracts the Variational Parameters*

Description

Computes the estimated variational parameters for each individual.

Usage

```
joint_ms_va_par(object, par = object$start_val)
```

Arguments

`object`	a joint_ms object from `joint_ms_ptr`.
`par`	parameter vector to be formatted.

Value

A list with one list for each individual with the estimated mean and covariance matrix.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# create the C++ object to do the fitting
model_ptr <- joint_ms_ptr(
  markers = list(m1, m2), survival_terms = s_term,
  max_threads = 2L, ders = list(0L, c(0L, -1L)))

# find the starting values
start_vals <- joint_ms_start_val(model_ptr)

# extract variational parameters for each individual
VA_pars <- joint_ms_va_par(object = model_ptr,par = start_vals)

# number of sets of variational parameters is equal to the number of subjects
length(VA_pars)
length(unique(pbc$id))

# mean and var-covar matrix for 1st individual
VA_pars[[1]]
```

`marker_term` *Creates Data for One Type of Marker*

Description

Creates Data for One Type of Marker

Usage

```
marker_term(formula, id, data, time_fixef, time_rng)
```

Arguments

formula	a two-sided formula with the marker outcome on the left-hand side and fixed effect covariates on the right-hand side.
id	the variable for the id of each individual.
data	a data.frame or environment to look at up the variables in.
time_fixef	the time-varying fixed effects. See .e.g. poly_term.
time_rng	the time-varying random effects. See .e.g. poly_term.

Details

The time_fixef should likely not include an intercept as this is often included in formula. Use poly_term(degree = 0, raw = TRUE, intercept = TRUE) if you want only a random intercept.

Value

An object of class marker_term containing longitudinal data.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
```

ns_term *Term for a Basis Matrix for Natural Cubic Splines*

Description

Term for a Basis Matrix for Natural Cubic Splines

Usage

```
ns_term(
  x = numeric(),
  df = NULL,
  knots = NULL,
  intercept = FALSE,
  Boundary.knots = range(if (use_log) log(x) else x),
  use_log = FALSE
)
```

Arguments

x, df, knots, intercept, Boundary.knots	same as ns.
use_log	TRUE if the polynomials should be in the log of the argument.

Value

A list like ns with an additional element called eval to evaluate the basis. See VAJointSurv-terms.

See Also

poly_term, bs_term, weighted_term, and stacked_term.

Examples

```
vals <- c(0.41, 0.29, 0.44, 0.1, 0.18, 0.65, 0.29, 0.85, 0.36, 0.47)
spline_basis <- ns_term(vals,df = 3)
# evaluate spline basis at 0.5
spline_basis$eval(0.5)
# evaluate first derivative of spline basis at 0.5
spline_basis$eval(0.5, der = 1)
```

plot_marker *Plots a Markers Mean Curve with Pointwise Quantiles*

Description

Plots a Markers Mean Curve with Pointwise Quantiles

Usage

```
plot_marker(
  time_fixef,
  time_rng,
  fixef_vary,
  x_range,
  vcov_vary,
  p = 0.95,
  xlab = "Time",
  ylab = "Marker",
  newdata = NULL,
  ...,
  panel.first = NULL
)
```

Arguments

time_fixef	the time-varying fixed effects. See .e.g. poly_term.
time_rng	the time-varying random effects. See .e.g. poly_term.
fixef_vary	fixed effect coefficients for time_fixef.
x_range	2D numeric vector with start and end points.
vcov_vary	the covariance matrix for time_rng.
p	coverage of the two quantiles.
xlab, ylab, ...	arguments passed to plot.
newdata	data.frame with data for the weights if any.
panel.first	Expression to evaluate after the grid and quantile band and before the mean curve.

Value

A list containing data for plotting.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

fixef_vary <- c(-0.1048, 0.2583, 1.0578, 2.4006, 2.9734)
vcov_vary <- rbind(c(0.96580, 0.09543), c(0.09543,  0.03998))

# plot marker's trajectory
plot_marker(
  time_fixef = m1$time_fixef,
  time_rng = m1$time_rng,
  fixef_vary = fixef_vary,
  vcov_vary = vcov_vary, x_range = c(0,5))
```

---

plot_surv *Plots Quantiles of the Conditional Hazards*

Description

Plots Quantiles of the Conditional Hazards

Usage

```
plot_surv(
  time_fixef,
  time_rng,
  x_range,
  fixef_vary,
  vcov_vary,
  frailty_var,
  ps = c(0.025, 0.5, 0.975),
  log_hazard_shift = 0,
  associations,
  xlab = "Time",
  ylab = "Hazard",
  ders = NULL,
  newdata = NULL,
```

```
  ...,
  panel.first = NULL,
  add = FALSE
)
```

Arguments

time_fixef	the time-varying fixed effects. See .e.g. poly_term. This is for the baseline hazard. Note that many basis expansions have boundary knots. It is important that these are set to cover the full range of survival times including time zero for some expansions.
time_rng	an expansion or a list of expansions for the time-varying random effects of the markers. See marker_term.
x_range	two dimensional numerical vector with the range the hazard should be plotted in.
fixef_vary	fixed effect coefficients for time_fixef.
vcov_vary	covariance matrix for the expansion or expansions in time_rng.
frailty_var	variance of the frailty.
ps	quantiles to plot.
log_hazard_shift	possible shift on the log hazard.
associations	association parameter for each time_rng or possible multiple parameters for each time_rng if ders is supplied.
xlab, ylab, ...	arguments passed to matplot.
ders	a list with integer vectors for how the survival outcome is linked to the markers. 0 implies present values, -1 is integral of, and 1 is the derivative. NULL implies the present value of the random effect for all markers.
newdata	data.frame with data for the weights if any.
panel.first	Expression to evaluate after the grid and before the first curve of a new plot.
add	If TRUE, draw the grid and then the curves on the current plot.

Value

A list containing data for plotting.

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# create the marker terms
```

```
m1 <- marker_term(
  log(bili) ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))
m2 <- marker_term(
  albumin ~ 1, id = id, data = pbcseq,
  time_fixef = bs_term(day_use, df = 5L),
  time_rng = poly_term(day_use, degree = 1L, raw = TRUE, intercept = TRUE))

# base knots on observed event times
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))

# expansion of time for the fixed effects in the survival term
time_fixef <- s_term$time_fixef
# expansion of time for the random effects in the marker terms
time_rng <- list(m1$time_rng, m2$time_rng)
# no frailty
frailty_var <- matrix(0L,1)
# var-covar matrix for time-varying random effects
vcov_vary <- matrix(
  data = c(0.9658, 0.0954, -0.1756, -0.0418, 0.0954, 0.04, -0.0276,
               -0.0128, -0.1756, -0.0276, 0.1189, 0.0077, -0.0418, -0.0128,
               0.0077, 0.0057),
  nrow = 4L)
# coefficients for time-varying fixed effects
fixef_vary <- c(1.0495, -0.2004, 1.4167, 1.255, 2.5007, 4.8545, 4.7889)
# association parameters
associations <- c(0.8627, -3.2358, 0.1842)
# constant shift on the log-hazard scale
log_hazard_shift <- -4.498513
# specify how the survival outcome is linked with markers
ders = list(0L, c(0L, -1L))

# plot the hazard with pointwise quantiles
plot_surv(
  time_fixef = time_fixef,
  time_rng = time_rng,
  x_range = c(0, 5), vcov_vary = vcov_vary, frailty_var = frailty_var,
  ps = c(.25, .5, .75), log_hazard_shift = log_hazard_shift,
  fixef_vary = fixef_vary, associations = associations, ders = ders)
```

---

poly_term *Term for Orthogonal Polynomials*

Description

Term for Orthogonal Polynomials

Usage

```
poly_term(
  x = numeric(),
  degree = 1,
  coefs = NULL,
  raw = FALSE,
  intercept = FALSE,
  use_log = FALSE
)
```

Arguments

x, degree, coefs, raw	same as poly.
intercept	TRUE if there should be an intercept.
use_log	TRUE if the polynomials should be in the log of the argument.

Value

A list like poly with an additional element called eval to evaluate the basis. See VAJointSurv-terms.

See Also

bs_term, ns_term, weighted_term, and stacked_term.

Examples

```
vals <- c(0.41, 0.29, 0.44, 0.1, 0.18, 0.65, 0.29, 0.85, 0.36, 0.47)
spline_basis <- poly_term(vals,degree = 3, raw = TRUE)
# evaluate spline basis at 0.5
spline_basis$eval(0.5)
# evaluate first derivative of spline basis at 0.5
spline_basis$eval(0.5, der = 1)
```

---

stacked_term *Term for a Basis Matrix for of Different Types of Terms*

Description

Creates a basis matrix consisting of different types of terms. E.g. to create a varying-coefficient.

Usage

```
stacked_term(...)
```

Arguments

...	term objects from the package.

Value

A list with an element called `eval` to evaluate the basis. See `VAJointSurv-terms`.

See Also

`poly_term`, `bs_term`, `ns_term`, and `weighted_term`.

Examples

```
vals <- c(0.41, 0.29, 0.44, 0.1, 0.18, 0.65, 0.29, 0.85, 0.36, 0.47)

spline_basis1 <- ns_term(vals, df = 3)
spline_basis2 <- bs_term(vals, df = 3)

# create stacked term from two spline bases
stacked_basis <- stacked_term(spline_basis1, spline_basis2)

# evaluate stacked basis at 0.5
stacked_basis$eval(0.5)
# evaluate first derivative of stacked basis at 0.5
stacked_basis$eval(0.5, der = 1)
```

---

surv_term *Creates Data for One Type of Survival Outcome*

Description

Creates Data for One Type of Survival Outcome

Usage

```
surv_term(formula, id, data, time_fixef, with_frailty = FALSE, delayed = NULL)
```

Arguments

formula	a two-sided `formula` with the survival outcome on the left-hand side and fixed effect covariates on the right-hand side. The left-hand side needs to be a `Surv` object and can be either right-censored and left-truncated.
id	the variable for the id of each individual.
data	`data.frame` with at least the time variable.
time_fixef	the time-varying fixed effects. See .e.g. `poly_term`. This is for the baseline hazard. Note that many basis expansions have boundary knots. It is important that these are set to cover the full range of survival times including time zero for some expansions.

with_frailty	TRUE if there should be a frailty term.
delayed	a vector with an entry which is TRUE if the left-truncation time from the survival outcome is from a delayed entry.

Details

The time_fixef should likely not include an intercept as this is often included in formula.

The delayed argument is to account for delayed entry with terminal events when observations are sampled in a way such that they must not have had the event prior to their left-truncation time. In this case, the proper complete data likelihood is

$$\frac{a(u)h(t_{ij} \mid u)^{d_{ij}} S(t_{ij} \mid u) g(u)}{\int a(u) S(v_{ij} \mid u) du}$$

and not

$$a(u)h(t_{ij} \mid u)^{d_{ij}} \frac{S(t_{ij} \mid u)}{S(v_{ij} \mid u)} g(u)$$

where h is conditional hazard, S is the conditional survival function, g is additional conditional likelihood factors from other outcomes, a is the random effect distribution, t_{ij} is the observed time, d_{ij} is an event indicator, and v_{ij} is the left truncation time.

The denominator in the proper complete likelihood becomes the expectation over all delayed entries when a cluster has more than one delayed entry. See van den Berg and Drepper (2016) and Crowther et al. (2016) for further details.

Value

An object of class surv_term with data required for survival outcome.

References

Crowther MJ, Andersson TM, Lambert PC, Abrams KR & Humphreys K (2016). *Joint modelling of longitudinal and survival data: incorporating delayed entry and an assessment of model misspecification*. Stat Med, 35(7):1193-1209. doi:10.1002/sim.6779

van den Berg GJ & Drepper B (2016). *Inference for Shared-Frailty Survival Models with Left-Truncated Data*. Econometric Reviews, 35:6, 1075-1098, doi: 10.1080/07474938.2014.975640

Examples

```
# load in the data
library(survival)
data(pbc, package = "survival")

# re-scale by year
pbcseq <- transform(pbcseq, day_use = day / 365.25)
pbc <- transform(pbc, time_use = time / 365.25)

# base knots on observed event times
```

```
bs_term_knots <-
  with(pbc, quantile(time_use[status == 2], probs = seq(0, 1, by = .2)))

boundary <- c(bs_term_knots[ c(1, length(bs_term_knots))])
interior <- c(bs_term_knots[-c(1, length(bs_term_knots))])

# create the survival term
s_term <- surv_term(
  Surv(time_use, status == 2) ~ 1, id = id, data = pbc,
  time_fixef = bs_term(time_use, Boundary.knots = boundary, knots = interior))
```

VAJointSurv-terms *Expansions in the VAJointSurv package*

Description

The VAJointSurv package uses different functions to allow for expansions in time possibly with covariate interactions. The main usage of the functions is internally but they do provide an element called 'eval()' which is a function to evaluate the expansion. These functions take the following arguments:

- `x` numeric vector with points at which to evaluate the expansion.
- `der` integer indicating whether to evaluate the expansion, its integral, or the derivative.
- `lower_limit` possible lower limit if integration is performed.
- `newdata` a `data.frame` with new data if this is required. E.g. for `weighted_term`.

The supported terms are `ns_term`, `bs_term`, `poly_term`, `weighted_term`, and a `stacked_term`.

---

weighted_term *Term for a Basis Matrix for Weighted Term*

Description

Creates a weighted basis matrix where the entries are weighted with a numeric vector to e.g. create a varying-coefficient.

Usage

```
weighted_term(x, weight)
```

Arguments

`x`	a term type from the package.
`weight`	a symbol for the weight. Notice that the symbol is first first used when the `eval` function on the returned object is called.

Value

A list with an element called `eval` to evaluate the basis. See VAJointSurv-terms.

See Also

poly_term, bs_term, ns_term, and stacked_term.

Examples

```
vals <- c(0.41, 0.29, 0.44, 0.1, 0.18, 0.65, 0.29, 0.85, 0.36, 0.47)

spline_basis <- ns_term(vals, df = 3)
ws <- c(4,5)
# create a weighted term
w_term <- weighted_term(spline_basis, weights)

# evaluate weighted basis at 0.5 and 0.7 with weights 4 and 5
w_term$eval(c(0.5,0.7), newdata = data.frame(weights = ws))
# evaluate the first derivative of weighted basis at 0.5 and 0.7
# with weights 4 and 5
w_term$eval(c(0.5,0.7), newdata = data.frame(weights = ws), der = 1)
```

Index

bs, *3*
bs_term, 2, *5*, *7*, *9*, *12*, *14*, *18*, *22*, *27, 28*, *30, 31*

data.frame, *28*, *30*

formula, *21*, *28*

integer, *14*, *25*

joint_ms_format, 3
joint_ms_hess, 5, *12*, *15*
joint_ms_lb, 7, *15*
joint_ms_lb_gr *(*joint_ms_lb*)*, 7
joint_ms_opt, 8, *11*, *15*
joint_ms_profile, 11
joint_ms_ptr, *3*, *5*, *7*, *9*, *11*, 14, *16*, *18, 19*
joint_ms_set_vcov, 15
joint_ms_start_val, *15*, 17
joint_ms_va_par, 19

list, *14*, *25*

marker_term, *14*, 20, *25*
matplot, *25*

ns, *22*
ns_term, *3*, *5*, *7*, *9*, *12*, *14*, *18*, 22, *27, 28*, *30, 31*

plot, *23*
plot_marker, 23
plot_surv, 24
poly, *27*
poly_term, *3*, *21–23*, *25*, 26, *28*, *30, 31*
psqn, *9, 10*, *12*, *18*
psqn_hess, *5*

stacked_term, *3*, *22*, 27, *27*, *30, 31*
Surv, *28*
surv_term, *14*, 28

VAJointSurv-terms, 30

weighted_term, *3*, *22*, *27, 28*, 30, *30*