

# Package: admisc (via r-universe)

December 8, 2024

**Version** 0.37

**Title** Adrian Dusa's Miscellaneous

**Depends** R (>= 3.5.0)

**Imports** methods

**Suggests** QCA (>= 3.7)

**Description** Contains functions used across packages 'DDIwR', 'QCA' and 'venn'. Interprets and translates, factorizes and negates SOP - Sum of Products expressions, for both binary and multi-value crisp sets, and extracts information (set names, set values) from those expressions. Other functions perform various other checks if possibly numeric (even if all numbers reside in a character vector) and coerce to numeric, or check if the numbers are whole. It also offers, among many others, a highly versatile recoding routine and some more flexible alternatives to the base functions 'with()' and 'within()'. SOP simplification functions in this package use related minimization from package 'QCA', which is recommended to be installed despite not being listed in the Imports field, due to circular dependency issues.

**License** GPL (>= 3)

**URL** <https://github.com/dusadrian/admisc>

**BugReports** <https://github.com/dusadrian/admisc/issues>

**NeedsCompilation** yes

**Author** Adrian Dusa [aut, cre, cph]  
(<https://orcid.org/0000-0002-3525-9253>)

**Maintainer** Adrian Dusa <dusa.adrian@unibuc.ro>

**Repository** CRAN

**Date/Publication** 2024-12-08 09:00:02 UTC

## Contents

.rda functions: listRDA, objRDA . . . . .	2
About the admisc package . . . . .	3
betweenQuotes . . . . .	4
Brackets . . . . .	4
change . . . . .	6
coerceMode . . . . .	7
combnk . . . . .	8
dimnames . . . . .	9
export . . . . .	9
factorize . . . . .	10
finvert . . . . .	12
frelevel . . . . .	13
getName . . . . .	14
hclr . . . . .	15
inside . . . . .	16
Interpret DNF/SOP expressions: compute, simplify, expand, translate . . . . .	17
intersection . . . . .	21
Negate DNF/SOP expressions . . . . .	23
Number equality . . . . .	25
numdec . . . . .	26
Numeric testing and coercion . . . . .	27
overwrite . . . . .	28
permutations . . . . .	29
recode . . . . .	30
recreate . . . . .	33
replaceText . . . . .	34
scan.clipboard . . . . .	36
Tilde operations . . . . .	36
tryCatchWEM . . . . .	37
using . . . . .	38
<b>Index</b>	<b>40</b>

---

.rda functions: listRDA, objRDA

*Load and list objects from an .rda file*

---

### Description

Utility functions to read the names and load the objects from an .rda file, into an R list.

### Usage

```
listRDA(.filename)
```

```
objRDA(.filename)
```

## Arguments

.filename      The path to the file where the R object is saved.

## Details

Files with the extension .rda are routinely created using the base function `save()`.

The function `listRDA()` loads the object(s) from the .rda file into a list, preserving the object names in the list components.

The .rda file can naturally be loaded with the base `load()` function, but in doing so the containing objects will overwrite any existing objects with the same names.

The function `objRDA()` returns the names of the objects from the .rda file.

## Value

A list, containing the objects from the loaded .rda file.

## Author(s)

Adrian Dusa

---

About the admisc package

*Adrian Dusa's Miscellaneous*

---

## Description

Contains functions used across packages 'DDIwR', 'QCA' and 'venn'. Interprets and translates, factorizes and negates SOP - Sum of Products expressions, for both binary and multi-value crisp sets, and extracts information (set names, set values) from those expressions. Other functions perform various checks if possibly numeric (even if all numbers reside in a character vector) and coerce to numeric, or check if the numbers are whole. It also offers, among many others, a highly versatile recoding routine and some more flexible alternatives to the base functions `with()` and `within()`. SOP simplification functions in this package use related minimization from package **QCA**, which is recommended to be installed despite not being listed in the Imports field, due to circular dependency issues.

## Details

Package: admisc  
Type: Package  
Version: 0.37  
Date: 2024-12-08  
License: GPL (>= 2)

**Author(s)****Authors:**

Adrian Dusa  
 Department of Sociology  
 University of Bucharest  
 <dusa.adrian@unibuc.ro>

**Maintainer:**

Adrian Dusa

---

betweenQuotes      *Extract information between quotes in a string*

---

**Description**

Functions to extract the between the (escaped) quotes, in a string.

**Usage**

betweenQuotes(x)

**Arguments**

x                    A string.

**Author(s)**

Adrian Dusa

**Examples**

```
x <- "An example of \"quoted\" text."
```

```
betweenQuotes(x)
```

---

Brackets                    *Extract information from a multi-value SOP/DNF expression*

---

**Description**

Functions to extract information from an expression written in SOP - sum of products form, (or from the canonical DNF - disjunctive normal form) for multi-value causal conditions. It extracts either the values within brackets, or the causal conditions' names outside the brackets.

**Usage**

```

betweenBrackets(x, type = "[", invert = FALSE, regexp = NULL)
outsideBrackets(x, type = "[", regexp = NULL)
curlyBrackets(x, outside = FALSE, regexp = NULL)
squareBrackets(x, outside = FALSE, regexp = NULL)
roundBrackets(x, outside = FALSE, regexp = NULL)

```

**Arguments**

x	A DNF/SOP expression.
type	Brackets type: curly, round or square.
invert	Logical, if activated returns whatever is not within the brackets.
outside	Logical, if activated returns the conditions' names outside the brackets.
regexp	Optional regular expression to extract information with.

**Details**

Expressions written in SOP - sum of products are used in Boolean logic, signaling a disjunction of conjunctions.

These expressions are useful in Qualitative Comparative Analysis, a social science methodology that is employed in the context of searching for causal configurations that are associated with a certain outcome.

They are also used to draw Venn diagrams with the package `venn`, which draws any kind of set intersection (conjunction) based on a custom SOP expression.

The functions `curlyBrackets`, `squareBrackets` and `roundBrackets` are just special cases of the functions `betweenBrackets` and `outsideBrackets`, using the argument `type` as either "{", "[" or "(".

The function `outsideBrackets` itself can be considered a special case of the function `betweenBrackets`, when it uses the argument `invert = TRUE`.

SOP expressions are usually written using curly brackets for multi-value conditions but to allow the evaluation of unquoted expressions, they first needs to get past R's internal parsing system. For this reason, multi-value conditions in unquoted expressions should use the square brackets notation, and conjunctions should always use the product `*` sign.

Sufficiency is recognized as "`=>`" in quoted expressions but this does not pass over R's parsing system in unquoted expressions. To overcome this problem, it is best to use the single arrow "`->`" notation. Necessity is recognized as either "`<=`" or "`<-`", both being valid in quoted and unquoted expressions.

**Author(s)**

Adrian Dusa

**Examples**

```
sop <- "A[1] + B[2]*C[0]"

betweenBrackets(sop) # 1, 2, 0

betweenBrackets(sop, invert = TRUE) # A, B, C

# unquoted (valid) SOP expressions are allowed, same result
betweenBrackets(A[1] + B[2]*C[0]) # the default type is "["

# curly brackets are also valid in quoted expressions
betweenBrackets("A{1} + B{2}*C{0}", type = "{")

# or
curlyBrackets("A{1} + B{2}*C{0}")

# and the condition names
curlyBrackets("A{1} + B{2}*C{0}", outside = TRUE)

squareBrackets(A[1] + B[2]*C[0]) # 1, 2, 0

squareBrackets(A[1] + B[2]*C[0], outside = TRUE) # A, B, C
```

---

change

*Generic function to change the structure of an object, function of the (changed) parameters used to create it.*

---

**Description**

A generic function that applies different altering methods for different types of objects (of certain classes).

**Usage**

```
change(x, ...)
```

**Arguments**

x                    An object of a particular class.  
...                   Arguments to be passed to a specific method.

**Details**

For the time being, this function is designed to change truth table objects (only). Future versions will likely add class methods for different other objects.

**Value**

The changed object.

**Author(s)**

Adrian Dusa

**Examples**

```
## Not run:
# An example to change a QCA truth table
library(QCA)

ttLF <- truthTable(LF, outcome = SURV, incl.cut = 0.8)
minimize(ttLF, include = "?")

# excluding contradictory simplifying assumptions
minimize(
  change(ttLF, exclude = findRows(type = 2)),
  include = "?"
)

## End(Not run)
```

---

`coerceMode`*Coerce an atomic vector to numeric or integer, if possible*

---

**Description**

This function verifies if an R vector is possibly numeric, and further if the numbers inside are whole numbers.

**Usage**`coerceMode(x)`**Arguments**

`x` An atomic R vector

**Value**

An R vector of coerced mode.

**Author(s)**

Adrian Dusa

**Examples**

```
obj <- c("1.0", 2:5)

is.integer(coerceMode(obj))
```

---

`combnk`*Generate all combinations of n numbers, taken k at a time*

---

**Description**

A fast function to generate all possible combinations of n numbers, taken k at a time, starting from the first k numbers or starting from a combination that contain a certain number.

**Usage**

```
combnk(n, k, ogte = 0, zerobased = FALSE)
```

**Arguments**

n	Vector of any kind, or a numerical scalar.
k	Numeric scalar.
ogte	At least one value greater than or equal to this number.
zerobased	Logical, zero or one based.

**Details**

When a scalar, argument n should be numeric, otherwise when a vector its length should not be less than k.

When the argument ogte is specified, the combinations will sequentially be incremented from those which contain a certain number, or a certain position from n when specified as a vector.

**Value**

A matrix with k rows and `choose(n, k)` columns.

**Author(s)**

Adrian Dusa

**Examples**

```
combnk(5, 2)
```

```
combnk(5, 2, ogte = 3)
```

```
combnk(letters[1:5], 2)
```



---

dimnames	<i>Set matrix row or column names</i>
----------	---------------------------------------

---

**Description**

Set matrix row or column names without copying, especially useful for (very) large matrices.

**Usage**

```
setColnames(matrix, colnames)
setRownames(matrix, rownames)
setDimnames(matrix, nameslist)
```

**Arguments**

matrix	An R matrix
colnames	Character vector of column names
rownames	Character vector of row names
nameslist	A two-component list containing rownames and colnames

**Author(s)**

Adrian Dusa

**Examples**

```
mat <- matrix(1:9, nrow = 3)
setDimnames(mat, list(LETTERS[1:3], letters[1:3]))
```

---

export	<i>Export an object to a file or a connection</i>
--------	---

---

**Description**

This is a generic function, usually a wrapper to [write.table\(\)](#).

**Usage**

```
export(what, ...)
```

**Arguments**

what	The object to be written (matrix or dataframe)
...	Specific arguments to class functions.

**Details**

The default convention for `write.table()` is to add a blank column name for the row names, but (despite it is a standard used for CSV files) that doesn't work with all spreadsheets or other programs that attempt to import the result of `write.table()`.

This function acts as if `write.table()` was called, with only one difference: if row names are present in the dataframe (i.e. any of them should be different from the default row numbers), the final result will display a new column called `cases` in the first position, except the situation that another column called `cases` already exists in the data, when the row names will be completely ignored.

If not otherwise specified, an argument `sep = ", "` is added by default.

The argument `row.names` is always set to `FALSE`, a new column being added anyways (if possible).

Since this function pipes everything to `write.table()`, the argument `file` can also be a connection open for writing, and `" "` indicates output to the console.

**Author(s)**

Adrian Dusa

**See Also**

The "R Data Import/Export" manual.

[write.table](#)

---

factorize

*Factorize Boolean expressions*

---

**Description**

This function finds all combinations of common factors in a Boolean expression written in SOP - sum of products. It makes use of the function `simplify()`, which uses the function `minimize()` from package **QCA**). Users are highly encouraged to install and load that package, despite not being present in the Imports field (due to circular dependency issues).

**Usage**

```
factorize(input, snames = "", noflevels = NULL, pos = FALSE, ...)
```

**Arguments**

<code>input</code>	A string representing a SOP expression, or a minimization object of class "qca".
<code>snames</code>	A string containing the sets' names, separated by commas.
<code>noflevels</code>	Numerical vector containing the number of levels for each set.
<code>pos</code>	Logical, if possible factorize using product(s) of sums.
<code>...</code>	Other arguments (mainly for backwards compatibility).

## Details

Factorization is a process of finding common factors in a Boolean expression, written in SOP - sum of products. Whenever possible, the factorization can also be performed in a POS - product of sums form.

Conjunctions should preferably be indicated with a star \* sign, but this is not necessary when conditions have single letters or when the expression is expressed in multi-value notation.

The argument `snames` is only needed when conjunctions are not indicated by any sign, and the set names have more than one letter each (see function [translate\(\)](#) for more details).

The number of levels in `noflevels` is needed only when negating multivalued conditions, and it should complement the `snames` argument.

If input is an object of class "qca" (the result of the function [minimize\(\)](#) from package **QCA**), a factorization is performed for each of the minimized solutions.

## Value

A named list, each component containing all possible factorizations of the input expression(s), found in the name(s).

## Author(s)

Adrian Dusa

## References

Ragin, C.C. (1987) *The Comparative Method. Moving beyond qualitative and quantitative strategies*, Berkeley: University of California Press

## See Also

[translate](#)

## Examples

```
# typical example with redundant conditions
factorize(a~b~cd + a~bc~d + a~bcd + abc~d)

# results presented in alphabetical order
factorize(~one*two*~four + ~one*three + three*~four)

# to preserve a certain order of the set names
factorize(~one*two*~four + ~one*three + three*~four,
          snames = c(one, two, three, four))

# using pos - products of sums
factorize(~a~c + ~ad + ~b~c + ~bd, pos = TRUE)

## Not run:
# make sure the package QCA is loaded
library(QCA)
```

```
# using an object of class "qca" produced with function minimize()
# in package QCA

pCVF <- minimize(CVF, outcome = "PROTEST", incl.cut = 0.8,
                include = "?", use.letters = TRUE)

factorize(pCVF)

# using an object of class "deMorgan" produced with negate()
factorize(negate(pCVF))

## End(Not run)
```

---

finvert

*Inverts the values of a factor*

---

### Description

Useful function to invert the values from a categorical variable, for instance a Likert response scale.

### Usage

```
finvert(x, levels = FALSE)
```

### Arguments

x	A categorical variable (a factor)
levels	Logical, invert the levels as well

### Value

A factor of the same length as the original one.

### Author(s)

Adrian Dusa

### Examples

```
words <- c("ini", "mini", "miny", "moe")
variable <- factor(words, levels = words)

# inverts the value, preserving the levels
finvert(variable)

# inverts both values and levels
finvert(variable, levels = TRUE)
```

---

frelevel	<i>Modified relevel() function</i>
----------	------------------------------------

---

### Description

The base function `relevel()` accepts a single argument "ref", which can only be a scalar and not a vector of values. `frelevel()` accepts more (even all) levels and reorders them.

### Usage

```
frelevel(variable, levels)
```

### Arguments

variable	The categorical variable of interest
levels	One or more levels of the factor, in the desired order

### Value

A factor of the same length as the initial one.

### Author(s)

Adrian Dusa

### See Also

[relevel](#)

### Examples

```
words <- c("ini", "mini", "miny", "moe")
variable <- factor(words, levels = words)

# modify the order of the levels, keeping the order of the values
frelevel(variable, c("moe", "ini", "miny", "mini"))
```

getName

*Get the name of the object being used in a function call*

---

**Description**

This is a utility to be used inside a function.

**Usage**

```
getName(x, object = FALSE)
```

**Arguments**

x	String, expression to be evaluated
object	Logical, return the object's name

**Details**

Within a function, the argument `x` can be anything and it is usually evaluated as an object.

This function should be used in conjunction with the base `match.call()`, to obtain the original name of the object being served as an input, regardless of how it is being served.

A particular use case of this function relates to the cases when a variable within a `data.frame` is used. The overall name of the object (the data frame) is irrelevant, as the real object of interest is the variable.

**Value**

A character vector of length 1.

**Author(s)**

Adrian Dusa

**Examples**

```
foo <- function(x) {  
  funargs <- sapply(match.call(), deparse)[-1]  
  return(getName(funargs[1]))  
}
```

```
dd <- data.frame(X = 1:5, Y = 1:5, Z = 1:5)
```

```
foo(dd)  
# dd
```

```
foo(dd$X)  
# X
```

```
foo(dd[["X"]])
# X

foo(dd[[c("X", "Y")]])
# X Y

foo(dd[, 1])
# X

foo(dd[, 2:3])
# Y Z
```

---

hclr

*Colors from the HCL spectrum*

---

### Description

Produces colors from the HCL (Hue Chroma Luminance) spectrum, based on the number of levels from a factor.

### Usage

```
hclr(x, starth = 25, c = 50, l = 75, alpha = 1, fixup = TRUE)
```

### Arguments

x	Number of factor levels, or the factor itself, or a frequency distribution from a factor
starth	Starting point for the hue (in the interval 0 - 360)
c	chroma - color purity, small values produce dark and high values produce bright colors
l	color luminance - a number between 0 and 100
alpha	color transparency, where 0 is a completely transparent color, up to 1
fixup	logical, corrects the RGB values to produce a realistic color

### Details

Any value of h outside the interval 0 - 360 is constrained to this interval using modulo values. For instance, 410 is constrained to  $50 = 410$

### Value

The RGB code for the corresponding HCL colors.

### Author(s)

Adrian Dusa

**Examples**

```
aa <- sample(letters[1:5], 100, replace = TRUE)

hclr(aa)

# same with
hclr(5)

# or
hclr(table(aa))
```

---

inside

*Evaluate an Expression in a Data Environment*


---

**Description**

Evaluate an R expression in an environment constructed from data.

**Usage**

```
inside(data, expr, ...)

## S3 method for class 'list'
inside(data, expr, keepAttrs = TRUE, ...)
```

**Arguments**

**data** Data to use for constructing an environment a data frame or a list.  
**expr** Expression to evaluate, often a “compound” expression, i.e., of the form

```
{
  a <- somefun()
  b <- otherfun()
  .....
  rm(unused1, temp)
}
```

**keepAttrs** For the `list` method of `inside()`, a `logical` specifying if the resulting list should keep the `attributes` from data and have its `names` in the same order. Often this is unneeded as the result is a *named* list anyway, and then `keepAttrs = FALSE` is more efficient.

**...** Arguments to be passed to (future) methods.

**Details**

This is a modified version of the base R function `within()`, with exactly the same arguments and functionality but only one fundamental difference: instead of returning a modified copy of the input data, this function alters the data directly.



**Author(s)**

Adrian Dusa

**Examples**

```
mt <- mtcars
inside(mt, hwratio <- hp/wt)

dim(mtcars)

dim(mt)
```

---

Interpret DNF/SOP expressions: compute, simplify, expand, translate  
*Functions to interpret and manipulate a SOP/DNF expression*

---

**Description**

These functions interpret an expression written in sum of products (SOP) or in canonical disjunctive normal form (DNF), for both crisp and multivalued notations. The function `compute()` calculates set membership scores based on a SOP expression applied to a calibrated data set (see function `calibrate()` from package **QCA**), while the function `translate()` translates a SOP expression into a matrix form.

The function `simplify()` transforms a SOP expression into a simpler equivalent, through a process of Boolean minimization. The package uses the function `minimize()` from package **QCA**, so users are highly encouraged to install and load that package, despite not being present in the Imports field (due to circular dependency issues).

Function `expand()` performs a Quine expansion to the complete DNF, or a partial expansion to a SOP expression with equally complex terms.

Function `asSOP()` returns a SOP expression from a POS (product of sums) expression. This function is different from the function `invert()`, which also negates each causal condition.

Function `mvSOP()` coerces an expression from crisp set notation to multi-valued notation.

**Usage**

```
asSOP(expression = "", snames = "", noflevels = NULL)

compute(expression = "", data = NULL, separate = FALSE, ...)

expand(expression = "", snames = "", noflevels = NULL, partial = FALSE,
        implicants = FALSE, ...)

mvSOP(expression = "", snames = "", data = NULL, keep.tilde = TRUE, ...)

simplify(expression = "", snames = "", noflevels = NULL, ...)

translate(expression = "", snames = "", noflevels = NULL, data = NULL, ...)
```

**Arguments**

expression	String, a SOP expression.
data	A dataset with binary cs, mv and fs data.
separate	Logical, perform computations on individual, separate paths.
snames	A string containing the sets' names, separated by commas.
noflevels	Numerical vector containing the number of levels for each set.
partial	Logical, perform a partial Quine expansion.
implicants	Logical, return an expanded matrix in the implicants space.
keep.tilde	Logical, preserves the tilde sign when coercing a factor level
...	Other arguments, mainly for backwards compatibility.

**Details**

An expression written in sum of products (SOP), is a "union of intersections", for example  $A*B + B*\sim C$ . The disjunctive normal form (DNF) is also a sum of products, with the restriction that each product has to contain all literals. The equivalent DNF expression is:  $A*B*\sim C + A*B*C + \sim A*B*\sim C$

The same expression can be written in multivalued notation:  $A[1]*B[1] + B[1]*C[0]$ .

Expressions can contain multiple values for the same condition, separated by a comma. If B was a multivalued causal condition, an expression could be:  $A[1] + B[1,2]*C[0]$ .

Whether crisp or multivalued, expressions are treated as Boolean. In this last example, all values in B equal to either 1 or 2 will be converted to 1, and the rest of the (multi)values will be converted to 0.

Negating a multivalued condition requires a known number of levels (see examples below). Intersections between multiple levels of the same condition are possible. For a causal condition with 3 levels (0, 1 and 2) the following expression  $\sim A[0,2]*A[1,2]$  is equivalent with  $A[1]$ , while  $A[0]*A[1]$  results in the empty set.

The number of levels, as well as the set names can be automatically detected from a dataset via the argument data. When specified, arguments snames and noflevels have precedence over data.

The product operator \* should always be used, but it can be omitted when the data is multivalued (where product terms are separated by curly brackets), and/or when the set names are single letters (for example  $AD + B\sim C$ ), and/or when the set names are provided via the argument snames.

When expressions are simplified, their simplest equivalent can result in the empty set, if the conditions cancel each other out.

The function mvSOP() assumes binary crisp conditions in the expression, except for categorical data used as multi-value conditions. The factor levels are read directly from the data, and they should be unique across all conditions.

**Value**

For the function compute(), a vector of set membership values.

For function simplify(), a character expression.

For the function translate(), a matrix containing the implicants on the rows and the set names on the columns, with the following codes:

- 0 absence of a causal condition
- 1 presence of a causal condition
- 1 causal condition was eliminated

The matrix was also assigned a class "translate", to avoid printing the -1 codes when signaling a minimized condition. The mode of this matrix is character, to allow printing multiple levels in the same cell, such as "1,2".

For function expand(), a character expression or a matrix of implicants.

### Author(s)

Adrian Dusa

### References

Ragin, C.C. (1987) *The Comparative Method: Moving beyond Qualitative and Quantitative Strategies*. Berkeley: University of California Press.

### Examples

```
# -----
# for compute()
## Not run:
# make sure the package QCA is loaded
library(QCA)
compute(DEV*~IND + URB*STB, data = LF)

# calculating individual paths
compute(DEV*~IND + URB*STB, data = LF, separate = TRUE)

## End(Not run)

# -----
# for simplify(), also make sure the package QCA is loaded
simplify(asSOP("(A + B)(A + ~B)")) # result is "A"

# works even without the quotes
simplify(asSOP((A + B)(A + ~B))) # result is "A"

# but to avoid confusion POS expressions are more clear when quoted
# to force a certain order of the set names
simplify("(URB + LIT*~DEV)(~LIT + ~DEV)", snames = c(DEV, URB, LIT))

# multilevel conditions can also be specified (and negated)
simplify("(A[1] + ~B[0])(B[1] + C[0])", snames = c(A, B, C), noflevels = c(2, 3, 2))

# Ragin's (1987) book presents the equation E = SG + LW as the result
# of the Boolean minimization for the ethnic political mobilization.
```

```

# intersecting the reactive ethnicity perspective (R =  $\sim L \sim W$ )
# with the equation E (page 144)

simplify(" $\sim L \sim W(SG + LW)$ ", snames = c(S, L, W, G))

# [1] "S $\sim L \sim WG$ "

# resources for size and wealth (C = SW) with E (page 145)
simplify("SW(SG + LW)", snames = c(S, L, W, G))

# [1] "SWG + SLW"

# and factorized
factorize(simplify("SW(SG + LW)", snames = c(S, L, W, G)))

# F1: SW(G + L)

# developmental perspective (D = Lg) and E (page 146)
simplify("L $\sim G(SG + LW)$ ", snames = c(S, L, W, G))

# [1] "LW $\sim G$ "

# subnations that exhibit ethnic political mobilization (E) but were
# not hypothesized by any of the three theories (page 147)
#  $\sim H = \sim(\sim L \sim W + SW + L \sim G) = GL \sim S + GL \sim W + G \sim SW + \sim L \sim SW$ 

simplify("(GL $\sim S + GL \sim W + G \sim SW + \sim L \sim SW$ )(SG + LW)", snames = c(S, L, W, G))

# -----
# for translate()
translate(A + B*C)

# same thing in multivalued notation
translate(A[1] + B[1]*C[1])

# tilde as a standard negation (note the condition "b"!))
translate( $\sim A + b * C$ )

# and even for multivalued variables
# in multivalued notation, the product sign * is redundant
translate(C[1] + T[2] + T[1]*V[0] + C[0])

# negation of multivalued sets requires the number of levels
translate( $\sim A[1] + \sim B[0] * C[1]$ , snames = c(A, B, C), nolevels = c(2, 2, 2))

# multiple values can be specified
translate(C[1] + T[1,2] + T[1]*V[0] + C[0])

# or even negated

```

```

translate(C[1] + ~T[1,2] + T[1]*V[0] + C[0], snames = c(C, T, V), noflevels = c(2,3,2))

# if the expression does not contain the product sign *
# snames are required to complete the translation
translate(AaBb + ~CcDd, snames = c(Aa, Bb, Cc, Dd))

# to print _all_ codes from the standard output matrix
(obj <- translate(A + ~B*C))
print(obj, original = TRUE) # also prints the -1 code

# ----
# for expand()
expand(~AB + B~C)

# S1: ~AB~C + ~ABC + AB~C

expand(~AB + B~C, snames = c(A, B, C, D))

# S1: ~AB~C~D + ~AB~CD + ~ABC~D + ~ABCD + AB~C~D + AB~CD

# In implicants form:
expand(~AB + B~C, snames = c(A, B, C, D), implicants = TRUE)

#      A B C D
# [1,] 1 2 1 1  ~AB~C~D
# [2,] 1 2 1 2  ~AB~CD
# [3,] 1 2 2 1  ~ABC~D
# [4,] 1 2 2 2  ~ABCD
# [5,] 2 2 1 1  AB~C~D
# [6,] 2 2 1 2  AB~CD

```

---

intersection

*Intersect expressions*

---

### Description

This function takes two or more SOP expressions (combinations of conjunctions and disjunctions) or even entire minimization objects, and finds their intersection.

### Usage

```
intersection(..., snames = "", noflevels)
```

### Arguments

...	One or more expressions, combined with / or minimization objects of class "QCA_min".
snames	A string containing the sets' names, separated by commas.
noflevels	Numerical vector containing the number of levels for each set.

## Details

The initial aim of this function was to provide a software implementation of the intersection examples presented by Ragin (1987: 144-147). That type of example can also be performed with the function `simplify()`, while this function is now mainly used in conjunction with the `modelFit()` function from package **QCA**, to assess the intersection between theory and a QCA model.

Irrespective of the input type (character expressions and / or minimization objects), this function is now a wrapper to the main `simplify()` function (which only accepts character expressions).

It can deal with any kind of expressions, but multivalent crisp conditions need additional information about their number of levels, via the argument `noflevels`.

The expressions can be formulated in terms of either lower case - upper case notation for the absence and the presence of the causal condition, or use the tilde notation (see examples below). Usage of either of these is automatically detected, as long as all expressions use the same notation.

If the `snames` argument is provided, the result is sorted according to the order of the causal conditions (set names) in the original dataset, otherwise it sorts the causal conditions in alphabetical order.

For minimization objects of class "QCA\_min", the number of levels, and the set names are automatically detected.

## Author(s)

Adrian Dusa

## References

Ragin, Charles C. 1987. *The Comparative Method: Moving beyond Qualitative and Quantitative Strategies*. Berkeley: University of California Press.

## Examples

```
# using minimization objects
## Not run:
library(QCA) # if not already loaded
ttLF <- truthTable(LF, outcome = "SURV", incl.cut = 0.8)
pLF <- minimize(ttLF, include = "?")

# for example the intersection between the parsimonious model and
# a theoretical expectation
intersection(pLF, DEV*STB)

# negating the model
intersection(negate(pLF), DEV*STB)

## End(Not run)

# -----
# in Ragin's (1987) book, the equation E = SG + LW is the result
```

```

# of the Boolean minimization for the ethnic political mobilization.

# intersecting the reactive ethnicity perspective (R = lw)
# with the equation E (page 144)
intersection(~L~W, SG + LW, snames = c(S, L, W, G))

# resources for size and wealth (C = SW) with E (page 145)
intersection(SW, SG + LW, snames = c(S, L, W, G))

# and factorized
factorize(intersection(SW, SG + LW, snames = c(S, L, W, G)))

# developmental perspective (D = L~G) and E (page 146)
intersection(L~G, SG + LW, snames = c(S, L, W, G))

# subnations that exhibit ethnic political mobilization (E) but were
# not hypothesized by any of the three theories (page 147)
# ~H = ~(~L~W + SW + L~G)
intersection(negate(~L~W + SW + L~G), SG + LW, snames = c(S, L, W, G))

```

---

Negate DNF/SOP expressions

*Negate Boolean expressions*

---

## Description

Functions to negate a DNF/SOP expression, or to invert a SOP to a negated POS or a POS to a negated SOP.

## Usage

```
negate(input, snames = "", noflevels, simplify = TRUE, ...)
```

```
invert(input, snames = "", noflevels)
```

## Arguments

input	A string representing a SOP expression, or a minimization object of class "QCA_min".
snames	A string containing the sets' names, separated by commas.
noflevels	Numerical vector containing the number of levels for each set.
simplify	Logical, allow users to choose between the raw negation or its simplest form.
...	Other arguments (mainly for backwards compatibility).

## Details

In Boolean algebra, there are two transformation rules named after the British mathematician Augustus De Morgan. These rules state that:

1. The complement of the union of two sets is the intersection of their complements.
2. The complement of the intersection of two sets is the union of their complements.

In "normal" language, these would be written as:

1. not (A and B) = (not A) or (not B)
2. not (A or B) = (not A) and (not B)

Based on these two laws, any Boolean expression written in disjunctive normal form can be transformed into its negation.

It is also possible to negate all models and solutions from the result of a Boolean minimization from function `minimize()` in package QCA. The resulting object, of class "qca", is automatically recognised by this function.

In a SOP expression, the products should normally be split by using a star \* sign, otherwise the sets' names will be considered the individual letters in alphabetical order, unless they are specified via snames.

To negate multilevel expressions, the argument `noflevels` is required.

It is entirely possible to obtain multiple negations of a single expression, since the result of the negation is passed to function `simplify()`.

Function `invert()` simply transforms an expression from a sum of products (SOP) to a negated product of sums (POS), and the other way round.

## Value

A character vector when the input is a SOP expression, or a named list for minimization input objects, each component containing all possible negations of the model(s).

## Author(s)

Adrian Dusa

## References

Ragin, Charles C. 1987. *The Comparative Method: Moving beyond Qualitative and Quantitative Strategies*. Berkeley: University of California Press.

## See Also

`minimize`, `simplify`

## Examples

```
# example from Ragin (1987, p.99)
negate(AC + B~C, simplify = FALSE)

# the simplified, logically equivalent negation
```



```
negate(AC + B~C)

# with different intersection operators
negate(AB*EF + ~CD*EF)

# invert to POS
invert(a*b + ~c*d)

## Not run:
# using an object of class "qca" produced with minimize()
# from package QCA
library(QCA)
cLC <- minimize(LC, outcome = SURV)

negate(cLC)

# parsimonious solution
pLC <- minimize(LC, outcome = SURV, include = "?")

negate(pLC)

## End(Not run)
```

---

Number equality	<i>Check difference and / or (in)equality of numbers</i>
-----------------	--

---

### Description

Check if one number is greater / lower than (or equal to) another.

### Usage

```
agtb(a, b, bincat)
altb(a, b, bincat)
agteb(a, b, bincat)
alteb(a, b, bincat)
aeqb(a, b, bincat)
aneqb(a, b, bincat)
```

### Arguments

a	Numerical vector
b	Numerical vector
bincat	Binary categorization values, an atomic vector of length 2

**Details**

Not all numbers (especially the decimal ones) can be represented exactly in floating point arithmetic, and their arithmetic may not give the normal expected result.

This set of functions check for the in(equality) between two numerical vectors a and b, with the following name convention:

gt means “greater than”

lt means a “lower than” b

gte means a “greater than or equal to” b

lte means a “lower than or equal to” b

eq means a “equal to” b

neq means a “not equal to” b

The argument values is useful to replace the TRUE / FALSE values with custom categories.

**Author(s)**

Adrian Dusa

**References**

Goldberg, David (1991) "What Every Computer Scientist Should Know About Floating-point Arithmetic", ACM Computing Surveys vol.23, no.1, pp.5-48, doi:[10.1145/103162.103163](https://doi.org/10.1145/103162.103163)

---

numdec

*Count number of decimals*

---

**Description**

Calculates the (maximum) number of decimals in a possibly numeric vector.

**Usage**

```
numdec(x, each = FALSE, na.rm = TRUE, maxdec = 15)
```

**Arguments**

x	A vector of values
each	Logical, return the result for each value in the vector
na.rm	Logical, ignore missing values
maxdec	Maximal number of decimals to count

**Author(s)**

Adrian Dusa

**Examples**

```
x <- c(12, 12.3, 12.34)

numdec(x) # 2

numdec(x, each = TRUE) # 0, 1, 2

x <- c("-.1", " 2.75 ", "12", "B", NA)

numdec(x) # 2

numdec(x, each = TRUE) # 1, 2, 0, NA, NA
```

---

Numeric testing and coercion  
*Numeric vectors*

---

**Description**

Coerces objects to class "numeric", and checks if an object is numeric.

**Usage**

```
asNumeric(x, ...)
possibleNumeric(x, each = FALSE)
wholeNumeric(x, each = FALSE)
```

**Arguments**

x	A vector of values
each	Logical, return the result for each value in the vector
...	Other arguments to be passed for class based methods

**Details**

Unlike the function `as.numeric()` from the **base** package, the function `asNumeric()` coerces to numeric without a warning if any values are not numeric. All such values are considered NA missing.

This is a generic function, with specific class methods for factors and objects of class "declared". The usual way of coercing factors to numeric is meaningless, converting the inner storage numbers. The class method of this particular function coerces the levels to numeric, via the default activated argument `levels`.

For objects of class "declared", a similar argument called `na_values` is by default activated to coerce the declared missing values to numeric.

The function `possibleNumeric()` tests if the values in a vector are possibly numeric, irrespective of their storing as character or numbers. In the case of factors, it tests its levels representation.

Function `wholeNumeric()` tests if numbers in a vector are whole (round) numbers. Whole numbers are different from “integer” numbers (which have special memory representation), and consequently the function `is.integer()` tests something different, how numbers are stored in memory (see the description of function `double()` for more details).

The function

### Author(s)

Adrian Dusa

### See Also

[numeric](#), [integer](#), [double](#)

### Examples

```
x <- c("-.1", " 2.7 ", "B")
asNumeric(x) # no warning

f <- factor(c(3, 2, "a"))

asNumeric(f)

asNumeric(f, levels = FALSE)

possibleNumeric(x) # FALSE

possibleNumeric(x, each = TRUE) # TRUE TRUE FALSE

possibleNumeric(c("1", 2, 3)) # TRUE

is.integer(1) # FALSE

# Signaling an integer in R
is.integer(1L) # TRUE

wholeNumeric(1) # TRUE

wholeNumeric(c(1, 1.1), each = TRUE) # TRUE FALSE
```

---

overwrite

*Overwrite an object in a given environment.*

---

### Description

Utility function to overwrite an object, and bypass the assignment operator.

### Usage

```
overwrite(objname, content, environment)
```

**Arguments**

objname        Character, the name of the object to overwrite.  
content        An R object  
environment    The environment where to perform the overwrite procedure.

**Value**

This function does not return anything.

**Author(s)**

Adrian Dusa

**Examples**

```
foo <- function(object, x) {  
  objname <- deparse(substitute(object))  
  object <- x  
  overwrite(objname, object, parent.frame())  
}
```

```
bar <- 1  
foo(bar, 2)
```

```
bar  
# [1] 2
```

```
bar <- list(A = bar)  
foo(bar$A, 3)
```

```
bar
```

---

permutations

*Calculates the permutations of a vector*

---

**Description**

Generates all possible permutations of elements from a vector.

**Usage**

```
permutations(x)
```

**Arguments**

x                Any kind of vector.

**Author(s)**

Adrian Dusa

**Examples**

```
permutations(1:3)
```

---

 recode

*Recode a variable*


---

**Description**

Recodes a vector (numeric, character or factor) according to a set of rules. It is similar to the function `recode()` from package **car**, but more flexible. It also has similarities with the function `findInterval()` from package **base**.

**Usage**

```
recode(x, rules = NULL, cut = NULL, values = NULL, ...)
```

**Arguments**

<code>x</code>	A vector of mode numeric, character or factor.
<code>rules</code>	Character string or a vector of character strings for recoding specifications.
<code>cut</code>	A vector of one or more unique cut points.
<code>values</code>	A vector of output values.
<code>...</code>	Other parameters, for compatibility with other functions such as <code>recode()</code> in package <b>car</b> but also <code>factor()</code> in package <b>base</b>

**Details**

Similar to the `recode()` function in package **car**, the recoding rules are separated by semicolons, of the form `input = output`, and allow for:

a single value	<code>1 = 0</code>
a range of values	<code>2:5 = 1</code>
a set of values	<code>c(6, 7, 10) = 2</code>
else	everything that is not covered by the previously specified rules

Contrary to the `recode()` function in package **car**, this function allows the `:` sequence operator (even for factors), so that a rule such as `c(1, 3, 5:7)`, or `c(a, d, f:h)` would be valid.

Actually, since all rules are specified in a string, it really doesn't matter if the `c()` function is used or not. For compatibility reasons it accepts it, but a more simple way to specify a set of rules is `"1,3,5:7=A; else=B"`

Special values `lo` and `hi` may also appear in the range of values, while `else` can be used with `else=copy` to copy all values which were not specified in the recoding rules.

In the package **car**, a character output would have to be quoted, like `"1:2='A'"` but that is not mandatory in this function, `"1:2=A"` would do just as well. Output values such as `"NA"` or `"missing"` are converted to `NA`.

Another difference from the **car** package: the output is **not** automatically converted to a factor even if the original variable is a factor. That option is left to the user's decision to specify `as.factor.result`, defaulted to `FALSE`.

A capital difference is the treatment of the values not present in the recoding rules. By default, package **car** copies all those values in the new object, whereas in this package the default values are `NA` and new values are added only if they are found in the rules. Users can choose to copy all other values not present in the recoding rules, by specifically adding `else=copy` in the rules.

Since the two functions have the same name, it is possible that users loading both packages to use one instead of the other (depending which package is loaded first). In order to preserve functionality and minimize possible namespace collisions with package **car**, special efforts have been invested to ensure perfect compatibility with the other `recode()` function (plus more).

The argument `...` allows for more arguments specific to the **car** package, such as `as.factor.result`, `as.numeric.result`. In addition, it also accepts `levels`, `labels` and `ordered` specific to function `factor()` in package **base**. When using the arguments `levels` and / or `labels`, the output will automatically be coerced to a factor, unless the argument `values` is used, as indicated below.

Blank spaces outside category labels are ignored, see the last example.

It is possible to use `recode()` in a similar way to function `cut()`, by specifying a vector of cut points. For any number of such `c` cut points, there should be `c + 1` values. If not otherwise specified, the argument `values` is automatically constructed as a sequence of numbers from 1 to `c + 1`.

Unlike the function `cut()`, arguments such as `include.lowest` or `right` are not necessary because the final outcome can be changed by tweaking the cut values.

If both arguments `values` and `labels` are provided, the labels are going to be stored as an attribute.

## Author(s)

Adrian Dusa

## Examples

```
x <- rep(1:3, 3)
# [1] 1 2 3 1 2 3 1 2 3

recode(x, "1:2 = A; else = B")
# [1] "A" "A" "B" "A" "A" "B" "A" "A" "B"

recode(x, "1:2 = 0; else = copy")
# [1] 0 0 3 0 0 3 0 0 3

set.seed(1234)
x <- sample(18:90, 20, replace = TRUE)
# [1] 45 39 26 22 55 33 21 87 31 73 79 21 21 38 57 73 84 22 83 64
```

```

recode(x, cut = "35, 55")
# [1] 2 2 1 1 2 1 1 3 1 3 3 1 1 2 3 3 3 1 3 3

set.seed(1234)
x <- factor(sample(letters[1:10], 20, replace = TRUE),
            levels = letters[1:10])
# [1] j f e i e f d b g f j f d h d d e h d h
# Levels: a b c d e f g h i j

recode(x, "b:d = 1; g:hi = 2; else = NA") # note the "hi" special value
# [1] 2 NA NA 2 NA NA 1 1 2 NA 2 NA 1 2 1 1 NA 2 1 2

recode(x, "a, c:f = A; g:hi = B; else = C", labels = "A, B, C")
# [1] B A A B A A A C B A B A A B A A A B A B
# Levels: A B C

recode(x, "a, c:f = 1; g:hi = 2; else = 3",
       labels = c("one", "two", "three"), ordered = TRUE)
# [1] two one one two one one one three two one
# [11] two one one two one one one two one two
# Levels: one < two < three

set.seed(1234)
categories <- c("An", "example", "that has", "spaces")
x <- factor(sample(categories, 20, replace = TRUE),
            levels = categories, ordered = TRUE)
sort(x)
# [1] An An An example example example example
# [8] example example example example that has that has that has
# [15] spaces spaces spaces spaces spaces spaces
# Levels: An < example < that has < spaces

recode(sort(x), "An : that has = 1; spaces = 2")
# [1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2

# single quotes work, but are not necessary
recode(sort(x), "An : 'that has' = 1; spaces = 2")
# [1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2

# same using cut values
recode(sort(x), cut = "that has")
# [1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2

# modifying the output values
recode(sort(x), cut = "that has", values = 0:1)
# [1] 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 1 1 1 1 1

# more treatment of "else" values
x <- 10:20

# recoding rules don't overlap all existing values, the rest are empty
recode(x, "8:15 = 1")

```



```
# [1] 1 1 1 1 1 1 NA NA NA NA NA
# all other values copied
recode(x, "8:15 = 1; else = copy")
# [1] 1 1 1 1 1 1 16 17 18 19 20
```

---

recreate	<i>Facilitate expression substitution</i>
----------	---

---

## Description

Utility function based on `substitute()`, to recover an unquoted input.

## Usage

```
recreate(x, snames = NULL, ...)
```

## Arguments

<code>x</code>	A substituted input.
<code>snames</code>	A character string containing set names.
<code>...</code>	Other arguments, mainly for internal use.

## Details

This function is especially useful when users have to provide lots of quoted inputs, such as the name of the columns from a data frame to be considered for a particular function.

This is actually one of the main uses of the base function `substitute()`, but here it can be employed to also detect SOP (sum of products) expressions, explained for instance in function `translate()`.

Such SOP expressions are usually used in contexts of sufficiency and necessity, which are indicated with the usual signs `->` and `<-`. These are both allowed by the R parser, indicating standard assignment. Due to the R's internal parsing system, a sufficient expression using `->` is automatically flipped to a necessity statement `<-` with reversed LHS to RHS, but this function is able to determine what is the expression and what is the output.

The other necessity code `<=` is also recognized, but the equivalent sufficiency code `=>` is not allowed in unquoted expressions.

## Value

A quoted, equivalent expression or a substituted object.

## Author(s)

Adrian Dusa

**See Also**

[substitute](#), [simplify](#)

**Examples**

```
recreate(substitute(A + ~B*C))

foo <- function(x, ...) recreate(substitute(list(...)))

foo(arg1 = 3, arg2 = A + ~B*C)

df <- data.frame(A = 1, B = 2, C = 3, Y = 4)

# substitute from the global environment
# the result is the builtin C() function
res <- recreate(substitute(C))

is.function(res) # TRUE

# search first within the column name space from df
recreate(substitute(C), colnames(df))
# "C"

# necessity well recognized
recreate(substitute(A <- B))

# but sufficiency is flipped
recreate(substitute(A -> B))

# more complex SOP expressions are still recovered
recreate(substitute(A + ~B*C -> Y))
```

---

replaceText

*Replace text in a string*

---

**Description**

Provides an improved method to replace strings, compared to function `gsub()` in package **base**.

**Usage**

```
replaceText(
  expression = "", target = "", replacement = "", protect = "",
  boolean = FALSE, ...)
```

**Arguments**

expression	Character string, usually a SOP - sum of products expression.
target	Character vector or a string containing the text to be replaced.
replacement	Character vector or a string containing the text to replace with.
protect	Character vector or a string containing the text to protect.
boolean	Treat characters in a boolean way, using upper and lower case letters.
...	Other arguments, from and to other functions.

**Details**

If the input expression is "J\*JSR", and the task is to replace "J" with "A" and "JSR" with "B", function gsub() is not very useful since the letter "J" is found in multiple places, including the second target.

This function finds the exact location(s) of each target in the input string, starting with those having the largest number of characters, making sure the locations are unique. For instance, the target "JSR" is found on the location from 3 to 5, while the target "J" is found on two locations 1 and 3, but 3 was already identified in the previously found location for the larger target.

In addition, this function can also deal with target strings containing spaces.

**Value**

The original string, replacing the target text with its replacement.

**Author(s)**

Adrian Dusa

**Examples**

```
replaceText("J*JSR", "J, JSR", "A, B")

# same output, on input expressions containing spaces
replaceText("J*JS R", "J, JS R", "A, B")

# works even with Boolean expressions, where lower case
# letters signal the absence of the causal condition
replaceText("DEV + urb*LIT", "DEV, URB, LIT", "A, B, C", boolean = TRUE)
```

---

scan.clipboard	<i>Cross platform scan/write clipboard</i>
----------------	--

---

**Description**

Functions to read and write to the system's clipboard, for copy/paste operations.

**Usage**

```
scan.clipboard(...)  
write.clipboard(x)
```

**Arguments**

x	Object to be written to the clipboard
...	Same arguments that are used in the base function scan

**Author(s)**

Adrian Dusa

---

Tilde operations	<i>Tilde operations</i>
------------------	-------------------------

---

**Description**

Checks and changes expressions containing set negations using a tilde.

**Usage**

```
hastilde(x)  
notilde(x)  
tilde1st(x)
```

**Arguments**

x	A vector of values
---	--------------------

**Details**

Boolean expressions can be negated in various ways. For binary crisp and fuzzy sets, one of the most straightforward ways to invert the set membership scores is to subtract them from 1. This is both possible using R vectors and also often used to signal a negation in SOP (sum of products) expressions.

Some other times, SOP expressions can signal a set negation (also known as the absence of a causal condition) by using lower case letters, while upper case letters are used to signal the presence of a causal condition. SOP expressions also use a tilde to signal a set negation, immediately preceding the set name.

This set of functions detect when and if a set present in a SOP expression contains a tilde (function `hasTilde`), whether the entire expression begins with a tilde (function `tilde1st`).

**Author(s)**

Adrian Dusa

**Examples**

```
hasTilde("~A")
```

---

tryCatchWEM

*Try functions to capture warnings, errors and messages.*

---

**Description**

This function combines the base functions `tryCatch()` and `withCallingHandlers()` for the specific purpose of capturing not only errors and warnings but messages as well.

**Usage**

```
tryCatchWEM(expr, capture = FALSE)
```

**Arguments**

<code>expr</code>	Expression to be evaluated.
<code>capture</code>	Logical, capture the visible output.

**Details**

In some situations it might be important not only to test a function, but also to capture everything that is written in the R console, be it an error, a warning or simply a message.

For instance package **QCA** (version 3.4) has a Graphical User Interface that simulates an R console embedded into a web based **shiny** app.

It is not intended to replace function `tryCatch()` in any way, especially not evaluating an expression before returning or exiting, it simply captures everything that is printed on the console (the visible output).

**Value**

A list, if anything would be printed on the screen, or an empty (NULL) object otherwise.

**Author(s)**

Adrian Dusa

---

using                      *Evaluate an expression in a data environment*

---

**Description**

A function almost identical to the base function `with()`, but allowing to evaluate the expression in every subset of a split file.

**Usage**

```
using(data, expr, split.by = NULL, ...)
```

**Arguments**

<code>data</code>	A data frame.
<code>expr</code>	Expression to evaluate
<code>split.by</code>	A factor variable from the data, or a declared/labelled variable
<code>...</code>	Other internal arguments.

**Value**

A list of results, or a matrix if each separate result is a vector.

**Author(s)**

Adrian Dusa

**Examples**

```
set.seed(123)
DF <- data.frame(
  Area = factor(sample(c("Rural", "Urban"), 123, replace = TRUE)),
  Gender = factor(sample(c("Female", "Male"), 123, replace = TRUE)),
  Age = sample(18:90, 123, replace = TRUE),
  Children = sample(0:5, 123, replace = TRUE)
)

# table of frequencies for Gender
table(DF$Gender)
```

```
# same with
using(DF, table(Gender))

# same, but split by Area
using(DF, table(Gender), split.by = Area)

# calculate the mean age by gender
using(DF, mean(Age), split.by = Gender)

# same, but select cases from the urban area
using(subset(DF, Area == "Urban"), mean(Age), split.by = Gender)

# mean age by gender and area
using(DF, mean(Age), split.by = Area & Gender)

# same with
using(DF, mean(Age), split.by = c(Area, Gender))

# average number of children by Area
using(DF, mean(Children), split.by = Area)

# frequency tables by Area
using(DF, table(Children), split.by = Area)
```

# Index

## \* functions

.rda functions: listRDA, objRDA, 2  
betweenQuotes, 4  
Brackets, 4  
change, 6  
coerceMode, 7  
combnk, 8  
dimnames, 9  
export, 9  
factorize, 10  
frelevel, 13  
getName, 14  
inside, 16  
Interpret DNF/SOP expressions:  
    compute, simplify, expand,  
    translate, 17  
intersection, 21  
Negate DNF/SOP expressions, 23  
Number equality, 25  
numdec, 26  
Numeric testing and coercion, 27  
overwrite, 28  
permutations, 29  
recode, 30  
recreate, 33  
replaceText, 34  
scan.clipboard, 36  
Tilde operations, 36  
tryCatchWEM, 37  
using, 38

## \* misc

finvert, 12  
hclr, 15

## \* package

About the admisc package, 3  
.rda functions: listRDA, objRDA, 2

About the admisc package, 3  
admisc-package (About the admisc  
    package), 3

aeqb (Number equality), 25  
agtb (Number equality), 25  
agteb (Number equality), 25  
altb (Number equality), 25  
aldeb (Number equality), 25  
aneqb (Number equality), 25  
asNumeric (Numeric testing and  
    coercion), 27  
asSOP (Interpret DNF/SOP expressions:  
    compute, simplify, expand,  
    translate), 17  
attributes, 16  
  
betweenBrackets (Brackets), 4  
betweenQuotes, 4  
Brackets, 4  
  
calibrate, 17  
change, 6  
coerceMode, 7  
combnk, 8  
compute (Interpret DNF/SOP  
    expressions: compute,  
    simplify, expand, translate),  
    17  
curlyBrackets (Brackets), 4  
  
deMorgan (Negate DNF/SOP expressions),  
    23  
dimnames, 9  
double, 28  
  
expand (Interpret DNF/SOP expressions:  
    compute, simplify, expand,  
    translate), 17  
export, 9  
  
factor, 30, 31  
factorize, 10  
findInterval, 30  
finvert, 12



- frelevel, [13](#)
- getName, [14](#)
- hastilde (Tilde operations), [36](#)
- hclr, [15](#)
- inside, [16](#)
- insideBrackets (Brackets), [4](#)
- integer, [28](#)
- Interpret DNF/SOP expressions:
  - compute, simplify, expand, translate, [17](#)
- intersection, [21](#)
- invert (Negate DNF/SOP expressions), [23](#)
- list, [16](#)
- listRDA (.rda functions: listRDA, objRDA), [2](#)
- load, [3](#)
- logical, [16](#)
- minimize, [10](#), [11](#), [17](#), [24](#)
- modelFit, [22](#)
- mvSOP (Interpret DNF/SOP expressions:
  - compute, simplify, expand, translate), [17](#)
- names, [16](#)
- negate (Negate DNF/SOP expressions), [23](#)
- Negate DNF/SOP expressions, [23](#)
- notilde (Tilde operations), [36](#)
- Number equality, [25](#)
- numdec, [26](#)
- numeric, [28](#)
- Numeric testing and coercion, [27](#)
- objRDA (.rda functions: listRDA, objRDA), [2](#)
- outsideBrackets (Brackets), [4](#)
- overwrite, [28](#)
- permutations, [29](#)
- possibleNumeric (Numeric testing and coercion), [27](#)
- recode, [30](#)
- recreate, [33](#)
- relevel, [13](#)
- replaceText, [34](#)
- roundBrackets (Brackets), [4](#)
- save, [3](#)
- scan.clipboard, [36](#)
- setColnames (dimnames), [9](#)
- setDimnames (dimnames), [9](#)
- setRownames (dimnames), [9](#)
- simplify, [10](#), [24](#), [34](#)
- simplify (Interpret DNF/SOP expressions:
  - compute, simplify, expand, translate), [17](#)
- sop (Interpret DNF/SOP expressions:
  - compute, simplify, expand, translate), [17](#)
- squareBrackets (Brackets), [4](#)
- substitute, [33](#), [34](#)
- Tilde operations, [36](#)
- tilde1st (Tilde operations), [36](#)
- translate, [11](#), [33](#)
- translate (Interpret DNF/SOP expressions:
  - compute, simplify, expand, translate), [17](#)
- tryCatchWEM, [37](#)
- using, [38](#)
- wholeNumeric (Numeric testing and coercion), [27](#)
- write.clipboard (scan.clipboard), [36](#)
- write.table, [9](#), [10](#)