Package: baseline (via r-universe)

October 18, 2026

Encoding UTF-8

Type Package

Title Baseline Correction of Spectra

Version 1.3-8

Date 2026-09-18

Maintainer Kristian Hovde Liland <kristian.liland@nmbu.no>

Description Collection of baseline correction algorithms, along with a framework and a Tcl/Tk enabled GUI for optimising baseline algorithm parameters. Typical use of the package is for removing background effects from spectra originating from various types of spectroscopy and spectrometry, possibly optimizing this with regard to regression or classification results. Correction methods include polynomial fitting, weighted local smoothers and many more.

License GPL-2

Copyright inst/COPYRIGHTS

Depends R (>= 3.5.0)

Imports graphics, SparseM, grDevices, stats, methods

Suggests gWidgets2, gWidgets2tcltk, IDPmisc, lattice, pls, MASS, roxygen2

LazyLoad true

LazyData true

URL https://github.com/khliland/baseline/

BugReports https://github.com/khliland/baseline/issues/

ZipData true

NeedsCompilation yes

Config/roxygen2/version 8.1.0

Author Kristian Hovde Liland [aut, cre] (ORCID: <https://orcid.org/0000-0001-6468-9423>), Bjørn-Helge Mevik [aut], Roberto Canteri [ctb]

Repository https://cran.r-universe.dev

Date/Publication 2026-09-18 16:33:56 UTC

RemoteUrl https://github.com/cran/baseline

RemoteRef HEAD

RemoteSha 5eedc49b9d8173ff95b11e09c5f46c4916665b49

Contents

baseline-package . . . 3
algorithm . . . 4
baseline . . . 5
baseline.als . . . 6
baseline.fillPeaks . . . 8
baseline.irls . . . 9
baseline.lowpass . . . 10
baseline.medianWindow . . . 11
baseline.modpolyfit . . . 12
baseline.peakDetection . . . 13
baseline.rfbaseline . . . 14
baseline.rollingBall . . . 16
baseline.shirley . . . 17
baseline.TAP . . . 19
baselineAlg . . . 21
baselineAlgClass . . . 21
baselineAlgorithms . . . 23
baselineAlgorithmsGUI . . . 24
baselineAlgResult . . . 24
baselineAlgResultMethods . . . 25
baselineAlgTest . . . 26
baselineClass . . . 27
baselineEnv . . . 28
baselineGUI . . . 29
custom.baseline . . . 30
doOptim . . . 31
funcName . . . 33
getSpectra . . . 34
milk . . . 35
optimWizard . . . 36
overall.min . . . 37
param . . . 38
plotBaseline . . . 39
plotOptim . . . 40
PLSRTestClass . . . 41
predictionResult . . . 42
predictionResultMethods . . . 43
predictionTest . . . 43

qualMeas 44
ridgeRegressionTestClass 45
runTest 46
XPSdata 47

Index **49**

`baseline-package` *Baseline correction*

Description

A common framework with implementations of several baseline correction methods

Details

Package:	baseline
Type:	Package
License:	GPL-2

Use function baseline for baseline correction. This function takes matrices of spectra, a method name and parameters needed for the specific method. See helpfiles for details.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

Maintainer: Kristian Hovde Liland <kristian.liland@nmbu.no>

References

Andreas F. Ruckstuhl, Matthew P. Jacobson, Robert W. Field, James A. Dodd: Baseline subtraction using robust local regression estimation; CHAD A. LIEBER and ANITA MAHADEVAN-JANSEN: Automated Method for Subtraction of Fluorescence from Biological Raman Spectra; Mark S. Friedrichs: A model-free algorithm for the removal of baseline artifacts; AHMET K. ATAKAN, W. E. BLASS, and D. E. JENNINGS: Elimination of Baseline Variations from a Recorded Spectrum by Ultra-low Frequency Filtering; M.A. Kneen, H.J. Annegarn: Algorithm for fitting XRF, SEM and PIXE X-ray spectra backgrounds; K.H. Liland, B.-H. Mevik, E.-O. Rukke, T. Almøy, M. Skaugen and T. Isaksson (2009) Quantitative whole spectrum analysis with MALDI-TOF MS, Part I: Measurement optimisation. *Chemometrics and Intelligent Laboratory Systems*, **96**(2), 210–218.

See Also

Useful links:

- https://github.com/khliland/baseline/
- Report bugs at https://github.com/khliland/baseline/issues/

Examples

```
# Load data
data(milk)
# The baseline() function is an S4 wrapper for all the different
# baseline correction methods. The default correction method
# is IRLS. Data must be organized as row vectors in a matrix
# or data.frame.
bc.irls <- baseline(milk$spectra[1,, drop=FALSE])
## Not run:
  # Computationally heavy
 plot(bc.irls)

## End(Not run)

# Available extractors are:
# getBaseline(bc.irls)
# getSpectra(bc.irls)
# getCorrected(bc.irls)
# getCall(bc.irls)

# Correction methods and parameters can be specified through the wrapper.
bc.fillPeaks <- baseline(milk$spectra[1,, drop=FALSE], lambda=6,
 hwi=50, it=10, int=2000, method='fillPeaks')
## Not run:
  # Computationally heavy
 plot(bc.fillPeaks)

## End(Not run)

# If a suitable gWidgets2 implementation is installed, a
# graphical user interface is available for interactive
# parameter adaption.
## Not run:
  # Dependent on external software
  baselineGUI(milk$spectra)

## End(Not run)
```

`algorithm` *Extraction methods for "baselineAlgTest" objects*

Description

Extraction methods specifically for objects of class `baselineAlgTest`

Usage

```
algorithm(object)

extraArgs(object)
```

Arguments

object	Object of class baselineAlgTest

Value

The corresponding slot

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland.

See Also

baselineAlgTest

---

baseline *Baseline correction*

Description

Common framework for baseline correction

Usage

```
baseline(spectra, method = "irls", ...)
```

Arguments

spectra	Matrix with spectra in rows
method	Baseline correction method
...	Additional parameters, sent to the method

Details

Estimates baselines for the spectra, using the algorithm named in method.

Value

An object of class baseline.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

Kristian Hovde Liland, Trygve Almøy, Bjørn-Helge Mevik (2010), Optimal Choice of Baseline Correction for Multivariate Calibration of Spectra, Applied Spectroscopy 64, pp. 1007-1016.

See Also

The functions implementing the baseline algorithms: baseline.als, baseline.fillPeaks, baseline.irls, baseline.lowpass, baseline.medianWindow, baseline.modpolyfit, baseline.peakDetection, baseline.rfbaseline, baseline.rollingBall, baseline.shirley, baseline.TAP

Examples

```
# Load data
data(milk)
# The baseline() function is an S4 wrapper for all the different
# baseline correction methods. The default correction method
# is IRLS. Data must be organized as row vectors in a matrix
# or data.frame.
bc.irls <- baseline(milk$spectra[1,, drop=FALSE])
## Not run:
  # Computationally heavy
 plot(bc.irls)

## End(Not run)

# Available extractors are:
# getBaseline(bc.irls)
# getSpectra(bc.irls)
# getCorrected(bc.irls)
# getCall(bc.irls)

# Correction methods and parameters can be specified through the wrapper.
bc.fillPeaks <- baseline(milk$spectra[1,, drop=FALSE], lambda=6,
 hwi=50, it=10, int=2000, method='fillPeaks')
## Not run:
  # Computationally heavy
 plot(bc.fillPeaks)

## End(Not run)

# If a suitable gWidgets2 implementation is installed, a
# graphical user interface is available for interactive
# parameter adaption.
## Not run:
  # Dependent on external software
  baselineGUI(milk$spectra)

## End(Not run)
```

`baseline.als` *Asymmetric Least Squares*

Description

Baseline correction by 2nd derivative constrained weighted regression. Original algorithm proposed by Paul H. C. Eilers and Hans F.M. Boelens

Usage

```
baseline.als(spectra, lambda = 6, p = 0.05, maxit = 20)
```

Arguments

spectra	Matrix with spectra in rows
lambda	2nd derivative constraint
p	Weighting of positive residuals
maxit	Maximum number of iterations

Details

Iterative algorithm applying 2nd derivative constraints. Weights from previous iteration is p for positive residuals and 1-p for negative residuals.

Value

baseline	Matrix of baselines corresponding to spectra spectra
corrected	Matrix of baseline corrected spectra
wgts	Matrix of final regression weights

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

Paul H. C. Eilers and Hans F.M. Boelens: Baseline Correction with Asymmetric Least Squares Smoothing

Examples

```
data(milk)
bc.als <- baseline(milk$spectra[1,, drop=FALSE], lambda=10, method='als')
## Not run:
plot(bc.als)

## End(Not run)
```

`baseline.fillPeaks` *Fill peaks*

Description

An iterative algorithm using suppression of baseline by means in local windows

Usage

```
baseline.fillPeaks(spectra, lambda, hwi, it, int)
```

Arguments

`spectra`	Matrix with spectra in rows
`lambda`	2nd derivative penalty for primary smoothing
`hwi`	Half width of local windows
`it`	Number of iterations in suppression loop
`int`	Number of buckets to divide spectra into

Details

In local windows of buckets the minimum of the mean and the previous iteration is chosen as the new baseline

Value

`baseline`	Matrix of baselines corresponding to spectra `spectra`
`corrected`	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

Kristian Hovde Liland, 4S Peak Filling - baseline estimation by iterative mean suppression, MethodsX 2015

Examples

```
data(milk)
bc.fillPeaks <- baseline(milk$spectra[1,, drop=FALSE], lambda=6,
 hwi=50, it=10, int=2000, method='fillPeaks')
## Not run:
 plot(bc.fillPeaks)

## End(Not run)
```

baseline.irls *Iterative Restricted Least Squares*

Description

An algorithm with primary smoothing and repeated baseline suppressions and regressions with 2nd derivative constraint

Usage

```
baseline.irls(spectra, lambda1 = 5, lambda2 = 9, maxit = 200, wi = 0.05)
```

Arguments

spectra	Matrix with spectra in rows
lambda1	2nd derivative constraint for primary smoothing
lambda2	2nd derivative constraint for secondary smoothing
maxit	Maximum number of iterations
wi	Weighting of positive residuals

Value

baseline	Matrix of baselines corresponding to spectra spectra
corrected	Matrix of baseline corrected spectra
smoothed	Matrix of primary smoothed spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

Examples

```
data(milk)
bc.irls <- baseline(milk$spectra[1,, drop=FALSE], method='irls')
## Not run:
 plot(bc.irls)

## End(Not run)
```

`baseline.lowpass` *Low-pass FFT filter*

Description

An algorithm for removing baselines based on Fast Fourier Transform filtering

Usage

```
baseline.lowpass(spectra, steep = 2, half = 5)
```

Arguments

`spectra`	Matrix with spectra in rows
`steep`	Steepness of filter curve
`half`	Half-way point of filter curve

Details

Since the scale of the spectra will be different after filtering, baselines will not be returned by the algorithm

Value

`baseline`	Matrix of baselines corresponding to spectra `spectra`
`corrected`	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

AHMET K. ATAKAN, W. E. BLASS, and D. E. JENNINGS: Elimination of Baseline Variations from a Recorded Spectrum by Ultra-low Frequency Filtering

Examples

```
data(milk)
bc.lowpass <- baseline(milk$spectra[1,, drop=FALSE], method='lowpass')
## Not run:
 plot(bc.lowpass)

## End(Not run)
```

`baseline.medianWindow` *Median window*

Description

An implementation and extention of Mark S. Friedrichs' model-free algorithm

Usage

```
baseline.medianWindow(spectra, hwm, hws, end = FALSE)
```

Arguments

`spectra`	Matrix with spectra in rows
`hwm`	Window half width for local medians
`hws`	Window half width for local smoothing (optional)
`end`	Original endpoint handling (optional boolean)

Details

An algorithm finding medians in local windows and smoothing with gaussian weighting

Value

`baseline`	Matrix of baselines corresponding to spectra `spectra`
`corrected`	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

Mark S. Friedrichs: A model-free algorithm for the removal of baseline artifacts

Examples

```
data(milk)
bc.medianWindow <- baseline(milk$spectra[1,, drop=FALSE], hwm=300,
 method='medianWindow')
## Not run:
 plot(bc.medianWindow)

## End(Not run)
```

`baseline.modpolyfit` *Modified polynomial fitting*

Description

An implementation of CHAD A. LIEBER and ANITA MAHADEVAN-JANSENs algorithm for polynomial fiting

Usage

```
baseline.modpolyfit(spectra, t, degree = 4, tol = 0.001, rep = 100)
```

Arguments

`spectra`	Matrix with spectra in rows
`t`	Optional vector of spectrum abcissa
`degree`	Degree of polynomial
`tol`	Tolerance of difference between iterations
`rep`	Maximum number of iterations

Details

Polynomial fitting with baseline suppression relative to original spectrum

Value

`baseline`	Matrix of baselines corresponding to spectra `spectra`
`corrected`	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

CHAD A. LIEBER and ANITA MAHADEVAN-JANSEN: Automated Method for Subtraction of Fluorescence from Biological Raman Spectra

Examples

```
data(milk)
bc.modpolyfit <- baseline(milk$spectra[1,, drop=FALSE], method='modpolyfit', deg=6)
## Not run:
 plot(bc.modpolyfit)

## End(Not run)
```

`baseline.peakDetection` *Simultaneous Peak Detection and Baseline Correction*

Description

A translation from Kevin R. Coombes et al.'s MATLAB code for detecting peaks and removing baselines

Usage

```
baseline.peakDetection(
  spectra,
  left,
  right,
  lwin,
  rwin,
  snminimum,
  mono = 0,
  multiplier = 5,
  left.right,
  lwin.rwin
)
```

Arguments

`spectra`	Matrix with spectra in rows
`left`	Smallest window size for peak widths
`right`	Largest window size for peak widths
`lwin`	Smallest window size for minimums and medians in peak removed spectra
`rwin`	Largest window size for minimums and medians in peak removed spectra
`snminimum`	Minimum signal to noise ratio for accepting peaks
`mono`	Monotonically decreasing baseline if `mono`>0
`multiplier`	Internal window size multiplier
`left.right`	Sets eflt and right to value of `left.right`
`lwin.rwin`	Sets lwin and rwin to value of `lwin.rwin`

Details

Peak detection is done in several steps sorting out real peaks through different criteria. Peaks are removed from spectra and minimums and medians are used to smooth the remaining parts of the spectra. If `snminimum` is omitted, y3, midspec, y and y2 are not returned (faster)

Value

baseline	Matrix of baselines corresponding to spectra spectra
corrected	Matrix of baseline corrected spectra
peaks	Final list of selected peaks
sn	List signal to noise ratios for peaks
y3	List of peaks prior to singal to noise selection
midspec	Mid-way baseline estimation
y	First estimate of peaks
y2	Second estimate of peaks

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

KEVIN R. COOMBES et al.: Quality control and peak finding for proteomics data collected from nipple aspirate fluid by surface-enhanced laser desorption and ionization.

Examples

```
data(milk)
bc.peakDetection <- baseline(milk$spectra[1,, drop=FALSE], method='peakDetection',
                             left=300, right=300, lwin=50, rwin=50)


  # To obtain the peak list, specify S/N threshold and call the baseline function directly:
  bc.peakDetection2 <- baseline.peakDetection(milk$spectra[1,, drop=FALSE],
                             left=300, right=300, lwin=50, rwin=50, snminimum = 5)


## Not run:
 plot(bc.peakDetection)

## End(Not run)
```

---

baseline.rfbaseline *Robust Baseline Estimation*

Description

Wrapper for Andreas F. Ruckstuhl, Matthew P. Jacobson, Robert W. Field, James A. Dodd's algorithm based on LOWESS and weighted regression

Usage

```
baseline.rfbaseline(
  spectra,
  span = 2/3,
  NoXP = NULL,
  maxit = c(2, 2),
  b = 3.5,
  weight = NULL,
  Scale = function(r) median(abs(r))/0.6745,
  delta = NULL,
  SORT = FALSE,
  DOT = FALSE,
  init = NULL
)
```

Arguments

spectra	Matrix with spectra in rows
span	Amount of smoothing (by fraction of points)
NoXP	Amount of smoothing (by number of points)
maxit	Maximum number of iterations in robust fit
b	Tuning constant in the biweight function
weight	Optional weights to be given to individual observations
Scale	S function specifying how to calculate the scale of the residuals
delta	Nonnegative parameter which may be used to save computation. (See rfbaseline
SORT	Boolean variable indicating whether x data must be sorted.
DOT	Disregard outliers totally (boolean)
init	Values of initial fit

Details

Most of the code is the original code as given by the authors. The ability to sort by X-values has been removed and ability to handle multiple spectra has been added

Value

baseline	Matrix of baselines corresponding to spectra spectra
corrected	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

Andreas F. Ruckstuhl, Matthew P. Jacobson, Robert W. Field, James A. Dodd: Baseline subtraction using robust local regression estimation

Examples

```
data(milk)
bc.rbe <- baseline(milk$spectra[1,, drop=FALSE], method='rfbaseline',
  span=NULL, NoXP=1000)
## Not run:
 plot(bc.rbe)

## End(Not run)
```

`baseline.rollingBall` *Rolling ball*

Description

Ideas from Rolling Ball algorithm for X-ray spectra by M.A.Kneen and H.J. Annegarn. Variable window width has been left out

Usage

```
baseline.rollingBall(spectra, wm, ws)
```

Arguments

`spectra`	Matrix with spectra in rows
`wm`	Width of local window for minimization/maximization
`ws`	Width of local window for smoothing

Value

`baseline`	Matrix of baselines corresponding to spectra `spectra`
`corrected`	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

M.A. Kneen, H.J. Annegarn: Algorithm for fitting XRF, SEM and PIXE X-ray spectra backgrounds

Examples

```
data(milk)
bc.rollingBall <- baseline(milk$spectra[1,, drop=FALSE], wm=200, ws=200,
 method='rollingBall')
## Not run:
 plot(bc.rollingBall)

## End(Not run)
```

`baseline.shirley` *Shirley Background Estimation*

Description

Shirley Background correction for X-ray Photoelectron Spectroscopy.

Usage

```
baseline.shirley(spectra, t = NULL, limits = NULL, maxit = 50, err = 1e-06)
```

Arguments

`spectra`	matrix with only 1 y-coordinates by rows (i.e.: y = spectra[1,])
`t`	Optional vector of spectrum abscissa
`limits`	list with the y coordinates between calculation of background. Ususally these are the extreme point of the data range.
`maxit`	max number of iteration
`err`	Tolerance of difference between iterations

Details

The shape of the spectrum background or baseline is affected by inelastic energy loss processes, secondary electrons and nearby peaks. A reasonable approximation is essential for a qualitative and quantitative analysis of XPS data especially if several components interfere in one spectrum. The choice of an adequate background model is determined by the physical and chemical conditions of the measurements and the significance of the background to the information to be obtained. The subtraction of the baseline before entering the fit iterations or the calculation of the peak area can be an acceptable approximation for simple analytical problems. In order to obtain chemical and physical parameters in detail, however, it is absolutely necessary to include the background function in the iterative peak fit procedure. The primary function F(E) results from the experimentally obtained function M(E) and the background function U(E) as

$$F(E) = M(E) - U(E)$$

The kinetic energy E of the spectra can be described as

$$E = SE + SW * (i - 1)$$

SE means the start energy in eV, SW is the step width in eV and i the channel number. i can assume values between 1 and N with N as the number of data points.

In case of baseline calculation before initiating the fit procedure, the background is set to the averaged experimental function M(E) in a sector around the chosen start and end channels. With i_1 as left channel (E_1: low energy side) and i_2 as right channel (E_2: high energy side) the simulation of the baseline is obtained as

$$U(E_1) = M(E_1)$$

and

$$U(E_2) = M(E_2)$$

If ZAP is the number of points used for averaging (can be set in the preferences), the intensity of the averaged measuring function at the low energy side is calculated by

$$M(i_1) = \frac{\sum_{i=0}^{ZAP-1} M(i_1 + i)}{ZAP}$$

and at the high energy side by

$$M(i_2) = \frac{\sum_{i=0}^{ZAP-1} M(i_2 + i)}{ZAP}$$

In many cases the Shirley model turned out to be a successful approximation for the inelastic background of core level peaks of buried species, which suffered significantly from inelastic losses of the emitted photoelectrons. The calculation of the baseline is an iterative procedure. The number of iteration cycles should be chosen high enough so that the shape of the obtained background function does not change anymore. The analytical expression for the Shirley background is

$$U(E) = \int_E^\infty F(E')dE' + c$$

The algorithm of Proctor and Sherwood ([1] A. Proctor, P.M.A. Sherwood, Anal. Chem. 54 (1982) 13) is based on the assumption that for every point of the spectrum the background intensity generated by a photoelectron line is proportional to the number of all photoelectrons with higher kinetic energy. The intensity of the background U(i) in channel i is given by

$$U(i) = \frac{(a-b)Q(i)}{P(i) + Q(i)} + b$$

where a and b are the measured intensities in channel i_1 and i_2, respectively, and P(i) and Q(i) represent the effective peak areas to lower and higher kinetic energies relative to the channel under consideration. An iterative procedure is necessary because P, Q, and U(i) are unknown. In first approximation U(i) = b is used.

The function `baseline.shirley` implements the `shirley` `baseline`. It is an iterative algorithm. The iteration stops when the deviation between two consequent iteration is lower than `err` or when the max number of iterations `maxit` is reached.

Value

The baseline function return an object of class `baseline`.

References

A. Proctor, P.M.A. Sherwood, Anal. Chem. 54 (1982) 13.

See Also

baseline

Examples

```
data("O1s")
Data <- O1s

## The same example with C1s data
# data("C1s")
# Data <- C1s

Y <- Data[2,, drop = FALSE]
X <- Data[1,]

corrected <- baseline(Y, method = "shirley", t = X)
plot(corrected, rev.x = TRUE, labels = X)

## Not run:
# Dependent on external software
baselineGUI(Y, labels=X, method="shirley")

## End(Not run)
```

`baseline.TAP` *TAP*

Description

An implementation of Roman Svoboda and Jirí Málek's algorithm for baseline identification in kinetic anlaysis of derivative kinetic data.

Usage

```
baseline.TAP(spectra, t = NULL, interval = 15, tol = 0.001)
```

Arguments

`spectra`	Matrix with spectra in rows
`t`	Optional vector of spectrum abcissa
`interval`	Distance from spectrum end to starting points for the TAP (default = 15)
`tol`	Tolerance of difference between iterations (default = 0.001)

Details

(i) A first approximation of the baseline equation is selected as the straight line between start and end of the curve. (ii) Based on the first approximation of the baseline equation, the phase change progress parameter is calculated. (iii) An updated equation of the baseline is calculated and the phase change progress parameter equation from step (ii). (iv) The baseline equation from step (iii) is compared (point by point) with the one from the previous iteration. If the convergence criterion is met (the difference between every baseline value corresponding to two successive iterations was less than 0.1%) the procedure is stopped and the final baseline equation is selected. If the convergence criterion is not fulfilled then a new iteration is carried out from step (ii) until convergence was achieved.

Value

`baseline`	Matrix of baselines corresponding to spectra `spectra`
`corrected`	Matrix of baseline corrected spectra

Author(s)

Kristian Hovde Liland

References

Roman Svoboda and Jirí Málek: Importance of proper baseline identification for the subsequent kinetic analysis of derivative kinetic data, Journal of Thermal Analysis and Calorimetry.

Examples

```
# My T
myT <- 40:170

# My artifical curve
myAlpha <- c(seq(0.01, 0.02, length.out=40),
             dnorm(seq(-3,3,length.out=51))/2+(0:50)/2000+0.02)
myAlpha <- c(myAlpha,
             seq(myAlpha[90]-0.001, 0.01, length.out=40))
myAlpha <- myAlpha - min(myAlpha)
myAlpha <- cumsum(dadt <- myAlpha/sum(myAlpha))

# Discrete derivative
mydAlpha <- c(0,diff(myAlpha)); mydAlpha <- matrix(mydAlpha, ncol=length(mydAlpha))
rm(myAlpha) # Throw away myAlpha

# Compute baseline from T and derivative
B <- baseline(mydAlpha, t=myT, method="TAP")

# Plot
plot(B, xlab = "T", ylab = "da/dT")
```

baselineAlg *Extraction methods for "baselineAlg" objects*

Description

Extraction methods specifically for objects of class baselineAlg

Usage

```
name(object)

description(object)
```

Arguments

object	Object of class baselineAlg

Value

The methods return the corresponding slot of the object.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

baselineAlg, funcName.

baselineAlgClass *Class "baselineAlg"*

Description

A class that describes a baseline correction algorithm. The idea is that it contains all information needed to use an algorithm with the optimisation framework and the graphical user interface (but see Notes below).

Slots

`name` Short-name of the algorithm. This must match the name of the object in the `baselineAlgorithms` list of algorithms, and is used throughout the code to identify the algorithm. It should thus start with a letter and contain only letters, digits, underscores ("_") or dots (".").

`description` Description of the algorithm, typically the full name. This will be used in the code to describe the algorith, so it should not be too long, and not contain newline characters.

`funcName` The name of the function used to estimate the baseline. The function must take an argument `spectra`, and return a list with the estimated baselines (`baseline`) original spectra (`spectra`) and the corrected spectra (`corrected`). It can also take other arguments (typically parameters) and return additional components in the list.

`param` A data frame with information about the parameters of the algorithm. It should contain the following coloumns: `name` - the name of the parameter; `integer` - `TRUE` if the parameter only takes integer values, otherwise `FALSE`; `min` - the lower limit of allowed values; `incl.min` - `TRUE` if the lower limit is an allowed value, otherwise `FALSE`; `default` - the default value; `max` - the upper limit of allowed values; `incl.max` - `TRUE` if the upper limit is an allowed value, otherwise `FALSE`

Methods

description `signature(object = "baselineAlg")`: Extract the `description` slot

funcName `signature(object = "baselineAlg")`: Extract the `funcName` slot

name `signature(object = "baselineAlg")`: Extract the `name` slot

param `signature(object = "baselineAlg")`: Extract the `param` slot

Objects from the Class

Objects can be created by calls of the form `new("baselineAlg", ...)`.

Note

The goal is that the optimisation framework and the GUI code should get all information about available baseline algorithms through a list of `baselineAlg` objects. This will make it relatively simple to add new baseline algorithms.

Currenly, there is information about the algorithms spread around in the code. We plan to move that information into the `baselineAlg` objects, and expand the class accordingly.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

Examples

```
showClass("baselineAlg")
```

`baselineAlgorithms` *List of available baseline algorithms*

Description

A list with descriptions of all baseline algorithms available through the optimisaiont framework and graphical user interface. The elements of the list are `baselineAlg` objects. The list is used by the code to extract names and information about the baseline algorithms.

Usage

```
baselineAlgorithms
```

Details

The list is not meant for usage by end-users, but is extendable and customizable, allowing for extra algorithms or removal of algoritms.

The names of the list must match the `name` slot of the elements.

Examples

```
## Get a list of all algorithms:
names(baselineAlgorithms)
## Show the descriptions
sapply(baselineAlgorithms, description)
## Add new algorithm
baseline.my.alg <- function(spectra, kappa=1, gamma=1){
   baseline  <- spectra-kappa+gamma
   corrected <- spectra-baseline
   list(baseline=baseline,corrected=corrected)
}

baselineAlgorithms$my.alg = new("baselineAlg",
     name = "my.alg",
     description = "A new baseline correction algorithm",
     funcName = "baseline.my.alg",
     param = data.frame(
        name = c("kappa","gamma"), # maxit
        integer = c(FALSE, FALSE),
        min = c(0, 0),
        incl.min = c(TRUE, TRUE),
        default = c(1, 1),
        max = c(Inf, 1),
        incl.max = c(FALSE, TRUE)
    ))
```

baselineAlgorithmsGUI *List of available baseline algorithms for GUI function*

Description

A list with data.frames containing parameters, minimum and maximum values for GUIs, step lengths for sliders, default values and currently selected values, plus a short description of each parameter. The list is used by the GUIs, and is user customizable.

Usage

```
baselineAlgorithmsGUI
```

Details

The list is not meant for usage by end-users, but is extendable and customizable, allowing for extra algorithms, removal of algoritms or changing of parameter sets.

Examples

```
## Get a list of all algorithms:
names(baselineAlgorithmsGUI)
## Add new algorithm:
baselineAlgorithmsGUI$my.alg <- as.data.frame(matrix(c(0,20,1,1, 0,20,1,1), 2,4, byrow=TRUE))
dimnames(baselineAlgorithmsGUI$my.alg) <- list(par=c("kappa", "gamma"),
 val=c("min","max","step","default"))
baselineAlgorithmsGUI$my.alg$current <- c(1,1)
baselineAlgorithmsGUI$my.alg$name <- c("Subtractive constand", "Additive constant")
```

baselineAlgResult *Class "baselineAlgResult"*

Description

A class describing the result of a baseline algorithm test

Slots

`param` A named list with the parameter values that were tested. This includes both the predictor parameters and the baseline algorithm parameters. All combinations of values are tested.

`qualMeas` A matrix of quality measure values for the different combinations of parameter values. Each row corresponds to one prediction parameter value, and each coloumn to one combination of baseline parameters.

`qualMeas.ind.min` The index in `qualMeas` of the minimum quality measure value

`minQualMeas` The minimum quality measure value

`param.ind.min` A vector of indices into the elemets of `param` of the parameter values corresponding to the minimum quality measure value

`param.min` A list of the parameter values corresponding to the minimum quality measure value

`qualMeasName` The name of the quality measure

Objects from the Class

Objects are typically created by running `runTest` on a `baselineAlgTest` object.

Methods

minQualMeas `signature(object = "baselineAlgResult")`: Extract the `minQualMeas` slot

param `signature(object = "baselineAlgResult")`: Extract the `param` slot

param.ind.min `signature(object = "baselineAlgResult")`: Extract the `param.ind.min` slot

param.min `signature(object = "baselineAlgResult")`: Extract the `param.min` slot

qualMeas `signature(object = "baselineAlgResult")`: Extract the `qualMeas` slot

qualMeas.ind.min `signature(object = "baselineAlgResult")`: Extract the `qualMeas.ind.min` slot

qualMeasName `signature(object = "baselineAlgResult")`: Extract the `qualMeasName` slot

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

Class `baselineAlgTest`, function `runTest`.

Examples

```
showClass("baselineAlgResult")
```

---

baselineAlgResultMethods

Extraction methods for "baselineAlgResult" objects

Description

Extraction methods that are specific for objects of class `baselineAlgResult`

Usage

```
qualMeas.ind.min(object)

param.ind.min(object)
```

Arguments

`object`	Object of class `baselineAlgResult`

Value

The corresponding slot

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

Class `baselineAlgResult`

`baselineAlgTest` *Class "baselineAlgTest"*

Description

A class that describes a baseline algorithm test. The test is performed with the function `runTest`.

Slots

`algorithm` A `"baselineAlg"` object. The baseline algorithm to test.

`param` A named list with parameter values to test. All combinations of parameters are tested.

`extraArgs` A named list of extra parameters to the baseline algorithm. These will be held fixed during the testing.

Objects from the Class

Objects can be created by calls of the form `new("baselineAlgTest", ...)`.

Methods

algorithm `signature(object = "baselineAlgTest")`: Extract the `algorithm` slot

extraArgs `signature(object = "baselineAlgTest")`: Extract the `extraArgs` slot ...

funcName `signature(object = "baselineAlgTest")`: Extract the `funcName` slot ...

param `signature(object = "baselineAlgTest")`: Extract the `param` slot

runTest `signature(object = "baselineAlgTest")`: Run the test.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

Classes baselineAlg, baselineAlgResult. Function runTest.

Examples

```
showClass("baselineAlgTest")
```

---

baselineClass *Class "baseline"*

Description

Stores the result of estimating baselines for one or more spectra.

Slots

baseline A matrix with the estimated baselines

corrected A matrix with the corrected spectra

spectra A matrix with the original spectra

call The call to baseline

Objects from the Class

The normal way to create objects is with the function baseline. Several baseline algorithms are available. See baseline for details. There is a plot method for the class; see plot,baseline-method.

Methods

getBaseline signature(object = "baseline"): Extract the estimated baselines

getCall signature(object = "baseline"): Extract the call to baseline used to create the object

getCorrected signature(object = "baseline"): Extract the corrected spectra

getSpectra signature(object = "baseline"): Extract the original spectra

Warning

In a future versoion, one of the slots might be removed from the class definition and calculated on the fly instead, in order to save space. Therefore, *do* use the extractor functions (getSpectra, getBaseline and getCorrected) instead of accessing the slots directly.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

baseline, getBaseline, getSpectra, getCorrected, getCall

Examples

```
showClass("baseline")
```

`baselineEnv` *Baseline environment*

Description

Methods to access the baseline environment.

Usage

```
baselineEnv()

putBaselineEnv(x, value)

getBaselineEnv(x, mode = "any")
```

Arguments

`x`	Name of object to put/get.
`value`	Object to put.
`mode`	Mode of object to get.

Value

`getBaseline` retrieves an object.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

See Also

The functions implementing the baseline algorithms: `baseline.als`, `baseline.fillPeaks`, `baseline.irls`, `baseline.lowpass`, `baseline.medianWindow`, `baseline.modpolyfit`, `baseline.peakDetection`, `baseline.rfbaseline`, `baseline.rollingBall`

Examples

```
putBaselineEnv('fish', '<==x-<')
getBaselineEnv('fish')
```

baselineGUI *Interactive plotting tool*

Description

An interactive plotting tool for dynamic visualization of baselines and their effect using the gWidgets2 package with GTK+ or Tcl/Tk.

Usage

```
baselineGUI(spectra, method = "irls", labels, rev.x = FALSE)
```

Arguments

spectra	Matrix with spectra in rows
method	Baseline correction method (optional)
labels	Labels for X-axis (optional)
rev.x	Reverse X-axis (optional, default=FALSE)

Details

Creates and updates a list containing current baseline and spectrum (baseline.result). Make sure a gWidget2 implementation is available, e.g gWidgets2RGtk2 or gWidgets2tcltk and a corresponding backend like GTK+ or Tcl/Tk. The GUI was developed using GTK which is an external dependency in Windows ans OS X.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

Examples

```
data(milk)
## Not run:
# Dependent on external software
baselineGUI(milk$spectra)

## End(Not run)
```

`custom.baseline` *Customized baseline correction*

Description

This function rescales spectrum abscissa by use of `breaks` and `gaps` before baseline correction. The effect is that the chosen baseline correction algorithm and paramters will have varying effects along the spectra, effectively giving local control of the amount of rigidity/flexibility of the estimated baseline.

Usage

```
custom.baseline(
  spectra,
  breaks,
  gaps,
  trans.win = NULL,
  just.plot = FALSE,
  method,
  ...
)
```

Arguments

`spectra`	Matrix with spectra in rows.
`breaks`	Vector of locations of break points between sections of varying baseline flexibility (given as abscissa numbers).
`gaps`	Vector giving the abscissa spacing between each instance of `breaks` (and endpoints if not specified in `breaks`).
`trans.win`	Optional width of transition window around break points used for smoothing rough breaks by LOWESS (default = NULL).
`just.plot`	Plot the rescaled spectra instead of applying the customized baseline correction if `just.plot`=TRUE (default = FALSE).
`method`	Baseline correction method to use (class character).
`...`	Additional named arguments to be passed to the baseline correction method.

Details

This is an implementation of the customized baseline correction suggested by Liland et al. 2011 for local changes in baseline flexibility.

Value

`baseline`	Estimated custom baselines.
`corrected`	Spectra corrected by custom baselines.

`spectra.scaled` Re-scaled spectra.

`baseline.scaled`
Estimated baselines of re-scaled spectra.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

References

Kristian Hovde Liland et al.: Customized baseline correction

Examples

```
data(milk)
spectrum1  <- milk$spectra[1,1:10000,drop=FALSE]
ordinary   <- baseline(spectrum1, method="als", lambda=6, p=0.01)
customized <- custom.baseline(spectrum1, 2900, c(1,20), trans.win=100,
 just.plot=FALSE, method="als", lambda=6, p=0.01)
## Not run:
plot(1:10000,spectrum1, type='l')
lines(1:10000,getBaseline(ordinary), lty=2, col=2, lwd=2)
lines(1:10000,customized$baseline, lty=3, col=3, lwd=2)

## End(Not run)
```

`doOptim` *Optimise several baseline algorithms on a data set*

Description

Tests several baseline algorithms with one predictor for a given data set. The baseline algorithms are represented as a list of `baselineAlgTest` objects, and the predictor as a `predictionTest` object.

Usage

```
doOptim(
  baselineTests,
  X,
  y,
  predictionTest,
  postproc = NULL,
  tmpfile = "tmp.baseline",
  verbose = FALSE,
  cleanTmp = FALSE
)

mvrValstats(
```

```
  object,
  estimate,
  newdata,
  ncomp = 1:object$ncomp,
  comps,
  intercept = cumulative,
  se = FALSE,
  ...
)
```

Arguments

baselineTests	a list of baselineAlgTest objects. The baseline algorithms and parameter values to test
X	A matrix. The spectra to use in the test
y	A vector or matrix. The response(s) to use in the test
predictionTest	A predictionTest object. The predictor and parameter values to use in the test
postproc	A function, used to postprocess the baseline corrected spectra prior to prediction testing. The function should take a matrix of spectra as its only argument, and return a matrix of postprocessed spectra
tmpfile	The basename of the files used to store intermediate calculations for checkpointing. Defaults to "tmp.baseline"
verbose	Logical, specifying whether the test should print out progress information. Default is FALSE
cleanTmp	Logical, specifying whether the intermediate files should be deleted when the optimisation has finished. Default is FALSE
object	An mvr object, as returned by pls::plsr. Internal helper used by doOptim; not meant to be called directly.
estimate	Character vector of estimate types, passed on from pls::MSEP.
newdata	Optional new data used to calculate the validation statistics.
ncomp	Vector of the number of components to calculate statistics for.
comps	Alternative to ncomp, a vector of specific components to use.
intercept	Logical, whether statistics for the intercept-only model should be included.
se	Logical, whether to calculate standard errors.
...	Other arguments, currently unused by mvrValstats.

Details

The function loops through the baseline algorithm tests in baselineTests, testing each of them with the given data and prediction test, and collects the results. The results of each baseline algorithm test is saved in a temporary file so that if the optimisation is interrupted, it can be re-run and will use the pre-calculated results. If cleanTmp is TRUE, the temporary files are deleted when the whole optimisation has finished.

Value

A list with components

baselineTests	The baselineTests argument
results	A list with the baselineAlgResult objects for each baseline test
minQualMeas	The minimum quality measure value
baselineAlg.min	The name of the baseline algorithm giving the minimum quality measure value
param.min	A list with the parameter values corresponding to the minimum quality measure value

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

baselineAlgTest,predictionTest

Examples

```
if (requireNamespace("pls", quietly = TRUE)) {
data(milk)
X <- milk$spectra[,-1]
y <- milk$spectra[,1]
opt <- doOptim(
    list(ALS = new("baselineAlgTest",
                   algorithm = baselineAlgorithms$als,
                   param=list(lambda=6:7,p=0.5))),
    X, y,
    new("PLSRTest",
        ncomp = 10,
        cvsegments = pls::cvsegments(N=45, k=5)),
    cleanTmp = TRUE)
}
```

---

funcName *Extract the "funcName" slot.*

Description

Extract the funcName slot from an object of class baselineAlg or baselineAlgTest

Usage

```
funcName(object)
```

Arguments

object	An object of class baselineAlg or baselineAlgTest

Value

The funcName slot of the object.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

baselineAlg, baselineAlgTest

---

getSpectra *Functions to extract the components of a "baseline" object*

Description

The functions extract the baseline, spectra, corrected or call slot of a baseline object; usually the result of a call to baseline.

Usage

```
getSpectra(object)

getCorrected(object)

getBaseline(object)

getCall(object)
```

Arguments

object	A baseline object

Value

getCall returns the baseline call used to create the object. The other functions return a matrix with the original spectra, estimated baselines or corrected spectra.

Warning

In a future versoion, one of the slots might be removed from the class definition and calculated on the fly instead, in order to save space. Therefore, *do* use the extractor functions (getSpectra, getBaseline and getCorrected) instead of accessing the slots directly.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

The function `baseline`, the class `baseline`

Examples

```
data(milk)
bl <- baseline(milk$spectra[1:2,])
baseline  <- getBaseline(bl)
spectra   <- getSpectra(bl)
corrected <- getCorrected(bl)
call      <- getCall(bl)
```

`milk` *MALDI-TOF mass spectra*

Description

Matrix of 45 spectra of 21451 m/z values from MALDI-TOF on mixed milk samples.

Usage

```
data(milk)
```

Format

A data frame with 45 observations on the following 2 variables.

`cow` a numeric vector

`spectra` a matrix with 21451 columns

Details

`cow` is the concentration of cow milk in mixed samples of cow, goat, and ewe milk.

References

Kristian Hovde Liland, Bjørn-Helge Mevik, Elling-Olav Rukke, Trygve Almøy, Morten Skaugen and Tomas Isaksson (2009) Quantitative whole spectrum analysis with MALDI-TOF MS, Part I: Measurement optimisation. *Chemometrics and Intelligent Laboratory Systems*, **96**(2), 210–218.

Examples

```
data(milk)
## Not run:
plot(milk$spectra[1,], type = "l")

## End(Not run)
```

---

optimWizard *Visual tool for setting up optimization*

Description

Set up optimization through a graphical user interface. Optionally collecting values directly from 'baselineGUI'. Retrieve optimisation parameters and results with `getOptim` and `getOptimRes`, respectively.

Usage

```
optimWizard(X, y, postproc, predictionTest, cvsegments)

getOptim()

getOptimRes()
```

Arguments

`X`	Matrix with spectra in rows
`y`	Response vector or matrix in analysis
`postproc`	Custum function for post processing of spectra (optional)
`predictionTest`	Custom prediction object (optional)
`cvsegments`	Cross-validation segments (optional)

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

Examples

```
## Not run:
# Computationally intensive
data(milk)
X <- milk$spectra[,-1]
y <- milk$spectra[,1]
optimWizard(X,y)

# Retrieve optimisation
myResults <- getOptimRes()
```

```
# After optimisation is complete
plotOptim(myResults)

## End(Not run)
```

`overall.min` *Extract the minimum from a baseline optimisation*

Description

Takes the result of an optimisation (a call to `doOptim`) and extracts the minimum quality measure value along with the parameters giving rise to the value.

Usage

```
overall.min(results)
```

Arguments

`results`	Result of call to `doOptim`

Value

A list with components

`qualMeas`	The minimum quality measure value
`algorithm`	The name of the baseline algorithm corresponding to the minimum
`param`	A list with the parameter values corresponding to the minimum quality measure value

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

`doOptim`

param *Extract the "param" slot*

Description

Extracts the param slot of the object.

Usage

```
param(object)

## S4 method for signature 'predictionResult'
param(object)

## S4 method for signature 'baselineAlg'
param(object)

## S4 method for signature 'baselineAlgTest'
param(object)

## S4 method for signature 'baselineAlgResult'
param(object)
```

Arguments

object	An object of class baselineAlg, baselineAlgTest, baselineAlgResult or predictionResult.

Value

The param slot of the object. Usually a data frame, list or numeric.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

Classes baselineAlg, baselineAlgTest, baselineAlgResult, predictionResult

plotBaseline *Plot method for "baseline" objects*

Description

Plot the original spectrum, the estimated baseline, and the corrected spectrum. Optionally zoom and pan plot, either with arguments or interactively.

Usage

```
plotBaseline(
  x,
  y,
  specNo = 1,
  grid = FALSE,
  labels = 1:n,
  rev.x = FALSE,
  zoom = list(xz = 1, yz = 1, xc = 0, yc = 0),
  ...
)

## S4 method for signature 'baseline'
plot(
  x,
  y,
  specNo = 1,
  grid = FALSE,
  labels = 1:n,
  rev.x = FALSE,
  zoom = NULL,
  ...
)
```

Arguments

x	The baseline object to be plotted
y	Unused. Ignored with a warning
specNo	The row number of the spectrum and baseline to plot. Defaults to 1
grid	Logical. Whether to show a grid or not. Defaults to FALSE
labels	Vector. Labels for the x tick marks. Defaults to 1:n
rev.x	Logical. Whether the spectrum should be reversed. Defaults to FALSE
zoom	Either TRUE (only for the plot method), which turns on the interactive zoom controls, or a list with components xz, xc, yz and yc, which specifies the desired zoom and pan. Defaults to no zoom or pan
...	Other arguments. Currently ignored

Details

The normal way to plot `baseline` objects is to use the `plot` method. The `plotBaseline` function is the underlying work-horse function, and is not meant for interactive use.

Note

Because the argument list of any plot method must start with `x`, `y`, and the plot method for the `baseline` class does not use the `y` argument, all arguments except `x` must be named explicitly. Positional matching will not work.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

See Also

`baseline`, `baseline`, `baselineGUI`

Examples

```
data(milk)
bl <- baseline(milk$spectra[1,, drop=FALSE])
## Not run:
  # Computationally intensive
  plot(bl)
  plot(bl, zoom = TRUE)
## End(Not run)
```

`plotOptim` *Plotting tool for result objects from optimization*

Description

A graphical user interface for plotting optimisation results, either one algorithm at the time or comparing algorithms.

Usage

```
plotOptim(results)
```

Arguments

`results`	Result list from optimization

Details

`plotOptim` creates a user interface based on the supplied results. Curve and level plots from single algorithms or comparison of algorithms is avilable.

For single algorithms subsets, levels corresponding to local or global minima, and averages can be extracted for plotting. For comparison of algorithms levels corresponding to local or global minima can be used, or levels corresponding to the minimum when averaging over selected values of the regression parameter, e.g. selected components in PLSR.

Author(s)

Kristian Hovde Liland and Bjørn-Helge Mevik

PLSRTestClass *Class "PLSRTest"*

Description

A class describing a PLSR prediction test. To run the test, the "pls" package must be installed.

Slots

`ncomp` Integer vector. The number of PLSR components to test.

`cvsegments` A list of the segments to use in the cross-validation.

Objects from the Class

Objects can be created by calls of the form `new("PLSRTest", ...)`.

Extends

Class `predictionTest`, directly.

Methods

`signature(object = "PLSRTest")`: Run the test

Author(s)

Bjørn-Helge Mevik and Krisitan Hovde Liland.

See Also

The base class `predictionTest`. The `runTest` function. The `plsr` function from the "pls" package.

Examples

```
showClass("PLSRTest")
```

predictionResult *Class "predictionResult"*

Description

A class containing the result of running a predictionTest.

Slots

param Numeric vector. The regression parameter values tested.

qualMeas Numeric vector. The quality measure values for each of the values of the param slot

ind.min The index (into qualMeas) of the minimum quality measure value.

minQualMeas The minimum quality measure value.

param.min The value of the parameter value corresponding to the minimum quality measure value.

qualMeasName The name of the quality measure.

paramName The name of the regression parameter.

Objects from the Class

The normal way to create objects is by calling the method runTest for any object of subclass of predictionTest.

Methods

ind.min: signature(object = "predictionResult"): Extract the ind.min slot minQualMeas: signature(object = "predictionResult"): Extract the minQualMeas slot param: signature(object = "predictionResult"): Extract the param slot param.min: signature(object = "predictionResult"): Extract the param.min slot paramName: signature(object = "predictionResult"): Extract the paramName slot qualMeas: signature(object = "predictionResult"): Extract the qualMeas slot qualMeasName: signature(object = "predictionResult"): Extract the qualMeasName slot

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

Function runTest, class predictionTest, subclasses PLSRTest and ridgeRegressionTest.

Examples

```
showClass("predictionResult")
```

predictionResultMethods *Extraction methods specific for "predictionResult" objects*

Description

Extract information from objects of class predictionResult.

Usage

```
ind.min(object)

paramName(object)
```

Arguments

object	Object of class predictionResult

Value

The corresponding slot of the object.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

predictionResult

predictionTest *Class "predictionTest"*

Description

A virtual class for all predictor test subclasses. Currently subclasses PLSRTest and ridgeRegressionTest are defined.

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

No methods defined with class "predictionTest" in the signature.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland.

See Also

Subclasses PLSRTest and ridgeRegressionTest.

---

qualMeas *Extraction functions for "predictionResult" or "baselineAlgResult" objects.*

Description

Extract slots from objects of class predictionResult or baselineAlgResult.

Usage

```
qualMeas(object, ...)

## S4 method for signature 'predictionResult'
qualMeas(object, ...)

minQualMeas(object)

param.min(object)

qualMeasName(object)

## S4 method for signature 'baselineAlgResult'
minQualMeas(object)

## S4 method for signature 'baselineAlgResult'
param.min(object)

## S4 method for signature 'baselineAlgResult'
qualMeasName(object)

## S4 method for signature 'baselineAlgResult'
qualMeas(
  object,
  ...,
  MIN,
  AVG,
  DEFAULT = c("all", "cond.min", "overall.min", "avg")
)
```

Arguments

object	An object of class predictionResult or baselineAlgResult
...	Other arguments. Selection of subsets of parameter levels. See Details.
MIN	List or vector of parameter names to take the minimum over. Not used if DEFAULT is "cond.min". See Details.
AVG	List or vector of parameter names to take the average over. Not used if DEFAULT is "avg". See Details.
DEFAULT	Character string. The default way to calculate the minimum (or average) for all parameters. See Details.

Details

The arguments to the baselineAlgResult method are interpreted in the following way:

Subsets of parameters levels can be selected by supplying their names and specifying the level indices as vectors. Substituting a vector with "all" will return all levels of the corresponding parameter, and substituting it with "overall" will return the level corresponding to the overall minimum. Minimum and average values for selected parameters can be chosen using MIN and AVG, respectively, together with a vector of parameter names.

DEFAULT specifies the action for each remaining parameters: If "all" (default): returns all levels. If "cond.min": take minimum for each remaining parameter (MIN is not used). If "overall.min": set any remaining parameters to their value corresponding to the overall min. If "avg": take average for each remaining parameter (AVG is not used).

Value

The qualMeas method for baselineAlgResult objects returns the subsets or minimum values of the qualMeas slot of the object as specified above. All other methods simply return the corresponding slot.

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

Function runTest, classes baselineAlgResult and predictionResult.

---

ridgeRegressionTestClass

Class "ridgeRegressionTest"

Description

A class describing a ridge regression test.

Slots

`lambda` Numeric vector. The smoothing parameter values to test

Objects from the Class

Objects can be created by calls of the form `new("ridgeRegressionTest", ...)`.

Extends

Class `predictionTest`, directly.

Methods

runTest `signature(object = "ridgeRegressionTest")`: Run the test

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

The base class `predictionTest`. The `runTest` function.

Examples

```
showClass("ridgeRegressionTest")
```

---

runTest *Run a predictionTest or baselineAlgTest*

Description

Runs the test defined in a `predictionTest` or `baselineAlgTest` object

Usage

```
runTest(object, X, y, ...)

## S4 method for signature 'PLSRTest'
runTest(object, X, y)

## S4 method for signature 'ridgeRegressionTest'
runTest(object, X, y)

## S4 method for signature 'baselineAlgTest'
runTest(object, X, y, predictionTest, postproc, verbose = FALSE)
```

Arguments

object	An object of class baselineAlgTest or subclass of predictionTest (currently PLSRTest or ridgeRegressionTest). The object specify the test to be run.
X	A matrix. The spectra to use in the test.
y	A vector or matrix. The response(s) to use in the test
...	Other arguments. Currently only used by the baselineAlgTest method.
predictionTest	A predictionTest object, describing the prediction test to use for this baseline algorithm test.
postproc	A function, used to postprocess the baseline corrected spectra prior to prediction testing. The function should take a matrix of spectra as its only argument, and return a matrix of postprocessed spectra.
verbose	Logical, specifying whether the test should print out progress information. Default is FALSE.

Value

runTest returns an object of class. predictionResult or baselineAlgResult.

Methods

signature(object = "baselineAlgTest"): Baseline corrects the spectra, optionally postprocesses them, and runs a prediction test on the corrected spectra. signature(object = "PLSRTest"): Runs PLSR on the data and calculates the cross-validated RMSEP signature(object = "ridgeRegressionTest"): Runs ridge regression on the data and calculates the GCV

Author(s)

Bjørn-Helge Mevik and Kristian Hovde Liland

See Also

baselineAlgTest, predictionTest, PLSRTest, ridgeRegressionTest

---

XPSdata *XPS core line data*

Description

Matrix of x,y values from X-Ray Photoelectron Spectroscopy on test sample.
The data are about the Carbon and Oxygen element for 1s shell.

Usage

```
data(C1s)
data(O1s)
```

Format

A matrix with the following 2 variables (rows).

`first row` is the abscissa, (Binding Energy [eV])

`second row` is the Intensity, (a.u.)

See Also

baseline.shirley

Examples

```
data(C1s)
data(O1s)
plot(C1s[1,], C1s[2,], type = "l")
plot(O1s[1,], O1s[2,], type = "l")
```

Index

∗ **baseline**
algorithm, 4
baseline, 5
baseline-package, 3
baseline.als, 6
baseline.fillPeaks, 8
baseline.irls, 9
baseline.lowpass, 10
baseline.medianWindow, 11
baseline.modpolyfit, 12
baseline.peakDetection, 13
baseline.rfbaseline, 14
baseline.rollingBall, 16
baseline.TAP, 19
baselineAlg, 21
baselineAlgorithms, 23
baselineAlgorithmsGUI, 24
baselineAlgResultMethods, 25
baselineEnv, 28
baselineGUI, 29
custom.baseline, 30
doOptim, 31
funcName, 33
getSpectra, 34
optimWizard, 36
overall.min, 37
param, 38
plotBaseline, 39
plotOptim, 40
qualMeas, 44
runTest, 46
∗ **classes**
baselineAlgClass, 21
baselineAlgResult, 24
baselineAlgTest, 26
baselineClass, 27
PLSRTestClass, 41
predictionResult, 42
predictionTest, 43
ridgeRegressionTestClass, 45
∗ **datasets**
milk, 35
XPSdata, 47
∗ **environment**
baselineEnv, 28
∗ **methods**
param, 38
predictionResultMethods, 43
qualMeas, 44
runTest, 46
∗ **plot**
plotBaseline, 39
∗ **spectra**
algorithm, 4
baseline, 5
baseline-package, 3
baseline.als, 6
baseline.fillPeaks, 8
baseline.irls, 9
baseline.lowpass, 10
baseline.medianWindow, 11
baseline.modpolyfit, 12
baseline.peakDetection, 13
baseline.rfbaseline, 14
baseline.rollingBall, 16
baseline.TAP, 19
baselineAlg, 21
baselineAlgResultMethods, 25
baselineGUI, 29
custom.baseline, 30
doOptim, 31
funcName, 33
getSpectra, 34
optimWizard, 36
overall.min, 37
param, 38
plotOptim, 40
qualMeas, 44

runTest, 46

algorithm, 4
algorithm,baselineAlgTest-method (algorithm), 4
algorithm-methods (algorithm), 4
als (baseline.als), 6

baseline, 5, *5*, *19*, *27*, *34, 35*, *40*
baseline-class (baselineClass), 27
baseline-package, 3
baseline.als, 6, *6*, *28*
baseline.fillPeaks, *6*, 8, *28*
baseline.irls, *6*, 9, *28*
baseline.lowpass, *6*, 10, *28*
baseline.medianWindow, *6*, 11, *28*
baseline.modpolyfit, *6*, 12, *28*
baseline.peakDetection, *6*, 13, *28*
baseline.rfbaseline, *6*, 14, *28*
baseline.rollingBall, *6*, 16, *28*
baseline.shirley, *6*, 17, *48*
baseline.TAP, *6*, 19
baselineAlg, 21, *21*, *23*, *27*, *33, 34*, *38*
baselineAlg-class (baselineAlgClass), 21
baselineAlgClass, 21
baselineAlgorithms, 23
baselineAlgorithmsGUI, 24
baselineAlgResult, 24, *25–27*, *38*, *44, 45*, *47*
baselineAlgResult-class (baselineAlgResult), 24
baselineAlgResultMethods, 25
baselineAlgTest, *4, 5*, *25*, 26, *31–34*, *38*, *46, 47*
baselineAlgTest-class (baselineAlgTest), 26
baselineClass, 27
baselineEnv, 28
baselineGUI, 29, *40*

C1s (XPSdata), 47
custom.baseline, 30

description (baselineAlg), 21
description,baselineAlg-method (baselineAlg), 21
description-methods (baselineAlg), 21
doOptim, 31, *37*

extraArgs (algorithm), 4
extraArgs,baselineAlgTest-method (algorithm), 4
extraArgs-methods (algorithm), 4

fillPeaks (baseline.fillPeaks), 8
funcName, *21*, 33
funcName,baselineAlg-method (funcName), 33
funcName,baselineAlgTest-method (funcName), 33
funcName-methods (funcName), 33

getBaseline, *27*
getBaseline (getSpectra), 34
getBaseline,baseline-method (getSpectra), 34
getBaselineEnv (baselineEnv), 28
getCall, *27*
getCall (getSpectra), 34
getCall,baseline-method (getSpectra), 34
getCorrected, *27*
getCorrected (getSpectra), 34
getCorrected,baseline-method (getSpectra), 34
getOptim (optimWizard), 36
getOptimRes (optimWizard), 36
getSpectra, *27*, 34
getSpectra,baseline-method (getSpectra), 34

ind.min (predictionResultMethods), 43
ind.min,predictionResult-method (predictionResultMethods), 43
ind.min-methods (predictionResultMethods), 43
irls (baseline.irls), 9

lowpass (baseline.lowpass), 10

medianWindow (baseline.medianWindow), 11
milk, 35
minQualMeas (qualMeas), 44
minQualMeas,baselineAlgResult-method (qualMeas), 44
minQualMeas,predictionResult-method (qualMeas), 44
minQualMeas-methods (qualMeas), 44
modpolyfit (baseline.modpolyfit), 12
mvrValstats (doOptim), 31

name (baselineAlg), 21
name,baselineAlg-method (baselineAlg), 21
name-methods (baselineAlg), 21

O1s (XPSdata), 47
optimWizard, 36
overall.min, 37

param, 38
param,baselineAlg-method (param), 38
param,baselineAlgResult-method (param), 38
param,baselineAlgTest-method (param), 38
param,predictionResult-method (param), 38
param-methods (param), 38
param.ind.min (baselineAlgResultMethods), 25
param.ind.min,baselineAlgResult-method (baselineAlgResultMethods), 25
param.ind.min-methods (baselineAlgResultMethods), 25
param.min (qualMeas), 44
param.min,baselineAlgResult-method (qualMeas), 44
param.min,predictionResult-method (qualMeas), 44
param.min-methods (qualMeas), 44
paramName (predictionResultMethods), 43
paramName,predictionResult-method (predictionResultMethods), 43
paramName-methods (predictionResultMethods), 43
peakDetection (baseline.peakDetection), 13
plot,baseline-method (plotBaseline), 39
plotBaseline, 39
plotOptim, 40
plsr, *41*
PLSRTest, *42–44*, *47*
PLSRTest-class (PLSRTestClass), 41
PLSRTestClass, 41
predictionResult, *38*, 42, *43–45*, *47*
predictionResult-class (predictionResult), 42
predictionResultMethods, 43
predictionTest, *31–33*, *41*, *42*, 43, *46*, *47*
predictionTest-class (predictionTest), 43
predictionTestClass (predictionTest), 43
putBaselineEnv (baselineEnv), 28

qualMeas, 44
qualMeas,baselineAlgResult-method (qualMeas), 44
qualMeas,predictionResult-method (qualMeas), 44
qualMeas-methods (qualMeas), 44
qualMeas.ind.min (baselineAlgResultMethods), 25
qualMeas.ind.min,baselineAlgResult-method (baselineAlgResultMethods), 25
qualMeas.ind.min-methods (baselineAlgResultMethods), 25
qualMeasName (qualMeas), 44
qualMeasName,baselineAlgResult-method (qualMeas), 44
qualMeasName,predictionResult-method (qualMeas), 44
qualMeasName-methods (qualMeas), 44

rfbaseline (baseline.rfbaseline), 14
ridgeRegressionTest, *42–44*, *47*
ridgeRegressionTest-class (ridgeRegressionTestClass), 45
ridgeRegressionTestClass, 45
rollingBall (baseline.rollingBall), 16
runTest, *41*, *42*, *45*, 46, *46*
runTest,baselineAlgTest-method (runTest), 46
runTest,PLSRTest-method (runTest), 46
runTest,ridgeRegressionTest-method (runTest), 46
runTest-methods (runTest), 46

shirley (baseline.shirley), 17

TAP (baseline.TAP), 19

XPSdata, 47