

Package: bolder (via r-universe)

May 18, 2026

Title 'RStudio' Add-Ins for Formatted Section Titles

Version 0.1.1

Description Provides 'RStudio' add-ins and helper functions for converting the current editor line, or a supplied character string, into formatted section titles for 'R' scripts. When used as an add-in, it uses 'rstudioapi' to read the active document context and replace only the selected line, so users can bind the add-ins to keyboard shortcuts. The formatter trims common comment and heading markers, converts the label to uppercase, and renders three styles: a five-line boxed title, a framed subtitle, and a simple inline header. Generated titles are padded or centered to a configurable width, using the package-specific width option when set and the session display width otherwise, which helps keep analysis scripts visually consistent and easier to navigate.

License MIT + file LICENSE

Encoding UTF-8

Imports rstudioapi

NeedsCompilation no

Author Gabriel Curti [aut, cre]

Maintainer Gabriel Curti <freitascurti@usp.br>

Repository <https://cran.r-universe.dev>

Date/Publication 2026-05-18 20:50:04 UTC

RemoteUrl <https://github.com/cran/bolder>

RemoteRef HEAD

RemoteSha bcd02330b9b168a7fd8e8316cb6fc816f2e974f7

Contents

bolder_format_title	2
bolder_simple	3
bolder_subtitle	3
bolder_title	3

bolder_format_title *Format a bolder title*

Description

Formats text using the bolder title styles.

Usage

```
bolder_format_title(  
  text,  
  level = c("title", "subtitle", "simple"),  
  width = bolder_width()  
)
```

Arguments

text	Text to format as a title.
level	Title level: title, subtitle, or simple.
width	Total title width. Defaults to <code>getOption("bolder.width")</code> when set, otherwise <code>getOption("width")</code> .

Details

Set options(`bolder.width = 90`) to customize the generated title width for addins and direct calls that use the default width argument.

Value

A character string containing the formatted title.

Examples

```
bolder_format_title("base de dados", "title")  
bolder_format_title("base de dados", "subtitle")  
bolder_format_title("base de dados", "simple")
```

bolder_simple	<i>Create a simple bolder title</i>
---------------	-------------------------------------

Description

RStudio addin that replaces the current editor line with a simple inline bolder title.

Usage

```
bolder_simple()
```

Value

Invisibly returns the generated replacement string. Called for the side effect of replacing the current editor line in RStudio.

bolder_subtitle	<i>Create a bolder subtitle</i>
-----------------	---------------------------------

Description

RStudio addin that replaces the current editor line with a centered bolder subtitle.

Usage

```
bolder_subtitle()
```

Value

Invisibly returns the generated replacement string. Called for the side effect of replacing the current editor line in RStudio.

bolder_title	<i>Create a bolder title</i>
--------------	------------------------------

Description

RStudio addin that replaces the current editor line with a centered bolder title.

Usage

```
bolder_title()
```

Value

Invisibly returns the generated replacement string. Called for the side effect of replacing the current editor line in RStudio.

Index

`bolder_format_title`, 2
`bolder_simple`, 3
`bolder_subtitle`, 3
`bolder_title`, 3