Package: clarabel (via r-universe)

October 27, 2026

Type Package

Title Interior Point Conic Optimization Solver

Version 0.11.3

Description A versatile interior point solver that solves linear programs (LPs), quadratic programs (QPs), second-order cone programs (SOCPs), semidefinite programs (SDPs), and problems with exponential and power cone constraints (<https://clarabel.org/stable/>). For quadratic objectives, unlike interior point solvers based on the standard homogeneous self-dual embedding (HSDE) model, Clarabel handles quadratic objective without requiring any epigraphical reformulation of its objective function. It can therefore be significantly faster than other HSDE-based solvers for problems with quadratic objective functions. Infeasible problems are detected using using a homogeneous embedding technique.

License Apache License (== 2.0)

Encoding UTF-8

URL https://oxfordcontrol.github.io/clarabel-r/

BugReports https://github.com/oxfordcontrol/clarabel-r/issues

Suggests knitr, Matrix, rmarkdown, tinytest

VignetteBuilder knitr

SystemRequirements Cargo (Rust's package manager), rustc (>= 1.70.0), and GNU Make

Imports cli, methods

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Balasubramanian Narasimhan [aut, cre], Paul Goulart [aut, cph], Yuwen Chen [aut], Hiroaki Yutani [ctb] (For vendoring/Makefile hints/R scripts for generating crate authors/licenses), David Zimmermann-Kollenda [ctb] (For configure scripts and tools/msvr.R lifted from rtiktoken package), The authors of the

dependency Rust crates [ctb] (see inst/AUTHORS file for details)

Maintainer Balasubramanian Narasimhan <naras@stanford.edu>

Config/pak/sysreqs make libclang-dev

Repository https://cran.r-universe.dev

Date/Publication 2026-08-23 04:40:08 UTC

RemoteUrl https://github.com/cran/clarabel

RemoteRef HEAD

RemoteSha 1f7bc9c8698f241a8dcf42bfda154b0feda6e08e

Contents

clarabel 2
clarabel_control 4
clarabel_solver 8
ClarabelSolver 10
solver_is_update_allowed 10
solver_solve 11
solver_status_descriptions 11
solver_update 12

Index **13**

`clarabel` *Interface to 'Clarabel', an interior point conic solver*

Description

Clarabel solves linear programs (LPs), quadratic programs (QPs), second-order cone programs (SOCPs) and semidefinite programs (SDPs). It also solves problems with exponential and power cone constraints. The specific problem solved is:

Minimize

$$\frac{1}{2}x^T Px + q^T x$$

subject to

$$Ax + s = b$$

$$s \in K$$

where $x \in R^n$, $s \in R^m$, $P = P^T$ and nonnegative-definite, $q \in R^n$, $A \in R^{m \times n}$, and $b \in R^m$. The set K is a composition of convex cones.

Usage

```
clarabel(A, b, q, P = NULL, cones, control = list(), strict_cone_order = TRUE)
```

Arguments

A	a matrix of constraint coefficients.
b	a numeric vector giving the primal constraints
q	a numeric vector giving the primal objective
P	a symmetric positive semidefinite matrix, default NULL
cones	a named list giving the cone sizes, see "Cone Parameters" below for specification
control	a list giving specific control parameters to use in place of default values, with an empty list indicating the default control parameters. Specified parameters should be correctly named and typed to avoid Rust system panics as no sanitization is done for efficiency reasons
strict_cone_order	a logical flag, default TRUE for forcing order of cones described below. If FALSE cones can be specified in any order and even repeated and directly passed to the solver without type and length checks

Details

The order of the rows in matrix A has to correspond to the order given in the table "Cone Parameters", which means means rows corresponding to *primal zero cones* should be first, rows corresponding to *non-negative cones* second, rows corresponding to *second-order cone* third, rows corresponding to *positive semidefinite cones* fourth, rows corresponding to *exponential cones* fifth and rows corresponding to *power cones* at last.

When the parameter strict_cone_order is FALSE, one can specify the cones in any order and even repeat them in the order they appear in the A matrix. See below.

Clarabel can solve:

1. linear programs (LPs)
2. second-order cone programs (SOCPs)
3. exponential cone programs (ECPs)
4. power cone programs (PCPs)
5. problems with any combination of cones, defined by the parameters listed in "Cone Parameters" below

Cone Parameters: The table below shows the cone parameter specifications. Mathematical definitions are in the vignette.

Parameter	Type	Length	Description
z	integer	1	number of primal zero cones (dual free cones), which corresponds to the primal equality constraints
l	integer	1	number of linear cones (non-negative cones)
q	integer	≥ 1	vector of second-order cone sizes
s	integer	≥ 1	vector of positive semidefinite cone sizes
ep	integer	1	number of primal exponential cones
p	numeric	≥ 1	vector of primal power cone parameters

gp	list	≥ 1	list of named lists of two items, a : a numeric vector of at least 2 exponent terms in the p

When the parameter `strict_cone_order` is `FALSE`, one can specify the cones in the order they appear in the `A` matrix. The `cones` argument in such a case should be a named list with names matching `^z*` indicating primal zero cones, `^l*` indicating linear cones, and so on. For example, either of the following would be valid: `list(z = 2L, l = 2L, q = 2L, z = 3L, q = 3L)`, or, `list(z1 = 2L, l1 = 2L, q1 = 2L, zb = 3L, qx = 3L)`, indicating a zero cone of size 2, followed by a linear cone of size 2, followed by a second-order cone of size 2, followed by a zero cone of size 3, and finally a second-order cone of size 3. Generalized power cones parameters have to specified as named lists, e.g., `list(z = 2L, gp1 = list(a = c(0.3, 0.7), n = 3L), gp2 = list(a = c(0.5, 0.5), n = 1L))`.

Note that when `strict_cone_order = FALSE`*, types of cone parameters such as integers, reals have to be explicit since the parameters are directly passed to the Rust interface with no sanity checks!*

Value

named list of solution vectors x, y, s and information about run

See Also

`clarabel_control()`

Examples

```
A <- matrix(c(1, 1), ncol = 1)
b <- c(1, 1)
obj <- 1
cone <- list(z = 2L)
control <- clarabel_control(tol_gap_rel = 1e-7, tol_gap_abs = 1e-7, max_iter = 100)
clarabel(A = A, b = b, q = obj, cones = cone, control = control)
```

---

clarabel_control *Control parameters with default values and types in parenthesis*

Description

Control parameters with default values and types in parenthesis

Usage

```
clarabel_control(
  max_iter = 200L,
  time_limit = Inf,
  verbose = TRUE,
  max_step_fraction = 0.99,
  tol_gap_abs = 1e-08,
  tol_gap_rel = 1e-08,
```

```
  tol_feas = 1e-08,
  tol_infeas_abs = 1e-08,
  tol_infeas_rel = 1e-08,
  tol_ktratio = 1e-06,
  reduced_tol_gap_abs = 5e-05,
  reduced_tol_gap_rel = 5e-05,
  reduced_tol_feas = 1e-04,
  reduced_tol_infeas_abs = 5e-12,
  reduced_tol_infeas_rel = 5e-05,
  reduced_tol_ktratio = 1e-04,
  equilibrate_enable = TRUE,
  equilibrate_max_iter = 10L,
  equilibrate_min_scaling = 1e-04,
  equilibrate_max_scaling = 10000,
  linesearch_backtrack_step = 0.8,
  min_switch_step_length = 0.1,
  min_terminate_step_length = 1e-04,
  max_threads = 0L,
  direct_kkt_solver = TRUE,
  direct_solve_method = c("auto", "qdldl"),
  static_regularization_enable = TRUE,
  static_regularization_constant = 1e-08,
 static_regularization_proportional = .Machine$double.eps * .Machine$double.eps,
  dynamic_regularization_enable = TRUE,
  dynamic_regularization_eps = 1e-13,
  dynamic_regularization_delta = 2e-07,
  iterative_refinement_enable = TRUE,
  iterative_refinement_reltol = 1e-13,
  iterative_refinement_abstol = 1e-12,
  iterative_refinement_max_iter = 10L,
  iterative_refinement_stop_ratio = 5,
  presolve_enable = TRUE,
  input_sparse_dropzeros = FALSE,
  chordal_decomposition_enable = TRUE,
 chordal_decomposition_merge_method = c("clique_graph", "parent_child", "none"),
  chordal_decomposition_compact = TRUE,
  chordal_decomposition_complete_dual = TRUE
)
```

Arguments

`max_iter`	maximum number of iterations (`200L`)
`time_limit`	maximum run time (seconds) (`Inf`)
`verbose`	verbose printing (`TRUE`)
`max_step_fraction`	maximum interior point step length (`0.99`)
`tol_gap_abs`	absolute duality gap tolerance (`1e-8`)
`tol_gap_rel`	relative duality gap tolerance (`1e-8`)

`tol_feas` feasibility check tolerance (primal and dual) (`1e-8`)

`tol_infeas_abs` absolute infeasibility tolerance (primal and dual) (`1e-8`)

`tol_infeas_rel` relative infeasibility tolerance (primal and dual) (`1e-8`)

`tol_ktratio` KT tolerance (`1e-6`)

`reduced_tol_gap_abs`
reduced absolute duality gap tolerance (`5e-5`)

`reduced_tol_gap_rel`
reduced relative duality gap tolerance (`5e-5`)

`reduced_tol_feas`
reduced feasibility check tolerance (primal and dual) (`1e-4`)

`reduced_tol_infeas_abs`
reduced absolute infeasibility tolerance (primal and dual) (`5e-12`)

`reduced_tol_infeas_rel`
reduced relative infeasibility tolerance (primal and dual) (`5e-5`)

`reduced_tol_ktratio`
reduced KT tolerance (`1e-4`)

`equilibrate_enable`
enable data equilibration pre-scaling (`TRUE`)

`equilibrate_max_iter`
maximum equilibration scaling iterations (`10L`)

`equilibrate_min_scaling`
minimum equilibration scaling allowed (`1e-4`)

`equilibrate_max_scaling`
maximum equilibration scaling allowed (`1e+4`)

`linesearch_backtrack_step`
linesearch backtracking (`0.8`)

`min_switch_step_length`
minimum step size allowed for asymmetric cones with PrimalDual scaling (`1e-1`)

`min_terminate_step_length`
minimum step size allowed for symmetric cones && asymmetric cones with Dual scaling (`1e-4`)

`max_threads` maximum solver threads for multithreaded KKT solvers, 0 lets the solver choose for itself (`0L`)

`direct_kkt_solver`
use a direct linear solver method (required true) (`TRUE`)

`direct_solve_method`
direct linear solver, either `"auto"` or `"qdldl"` (`"auto"`). This build links only the QDLDL solver, so `"auto"` resolves to `"qdldl"`; the two are equivalent here.

`static_regularization_enable`
enable KKT static regularization (`TRUE`)

`static_regularization_constant`
KKT static regularization parameter (`1e-8`)

`static_regularization_proportional`
additional regularization parameter w.r.t. the maximum abs diagonal term (`.Machine.double_eps^2`)

`dynamic_regularization_enable`
: enable KKT dynamic regularization (`TRUE`)

`dynamic_regularization_eps`
: KKT dynamic regularization threshold (`1e-13`)

`dynamic_regularization_delta`
: KKT dynamic regularization shift (`2e-7`)

`iterative_refinement_enable`
: KKT solve with iterative refinement (`TRUE`)

`iterative_refinement_reltol`
: iterative refinement relative tolerance (`1e-13`)

`iterative_refinement_abstol`
: iterative refinement absolute tolerance (`1e-12`)

`iterative_refinement_max_iter`
: iterative refinement maximum iterations (`10L`)

`iterative_refinement_stop_ratio`
: iterative refinement stalling tolerance (`5.0`)

`presolve_enable`
: whether to enable presolvle (`TRUE`)

`input_sparse_dropzeros`
: explicitly drop structural zeros from sparse data inputs (`FALSE`); see details

`chordal_decomposition_enable`
: whether to enable chordal decomposition for SDPs (`TRUE`)

`chordal_decomposition_merge_method`
: chordal decomposition merge method, one of `'clique_graph'`, `'parent_child'` or `'none'`, for SDPs (`'clique_graph'`)

`chordal_decomposition_compact`
: a boolean flag for SDPs indicating whether to assemble decomposed system in *compact* form for SDPs (`TRUE`)

`chordal_decomposition_complete_dual`
: a boolean flag indicating complete PSD dual variables after decomposition for SDPs (`TRUE`)

Details

Setting `input_sparse_dropzeros` to `TRUE` will disable parametric updating functionality. See documentation of 'dropzeros' in Rust `struct CscMatrix` for dropping structural zeros before passing to the solver.

These defaults track the Rust solver (Clarabel.rs 0.11.1) exactly. The only departure is the set of values accepted for `direct_solve_method`, which is limited by the features this package is built with.

Chordal decomposition applies only to semidefinite programs, and only when the aggregate sparsity pattern of the semidefinite constraints is decomposable. For such problems it can be dramatically faster, since it replaces one large semidefinite cone by several small ones. It has two consequences worth knowing. The reported dual variables for semidefinite constraints are not in general the same as those obtained without decomposition, because the decomposition is reversed and the dual completed, and a positive semidefinite completion is not unique. It also blocks the data updates used

for warm starts, but only when a decomposition actually took place: linear, quadratic and second-order cone problems are unaffected, and remain updatable. See `solver_is_update_allowed()` to check a particular solver instance.

Value

a list containing the control parameters.

Examples

```
# Default control parameters
ctrl <- clarabel_control()
ctrl$max_iter
# Custom tolerances and quiet output
ctrl <- clarabel_control(verbose = FALSE, tol_gap_rel = 1e-7, max_iter = 100L)
```

---

clarabel_solver *Create a persistent Clarabel solver object*

Description

Creates a persistent solver that can be reused across multiple solves with updated problem data (warm starts). This avoids the overhead of reallocating the solver's internal data structures when only the problem data changes but the sparsity pattern stays the same.

Usage

```
clarabel_solver(
  A,
  b,
  q,
  P = NULL,
  cones,
  control = list(),
  strict_cone_order = TRUE
)
```

Arguments

A	a matrix of constraint coefficients.
b	a numeric vector giving the primal constraints
q	a numeric vector giving the primal objective
P	a symmetric positive semidefinite matrix, default NULL
cones	a named list giving the cone sizes, see "Cone Parameters" below for specification

`control` a list giving specific control parameters to use in place of default values, with an empty list indicating the default control parameters. Specified parameters should be correctly named and typed to avoid Rust system panics as no sanitization is done for efficiency reasons

`strict_cone_order` a logical flag, default `TRUE` for forcing order of cones described below. If `FALSE` cones can be specified in any order and even repeated and directly passed to the solver without type and length checks

Details

Data updates are refused once the solver has altered the structure of the problem, since the stored factorization no longer corresponds to the data being updated. Three settings can cause that: `presolve_enable`, `input_sparse_dropzeros` and `chordal_decomposition_enable`. What matters is whether the transformation actually took place, not whether it was permitted: presolve rewrites the problem only if it finds something to remove, and chordal decomposition engages only for semidefinite constraints whose sparsity pattern is decomposable. Use `solver_is_update_allowed()` to check the instance you built.

Value

a `ClarabelSolver` environment object with methods `solve()`, `update_data(Px, Ax, q, b)`, and `is_update_allowed()`

See Also

`solver_solve()`, `solver_update()`, `solver_is_update_allowed()`, `clarabel()`

Examples

```
## Not run:
P <- Matrix::sparseMatrix(i = 1:2, j = 1:2, x = c(2, 1), dims = c(2, 2))
A <- matrix(c(1, 0, 0, 1), nrow = 2)
b <- c(1, 1)
q <- c(-2, -3)
cones <- list(l = 2L)
ctrl <- clarabel_control(presolve_enable = FALSE, verbose = FALSE)
s <- clarabel_solver(A, b, q, P, cones, control = ctrl)
sol1 <- solver_solve(s)
solver_update(s, q = c(-4, -1))
sol2 <- solver_solve(s)

## End(Not run)
```

ClarabelSolver — *A persistent Clarabel solver that can be reused across R calls.*

Description

A persistent Clarabel solver that can be reused across R calls.

Usage

```
ClarabelSolver
```

solver_is_update_allowed — *Check if data updates are allowed on a persistent solver*

Description

Returns `FALSE` if presolve, chordal decomposition or `input_sparse_dropzeros` has actually restructured this problem, which prevents data updates. Enabling one of those settings is not by itself enough to prevent updates; the transformation has to have taken place.

Usage

```
solver_is_update_allowed(solver)
```

Arguments

`solver`	a `ClarabelSolver` object created by `clarabel_solver()`

Value

logical scalar

See Also

`clarabel_solver()`, `solver_update()`

Examples

```
## Not run:
solver_is_update_allowed(s)  # FALSE if the problem was restructured

## End(Not run)
```

solver_solve *Solve using a persistent Clarabel solver*

Description

Solve using a persistent Clarabel solver

Usage

```
solver_solve(solver)
```

Arguments

solver	a ClarabelSolver object created by clarabel_solver()

Value

the same named list as clarabel(): solution vectors x, z, s and solver information

See Also

clarabel_solver(), solver_update()

Examples

```
## Not run:
s <- clarabel_solver(A, b, q, P, cones,
                     control = clarabel_control(presolve_enable = FALSE,
                                                verbose = FALSE))
sol <- solver_solve(s)
sol$status

## End(Not run)
```

solver_status_descriptions *Return the solver status description as a named character vector*

Description

Return the solver status description as a named character vector

Usage

```
solver_status_descriptions()
```

Value

a named list of solver status descriptions, in order of status codes returned by the solver

Examples

```
solver_status_descriptions()[2] ## for solved problem
solver_status_descriptions()[8] ## for max iterations limit reached
```

`solver_update` *Update problem data on a persistent Clarabel solver*

Description

Update one or more of P (objective), q (linear objective), A (constraints), b (constraint RHS) on an existing solver. The sparsity pattern of P and A must remain the same as the original problem; only the nonzero values can change.

Usage

```
solver_update(solver, P = NULL, q = NULL, A = NULL, b = NULL)
```

Arguments

`solver`	a `ClarabelSolver` object created by `clarabel_solver()`
`P`	new upper-triangular P matrix (same sparsity), or `NULL` to leave unchanged
`q`	new linear objective vector, or `NULL` to leave unchanged
`A`	new constraint matrix (same sparsity), or `NULL` to leave unchanged
`b`	new constraint RHS vector, or `NULL` to leave unchanged

Value

invisible `NULL`

See Also

`clarabel_solver()`, `solver_solve()`

Examples

```
## Not run:
solver_update(s, q = c(-4, -1))   # update linear objective only
solver_update(s, b = c(2, 2))     # update constraint RHS only
sol2 <- solver_solve(s)           # re-solve with updated data

## End(Not run)
```

Index

clarabel, 2
clarabel(), *9*, *11*
clarabel_control, 4
clarabel_control(), *4*
clarabel_solver, 8
clarabel_solver(), *10–12*
ClarabelSolver, 10

solver_is_update_allowed, 10
solver_is_update_allowed(), *8, 9*
solver_solve, 11
solver_solve(), *9*, *12*
solver_status_descriptions, 11
solver_update, 12
solver_update(), *9–11*