Package: cld3 (via r-universe)

October 29, 2026

Type Package

Title Google's Compact Language Detector 3

Version 1.6.2

Description Google's Compact Language Detector 3 is a neural network model for language identification and the successor of 'cld2' (available from CRAN). The algorithm is still experimental and takes a novel approach to language detection with different properties and outcomes. It can be useful to combine this with the Bayesian classifier results from 'cld2'. See <https://github.com/google/cld3#readme> for more information.

License Apache License 2.0

Encoding UTF-8

URL https://docs.ropensci.org/cld3/
https://ropensci.r-universe.dev/cld3

BugReports https://github.com/ropensci/cld3/issues

Imports Rcpp

LinkingTo Rcpp

RoxygenNote 6.0.1.9000

SystemRequirements libprotobuf and protobuf-compiler

Suggests testthat, cld2

NeedsCompilation yes

Author Jeroen Ooms [aut, cre] (ORCID: <https://orcid.org/0000-0002-4035-0289>), Google Inc [cph] (CLD3 C++ library)

Maintainer Jeroen Ooms <jeroenooms@gmail.com>

Config/pak/sysreqs libprotobuf-dev protobuf-compiler libprotoc-dev

Repository https://cran.r-universe.dev

Date/Publication 2026-07-26 23:10:07 UTC

RemoteUrl https://github.com/cran/cld3

RemoteRef HEAD

RemoteSha c19a483940821294a9bf9c2ab7f1dca03053e7ab

Contents

cld3 2

Index **3**

`cld3` *Compact Language Detector 3*

Description

The function `detect_language()` is vectorised and guesses the the language of each string in `text` or returns `NA` if the language could not reliably be determined. The function `detect_language_multi()` is not vectorised and detects all languages inside the entire character vector as a whole.

Usage

```
detect_language(text)

detect_language_mixed(text, size = 3)
```

Arguments

`text`	a string with text to classify or a connection to read from
`size`	number of languages to detect

Examples

```
# Vectorized best guess
text <- c("To be or not to be?", "Ce n'est pas grave.",
  "Hij heeft de klok horen luiden maar weet niet waar de klepel hangt.")
detect_language(text)

# Multiple languages in one text (doesn't seem to work well)
detect_language_mixed(text)
```

Index

cld3, 2

detect_language *(*cld3*)*, 2
detect_language(), *2*
detect_language_mixed *(*cld3*)*, 2
detect_language_multi *(*cld3*)*, 2
detect_language_multi(), *2*