

Package: convertid (via r-universe)

October 25, 2024

Type Package

Title Convert Gene IDs Between Each Other and Fetch Annotations from Biomart

Version 0.1.8

Date 2023-11-29

Author Vidal Fey [aut, cre], Henrik Edgren [aut]

Maintainer Vidal Fey <vidal.fey@gmail.com>

Description Gene Symbols or Ensembl Gene IDs are converted using the Bimap interface in 'AnnotationDbi' in `convertId2()` but that function is only provided as fallback mechanism for the most common use cases in data analysis. The main function in the package is `convert.bm()` which queries BioMart using the full capacity of the API provided through the 'biomaRt' package. Presets and defaults are provided for convenience but all ```marts```, ```filters``` and ```attributes``` can be set by the user. Function `convert.alias()` converts Gene Symbols to Aliases and vice versa and function `likely_symbol()` attempts to determine the most likely current Gene Symbol.

Depends AnnotationDbi

Imports org.Hs.eg.db, org.Mm.eg.db, plyr, stringr, biomaRt, stats, xml2, utils, rappdirs, assertthat, methods, httr, BiocFileCache

License GPL-3

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Repository CRAN

Date/Publication 2023-11-29 13:40:02 UTC

Contents

<code>convert.alias</code>	2
--------------------------------------	---

convert.bm	3
convertid	4
convertId2	5
get.bm	6
likely_symbol	7
todisp2	9

Index	10
--------------	-----------

convert.alias	<i>Convert Symbols to Aliases and Vice Versa.</i>
---------------	---

Description

convert.alias() attempts to find all possible symbol-alias combinations for a given gene symbol, i.e., it assumes the input ID to be either an Alias or a Symbol and performs multiple queries to find all possible counterparts. The input IDs are converted to title and upper case before querying and all possibilities are tested. There are species presets for Human and Mouse annotations.

Usage

```
convert.alias(id, species = c("Human", "Mouse"), db = NULL)
```

Arguments

id (character). Vector of gene symbols.
species (character). One of "Human" and "Mouse". Defaults to "Human".
db (AnnotationDb object). Annotation package object.

Value

A data.frame with two columns:

'SYMBOL': The official gene symbol.
'ALIAS': All possible aliases.

See Also

[select](#)

Examples

```
convert.alias("TRPV4")
```

Description

`convert.bm()` is a wrapper for `get.bm()` which in turn makes use of `getBM()` from the *biomaRt* package. It takes a matrix or data frame with the IDs to be converted in one column or as row names as input and returns a data frame with additional annotations after cleaning the fetched annotations and merging them with the input data frame.

Usage

```
convert.bm(
  dat,
  id = "ID",
  biom.data.set = c("human", "mouse"),
  biom.mart = c("ensembl", "mouse", "snp", "funcgen", "plants"),
  host = "https://www.ensembl.org",
  biom.filter = "ensembl_gene_id",
  biom.attributes = c("ensembl_gene_id", "hgnc_symbol", "description"),
  biom.cache = rappdirs::user_cache_dir("biomaRt"),
  use.cache = TRUE,
  sym.col = "hgnc_symbol",
  rm.dups = FALSE,
  verbose = FALSE
)
```

Arguments

<code>dat</code>	matrix or data.frame. Matrix or data frame with the ids to be converted in a column or as row names.
<code>id</code>	character. Name of the column with the ids to be converted, special name "rownames" will use the row names.
<code>biom.data.set</code>	character of length one. Biomart data set to use.
<code>biom.mart</code>	character vector. Biomart to use (uses the first element of the vector), defaults to "ensembl".
<code>host</code>	character of length one. Host URL.
<code>biom.filter</code>	character of length one. Name of biomart filter, i.e., type of query ids, defaults to "ensembl_gene_id".
<code>biom.attributes</code>	character vector. Biomart attributes, i.e., type of desired result(s); make sure query id type is included!
<code>biom.cache</code>	character. Path name giving the location of the cache <code>getBM()</code> uses if <code>use.cache=TRUE</code> . Defaults to the value in the <i>BIOMART_CACHE</i> environment variable.

use.cache	(logical). Should getBM() use the cache? Defaults to TRUE as in the getBM() function and is passed on to that.
sym.col	character. Name of the column in the query result with gene symbols.
rm.dups	logical. Should duplicated input IDs ('biom.filter') be removed from the result?
verbose	(logical). Should verbose output be written to the console? Defaults to FALSE.

Details

Wrapped around 'get.bm'.

Value

A data frame with the retrieved information.

Author(s)

Vidal Fey

See Also

[getBM](#)

Examples

```
## Not run:
dat <- data.frame(ID=c("ENSG00000111199", "ENSG00000134121", "ENSG00000176102", "ENSG00000171611"))
bm <- convert.bm(dat)
bm

## End(Not run)
```

convertid

Convert Gene IDs Between Each Other and Fetch Annotations from Biomart

Description

Gene Symbols or Ensembl Gene IDs are converted using the Bimap interface in 'AnnotationDbi' in convertId2() but that function is only provided as fallback mechanism for the most common use cases in data analysis. The main function in the package is convert.bm() which queries Biomart using the full capacity of the API provided through the 'biomaRt' package. Presets and defaults are provided for convenience but all "marts", "filters" and "attributes" can be set by the user. Function convert.alias() converts Gene Symbols to Aliases and vice versa and function likely_symbol() attempts to determine the most likely current Gene Symbol.

Details

Package: convertid
Type: Package
Initial version: 0.1-0
Created: 2021-08-18
License: GPL-3
LazyLoad: yes

Author(s)

Vidal Fey <vidal.fey@gmail.com> Maintainer: Vidal Fey <vidal.fey@gmail.com>

convertId2

Convert Gene Symbols to Ensembl Gene IDs or vice versa

Description

convertId2() uses the Bimap interface in AnnotationDbi to extract information from annotation packages. The function is limited to Human and Mouse annotations and is provided only as fallback mechanism for the most common use cases in data analysis. Please use the Biomart interface function `convert.bm()` for more flexibility.

Usage

```
convertId2(id, species = c("Human", "Mouse"))
```

Arguments

`id` (character). Vector of gene symbols.
`species` (character). One of "Human" and "Mouse". Defaults to "Human".

Value

A named character vector where the input IDs are the names and the query results the values.

See Also

[Bimap-envirAPI](#)

Examples

```
convertId2("ENSG00000111199")  
convertId2("TRPV4")
```

 get.bm

Make a Query to Biomart.

Description

get.bm() is a user-friendly wrapper for getBM() from the *biomaRt* package with default settings for Human and Mouse. It sets all needed variables and performs the query.

Usage

```
get.bm(
  values,
  biom.data.set = c("human", "mouse"),
  biom.mart = c("ensembl", "mouse", "snp", "funcgen", "plants"),
  host = "https://www.ensembl.org",
  biom.filter = "ensembl_gene_id",
  biom.attributes = c("ensembl_gene_id", "hgnc_symbol", "description"),
  biom.cache = rappdirs::user_cache_dir("biomaRt"),
  use.cache = TRUE,
  verbose = FALSE
)
```

Arguments

values	character vector of ids to be converted.
biom.data.set	character of length one. Biomart data set to use. Defaults to 'human' (internally translated to "hsapiens_gene_ensembl" if biom.mart="ensembl").
biom.mart	character vector. Biomart to use (uses the first element of the vector), defaults to "ensembl".
host	character of length one. Host URL.
biom.filter	character of length one. Name of biomart filter, i.e., type of query ids, defaults to "ensembl_gene_id".
biom.attributes	character vector. Biomart attributes, i.e., type of desired result(s); make sure query id type is included!
biom.cache	character. Path name giving the location of the cache getBM() uses if use.cache=TRUE. Defaults to the value in the <i>BIOMART_CACHE</i> environment variable.
use.cache	(logical). Should getBM() use the cache? Defaults to TRUE as in the getBM() function and is passed on to that.
verbose	(logical). Should verbose output be written to the console? Defaults to FALSE.

Value

A data frame with the retrieved information.

Author(s)

Vidal Fey

See Also[getBM](#)**Examples**

```
## Not run:
val <- c("ENSG00000111199", "ENSG00000134121", "ENSG00000176102", "ENSG00000171611")
bm <- get.bm(val)
bm

## End(Not run)
```

likely_symbol	<i>Retrieve Symbol Aliases and Previous symbols to determine a likely current symbol</i>
---------------	--

Description

likely_symbol() downloads the latest version of the HGNC gene symbol database as a text file and query it to obtain symbol aliases, previous symbols and all symbols currently in use. (Optionally) assuming the input ID to be either an Alias or a Symbol or a Previous Symbol it performs multiple queries and compares the results of all possible combinations to determine a likely current Symbol.

Usage

```
likely_symbol(
  syms,
  alias_sym = TRUE,
  prev_sym = TRUE,
  orgnsm = "human",
  hgnc = NULL,
  hgnc_url = NULL,
  output = c("likely", "symbols", "all"),
  verbose = TRUE
)
```

Arguments

syms	(character). Vector of Gene Symbols to be tested.
alias_sym	(logical). Should the input be assumed to be an Alias? Defaults to TRUE.
prev_sym	(logical). Should the input be assumed to be a Previous Symbol? Defaults to TRUE.

orgnsm	(character). The organism for which the Symbols are tested.
hgnc	(data.frame). An optional data frame with the needed HGNC annotations. (Needs to match the format available at hgnc_ut1!)
hgnc_url	(character). URL where to download the HGNC annotation dataset. Defaults to "ftp://ftp.ebi.ac.uk/pub/databases/genenames/new/tsv/hgnc_complete_set.txt".
output	(character). One of "likely", "symbols" and "all". Determines the scope of the output data frame. Defaults to "likely" which will return the inout Symbol and the determined likely Symbol.
verbose	(logical). Should messages be written to the console? Defaults to TRUE.

Details

Please note that the algorithm is very slow for large input vectors.

Value

A data.frame with the following columns depending on the output setting. output="likely":

```
'likely_symbol'
'input_symbol'
```

output="symbols":

```
'current_symbols'
'likely_symbol'
'input_symbol'
'all_symbols'
```

output="all":

```
'orig_input'
'organism'
'current_symbols'
'likely_symbol'
'input_symbol'
'all_symbols'
```

Note

Only fully implemented for Human for now.

Examples

```
## Not run:
likely_symbol(c("ABCC4", "ACPP", "KIAA1524"))

## End(Not run)
```


Description

`todisp2()` uses Biomart by employing `get.bm()` to retrieve Gene Symbols for a set of Ensembl Gene IDs. It is mainly meant as a fast way to convert IDs in standard gene expression analysis output to Symbols, e.g., for visualisation, which is why the input ID type is hard coded to ENSG IDs. If Biomart is not available the function can fall back to use `convertId2()` or a user-provided data frame with corresponding ENSG IDs and Symbols.

Usage

```
todisp2(ensg, lab = NULL, biomart = TRUE, verbose = FALSE)
```

Arguments

<code>ensg</code>	(character). Vector of Ensemble Gene IDs. Other ID types are not yet supported.
<code>lab</code>	(data.frame). A data frame with Ensembl Gene IDs as row names and Gene Symbols in the only column.
<code>biomart</code>	(logical). Should Biomart be used? Defaults to TRUE.
<code>verbose</code>	(logical). Should verbose output be written to the console? Defaults to FALSE.

Value

A character vector of Gene Symbols.

See Also

[get.bm](#)

Examples

```
## Not run:
val <- c("ENSG00000111199", "ENSG00000134121", "ENSG00000176102", "ENSG00000171611")
sym <- todisp2(val)
sym

## End(Not run)
```

Index

* **package**

convertid, 4

* **utilities**

convert.bm, 3

get.bm, 6

todisp2, 9

convert.alias, 2

convert.bm, 3

convertid, 4

convertId2, 5

get.bm, 6, 9

getBM, 4, 7

likely_symbol, 7

select, 2

todisp2, 9