Package: correctedWS (via r-universe)

November 24, 2026

Type Package

Title Corrected Welch-Satterthwaite Degrees of Freedom

Version 0.1.0

Description Calculates corrected Welch-Satterthwaite effective degrees of freedom for weighted sums of independent variance components. Provides corrected-default one-sample, paired, and two-sample t-tests, together with the classical Welch-Satterthwaite calculation for explicit comparison.

License CC0

URL https://github.com/cycologist/Corrected-Welch-Satterthwaite

BugReports https://github.com/cycologist/Corrected-Welch-Satterthwaite/issues

Encoding UTF-8

RoxygenNote 7.3.3

NeedsCompilation no

Imports stats

Suggests knitr, rmarkdown

VignetteBuilder knitr

Author Matthias von Davier [aut, cre]

Maintainer Matthias von Davier <mvondavier@gmail.com>

Repository https://cran.r-universe.dev

Date/Publication 2026-11-23 15:00:21 UTC

RemoteUrl https://github.com/cran/correctedWS

RemoteRef HEAD

RemoteSha 76c329f4eed53c963e844e808392d0646b80a6b6

Contents

correctedWS-package 2
corrected_t_test 2
cws 3
cws2 4
ws_classical 4

Index **6**

`correctedWS-package` *Corrected Welch-Satterthwaite Degrees of Freedom*

Description

Corrected Welch-Satterthwaite effective degrees of freedom for weighted sums of independent variance components, with corrected-default t-test utilities.

Details

The package implements the corrected estimator described in von Davier (2026): the denominator uses `nu + 2` and the result subtracts 2. The classical calculation remains available through `ws_classical()` and `method = "classical"`.

See Also

`cws`, `corrected_t_test`

`corrected_t_test` *One- and Two-Sample t-Tests with Corrected Default Degrees of Freedom*

Description

Performs one-sample, paired, pooled two-sample, or unequal-variance two-sample t-tests. The corrected Welch-Satterthwaite calculation is the default for the unequal-variance two-sample case.

Usage

```
corrected_t_test(x, y = NULL, alternative = c("two.sided", "less", "greater"),
  mu = 0, paired = FALSE, var.equal = FALSE, conf.level = 0.95,
  method = c("corrected", "classical"))
```

Arguments

x	Numeric vector of observations.
y	Optional numeric vector for a two-sample or paired test.
alternative	Alternative hypothesis: "two.sided", "less", or "greater".
mu	Null mean or null difference in means.
paired	Logical; perform a paired test when TRUE.
var.equal	Logical; use the pooled-variance test for an independent two-sample test.
conf.level	Confidence level for the interval.
method	"corrected" by default, or "classical" for the usual Welch-Satterthwaite calculation.

Value

An object of class "htest".

Examples

```
corrected_t_test(1:10, y = 2:11)
corrected_t_test(1:10, y = 2:11, method = "classical")
```

---

cws *Corrected Welch-Satterthwaite Effective Degrees of Freedom*

Description

Calculates corrected effective degrees of freedom for a weighted sum of independent variance components.

Usage

```
cws(s2, nu, w = rep(1, length(s2)))
```

Arguments

s2	Numeric vector of estimated variance components.
nu	Numeric vector of component degrees of freedom.
w	Numeric vector of positive weights.

Value

A single numeric corrected effective degrees of freedom, or NA_real_ when the denominator is zero.

Examples

```
cws(c(2, 3), c(10, 20))
cws(c(2, 3), c(10, 20), c(1, 2))
```

cws2 *Corrected Welch-Satterthwaite Calculation for Two Components*

Description

Convenience wrapper for the corrected Welch-Satterthwaite calculation with two variance components.

Usage

```
cws2(s2_1, s2_2, nu_1, nu_2, w1 = 1, w2 = 1)
```

Arguments

s2_1	First estimated variance component.
s2_2	Second estimated variance component.
nu_1	Degrees of freedom for the first component.
nu_2	Degrees of freedom for the second component.
w1	Positive first-component weight.
w2	Positive second-component weight.

Value

A single numeric corrected effective degrees of freedom.

Examples

```
cws2(2, 3, 10, 20)
cws2(4, 9, 5, 8, w1 = 2, w2 = 3)
```

ws_classical *Classical Welch-Satterthwaite Effective Degrees of Freedom*

Description

Calculates the classical Welch-Satterthwaite effective degrees of freedom for explicit comparison with the corrected estimator.

Usage

```
ws_classical(s2, nu, w = rep(1, length(s2)))
```

Arguments

s2	Numeric vector of estimated variance components.
nu	Numeric vector of component degrees of freedom.
w	Numeric vector of positive weights.

Value

A single numeric classical Welch-Satterthwaite effective degrees of freedom.

Examples

```
ws_classical(c(1, 1), c(1, 2))
```

Index

corrected_t_test, 2, *2*
correctedWS-package, 2
cws, *2*, 3
cws2, 4

ws_classical, 4