

Package: `ctrl` (via `r-universe`)

May 19, 2026

Title Clinical Tolerance Limits for Assessing Agreement

Version 0.1.0

Description Implements clinical tolerance limits (CTL) methodology for assessing agreement between two measurement methods. Estimates the true latent trait using Best Linear Unbiased Predictors (BLUP), models bias and variance components, and calculates overall and conditional agreement probabilities. Provides visualization tools including tolerance limit plots and conditional probability of agreement plots with confidence bands. This package is based on methods described in Taffé (2016) <[doi:10.1177/0962280216666667](https://doi.org/10.1177/0962280216666667)>, Taffé (2019) <[doi:10.1177/0962280219844535](https://doi.org/10.1177/0962280219844535)>, and 'Stata' package Taffé (2025) <[doi:10.1177/1536867X251365501](https://doi.org/10.1177/1536867X251365501)>.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

LazyData true

Suggests testthat (>= 3.0.0), withr (>= 2.0.0)

Config/testthat/edition 3

Imports binom (>= 1.1-1.1), dplyr (>= 1.1.0), ggplot2 (>= 3.3.0), lme4 (>= 1.1-35), lmtest (>= 0.9-40), MASS (>= 7.3-60), mfp2 (>= 1.0.1), sandwich (>= 3.0-0), stats, utils

NeedsCompilation no

Author Eliane Maalouf [aut] (ORCID: <<https://orcid.org/0000-0003-1549-7948>>), Patrick Taffé [cre, aut, cph] (ORCID: <<https://orcid.org/0000-0002-2049-6651>>)

Maintainer Patrick Taffé <patrick.taffe@unisante.ch>

Repository <https://cran.r-universe.dev>

Date/Publication 2026-03-20 10:50:02 UTC

RemoteUrl <https://github.com/cran/ctrl>

RemoteRef HEAD

RemoteSha 73af506c8035e096f20be989edca687016d15758

Contents

| | |
|------------------------|----------|
| ctl | 2 |
| ctl_dataset1 | 5 |
| ctl_dataset2 | 5 |
| Index | 7 |

| | |
|-----|--|
| ctl | <i>Clinical Tolerance Limits for Assessing Agreement</i> |
|-----|--|

Description

Assesses agreement between two measurement methods using clinical tolerance limits (CTL). The function estimates the true latent trait, models bias and variance components, calculates overall and conditional agreement probabilities, and optionally generates tolerance limits or conditional probability of agreement plots.

Usage

```
ctl(
  data,
  idvar,
  ynew,
  yref,
  intercept = 0,
  slope = 0,
  nbsimul = 1000L,
  seed = 123456789L,
  tlplot = FALSE,
  cpaplot = FALSE,
  pointwise = FALSE,
  simultaneous = FALSE,
  plots_to_file = FALSE,
  results_to_file = FALSE,
  outputs_path = NULL,
  horizontal_ticks = c(5, 10),
  vertical_ticks = c(5, 7),
  font_size = 14
)
```

Arguments

| | |
|-------------------------------|---|
| <code>data</code> | A data frame containing the measurements. |
| <code>idvar</code> | Character string specifying the name of the ID variable (subject identifier). |
| <code>ynew</code> | Character string specifying the name of the new method variable. |
| <code>yref</code> | Character string specifying the name of the reference method variable. |
| <code>intercept</code> | Numeric scalar for the intercept of tolerance limits. Default is 0. |
| <code>slope</code> | Numeric scalar for the slope of tolerance limits. Default is 0. |
| <code>nbsimul</code> | Integer specifying the number of Monte Carlo simulations for confidence bands. Default is 1000. |
| <code>seed</code> | Integer specifying the random seed for reproducibility. Default is 123456789. |
| <code>tlplot</code> | Logical; if TRUE, generates a tolerance limits plot. Default is FALSE. |
| <code>cpaplot</code> | Logical; if TRUE, generates a conditional probability of agreement (CPA) plot. Default is FALSE. |
| <code>pointwise</code> | Logical; if TRUE, includes pointwise confidence bands in the CPA plot. Default is FALSE. |
| <code>simultaneous</code> | Logical; if TRUE, includes simultaneous confidence bands in the CPA plot. Default is FALSE. |
| <code>plots_to_file</code> | Logical; if TRUE, exports generated plots as PDF files to the "ctl_outputs/" directory. Default is FALSE. |
| <code>results_to_file</code> | Logical; if TRUE, saves the results dataset to "ctl_outputs/ctl_results.rda". Default is FALSE. |
| <code>outputs_path</code> | Character string specifying the directory path where an "ctl_outputs" directory can be created to store the results' file and/or the plots, as required by <code>plots_to_file</code> and <code>results_to_file</code> arguments. Default is NULL and causes an error message if one of <code>plots_to_file</code> or <code>results_to_file</code> is TRUE. |
| <code>horizontal_ticks</code> | Numeric vector of length 2 specifying the range for the number of ticks on the x-axis (true latent trait). Default is <code>c(5, 10)</code> . |
| <code>vertical_ticks</code> | Numeric vector of length 2 specifying the range for the number of ticks on the y-axis. Only relevant for <code>tlplot</code> . Default is <code>c(5, 7)</code> . |
| <code>font_size</code> | Numeric scalar specifying the base font size for plot text elements in points. Default is 14. Title, axis labels, and other text elements are scaled relative to this base font size. |

Details

The function performs the following steps:

1. Estimates Best Linear Unbiased Predictors (BLUP) for the true latent trait using the reference method with a linear mixed model.
2. Models residual variance for the reference method (y_2) as a function of the latent trait.

3. Estimates differential and proportional bias between methods using heteroscedasticity-consistent standard errors.
4. Models residual variance for the new method as a function of the latent trait.
5. Calculates overall agreement as the proportion of observations falling within the clinical tolerance limits, with 95% confidence intervals using the Agresti-Coull method.
6. Optionally generates tolerance limits plots and/or conditional probability of agreement plots with confidence bands.

The function creates a "ctl_outputs" directory at the specified `outputs_path` to store generated plots and results when requested.

When `cpaplot = TRUE` and `results = TRUE`, the saved dataset includes agreement probabilities and confidence bounds. The structure depends on the `pointwise` and `simultaneous` arguments.

Value

Invisibly returns `ctl_results`. The function is called for: printing results to the console, generating plots, and optionally saving results and plots to files. Console messages are suppressable with `suppressMessages()`.

References

- Taffé P. (2016) "Effective plots to assess bias and precision in method comparison studies" *Statistical Methods in Medical Research*, 27, Number 6, pp. 1650-1660. doi:[10.1177/0962280216666667](https://doi.org/10.1177/0962280216666667)
- Taffé P. (2019) "Assessing bias, precision, and agreement in method comparison studies" *Statistical Methods in Medical Research*, 29, Number 3, pp. 778-796. doi:[10.1177/0962280219844535](https://doi.org/10.1177/0962280219844535)
- Taffé, P. (2025). "ctl: A package for assessing agreement based on clinical tolerance limits" *The Stata Journal*, 25, Number 3, pp. 659–676. doi:[10.1177/1536867X251365501](https://doi.org/10.1177/1536867X251365501)

Examples

```
withr::with_tempdir({
  # Tolerance limit plot
  ctl(ctl_dataset1, idvar = "id", ynew = "y1", yref = "y2", intercept = 5, slope = 0.15,
      tlplot = TRUE, plots_to_file = TRUE, results_to_file = TRUE, outputs_path = ".")

  ctl(ctl_dataset2, idvar = "id", ynew = "y1", yref = "y2", intercept = 1, slope = 0.2,
      seed = 11446158, tlplot = TRUE, plots_to_file = TRUE, results_to_file = TRUE,
      outputs_path = ".")

  # Conditional probability of agreement plot
  ctl(ctl_dataset1, idvar = "id", ynew = "y1", yref = "y2", intercept = 5, slope = 0.15,
      nbsimul = 100, cpaplot = TRUE, plots_to_file = TRUE, results_to_file = TRUE,
      outputs_path = ".")

  ctl(ctl_dataset1, idvar = "id", ynew = "y1", yref = "y2", intercept = 0, slope = 0.15,
      nbsimul = 100, cpaplot = TRUE, pointwise = TRUE, plots_to_file = TRUE,
      results_to_file = TRUE, outputs_path = ".")

  ctl(ctl_dataset2, idvar = "id", ynew = "y1", yref = "y2", intercept = 1, slope = 0.2,
```

```
        seed = 11446158, nbsimul = 100, cpaplot = TRUE, simultaneous = TRUE)  
    })
```

ctl_dataset1

ctl_dataset1

Description

A simulated dataset where the number of individuals is 100 and the number of repeated measurements per individual is 5 for both methods.

Usage

```
ctl_dataset1
```

Format

ctl_dataset1:

A data frame with 500 rows and 4 variables:

id represents the individual

t the index for the repeated measurements

y1 the measurements made by method 1

y2 the measurements made by method 2

Source

Taffé, P. (2025). "ctl: A package for assessing agreement based on clinical tolerance limits" The Stata Journal, 25, Number 3, pp. 659–676. doi:[10.1177/1536867X251365501](https://doi.org/10.1177/1536867X251365501)

ctl_dataset2

ctl_dataset2

Description

A simulated dataset where the number of individuals is 100 and the number of repeated measurements per individual varies between 1 to 3 for method 1 and between 5 to 10 for method 2.

Usage

```
ctl_dataset2
```

Format

ctl_dataset2:

A data frame with 745 rows and 4 variables:

id represents the individual

t the index for the repeated measurements

y1 the measurements made by method 1

y2 the measurements made by method 2

Source

Taffé, P. (2025). "ctl: A package for assessing agreement based on clinical tolerance limits" *The Stata Journal*, 25, Number 3, pp. 659–676. doi:[10.1177/1536867X251365501](https://doi.org/10.1177/1536867X251365501)

Index

* datasets

ctl_dataset1, 5

ctl_dataset2, 5

ctl, 2

ctl_dataset1, 5

ctl_dataset2, 5