Package: curl (via r-universe)

October 14, 2026

Type Package

Title A Modern and Flexible Web Client for R

Version 8.1.0

Description Bindings to 'libcurl' <https://curl.se/libcurl/> for performing fully configurable HTTP/FTP requests where responses can be processed in memory, on disk, or streaming via the callback or connection interfaces. Some knowledge of 'libcurl' is recommended; for a more-user-friendly web client see the 'httr2' package which builds on this package with http specific tools and logic.

License MIT + file LICENSE

SystemRequirements libcurl (>= 7.73): libcurl-devel (rpm) or libcurl4-openssl-dev (deb)

URL https://jeroen.r-universe.dev/curl

BugReports https://github.com/jeroen/curl/issues

Suggests spelling, testthat (>= 1.0.0), knitr, jsonlite, later, rmarkdown, httpuv (>= 1.4.4), webutils

VignetteBuilder knitr

Depends R (>= 3.0.0)

Encoding UTF-8

Language en-US

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Jeroen Ooms [aut, cre] (ORCID: <https://orcid.org/0000-0002-4035-0289>), Hadley Wickham [ctb], Posit Software, PBC [cph]

Maintainer Jeroen Ooms <jeroenooms@gmail.com>

Config/pak/sysreqs libssl-dev

Repository https://cran.r-universe.dev

Date/Publication 2026-10-14 12:56:39 UTC

RemoteUrl https://github.com/cran/curl

RemoteRef HEAD

RemoteSha 9d5e41e20319d27d03b99f6cce807dc7a86e33b9

Contents

curl . . . 2
curl_download . . . 4
curl_echo . . . 5
curl_escape . . . 6
curl_fetch_memory . . . 6
curl_options . . . 8
curl_parse_url . . . 15
curl_upload . . . 17
file_writer . . . 18
handle . . . 19
handle_cookies . . . 21
ie_proxy . . . 21
multi . . . 22
multi_download . . . 24
multipart . . . 27
nslookup . . . 27
parse_date . . . 28
parse_headers . . . 28
send_mail . . . 29

Index **32**

`curl` *Curl connection interface*

Description

Drop-in replacement for base `url()` that supports https, ftps, gzip, deflate, etc. Default behavior is identical to `url()`, but request can be fully configured by passing a custom `handle()`.

Usage

```
curl(url = "https://hb.cran.dev/get", open = "", handle = new_handle())
```

Arguments

`url`	character string. See examples.
`open`	character string. How to open the connection if it should be opened initially. Currently only "r" and "rb" are supported.
`handle`	a curl handle object

Details

As of version 2.3 curl connections support `open(con, blocking = FALSE)`. In this case `readBin` and `readLines` will return immediately with data that is available without waiting. For such non-blocking connections the caller needs to call `isIncomplete()` to check if the download has completed yet.

Examples

```
## Not run:
con <- curl("https://hb.cran.dev/get")
readLines(con)

# Auto-opened connections can be recycled
open(con, "rb")
bin <- readBin(con, raw(), 999)
close(con)
rawToChar(bin)

# HTTP error
curl("https://hb.cran.dev/status/418", "r")

# Follow redirects
readLines(curl("https://hb.cran.dev/redirect/3"))

# Error after redirect
curl("https://hb.cran.dev/redirect-to?url=https://hb.cran.dev/status/418", "r")

# Auto decompress Accept-Encoding: gzip / deflate (rfc2616 #14.3)
readLines(curl("https://hb.cran.dev/gzip"))
readLines(curl("https://hb.cran.dev/deflate"))

# Binary support
buf <- readBin(curl("https://hb.cran.dev/bytes/98765", "rb"), raw(), 1e5)
length(buf)

# Read file from disk
test <- paste0("file://", system.file("DESCRIPTION"))
readLines(curl(test))

# Other protocols
read.csv(curl("ftp://cran.r-project.org/pub/R/CRAN_mirrors.csv"))
readLines(curl("ftps://test.rebex.net:990/readme.txt"))
readLines(curl("gopher://quux.org/1"))

# Streaming data
con <- curl("http://jeroen.github.io/data/diamonds.json", "r")
while(length(x <- readLines(con, n = 5))){
  print(x)
}

# Stream large dataset over https with gzip
library(jsonlite)
```

```
con <- gzcon(curl("https://jeroen.github.io/data/nycflights13.json.gz"))
nycflights <- stream_in(con)

## End(Not run)
```

`curl_download` *Download file to disk*

Description

Libcurl implementation of `C_download` (the "internal" download method) with added support for https, ftps, gzip, etc. Default behavior is identical to `download.file()`, but request can be fully configured by passing a custom `handle()`.

Usage

```
curl_download(url, destfile, quiet = TRUE, mode = "wb", handle = new_handle())
```

Arguments

`url`	A character string naming the URL of a resource to be downloaded.
`destfile`	A character string with the name where the downloaded file is saved. Tilde-expansion is performed.
`quiet`	If `TRUE`, suppress status messages (if any), and the progress bar.
`mode`	A character string specifying the mode with which to write the file. Useful values are `"w"`, `"wb"` (binary), `"a"` (append) and `"ab"`.
`handle`	a curl handle object

Details

The main difference between `curl_download` and `curl_fetch_disk` is that `curl_download` checks the http status code before starting the download, and raises an error when status is non-successful. The behavior of `curl_fetch_disk` on the other hand is to proceed as normal and write the error page to disk in case of a non success response.

The `curl_download` function does support resuming and removes the temporary file if the download did not complete successfully. For a more advanced download interface which supports concurrent requests and resuming large files, have a look at the multi_download function.

Value

Path of downloaded file (invisibly).

See Also

Advanced download interface: multi_download

Examples

```
# Download large file
## Not run:
url <- "http://www2.census.gov/acs2011_5yr/pums/csv_pus.zip"
tmp <- tempfile()
curl_download(url, tmp)

## End(Not run)
```

---

curl_echo *Echo Service*

Description

This function is only for testing purposes. It starts a local httpuv server to echo the request body and content type in the response.

Usage

```
curl_echo(handle, port = find_port(), progress = interactive(), file = NULL)

find_port(range = NULL)
```

Arguments

handle	a curl handle object
port	the port number on which to run httpuv server
progress	show progress meter during http transfer
file	path or connection to write body. Default returns body as raw vector.
range	optional integer vector of ports to consider

Examples

```
if(require('httpuv')){
h <- new_handle(url = 'https://hb.cran.dev/post')
handle_setform(h, foo = "blabla", bar = charToRaw("test"),
  myfile = form_file(system.file("DESCRIPTION"), "text/description"))

# Echo the POST request data
formdata <- curl_echo(h)

# Show the multipart body
cat(rawToChar(formdata$body))

# Parse multipart
webutils::parse_http(formdata$body, formdata$content_type)
}
```

curl_escape *URL encoding*

Description

Escape all special characters (i.e. everything except for a-z, A-Z, 0-9, '-', '.', '_' or '~') for use in URLs.

Usage

```
curl_escape(url)

curl_unescape(url)
```

Arguments

url	A character vector (typically containing urls or parameters) to be encoded/decoded

Examples

```
# Escape strings
out <- curl_escape("foo = bar + 5")
curl_unescape(out)

# All non-ascii characters are encoded
mu <- "\u00b5"
curl_escape(mu)
curl_unescape(curl_escape(mu))
```

curl_fetch_memory *Fetch the contents of a URL*

Description

Low-level bindings to write data from a URL into memory, disk or a callback function.

Usage

```
curl_fetch_memory(url, handle = new_handle())

curl_fetch_disk(url, path, handle = new_handle())

curl_fetch_stream(url, fun, handle = new_handle())

curl_fetch_multi(
  url,
```

```
  done = NULL,
  fail = NULL,
  pool = NULL,
  data = NULL,
  handle = new_handle()
)

curl_fetch_echo(url, handle = new_handle())

handle_data(handle)
```

Arguments

url	A character string naming the URL of a resource to be downloaded.
handle	A curl handle object.
path	Path to save results
fun	Callback function. Should have one argument, which will be a raw vector.
done	callback function for completed request. Single argument with response data in same structure as curl_fetch_memory.
fail	callback function called on failed request. Argument contains error message.
pool	a multi handle created by new_pool. Default uses a global pool.
data	(advanced) callback function, file path, or connection object for writing incoming data. This callback should only be used for *streaming* applications, where small pieces of incoming data get written before the request has completed. The signature for the callback function is `write(data, final = FALSE)`. If set to `NULL` the entire response gets buffered internally and returned by in the done callback (which is usually what you want).

Details

The `curl_fetch_*()` functions automatically raise an error upon protocol problems (network, disk, TLS, etc.) but do not implement application logic. For example, you need to check the status code of HTTP requests in the response by yourself, and deal with it accordingly.

Both `curl_fetch_memory()` and `curl_fetch_disk` have a blocking and a non-blocking C implementation. The latter is slightly slower but allows for interrupting the download prematurely (using e.g. CTRL+C or ESC). Interrupting is enabled when R runs in interactive mode or when `getOption("curl_interrupt") == TRUE`.

The `curl_fetch_multi()` function is the asynchronous equivalent of `curl_fetch_memory()`. It wraps `multi_add()` to schedule requests which are executed concurrently when calling `multi_run()`. For each successful request, the done callback is triggered with response data. For failed requests (when `curl_fetch_memory()` would raise an error), the `fail` function is triggered with the error message.

After a request has been performed, metadata from the request can be read from the handle object using `handle_data()` (this same information also gets returned by `curl_fetch_memory()` directly). It includes things like:

- Final URL (after redirects)
- HTTP status code
- Content-type
- Response headers
- Timings
- Http-version This data remains available in the handle until it is either re-used for a new request, or `handle_reset()` is called.

Examples

```
# Load in memory
res <- curl_fetch_memory("https://hb.cran.dev/cookies/set?foo=123&bar=ftw")
res$content

# Save to disk
res <- curl_fetch_disk("https://hb.cran.dev/stream/10", tempfile())
res$content
readLines(res$content)

# Stream with callback
drip_url <- "https://hb.cran.dev/drip?duration=3&numbytes=15&code=200"
res <- curl_fetch_stream(drip_url, function(x){
  cat(rawToChar(x))
})

# Async API
data <- list()
success <- function(res){
  cat("Request done! Status:", res$status, "\n")
  data <<- c(data, list(res))
}
failure <- function(msg){
  cat("Oh noes! Request failed!", msg, "\n")
}
curl_fetch_multi("https://hb.cran.dev/get", success, failure)
curl_fetch_multi("https://hb.cran.dev/status/418", success, failure)
curl_fetch_multi("https://urldoesnotexist.xyz", success, failure)
multi_run()
str(data)
```

`curl_options` *Listing curl features and options*

Description

The functions `curl_version()` and `curl_options()` show the available features, protocols and options supported by the local version of libcurl.

You can use `curl_options_table()` to lookup the type for each option: most options take a string, number, or `TRUE`/`FALSE` value, but some options need a special enum/bitmask value: these are listed in the sections below.

Usage

```
curl_options(filter = "")

curl_options_table(filter = "")

curl_version()
```

Arguments

`filter`	string: only return options with string in name

Details

Several curl options take an enum or bitmask value, for which the libcurl manual pages give symbolic names. These constants are exported as R variables, so you can copy such values literally from the libcurl documentation:

```
h <- new_handle()
handle_setopt(h, http_version = CURL_HTTP_VERSION_1_1)
handle_setopt(h, httpauth = CURLAUTH_NEGOTIATE)
```

For bitmask options, each constant is a single distinct bit, so where the libcurl documentation combines flags with `|`, you can simply add them up:

```
handle_setopt(h, httpauth = CURLAUTH_BASIC + CURLAUTH_DIGEST)
handle_setopt(h, altsvc_ctrl = CURLALTSVC_H1 + CURLALTSVC_H2)
```

Note that a few wide bitmasks such as `CURLAUTH_ANY` exceed the range of R integers and are therefore stored as doubles, holding the exact same numeric value as their C counterparts.

The sections below list the supported options with their values, in the same order as the corresponding libcurl manual pages. As usual with `handle_setopt()`, the R option name is the `CURLOPT_` constant, lowercase and without the prefix, e.g. `CURLOPT_HTTPAUTH` becomes `httpauth`.

CURLOPT_ALTSVC_CTRL

Bitmask to enable Alt-Svc support, see https://curl.se/libcurl/c/CURLOPT_ALTSVC_CTRL.html.

- `CURLALTSVC_H1`: accept alternative services offered over HTTP/1.1
- `CURLALTSVC_H2`: accept alternative services offered over HTTP/2
- `CURLALTSVC_H3`: accept alternative services offered over HTTP/3
- `CURLALTSVC_READONLYFILE`: do not write the alt-svc cache back to the file

CURLOPT_FOLLOWLOCATION

In addition to classic TRUE/FALSE, libcurl >= 8.13 supports these modes, see https://curl.se/libcurl/c/CURLOPT_FOLLOWLOCATION.html.

- CURLFOLLOW_ALL: follow redirects (same as TRUE)
- CURLFOLLOW_OBEYCODE: follow redirects, but do not use the custom method in the follow-up request when the HTTP code (301, 302, 303) instructs so
- CURLFOLLOW_FIRSTONLY: only use the custom method in the first request, always reset it in the next

CURLOPT_FTP_CREATE_MISSING_DIRS

See https://curl.se/libcurl/c/CURLOPT_FTP_CREATE_MISSING_DIRS.html.

- CURLFTP_CREATE_DIR_NONE: do not create missing directories
- CURLFTP_CREATE_DIR: create a missing directory, fail if that does not work
- CURLFTP_CREATE_DIR_RETRY: retry the CWD command again if the directory could not be created, in case it was created by a third party in the meantime

CURLOPT_FTP_FILEMETHOD

Select how to reach a file on an FTP(S) server, see https://curl.se/libcurl/c/CURLOPT_FTP_FILEMETHOD.html.

- CURLFTPMETHOD_DEFAULT: let libcurl pick (same as MULTICWD)
- CURLFTPMETHOD_MULTICWD: a CWD command for each path part
- CURLFTPMETHOD_NOCWD: no CWD at all, use the full path in every command
- CURLFTPMETHOD_SINGLECWD: one CWD with the full target directory

CURLOPT_FTP_SSL_CCC

Clear Command Channel mode, see https://curl.se/libcurl/c/CURLOPT_FTP_SSL_CCC.html.

- CURLFTPSSL_CCC_NONE: do not attempt to shut down the SSL/TLS layer
- CURLFTPSSL_CCC_PASSIVE: do not initiate the shutdown, wait for the server
- CURLFTPSSL_CCC_ACTIVE: initiate the shutdown ourselves

CURLOPT_FTPSSLAUTH

Order in which to attempt TLS vs SSL when upgrading an FTP connection, see https://curl.se/libcurl/c/CURLOPT_FTPSSLAUTH.html.

- CURLFTPAUTH_DEFAULT: let libcurl decide
- CURLFTPAUTH_SSL: try AUTH SSL first
- CURLFTPAUTH_TLS: try AUTH TLS first

CURLOPT_GSSAPI_DELEGATION

See https://curl.se/libcurl/c/CURLOPT_GSSAPI_DELEGATION.html.

- CURLGSSAPI_DELEGATION_NONE: no delegation (default)
- CURLGSSAPI_DELEGATION_POLICY_FLAG: delegate if the OK-AS-DELEGATE flag is set in the service ticket
- CURLGSSAPI_DELEGATION_FLAG: unconditionally allow delegation

CURLOPT_HEADEROPT

How to send custom headers to a proxy, see https://curl.se/libcurl/c/CURLOPT_HEADEROPT.html.

- CURLHEADER_UNIFIED: the headers set with `httpheader` are also sent to the proxy
- CURLHEADER_SEPARATE: only headers set with `proxyheader` are sent to the proxy

CURLOPT_HSTS_CTRL

Bitmask to enable HSTS (HTTP Strict Transport Security), see https://curl.se/libcurl/c/CURLOPT_HSTS_CTRL.html.

- CURLHSTS_ENABLE: enable the in-memory HSTS cache
- CURLHSTS_READONLYFILE: do not write the HSTS cache back to the file

CURLOPT_HTTP_VERSION

Preferred HTTP protocol version, see https://curl.se/libcurl/c/CURLOPT_HTTP_VERSION.html.

- CURL_HTTP_VERSION_NONE: no preference, let libcurl choose (default)
- CURL_HTTP_VERSION_1_0: enforce HTTP 1.0
- CURL_HTTP_VERSION_1_1: enforce HTTP 1.1
- CURL_HTTP_VERSION_2_0: attempt HTTP 2, fall back to HTTP 1.1 (CURL_HTTP_VERSION_2 is an alias)
- CURL_HTTP_VERSION_2TLS: attempt HTTP 2 for HTTPS only, HTTP 1.1 otherwise
- CURL_HTTP_VERSION_2_PRIOR_KNOWLEDGE: use HTTP 2 without HTTP/1.1 Upgrade
- CURL_HTTP_VERSION_3: attempt HTTP 3, fall back to earlier versions
- CURL_HTTP_VERSION_3ONLY: use HTTP 3 or fail

CURLOPT_HTTPAUTH

Bitmask of HTTP authentication methods libcurl may use, see https://curl.se/libcurl/c/CURLOPT_HTTPAUTH.html. The same values apply to `proxyauth` (CURLOPT_PROXYAUTH).

- CURLAUTH_NONE: no authentication
- CURLAUTH_BASIC: HTTP Basic authentication (default)
- CURLAUTH_DIGEST: HTTP Digest authentication

- CURLAUTH_DIGEST_IE: HTTP Digest authentication with an IE flavor
- CURLAUTH_BEARER: HTTP Bearer token (OAuth 2.0) authentication
- CURLAUTH_NEGOTIATE: HTTP Negotiate (SPNEGO) authentication (CURLAUTH_GSSAPI is an alias)
- CURLAUTH_NTLM: HTTP NTLM authentication
- CURLAUTH_AWS_SIGV4: HTTP AWS V4 signature authentication
- CURLAUTH_ANY: all supported methods, libcurl picks the most secure
- CURLAUTH_ANYSAFE: all supported methods except Basic
- CURLAUTH_ONLY: modifier bit: use only the method set alongside it, e.g. CURLAUTH_ONLY + CURLAUTH_DIGEST

CURLOPT_IPRESOLVE

See https://curl.se/libcurl/c/CURLOPT_IPRESOLVE.html.

- CURL_IPRESOLVE_WHATEVER: resolve to any IP version (default)
- CURL_IPRESOLVE_V4: only use IPv4 addresses
- CURL_IPRESOLVE_V6: only use IPv6 addresses

CURLOPT_MIME_OPTIONS

See https://curl.se/libcurl/c/CURLOPT_MIME_OPTIONS.html.

- CURLMIMEOPT_FORMESCAPE: backslash-escape quotes and backslashes in multipart form field and file names

CURLOPT_NETRC

Whether to read credentials from the .netrc file, see https://curl.se/libcurl/c/CURLOPT_NETRC.html.

- CURL_NETRC_IGNORED: ignore the netrc file (default)
- CURL_NETRC_OPTIONAL: use the netrc file, but credentials in the URL take precedence
- CURL_NETRC_REQUIRED: only use the netrc file, ignore credentials in the URL

CURLOPT_POSTREDIR

Bitmask of redirect codes after which a POST must remain a POST, see https://curl.se/libcurl/c/CURLOPT_POSTREDIR.html.

- CURL_REDIR_POST_301: keep the POST method after a 301 redirect
- CURL_REDIR_POST_302: keep the POST method after a 302 redirect
- CURL_REDIR_POST_303: keep the POST method after a 303 redirect
- CURL_REDIR_POST_ALL: all of the above
- CURL_REDIR_GET_ALL: convert to GET on all redirects (default)

CURLOPT_PROXYTYPE

Type of the proxy set with `proxy`, see https://curl.se/libcurl/c/CURLOPT_PROXYTYPE.html.

- `CURLPROXY_HTTP`: HTTP proxy (default)
- `CURLPROXY_HTTPS`: HTTPS proxy using HTTP/1.x
- `CURLPROXY_HTTPS2`: HTTPS proxy, attempt HTTP/2
- `CURLPROXY_HTTP_1_0`: HTTP proxy, force HTTP 1.0
- `CURLPROXY_SOCKS4`: SOCKS4 proxy
- `CURLPROXY_SOCKS4A`: SOCKS4a proxy, proxy resolves the hostname
- `CURLPROXY_SOCKS5`: SOCKS5 proxy
- `CURLPROXY_SOCKS5_HOSTNAME`: SOCKS5 proxy, proxy resolves the hostname

CURLOPT_SOCKS5_AUTH

Bitmask of allowed methods for SOCKS5 proxy authentication, see https://curl.se/libcurl/c/CURLOPT_SOCKS5_AUTH.html: `CURLAUTH_BASIC` (username/password), `CURLAUTH_GSSAPI` and `CURLAUTH_NONE`.

CURLOPT_SSH_AUTH_TYPES

Bitmask of authentication types for SFTP/SCP connections, see https://curl.se/libcurl/c/CURLOPT_SSH_AUTH_TYPES.html.

- `CURLSSH_AUTH_PUBLICKEY`: public/private key files
- `CURLSSH_AUTH_PASSWORD`: password
- `CURLSSH_AUTH_HOST`: host key files
- `CURLSSH_AUTH_KEYBOARD`: keyboard interactive
- `CURLSSH_AUTH_AGENT`: ssh-agent
- `CURLSSH_AUTH_GSSAPI`: gssapi (kerberos, ...)
- `CURLSSH_AUTH_ANY`: any method (default, `CURLSSH_AUTH_DEFAULT` is an alias)
- `CURLSSH_AUTH_NONE`: no allowed methods

CURLOPT_SSL_OPTIONS

Bitmask of SSL behavior options, see https://curl.se/libcurl/c/CURLOPT_SSL_OPTIONS.html. The same values apply to `proxy_ssl_options` (CURLOPT_PROXY_SSL_OPTIONS).

- `CURLSSLOPT_ALLOW_BEAST`: allow the BEAST SSL vulnerability for interoperability reasons
- `CURLSSLOPT_NO_REVOKE`: disable certificate revocation checks (Schannel)
- `CURLSSLOPT_NO_PARTIALCHAIN`: do not accept partial certificate chains
- `CURLSSLOPT_REVOKE_BEST_EFFORT`: ignore revocation check failures due to missing/offline distribution points (Schannel)
- `CURLSSLOPT_NATIVE_CA`: use the operating system's native CA store
- `CURLSSLOPT_AUTO_CLIENT_CERT`: automatically locate and use a client certificate for authentication (Schannel)

CURLOPT_SSLVERSION

Preferred TLS/SSL version, see https://curl.se/libcurl/c/CURLOPT_SSLVERSION.html. The same values apply to `proxy_sslversion` (CURLOPT_PROXY_SSLVERSION).

- `CURL_SSLVERSION_DEFAULT`: default, currently the minimum is TLS v1.0
- `CURL_SSLVERSION_TLSv1`: TLS v1.0 or later
- `CURL_SSLVERSION_TLSv1_0`: TLS v1.0 or later
- `CURL_SSLVERSION_TLSv1_1`: TLS v1.1 or later
- `CURL_SSLVERSION_TLSv1_2`: TLS v1.2 or later
- `CURL_SSLVERSION_TLSv1_3`: TLS v1.3 or later

The maximum TLS version can be set by adding one of these to the value above, e.g. `CURL_SSLVERSION_TLSv1_1 + CURL_SSLVERSION_MAX_TLSv1_2`:

- `CURL_SSLVERSION_MAX_DEFAULT`: the highest supported TLS version (`CURL_SSLVERSION_MAX_NONE` has the same effect)
- `CURL_SSLVERSION_MAX_TLSv1_0`: at most TLS v1.0
- `CURL_SSLVERSION_MAX_TLSv1_1`: at most TLS v1.1
- `CURL_SSLVERSION_MAX_TLSv1_2`: at most TLS v1.2
- `CURL_SSLVERSION_MAX_TLSv1_3`: at most TLS v1.3

CURLOPT_TIMECONDITION

How to compare the `timevalue` timestamp, see https://curl.se/libcurl/c/CURLOPT_TIMECONDITION.html.

- `CURL_TIMECOND_NONE`: no time condition (default)
- `CURL_TIMECOND_IFMODSINCE`: only transfer if modified since `timevalue`
- `CURL_TIMECOND_IFUNMODSINCE`: only transfer if not modified since `timevalue`
- `CURL_TIMECOND_LASTMOD`: (FTP only)

CURLOPT_USE_SSL

Request TLS upgrade for FTP, SMTP, POP3 and IMAP transfers, see https://curl.se/libcurl/c/CURLOPT_USE_SSL.html.

- `CURLUSESSL_NONE`: do not attempt to use SSL (default)
- `CURLUSESSL_TRY`: try SSL, proceed as normal otherwise
- `CURLUSESSL_CONTROL`: require SSL for the control connection, or fail
- `CURLUSESSL_ALL`: require SSL for all communication, or fail

CURLOPT_WS_OPTIONS

Bitmask with websocket behavior options, see https://curl.se/libcurl/c/CURLOPT_WS_OPTIONS.html.

- `CURLWS_RAW_MODE`: deliver raw websocket traffic to the write callback
- `CURLWS_NOAUTOPONG`: disable the automatic reply to PING frames (libcurl >= 8.14)

Other symbols

The sections above cover the option values supported by handle_setopt(). Use curl_symbols() was previously used to lookup the value of any symbol from the libcurl symbol table, along with the libcurl version in which it was introduced, deprecated, or removed.

See Also

handle_setopt()

Examples

```
# Available options
curl_options()

# List proxy options
curl_options("proxy")
# Curl/ssl version info
curl_version()
# Set options using symbolic constants
h <- new_handle()
handle_setopt(h, http_version = CURL_HTTP_VERSION_1_1)
handle_setopt(h, httpauth = CURLAUTH_BASIC + CURLAUTH_DIGEST)
```

---

curl_parse_url *Normalizing URL parser*

Description

Interfaces the libcurl URL parser. URLs are automatically normalized where possible, such as in the case of relative paths or url-encoded queries (see examples). When parsing hyperlinks from a HTML document, it is possible to set baseurl to the location of the document itself such that relative links can be resolved.

Usage

```
curl_parse_url(
  url,
  baseurl = NULL,
  decode = TRUE,
  params = TRUE,
  default_scheme = FALSE
)

curl_modify_url(
  url = NULL,
  scheme = NULL,
  host = NULL,
```

```
  port = NULL,
  path = NULL,
  query = NULL,
  fragment = NULL,
  user = NULL,
  password = NULL,
  params = NULL
)
```

Arguments

`url`	either URL string or list returned by curl_parse_url. Use this to modify a URL using the other parameters.
`baseurl`	use this as the parent if `url` may be a relative path
`decode`	automatically url-decode output into the actual values. If set to `FALSE`, values for `query`, `path`, `fragment`, `user` and `password` are returned in url-encoded format.
`params`	named character vector with http GET parameters. This will automatically be converted to `application/x-www-form-urlencoded` and override `query`,
`default_scheme`	when `url` is provided without a scheme prefix, assume `https://`.
`scheme`	string with e.g. `https`. Required if no `url` parameter was given.
`host`	string with hostname. Required if no `url` parameter was given.
`port`	string or number with port, e.g. `"443"`.
`path`	piece of the url starting with `/` up till `?` or `#`
`query`	piece of url starting with `?` up till `#`. Only used if no `params` is given.
`fragment`	part of url starting with `#`.
`user`	string with username
`password`	string with password

Details

A valid URL contains at least a scheme and a host, other pieces are optional. If these are missing, the parser raises an error. Otherwise it returns a list with the following elements:

- *url*: the normalized input URL
- *scheme*: the protocol part before the `://` (required)
- *host*: name of host without port (required)
- *port*: decimal between 0 and 65535
- *path*: normalized path up till the ? of the url
- *query*: search query: part between the ? and # of the url. Use `params` below to get individual parameters from the query.
- *fragment*: the hash part after the # of the url
- *user*: authentication username

- *password*: authentication password
- *params*: named vector with parameters from `query` if set

Each element above is either a string or `NULL`, except for `params` which is always a character vector with the length equal to the number of parameters.

Note that the `params` field is only usable if the `query` is in the usual `application/x-www-form-urlencoded` format which is technically not part of the RFC. Some services may use e.g. a json blob as the query, in which case the parsed `params` field here can be ignored. There is no way for the parser to automatically infer or validate the query format, this is up to the caller.

For more details on the URL format see rfc3986 or the steps explained in the whatwg basic url parser.

You can use `curl_modify_url()` both to modify an existing URL, or to create new URL from scratch. Arguments get automatically URL-encoded where needed, unless wrapped in `I()`. If `params` is given, this gets converted into a `application/x-www-form-urlencoded` string which overrides `query`. When modifying a URL, use an empty string `""` to unset a piece of the URL.

Examples

```
url <- "https://jerry:secret@google.com:888/foo/bar?test=123#bla"
curl_parse_url(url)

# Resolve relative links from a baseurl
curl_parse_url("/somelink", baseurl = url)

# Paths get normalized
curl_parse_url("https://foobar.com/foo/bar/../baz/../yolo")$url

# Also normalizes URL-encoding (these URLs are equivalent):
url1 <- "https://ja.wikipedia.org/wiki/\u5bff\u53f8"
url2 <- "https://ja.wikipedia.org/wiki/%e5%af%bf%e5%8f%b8"
curl_parse_url(url1)$path
curl_parse_url(url2)$path
curl_parse_url(url1, decode = FALSE)$path
curl_parse_url(url1, decode = FALSE)$path
```

---

curl_upload *Upload a File*

Description

Upload a file to an `http://`, `ftp://`, or `sftp://` (ssh) server. Uploading to HTTP means performing an `HTTP PUT` on that URL. Be aware that sftp is only available for libcurl clients built with libssh2.

Usage

```
curl_upload(file, url, verbose = TRUE, reuse = TRUE, ...)
```

Arguments

file	connection object or path to an existing file on disk
url	where to upload, should start with e.g. ftp://
verbose	emit some progress output
reuse	try to keep alive and recycle connections when possible
...	other arguments passed to handle_setopt(), for example a username and password.

Examples

```
## Not run: # Upload package to winbuilder:
curl_upload('mypkg_1.3.tar.gz', 'ftp://win-builder.r-project.org/R-devel/')

## End(Not run)
```

---

file_writer *Lazy File Writer*

Description

Generates a closure that writes binary (raw) data to a file.

Usage

```
file_writer(path, append = FALSE)
```

Arguments

path	file name or path on disk
append	open file in append mode

Details

The writer function automatically opens the file on the first write and closes when it goes out of scope, or explicitly by setting close = TRUE. This can be used for the data callback in multi_add() or curl_fetch_multi() such that we only keep open file handles for active downloads. This prevents running out of file descriptors when performing thousands of concurrent requests.

Value

Function with signature writer(data = raw(), close = FALSE)

Examples

```
# Doesn't open yet
tmp <- tempfile()
writer <- file_writer(tmp)

# Now it opens
writer(charToRaw("Hello!\n"))
writer(charToRaw("How are you?\n"))

# Close it!
writer(charToRaw("All done!\n"), close = TRUE)

# Check it worked
readLines(tmp)
```

---

handle *Create and configure a curl handle*

Description

Handles are the work horses of libcurl. A handle is used to configure a request with custom options, headers and payload. Once the handle has been set up, it can be passed to any of the download functions such as `curl()` ,`curl_download()` or `curl_fetch_memory()`. The handle will maintain state in between requests, including keep-alive connections, cookies and settings.

Usage

```
new_handle(...)

handle_setopt(handle, ..., .list = list())

handle_setheaders(handle, ..., .list = list())

handle_getheaders(handle)

handle_setform(handle, ..., .list = list())

handle_reset(handle)
```

Arguments

`...`	named options / headers to be set in the handle. To send a file, see `form_file()`. To list all allowed options, see `curl_options()`
`handle`	Handle to modify
`.list`	A named list of options. This is useful if you've created a list of options elsewhere, avoiding the use of `do.call()`.

Details

Use `new_handle()` to create a new clean curl handle that can be configured with custom options and headers. Note that `handle_setopt` appends or overrides options in the handle, whereas `handle_setheaders` replaces the entire set of headers with the new ones. The `handle_reset` function resets only options/headers/forms in the handle. It does not affect active connections, cookies or response data from previous requests. The safest way to perform multiple independent requests is by using a separate handle for each request. There is very little performance overhead in creating handles.

The handle_setform function is used to perform a `multipart/form-data` HTTP POST request (a.k.a. posting a form). The form fields can be specified as strings, raw vectors (for binary data), or form_file and form_data for upload elements. See the examples.

Value

A handle object (external pointer to the underlying curl handle). All functions modify the handle in place but also return the handle so you can create a pipeline of operations.

See Also

Other handles: `handle_cookies()`

Examples

```
h <- new_handle()
handle_setopt(h, customrequest = "PUT")
handle_setform(h, a = "1", b = "2")
r <- curl_fetch_memory("https://hb.cran.dev/put", h)
cat(rawToChar(r$content))

# Or use the list form
h <- new_handle()
handle_setopt(h, .list = list(customrequest = "PUT"))
handle_setform(h, .list = list(a = "1", b = "2"))
r <- curl_fetch_memory("https://hb.cran.dev/put", h)
cat(rawToChar(r$content))

# Posting multipart forms
h <- new_handle()
handle_setform(h,
  foo = "blabla",
  bar = charToRaw("boeboe"),
  iris = form_data(serialize(iris, NULL), "application/rda"),
  description = form_file(system.file("DESCRIPTION")),
  logo = form_file(file.path(R.home('doc'), "html/logo.jpg"), "image/jpeg")
)
req <- curl_fetch_memory("https://hb.cran.dev/post", handle = h)
```

handle_cookies *Extract cookies from a handle*

Description

The handle_cookies function returns a data frame with 7 columns as specified in the netscape cookie file format.

Usage

```
handle_cookies(handle)
```

Arguments

handle	a curl handle object

See Also

Other handles: handle

Examples

```
h <- new_handle()
handle_cookies(h)

# Server sets cookies
req <- curl_fetch_memory("https://hb.cran.dev/cookies/set?foo=123&bar=ftw", handle = h)
handle_cookies(h)

# Server deletes cookies
req <- curl_fetch_memory("https://hb.cran.dev/cookies/delete?foo", handle = h)
handle_cookies(h)

# Cookies will survive a reset!
handle_reset(h)
handle_cookies(h)
```

ie_proxy *Internet Explorer proxy settings*

Description

Lookup and mimic the system proxy settings on Windows as set by Internet Explorer. This can be used to configure curl to use the same proxy server.

Usage

```
ie_proxy_info()

ie_get_proxy_for_url(target_url = "http://www.google.com")
```

Arguments

target_url	url with host for which to lookup the proxy server

Details

The ie_proxy_info function looks up your current proxy settings as configured in IE under "Internet Options" under "LAN Settings". The ie_get_proxy_for_url determines if and which proxy should be used to connect to a particular URL. If your settings have an "automatic configuration script" this involves downloading and executing a PAC file, which can take a while.

---

multi *Async Concurrent Requests*

Description

AJAX style concurrent requests, possibly using HTTP/2 multiplexing. Results are only available via callback functions. Advanced use only! For downloading many files in parallel use multi_download instead.

Usage

```
multi_add(handle, done = NULL, fail = NULL, data = NULL, pool = NULL)

multi_run(timeout = Inf, poll = FALSE, pool = NULL)

multi_set(
  total_con = 50,
  host_con = 6,
  max_streams = 10,
  multiplex = TRUE,
  pool = NULL
)

multi_list(pool = NULL)

multi_cancel(handle)

new_pool(total_con = 100, host_con = 6, max_streams = 10, multiplex = TRUE)

multi_fdset(pool = NULL)
```

Arguments

handle	a curl handle with preconfigured url option.
done	callback function for completed request. Single argument with response data in same structure as curl_fetch_memory.
fail	callback function called on failed request. Argument contains error message.
data	(advanced) callback function, file path, or connection object for writing incoming data. This callback should only be used for *streaming* applications, where small pieces of incoming data get written before the request has completed. The signature for the callback function is write(data, final = FALSE). If set to NULL the entire response gets buffered internally and returned by in the done callback (which is usually what you want).
pool	a multi handle created by new_pool. Default uses a global pool.
timeout	max time in seconds to wait for results. Use 0 to poll for results without waiting at all.
poll	If TRUE then return immediately after any of the requests has completed. May also be an integer in which case it returns after n requests have completed.
total_con	max total concurrent connections.
host_con	max concurrent connections per host.
max_streams	max HTTP/2 concurrent multiplex streams per connection.
multiplex	use HTTP/2 multiplexing if supported by host and client.

Details

Requests are created in the usual way using a curl handle and added to the scheduler with multi_add. This function returns immediately and does not perform the request yet. The user needs to call multi_run which performs all scheduled requests concurrently. It returns when all requests have completed, or case of a timeout or SIGINT (e.g. if the user presses ESC or CTRL+C in the console). In case of the latter, simply call multi_run again to resume pending requests.

When the request succeeded, the done callback gets triggered with the response data. The structure if this data is identical to curl_fetch_memory. When the request fails, the fail callback is triggered with an error message. Note that failure here means something went wrong in performing the request such as a connection failure, it does not check the http status code. Just like curl_fetch_memory, the user has to implement application logic.

Raising an error within a callback function stops execution of that function but does not affect other requests.

A single handle cannot be used for multiple simultaneous requests. However it is possible to add new requests to a pool while it is running, so you can re-use a handle within the callback of a request from that same handle. It is up to the user to make sure the same handle is not used in concurrent requests.

The multi_cancel function can be used to cancel a pending request. It has no effect if the request was already completed or canceled.

The multi_fdset function returns the file descriptors curl is polling currently, and also a timeout parameter, the number of milliseconds an application should wait (at most) before proceeding. It is equivalent to the curl_multi_fdset and curl_multi_timeout calls. It is handy for applications that is expecting input (or writing output) through both curl, and other file descriptors.

See Also

Advanced download interface: multi_download

Examples

```
results <- list()
success <- function(x){
  results <<- append(results, list(x))
}
failure <- function(str){
  cat(paste("Failed request:", str), file = stderr())
}
# This handle will take longest (3sec)
h1 <- new_handle(url = "https://hb.cran.dev/delay/3")
multi_add(h1, done = success, fail = failure)

# This handle writes data to a file
con <- file("output.txt")
h2 <- new_handle(url = "https://hb.cran.dev/post", postfields = "bla bla")
multi_add(h2, done = success, fail = failure, data = con)

# This handle raises an error
h3 <- new_handle(url = "https://urldoesnotexist.xyz")
multi_add(h3, done = success, fail = failure)

# Actually perform the requests
multi_run(timeout = 2)
multi_run()

# Check the file
readLines("output.txt")
unlink("output.txt")
```

---

multi_download *Advanced download interface*

Description

Download multiple files concurrently, with support for resuming large files. This function is based on multi_run() and hence does not error in case any of the individual requests fail; you should inspect the return value to find out which of the downloads were completed successfully.

Usage

```
multi_download(
  urls,
  destfiles = NULL,
  resume = FALSE,
  progress = TRUE,
```

```
  multi_timeout = Inf,
  multiplex = TRUE,
  ...
)
```

Arguments

urls	vector with URLs to download. Alternatively it may also be a list of handle objects that have the url option already set.
destfiles	vector (of equal length as urls) with paths of output files, or NULL to use basename of urls.
resume	if the file already exists, resume the download. Note that this may change server responses, see details.
progress	print download progress information
multi_timeout	in seconds, passed to multi_run
multiplex	passed to new_pool
...	extra handle options passed to each request new_handle

Details

Upon completion of all requests, this function returns a data frame with results. The success column indicates if a request was successfully completed (regardless of the HTTP status code). If it failed, e.g. due to a networking issue, the error message is in the error column. A success value NA indicates that the request was still in progress when the function was interrupted or reached the elapsed multi_timeout and perhaps the download can be resumed if the server supports it.

It is also important to inspect the status_code column to see if any of the requests were successful but had a non-success HTTP code, and hence the downloaded file probably contains an error page instead of the requested content.

Note that when you set resume = TRUE you should expect HTTP-206 or HTTP-416 responses. The latter could indicate that the file was already complete, hence there was no content left to resume from the server. If you try to resume a file download but the server does not support this, success if FALSE and the file will not be touched. In fact, if we request to a download to be resumed and the server responds HTTP 200 instead of HTTP 206, libcurl will error and not download anything, because this probably means the server did not respect our range request and is sending us the full file.

About HTTP/2:

Availability of HTTP/2 can increase the performance when making many parallel requests to a server, because HTTP/2 can multiplex many requests over a single TCP connection. Support for HTTP/2 depends on the version of libcurl that your system has, and the TLS back-end that is in use, check curl_version. For clients or servers without HTTP/2, curl makes at most 6 connections per host over which it distributes the queued downloads.

On Windows and MacOS you can switch the active TLS backend by setting an environment variable CURL_SSL_BACKEND in your ~/.Renviron file. On Windows you can switch between SecureChannel (default) and OpenSSL where only the latter supports HTTP/2. On MacOS you can use either SecureTransport or LibreSSL, the default varies by MacOS version.

Value

The function returns a data frame with one row for each downloaded file and the following columns:

- `success` if the HTTP request was successfully performed, regardless of the response status code. This is `FALSE` in case of a network error, or in case you tried to resume from a server that did not support this. A value of `NA` means the download was interrupted while in progress.
- `status_code` the HTTP status code from the request. A successful download is usually `200` for full requests or `206` for resumed requests. Anything else could indicate that the downloaded file contains an error page instead of the requested content.
- `resumefrom` the file size before the request, in case a download was resumed.
- `url` final url (after redirects) of the request.
- `destfile` downloaded file on disk.
- `error` if `success == FALSE` this column contains an error message.
- `type` the `Content-Type` response header value.
- `modified` the `Last-Modified` response header value.
- `time` total elapsed download time for this file in seconds.
- `headers` vector with http response headers for the request.

Examples

```
## Not run:
# Example: some large files
urls <- sprintf(
  "https://d37ci6vzurychx.cloudfront.net/trip-data/yellow_tripdata_2021-%02d.parquet", 1:12)
res <- multi_download(urls, resume = TRUE) # You can interrupt (ESC) and resume

# Example: revdep checker
# Download all reverse dependencies for the 'curl' package from CRAN:
pkg <- 'curl'
mirror <- 'https://cloud.r-project.org'
db <- available.packages(repos = mirror)
packages <- c(pkg, tools::package_dependencies(pkg, db = db, reverse = TRUE)[[pkg]])
versions <- db[packages,'Version']
urls <- sprintf("%s/src/contrib/%s_%s.tar.gz", mirror, packages,  versions)
res <- multi_download(urls)
all.equal(unname(tools::md5sum(res$destfile)), unname(db[packages, 'MD5sum']))
# And then you could use e.g.: tools:::check_packages_in_dir()

# Example: URL checker
pkg_url_checker <- function(dir){
  db <- tools:::url_db_from_package_sources(dir)
  res <- multi_download(db$URL, rep('/dev/null', nrow(db)), nobody=TRUE)
  db$OK <- res$status_code == 200
  db
}

# Use a local package source directory
pkg_url_checker(".")
```

```
## End(Not run)
```

`multipart` *POST files or data*

Description

Build multipart form data elements. The `form_file` function uploads a file. The `form_data` function allows for posting a string or raw vector with a custom content-type.

Usage

```
form_file(path, type = NULL, name = NULL)

form_data(value, type = NULL)
```

Arguments

`path`	a string with a path to an existing file on disk
`type`	MIME content-type of the file.
`name`	a string with the file name to use for the upload
`value`	a character or raw vector to post

`nslookup` *Lookup a hostname*

Description

The `nslookup` function is similar to `nsl` but works on all platforms and can resolve ipv6 addresses if supported by the OS. Default behavior raises an error if lookup fails.

Usage

```
nslookup(host, ipv4_only = FALSE, multiple = FALSE, error = TRUE)

has_internet()
```

Arguments

`host`	a string with a hostname
`ipv4_only`	always return ipv4 address. Set to `FALSE` to allow for ipv6 as well.
`multiple`	returns multiple ip addresses if possible
`error`	raise an error for failed DNS lookup. Otherwise returns `NULL`.

Details

The has_internet function tests for internet connectivity by performing a dns lookup. If a proxy server is detected, it will also check for connectivity by connecting via the proxy.

Examples

```
# Should always work if we are online
nslookup("www.google.com")

# If your OS supports IPv6
nslookup("ipv6.test-ipv6.com", ipv4_only = FALSE, error = FALSE)
```

---

parse_date *Parse date/time*

Description

Can be used to parse dates appearing in http response headers such as Expires or Last-Modified. Automatically recognizes most common formats. If the format is known, strptime() might be easier.

Usage

```
parse_date(datestring)
```

Arguments

datestring	a string consisting of a timestamp

Examples

```
# Parse dates in many formats
parse_date("Sunday, 06-Nov-94 08:49:37 GMT")
parse_date("06 Nov 1994 08:49:37")
parse_date("20040911 +0200")
```

---

parse_headers *Parse response headers*

Description

Parse response header data as returned by curl_fetch, either as a set of strings or into a named list.

Usage

```
parse_headers(txt, multiple = FALSE)

parse_headers_list(txt)
```

Arguments

`txt`	raw or character vector with the header data
`multiple`	parse multiple sets of headers separated by a blank line. See details.

Details

The parse_headers_list function parses the headers into a normalized (lowercase field names, trimmed whitespace) named list.

If a request has followed redirects, the data can contain multiple sets of headers. When multiple = TRUE, the function returns a list with the response headers for each request. By default it only returns the headers of the final request.

Examples

```
req <- curl_fetch_memory("https://hb.cran.dev/redirect/3")
parse_headers(req$headers)
parse_headers(req$headers, multiple = TRUE)

# Parse into named list
parse_headers_list(req$headers)
```

`send_mail` *Send email*

Description

Use the curl SMTP client to send an email. The `message` argument must be properly formatted RFC2822 email message with From/To/Subject headers and CRLF line breaks.

Usage

```
send_mail(
  mail_from,
  mail_rcpt,
  message,
  smtp_server = "smtp://localhost",
  use_ssl = c("try", "no", "force"),
  verbose = TRUE,
  ...
)
```

Arguments

`mail_from`	email address of the sender.
`mail_rcpt`	one or more recipient email addresses. Do not include names, these go into the `message` headers.

message	either a string or connection with (properly formatted) email message, including sender/recipient/subject headers. See example.
smtp_server	hostname or address of the SMTP server, or, an smtp:// or smtps:// URL. See "Specifying the server, port, and protocol" below.
use_ssl	Request to upgrade the connection to SSL using the STARTTLS command, see CURLOPT_USE_SSL for details. Default will try to SSL, proceed as normal otherwise.
verbose	print output
...	other options passed to handle_setopt(). In most cases you will need to set a username and password or login_options to authenticate with the SMTP server, see details.

Specifying the server, port, and protocol

The smtp_server argument takes a hostname, or an SMTP URL:

- mail.example.com - hostname only
- mail.example.com:587 - hostname and port
- smtp://mail.example.com - protocol and hostname
- smtp://mail.example.com:587 - full SMTP URL
- smtps://mail.example.com:465 - full SMTPS URL

By default, the port will be 25, unless smtps:// is specified–then the default will be 465 instead.

For internet SMTP servers you probably need to pass a username and passwords option. For some servers you also need to pass a string with login_options for example login_options="AUTH=NTLM".

Encrypting connections via SMTPS or STARTTLS

There are two different ways in which SMTP can be encrypted: SMTPS servers run on a port which only accepts encrypted connections, similar to HTTPS. Alternatively, a regular insecure smtp connection can be "upgraded" to a secure TLS connection using the STARTTLS command. It is important to know which method your server expects.

If your smtp server listens on port 465, then use a smtps://hostname:465 URL. The SMTPS protocol *guarantees* that TLS will be used to protect all communications from the start.

If your email server listens on port 25 or 587, use an smtp:// URL in combination with the use_ssl parameter to control if the connection should be upgraded with STARTTLS. The default value "try" will *opportunistically* try to upgrade to a secure connection if the server supports it, and proceed as normal otherwise.

Examples

```
## Not run: # Set sender and recipients (email addresses only)
recipients <- readline("Enter your email address to receive test: ")
sender <- 'test@noreply.com'

# Full email message in RFC2822 format
message <- 'From: "R (curl package)" <test@noreply.com>
```

```
To: "Roger Recipient" <roger@noreply.com>
Subject: Hello R user!

Dear R user,

I am sending this email using curl.'

# Send the email
send_mail(sender, recipients, message, smtp_server = 'smtps://smtp.gmail.com',
  username = 'curlpackage', password  = 'qyyjddvphjsrbnlm')
## End(Not run)
```

Index

∗ **handles**
    handle, 19
    handle_cookies, 21

basename, *25*

curl, 2
curl(), *19*
curl_download, 4
curl_download(), *19*
curl_echo, 5
curl_escape, 6
curl_fetch_disk *(*curl_fetch_memory*)*, 6
curl_fetch_echo *(*curl_fetch_memory*)*, 6
curl_fetch_memory, 6, *7*, *23*
curl_fetch_memory(), *19*
curl_fetch_multi *(*curl_fetch_memory*)*, 6
curl_fetch_stream *(*curl_fetch_memory*)*, 6
CURL_HTTP_VERSION_1_0 *(*curl_options*)*, 8
CURL_HTTP_VERSION_1_1 *(*curl_options*)*, 8
CURL_HTTP_VERSION_2 *(*curl_options*)*, 8
CURL_HTTP_VERSION_2_0 *(*curl_options*)*, 8
CURL_HTTP_VERSION_2_PRIOR_KNOWLEDGE *(*curl_options*)*, 8
CURL_HTTP_VERSION_2TLS *(*curl_options*)*, 8
CURL_HTTP_VERSION_3 *(*curl_options*)*, 8
CURL_HTTP_VERSION_3ONLY *(*curl_options*)*, 8
CURL_HTTP_VERSION_NONE *(*curl_options*)*, 8
CURL_IPRESOLVE_V4 *(*curl_options*)*, 8
CURL_IPRESOLVE_V6 *(*curl_options*)*, 8
CURL_IPRESOLVE_WHATEVER *(*curl_options*)*, 8
curl_modify_url *(*curl_parse_url*)*, 15
curl_modify_url(), *17*
CURL_NETRC_IGNORED *(*curl_options*)*, 8
CURL_NETRC_OPTIONAL *(*curl_options*)*, 8
CURL_NETRC_REQUIRED *(*curl_options*)*, 8
curl_options, 8
curl_options(), *19*
curl_options_table *(*curl_options*)*, 8
curl_parse_url, 15, *16*
CURL_REDIR_GET_ALL *(*curl_options*)*, 8
CURL_REDIR_POST_301 *(*curl_options*)*, 8
CURL_REDIR_POST_302 *(*curl_options*)*, 8
CURL_REDIR_POST_303 *(*curl_options*)*, 8
CURL_REDIR_POST_ALL *(*curl_options*)*, 8
CURL_SSLVERSION_DEFAULT *(*curl_options*)*, 8
CURL_SSLVERSION_MAX_DEFAULT *(*curl_options*)*, 8
CURL_SSLVERSION_MAX_NONE *(*curl_options*)*, 8
CURL_SSLVERSION_MAX_TLSv1_0 *(*curl_options*)*, 8
CURL_SSLVERSION_MAX_TLSv1_1 *(*curl_options*)*, 8
CURL_SSLVERSION_MAX_TLSv1_2 *(*curl_options*)*, 8
CURL_SSLVERSION_MAX_TLSv1_3 *(*curl_options*)*, 8
CURL_SSLVERSION_TLSv1 *(*curl_options*)*, 8
CURL_SSLVERSION_TLSv1_0 *(*curl_options*)*, 8
CURL_SSLVERSION_TLSv1_1 *(*curl_options*)*, 8
CURL_SSLVERSION_TLSv1_2 *(*curl_options*)*, 8
CURL_SSLVERSION_TLSv1_3 *(*curl_options*)*, 8
curl_symbols *(*curl_options*)*, 8
CURL_TIMECOND_IFMODSINCE *(*curl_options*)*, 8
CURL_TIMECOND_IFUNMODSINCE *(*curl_options*)*, 8
CURL_TIMECOND_LASTMOD *(*curl_options*)*, 8
CURL_TIMECOND_NONE *(*curl_options*)*, 8
curl_unescape *(*curl_escape*)*, 6
curl_upload, 17

curl_version, *25*
curl_version *(curl_options)*, 8
CURLALTSVC_H1 *(curl_options)*, 8
CURLALTSVC_H2 *(curl_options)*, 8
CURLALTSVC_H3 *(curl_options)*, 8
CURLALTSVC_READONLYFILE *(curl_options)*, 8
CURLAUTH_ANY *(curl_options)*, 8
CURLAUTH_ANYSAFE *(curl_options)*, 8
CURLAUTH_AWS_SIGV4 *(curl_options)*, 8
CURLAUTH_BASIC *(curl_options)*, 8
CURLAUTH_BEARER *(curl_options)*, 8
CURLAUTH_DIGEST *(curl_options)*, 8
CURLAUTH_DIGEST_IE *(curl_options)*, 8
CURLAUTH_GSSAPI *(curl_options)*, 8
CURLAUTH_NEGOTIATE *(curl_options)*, 8
CURLAUTH_NONE *(curl_options)*, 8
CURLAUTH_NTLM *(curl_options)*, 8
CURLAUTH_ONLY *(curl_options)*, 8
CURLFOLLOW_ALL *(curl_options)*, 8
CURLFOLLOW_FIRSTONLY *(curl_options)*, 8
CURLFOLLOW_OBEYCODE *(curl_options)*, 8
CURLFTP_CREATE_DIR *(curl_options)*, 8
CURLFTP_CREATE_DIR_NONE *(curl_options)*, 8
CURLFTP_CREATE_DIR_RETRY *(curl_options)*, 8
CURLFTPAUTH_DEFAULT *(curl_options)*, 8
CURLFTPAUTH_SSL *(curl_options)*, 8
CURLFTPAUTH_TLS *(curl_options)*, 8
CURLFTPMETHOD_DEFAULT *(curl_options)*, 8
CURLFTPMETHOD_MULTICWD *(curl_options)*, 8
CURLFTPMETHOD_NOCWD *(curl_options)*, 8
CURLFTPMETHOD_SINGLECWD *(curl_options)*, 8
CURLFTPSSL_CCC_ACTIVE *(curl_options)*, 8
CURLFTPSSL_CCC_NONE *(curl_options)*, 8
CURLFTPSSL_CCC_PASSIVE *(curl_options)*, 8
CURLGSSAPI_DELEGATION_FLAG *(curl_options)*, 8
CURLGSSAPI_DELEGATION_NONE *(curl_options)*, 8
CURLGSSAPI_DELEGATION_POLICY_FLAG *(curl_options)*, 8
CURLHEADER_SEPARATE *(curl_options)*, 8
CURLHEADER_UNIFIED *(curl_options)*, 8
CURLHSTS_ENABLE *(curl_options)*, 8
CURLHSTS_READONLYFILE *(curl_options)*, 8
CURLMIMEOPT_FORMESCAPE *(curl_options)*, 8
CURLPROXY_HTTP *(curl_options)*, 8
CURLPROXY_HTTP_1_0 *(curl_options)*, 8
CURLPROXY_HTTPS *(curl_options)*, 8
CURLPROXY_HTTPS2 *(curl_options)*, 8
CURLPROXY_SOCKS4 *(curl_options)*, 8
CURLPROXY_SOCKS4A *(curl_options)*, 8
CURLPROXY_SOCKS5 *(curl_options)*, 8
CURLPROXY_SOCKS5_HOSTNAME *(curl_options)*, 8
CURLSSH_AUTH_AGENT *(curl_options)*, 8
CURLSSH_AUTH_ANY *(curl_options)*, 8
CURLSSH_AUTH_DEFAULT *(curl_options)*, 8
CURLSSH_AUTH_GSSAPI *(curl_options)*, 8
CURLSSH_AUTH_HOST *(curl_options)*, 8
CURLSSH_AUTH_KEYBOARD *(curl_options)*, 8
CURLSSH_AUTH_NONE *(curl_options)*, 8
CURLSSH_AUTH_PASSWORD *(curl_options)*, 8
CURLSSH_AUTH_PUBLICKEY *(curl_options)*, 8
CURLSSLOPT_ALLOW_BEAST *(curl_options)*, 8
CURLSSLOPT_AUTO_CLIENT_CERT *(curl_options)*, 8
CURLSSLOPT_NATIVE_CA *(curl_options)*, 8
CURLSSLOPT_NO_PARTIALCHAIN *(curl_options)*, 8
CURLSSLOPT_NO_REVOKE *(curl_options)*, 8
CURLSSLOPT_REVOKE_BEST_EFFORT *(curl_options)*, 8
CURLUSESSL_ALL *(curl_options)*, 8
CURLUSESSL_CONTROL *(curl_options)*, 8
CURLUSESSL_NONE *(curl_options)*, 8
CURLUSESSL_TRY *(curl_options)*, 8
CURLWS_NOAUTOPONG *(curl_options)*, 8
CURLWS_RAW_MODE *(curl_options)*, 8

download.file(), *4*

file_writer, 18
find_port *(curl_echo)*, 5
form_data, *20*
form_data *(multipart)*, 27
form_file, *20*
form_file *(multipart)*, 27
form_file(), *19*

handle, 19, *21*, *23*, *25*
handle(), *2*, *4*
handle_cookies, 21
handle_cookies(), *20*

handle_data *(curl_fetch_memory)*, 6
handle_getheaders *(handle)*, 19
handle_reset *(handle)*, 19
handle_setform, *20*
handle_setform *(handle)*, 19
handle_setheaders *(handle)*, 19
handle_setopt *(handle)*, 19
handle_setopt(), *9*, *15*, *18*, *30*
has_internet *(nslookup)*, 27

ie_get_proxy_for_url, *22*
ie_get_proxy_for_url *(ie_proxy)*, 21
ie_proxy, 21
ie_proxy_info, *22*
ie_proxy_info *(ie_proxy)*, 21
isIncomplete(), *3*

multi, 22
multi_add, *23*
multi_add *(multi)*, 22
multi_add(), *7*
multi_cancel, *23*
multi_cancel *(multi)*, 22
multi_download, *4*, *22*, 24, *24*
multi_fdset, *23*
multi_fdset *(multi)*, 22
multi_list *(multi)*, 22
multi_run, *23*, *25*
multi_run *(multi)*, 22
multi_run(), *7*, *24*
multi_set *(multi)*, 22
multipart, 27

new_handle, *25*
new_handle *(handle)*, 19
new_pool, *7*, *23*, *25*
new_pool *(multi)*, 22
nslookup, 27

parse_date, 28
parse_headers, 28
parse_headers_list *(parse_headers)*, 28

send_mail, 29
strptime(), *28*

url(), *2*
url-decode, *16*