

# Package: diffeqr (via r-universe)

December 4, 2024

**Type** Package

**Title** Solving Differential Equations (ODEs, SDEs, DDEs, DAEs)

**Version** 2.1.0

**Description** An interface to 'DifferentialEquations.jl'

<<https://diffeq.sciml.ai/dev/>> from the R programming language.

It has unique high performance methods for solving ordinary differential equations (ODE), stochastic differential equations (SDE), delay differential equations (DDE), differential-algebraic equations (DAE), and more. Much of the functionality, including features like adaptive time stepping in SDEs, are unique and allow for multiple orders of magnitude speedup over more common methods. Supports GPUs, with support for CUDA (NVIDIA), AMD GPUs, Intel oneAPI GPUs, and Apple's Metal (M-series chip GPUs). 'diffeqr' attaches an R interface onto the package, allowing seamless use of this tooling by R users. For more information, see Rackauckas and Nie (2017) <[doi:10.5334/jors.151](https://doi.org/10.5334/jors.151)>.

**Depends** R (>= 3.4.0)

**Encoding** UTF-8

**License** MIT + file LICENSE

**URL** <https://github.com/SciML/diffeqr>

**SystemRequirements** Julia (>= 1.6), DifferentialEquations.jl, ModelingToolkit.jl

**Imports** JuliaCall

**RoxygenNote** 7.1.1

**Suggests** testthat, knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Christopher Rackauckas [aut, cre, cph]

**Maintainer** Christopher Rackauckas <[me@chrisrackauckas.com](mailto:me@chrisrackauckas.com)>

**Repository** CRAN

**Date/Publication** 2024-12-04 18:30:02 UTC

## Contents

diffeqgpu_setup . . . . .	2
diffeq_setup . . . . .	3
jitoptimize_ode . . . . .	3
jitoptimize_sde . . . . .	4
<b>Index</b>	<b>6</b>

---

diffeqgpu_setup	<i>Setup DiffEqGPU</i>
-----------------	------------------------

---

## Description

This function initializes the DiffEqGPU package for GPU-parallelized ensembles. The first time will be long since it includes precompilation.

## Usage

```
diffeqgpu_setup(backend)
```

## Arguments

backend            the backend for the GPU computation. Choices are "CUDA", "AMDGPU", "Metal", or "oneAPI"

## Value

Returns a degpu object which holds the module state of the Julia-side DiffEqGPU package. The core use is to use degpu\$EnsembleGPUKernel() for choosing the GPU dispatch in the solve.

## Examples

```
## Not run: ## diffeqgpu_setup() is time-consuming and requires Julia+DifferentialEquations.jl

degpu <- diffeqr::diffeqgpu_setup(backend)

## End(Not run)
```

---

diffeq\_setup

*Setup diffeqr*


---

**Description**

This function initializes Julia and the DifferentialEquations.jl package. The first time will be long since it includes precompilation. Additionally, this will install Julia and the required packages if they are missing.

**Usage**

```
diffeq_setup(pkg_check = TRUE, ...)
```

**Arguments**

pkg_check	logical, check for DifferentialEquations.jl package and install if necessary
...	Parameters are passed down to JuliaCall::julia_setup

**Value**

Returns the `de` object which gives R-side calls to DifferentialEquations.jl's functions. For example, `de$solve` calls the `DifferentialEquations.solve` function, and `de$ODEProblem` calls the `DifferentialEquations`.

**Examples**

```
## Not run: ## diffeq_setup() is time-consuming and requires Julia+DifferentialEquations.jl
diffeqr::diffeq_setup()

## End(Not run)
```

---

jitoptimize\_ode

*Jit Optimize an ODEProblem*


---

**Description**

This function JIT Optimizes and ODEProblem utilizing the Julia ModelingToolkit and JIT compiler.

**Usage**

```
jitoptimize_ode(de, prob)
```

**Arguments**

de                    the current diffeqr environment  
 prob                 an ODEProblem

**Value**

Returns an ODEProblem which has been JIT-optimized by Julia.

**Examples**

```
## Not run: ## diffeq_setup() is time-consuming and requires Julia+DifferentialEquations.jl
de <- diffeqr::diffeq_setup()
f <- function(u,p,t) {
  du1 = p[1]*(u[2]-u[1])
  du2 = u[1]*(p[2]-u[3]) - u[2]
  du3 = u[1]*u[2] - p[3]*u[3]
  return(c(du1,du2,du3))
}
u0 <- c(1.0,0.0,0.0)
tspan <- c(0.0,100.0)
p <- c(10.0,28.0,8/3)
prob <- de$ODEProblem(f, u0, tspan, p)
fastprob <- diffeqr::jitoptimize_ode(de,prob)
sol <- de$solve(fastprob,de$Tsit5())

## End(Not run)
```

---

jitoptimize\_sde

*Jit Optimize an SDEProblem*


---

**Description**

This function JIT Optimizes and SDEProblem utilizing the Julia ModelingToolkit and JIT compiler.

**Usage**

```
jitoptimize_sde(de, prob)
```

**Arguments**

de                    the current diffeqr environment  
 prob                 an SDEProblem

**Value**

Returns an SDEProblem which has been JIT-optimized by Julia.

**Examples**

```
## Not run: ## diffeq_setup() is time-consuming and requires Julia+DifferentialEquations.jl
diffeqr::diffeq_setup()

## End(Not run)
```

# Index

diffeq\_setup, 3  
diffeqgpu\_setup, 2  
  
jitooptimize\_ode, 3  
jitooptimize\_sde, 4