

Package: dtreg (via r-universe)

May 23, 2026

Title Interact with Data Type Registries and Create Machine-Readable Data

Version 1.1.2

Description You can load a schema from a DTR (data type registry) as an R object. Use this schema to write your data in JSON-LD (JavaScript Object Notation for Linked Data) format to make it machine readable.

License MIT + file LICENSE

URL <https://gitlab.com/TIBHannover/lki/knowledge-loom/dtreg-r>

BugReports <https://gitlab.com/TIBHannover/lki/knowledge-loom/dtreg-r/-/issues>

Depends R (>= 4.1.0)

Imports htr2, jsonlite, methods, R6, stringr

Suggests knitr, rmarkdown, sets, stats, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Olga Lezhnina [aut] (ORCID: <https://orcid.org/0000-0003-2237-7725>), Manuel Prinz [aut] (ORCID: <https://orcid.org/0000-0003-2151-4556>), Markus Stocker [aut, cre] (ORCID: <https://orcid.org/0000-0001-5492-3212>), Open Research Knowledge Graph Project and Contributors [cph]

Maintainer Markus Stocker <markus.stocker@tib.eu>

Repository <https://cran.r-universe.dev>

Date/Publication 2025-11-24 13:30:13 UTC

RemoteUrl <https://github.com/cran/dtreg>

RemoteRef HEAD

RemoteSha 5e161458c9fa19ffe498f9345416789f896e0386

Contents

load_datatype	2
show_fields	2
to_jsonld	3

Index	4
--------------	----------

load_datatype	<i>Load classes for a schema with the known identifier</i>
---------------	--

Description

Load a list of R6 classes for a schema identifier, such as an ePIC datatype DOI or an ORKG template URL. The classes contain information of the requested schema and nested schemata.

Usage

```
load_datatype(datatype_id)
```

Arguments

datatype_id A schema identifier, such as a DOI or a URL

Value

A list of R6 classes

Examples

```
dt <- dtreg::load_datatype("https://doi.org/21.T11969/aff130c76e68ead3862e")
```

show_fields	<i>Show schema fields</i>
-------------	---------------------------

Description

Show which fields of a schema can be used for creating an instance

Usage

```
show_fields(datatype)
```

Arguments

datatype An R6 class from dtreg::load_datatype

Value

A character vector of available fields

Examples

```
dt <- dtreg::load_datatype("https://doi.org/21.T11969/aff130c76e68ead3862e")
dtreg::show_fields(dt$data_item())
```

to_jsonld

Write an instance in JSON-LD format

Description

Write an instance of a schema-related class in JSON-LD format as a string

Usage

```
to_jsonld(instance)
```

Arguments

instance An instance of an R6 class

Value

JSON string in JSON-LD format

Examples

```
dt <- dtreg::load_datatype("https://doi.org/21.T11969/aff130c76e68ead3862e")
instance <- dt$data_item(label = "my_results")
result <- dtreg::to_jsonld(instance)
```

Index

`load_datatype`, 2

`show_fields`, 2

`to_jsonld`, 3