

# Package: duckdb (via r-universe)

October 16, 2024

**Title** DBI Package for the DuckDB Database Management System

**Version** 1.1.1

**Description** The DuckDB project is an embedded analytical data management system with support for the Structured Query Language (SQL). This package includes all of DuckDB and an R Database Interface (DBI) connector.

**License** MIT + file LICENSE

**URL** <https://r.duckdb.org/>, <https://github.com/duckdb/duckdb-r>

**BugReports** <https://github.com/duckdb/duckdb-r/issues>

**Depends** DBI, R (>= 3.6.0)

**Imports** methods, utils

**Suggests** adbcdrivermanager, arrow (>= 13.0.0), bit64, callr, clock, DBItest, dbplyr, dplyr, rlang, testthat, tibble, vctrs, withr

**Encoding** UTF-8

**RoxygenNote** 7.3.2.9000

**Config/build/compilation-database** true

**NeedsCompilation** yes

**Author** Hannes Mühleisen [aut]

(<<https://orcid.org/0000-0001-8552-0029>>), Mark Raasveldt [aut]

(<<https://orcid.org/0000-0001-5005-6844>>), Kirill Müller [cre]

(<<https://orcid.org/0000-0002-1416-3412>>), Stichting DuckDB

Foundation [cph], Apache Software Foundation [cph], PostgreSQL

Global Development Group [cph], The Regents of the University

of California [cph], Cameron Desrochers [cph], Victor Zverovich

[cph], RAD Game Tools [cph], Valve Software [cph], Rich

Geldreich [cph], Tenacious Software LLC [cph], The RE2 Authors

[cph], Google Inc. [cph], Facebook Inc. [cph], Steven G.

Johnson [cph], Jiahao Chen [cph], Tony Kelman [cph], Jonas

Fonseca [cph], Lukas Fittl [cph], Salvatore Sanfilippo [cph],

Art.sy, Inc. [cph], Oran Agra [cph], Redis Labs, Inc. [cph],

Melissa O'Neill [cph], PCG Project contributors [cph]

**Maintainer** Kirill Müller <kirill@cynkra.com>

**Repository** CRAN

**Date/Publication** 2024-10-16 14:00:02 UTC

## Contents

backend-duckdb . . . . .	2
duckdb . . . . .	3
duckdb_explain-class . . . . .	6
duckdb_get_substrait . . . . .	6
duckdb_get_substrait_json . . . . .	7
duckdb_prepare_substrait . . . . .	7
duckdb_prepare_substrait_json . . . . .	8
duckdb_read_csv . . . . .	9
duckdb_register . . . . .	10
duckdb_register_arrow . . . . .	11

**Index** **12**

---

backend-duckdb	<i>DuckDB SQL backend for dbplyr</i>
----------------	--------------------------------------

---

## Description

This is a SQL backend for dbplyr tailored to take into account DuckDB's possibilities. This mainly follows the backend for PostgreSQL, but contains more mapped functions.

`tbl_file()` is an experimental variant of `dbplyr::tbl()` to directly access files on disk. It is safer than `dbplyr::tbl()` because there is no risk of misinterpreting the request, and paths with special characters are supported.

`tbl_function()` is an experimental variant of `dbplyr::tbl()` to create a lazy table from a table-generating function, useful for reading nonstandard CSV files or other data sources. It is safer than `dbplyr::tbl()` because there is no risk of misinterpreting the query. See <https://duckdb.org/docs/data/overview> for details on data importing functions.

As an alternative, use `dbplyr::tbl(src, dbplyr::sql("SELECT ... FROM ..."))` for custom SQL queries.

`tbl_query()` is deprecated in favor of `tbl_function()`.

Use `simulate_duckdb()` with `lazy_frame()` to see simulated SQL without opening a DuckDB connection.

**Usage**

```
tbl_file(src, path, ..., cache = FALSE)

tbl_function(src, query, ..., cache = FALSE)

tbl_query(src, query, ...)

simulate_duckdb(...)
```

**Arguments**

src	A duckdb connection object
path	Path to existing Parquet, CSV or JSON file
...	Any parameters to be forwarded
cache	Enable object cache for Parquet files
query	SQL code, omitting the FROM clause

**Examples**

```
library(dplyr, warn.conflicts = FALSE)
con <- DBI::dbConnect(duckdb(), path = ":memory:")

db <- copy_to(con, data.frame(a = 1:3, b = letters[2:4]))

db %>%
  filter(a > 1) %>%
  select(b)

path <- tempfile(fileext = ".csv")
write.csv(data.frame(a = 1:3, b = letters[2:4]))

db_csv <- tbl_file(con, path)
db_csv %>%
  summarize(sum_a = sum(a))

db_csv_fun <- tbl_function(con, paste0("read_csv_auto('", path, "')"))
db_csv %>%
  count()

DBI::dbDisconnect(con, shutdown = TRUE)
```

**Description**

duckdb() creates or reuses a database instance.

duckdb\_shutdown() shuts down a database instance.

Return an `adbcdrivermanager::adbc_driver()` for use with Arrow Database Connectivity via the `adbcdrivermanager` package.

dbConnect() connects to a database instance.

dbDisconnect() closes a DuckDB database connection. The associated DuckDB database instance is shut down automatically, it is no longer necessary to set `shutdown = TRUE` or to call `duckdb_shutdown()`.

**Usage**

```
duckdb(
  dbdir = DBDIR_MEMORY,
  read_only = FALSE,
  bigint = "numeric",
  config = list()
)

duckdb_shutdown(drv)

duckdb_adbc()

## S4 method for signature 'duckdb_driver'
dbConnect(
  drv,
  dbdir = DBDIR_MEMORY,
  ...,
  debug = getOption("duckdb.debug", FALSE),
  read_only = FALSE,
  timezone_out = "UTC",
  tz_out_convert = c("with", "force"),
  config = list(),
  bigint = "numeric"
)

## S4 method for signature 'duckdb_connection'
dbDisconnect(conn, ..., shutdown = TRUE)
```

**Arguments**

<code>dbdir</code>	Location for database files. Should be a path to an existing directory in the file system. With the default (or <code>"</code> ), all data is kept in RAM.
<code>read_only</code>	Set to <code>TRUE</code> for read-only operation. For file-based databases, this is only applied when the database file is opened for the first time. Subsequent connections (via the same <code>drv</code> object or a <code>drv</code> object pointing to the same path) will silently ignore this flag.

bigint	How 64-bit integers should be returned. There are two options: "numeric" and "integer64". If "numeric" is selected, bigint integers will be treated as double/numeric. If "integer64" is selected, bigint integers will be set to bit64 encoding.
config	Named list with DuckDB configuration flags, see <a href="https://duckdb.org/docs/configuration/overview#configuration-reference">https://duckdb.org/docs/configuration/overview#configuration-reference</a> for the possible options. These flags are only applied when the database object is instantiated. Subsequent connections will silently ignore these flags.
drv	Object returned by duckdb()
...	Ignored
debug	Print additional debug information such as queries
timezone_out	The time zone returned to R, defaults to "UTC", which is currently the only timezone supported by duckdb. If you want to display datetime values in the local timezone, set to <code>Sys.timezone()</code> or "".
tz_out_convert	How to convert timestamp columns to the timezone specified in <code>timezone_out</code> . There are two options: "with", and "force". If "with" is chosen, the timestamp will be returned as it would appear in the specified time zone. If "force" is chosen, the timestamp will have the same clock time as the timestamp in the database, but with the new time zone.
conn	A <code>duckdb_connection</code> object
shutdown	Unused. The database instance is shut down automatically.

## Value

`duckdb()` returns an object of class `duckdb_driver`.

`dbDisconnect()` and `duckdb_shutdown()` are called for their side effect.

An object of class "adbcd\_driver"

`dbConnect()` returns an object of class `duckdb_connection`.

## Examples

```
library(adbcdrivermanager)
with_adbc(db <- adbc_database_init(duckdb_adbc()), {
  as.data.frame(read_adbc(db, "SELECT 1 as one;"))
})
```

```
drv <- duckdb()
con <- dbConnect(drv)
```

```
dbGetQuery(con, "SELECT 'Hello, world!'")
```

```
dbDisconnect(con)
duckdb_shutdown(drv)
```

```
# Shorter:
con <- dbConnect(duckdb())
dbGetQuery(con, "SELECT 'Hello, world!'")
dbDisconnect(con, shutdown = TRUE)
```

---

duckdb\_explain-class *DuckDB EXPLAIN query tree*

---

### Description

DuckDB EXPLAIN query tree

---

duckdb\_get\_substrait *Get the Substrait plan for a SQL query Transforms a SQL query into a raw vector containing the serialized Substrait query blob*

---

### Description

Get the Substrait plan for a SQL query Transforms a SQL query into a raw vector containing the serialized Substrait query blob

### Usage

```
duckdb_get_substrait(conn, query, enable_optimizer = TRUE)
```

### Arguments

conn	A DuckDB connection, created by <code>dbConnect()</code> .
query	The query string in SQL
enable_optimizer	Optional parameter to enable/disable query-optimizer. By default optimizer is enabled.

### Value

A raw vector containing the substrait protobuf blob

---

 duckdb\_get\_substrait\_json

*Get the Substrait plan for a SQL query in the JSON format Transforms a SQL query into a vector containing the serialized Substrait query JSON*

---

### Description

Get the Substrait plan for a SQL query in the JSON format Transforms a SQL query into a vector containing the serialized Substrait query JSON

### Usage

```
duckdb_get_substrait_json(conn, query, enable_optimizer = TRUE)
```

### Arguments

conn	A DuckDB connection, created by dbConnect().
query	The query string in SQL
enable_optimizer	Optional parameter to enable/disable query-optimizer. By default optimizer is enabled.

### Value

A vector containing the substrait protobuf JSON

---

duckdb\_prepare\_substrait

*Query DuckDB using Substrait Method for interpreting a Substrait BLOB plan as a DuckDB Query Plan It interprets and executes the query.*

---

### Description

Query DuckDB using Substrait Method for interpreting a Substrait BLOB plan as a DuckDB Query Plan It interprets and executes the query.

### Usage

```
duckdb_prepare_substrait(conn, query, arrow = FALSE)
```

**Arguments**

conn	A DuckDB connection, created by <code>dbConnect()</code> .
query	The Protobuf-encoded Substrait Query Plan. Qack!
arrow	Whether the result should be in Arrow format

**Value**

A DuckDB Query Result

---

duckdb\_prepare\_substrait\_json

*Query DuckDB using Substrait Method for interpreting a Substrait JSON plan as a DuckDB Query Plan It interprets and executes the query.*

---

**Description**

Query DuckDB using Substrait Method for interpreting a Substrait JSON plan as a DuckDB Query Plan It interprets and executes the query.

**Usage**

```
duckdb_prepare_substrait_json(conn, json, arrow = FALSE)
```

**Arguments**

conn	A DuckDB connection, created by <code>dbConnect()</code> .
json	The Json Query Plan. Qack!
arrow	Whether the result should be in Arrow format

**Value**

A DuckDB Query Result



---

duckdb_read_csv	<i>Reads a CSV file into DuckDB</i>
-----------------	-------------------------------------

---

### Description

Directly reads a CSV file into DuckDB, tries to detect and create the correct schema for it. This usually is much faster than reading the data into R and writing it to DuckDB.

### Usage

```
duckdb_read_csv(
  conn,
  name,
  files,
  ...,
  header = TRUE,
  na.strings = "",
  nrow.check = 500,
  delim = ",",
  quote = "\"",
  col.names = NULL,
  lower.case.names = FALSE,
  sep = delim,
  transaction = TRUE,
  temporary = FALSE
)
```

### Arguments

conn	A DuckDB connection, created by <code>dbConnect()</code> .
name	The name for the virtual table that is registered or unregistered
files	One or more CSV file names, should all have the same structure though
...	Reserved for future extensions, must be empty.
header	Whether or not the CSV files have a separate header in the first line
na.strings	Which strings in the CSV files should be considered to be NULL
nrow.check	How many rows should be read from the CSV file to figure out data types
delim	Which field separator should be used
quote	Which quote character is used for columns in the CSV file
col.names	Override the detected or generated column names
lower.case.names	Transform column names to lower case
sep	Alias for <code>delim</code> for compatibility
transaction	Should a transaction be used for the entire operation
temporary	Set to TRUE to create a temporary table

**Value**

The number of rows in the resulted table, invisibly.

**Examples**

```
con <- dbConnect(duckdb())

data <- data.frame(a = 1:3, b = letters[1:3])
path <- tempfile(fileext = ".csv")

write.csv(data, path, row.names = FALSE)

duckdb_read_csv(con, "data", path)
dbReadTable(con, "data")

dbDisconnect(con)
```

---

duckdb_register	<i>Register a data frame as a virtual table</i>
-----------------	-------------------------------------------------

---

**Description**

duckdb\_register() registers a data frame as a virtual table (view) in a DuckDB connection. No data is copied.

**Usage**

```
duckdb_register(conn, name, df, overwrite = FALSE, experimental = FALSE)

duckdb_unregister(conn, name)
```

**Arguments**

conn	A DuckDB connection, created by dbConnect().
name	The name for the virtual table that is registered or unregistered
df	A data.frame with the data for the virtual table
overwrite	Should an existing registration be overwritten?
experimental	Enable experimental optimizations

**Details**

duckdb\_unregister() unregisters a previously registered data frame.

**Value**

These functions are called for their side effect.

**Examples**

```
con <- dbConnect(duckdb())

data <- data.frame(a = 1:3, b = letters[1:3])

duckdb_register(con, "data", data)
dbReadTable(con, "data")

duckdb_unregister(con, "data")

dbDisconnect(con)
```

---

duckdb\_register\_arrow *Register an Arrow data source as a virtual table*

---

**Description**

duckdb\_register\_arrow() registers an Arrow data source as a virtual table (view) in a DuckDB connection. No data is copied.

**Usage**

```
duckdb_register_arrow(conn, name, arrow_scannable, use_async = NULL)

duckdb_unregister_arrow(conn, name)

duckdb_list_arrow(conn)
```

**Arguments**

conn	A DuckDB connection, created by dbConnect().
name	The name for the virtual table that is registered or unregistered
arrow_scannable	A scannable Arrow-object
use_async	Switched to the asynchronous scanner. (deprecated)

**Details**

duckdb\_unregister\_arrow() unregisters a previously registered data frame.

**Value**

These functions are called for their side effect.

# Index

`adbcdrivermanager::adbc_driver()`, 4

`backend-duckdb`, 2

`dbConnect`, `duckdb_driver`-method  
(`duckdb`), 3

`dbConnect__duckdb_driver` (`duckdb`), 3

`dbDisconnect`, `duckdb_connection`-method  
(`duckdb`), 3

`dbDisconnect__duckdb_connection`  
(`duckdb`), 3

`dplyr::tbl()`, 2

`duckdb`, 3

`duckdb_adbc` (`duckdb`), 3

`duckdb_connection`, 5

`duckdb_driver`, 5

`duckdb_explain` (`duckdb_explain-class`), 6

`duckdb_explain-class`, 6

`duckdb_get_substrait`, 6

`duckdb_get_substrait_json`, 7

`duckdb_list_arrow`  
(`duckdb_register_arrow`), 11

`duckdb_prepare_substrait`, 7

`duckdb_prepare_substrait_json`, 8

`duckdb_read_csv`, 9

`duckdb_register`, 10

`duckdb_register_arrow`, 11

`duckdb_shutdown` (`duckdb`), 3

`duckdb_unregister` (`duckdb_register`), 10

`duckdb_unregister_arrow`  
(`duckdb_register_arrow`), 11

`print.duckdb_explain`  
(`duckdb_explain-class`), 6

`simulate_duckdb` (`backend-duckdb`), 2

`Sys.timezone()`, 5

`tbl_file` (`backend-duckdb`), 2

`tbl_function` (`backend-duckdb`), 2

`tbl_query` (`backend-duckdb`), 2