

# Package: dyncomp (via r-universe)

September 5, 2024

**Type** Package

**Title** Complexity of Short and Coarse-Grained Time Series

**Version** 0.0.2-1

**Author** Tim Kaiser

**Maintainer** Tim Kaiser <Tim.Kaiser@sbg.ac.at>

**Depends** zoo

**Description** While there are many well-established measures for identifying critical fluctuations and phase transitions, these measures only work with many points of measurement and thus are unreliable when studying short and coarse-grained time series. This package provides a measure for complexity in a time series that does not rely on long time series (Kaiser (2017), <[doi:10.17605/OSF.IO/GWTKX](https://doi.org/10.17605/OSF.IO/GWTKX)>).

**License** MIT + file LICENSE

**LazyData** TRUE

**RoxygenNote** 6.0.1

**Suggests** testthat

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-08-16 21:20:03 UTC

## Contents

|                      |          |
|----------------------|----------|
| complexity . . . . . | 2        |
| <b>Index</b>         | <b>3</b> |

---

`complexity`*Calculate dynamic complexity of time series*

---

**Description**

A function to calculate the dynamic complexity of a series of observations, resulting from the degree of fluctuation and the degree of scattering. This measure is calculated in moving windows of a specified width, resulting in a series of values of a length equal to the length of the series of observations.

**Usage**

```
complexity(x, scaleMin, scaleMax, width = 7, measure = "complexity", rescale = FALSE)
```

**Arguments**

|                       |  |
|-----------------------|--|
| <code>x</code>        | The data to be used (representing a series of observations).   |
| <code>scaleMin</code> | Theoretical minimum of the data. Will default to the observed minimum of <code>x</code> .  |
| <code>scaleMax</code> | Theoretical maximum of the data. Will default to the observed maximum of <code>x</code> .  |
| <code>width</code>    | Width of the moving window. Default is 7.  |
| <code>measure</code>  | Either "complexity", "fluctuation" or "distribution". Indicates which value should be returned. Default is "complexity".                               |
| <code>rescale</code>  | If TRUE, rescales the returned values to scale minimum and maximum. This is sometimes useful for graphical interpretation or plotting. Default: FALSE. |

**Author(s)**

Tim Kaiser <Tim.Kaiser@sbg.ac.at>

**References**

Kaiser, T. (2017). `dyncomp`: an R package for Estimating the Complexity of Short Time Series. DOI 10.17605/OSF.IO/GWTKX

**Examples**

```
t <- runif(100, 0, 10)
c <- complexity(x = t, scaleMin = 0, scaleMax = 10, width = 5, measure = "complexity",
rescale = TRUE)
plot(t, type = "l")
lines(c, col = "red", lty = 4)
```

# Index

complexity, 2