Package: eha (via r-universe)

October 28, 2026

Encoding UTF-8

Version 2.12.0

Date 2026-06-01

Title Event History Analysis

Description Parametric proportional hazards fitting with left truncation and right censoring for common families of distributions, piecewise constant hazards, and discrete models. Parametric accelerated failure time models for left truncated and right censored data. Proportional hazards models for tabular and register data. Sampling of risk sets in Cox regression, selections in the Lexis diagram, bootstrapping. Broström (2022) <doi:10.1201/9780429503764>.

BugReports https://github.com/goranbrostrom/eha/issues

License GPL (>= 2)

LazyData yes

ByteCompile yes

URL https://ehar.se/r/eha/

Depends R (>= 3.5.0)

Imports stats, graphics, survival (>= 3.0)

NeedsCompilation yes

Maintainer Göran Broström <goran.brostrom@umu.se>

RoxygenNote 7.3.3

Suggests knitr, rmarkdown, bookdown

VignetteBuilder knitr, utils

Author Göran Broström [aut, cre], Jianming Jin [ctb]

Repository https://cran.r-universe.dev

Date/Publication 2026-06-01 20:30:02 UTC

RemoteUrl https://github.com/cran/eha

RemoteRef HEAD

RemoteSha b9bdbd1a8e90b1efc33f355789ffeda94d7ef8bd

Contents

eha-package . . . 4
aftGompreg . . . 5
aftGompreg.fit . . . 7
aftreg . . . 8
aftreg.fit . . . 11
age.window . . . 12
cal.window . . . 13
check.dist . . . 14
check.surv . . . 15
child . . . 16
compHaz . . . 17
coxfunk . . . 18
coxreg . . . 19
coxreg.fit . . . 22
coxreg2 . . . 24
cro . . . 27
EV . . . 28
fert . . . 29
frail.fit . . . 30
geome.fit . . . 31
Gompertz . . . 32
hazards . . . 33
HiscoHisclass . . . 33
import_strata . . . 34
import_Surv . . . 34
infants . . . 35
join.spells . . . 36
Loglogistic . . . 37
Lognormal . . . 38
logrank . . . 39
logrye . . . 40
ltx . . . 41
ltx2 . . . 42
make.communal . . . 43
makeham . . . 45
male.mortality . . . 46
mlreg . . . 47
mort . . . 50
oe . . . 51
oldmort . . . 51
Pch . . . 52
pchreg . . . 53
perstat . . . 56
phfunc . . . 56
phreg . . . 58
phreg.fit . . . 61

piecewise . . . 62
plot.aftGompreg . . . 63
plot.aftreg . . . 64
plot.coxreg . . . 66
plot.hazdata . . . 67
plot.logrank . . . 68
plot.phreg . . . 70
plot.tpchreg . . . 71
plot.weibreg . . . 73
plotHaz . . . 74
print.aftGompreg . . . 75
print.aftreg . . . 76
print.coxreg . . . 77
print.logrank . . . 78
print.phreg . . . 78
print.risksets . . . 79
print.summary.aftGompreg . . . 80
print.summary.aftreg . . . 81
print.summary.coxreg . . . 81
print.summary.phreg . . . 82
print.summary.tpchreg . . . 83
print.tpchreg . . . 84
print.weibreg . . . 84
regtable . . . 85
risksets . . . 86
rmsGomp . . . 87
scania . . . 88
summary.aftGompreg . . . 89
summary.aftreg . . . 90
summary.coxreg . . . 90
summary.phreg . . . 91
summary.tpchreg . . . 92
summary.weibreg . . . 92
SurvSplit . . . 93
swedeaths . . . 94
swepop . . . 96
table.events . . . 97
toBinary . . . 98
toDate . . . 99
toTime . . . 100
toTpch . . . 101
tpchreg . . . 102
weibreg . . . 103
weibreg.fit . . . 105
Weibull . . . 106
wfunk . . . 107

Index **109**

eha-package *eha: Event History Analysis*

Description

Parametric proportional hazards fitting with left truncation and right censoring for common families of distributions, piecewise constant hazards, and discrete models. Parametric accelerated failure time models for left truncated and right censored data. Proportional hazards models for tabular and register data. Sampling of risk sets in Cox regression, selections in the Lexis diagram, bootstrapping. Broström (2022) doi:10.1201/9780429503764.

Details

Eha enhances the recommended **survival** package in several ways, see the description. The main applications in mind are demography and epidemiology. For standard Cox regression analysis the function `coxph` in **survival** is still recommended. The function `coxreg` in **eha** in fact calls coxph for the standard kind of analyses.

Author(s)

Maintainer: Göran Broström <goran.brostrom@umu.se>

Other contributors:

- Jianming Jin [contributor]

References

Broström, G. (2012). *Event History Analysis with R*, Chapman and Hall/CRC Press, Boca Raton, FL.

See Also

Useful links:

- https://ehar.se/r/eha/
- Report bugs at https://github.com/goranbrostrom/eha/issues

`aftGompreg` *Accelerated Failure Time Regression for Gompertz distribution*

Description

The accelerated failure time model with parametric baseline hazard(s). Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data. Gompert

Usage

```
aftGompreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  init,
  id,
  param = c("lifeAcc", "lifeExp"),
  control = list(eps = 1e-08, maxiter = 20, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  x = FALSE,
  y = TRUE
)
```

Arguments

`formula`	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
`data`	a data.frame in which to interpret the variables named in the formula.
`na.action`	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is `options()$na.action`.
`init`	vector of initial values of the iteration. Default initial value is zero for all variables.
`id`	If there are more than one spell per individual, it is essential to keep spells together by the id argument. This allows for time-varying covariates.
`param`	Which parametrization should be used? The `lifeAcc` uses the parametrization given in the vignette, while the `lifeExp` uses the same as in the `survreg` function.
`control`	a list with components `eps` (convergence criterion), `maxiter` (maximum number of iterations), and `trace` (logical, debug output if `TRUE`). You can change any component without mention the other(s).
`singular.ok`	Not used.
`model`	Not used.
`x`	Return the design matrix in the model object?
`y`	Return the response in the model object?

Details

The parameterization is different from the one used by survreg, when param = "lifeAcc". The result is then true acceleration of time. Then the model is

$$S(t; a, b, \beta, z) = S_0((t/\exp(b - z\beta))^{\exp(a)})$$

where S_0 is the standardized Gompertz survivor function. The baseline parameters a and b are log shape and log scale, respectively. This is for the default parametrization. With the lifeExp parametrization, some signs are changed:

$$b - zbeta$$

is changed to

$$b + zbeta$$

. For the Gompertz distribution, the base parametrization is canonical, a necessity for consistency with the shape/scale paradigm (this is new in 2.3).

Value

A list of class "aftGompreg" with components

coefficients	Fitted parameter estimates.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second componet is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
means	Means of the columns of the design matrix.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).
n.events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
wald.test	The Wald test statistic (at the initial value).
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
call	The call.

method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).
param	The parametrization.
baselineMean	Mean survival time by strata.
nullModel	TRUE if covariates in the model, otherwise FALSE.

Author(s)

Göran Broström

See Also

coxreg, phreg, aftreg, survreg

Examples

```
data(mort)
aftGompreg(Surv(enter, exit, event) ~ ses, param = "lifeExp", data = mort)
```

---

aftGompreg.fit *Parametric AFT regression*

Description

This function is called by aftreg, but it can also be directly called by a user.

Usage

```
aftGompreg.fit(X, Y, param, strata, offset, init, id, control)
```

Arguments

X	The design (covariate) matrix.
Y	A survival object, the response.
param	Which parametrization?
strata	A stratum variable.
offset	Offset.
init	Initial regression parameter values.
id	See corresponding argument to aftreg.
control	Controls convergence and output.

Details

See aftreg for more detail.

Value

coefficients	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
df	Degrees of freedom; No. of regression parameters.
var	Variance-covariance matrix
loglik	Vector of length 2. The first component is the maximized loglihood with only scale and shape in the model, the second the final maximum.
conver	TRUE if convergence
fail	TRUE if failure
iter	Number of Newton-Raphson iterates.
n.strata	The number of strata in the data.

Author(s)

Göran Broström

See Also

aftreg

---

aftreg *Accelerated Failure Time Regression*

Description

The accelerated failure time model with parametric baseline hazard(s). Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data.

Usage

```
aftreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  dist = "weibull",
  init,
  shape = 0,
  id,
  param = c("lifeAcc", "lifeExp"),
  control = list(eps = 1e-08, maxiter = 20, trace = FALSE),
  singular.ok = TRUE,
```

```
  model = FALSE,
  x = FALSE,
  y = TRUE
)
```

Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()$na.action.
dist	Which distribution? Default is "weibull", with the alternatives "gompertz", "ev", "loglogistic" and "lognormal". A special case like the exponential can be obtained by choosing "weibull" in combination with shape = 1.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
shape	If positive, the shape parameter is fixed at that value. If zero or negative, the shape parameter is estimated. Stratification is now regarded as a meaningful option even if shape is fixed.
id	If there are more than one spell per individual, it is essential to keep spells together by the id argument. This allows for time-varying covariates.
param	Which parametrization should be used? The lifeAcc uses the parametrization given in the vignette, while the lifeExp uses the same as in the survreg function.
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and trace (logical, debug output if TRUE). You can change any component without mention the other(s).
singular.ok	Not used.
model	Not used.
x	Return the design matrix in the model object?
y	Return the response in the model object?

Details

The parameterization is different from the one used by survreg, when param = "lifeAcc". The result is then true acceleration of time. Then the model is

$$S(t; a, b, \beta, z) = S_0((t/\exp(b - z\beta))^{\exp(a)})$$

where S_0 is some standardized survivor function. The baseline parameters a and b are log shape and log scale, respectively. This is for the default parametrization. With the lifeExp parametrization, some signs are changed:

$$b - zbeta$$

is changed to

$$b + zbeta$$

. For the Gompertz distribution, the base parametrization is `canonical`, a necessity for consistency with the shape/scale paradigm (this is new in 2.3).

Value

A list of class `"aftreg"` with components

`coefficients`	Fitted parameter estimates, including scale and shape.
`var`	Covariance matrix of the estimates.
`loglik`	Vector of length two; first component is the value at the initial parameter values, the second componet is the maximized value.
`score`	The score test statistic (at the initial value).
`linear.predictors`	The estimated linear predictors.
`means`	Means of the columns of the design matrix.
`w.means`	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
`n`	Number of spells in indata (possibly after removal of cases with NA's).
`n.events`	Number of events in data.
`terms`	Used by extractor functions.
`assign`	Used by extractor functions.
`wald.test`	The Wald test statistic (at the initial value).
`y`	The Surv vector.
`isF`	Logical vector indicating the covariates that are factors.
`covars`	The covariates.
`ttr`	Total Time at Risk.
`levels`	List of levels of factors.
`formula`	The calling formula.
`call`	The call.
`method`	The method.
`convergence`	Did the optimization converge?
`fail`	Did the optimization fail? (Is `NULL` if not).
`pfixed`	TRUE if shape was fixed in the estimation.
`param`	The parametrization.

Author(s)

Göran Broström

See Also

coxreg, phreg, survreg

Examples

```
data(mort)
aftreg(Surv(enter, exit, event) ~ ses, param = "lifeExp", data = mort)
```

`aftreg.fit` *Parametric proportional hazards regression*

Description

This function is called by aftreg, but it can also be directly called by a user.

Usage

```
aftreg.fit(X, Y, dist, param, strata, offset, init, shape, id, control, pfixed)
```

Arguments

X	The design (covariate) matrix.
Y	A survival object, the response.
dist	Which baseline distribution?
param	Which parametrization?
strata	A stratum variable.
offset	Offset.
init	Initial regression parameter values.
shape	If positive, a fixed value of the shape parameter in the distribution. Otherwise, the shape is estimated.
id	See corresponding argument to aftreg.
control	Controls convergence and output.
pfixed	A logical indicating fixed shape parameter(s).

Details

See aftreg for more detail.

Value

coefficients	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
df	Degrees of freedom; No. of regression parameters.
var	Variance-covariance matrix
loglik	Vector of length 2. The first component is the maximized loglihood with only scale and shape in the model, the second the final maximum.
conver	TRUE if convergence
fail	TRUE if failure
iter	Number of Newton-Raphson iterates.
n.strata	The number of strata in the data.

Author(s)

Göran Broström

See Also

aftreg

---

age.window *Age cut of survival data*

Description

For a given age interval, each spell is cut to fit into the given age interval.

Usage

```
age.window(dat, window, surv = c("enter", "exit", "event"))
```

Arguments

dat	Input data frame. Must contain survival data.
window	Vector of length two; the age interval.
surv	Vector of length three giving the names of the central variables in 'dat'.

Details

The window must be in the order (begin, end)

Value

A data frame of the same form as the input data frame, but 'cut' as desired. Intervals exceeding window[2] will be given event = 0. If the selection gives an empty result, NULL is returned, with no warning.

Author(s)

Göran Broström

See Also

cal.window, coxreg, aftreg

Examples

```
dat <- data.frame(enter = 0, exit = 5.731, event = 1, x = 2)
window <- c(2, 5.3)
dat.trim <- age.window(dat, window)
```

---

cal.window *Calendar time cut of survival data*

Description

For a given time interval, each spell is cut so that it fully lies in the given time interval

Usage

```
cal.window(dat, window, surv = c("enter", "exit", "event", "birthdate"))
```

Arguments

dat	Input data frame. Must contain survival data and a birth date.
window	Vector of length two; the time interval
surv	Vector of length four giving the names of the central variables in 'dat'.

Details

The window must be in the order (begin, end)

Value

A data frame of the same form as the input data frame, but 'cut' as desired. Intervals exceeding window[2] will be given event = 0

Author(s)

Göran Broström

See Also

age.window, coxreg, aftreg

Examples

```
dat <- data.frame(enter = 0, exit = 5.731, event = 1,
birthdate = 1962.505, x = 2)
window <- c(1963, 1965)
dat.trim <- cal.window(dat, window)
```

`check.dist` *Graphical goodness-of-fit test*

Description

Comparison of the cumulative hazards functions for a semi-parametric and a parametric model.

Usage

```
check.dist(sp, pp, main = NULL, col = 1:2, lty = 1:2, printLegend = TRUE)
```

Arguments

`sp`	An object of type "coxreg", typically output from `coxreg`
`pp`	An object of type "phreg", typically output from `phreg`
`main`	Header for the plot. Default is distribution and "cumulative hazard function"
`col`	Line colors. should be `NULL` (black lines) or of length 2
`lty`	line types.
`printLegend`	Should a legend be printed? Default is `TRUE`.

Details

For the moment only a graphical comparison. The arguments `sp` and `pp` may be swapped.

Value

No return value.

Author(s)

Göran Broström

See Also

`coxreg` and `phreg`.

Examples

```
data(mort)
oldpar <- par(mfrow = c(2, 2))
fit.cr <- coxreg(Surv(enter, exit, event) ~ ses, data = mort)
fit.w <- phreg(Surv(enter, exit, event) ~ ses, data = mort)
fit.g <- phreg(Surv(enter, exit, event) ~ ses, data = mort,
dist = "gompertz")
fit.ev <- phreg(Surv(enter, exit, event) ~ ses, data = mort,
dist = "ev")
check.dist(fit.cr, fit.w)
check.dist(fit.cr, fit.g)
check.dist(fit.cr, fit.ev)
par(oldpar)
```

---

check.surv *Check the integrity of survival data.*

Description

Check that exit occurs after enter, that spells from an individual do not overlap, and that each individual experiences at most one event.

Usage

```
check.surv(enter, exit, event, id = NULL, eps = 1e-08)
```

Arguments

enter	Left truncation time.
exit	Time of exit.
event	Indicator of event. Zero means 'no event'.
id	Identification of individuals.
eps	The smallest allowed spell length or overlap.

Details

Interval lengths must be strictly positive.

Value

A vector of id's for the insane individuals. Of zero length if no errors.

Author(s)

Göran Broström

See Also

join.spells, coxreg, aftreg

Examples

```
xx <- data.frame(enter = c(0, 1), exit = c(1.5, 3), event = c(0, 1), id =
c(1,1))
check.surv(xx$enter, xx$exit, xx$event, xx$id)
```

---

child *Child mortality, Skellefteå, Sweeden 1850–1900.*

Description

Children born in Skellefteå, Sweden, 1850-1884, are followed fifteen years or until death or out-migration.

Usage

```
data(child)
```

Format

A data frame with 26855 children born 1850-1884.

`id` An identification number.

`m.id` Mother's id.

`sex` Sex.

`socBranch` Working branch of family (father).

`birthdate` Birthdate.

`enter` Start age of follow-up, always zero.

`exit` Age of departure, either by death or emigration.

`event` Type of departure, death = 1, right censoring = 0.

`illeg` Born out of marriage ("illegitimate")?

`m.age` Mother's age.

Details

The Skellefteå region is a large region in the northern part of Sweden.

Source

Data originate from the Centre for Demographic and Ageing Research, Umeå University, Umeå, Sweden, https://www.umu.se/en/centre-for-demographic-and-ageing-research/.

Examples

```
fit <- coxreg(Surv(enter, exit, event) ~ sex + socBranch, data = child, coxph = TRUE)
summary(fit)
```

---

compHaz *Graphical comparison of cumulative hazards*

Description

Comparison of the estimated baseline cumulative hazards functions for two survival models.

Usage

```
compHaz(
  fit1,
  fit2,
  main = NULL,
  lty = 1:2,
  col = c("red", "blue"),
  printLegend = TRUE
)
```

Arguments

fit1	An object of type "coxreg", "phreg", or other output from from survival fitters.
fit2	An object of type "coxreg", "phreg", or other output from survival fitters.
main	Header for the plot. Default is NULL.
lty	line types.
col	Line colors. should be NULL (black lines) or of length 2.
printLegend	Should a legend be printed? Default is TRUE.

Value

No return value.

Author(s)

Göran Broström

See Also

hazards, coxreg, and phreg.

Examples

```
fit.cr <- coxreg(Surv(enter, exit, event) ~ sex, data = oldmort)
fit.w <- phreg(Surv(enter, exit, event) ~ sex, data = oldmort)
compHaz(fit.cr, fit.w)
```

coxfunk *Loglihood function (partial likelihood) of a Cox regression*

Description

Calculates minus the log likelihood function and its first and second order derivatives for data from a Cox regression model. It is used by `coxreg` if the argument `coxph = FALSE`

Usage

```
coxfunk(beta, X, offset, rs, what = 2)
```

Arguments

`beta`	Regression parameters
`X`	The design (covariate) matrix.
`offset`	Offset.
`rs`	Risk set created by `risksets(..., collate_sets = TRUE)`
`what`	what = 0 means only loglihood, 1 means score vector as well, 2 loglihood, score and hessian.

Details

Note that the function returns log likelihood, score vector and minus hessian, i.e. the observed information. The model is

Value

A list with components

`loglik`	The log likelihood.
`dloglik`	The score vector. Nonzero if `what >= 1`
`d2loglik`	The hessian. Nonzero if `ord >= 2`

Author(s)

Göran Broström

See Also

`coxreg`

coxreg *Cox regression*

Description

Performs Cox regression with some special attractions, especially *sampling of risksets* and *the weird bootstrap*.

Usage

```
coxreg(formula = formula(data), data = parent.frame(), weights,
subset, t.offset, na.action = getOption("na.action"), init = NULL, method =
c("efron", "breslow", "mppl", "ml"), control = list(eps = 1e-08, maxiter =
25, trace = FALSE), singular.ok = TRUE, model = FALSE, center = NULL, x =
FALSE, y = TRUE, hazards = NULL, boot = FALSE, efrac = 0, geometric = FALSE,
rs = NULL, frailty = NULL, max.survs = NULL, coxph = TRUE)
```

Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
weights	Case weights; time-fixed or time-varying.
subset	An optional vector specifying a subset of observations to be used in the fitting process.
t.offset	Case offsets; time-varying.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()$na.action.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
method	Method of treating ties, "efron" (default), "breslow", "mppl" (maximum partial partial likelihood), or "ml" (maximum likelihood).
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used
model	Not used
center	deprecated. See Details.
x	Return the design matrix in the model object?
y	return the response in the model object?
hazards	deprecated. Was: Calculate baseline hazards? Default is TRUE. Calculating hazards is better done separately, after fitting. In most cases.

boot	Number of boot replicates. Defaults to FALSE, no boot samples.
efrac	Upper limit of fraction failures in 'mppl'.
geometric	If TRUE, forces an 'ml' model with constant riskset probability. Default is FALSE.
rs	Risk set?
frailty	Grouping variable for frailty analysis. Not in use (yet).
max.survs	Sampling of risk sets? If given, it should be (the upper limit of) the number of survivors in each risk set.
coxph	Logical, defaults to TRUE. Determines if standard work should be passed to coxph via entry points.

Details

The default method, efron, and the alternative, breslow, are both the same as in coxph in package survival. The methods mppl and ml are maximum likelihood, discrete-model, based.

Value

A list of class c("coxreg", "coxph") with components

coefficients	Fitted parameter estimates.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
residuals	The martingale residuals.
hazards	The estimated baseline hazards, calculated at the value zero of the covariates (rather, columns of the design matrix). Is a list, with one component per stratum. Each component is a matrix with two columns, the first contains risk times, the second the corresponding hazard atom.
means	Means of the columns of the design matrix corresponding to covariates, if center = TRUE. Columns corresponding to factor levels gice a zero in the corresponding position in means. If center = FALSE, means are all zero.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).
n.events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.

covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
bootstrap	The (matrix of) bootstrap replicates, if requested on input. It is up to the user to do whatever desirable with this sample.
call	The call.
method	The method.
n.strata	Number of strata.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).

Warning

The use of rs is dangerous, see note. It can however speed up computing time considerably for huge data sets.

Note

This function starts by creating risksets, if no riskset is supplied via rs, with the aid of risksets. Supplying output from risksets via rs fails if there are any NA's in the data! Note also that it depends on stratification, so rs contains information about stratification. Giving another strata variable in the formula is an error. The same is ok, for instance to supply stratum interactions.

Author(s)

Göran Broström

References

Broström, G. and Lindkvist, M. (2008). Partial partial likelihood. Communications in Statistics: Simulation and Computation 37:4, 679-686.

See Also

coxph, risksets

Examples

```
dat <- data.frame(time=  c(4, 3,1,1,2,2,3),
                  status=c(1,1,1,0,1,1,0),
                  x=     c(0, 2,1,1,1,0,0),
                  sex=   c(0, 0,0,0,1,1,1))
coxreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
# Same as:
rs <- risksets(Surv(dat$time, dat$status), strata = dat$sex)
coxreg( Surv(time, status) ~ x, data = dat, rs = rs) #stratified model
```

coxreg.fit *Cox regression*

Description

Called by coxreg, but a user can call it directly.

Usage

```
coxreg.fit(
  X,
  Y,
  rs,
  weights,
  t.offset = NULL,
  strats,
  offset,
  init,
  max.survs,
  method = "efron",
  boot = FALSE,
  efrac = 0,
  calc.martres = TRUE,
  control,
  verbose = TRUE,
  calc.hazards = NULL,
  center = NULL
)
```

Arguments

X	The design matrix.
Y	The survival object.
rs	The risk set composition. If absent, calculated.
weights	Case weights; time-fixed or time-varying.
t.offset	Case offset; time-varying.
strats	The stratum variable. Can be absent.
offset	Offset. Can be absent.
init	Start values. If absent, equal to zero.
max.survs	Sampling of risk sets? If so, gives the maximum number of survivors in each risk set.
method	Either "efron" (default) or "breslow".
boot	Number of bootstrap replicates. Defaults to FALSE, no bootstrapping.
efrac	Upper limit of fraction failures in 'mppl'.

calc.martres	Should martingale residuals be calculated?
control	See coxreg
verbose	Should Warnings about convergence be printed?
calc.hazards	Deprecated. See coxreg.
center	Deprecated. See coxreg.

Details

rs is dangerous to use when NA's are present.

Value

A list with components

coefficients	Estimated regression parameters.
var	Covariance matrix of estimated coefficients.
loglik	First component is value at init, second at maximum.
score	Score test statistic, at initial value.
linear.predictors	Linear predictors.
residuals	Martingale residuals.
hazard	Estimated baseline hazard. At value zero of design variables.
means	Means of the columns of the design matrix.
bootstrap	The bootstrap replicates, if requested on input.
conver	TRUE if convergence.
f.conver	TRUE if variables converged.
fail	TRUE if failure.
iter	Number of performed iterations.

Note

It is the user's responsibility to check that indata is sane.

Author(s)

Göran Broström

See Also

coxreg, risksets

Examples

```
X <- as.matrix(data.frame(
               x=     c(0, 2,1,4,1,0,3),
               sex=   c(1, 0,0,0,1,1,1)))
time <- c(1,2,3,4,5,6,7)
status <- c(1,1,1,0,1,1,0)
stratum <- rep(1, length(time))

coxreg.fit(X, Surv(time, status), strats = stratum, max.survs = 6,
    control = list(eps=1.e-4, maxiter = 10, trace = FALSE))
```

---

coxreg2 *Cox regression*

Description

Performs Cox regression with some special attractions, especially *sampling of risksets* and *the weird bootstrap*.

Usage

```
coxreg2(formula = formula(data), data = parent.frame(), weights,
subset, t.offset, na.action = getOption("na.action"), init = NULL, method =
c("efron", "breslow", "mppl", "ml"), control = list(eps = 1e-08, maxiter =
25, trace = FALSE), singular.ok = TRUE, model = FALSE, center = NULL, x =
FALSE, y = TRUE, hazards = NULL, boot = FALSE, efrac = 0, geometric = FALSE,
rs = NULL, frailty = NULL, max.survs = NULL, coxph = TRUE)
```

Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
weights	Case weights; time-fixed or time-varying.
subset	An optional vector specifying a subset of observations to be used in the fitting process.
t.offset	Case offsets; time-varying.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is `options()$na.action`.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
method	Method of treating ties, "efron" (default), "breslow", "mppl" (maximum partial partial likelihood), or "ml" (maximum likelihood).

control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used
model	Not used
center	deprecated. See Details.
x	Return the design matrix in the model object?
y	return the response in the model object?
hazards	deprecated. Was: Calculate baseline hazards? Default is TRUE. Calculating hazards is better done separately, after fitting. In most cases.
boot	Number of boot replicates. Defaults to FALSE, no boot samples.
efrac	Upper limit of fraction failures in 'mppl'.
geometric	If TRUE, forces an 'ml' model with constant riskset probability. Default is FALSE.
rs	Risk set?
frailty	Grouping variable for frailty analysis. Not in use (yet).
max.survs	Sampling of risk sets? If given, it should be (the upper limit of) the number of survivors in each risk set.
coxph	Logical, defaults to TRUE. Determines if standard work should be passed to coxph via entry points.

Details

The default method, efron, and the alternative, breslow, are both the same as in coxph in package survival. The methods mppl and ml are maximum likelihood, discrete-model, based.

Value

A list of class c("coxreg", "coxph") with components

coefficients	Fitted parameter estimates.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
residuals	The martingale residuals.
hazards	The estimated baseline hazards, calculated at the value zero of the covariates (rather, columns of the design matrix). Is a list, with one component per stratum. Each component is a matrix with two columns, the first contains risk times, the second the corresponding hazard atom.

means	Means of the columns of the design matrix corresponding to covariates, if center = TRUE. Columns corresponding to factor levels gice a zero in the corresponding position in means. If center = FALSE, means are all zero.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).
n.events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
bootstrap	The (matrix of) bootstrap replicates, if requested on input. It is up to the user to do whatever desirable with this sample.
call	The call.
method	The method.
n.strata	Number of strata.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).

Warning

The use of rs is dangerous, see note. It can however speed up computing time considerably for huge data sets.

Note

This function starts by creating risksets, if no riskset is supplied via rs, with the aid of risksets. Supplying output from risksets via rs fails if there are any NA's in the data! Note also that it depends on stratification, so rs contains information about stratification. Giving another strata variable in the formula is an error. The same is ok, for instance to supply stratum interactions.

Author(s)

Göran Broström

References

Broström, G. and Lindkvist, M. (2008). Partial partial likelihood. Communications in Statistics: Simulation and Computation 37:4, 679-686.

See Also

coxph, risksets

Examples

```
dat <- data.frame(time=  c(4, 3,1,1,2,2,3),
                  status=c(1,1,1,0,1,1,0),
                  x=     c(0, 2,1,1,1,0,0),
                  sex=   c(0, 0,0,0,1,1,1))
coxreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
# Same as:
rs <- risksets(Surv(dat$time, dat$status), strata = dat$sex)
coxreg( Surv(time, status) ~ x, data = dat, rs = rs) #stratified model
```

---

cro *Creates a minimal representation of a data frame.*

Description

Given a data frame with a defined response variable, this function creates a unique representation of the covariates in the data frame, vector (matrix) of responses, and a pointer vector, connecting the responses with the corresponding covariates.

Usage

```
cro(dat, response = 1)
```

Arguments

dat	A data frame
response	The column(s) where the response resides.

Details

The rows in the data frame are converted to text strings with paste and compared with match.

Value

A list with components

y	The response.
covar	A data frame with unique rows of covariates.
keys	Pointers from y to covar, connecting each response with its covariate vector.

Note

This function is based on suggestions by Anne York and Brian Ripley.

Author(s)

Göran Broström

See Also

match, paste

Examples

```
dat <- data.frame(y = c(1.1, 2.3, 0.7), x1 = c(1, 0, 1), x2 = c(0, 1, 0))
cro(dat)
```

EV *The EV Distribution*

Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the EV distribution with parameters shape and scale.

Usage

```
dEV(x, shape = 1, scale = 1, log = FALSE)
pEV(q, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
qEV(p, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
hEV(x, shape = 1, scale = 1, log = FALSE)
HEV(x, shape = 1, scale = 1, log.p = FALSE)
rEV(n, shape = 1, scale = 1)
```

Arguments

shape, scale	shape and scale parameters, both defaulting to 1.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise, $P(X > x)$.
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as log(p).

Details

The EV distribution with scale parameter a and shape parameter σ has hazard function given by

$$h(x) = (b/\sigma)(x/\sigma)^(b-1)\exp((x/\sigma)^b)$$

for $x \geq 0$.

Value

dEV gives the density, pEV gives the distribution function, qEV gives the quantile function, hEV gives the hazard function, HEV gives the cumulative hazard function, and rEV generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

---

fert *Marital fertility nineteenth century*

Description

Birth intervals for married women with at least one birth, 19th northern Sweden

Usage

```
data(fert)
```

Format

A data frame with 12169 observations the lengths (in years) of birth intervals for 1859 married women with at least one birth. The first interval (parity = 0) is the interval from marriage to first birth.

id Personal identification number for mother.

parity Time order of birth interval for the present mother. The interval with parity = 0 is the first, from marriage to first birth.

age The age of mother at start of interval.

year The calendar year at start of interval.

next.ivl The length of the coming time interval.

event An indicator for whether the next.ivl ends in a new birth (event = 1) or is right censored (event = 0). Censoring occurs when the woman ends her fertility period within her first marriage (marriage dissolution or reaching the age of 48).

prev.ivl The length of the previous time interval. May be used as explanatory variable in a Cox regression of birth intervals.

ses Socio-economic status, a factor with levels lower, upper, farmer, and unknown.

parish The Skelleftea region consists of three parishes, Jorn, Norsjo, and Skelleftea.

Details

The data set contain clusters of dependent observations defined by mother's id.

Source

Data is coming from The Demographic Data Base, Umea University, Umea, Sweden.

References

https://www.umu.se/enheten-for-demografi-och-aldrandeforskning/

Examples

```
data(fert)
fit <- coxreg(Surv(next.ivl, event) ~ ses + prev.ivl, data = fert, subset =
(parity == 1))
summary(fit)
```

`frail.fit` *Frailty experiment*

Description

Utilizing GLMM models: Experimental, not exported (yet).

Usage

```
frail.fit(X, Y, rs, strats, offset, init, max.survs, frailty, control)
```

Arguments

`X`	design matrix
`Y`	survival object
`rs`	output from `risksets`
`strats`	strata
`offset`	offset
`init`	start values
`max.survs`	for sampling of riskset survivors
`frailty`	grouping variable
`control`	control of optimization

`geome.fit` *Constant intensity discrete time proportional hazards*

Description

This function is called from `coxreg`. A user may call it directly.

Usage

```
geome.fit(X, Y, rs, strats, offset, init, max.survs, method = "ml", control)
```

Arguments

`X`	The design matrix
`Y`	Survival object
`rs`	risk set produced by `risksets`
`strats`	Stratum indicator
`offset`	Offset
`init`	Initial values
`max.survs`	Maximal survivors
`method`	"ml", always, i.e., this argument is ignored.
`control`	See `coxreg`.

Value

See the code.

Note

Nothing special

`coxreg` is a defunct function

Author(s)

Göran Broström

References

See `coxreg`.

See Also

`coxreg`

Gompertz *The Gompertz Distribution*

Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Gompertz distribution with parameters shape and scale.

Usage

```
dgompertz(x, shape = 1, scale = 1, rate, log = FALSE,
param = c("default", "canonical", "rate"))
pgompertz(q, shape = 1, scale = 1, rate, lower.tail = TRUE, log.p = FALSE,
param = c("default", "canonical", "rate"))
qgompertz(p, shape = 1, scale = 1, rate, lower.tail = TRUE, log.p = FALSE,
param = c("default", "canonical", "rate"))
hgompertz(x, shape = 1, scale = 1, rate, log = FALSE,
param = c("default", "canonical", "rate"))
Hgompertz(x, shape = 1, scale = 1, rate, log.p = FALSE,
param = c("default", "canonical", "rate"))
rgompertz(n, shape = 1, scale = 1, rate,
param = c("default", "canonical", "rate"))
```

Arguments

shape, scale	shape and scale parameters, both defaulting to 1.
rate	the rate parameter for that parametrization, replaces scale.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise, $P(X > x)$.
param	default or canonical or rate.
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as log(p).

Details

The Gompertz distribution with scale parameter a and shape parameter σ has hazard function given by

$$h(x) = a \exp(x/\sigma)$$

for $x \geq 0$. If param = "canonical", then then a –> a/b, so that b is a true scale parameter (for any fixed a), and b is an 'AFT parameter'. If param = "rate", then b –> 1/b.

Value

dgompertz gives the density, pgompertz gives the distribution function, qgompertz gives the quantile function, hgompertz gives the hazard function, Hgompertz gives the cumulative hazard function, and rgompertz generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

---

hazards *Get baseline hazards atoms from fits from*

Description

Get baseline hazards atoms from fits from

Usage

```
hazards(x, cum = TRUE, ...)
```

Arguments

x	A reg object.
cum	Logical: Should the cumulative hazards be returned?
...	Additional arguments for various methods.

Value

A list where each component is a two-column matrix representing hazard atoms from one stratum. The first column is event time, and the second column is the corresponding hazard atom.

HiscoHisclass *HISCO to HISCLASS transformation*

Description

HISCO to HISCLASS transformation

Usage

```
HiscoHisclass(hisco, status = NULL, relation = NULL, urban = NULL,
debug = FALSE)
```

Arguments

hisco	Hisco codes to be transformed to hisclass.
status	Optional standard description of status.
relation	Relation between owner of occupation and self.
urban	Logical, "Is residence in an urban area?"
debug	Logical, prints intermediate values if TRUE.

Value

A vector of hisclass codes, same length as input hisco.

Author(s)

Göran Broström with translation and modification of a Stata do.

References

Van Leeuwen, M. and Maas, I. (2011). HISCLASS. A Historical International Social Class Scheme. Leuwen University Press.

---

import_strata `strata` *function imported from* `survival`

Description

This function is imported from the `survival` package. See `strata`.

---

import_Surv `Surv` *function imported from* `survival`

Description

This function is imported from the `survival` package. See `Surv`.

infants *Infant mortality and maternal death, Sweeden 1821–1894.*

Description

Matched data on infant mortality, from seven parishes in Sweden, 1821–1894.

Usage

```
data(infants)
```

Format

A data frame with 80 rows and five variables.

`stratum` Triplet No. Each triplet consist of one infant whose mother died (a case), and two controls, i.e, infants whose mother did not die. Matched on covariates below.

`enter` Age (in days) of case when its mother died.

`exit` Age (in days) at death or right censoring (at age 365 days).

`event` Follow-up ends with death (1) or right censoring (0).

`mother` `dead` for cases, `alive` for controls.

`age` Mother's age at infant's birth.

`sex` The infant's sex.

`parish` Birth parish, either Nedertornea or not Nedertornea.

`civst` Civil status of mother, `married` or `unmarried`.

`ses` Socio-economic status of mother, either farmer or not farmer.

`year` Year of birth of the infant.

Details

From 5641 first-born in seven Swedish parishes 1820-1895, from Fleninge in the very south to Nedertorneå in the very north, those whose mother died during their first year of life were selected, in all 35 infants. To each of them, two controls were selected by matching on the given covariates.

Source

Data originate from The Demographic Data Base, Umeå University, Umeå, Sweden, https://www.umu.se/enheten-for-demografi-och-aldrandeforskning/.

References

Broström, G. (1987). The influence of mother's death on infant mortality: A case study in matched data survival analysis. Scandinavian Journal of Statistics 14, 113-123.

Examples

```
data(infants)
fit <- coxreg(Surv(enter, exit, event) ~ strata(stratum) + mother, data
= infants)
fit
fit.w <- phreg(Surv(enter, exit, event) ~ mother + parish + ses, data =
infants)
summary(fit.w) ## Weibull proportional hazards model.
```

`join.spells` *Straighten up a survival data frame*

Description

Unnecessary cut spells are glued together, overlapping spells are "polished", etc.

Usage

```
join.spells(dat, strict = FALSE, eps = 1e-08)
```

Arguments

`dat`	A data frame with names enter, exit, event, id.
`strict`	If TRUE, nothing is changed if errors in spells (non-positive length, overlapping intervals, etc.) are detected. Otherwise (the default), bad spells are removed, with "earlier life" having higher priority.
`eps`	Tolerance for equality of two event times. Should be kept small.

Details

In case of overlapping intervals (i.e., a data error), the appropriate id's are returned if `strict` is `TRUE`.

Value

A data frame with the same variables as the input, but individual spells are joined, if possible (identical covariate values, and adjacent time intervals).

Author(s)

Göran Broström

References

Therneau, T.M. and Grambsch, P.M. (2000). *Modeling Survival Data: Extending the Cox model.* Springer.

See Also

coxreg, aftreg, check.surv

`Loglogistic` *The Loglogistic Distribution*

Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Loglogistic distribution with parameters `shape` and `scale`.

Usage

```
dllogis(x, shape = 1, scale = 1, log = FALSE)
pllogis(q, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
qllogis(p, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
hllogis(x, shape = 1, scale = 1, prop = 1, log = FALSE)
Hllogis(x, shape = 1, scale = 1, prop = 1, log.p = FALSE)
rllogis(n, shape = 1, scale = 1)
```

Arguments

`shape`, `scale`	shape and scale parameters, both defaulting to 1.
`lower.tail`	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise, $P(X > x)$.
`x`, `q`	vector of quantiles.
`p`	vector of probabilities.
`n`	number of observations. If `length(n) > 1`, the length is taken to be the number required.
`log`, `log.p`	logical; if TRUE, probabilities p are given as log(p).
`prop`	proportionality constant in the extended Loglogistic distribution.

Details

The Loglogistic distribution with `scale` parameter a and `shape` parameter σ has hazard function given by

$$h(x) = (b/\sigma)(x/\sigma)^(b-1)\exp((x/\sigma)^b)$$

for $x \geq 0$.

Value

`dllogis` gives the density, `pllogis` gives the distribution function, `qllogis` gives the quantile function, `hllogis` gives the hazard function, `Hllogis` gives the cumulative hazard function, and `rllogis` generates random deviates.

Invalid arguments will result in return value `NaN`, with a warning.

Lognormal *The Lognormal Distribution*

Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Lognormal distribution with parameters shape and scale.

Usage

```
hlnorm(x, meanlog = 0, sdlog = 1, shape = 1 / sdlog, scale = exp(meanlog),
prop = 1, log = FALSE)
Hlnorm(x, meanlog = 0, sdlog = 1, shape = 1 / sdlog, scale = exp(meanlog),
prop = 1, log.p = FALSE)
```

Arguments

x	vector of quantiles.
meanlog	mean in the Normal distribution.
sdlog, shape	sdlog is standard deviation in the Normal distrimution, shape = 1/sdlog.
scale	is exp(meanlog).
prop	proportionality constant in the extended Lognormal distribution.
log, log.p	logical; if TRUE, probabilities p are given as log(p).

Details

The Lognormal distribution with scale parameter a and shape parameter σ has hazard function given by

$$h(x) = (b/\sigma)(x/\sigma)^(b-1)\exp((x/\sigma)^b)$$

for $x \geq 0$.

Value

dlnorm gives the density, plnorm gives the distribution function, qlnorm gives the quantile function, hlnorm gives the hazard function, Hlnorm gives the cumulative hazard function, and rlnorm generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

`logrank` *The Log-rank test*

Description

Performs the log-rank test on survival data, possibly stratified.

Usage

```
logrank(Y, group, data = parent.frame())
```

Arguments

`Y`	a survival object as returned by the `Surv` function.
`group`	defines the groups to be compared. Coerced to a factor.
`data`	a data.frame in which to interpret the variables.

Value

A list of class `logrank` with components

`test.statistic`	The logrank (score) test statistic.
`df`	The degrees of freedom of the test statistic.
`p.value`	The p value of the test.
`hazards`	A list of two-column matrices, describing event times and corresponding hazard atoms in each stratum (class 'hazdata').
`call`	The call

Note

The test is performed by fitting a Cox regression model and reporting its `score test`. With tied data, this might be slightly different from the true logrank test, but the difference is unimportant in practice.

Author(s)

Göran Broström

See Also

`coxreg`, `print.logrank`.

Examples

```
fit <- logrank(Y = Surv(enter, exit, event), group = civ,
data = oldmort[oldmort$region == "town", ])
fit
```

`logrye` *Rye prices, Scania, southern Sweden, 1801-1894.*

Description

The data consists of yearly rye prices from 1801 to 1894. Logged and detrended, so the time series is supposed to measure short term fluctuations in rye prices.

Usage

```
data(scania)
```

Format

A data frame with 94 observations in two columns on the following 2 variables.

`year` The year the price is recorded.

`foodprices` Detrended log rye prices.

Details

The Scanian area in southern Sweden was during the 19th century a mainly rural area.

Source

The Scanian Economic Demographic Database.

References

Jörberg, L. (1972). A History of Prices in Sweden 1732-1914, CWK Gleerup, Lund.

Examples

```
data(logrye)
summary(logrye)
```

ltx *LaTeX printing of regression results.*

Description

This (generic) function prints the LaTeX code of the results of a fit from coxreg, phreg, tpchreg, or aftreg, similar to what xtable does for fits from other functions.

Usage

```
ltx(
  x,
  caption = NULL,
  label = NULL,
  dr = NULL,
  digits = max(options()$digits - 4, 3),
  ...
)
```

Arguments

x	The output from a call to coxreg, tpchreg, or aftreg
caption	A suitable caption for the table.
label	A label used in the LaTeX code.
dr	Output from a drop1 call.
digits	Number of digits to be printed.
...	Not used.

Details

The result is a printout which is (much) nicer than the standard printed output from glm and friends,

Value

LaTeX code version of the results from a run with coxreg, phreg, phreg, or aftreg.

Note

For printing confidence limits, use ltx2.

Author(s)

Göran Broström.

See Also

ltx2, coxreg, phreg, phreg, and aftreg.

Examples

```
data(oldmort)
fit <- coxreg(Surv(enter, exit, event) ~ civ + sex, data = oldmort)
dr <- drop1(fit, test = "Chisq")
ltx(fit, dr = dr, caption = "A test example.", label = "tab:test1")
```

`ltx2` *LaTeX alternative printing of regression results.*

Description

This (generic) function prints the LaTeX code of the results of a fit from coxreg, phreg, tpchreg, or aftreg.

Usage

```
ltx2(
  x,
  caption = NULL,
  label = NULL,
  dr = NULL,
  digits = max(options()$digits - 4, 4),
  conf = 0.95,
  keep = NULL,
  ...
)
```

Arguments

x	The output from a call to coxreg, tpchreg, or aftreg
caption	A suitable caption for the table.
label	A label used in the LaTeX code.
dr	Output from a drop1 call.
digits	Number of digits to be printed.
conf	Confidence intervals level.
keep	Number of covariates to present.
...	Not used.

Value

LaTeX code version of the results from a run with coxreg, phreg, phreg, aftreg.

Note

Resulting tables contain estimated hazard ratios and confidence limits instead of regression coefficients and standard errors as in `ltx`.

Author(s)

Göran Broström.

See Also

`xtable`, `coxreg`, `phreg`, `phreg`, `aftreg`, and `ltx`.

Examples

```
data(oldmort)
fit <- coxreg(Surv(enter, exit, event) ~ sex, data = oldmort)
ltx2(fit, caption = "A test example.", label = "tab:test1")
```

---

make.communal *Put communals in "fixed" data frame*

Description

Given an ordinary data frame suitable for survival analysis, and a data frame with "communal" time series, this function includes the communal covariates as fixed, by the "cutting spells" method.

Usage

```
make.communal(
  dat,
  com.dat,
  communal = TRUE,
  start,
  period = 1,
  lag = 0,
  surv = c("enter", "exit", "event", "birthdate"),
  tol = 1e-04,
  fortran = TRUE
)
```

Arguments

`dat`	A data frame containing interval specified survival data and covariates, of which one must give a "birth date", the connection between duration and calendar time
`com.dat`	Data frame with communal covariates. They must have the same start year and periodicity, given by `start` and `lag`.

communal	Boolean; if TRUE, then it is a true communal (default), otherwise a fixed. The first component is the first year (start date in decimal form), and the second component is the period length. The third is lag and the fourth is scale.
start	Start date in decimal form.
period	Period length. Defaults to one.
lag	The lag of the effect. Defaults to zero.
surv	Character vector of length 4 giving the names of interval start, interval end, event indicator, birth date, in that order. These names must correspond to names in dat
tol	Largest length of an interval considered to be of zero length. The cutting sometimes produces zero length intervals, which we want to discard.
fortran	If TRUE, then a Fortran implementation of the function is used. This is the default. This possibility is only for debugging purposes. You should of course get identical results with the two methods.

Details

The main purpose of this function is to prepare a data file for use with coxreg, aftreg, and coxph.

Value

The return value is a data frame with the same variables as in the combination of dat and com.dat. Therefore it is an error to have common name(s) in the two data frames.

Note

Not very vigorously tested.

Author(s)

Göran Broström

See Also

coxreg, aftreg, coxph, cal.window

Examples

```
dat <- data.frame(enter = 0, exit = 5.731, event = 1,
birthdate = 1962.505, x = 2)
## Birth date: July 2, 1962 (approximately).
com.dat <- data.frame(price = c(12, 3, -5, 6, -8, -9, 1, 7))
dat.com <- make.communal(dat, com.dat, start = 1962.000)
```

makeham *The Gompertz-Makeham Distribution*

Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Gompertz-Makeham distribution with parameters shape and scale.

Usage

```
dmakeham(x, shape = c(1, 1), scale = 1, log = FALSE)
pmakeham(q, shape = c(1, 1), scale = 1, lower.tail = TRUE, log.p = FALSE)
qmakeham(p, shape = c(1, 1), scale = 1, lower.tail = TRUE, log.p = FALSE)
hmakeham(x, shape = c(1, 1), scale = 1, log = FALSE)
Hmakeham(x, shape = c(1, 1), scale = 1, log.p = FALSE)
rmakeham(n, shape = c(1, 1), scale = 1)
```

Arguments

shape	A vector, default value c(1, 1).
scale	defaulting to 1.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise, $P(X > x)$.
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as log(p).

Details

The Gompertz-Makeham distribution with shape parameter a and scale parameter σ has hazard function given by

$$h(x) = a[2] + a[1] \exp(x/\sigma)$$

for $x \geq 0$.

Value

dmakeham gives the density, pmakeham gives the distribution function, qmakeham gives the quantile function, hmakeham gives the hazard function, Hmakeham gives the cumulative hazard function, and rmakeham generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

`male.mortality` *Male mortality in ages 40-60, nineteenth century*

Description

Males born in the years 1800-1820 and surving at least 40 years in the parish Skellefteå in northern Sweden are followed from their fortieth birthday until death or the sixtieth birthday, whichever comes first.

Usage

```
data(male.mortality)
```

Format

A data frame with 2058 observations on the following 6 variables.

`id` Personal identification number.

`enter` Start of duration. Measured in years since the fortieth birthday.

`exit` End of duration. Measured in years since the fortieth birthday.

`event` a logical vector indicating death at end of interval.

`birthdate` The birthdate in decimal form.

`ses` Socio-economic status, a factor with levels `lower`, `upper`

Details

The interesting explanatory covariate is `ses` (socioeconomic status), which is a time-varying covariate. This explains why several individuals are representated by more than one record each. Left trucation and right censoring are introduced this way.

Note

This data set is also known, and accessible, as `mort`.

Source

Data is coming from The Demographic Data Base, Umea University, Umeå, Sweden.

References

https://www.umu.se/enheten-for-demografi-och-aldrandeforskning/

Examples

```
data(male.mortality)
fit <- coxreg(Surv(enter, exit, event) ~ ses, data = male.mortality)
summary(fit)
```

mlreg *ML proportional hazards regression*

Description

Maximum Likelihood estimation of proportional hazards models. Is deprecated, use coxreg instead.

Usage

```
mlreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  init = NULL,
  method = c("ML", "MPPL"),
  control = list(eps = 1e-08, maxiter = 10, n.points = 12, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  center = TRUE,
  x = FALSE,
  y = TRUE,
  boot = FALSE,
  geometric = FALSE,
  rs = NULL,
  frailty = NULL,
  max.survs = NULL
)
```

Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()$na.action.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
method	Method of treating ties, "ML", the default, means pure maximum likelihood, i.e, data are treated as discrete. The choice "MPPL" implies that risk sets with no tied events are treated as in ordinary Cox regression. This is a cameleont that adapts to data, part discrete and part continuous.
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).

singular.ok	Not used.
model	Not used.
center	Should covariates be centered? Default is TRUE
x	Return the design matrix in the model object?
y	return the response in the model object?
boot	No. of bootstrap replicates. Defaults to FALSE, i.e., no bootstrapping.
geometric	If TRUE, the intensity is assumed constant within strata.
rs	Risk set? If present, speeds up calculations considerably.
frailty	A grouping variable for frailty analysis. Full name is needed.
max.survs	Sampling of risk sets?

Details

Method ML performs a true discrete analysis, i.e., one parameter per observed event time. Method MPPL is a compromize between the discrete and continuous time approaches; one parameter per observed event time with multiple events. With no ties in data, an ordinary Cox regression (as with coxreg) is performed.

Value

A list of class c("mlreg", "coxreg", "coxph") with components

coefficients	Fitted parameter estimates.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second componet is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
residuals	The martingale residuals.
hazard	The estimated baseline hazard.
means	Means of the columns of the design matrix.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).
events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
wald.test	The Walt test statistic (at the initial value).
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.

ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
call	The call.
bootstrap	The bootstrap sample, if requested on input.
sigma	Present if a frailty model is fitted. Equals the estimated frailty standard deviation.
sigma.sd	The standard error of the estimated frailty standard deviation.
method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).

Warning

The use of rs is dangerous, see note above. It can however speed up computing time.

Note

This function starts by creating risksets, if no riskset is supplied via rs, with the aid of risksets. This latter mechanism fails if there are any NA's in the data! Note also that it depends on stratification, so rs contains information about stratification. Giving another strata variable in the formula is an error. The same is ok, for instance to supply stratum interactions.

Note futher that mlreg is deprecated. coxreg should be used instead.

Author(s)

Göran Broström

References

Broström, G. (2002). Cox regression; Ties without tears. *Communications in Statistics: Theory and Methods* **31**, 285–297.

See Also

coxreg, risksets

Examples

```
dat <- data.frame(time=  c(4, 3,1,1,2,2,3),
                  status=c(1,1,1,0,1,1,0),
                  x=     c(0, 2,1,1,1,0,0),
                  sex=   c(0, 0,0,0,1,1,1))
mlreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
# Same as:
rs <- risksets(Surv(dat$time, dat$status), strata = dat$sex)
mlreg( Surv(time, status) ~ x, data = dat, rs = rs) #stratified model
```

mort *Male mortality in ages 40-60, nineteenth century*

Description

Males born in the years 1800-1820 and surving at least 40 years in the parish Skellefteå in northern Sweden are followed from their fortieth birthday until death or the sixtieth birthday, whichever comes first.

Usage

```
data(mort)
```

Format

A data frame with 2058 observations on the following 6 variables.

`id` Personal identification number.

`enter` Start of duration. Measured in years since the fortieth birthday.

`exit` End of duration. Measured in years since the fortieth birthday.

`event` a logical vector indicating death at end of interval.

`birthdate` The birthdate in decimal form.

`ses` Socio-economic status, a factor with levels `lower`, `upper`

Details

The interesting explanatory covariate is `ses` (socioeconomic status), which is a time-varying covariate. This explains why several individuals are representated by more than one record each. Left trucation and right censoring are introduced this way.

Note

This data set is also known, and accessible, as `male.mortality`

Source

Data is coming from The Demographic Data Base, Umea University, Umeå, Sweden.

References

https://www.umu.se/enheten-for-demografi-och-aldrandeforskning/

Examples

```
data(mort)
fit <- coxreg(Surv(enter, exit, event) ~ ses, data = mort)
summary(fit)
```

oe *Create an oe object*

Description

Create an *oe* ("occurrence/exposure") object, used as a response variable in a model formula specifically in tpchreg.

Usage

```
oe(count, exposure)
```

Arguments

count	Number of events, a non-negative integer-valued vector.
exposure	exposure time corresponding to count. A positive numeric vector.

See Also

tpchreg.

oldmort *Old age mortality, Sundsvall, Sweden, 1860-1880.*

Description

The data consists of old age life histories from 1 January 1860 to 31 december 1880, 21 years. Only (parts of) life histories above age 60 is considered.

Usage

```
data(oldmort)
```

Format

A data frame with 6508 observations from 4603 persons on the following 13 variables.

`id` Identification number.

`enter` Start age for the interval.

`exit` Stop age for the interval.

`event` Indicator of death; equals `TRUE` if the person died at the end of the interval, `FALSE` otherwise.

`birthdate` Birthdate as a real number (i.e., "1765-06-27" is 1765.490).

`m.id` Mother's identification number.

`f.id` Father's identification number.

`sex` Gender, a factor with levels `male` `female`

`civ` Civil status, a factor with levels `unmarried` `married` `widow`

`ses.50` Socio-economic status at age 50, a factor with levels `middle` `unknown` `upper` `farmer` `lower`

`birthplace` a factor with levels `parish` `region` `remote`

`imr.birth` Infant mortality rate at birth in the region of birth

`region` Subregion of Sundsvall, a factor with levels `town` `industry` `rural`

Details

The Sundsvall area in mid-Sweden was during the 19th century a fast growing forest industry. At the end of the century, it was one of the largest sawmill area in Europe. The town Sundsvall is fast growing part of the region and center for the commerse.

Source

The Demographic Data Base, Umeå University, Sweden.

References

Edvinsson, S. (2000). The Demographic Data Base at Umeå University: A resource for historical studies. In Hall, McKaa, and Thorvaldsen (eds), "Handbook of International Historical Microdata for Population Research", Minnesota Population Center, Minneapolis.

Examples

```
data(oldmort)
summary(oldmort)
## maybe str(oldmort) ; plot(oldmort) ...
```

Pch *The Piecewise Constant Hazards distribution.*

Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, mean, and random generation for the Piecewice Constant Hazards (pch) distribution.

Usage

```
ppch(q, cuts, levels, lower.tail = TRUE, log.p = FALSE)
dpch(x, cuts, levels, log = FALSE)
hpch(x, cuts, levels, log = FALSE)
Hpch(x, cuts, levels, log.p = FALSE)
qpch(p, cuts, levels, lower.tail = TRUE, log.p = FALSE)
mpch(cuts, levels)
rpch(n, cuts, levels)
```

Arguments

cuts	Vector of cut points defining the intervals where the hazard function is constant.
levels	Vector of levels (values of the hazard function).
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise, $P(X > x)$.
x, q	vector of quantiles.
p	vector of probabilities.
log, log.p	logical; if TRUE, probabilities p are given as log(p).
n	number of observations. If length(n) > 1, the length is taken to be the number required.

Details

The pch distribution has a hazard function that is piecewise constant on intervals defined by cut-points

$$0 < c_1 < \cdots < c_n < \infty, n \geq 0$$

If n = 0, this reduces to an exponential distribution.

Value

dpch gives the density, ppch gives the distribution function, qpch gives the quantile function, hpch gives the hazard function, Hpch gives the cumulative hazard function, mpch gives the mean, and rpch generates random deviates.

Note

the parameter levels must have length at least 1, and the number of cut points must be one less than the number of levels.

---

pchreg *Piecewise Constant Proportional Hazards Regression*

Description

Proportional hazards model with piecewise constant baseline hazard(s). Allows for stratification and left truncated and right censored data.

Usage

```
pchreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  cuts = NULL,
  init,
  control = list(eps = 1e-08, maxiter = 20, trace = FALSE),
```

```
  singular.ok = TRUE,
  model = FALSE,
  x = FALSE,
  y = TRUE
)
```

Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()$na.action.
cuts	Specifies the points in time where the hazard function jumps. If omitted, an exponential model is fitted.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used.
model	Not used.
x	Return the design matrix in the model object?
y	Return the response in the model object?

Value

A list of class "pchreg" with components

coefficients	Fitted parameter estimates.
cuts	Cut points (NULL if no cut points).
hazards	The estimated constant levels.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
means	Means of the columns of the design matrix, except those columns corresponding to a factor level. Otherwise all zero.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).

n.events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
wald.test	The Wald test statistic (at the initial value).
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
call	The call.
method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).

Author(s)

Göran Broström

See Also

phreg, coxreg, link{aftreg}.

Examples

```
## Not run:
dat <- age.window(oldmort, c(60, 80))
fit <- pchreg(Surv(enter, exit, event) ~ ses.50 + sex,
data = dat, cuts = seq(60, 80, by = 4))
summary(fit)

fit.cr <- coxreg(Surv(enter, exit, event) ~ ses.50 + sex, data = dat)
check.dist(fit.cr, fit, main = "Cumulative hazards")

## End(Not run)
```

perstat *Period statistics*

Description

Calculates occurrence / exposure rates for time periods given by `period` and for ages given by `age`.

Usage

```
perstat(surv, period, age = c(0, 200))
```

Arguments

`surv`	An (extended) `surv` object (4 columns with `enter`, `exit`, `event`, `birthdate`)
`period`	A vector of dates (in decimal form)
`age`	A vector of length 2; lowest and highest age

Value

A list with components

`events`	No. of events in eavh time period.
`exposure`	Exposure times in each period.
`intensity`	`events / exposure`

Author(s)

Göran Broström

See Also

`piecewise`

phfunc *Loglihood function of a proportional hazards regression*

Description

Calculates minus the log likelihood function and its first and second order derivatives for data from a Weibull regression model.

Usage

```
phfunc(
  beta = NULL,
  lambda,
  p,
  X = NULL,
  Y,
  offset = rep(0, length(Y)),
  ord = 2,
  pfixed = FALSE,
  dist = "weibull"
)
```

Arguments

beta	Regression parameters
lambda	The scale paramater
p	The shape parameter
X	The design (covariate) matrix.
Y	The response, a survival object.
offset	Offset.
ord	ord = 0 means only loglihood, 1 means score vector as well, 2 loglihood, score and hessian.
pfixed	Logical, if TRUE the shape parameter is regarded as a known constant in the calculations, meaning that it is not cosidered in the partial derivatives.
dist	Which distribtion? The default is "weibull", with the alternatives "loglogistic" and "lognormal".

Details

Note that the function returns log likelihood, score vector and minus hessian, i.e. the observed information. The model is

$$S(t; p, \lambda, \beta, z) = S_0((t/\lambda)^p)^{e^(z\beta)}$$

Value

A list with components

f	The log likelihood. Present if ord >= 0
fp	The score vector. Present if ord >= 1
fpp	The negative of the hessian. Present if ord >= 2

Author(s)

Göran Broström

See Also

phreg

---

phreg *Parametric Proportional Hazards Regression*

Description

Proportional hazards model with parametric baseline hazard(s). Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data.

Usage

```
phreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  dist = "weibull",
  cuts = NULL,
  init,
  shape = 0,
  param = c("canonical", "rate"),
  control = list(eps = 1e-08, maxiter = 20, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  x = FALSE,
  y = TRUE
)
```

Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()$na.action.
dist	Which distribution? Default is "weibull", with the alternatives "ev" (Extreme value), "gompertz", "pch" (piecewise constant hazards function), "loglogistic" and "lognormal". A special case like the exponential can be obtained by choosing "weibull" in combination with shape = 1, or "pch" without cuts.
cuts	Only used with dist = "pch". Specifies the points in time where the hazard function jumps. If omitted, an exponential model is fitted.
init	vector of initial values of the iteration. Default initial value is zero for all variables.

shape — If positive, the shape parameter is fixed at that value (in each stratum). If zero or negative, the shape parameter is estimated. If more than one stratum is present in data, each stratum gets its own estimate. Only relevant for the Weibull and Extreme Value distributions.

param — Applies only to the Gompertz distribution: "canonical" is defined in the description of the Gompertz distribution; "rate" transforms scale to 1/log(scale), giving the same parametrization as in Stata and SAS. The latter thus allows for a negative rate, or a "cure" (Gompertz) model. The default is "canonical"; if this results in extremely large scale and/or shape estimates, consider trying "rate".

control — a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).

singular.ok — Not used.

model — Not used.

x — Return the design matrix in the model object?

y — Return the response in the model object?

Details

The parameterization is the same as in coxreg and coxph, but different from the one used by survreg (which is not a proportional hazards modelling function). The model is

$$S(t; a, b, \beta, z) = S_0((t/b)^a)^{\exp((z-mean(z))\beta)}$$

where S0 is some standardized survivor function.

Value

A list of class c("phreg", "coxreg") with components

coefficients — Fitted parameter estimates.

cuts — Cut points for the "pch" distribution. NULL otherwise.

hazards — The estimated constant levels in the case of the "pch" distribution. NULL otherwise.

var — Covariance matrix of the estimates.

loglik — Vector of length two; first component is the value at the initial parameter values, the second componet is the maximized value.

score — The score test statistic (at the initial value).

linear.predictors — The estimated linear predictors.

means — Means of the columns of the design matrix, except those columns corresponding to a factor level. Otherwise all zero.

w.means — Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.

n — Number of spells in indata (possibly after removal of cases with NA's).

n.events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
wald.test	The Wald test statistic (at the initial value).
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
call	The call.
method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).
pfixed	TRUE if shape was fixed in the estimation.

Warning

The lognormal and loglogistic distributions are included on an experimental basis for the moment. Use with care, results may be unreliable!

The gompertz distribution has an exponentially increasing hazard function under the canonical parametrization. This may cause instability in the convergence of the fitting algorithm in the case of near-exponential data. It may be resolved by using `param = "rate"`.

Note

The lognormal and loglogistic baseline distributions are extended to a three-parameter family by adding a "proportionality" parameter (multiplying the baseline hazard function). The log of the estimated parameter turns up as '(Intercept)' in the printed output. The reason for this extension is that the standard lognormal and loglogistic distributions are not closed under proportional hazards.

Author(s)

Göran Broström

See Also

coxreg, check.dist, link{aftreg}.

Examples

```
data(mort)
fit <- phreg(Surv(enter, exit, event) ~ ses, data = mort)
fit
plot(fit)
fit.cr <- coxreg(Surv(enter, exit, event) ~ ses, data = mort)
check.dist(fit.cr, fit)
```

---

phreg.fit *Parametric proportional hazards regression*

Description

This function is called by phreg, but it can also be directly called by a user.

Usage

```
phreg.fit(X, Y, dist, strata, offset, init, shape, control)
```

Arguments

X	The design (covariate) matrix.
Y	A survival object, the response.
dist	Which baseline distribution?
strata	A stratum variable.
offset	Offset.
init	Initial regression parameter values.
shape	If positive, a fixed value of the shape parameter in the distribution. Otherwise, the shape is estimated.
control	Controls convergence and output.

Details

See phreg for more detail.

Value

coefficients	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
var	Variance-covariance matrix
loglik	Vector of length 2. The first component is the maximized loglihood with only scale and shape in the model, the second the final maximum.
score	Score test statistic at initial values

linear.predictors	Linear predictors for each interval.
means	Means of the covariates
conver	TRUE if convergence
fail	TRUE if failure
iter	Number of Newton-Raphson iterates.
n.strata	The number of strata in the data.

Author(s)

Göran Broström

See Also

phreg

`piecewise` *Piecewise hazards*

Description

Calculate piecewise hazards, no. of events, and exposure times in each interval indicated by cutpoints.

Usage

```
piecewise(enter, exit, event, cutpoints)
```

Arguments

enter	Left interval endpoint
exit	Right interval endpoint
event	Indicator of event
cutpoints	Vector of cutpoints

Details

Exact calculation.

Value

A list with components

events	Vector of number of events
exposure	Vector of total exposure time
intensity	Vector of hazards, intensity == events / exposure

Author(s)

Göran Broström

See Also

perstat

---

plot.aftGompreg *Plots output from an AFT regression, aftGompreg.*

Description

Just a simple plot of the hazard (cumulative hazard, density, survival) functions for each stratum.

Usage

```
## S3 method for class 'aftGompreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = "Duration",
  ylab = "",
  col,
  lty,
  printLegend = TRUE,
  new.data = x$means,
  ...
)
```

Arguments

x	A aftGompreg object
fn	Which functions shoud be plotted! Default is the hazard function(s)
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
col	Colors?
lty	Line types?

printLegend	Logical, or character ("topleft", "bottomleft", "topright" or "bottomright"); if TRUE or character, a legend is added to the plot if the number of strata is two or more.
new.data	At which covariate values?
...	Extra parameters passed to 'plot'

Details

The plot is drawn at the mean values of the covariates, by default.

Value

No return value.

Author(s)

Göran Broström

See Also

aftreg

Examples

```
y <- rllogis(40, shape = 1, scale = 1)
x <- rep(c(1,1,2,2), 10)
fit <- aftreg(Surv(y, rep(1, 40)) ~ x, dist = "loglogistic")
plot(fit)
```

---

plot.aftreg *Plots output from an AFT regression*

Description

Just a simple plot of the hazard (cumulative hazard, density, survival) functions for each stratum.

Usage

```
## S3 method for class 'aftreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = "Duration",
  ylab = "",
```

```
  col,
  lty,
  printLegend = TRUE,
  new.data = x$means,
  ...
)
```

Arguments

x	A aftreg object
fn	Which functions shoud be plotted! Default is the hazard function(s)
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
col	Colors?
lty	Line types?
printLegend	Logical, or character ("topleft", "bottomleft", "topright" or "bottomright"); if TRUE or character, a legend is added to the plot if the number of strata is two or more.
new.data	At which covariate values?
...	Extra parameters passed to 'plot'

Details

The plot is drawn at the mean values of the covariates, by default.

Value

No return value.

Author(s)

Göran Broström

See Also

aftreg

Examples

```
y <- rllogis(40, shape = 1, scale = 1)
x <- rep(c(1,1,2,2), 10)
fit <- aftreg(Surv(y, rep(1, 40)) ~ x, dist = "loglogistic")
plot(fit)
```

plot.coxreg *Plot method for* coxreg *objects*

Description

A plot of a baseline function of a coxreg fit is produced, one curve for each stratum. A wrapper for plot.survfit.

Usage

```
## S3 method for class 'coxreg'
plot(
  x,
  fn = c("cum", "surv", "log", "loglog"),
  conf.int = FALSE,
  fig = TRUE,
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  xlab = "Duration",
  ylab = "",
  col = 1,
  lty = 1,
  printLegend = TRUE,
  ...
)
```

Arguments

x	A coxreg object
fn	What should be plotted? Default is "cumhaz", and the other choices are "surv", "log", and "loglog".
conf.int	logical or a value like 0.95 (default for one curve).
fig	logical. If TRUE the plot is actually drawn, otherwise only the coordinates of the curve(s) are returned.
xlim	Start and end of the x axis.
ylim	Start and end of the y axis.
main	A headline for the plot
xlab	Label on the x axis.
ylab	Label on the y axis.
col	Color of the curves. Defaults to 'black'.
lty	Line type(s).
printLegend	Either a logical or a text string; if TRUE, a legend is printed at a default place, if FALSE, no legend is printed. Otherwise, if a text string, it should be one of "bottomleft", "bottomright", "topleft", etc., see legend for all possible choices.
...	Other parameters to pass to the plot.

Value

An object of class hazdata containing the coordinates of the curve(s).

---

plot.hazdata *Plots of hazdata objects.*

Description

Baseline hazards estimates.

Usage

```
## S3 method for class 'hazdata'
plot(
  x,
  strata = NULL,
  fn = c("cum", "surv", "log", "loglog"),
  fig = TRUE,
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  xlab = "",
  ylab = "",
  col = "black",
  lty = 1,
  printLegend = TRUE,
  ...
)
```

Arguments

x	A hazdata object, typically the 'hazards' element in the output from link{coxreg} with method = "ml" or method = "mppl" or coxph = FALSE.
strata	Stratum names if there are strata present.
fn	Which type of plot? Allowed values are "cum" (or "cumhaz"), "surv" (or "sur"), "log", or "loglog". The last two plots the cumulative hazards on a log (y) scale or a log-log (xy) scale, respectively.
fig	Should a plot actually be produced? Default is TRUE.
xlim	Horizontal plot limits. If NULL, calculated by the function.
ylim	Vertical plot limits. If NULL, set to c(0, 1) for a plot of the survival function.
main	A heading for the plot.
xlab	Label on the x axis.
ylab	Label on the y-axis.
col	Color of the lines. May be a vector of length equal to No. of strata.

lty	Line type(s). May be a vector of length equal to No. of strata.
printLegend	Logical or character; should a legend be produced? Defaults to TRUE. If character, it should be one of bottomleft, bottomright, etc, see legend.
...	Anything that plot.default likes...

Details

It is also possible to have as first argument an object of type "coxreg", given that it contains a component of type "hazdata".

Value

A list where the elements are two-column matrices, one for each stratum in the model. The first column contains risktimes, and the second the y coordinates for the requested curve(s).

Note

x is a list where each element is a two-column matrix. The first column contains failure times, and the second column contains the corresponding 'hazard atoms'.

Author(s)

Göran Broström

Examples

```
time0 <- numeric(50)
group <- c(rep(0, 25), rep(1, 25))
x <- runif(50, -0.5, 0.5)
time1 <- rexp( 50, exp(group) )
event <- rep(1, 50)
fit <- coxreg(Surv(time0, time1, event) ~ x + strata(group), method = "ml")
plot(fit$hazards, col = 1:2, fn = "surv", xlab = "Duration")
## Same result as:
## plot(fit, col = 1:2, fn = "sur", xlab = "Duration")
```

---

plot.logrank *Plots of hazdata objects.*

Description

Baseline hazards estimates.

Usage

```
## S3 method for class 'logrank'
plot(
  x,
  fn = c("cum", "surv", "log", "loglog"),
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  xlab = "",
  ylab = "",
  col = "black",
  lty = 1,
  printLegend = TRUE,
  ...
)
```

Arguments

x	A logrank object, typically the 'hazards' element in the output from link{logrank}.
fn	Which type of plot? Allowed values are "cum" (or "cumhaz"), "surv" (or "sur"), "log", or "loglog". The last two plots the cumulative hazards on a log (y) scale or a log-log (xy) scale, respectively.
xlim	Horizontal plot limits. If NULL, calculated by the function.
ylim	Vertical plot limits. If NULL, set to c(0, 1) for a plot of the survival function.
main	A heading for the plot.
xlab	Label on the x axis.
ylab	Label on the y-axis.
col	Color of the lines. May be a vector of length equal to No. of strata.
lty	Line type(s). May be a vector of length equal to No. of strata.
printLegend	Logical or character; should a legend be produced? Defaults to TRUE. If character, it should be one of bottomleft, bottomright, etc, see legend.
...	Anything that plot.default likes...

Details

It is also possible to have as first argument an object of type "coxreg", given that it contains a component of type "hazdata".

Value

A list where the elements are two-column matrices, one for each stratum in the model. The first column contains risktimes, and the second the y coordinates for the requested curve(s).

Note

x is a list where each element is a two-column matrix. The first column contains failure times, and the second column contains the corresponding 'hazard atoms'.

Author(s)

Göran Broström

Examples

```
fit <- logrank(Surv(enter, exit, event), group = civ, data = oldmort[oldmort$region == "town", ])
plot(fit)
```

---

plot.phreg *Plots output from a phreg regression*

Description

Plot(s) of the hazard, density, cumulative hazards, and/or the survivor function(s) for each stratum.

Usage

```
## S3 method for class 'phreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = "Duration",
  ylab = "",
  col,
  lty,
  printLegend = TRUE,
  score = 1,
  fig = TRUE,
  ...
)
```

Arguments

x	A phreg object
fn	Which function should be plotted? Default is the hazard function(s).
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
col	Color(s) for the curves. Defaults to black.

lty	Line type for the curve(s). Defaults to 1:(No. of strata).
printLegend	Logical, or character ("topleft", "bottomleft", "topright" or "bottomright"); if TRUE or character, a legend is added to the plot if the number of strata is two or more.
score	Multiplication factor for the hazard function.
fig	logical, should the graph be drawn? If FALSE, data is returned.
...	Extra parameters passed to 'plot' and 'lines'.

Value

No return value if fig = TRUE, otherwise the cumulative hazards function (coordinates), given fn = "cum".

Note

Reference hazard is given by the fit; zero for all covariates, and the reference category for factors.

Author(s)

Göran Broström

See Also

phreg

Examples

```
y <- rllogis(40, shape = 1, scale = 1)
x <- rep(c(1,1,2,2), 10)
fit <- phreg(Surv(y, rep(1, 40)) ~ x, dist = "loglogistic")
plot(fit)
```

---

plot.tpchreg *Plots output from a tpchreg regression*

Description

Plot(s) of the hazard, cumulative hazards, and/or the survivor function(s) for each stratum.

Usage

```
## S3 method for class 'tpchreg'
plot(
  x,
  fn = c("haz", "cum", "sur"),
  log = "",
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = "Duration",
  ylab = "",
  col,
  lty,
  printLegend = TRUE,
  ...
)
```

Arguments

x	A tpchreg object
fn	Which functions should be plotted? Default is the hazard function.
log	character, "" (default), "y", or "xy".
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
col	Color(s) for the curves. Defaults to black.
lty	Line type for the curve(s). Defaults to 1:(No. of strata).
printLegend	Logical, or character ("topleft", "bottomleft", "topright" or "bottomright"); if TRUE or character, a legend is added to the plot if the number of strata is two or more.
...	Extra parameters passed to 'plot' and 'lines'.

Value

No return value.

Author(s)

Göran Broström

See Also

tpchreg

`plot.weibreg` *Plots output from a Weibull regression*

Description

Plot(s) of the hazard, density, cumulative hazards, and/or the survivor function(s) for each stratum.

Usage

```
## S3 method for class 'weibreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = NULL,
  ylab = NULL,
  new.data = x$means,
  ...
)
```

Arguments

`x`	A `weibreg` object
`fn`	Which functions shoud be plotted! Default is all. They will scroll by, so you have to take care explicitely what you want to be produced. See, eg, `par(mfrow = ...)`
`main`	Header for the plot
`xlim`	x limits
`ylim`	y limits
`xlab`	x label
`ylab`	y label
`new.data`	At which covariate values?
`...`	Extra parameters passed to 'plot'

Details

The plot is drawn at the mean values of the covariates.

Value

No return value

Author(s)

Göran Broström

See Also

phreg, weibreg

Examples

```
y <- rweibull(4, shape = 1, scale = 1)
x <- c(1,1,2,2)
fit <- weibreg(Surv(y, c(1,1,1,1)) ~ x)
plot(fit)
```

---

plotHaz *Graphical comparing of cumulative hazards*

Description

Comparison of the cumulative hazards functions for a semi-parametric and parametric models.

Usage

```
plotHaz(
  sp,
  pp,
  interval,
  main = NULL,
  xlab = "Time",
  ylab = "Cum. hazards",
  leglab,
  col = c("blue", "red"),
  lty = 1:2,
  ylim,
  log = "",
  printLegend = TRUE
)
```

Arguments

sp	An object of type "coxreg" or "phreg", typically output from coxreg or phreg.
pp	An object of type "coxreg" or "phreg", typically output from coxreg or phreg.
interval	Time interval for the plot, if missing, calculated from sp.
main	Header for the plot. Default is distribution and "cumulative hazard function"
xlab	Label on x axis (default "Time")

ylab	Label on y axis (default "Cum. Hazards")
leglab	Labels in legend.
col	Line colors. should be NULL (black lines) or of length 2
lty	line types.
ylim	Y limits for the plot.
log	Argument sent to plot, defaults to "".
printLegend	Should a legend be printed? Default is TRUE.

Details

For the moment only a graphical comparison. The arguments sp and pp may be swapped.

Value

No return value.

Author(s)

Göran Broström

See Also

check.dist, coxreg and phreg.

Examples

```
data(mort)
op <- par(mfrow = c(1, 2))
fit.cr <- coxreg(Surv(enter, exit, event) ~ ses, data = mort)
fit.w <- phreg(Surv(enter, exit, event) ~ ses, data = mort)
fit.g <- phreg(Surv(enter, exit, event) ~ ses, data = mort,
dist = "gompertz")
plotHaz(fit.cr, fit.w, interval = c(0, 20), main = "Weibull")
plotHaz(fit.cr, fit.g, main = "Gompertz")
par(op)
```

---

print.aftGompreg *Prints aftGompreg objects*

Description

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

Usage

```
## S3 method for class 'aftGompreg'
print(x, digits = max(options()$digits - 4, 3), ...)
```

Arguments

x	A aftreg object
digits	Precision in printing
...	Not used.

Value

No value is returned.

Note

Doesn't work for threeway or higher order interactions. Use print.coxph in that case.

Author(s)

Göran Broström

See Also

phreg, print.coxph

---

print.aftreg *Prints aftreg objects*

Description

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

Usage

```
## S3 method for class 'aftreg'
print(x, digits = max(options()$digits - 4, 3), ...)
```

Arguments

x	A aftreg object
digits	Precision in printing
...	Not used.

Value

No value is returned.

Note

Doesn't work for threeway or higher order interactions. Use print.coxph in that case.

Author(s)

Göran Broström

See Also

phreg, print.coxph

`print.coxreg` *Prints coxreg objects*

Description

More "pretty-printing" than `print.coxph`, which is a fall-back for 'difficult' objects.

Usage

```
## S3 method for class 'coxreg'
print(x, digits = max(options()$digits - 4, 3), ...)
```

Arguments

`x`	A `coxreg` object, typically the result of running `coxreg`
`digits`	Output format.
`...`	Other arguments.

Details

Doesn't work with three-way and higher interactions, in which case `print.coxph` is used.

Value

No value is returned.

Author(s)

Göran Broström

See Also

coxreg, print.coxph

print.logrank *Prints logrank objects*

Description

The result of logrank is printed

Usage

```
## S3 method for class 'logrank'
print(x, digits = max(options()$digits - 4, 6), ...)
```

Arguments

x	A logrank object
digits	Precision in printing
...	Not used.

Value

The input is returned invisibly.

Author(s)

Göran Broström

See Also

logrank, coxreg

print.phreg *Prints phreg objects*

Description

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

Usage

```
## S3 method for class 'phreg'
print(x, digits = max(options()$digits - 4, 3), ...)
```

Arguments

x	A phreg object
digits	Precision in printing
...	Not used.

Value

No value is returned.

Note

Doesn't work for threeway or higher order interactions. Use print.coxph in that case.

Author(s)

Göran Broström

See Also

phreg, print.coxph

---

print.risksets *Prints a summary of the content of a set of risk sets.*

Description

Given the output from risksets, summary statistics are given for it.

Usage

```
## S3 method for class 'risksets'
print(x, ...)
```

Arguments

x	An object of class 'risksets'.
...	Not used for the moment.

Value

No value is returned; the function prints summary statistics of risk sets.

Note

There is no summary.risksets yet. On the TODO list.

Author(s)

Göran Broström

See Also

risksets

Examples

```
rs <- with(mort, risksets(Surv(enter, exit, event)))
print(rs)
```

---

print.summary.aftGompreg

Prints summary.aftGompreg objects

Description

Prints summary.aftGompreg objects

Usage

```
## S3 method for class 'summary.aftGompreg'
print(x, digits = max(getOption("digits") - 3, 3), short = FALSE, ...)
```

Arguments

x	A summary.aftreg object, typically the result of running summary.aftreg, summary on a phreg object.
digits	Output format.
short	Logical: If TRUE, short output, only regression.
...	Other arguments.

Value

No value is returned.

Author(s)

Göran Broström

See Also

aftreg, summary.aftreg

print.summary.aftreg *Prints summary.aftreg objects*

Description

Prints summary.aftreg objects

Usage

```
## S3 method for class 'summary.aftreg'
print(x, digits = max(getOption("digits") - 3, 3), short = FALSE, ...)
```

Arguments

x	A summary.aftreg object, typically the result of running summary.aftreg, summary on a phreg object.
digits	Output format.
short	Logical: If TRUE, short output, only regression.
...	Other arguments.

Value

No value is returned.

Author(s)

Göran Broström

See Also

aftreg, summary.aftreg

print.summary.coxreg *Prints summary.coxreg objects*

Description

Prints summary.coxreg objects

Usage

```
## S3 method for class 'summary.coxreg'
print(x, digits = 3, short = FALSE, ...)
```

Arguments

x	A summary.coxreg object, typically the result of running summary.coxreg, summary on a coxreg object.
digits	Output format.
short	Logical, short or long (default) output?
...	Other arguments.

Value

No value is returned.

Author(s)

Göran Broström

See Also

coxreg, summary.coxreg

---

print.summary.phreg *Prints summary.phreg objects*

Description

Prints summary.phreg objects

Usage

```
## S3 method for class 'summary.phreg'
print(x, digits = max(getOption("digits") - 3, 3), ...)
```

Arguments

x	A summary.phreg object, typically the result of running summary.phreg, summary on a phreg object.
digits	Output format.
...	Other arguments.

Value

No value is returned.

Author(s)

Göran Broström

See Also

phreg, summary.phreg

`print.summary.tpchreg` *Prints summary.tpchreg objects*

Description

Prints summary.tpchreg objects

Usage

```
## S3 method for class 'summary.tpchreg'
print(x, digits = max(getOption("digits") - 3, 3), ...)
```

Arguments

`x`	A `summary.tpchreg` object, typically the result of running `summary.tpchreg`, summary on a tpchreg object.
`digits`	Output format.
`...`	Other arguments.

Value

No value is returned.

Author(s)

Göran Broström

See Also

tpchreg, summary.tpchreg

print.tpchreg *Prints tpchreg objects*

Description

More "pretty-printing"

Usage

```
## S3 method for class 'tpchreg'
print(x, digits = max(options()$digits - 4, 3), ...)
```

Arguments

x	A tpchreg object, typically the result of running tpchreg
digits	Output format.
...	Other arguments.

Details

Doesn't work with three-way or higher interactions.

Value

No value is returned.

Author(s)

Göran Broström

See Also

tpchreg, print.coxreg

print.weibreg *Prints weibreg objects*

Description

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

Usage

```
## S3 method for class 'weibreg'
print(x, digits = max(options()$digits - 4, 3), ...)
```

Arguments

x	A weibreg object
digits	Precision in printing
...	Not used.

Value

No value is returned.

Note

Doesn't work for threeway or higher order interactions. Use print.coxph in that case.

Author(s)

Göran Broström

See Also

weibreg, print.coxph

---

regtable *Retrieves regression tables*

Description

Retrieves regression tables

Usage

```
regtable(x, digits = 3, short = TRUE, ...)
```

Arguments

x	A summary.XXreg object, typically the result of running summary.XXreg, summary on a XXreg object.
digits	Output format.
short	If TRUE, return only coefficients table.
...	Other arguments.

Value

A character data frame, ready to print in various formats.

Note

Should not be used if interactions present.

Author(s)

Göran Broström

See Also

coxreg, summary.coxreg

`risksets` *Finds the compositions and sizes of risk sets*

Description

Focus is on the risk set composition just prior to a failure.

Usage

```
risksets(
  x,
  strata = NULL,
  max.survs = NULL,
  members = TRUE,
  collate_sets = FALSE
)
```

Arguments

`x`	A `Surv` object.
`strata`	Stratum indicator.
`max.survs`	Maximum number of survivors in each risk set. If smaller than the 'natural number', survivors are sampled from the present ones. No sampling if missing.
`members`	If TRUE, all members of all risk sets are listed in the resulting list, see below.
`collate_sets`	logical. If TRUE, group information by risk sets in a list. Only if `members = TRUE`.

Details

If the input argument max.survs is left alone, all survivors are accounted for in all risk sets.

Value

A list with components (if `collate_sets = FALSE`)

`antrs`	No. of risk sets in each stratum. The number of strata is given by `length(antrs)`.
`risktimes`	Ordered distinct failure time points.
`eventset`	If 'members' is TRUE, a vector of pointers to events in each risk set, else NULL.

riskset	If 'members' is TRUE, a vector of pointers to the members of the risk sets, in order. The 'n.events' first are the events. If 'members' is FALSE, 'riskset' is NULL.
size	The sizes of the risk sets.
n.events	The number of events in each risk set.
sample_fraction	If 'members' is TRUE, the sampling fraction of survivors in each risk set.

Note

Can be used to "sample the risk sets".

Author(s)

Göran Broström

See Also

table.events, coxreg.

Examples

```
enter <- c(0, 1, 0, 0)
exit <- c(1, 2, 3, 4)
event <- c(1, 1, 1, 0)
risksets(Surv(enter, exit, event))
```

---

rmsGomp *Restricted mean survival calculation for the Gompertz distribution by numerical integration of the survival function.*

Description

Restricted mean survival calculation for the Gompertz distribution by numerical integration of the survival function.

Usage

```
rmsGomp(
  from = 0,
  to = Inf,
  scale = 1,
  shape = 1,
  param = c("canonical", "rate"),
  fit
)
```

Arguments

from	Start time for the integration
to	Stop time of the integration.
scale	The scale parameter.
shape	The shape parameter.
param	Which parametrization? Defaults to 'canonical', the other choice is 'rate' (not developed yet, avoid until next version of eha!).
fit	The result of a call to 'aftGompreg'. If not missing, scale and shape will be taken from the fit, and corresponding argumens in the call will be ignored.

Examples

```
res <- aftGompreg(Surv(enter-60, exit-60, event) ~ ses.50 + strata(sex), data = oldmort)
rmsGomp(from = 0, to = 40, fit = res)
```

---

scania *Old age mortality, Scania, southern Sweden, 1813-1894.*

Description

The data consists of old age life histories from 1 January 1813 to 31 december 1894. Only (parts of) life histories above age 50 is considered.

Usage

```
data(scania)
```

Format

A data frame with 1931 observations from 1931 persons on the following 9 variables.

`id` Identification number (enumeration).

`enter` Start age for the interval.

`exit` Stop age for the interval.

`event` Indicator of death; equals `TRUE` if the person died at the end of the interval, `FALSE` otherwise.

`birthdate` Birthdate as a real number (i.e., "1765-06-27" is 1765.490).

`sex` Gender, a factor with levels `male` `female`.

`parish` One of five parishes in Scania, coded 1, 2, 3, 4, 5. Factor.

`ses` Socio-economic status at age 50, a factor with levels `upper` and `lower`.

`immigrant` a factor with levels `no` `region` and `yes`.

Details

The Scanian area in southern Sweden was during the 19th century a mainly rural area.

Source

The Scanian Economic Demographic Database, Lund University, Sweden.

References

https://www.lusem.lu.se/organisation/research-centres/centre-economic-demography/cedpop-databases-ced

Examples

```
data(scania)
summary(scania)
```

`summary.aftGompreg` *Creates a summary of aftGompreg objects*

Description

Creates a summary of aftGompreg objects

Usage

```
## S3 method for class 'aftGompreg'
summary(object, ...)
```

Arguments

`object`	A `aftGompreg` object
`...`	Additional ...

Author(s)

Göran Broström

See Also

`summary.aftreg`

Examples

```
## The function is currently defined as
function (object, ...)
print(object)
```

summary.aftreg *Summarizes aftreg objects*

Description

Summarizes aftreg objects

Usage

```
## S3 method for class 'aftreg'
summary(object, ...)
```

Arguments

object	A aftreg object
...	Additional ...

Author(s)

Göran Broström

See Also

print.coxreg

Examples

```
## The function is currently defined as
function (object, ...)
print(object)
```

summary.coxreg *A summary of coxreg objects.*

Description

A summary of coxreg objects.

Usage

```
## S3 method for class 'coxreg'
summary(object, ...)
```

Arguments

object	A coxreg object
...	Additional ...

Author(s)

Göran Broström

See Also

print.coxreg

Examples

```
fit <- coxreg(Surv(enter, exit, event) ~ sex + civ, data = oldmort)
summary(fit)
```

---

summary.phreg *A summary of phreg objects.*

Description

A summary of phreg objects.

Usage

```
## S3 method for class 'phreg'
summary(object, ...)
```

Arguments

object	A phreg object
...	Additional ...

Author(s)

Göran Broström

See Also

print.phreg

Examples

```
fit <- phreg(Surv(enter, exit, event) ~ sex + civ,
data = oldmort[oldmort$region == "town", ])
summary(fit)
```

summary.tpchreg *Summary for tpchreg objects*

Description

Summary for tpchreg objects

Usage

```
## S3 method for class 'tpchreg'
summary(object, ci = FALSE, level = 0.95, ...)
```

Arguments

object	A tpchreg object.
ci	Logical. If TRUE, confidence limits are given instead of se's.
level	Confidence level, used if ci.
...	Additional ...

Author(s)

Göran Broström

See Also

tpchreg

Examples

```
## The function is currently defined as
## function (object, ...)
```

summary.weibreg *Prints a weibreg object*

Description

This is the same as print.weibreg

Usage

```
## S3 method for class 'weibreg'
summary(object, ...)
```

Arguments

object	A weibreg object
...	Additional ...

Author(s)

Göran Broström

See Also

print.weibreg

Examples

```
## The function is currently defined as
function (object, ...)
print(object)
```

SurvSplit *Split a survival object at specified durations.*

Description

Given a survival object, (a matrix with two or three columns) and a set of specified cut times, split each record into multiple subrecords at each cut time. The new survival object will be in 'counting process' format, with an enter time, exit time, and event status for each record.

Usage

```
SurvSplit(Y, cuts)
```

Arguments

Y	A survival object, a matrix with two or three columns.
cuts	The cut points, must be strictly positive and distinct.

Value

A list with components

Y	The new survival object with three columns, i.e., in 'counting process' form.
ivl	Interval No., starting from leftmost, (0, cuts[1]) or similar.
idx	Row number for original Y row.

Note

This function is used in phreg for the piecewise constant hazards model. It uses age.window for each interval.

Author(s)

Göran Broström

See Also

survSplit, age.window.

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==>  Define data, use random,
##-- or do  help(data=index)  for the standard data sets.

## The function is currently defined as
function(Y, cuts){
    if (NCOL(Y) == 2) Y <- cbind(rep(0, NROW(Y)), Y)
    indat <- cbind(Y, 1:NROW(Y), rep(-1, NROW(Y)))
    colnames(indat) <- c("enter", "exit", "event", "idx", "ivl")
    n <- length(cuts)
    cuts <- sort(cuts)
    if ((cuts[1] <= 0) || (cuts[n] == Inf))
        stop("'cuts' must be positive and finite.")
    cuts <- c(0, cuts, Inf)
    n <- n + 1
    out <- list()
    indat <- as.data.frame(indat)
    for (i in 1:n){
        out[[i]] <- age.window(indat, cuts[i:(i+1)])
        out[[i]]$ivl <- i
        out[[i]] <- t(out[[i]])
    }
    Y <- matrix(unlist(out), ncol = 5, byrow = TRUE)
    colnames(Y) <- colnames(indat)
    list(Y = Y[, 1:3],
         ivl = Y[, 5],
         idx = Y[, 4]
         )
  }
```

---

swedeaths *Swedish death data, 1969-2020.*

Description

A data frame containing data on the number of deaths by sex, age and year, Sweden 1969-2020.

Usage

```
data(swedeaths)
```

Format

A data frame with 5 variables and 10504 observations.

`age` Numerical with integer values 0-100, representing achieved age in years during the actual calendar year. The highest value, 100, represents ages 100 and above.

`sex` A factor with two levels, "women" and "men".

`year` Calendar year.

`deaths` Number of deaths by age, sex, and year.

`id` Created by the `reshape` procedure, see Details.

Details

Data are downloaded from Statistics Sweden in the form of a csv file and and in that process converted to a data frame. Variable names are translated from Swedish, and some of them are coverted to factors. Each numeric column contains the number of deaths by sex and age. The original data set is in wide form and then converted to long format.

Source

Statistics Sweden, https://www.scb.se.

See Also

swepop, tpchreg

Examples

```
summary(swedeaths)
## maybe str(swedeaths) ...
```

swepop *Swedish population data, 1969-2020.*

Description

A data frame containing data on the population size by sex, age and year, Sweden 1969-2020.

Usage

```
data(swepop)
```

Format

A data frame with 5 variables and 10504 observations.

`age` Numerical with integer values 0-100, representing achieved age in years during the actual calendar year.The highest value, 100, represents ages 100 and above.

`sex` A factor with two levels, "women" and "men".

`year` Calendar year.

`pop` Average population by age, sex, and year.

id Created by the `reshape` procedure, see Details.

Details

Data are downloaded from Statistics Sweden in the form of a csv file and converted to a data frame. Variable names are translated from Swedish, and some of them are coverted to factors. The variable `pop` contains the average population by sex and age, calculated by taking the mean value of the population size at December 31 the previous year and December 31 the current year. The original data contain the sizes at the end of each year. The original data set is in wide format and converted to long format by `reshape`.

Source

Statistics Sweden, https://www.scb.se.

See Also

swedeaths

Examples

```
summary(swepop)
## maybe str(swepop) ...
```

`table.events` *Calculating failure times, risk set sizes and No. of events in each risk set*

Description

From input data of the 'interval' type, with an event indicator, summary statistics for each risk set (at an event time point) are calculated.

Usage

```
table.events(enter = rep(0, length(exit)), exit, event, strict = TRUE)
```

Arguments

`enter`	Left truncation time point.
`exit`	End time point, an event or a right censoring.
`event`	Event indicator.
`strict`	If TRUE, then tabulating is not done after a time point where all individuals in a riskset failed.

Value

A list with components

`times`	Ordered distinct event time points.
`events`	Number of events at each event time point.
`riskset.sizes`	Number at risk at each event time point.

Author(s)

Göran Broström

See Also

`risksets`

Examples

```
exit = c(1,2,3,4,5)
event = c(1,1,0,1,1)
table.events(exit = exit, event = event)
```

`toBinary` *Transforms a "survival" data frame into a data frame suitable for binary (logistic) regression*

Description

The result of the transformation can be used to do survival analysis via logistic regression. If the `cloglog` link is used, this corresponds to a discrete time analogue to Cox's proportional hazards model.

Usage

```
toBinary(
  dat,
  surv = c("enter", "exit", "event"),
  strats,
  max.survs = NROW(dat)
)
```

Arguments

`dat`	A data frame with three variables representing the survival response. The default is that they are named `enter`, `exit`, and `event`
`surv`	A character vector with the names of the three variables representing survival.
`strats`	An eventual stratification variable.
`max.survs`	Maximal number of survivors per risk set. If set to a (small) number, survivors are sampled from the risk sets.

Details

toBinary calls `risksets` in the `eha` package.

Value

Returns a data frame expanded risk set by risk set. The three "survival variables" are replaced by a variable named `event` (which overwrites an eventual variable by that name in the input). Two more variables are created, `riskset` and `orig.row`.

`event`	Indicates an event in the corresponding risk set.
`riskset`	Factor (with levels 1, 2, ...) indicating risk set.
`risktime`	The 'risktime' (age) in the corresponding riskset.
`orig.row`	The row number for this item in the original data frame.

Note

The survival variables must be three. If you only have *exit* and *event*, create a third containing all zeros.

Author(s)

Göran Broström

See Also

coxreg, glm.

Examples

```
enter <- rep(0, 4)
exit <- 1:4
event <- rep(1, 4)
z <- rep(c(-1, 1), 2)
dat <- data.frame(enter, exit, event, z)
binDat <- toBinary(dat)
dat
binDat
coxreg(Surv(enter, exit, event) ~ z, method = "ml", data = dat)
## Same as:
summary(glm(event ~ z + riskset, data = binDat, family = binomial(link = cloglog)))
```

---

toDate *Convert time in years since "0000-01-01" to a date.*

Description

This function uses `as.Date` and a simple linear transformation.

Usage

```
toDate(times)
```

Arguments

`times`	a vector of durations

Value

A vector of dates as character strings of the type "1897-05-21".

Author(s)

Göran Broström

See Also

toTime

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==>  Define data, use random,
##-- or do  help(data=index)  for the standard data sets.
toDate(1897.357)
```

`toTime` *Calculate duration in years from "0000-01-01" to a given date*

Description

Given a vector of dates, the output is a vector of durations in years since "0000-01-01".

Usage

```
toTime(dates)
```

Arguments

`dates`	A vector of dates in character form or of class `Date`

Value

A vector of durations, as decribed above.

Author(s)

Göran Broström

See Also

`toDate`

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==>  Define data, use random,
##-- or do  help(data=index)  for the standard data sets.


toTime(c("1897-05-16", "1901-11-21"))
```

toTpch *Transform survival data to tabular form*

Description

Transform a "survival data frame" to tabular form aggregating number of events and exposure time by time intervals and covariates.

Usage

```
toTpch(formula, data, cuts, enter = "enter", exit = "exit",
event = "event", episode = "age")
```

Arguments

formula	A model formula.
data	A data frame with survival data.
cuts	An ordered, non-negative vector of time points at which a hazard function changes value. Note that data are left truncated at cuts[1] (the smallest value) and right censored at c[n], where n is the length of cuts and cuts[n] == max(cuts).
enter	Character string with the name of the variable representing left truncation values.
exit	Character string with the name of the event/censoring time variable.
event	Character string with the name of the event indicator variable.
episode	Character string with the name of the output variable of the grouped time (a factor variable).

Details

If cuts is missing, nothing is done. Internally, this function first calls survival::survSplit and then stats::aggregate.

Value

A data frame with exposure time and number of events aggregated by time intervals and covariates. If all covariates are factors,this usually results in a huge reduction of the size of thedata frame, but otherwise the size of the output may be larger than the size of the input data frame

Note

Episodes, or parts of episodes, outside min(cuts), max(cuts) are cut off. With continuous covariates, consider rounding them so that the number of distinct oberved values is not too large.

Author(s)

Göran Broström

tpchreg *Proportional hazards regression with piecewise constant hazards and tabular data.*

Description

Proportional hazards regression with piecewise constant hazards and tabular data.

Usage

```
tpchreg(formula, data, time, weights, last, subset, na.action,
contrasts = NULL, start.coef = NULL,
control = list(epsilon = 1.e-8, maxit = 200, trace = FALSE))
```

Arguments

formula	a formula with 'oe(count, exposure) ~ x1 + ...'
data	a data frame with occurrence/exposure data plus covariates.
time	the time variable, a factor character vector indicating time intervals, or numeric, indicating the start of intervals.
weights	Case weights.
last	If time is numeric, the closing of the last interval.
subset	subset of data, not implemented yet.
na.action	Not implemented yet.
contrasts	Not implemented yet.
start.coef	For the moment equal to zero, not used.
control	list of control parameters for the optimization.

Note

The interpretation of cuts is different from that in hpch. This is intentional.

See Also

oe.

Examples

```
sw <- swepop
sw$deaths <- swedeaths$deaths
fit <- tpchreg(oe(deaths, pop) ~ strata(sex) + I(year - 2000),
time = age, last = 101, data = sw[sw$year >= 2000, ])
summary(fit)
```

`weibreg` *Weibull Regression*

Description

Proportional hazards model with baseline hazard(s) from the Weibull family of distributions. Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data.

Usage

```
weibreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  init,
  shape = 0,
  control = list(eps = 1e-04, maxiter = 10, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  x = FALSE,
  y = TRUE,
  center = TRUE
)
```

Arguments

`formula`	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
`data`	a data.frame in which to interpret the variables named in the formula.
`na.action`	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is `options()$na.action`.
`init`	vector of initial values of the iteration. Default initial value is zero for all variables.
`shape`	If positive, the shape parameter is fixed at that value (in each stratum). If zero or negative, the shape parameter is estimated. If more than one stratum is present in data, each stratum gets its own estimate.
`control`	a list with components `eps` (convergence criterion), `maxiter` (maximum number of iterations), and `silent` (logical, controlling amount of output). You can change any component without mention the other(s).
`singular.ok`	Not used.
`model`	Not used.
`x`	Return the design matrix in the model object?
`y`	Return the response in the model object?
`center`	Deprecated, and not used. Will be removed in the future.

Details

The parameterization is the same as in coxreg and coxph, but different from the one used by survreg. The model is

$$h(t; a, b, \beta, z) = (a/b)(t/b)^{a-1} exp(z\beta)$$

This is in correspondence with Weibull. To compare regression coefficients with those from survreg you need to divide by estimated shape ($\hat{a}$) and change sign. The p-values and test statistics are however the same, with one exception; the score test is done at maximized scale and shape in weibreg.

This model is a Weibull distribution with shape parameter a and scale parameter $b \exp(-z\beta/a)$

Value

A list of class c("weibreg", "coxreg") with components

coefficients	Fitted parameter estimates.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second componet is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
means	Means of the columns of the design matrix.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).
events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
wald.test	The Wald test statistic (at the initial value).
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
call	The call.
method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).
pfixed	TRUE if shape was fixed in the estimation.

Warning

The print method `print.weibreg` doesn't work if threeway or higher order interactions are present.

Note further that covariates are internally centered, if `center = TRUE`, by this function, and this is not corrected for in the output. This affects the estimate of $\log(scale)$, but nothing else. If you don't like this, set `center = FALSE`.

Note

This function is not maintained, and may behave in unpredictable ways. Use `phreg` with `dist = "weibull"` (the default) instead! Will soon be declared deprecated.

Author(s)

Göran Broström

See Also

`phreg`, `coxreg`, `print.weibreg`

Examples

```
dat <- data.frame(time = c(4, 3, 1, 1, 2, 2, 3),
                  status = c(1, 1, 1, 0, 1, 1, 0),
                  x = c(0, 2, 1, 1, 1, 0, 0),
                  sex = c(0, 0, 0, 0, 1, 1, 1))
weibreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
```

---

weibreg.fit *Weibull regression*

Description

This function is called by `weibreg`, but it can also be directly called by a user.

Usage

```
weibreg.fit(X, Y, strata, offset, init, shape, control, center = TRUE)
```

Arguments

`X`	The design (covariate) matrix.
`Y`	A survival object, the response.
`strata`	A stratum variable.
`offset`	Offset.
`init`	Initial regression parameter values.

shape	If positive, a fixed value of the shape parameter in the Weibull distribution. Otherwise, the shape is estimated.
control	Controls convergence and output.
center	Should covariates be centered?

Details

See weibreg for more detail.

Value

coefficients	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
var	
loglik	Vector of length 2. The first component is the maximized loglihood with only scale and shape in the model, the second the final maximum.
score	Score test statistic at initial values
linear.predictors	Linear predictors for each interval.
means	Means of the covariates
conver	TRUE if convergence
fail	TRUE if failure
iter	Number of Newton-Raphson iterates.
n.strata	The number of strata in the data.

Author(s)

Göran Broström

See Also

weibreg

Weibull *The (Cumulative) Hazard Function of a Weibull Distribution*

Description

hweibull calculates the hazard function of a Weibull distribution, and Hweibull calculates the corresponding cumulative hazard function.

Usage

```
hweibull(x, shape, scale = 1, log = FALSE)
```

Arguments

x	Vector of quantiles.
shape	The shape parameter.
scale	The scale parameter, defaults to 1.
log	logical; if TRUE, the log of the hazard function is given.

Details

See dweibull.

Value

The (cumulative) hazard function, evaluated at x.

Author(s)

Göran Broström

See Also

pweibull

Examples

```
hweibull(3, 2, 1)
dweibull(3, 2, 1) / pweibull(3, 2, 1, lower.tail = FALSE)
Hweibull(3, 2, 1)
-pweibull(3, 2, 1, log.p = TRUE, lower.tail = FALSE)
```

---

wfunk *Loglihood function of a Weibull regression*

Description

Calculates minus the log likelihood function and its first and second order derivatives for data from a Weibull regression model. Is called by weibreg.

Usage

```
wfunk(
  beta = NULL,
  lambda,
  p,
  X = NULL,
  Y,
  offset = rep(0, length(Y)),
```

```
  ord = 2,
  pfixed = FALSE
)
```

Arguments

beta	Regression parameters
lambda	The scale paramater
p	The shape parameter
X	The design (covariate) matrix.
Y	The response, a survival object.
offset	Offset.
ord	ord = 0 means only loglihood, 1 means score vector as well, 2 loglihood, score and hessian.
pfixed	Logical, if TRUE the shape parameter is regarded as a known constant in the calculations, meaning that it is not cosidered in the partial derivatives.

Details

Note that the function returns log likelihood, score vector and minus hessian, i.e. the observed information. The model is

$$h(t; p, \lambda, \beta, z) = p/\lambda(t/\lambda)^{(p-1)} \exp\left(-(t/\lambda)^p\right) \exp(z\beta)$$

This is in correspondence with dweibull.

Value

A list with components

f	The log likelihood. Present if ord >= 0
fp	The score vector. Present if ord >= 1
fpp	The negative of the hessian. Present if ord >= 2

Author(s)

Göran Broström

See Also

weibreg

Index

∗ **cluster**
toBinary, 98
∗ **datasets**
child, 16
fert, 29
infants, 35
logrye, 40
male.mortality, 46
mort, 50
oldmort, 51
scania, 88
swedeaths, 94
swepop, 96
∗ **distribution**
check.dist, 14
compHaz, 17
coxfunk, 18
EV, 28
Gompertz, 32
Loglogistic, 37
Lognormal, 38
makeham, 45
Pch, 52
phfunc, 56
plotHaz, 74
wfunk, 107
∗ **dplot**
plot.aftGompreg, 63
plot.aftreg, 64
plot.phreg, 70
plot.tpchreg, 71
plot.weibreg, 73
∗ **manip**
check.surv, 15
cro, 27
join.spells, 36
SurvSplit, 93
toTpch, 101
∗ **nonparametric**
perstat, 56
piecewise, 62
∗ **printing**
ltx, 41
ltx2, 42
∗ **print**
summary.aftreg, 90
summary.coxreg, 90
summary.weibreg, 92
∗ **regression**
aftGompreg, 5
aftGompreg.fit, 7
aftreg, 8
aftreg.fit, 11
coxreg, 19
coxreg.fit, 22
coxreg2, 24
mlreg, 47
pchreg, 53
phreg, 58
phreg.fit, 61
print.aftGompreg, 75
print.aftreg, 76
print.logrank, 78
print.phreg, 78
print.weibreg, 84
tpchreg, 102
weibreg, 103
weibreg.fit, 105
∗ **summary**
print.risksets, 79
summary.aftGompreg, 89
summary.tpchreg, 92
∗ **survival**
aftGompreg, 5
aftGompreg.fit, 7
aftreg, 8
aftreg.fit, 11
age.window, 12

cal.window, 13
check.surv, 15
coxfunk, 18
coxreg, 19
coxreg.fit, 22
coxreg2, 24
geome.fit, 31
join.spells, 36
logrank, 39
make.communal, 43
mlreg, 47
pchreg, 53
perstat, 56
phfunc, 56
phreg, 58
phreg.fit, 61
piecewise, 62
plot.aftGompreg, 63
plot.aftreg, 64
plot.hazdata, 67
plot.logrank, 68
plot.phreg, 70
plot.tpchreg, 71
plot.weibreg, 73
print.aftGompreg, 75
print.aftreg, 76
print.coxreg, 77
print.logrank, 78
print.phreg, 78
print.summary.aftGompreg, 80
print.summary.aftreg, 81
print.summary.coxreg, 81
print.summary.phreg, 82
print.summary.tpchreg, 83
print.tpchreg, 84
print.weibreg, 84
regtable, 85
risksets, 86
summary.aftGompreg, 89
summary.aftreg, 90
summary.coxreg, 90
summary.phreg, 91
summary.tpchreg, 92
summary.weibreg, 92
table.events, 97
toBinary, 98
toDate, 99
toTime, 100
tpchreg, 102
weibreg, 103
weibreg.fit, 105
Weibull, 106
wfunk, 107

∗ **table**
tpchreg, 102

aftGompreg, 5
aftGompreg.fit, 7
aftreg, *7*, 8, *8*, *11–13*, *16*, *37*, *41–44*, *64*, *65*, *80*, *81*
aftreg.fit, 11
age.window, 12, *13*, *94*

cal.window, 13, *13*, *44*
check.dist, 14, *60*, *75*
check.surv, 15, *37*
child, 16
compHaz, 17
coxfunk, 18
coxph, *4*, *20*, *21*, *25*, *27*, *44*, *59*, *104*
coxreg, *4*, *7*, *11*, *13*, *14*, *16–18*, 19, *22*, *23*, *31*, *37*, *39*, *41–44*, *48*, *49*, *55*, *59*, *60*, *74*, *75*, *77*, *78*, *82*, *86*, *87*, *99*, *104*, *105*
coxreg.fit, 22
coxreg2, 24
cro, 27

dEV *(*EV*)*, 28
dgompertz *(*Gompertz*)*, 32
dllogis *(*Loglogistic*)*, 37
dlnorm *(*Lognormal*)*, 38
dmakeham *(*makeham*)*, 45
dpch *(*Pch*)*, 52
dweibull, *107*, *108*

eha *(*eha-package*)*, 4
eha-package, 4
EV, 28

fert, 29
frail.fit, 30

geome.fit, 31
glm, *99*
Gompertz, 32, *59*
gompertz *(*Gompertz*)*, 32

hazards, *17*, 33

HEV (EV), 28
hEV (EV), 28
Hgompertz (Gompertz), 32
hgompertz (Gompertz), 32
HiscoHisclass, 33
Hllogis (Loglogistic), 37
hllogis (Loglogistic), 37
Hlnorm (Lognormal), 38
hlnorm (Lognormal), 38
Hmakeham (makeham), 45
hmakeham (makeham), 45
Hpch (Pch), 52
hpch, *102*
hpch (Pch), 52
Hweibull (Weibull), 106
hweibull (Weibull), 106

import_strata, 34
import_Surv, 34
infants, 35

join.spells, *16*, 36

legend, *66*, *68*, *69*
Llogis (Loglogistic), 37
Lnorm (Lognormal), 38
Loglogistic, 37
Lognormal, 38
logrank, 39, *78*
logrye, 40
ltx, 41, *43*
ltx2, *41*, 42

make.communal, 43
makeham, 45
male.mortality, 46
match, *28*
mlreg, 47
mort, 50
mpch (Pch), 52

oe, 51, *102*
oldmort, 51

paste, *28*
Pch, 52
pch (Pch), 52
pchreg, 53
perstat, 56, *63*
pEV (EV), 28
pgompertz (Gompertz), 32
phfunc, 56
phreg, *7*, *11*, *14*, *17*, *41–43*, *55*, 58, *58*, *61*, *62*, *71*, *74–77*, *79*, *83*, *94*, *105*
phreg.fit, 61
piecewise, *56*, 62
pllogis (Loglogistic), 37
plnorm (Lognormal), 38
plot.aftGompreg, 63
plot.aftreg, 64
plot.coxreg, 66
plot.default, *68*, *69*
plot.hazdata, 67
plot.logrank, 68
plot.phreg, 70
plot.survfit, *66*
plot.tpchreg, 71
plot.weibreg, 73
plotHaz, 74
pmakeham (makeham), 45
ppch (Pch), 52
print.aftGompreg, 75
print.aftreg, 76
print.coxph, *76*, *77*, *79*, *85*
print.coxreg, 77, *84*, *90*, *91*
print.logrank, *39*, 78
print.phreg, 78, *91*
print.risksets, 79
print.summary.aftGompreg, 80
print.summary.aftreg, 81
print.summary.coxreg, 81
print.summary.phreg, 82
print.summary.tpchreg, 83
print.tpchreg, 84
print.weibreg, 84, *92*, *93*, *105*
pweibull, *107*

qEV (EV), 28
qgompertz (Gompertz), 32
qllogis (Loglogistic), 37
qlnorm (Lognormal), 38
qmakeham (makeham), 45
qpch (Pch), 52

regtable, 85
rEV (EV), 28
rgompertz (Gompertz), 32
risksets, *21*, *23*, *26*, *27*, *30*, *31*, *49*, 86, *97*
rllogis (Loglogistic), 37

rlnorm *(*Lognormal*)*, 38
rmakeham *(*makeham*)*, 45
rmsGomp, 87
rpch *(*Pch*)*, 52

scania, 88
strata, *34*
strata *(*import_strata*)*, 34
summary.aftGompreg, 89
summary.aftreg, *80, 81*, *89*, 90
summary.coxreg, *82*, *86*, 90
summary.phreg, *83*, 91
summary.tpchreg, *83*, 92
summary.weibreg, 92
Surv, *34*, *39*
Surv *(*import_Surv*)*, 34
survreg, *5–7*, *9*, *11*, *59*, *104*
SurvSplit, 93
survSplit, *94*
swedeaths, 94, *96*
swepop, *95*, 96

table.events, *87*, 97
toBinary, 98
toDate, 99, *100*
toTime, *99*, 100
toTpch, 101
tpchreg, *41, 42*, *51*, *72*, *83, 84*, *92*, *95*, 102

weibreg, *74*, *85*, 103, *105–108*
weibreg.fit, 105
Weibull, *104*, 106
wfunk, 107