

Package: emBALVI (via r-universe)

May 16, 2026

Title EM Bayesian Adaptive LASSO Variational Inference Based GWAS

Version 0.1.0

Description Performs Genome-Wide Association Study (GWAS) analysis using Expectation-Maximization Bayesian Adaptive LASSO with Variational Inference (emBALVI). Includes genotype preprocessing, genomic relationship matrix construction, GWAS analysis, Manhattan and QQ plotting.s.

Depends R (>= 4.0)

Imports ggplot2, RColorBrewer

Suggests rmarkdown, testthat (>= 3.0.0), roxygen2

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

NeedsCompilation no

Author Prakash Kumar [aut, cre], Himadri Sekhar Roy [aut], Ranjit Kumar Paul [aut], Md. Yeasin [aut], Neeraj Budhlakoti [aut], Sunil Kumar Yadav [aut], Amrit Kumar Paul [aut]

Maintainer Prakash Kumar <prakash289111@gmail.com>

Repository <https://cran.r-universe.dev>

Date/Publication 2026-04-16 09:53:08 UTC

RemoteUrl <https://github.com/cran/emBALVI>

RemoteRef HEAD

RemoteSha 56aff80a3a1a494f5403adc2b4b846865eaae4b9

Contents

buildGRM	2
convert_to_dosage	2
emBALVI	3

phenotypes_potatoyield	3
plot_manhattan	4
plot_qq	4
snp_NN_10_hmp	5

Index	6
--------------	----------

buildGRM	<i>Build VanRaden Genomic Relationship Matrix</i>
----------	---

Description

Build VanRaden Genomic Relationship Matrix

Usage

```
buildGRM(X)
```

Arguments

X Numeric genotype matrix

Value

GRM matrix

convert_to_dosage	<i>Convert HMP Genotype to Dosage</i>
-------------------	---------------------------------------

Description

Convert HMP Genotype to Dosage

Usage

```
convert_to_dosage(snp_matrix)
```

Arguments

snp_matrix SNP matrix

Value

Numeric dosage matrix

emBALVI

EM-BALVI GWAS

Description

Performs genome-wide association using expectation-maximization Bayesian adaptive LASSO with variational inference.

Usage

```
emBALVI(Y, X, B, G, max_iter = 20, tol = 1e-06)
```

Arguments

Y	Phenotype vector
X	Genotype matrix (numeric dosage)
B	Fixed effect design matrix
G	Genomic relationship matrix
max_iter	Maximum iterations
tol	Convergence tolerance

Value

Data frame of marker effects and p-values

phenotypes_potatoyield

Potato Yield Phenotype Dataset

Description

Phenotypic data used for GWAS analysis in emBALVI.

Usage

```
phenotypes_potatoyield
```

Format

A data frame with genotype IDs and yield phenotype.

Source

Real potato yield experiment dataset

plot_manhattan	<i>Manhattan Plot for emBALVI</i>
----------------	-----------------------------------

Description

Manhattan Plot for emBALVI

Usage

```
plot_manhattan(results)
```

Arguments

results	GWAS result data frame
---------	------------------------

Value

A ggplot object

plot_qq	<i>QQ Plot for emBALVI GWAS Results</i>
---------	---

Description

Generates a Quantile-Quantile (QQ) plot for GWAS p-values.

Usage

```
plot_qq(results)
```

Arguments

results	GWAS result data frame (must contain column 'p')
---------	--

Value

A ggplot object

snp_NN_10_hmp

SNP Genotype Dataset (HMP Format)

Description

Raw SNP genotype matrix in HapMap-like format.

Usage

snp_NN_10_hmp

Format

A data frame containing SNP markers and genotype calls.

Source

Real SNP dataset used for EM-BALVI GWAS

Index

* datasets

phenotypes_potatoyield, 3

snp_NN_10_hmp, 5

buildGRM, 2

convert_to_dosage, 2

emBALVI, 3

phenotypes_potatoyield, 3

plot_manhattan, 4

plot_qq, 4

snp_NN_10_hmp, 5