Package: epts (via r-universe)

October 19, 2026

Type Package

Title Educational Platform Trials Simulator

Version 1.2.2

Description Simulating multi-arm cluster-randomized, multi-site, and simple randomized trials. Includes functions for conducting multilevel analyses using both Bayesian and Frequentist methods. Supports futility and superiority analyses through Bayesian approaches, along with visualization tools to aid interpretation and presentation of results.

License AGPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

LazyData true

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Depends R (>= 4.3.0)

Imports eefAnalytics, lme4, ggplot2, ggpubr, methods, graphics, stats, mvtnorm, coda, MCMCvis, dplyr, magrittr, shiny

NeedsCompilation no

Author Mohammad Sayari [aut, cre], Akansha Singh [aut], Germaine Uwimpuhwe [aut], Jochen Einbeck [aut]

Maintainer Mohammad Sayari <md.sayari13@gmail.com>

Config/testthat/edition 3

Repository https://cran.r-universe.dev

Date/Publication 2025-05-20 08:44:18 UTC

RemoteUrl https://github.com/cran/epts

RemoteRef HEAD

RemoteSha d87f01ee5e7389ea092a6d27dfeef642f61be3d1

Contents

crt4armSimData . . . 2
crtAddIntervention . . . 3
crtDataSimulation . . . 4
futilityAnalysis . . . 6
mst4armSimData . . . 8
mstAddIntervention . . . 8
mstDataSimulation . . . 10
multiArmAnalysis . . . 12
plotPosteriorProbs . . . 15
runEPTS . . . 17
srt4armSimData . . . 18
srtAddIntervention . . . 19
srtDataSimulation . . . 20
superiorityAnalysis . . . 21

Index **24**

`crt4armSimData` *Simulated 4-Arm Cluster Randomized Trial (CRT) Data*

Description

A simulated cluster randomised trial dataset containing 10 schools and 1,000 pupils. This is a 4-arm trial design with one control group and three intervention groups.

Usage

```
crt4armSimData
```

Format

A data frame with 1,000 rows and 7 variables:

pupils Identifier for each pupil

schools Identifier for each school

interventions Treatment assignment coded as 0 for control and 1–3 for intervention groups

pretest Pre-test scores

gender Binary gender

ethnicity A categorical variable with 3 categories

posttest Post-test scores

Source

Simulated

`crtAddIntervention` *Add a New Intervention Group to Clustered Randomized Trial (CRT)*

Description

This function adds a new intervention group to an existing CRT dataset. It models post-test outcomes using fixed and random effects estimated from the original data and incorporates user-specified effect size and attrition for the new intervention.

Usage

```
crtAddIntervention(
  originalData,
  ns,
  np,
  es,
  attritionrate,
  outcome,
  interventions,
  schoolsID,
  pupilsID,
  continuous_covariates,
  categorical_covariates
)
```

Arguments

`originalData`	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention for CRT design.
`ns`	The number of schools to assign to the new intervention group.
`np`	The number of pupils per new school.
`es`	The standardized effect size for the new intervention group.
`attritionrate`	The proportion of pupils in the new group to drop due to attrition.
`outcome`	A string specifying the name of the column containing outcome variable (e.g., post-test scores).
`interventions`	A string specifying the name of the intervention assignment column.
`schoolsID`	A string specifying the name of the school ID column.
`pupilsID`	A string specifying the name of the pupil ID column.
`continuous_covariates`	A character vector specifying the names of continuous covariates in the model.
`categorical_covariates`	A character vector specifying the names of categorical covariates in the model (converted to factors).

Details

The function performs the following:

- Fits a linear mixed-effects model (`lmer`) to the original dataset using provided covariates.
- Applies the specified effect size (`es`) and generates new post-test scores.
- Simulates attrition by removing post-test scores at random.

Value

A `data.frame` combining the original and new intervention group, including post-test outcomes simulated for the new intervention based on the estimated mixed model.

See Also

`lmer` from the **lme4** package

Examples

```
data(crt4armSimData)
new_crt5armData <- crtAddIntervention(originalData = crt4armSimData, ns = 2,
np = 100, es = 0.3, attritionrate = 0.1, outcome = "posttest", interventions = "interventions",
schoolsID = "schools", pupilsID = "pupils",
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"))
head(new_crt5armData)
```

---

crtDataSimulation *Simulate Clustered Randomized Trial (CRT) Data*

Description

This function simulates a multiple intervention arms CRT data. The model includes intervention and pre-test scores as covariates.

Usage

```
crtDataSimulation(
  ni,
  nstreated,
  np,
  ns,
  sigma,
  ICC,
  B0,
  es,
  seed,
  attritionrates,
  covariates
)
```

Arguments

`ni`	The number of intervention groups excluding the control group.
`nstreated`	The number of schools in each group, including the control group. It should be specified as an integer vector of length ni + 1.
`np`	The number of pupils per school.
`ns`	The total number of schools.
`sigma`	The standard deviation of the individual-level error.
`ICC`	The intra-class correlation coefficient.
`B0`	The intercept of the model.
`es`	The standardized effect sizes for each intervention group. It should be specified as a numeric vector.
`seed`	The random seed for reproducibility.
`attritionrates`	The proportion of attrition for each group, including the control group. It should be specified as a numeric vector of length ni + 1.
`covariates`	List of covariate specifications. Each element should be a list with the following fields: **name** Character. Name of the covariate. **type** Character. Either `"continuous"` or `"categorical"`. **sd** Numeric. Standard deviation (only for continuous covariates). **coefficient** Numeric. Coefficient (only for continuous covariates). **levels** Character vector. Category levels (only for categorical covariates). **probs** Numeric vector. Sampling probabilities (must sum to 1) (categorical only). **reference** Character. Reference category (categorical only). **coefficients** Named list of numeric values. Coefficients for each non-reference level.

Value

A `data.frame` containing:

pupils Unique pupil ID

schools School ID

interventions Intervention group (0 = control, 1 to `ni` for interventions)

covariates Simulated covariates

posttest Simulated posttest scores (NA if attrited)

Examples

```
covariates <- list(
 list(name = "pretest", type = "continuous", sd = 1, coefficient = 1.7),
 list(name = "gender", type = "categorical", levels = c("Male", "Female"),
 probs = c(0.3, 0.7), reference = "Male", coefficients = list(B = -0.5)),
```

```
 list(name = "ethnicity", type = "categorical", levels = c("White", "Black", "Asian"),
 probs = c(0.3, 0.3, 0.4), reference = "White", coefficients = list(B = 1.02, C = 1.3))
)

crtdata <- crtDataSimulation(ni = 3, ns = 10, np = 100, nstreated = c(2, 3, 2, 3),
sigma = 1, ICC = 0.1, B0 = 1.45, es = c(0.1, 0.2, 0.5),
seed = 1234, attritionrates = c(0, 0.1, 0.2, 0.1), covariates = covariates)
head(crtdata)
```

`futilityAnalysis` *Futility Analysis Across Interventions for CRT, MST, or SRT Designs*

Description

This function performs a Bayesian futility analysis for each intervention group compared to control, across cluster randomized trials (CRT), multisite trials (MST) or simple randomized trials (SRT).

Usage

```
futilityAnalysis(
  method = c("crt", "mst", "srt"),
  data,
  outcome = "posttest",
  interventions = "interventions",
  Random = "schools",
  Nsim = 10000,
  Threshold = 0.05,
  FutThreshold = 0.8,
  continuous_covariates = NULL,
  categorical_covariates = NULL
)
```

Arguments

`method`	The trial design type: "crt", "mst", or "srt".
`data`	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention.
`outcome`	The name of the outcome (post-test) variable.
`interventions`	A string specifying the intervention variable.
`Random`	The name of the clustering variable (e.g., schools or sites) for CRT and MST designs.
`Nsim`	Number of MCMC iterations to be performed. A minimum of 10,000 is recommended to ensure convergence.
`Threshold`	The effect size threshold for posterior computation (default = 0.05).
`FutThreshold`	The minimum posterior probability threshold for non-futility (default = 0.8).

`continuous_covariates`
: A character vector specifying the names of continuous covariates.

`categorical_covariates`
: A character vector specifying the names of categorical covariates (converted to factors).

Details

The function loops over each intervention, fits the appropriate Bayesian model (`crtBayes`, `mstBayes`, `srtBayes`), extracts the posterior probability, and determines futility based on the specified probability threshold.

Value

A `data.frame` with columns:

- `Intervention`: Intervention group identifier.
- `Futility`: 1 if considered futile (posterior probability < FutThreshold), 0 otherwise.
- `ProbES`: Bayesian posterior probabilities that the observed effect size is greater than or equal to a pre-specified threshold

See Also

`crtBayes`, `mstBayes`, `srtBayes` functions from the **eefAnalytics** package

Examples

```
###Futility analysis of cluster randomized trial###
data(crt4armSimData)
futilityAnalysis(method = "crt", data = crt4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000,
Threshold = 0.05, FutThreshold = 0.8,continuous_covariates = c("pretest"),
categorical_covariates = c("gender", "ethnicity"))

###Futility analysis of multisite trial###
data(mst4armSimData)
futilityAnalysis(method = "mst", data = mst4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000,
Threshold = 0.05, FutThreshold = 0.8,continuous_covariates = c("pretest"),
categorical_covariates = c("gender", "ethnicity"))

###Futility analysis of simple randomized trial###
data(srt4armSimData)
futilityAnalysis(method = "srt", data = srt4armSimData, outcome = "posttest",
interventions = "interventions", Nsim = 10000, Threshold = 0.05, FutThreshold = 0.8,
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"))
```

mst4armSimData *Simulated 4-Arm Multisite Trial (MST) Data*

Description

A simulated multisite trial dataset containing 10 schools and 1,000 pupils. This is a 4-arm trial design with one control group and three intervention groups.

Usage

```
mst4armSimData
```

Format

A data frame with 1,000 rows and 7 variables:

pupils Identifier for each pupil

schools Identifier for each school

interventions Treatment assignment coded as 0 for control and 1–3 for intervention groups

pretest Pre-test scores

gender Binary gender

ethnicity A categorical variable with 3 categories

posttest Post-test scores

Source

Simulated

mstAddIntervention *Add a New Intervention Group to Multisite Trial (MST)*

Description

This function adds a new intervention group to an existing Multisite Trial (MST) dataset. It fits a linear mixed-effects model to the original data, then uses its estimates to generate post-test outcomes for the new group, incorporating random intercepts, slopes, and user-defined effect size.

Usage

```
mstAddIntervention(
  originalData,
  ns,
  np,
  es,
  attritionrate,
  intper,
  outcome,
  interventions,
  schoolsID,
  pupilsID,
  continuous_covariates,
  categorical_covariates
)
```

Arguments

originalData	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention for MST design.
ns	The number of schools to assign to the new intervention group.
np	The number of pupils per new school.
es	The standardized effect size for the new intervention group.
attritionrate	The proportion of pupils in the new group to drop due to attrition.
intper	Proportion of pupils per new school assigned to the Intervention group.
outcome	A string specifying the name of the column containing outcome variable (e.g., post-test scores).
interventions	A string specifying the name of the intervention assignment column.
schoolsID	A string specifying the name of the school ID column.
pupilsID	A string specifying the name of the pupil ID column.
continuous_covariates	A character vector specifying the names of continuous covariates.
categorical_covariates	A character vector specifying the names of categorical covariates (converted to factors).

Details

The function:

- Fits a linear mixed-effects model (`lmer`) with random slopes and intercepts using existing MST data.
- Simulates new schools and pupils, assigning intervention randomly by specified percentage.
- Simulates attrition by removing post-test scores at random.

Value

A `data.frame` containing the combined dataset with the newly added intervention group and simulated outcomes.

See Also

`lmer` from the **lme4** package

Examples

```
data(mst4armSimData)
new_mst5armData <- mstAddIntervention(originalData = mst4armSimData, ns = 2, np = 100, es = 0.3,
intper = 0.5, attritionrate = 0.1, outcome = "posttest", interventions = "interventions",
schoolsID = "schools", pupilsID = "pupils",
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"))
head(new_mst5armData)
```

---

mstDataSimulation *Simulate Multisite Trial (MST) Data*

Description

This function simulates a multiple intervention arms Multisite Trial (MST) data. The model includes intervention and pre-test scores as covariates.

Usage

```
mstDataSimulation(
  ni,
  tpi,
  np,
  ns,
  sigma,
  sigmab0,
  sigmab1,
  B0,
  es,
  seed,
  attritionrates,
  covariates
)
```

Arguments

ni	The number of intervention groups excluding the control group.
tpi	The proportions (in percent) of total participants assigned to each group, with the first value for the control group. It should be specified as a numeric vector of length ni + 1.
np	The number of pupils per school.
ns	The number of schools.
sigma	The standard deviation of the individual-level error.
sigmab0	The standard deviation of random intercepts at the school level.
sigmab1	The standard deviation of random slopes for the intervention effect.
B0	The intercept of the model.
es	The standardized effect sizes for each intervention group. It should be specified as a numeric vector.
seed	The random seed for reproducibility.
attritionrates	The attrition proportions for each group, including the control group. It should be specified as a numeric vector of length ni + 1.
covariates	List of covariate specifications. Each element should be a list with the following fields:

name Character. Name of the covariate.

type Character. Either "continuous" or "categorical".

sd Numeric. Standard deviation (only for continuous covariates).

coefficient Numeric. Coefficient (only for continuous covariates).

levels Character vector. Category levels (only for categorical covariates).

probs Numeric vector. Sampling probabilities (must sum to 1) (categorical only).

reference Character. Reference category (categorical only).

coefficients Named list of numeric values. Coefficients for each non-reference level.

Value

A data.frame containing:

pupils Pupil ID

schools School ID

interventions Intervention group assignment (0 = control, 1 to ni = intervention groups)

covariates Simulated covariates

posttest Posttest score (NA if attrited)

Examples

```
covariates <- list(
 list(name = "pretest", type = "continuous", sd = 1, coefficient = 1.7),
 list(name = "gender", type = "categorical", levels = c("Male", "Female"),
 probs = c(0.3, 0.7), reference = "Male", coefficients = list(B = -0.5)),
 list(name = "ethnicity", type = "categorical", levels = c("White", "Black", "Asian"),
 probs = c(0.3, 0.3, 0.4), reference = "White", coefficients = list(B = 1.02, C = 1.3))
)

mstdata <- mstDataSimulation(ni = 3, ns = 10, np = 100, tpi = c(30, 30, 20, 20),
sigma = 1, sigmab0 = 0.5, sigmab1 = 0.5, B0 = 1.45,
es = c(0.2, 0.3, 0.1), seed = 1234, attritionrates = c(0.1, 0.1, 0.1, 0), covariates = covariates)
head(mstdata)
```

`multiArmAnalysis` *Bayesian or Frequentist Analysis with Forest Plot Comparison for Multi-Arm Trial Designs*

Description

This function fits Bayesian or frequentist and producing a forest plot across multiple intervention groups for cluster randomized trials (CRT), multisite trials (MST) or simple randomized trials (SRT).

Usage

```
multiArmAnalysis(
  method = "crtBayes",
  data,
  outcome = "posttest",
  interventions = "interventions",
  Random = "schools",
  Nsim = 10000,
  Threshold = 0.05,
  FREQoption = "Default",
  nPerm = NULL,
  nBoot = NULL,
  bootType = NULL,
  continuous_covariates = NULL,
  categorical_covariates = NULL,
  maintitle = NULL,
  xlabel = NULL,
  ylabel = NULL,
  vlinecolor = "black",
  intlabels = NULL,
  intcolors = NULL
)
```

Arguments

method	The model fitting method. Should be specified as a character string. Choices are: • "crtBayes": Bayesian analysis of cluster randomised trials using vague priors. • "crtFREQ": Analysis of cluster randomised trials using a multilevel model under a frequentist setting. • "mstBayes": Bayesian analysis of multisite randomised trials using vague priors. • "mstFREQ": Analysis of multisite randomised trials using a multilevel model under a frequentist setting. • "srtBayes": Bayesian analysis of simple randomised trials using vague priors. • "srtFREQ": Analysis of simple randomised trials under a frequentist setting.
data	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention.
outcome	The name of the outcome (post-test) variable.
interventions	A string specifying the intervention variable.
Random	The name of the clustering variable (e.g., schools or sites) for CRT and MST designs.
Nsim	Number of MCMC iterations to be performed for Bayesian analysis. A minimum of 10,000 is recommended to ensure convergence.
Threshold	The effect size threshold for posterior computation for Bayesian analysis (default = 0.05).
FREQoption	The option for frequentist methods. Choices are "Default", "Permutation", or "Bootstrap".
nPerm	The number of permutations required to generate a permutated p-value.
nBoot	The number of bootstraps required to generate bootstrap confidence intervals.
bootType	method of bootstrapping including case re-sampling at student level "case(1)",case re-sampling at school level "case(2)", case re-sampling at both levels "case(1,2)" and residual bootstrapping using "residual". If not provided, default will be case re-sampling at student level.
continuous_covariates	A character vector specifying the names of continuous covariates.
categorical_covariates	A character vector specifying the names of categorical covariates (converted to factors).
maintitle	main title for the plot.
xlabel	Label for the x-axis.
ylabel	Label for the y-axis.
vlinecolor	Color of the vertical reference line (default = "black").
intlabels	Optional custom intervention labels for the plot.
intcolors	Optional intervention colors for the plot.

Details

This function loops through each intervention, fits the requested statistical model, stores the results, and forest plot visualization for easy comparison. It allows flexible customization for plotting aesthetics.

Value

A ggplot object showing intervention effect sizes and their confidence intervals.

See Also

Functions from the **eefAnalytics** package: crtBayes, crtFREQ, mstBayes, mstFREQ, srtBayes, srtFREQ

Examples

```
### Bayesian analysis of cluster randomised trials ###
data(crt4armSimData)
multiArmAnalysis(method = "crtBayes", data = crt4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000, Threshold = 0.05,
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
intlabels = c("Intervention A", "Intervention B", "Intervention C"),
maintitle = "Forest plot of comparison of effect sizes", xlabel = "Hedges'g",
ylabel = "Interventions", vlinecolor = "black")

###MLM analysis of multisite trials with residual bootstrap confidence intervals ###
data(mst4armSimData)
multiArmAnalysis(method = "mstFREQ", data = mst4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", nBoot = 1000, bootType="residual",
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
intlabels = c("Intervention A", "Intervention B", "Intervention C"),
intcolors = c("Intervention A" = "blue", "Intervention B" = "green", "Intervention C" = "red"),
maintitle = "Forest plot of comparison of effect sizes ", xlabel = "Hedges'g",
ylabel = "Interventions", vlinecolor = "black")

###MLM analysis of multisite trials with permutation p-value###
data(mst4armSimData)
multiArmAnalysis(method = "mstFREQ", data = mst4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", nPerm = 1000,
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
intlabels = c("Intervention A", "Intervention B", "Intervention C"),
intcolors = c("Intervention A" = "blue", "Intervention B" = "green", "Intervention C" = "red"),
maintitle = "Forest plot of comparison of effect sizes ",
xlabel = "Hedges'g", ylabel = "Interventions", vlinecolor = "black")


###Bayesian analysis of simple randomised trials###
data(srt4armSimData)
multiArmAnalysis(method = "srtBayes", data = srt4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000, Threshold = 0.05,
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
intlabels = c("Int A", "Int B", "Int C"),
```

```
intcolors = c("Int A" = "#1F77B4", "Int B" = "#2CA02C", "Int C" = "#D62728"),
maintitle = "Forest plot of comparison of effect sizes ", xlabel = "Hedges'g",
ylabel = "Interventions", vlinecolor = "black")
```

`plotPosteriorProbs` *Plot Posterior Probabilities Across Thresholds for CRT, MST, or SRT Designs*

Description

This function generates a Bayesian posterior probability plot across multiple thresholds for each intervention group in a clustered randomized trial (CRT), multisite trial (MST), or simple randomized trial (SRT).

Usage

```
plotPosteriorProbs(
  method = c("crt", "mst", "srt"),
  data,
  outcome = "posttest",
  interventions = "interventions",
  Random = "schools",
  Nsim = 10000,
  continuous_covariates = NULL,
  categorical_covariates = NULL,
  VerticalLine = NULL,
  VerticalLineColor = "#0000FF",
  HorizontalLine = NULL,
  HorizontalLineColor = "#FF0000",
  threshold_range = c(0, 1),
  maintitle = "Posterior Probabilities Across Thresholds",
  xlabel = "Threshold",
  ylabel = "Posterior Probability",
  intcolors = NULL,
  intlabels = NULL,
  xbreaks = NULL,
  ybreaks = seq(0, 1, by = 0.1)
)
```

Arguments

`method`	The trial design type: "crt", "mst", or "srt".
`data`	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention.
`outcome`	The name of the outcome (post-test) variable.

`interventions` A string specifying the intervention variable.

`Random` The name of the clustering variable (e.g., schools or sites) for CRT and MST designs.

`Nsim` Number of MCMC iterations to be performed. A minimum of 10,000 is recommended to ensure convergence.

`continuous_covariates`
A character vector specifying the names of continuous covariates.

`categorical_covariates`
A character vector specifying the names of categorical covariates (converted to factors).

`VerticalLine` Optional vertical reference line added at a threshold value. It should be specified as a numeric value.

`VerticalLineColor`
The color of the vertical reference line. It should be specified as a character string (default = "#0000FF").

`HorizontalLine` Optional posterior probability cutoff for adding a horizontal reference line. It should be specified as a numeric value.

`HorizontalLineColor`
The color of the horizontal reference line. It should be specified as a character string (default = "#FF0000").

`threshold_range`
The range of thresholds to evaluate. It should be specified as a numeric vector of length 2 (default = c(0, 1.0)).

`maintitle` The main title of the plot.

`xlabel` The label for the x-axis.

`ylabel` The label for the y-axis.

`intcolors` Optional intervention colors specified manually. It should be provided as a named character vector.

`intlabels` Optional intervention labels to use instead of default names. It should be specified as a character vector.

`xbreaks` Tick marks for the x-axis. Must be a numeric vector with values within the specified threshold_range (default = 0.1).

`ybreaks` Tick marks for the y-axis. It should be specified as a numeric vector (default = seq(0, 1, by = 0.1)).

Details

The function uses `crtBayes()`, `mstBayes()`, or `srtBayes()` from eefAnalytics package depending on the `method`.

Value

A `ggplot` object that displays posterior probabilities across thresholds for each intervention.

See Also

crtBayes, mstBayes, srtBayes functions from the **eefAnalytics** package

Examples

```
###Plot Posterior Probabilities of cluster randomized trial###
data(crt4armSimData)
plotPosteriorProbs(method = "crt",data = crt4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000,
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
threshold_range = c(0, 0.1), VerticalLine = 0.05, HorizontalLine = 0.8,
VerticalLineColor= "purple", HorizontalLineColor= "black",
intlabels = c("Intervention A", "Intervention B", "Intervention C"),
intcolors = c("Intervention A" = "blue", "Intervention B" = "red",
"Intervention C" = "green"), maintitle= "Posterior probability plot",
xlabel= "Threshold", ylabel= "Posterior probability",
xbreaks= 0.1, ybreaks= seq(0, 1, by = 0.1))

###Plot Posterior Probabilities of multisite trial###
data(mst4armSimData)
plotPosteriorProbs(method = "ms",data = mst4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000,
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
threshold_range = c(0, 0.1), VerticalLine = 0.05, HorizontalLine = 0.8,
VerticalLineColor= "purple", HorizontalLineColor= "black",
intlabels = c("Intervention A", "Intervention B", "Intervention C"),
intcolors = c("Intervention A" = "blue", "Intervention B" = "red",
"Intervention C" = "green"), maintitle= "Posterior probability plot",
xlabel= "Threshold", ylabel= "Posterior probability",
xbreaks= 0.1, ybreaks= seq(0, 1, by = 0.1))

###Futility analysis of simple randomized trial###
data(srt4armSimData)
plotPosteriorProbs(method = "srt",data = srt4armSimData, outcome = "posttest",
interventions = "interventions", Nsim = 10000, threshold_range = c(0, 0.2),
continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"),
VerticalLine = 0.05, HorizontalLine = 0.8, VerticalLineColor= "purple",
HorizontalLineColor= "black", intlabels = c("Intervention A", "Intervention B",
"Intervention C"), intcolors = c("Intervention A" = "#1F77B4",
"Intervention B" = "#D62728", "Intervention C" = "#2CA02C"),
maintitle= "Posterior probability plot", xlabel= "Threshold",
ylabel= "Posterior probability", xbreaks= 0.1, ybreaks= seq(0, 1, by = 0.1))
```

---

runEPTS *Run the EPTS Shiny Application*

Description

Launches a Shiny application that provides an interactive user interface to run the functions provided by the epts package.

Usage

```
runEPTS()
```

Examples

```
if (interactive()) {
  runEPTS()
}
```

`srt4armSimData` *Simulated 4-Arm Simple Randomized Trial (SRT) Data*

Description

A simulated simple randomized trial dataset containing 1,000 individuals. This is a 4-arm trial design with one control group and three intervention groups.

Usage

```
srt4armSimData
```

Format

A data frame with 1,000 rows and 6 variables:

ID Identifier for participants ID

interventions Treatment assignment coded as 0 for control and 1–3 for intervention groups

pretest Pre-test scores

gender Binary gender

ethnicity A categorical variable with 3 categories

posttest Post-test scores

Source

Simulated

`srtAddIntervention` *Add a New Intervention Group to Simple Randomized Trial (SRT) Data*

Description

This function adds a new intervention group to an existing SRT dataset by generating new participant-level data.

Usage

```
srtAddIntervention(
  existing_data,
  np,
  es,
  attritionrate,
  outcome,
  interventions,
  id,
  continuous_covariates,
  categorical_covariates
)
```

Arguments

`existing_data`	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention for CRT design.
`np`	The number of new participants to generate for the new intervention group.
`es`	The standardized effect size for the new intervention group.
`attritionrate`	The proportion of pupils in the new group to drop due to attrition.
`outcome`	A string specifying the name of the column containing outcome variable (post-test scores).
`interventions`	A string specifying the name of the intervention assignment column.
`id`	A string specifying the name of the participant ID column.
`continuous_covariates`	A character vector specifying the names of continuous covariates.
`categorical_covariates`	A character vector specifying the names of categorical covariates (converted to factors).

Value

A `data.frame` combining the original dataset with the newly simulated intervention group.

Examples

```
data(srt4armSimData)
new_srt5armData <- srtAddIntervention(existing_data = srt4armSimData, np = 100,
es = 0.3, attritionrate = 0.1, outcome = "posttest", interventions = "interventions",
id = "ID", continuous_covariates = c("pretest"), categorical_covariates = c("gender", "ethnicity"))
head(new_srt5armData)
```

`srtDataSimulation` *Simulate Simple Randomized Trial (SRT) Data*

Description

This function simulates a Simple Randomized Trial (SRT), with multiple intervention arms, pre-test and post-test scores, and individual-level attrition. No clustering or hierarchical structure is assumed.

Usage

```
srtDataSimulation(ni, tpi, np, sigma, B0, es, seed, attritionrates, covariates)
```

Arguments

`ni`	The number of intervention groups excluding the control group.
`tpi`	The proportions (in percent) assigned to each group, with the first value for the control group followed by the intervention groups. Must sum to 100. It should be specified as a numeric vector of length ni + 1.
`np`	The total number of participants.
`sigma`	The standard deviation of individual-level error for the post-test score.
`B0`	The intercept term in the model.
`es`	The standardized effect sizes for each intervention group. It should be specified as a numeric vector.
`seed`	The random seed for reproducibility.
`attritionrates`	The attrition rates for each group, including the control group. It should be specified as a numeric vector of length ni + 1.
`covariates`	List of covariate specifications. Each element should be a list with the following fields: **name** Character. Name of the covariate. **type** Character. Either `"continuous"` or `"categorical"`. **sd** Numeric. Standard deviation (only for continuous covariates). **coefficient** Numeric. Coefficient (only for continuous covariates). **levels** Character vector. Category levels (only for categorical covariates). **probs** Numeric vector. Sampling probabilities (must sum to 1) (categorical only).

reference Character. Reference category (categorical only).

coefficients Named list of numeric values. Coefficients for each non-reference level.

Value

A `data.frame` containing:

ID Participant ID

interventions Intervention assignment (0 = control, 1 to `ni` = intervention groups)

covariates Simulated covariates

posttest Posttest score (NA if participant attrited)

Examples

```
covariates <- list(
 list(name = "pretest", type = "continuous", sd = 1, coefficient = 1.7),
 list(name = "gender", type = "categorical", levels = c("Male", "Female"),
 probs = c(0.3, 0.7), reference = "Male", coefficients = list(B = -0.5)),
 list(name = "ethnicity", type = "categorical", levels = c("White", "Black", "Asian"),
 probs = c(0.3, 0.3, 0.4), reference = "White", coefficients = list(B = 1.02, C = 1.3))
)

srtdata <- srtDataSimulation(ni = 3, np = 1000, tpi = c(30, 30, 20, 20),
sigma = 1, B0 = 1.45,  es = c(0.2, 0.3, 0.1), seed = 1234,
attritionrates = c(0.1, 0.1, 0.1, 0), covariates = covariates)
head(srtdata)
```

---

superiorityAnalysis *Superiority Analysis Across Interventions for CRT, MST, or SRT Designs*

Description

This function performs a Bayesian superiority analysis, comparing each intervention against a reference intervention, across cluster randomized trials (CRT), multisite trials (MST) or simple randomized trials (SRT).

Usage

```
superiorityAnalysis(
  method = c("crt", "mst", "srt"),
  data,
  outcome = "posttest",
  interventions = "interventions",
  Random = "schools",
  Nsim = 10000,
```

```
  Threshold = 0.05,
  refintervention = 1,
  SupThreshold = 0.8,
  continuous_covariates = NULL,
  categorical_covariates = NULL
)
```

Arguments

`method`	The trial design type: "crt", "mst", or "srt".
`data`	A data frame containing the variables including outcome, predictors, the clustering variable, and the intervention.
`outcome`	The name of the outcome (post-test) variable.
`interventions`	A string specifying the intervention variable.
`Random`	The name of the clustering variable (e.g., schools or sites) for CRT and MST designs.
`Nsim`	Number of MCMC iterations to be performed. A minimum of 10,000 is recommended to ensure convergence.
`Threshold`	The effect size threshold for posterior computation (default = 0.05).
`refintervention`	The value of the intervention used as the reference group (default = 1).
`SupThreshold`	The minimum posterior probability threshold to declare superiority (default = 0.8).
`continuous_covariates`	A character vector specifying the names of continuous covariates.
`categorical_covariates`	A character vector specifying the names of categorical covariates (converted to factors).

Details

The effect size is estimated against a reference intervention, which by default is intervention 1 but can be reassigned to any other intervention, including the control (refintervention = 0).

Value

A `data.frame` with columns:

- `Intervention`: Intervention group identifier.
- `ProbES`: Posterior probability of superiority over the reference intervention.
- `Superiority`: Label indicating `"Superior"`, `"Not Superior"`, or `"Reference"`.

See Also

`crtBayes`, `mstBayes`, `srtBayes` functions from the **eefAnalytics** package

Examples

```
###Superiority analysis of cluster randomized trial###
data(crt4armSimData)
superiorityAnalysis(method = "crt", data = crt4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000, refintervention = 2,
Threshold = 0.05, SupThreshold = 0.8,continuous_covariates = c("pretest"),
categorical_covariates = c("gender", "ethnicity"))

###Superiority analysis of multisite trial###
data(mst4armSimData)
superiorityAnalysis(method = "mst", data = mst4armSimData, outcome = "posttest",
interventions = "interventions", Random = "schools", Nsim = 10000, refintervention = 2,
Threshold = 0.05, SupThreshold = 0.8,continuous_covariates = c("pretest"),
categorical_covariates = c("gender", "ethnicity"))

###Superiority analysis of simple randomized trial###
data(srt4armSimData)
superiorityAnalysis(method = "srt", data = srt4armSimData, outcome = "posttest",
interventions = "interventions", Nsim = 10000, refintervention = 2,
Threshold = 0.05, SupThreshold = 0.8,continuous_covariates = c("pretest"),
categorical_covariates = c("gender", "ethnicity"))
```

Index

∗ **datasets**
crt4armSimData, 2
mst4armSimData, 8
srt4armSimData, 18

crt4armSimData, 2
crtAddIntervention, 3
crtBayes, *7*, *14*, *17*, *22*
crtDataSimulation, 4
crtFREQ, *14*

futilityAnalysis, 6

lmer, *4*, *10*

mst4armSimData, 8
mstAddIntervention, 8
mstBayes, *7*, *14*, *17*, *22*
mstDataSimulation, 10
mstFREQ, *14*
multiArmAnalysis, 12

plotPosteriorProbs, 15

runEPTS, 17

srt4armSimData, 18
srtAddIntervention, 19
srtBayes, *7*, *14*, *17*, *22*
srtDataSimulation, 20
srtFREQ, *14*
superiorityAnalysis, 21