Package: ern (via r-universe)

October 14, 2026

Title Effective Reproduction Number Estimation

Version 2.1.2

Maintainer David Champredon <david.champredon@canada.ca>

Description Estimate the effective reproduction number from wastewater and clinical data sources.

License MIT + file LICENSE

Imports assertthat, coda, dplyr, EpiEstim, ggplot2, lubridate, patchwork, rjags, runjags, stats, stringr, tibble, tidyr, zoo

Suggests knitr, rmarkdown, bookdown, purrr, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.1

Depends R (>= 4.1.0)

LazyData true

NeedsCompilation no

Author David Champredon [aut, cre] (<https://orcid.org/0000-0002-7090-8757>), Warsame Yusuf [aut] (<https://orcid.org/0000-0001-5571-8122>), Irena Papst [aut] (<https://orcid.org/0000-0001-5901-7585>)

Repository https://cran.r-universe.dev

Date/Publication 2025-01-16 18:20:02 UTC

RemoteUrl https://github.com/cran/ern

RemoteRef HEAD

RemoteSha d27f04cecfe522738e08985ad7270ff55ab1afe6

Contents

agg_to_daily . . . 2
cl.data . . . 4
def_dist . . . 5
estimate_R_cl . . . 6
estimate_R_ww . . . 10
extract_mcmc_values . . . 12
get_discrete_dist . . . 13
linear_int_daily . . . 14
plot_diagnostic_cl . . . 14
plot_diagnostic_ww . . . 16
plot_dist . . . 18
plot_gelman_rubin . . . 19
plot_traces . . . 19
ww.data . . . 20

Index **21**

`agg_to_daily` *Infer daily counts from aggregates*

Description

Infer daily counts from aggregates

Usage

```
agg_to_daily(cl.data, dist.gi, prm.daily, silent = FALSE)
```

Arguments

`cl.data`	Data frame. Must have variables: • `date`: calendar date of report • `value`: count of reported cases
`dist.gi`	List. Parameters for the generation interval distribution in the same format as returned by `def_dist()`.
`prm.daily`	List. Parameters for daily report inference via MCMC. Elements include: • `method`: String. Method name to infer the daily incidence reports from aggregated ones. Either `linear` or `renewal` is currently implemented. The `linear` method simply performs a linear interpolation that matches the aggregated values. The `renewal` method fits a SIR-like model using a renewal equation to infer the daily incidence. In this case, the fitting algorithm is a Markov Chain Monte Carlo (MCMC) implemented in JAGS and needs the parameters below (e.g., `burn`,`iter`,`chains`,...). The `renewal` method is more adapted for short single wave epidemics as this models i) naturally fits a single wave and ii) has longer computing time. For longer time series, user may perfer the `linear` method.

- `popsize`: Integer. Population size to use in MCMC simulation to infer daily observations from aggregated input data.
- `burn`: Numeric. Length of burn-in period (number of days).
- `iter`: Numeric. Number of iterations after burn-in period (number of days).
- `chains`: Numeric. Number of chains to simulate.
- `prior_R0_shape`: Shape of the (hyper-)parameter for the prior Gamma distribution for R0.
- `prior_R0_rate`: Rate of the (hyper-)parameter for the prior Gamma distribution for R0.
- `prior_alpha_shape`: Shape of the (hyper-)parameter for the prior Gamma distribution for alpha.
- `prior_alpha_rate`: Rate of the (hyper-)parameter for the prior Gamma distribution for alpha.
- `first.agg.period`: length of aggregation period for first aggregated observation (number of days); if NULL, assume same aggregation period as observed for second observation (gap between first and second observations)

`silent` Logical. Flag to suppress all output messages, warnings, and progress bars.

Value

A list containing a data frame with individual realizations of daily reported cases and the JAGS object.

Examples

```
# Importing data attached to the `ern` package
# and selecting the Omicron wave in Ontario, Canada.
# This is *weekly* incidence.
data(cl.data)
data = cl.data[cl.data$pt == 'on' &
                  cl.data$date > as.Date('2021-11-30') &
                  cl.data$date < as.Date('2021-12-31'),]
head(data)
dist.gi = ern::def_dist(
 dist     = "gamma",
 mean     = 6.84,
 mean_sd  = 0.7486,
 shape    = 2.39,
 shape_sd = 0.3573,
 max      = 15
)

a = agg_to_daily(
cl.data = data,
dist.gi = dist.gi,
  prm.daily = list(
  method = "renewal",
  popsize = 14e6,
```

```
  # MCMC parameters.
  # small values for computation speed for this example.
  # Increase for better accuracy
  burn = 100,
  iter = 100,
  chains = 2,
  # - - - - -
  prior_R0_shape = 2,
  prior_R0_rate = 0.6,
  prior_alpha_shape = 1,
  prior_alpha_rate = 1
))
# This is a Bayesian inference, so we
# have a posterior distribution of
# daily incidences. Here we just plot
# one single draw:

 df = a$df
 df1 = df[df$id==1,]
 plot(x = df1$t, y = df1$value, typ = 'o',
      xlab = 'days', ylab = 'daily incidence',
      main = 'Posterior daily incidence infered from weekly incidence')

 # Extract of the parameters values from the first chain
 a$jags.object[[1]][1:9,1:9]
```

`cl.data` *Sample of aggregated clinical reports*

Description

A subset of COVID-19 weekly reports in the Government of Canada Health Infobase. See https://health-infobase.canada.ca/covid-19/

Usage

```
cl.data
```

Format

`cl.data`**:**

A data frame with 96 rows and 3 columns:

- `pt`: standard two-character abbreviation (lowercase) of the province name (based on Statistics Canada 2021 census abbreviations)
- `date`: report date
- `value`: count of reported cases for the previous week

Filter indicating a specific province to extract a sample dataset for use with `estimate_R_cl()`, *e.g.*
`estimate_R_cl(cl.data = dplyr::filter(cl.data, pt == 'bc'), ...)`

`def_dist` *Define a family of distributions.*

Description

Define a family of distributions.

Usage

```
def_dist(dist, ...)
```

Arguments

`dist`	distribution type. Distributions currently supported are: • `norm` = normal, • `lnorm` = log-normal, • `gamma` = Gamma, • `unif` = uniform
`...`	a series of distribution parameters. Included should be the following: • `mean` distribution mean (only for `dist` = `lnorm` or `gamma`). • `mean_sd` standard deviation of the mean (only for `dist` = `lnorm` or `gamma`). • `sd` standard deviation (only for `dist` = `lnorm` or `gamma`). • `sd_sd` standard deviation of the standard deviation (only for `dist` = `lnorm` or `gamma`). • `min` minimum value of the random variable modelled by this distribution (only for `dist` = `unif`). • `max` maximum value of the random variable modelled by this distribution.

Value

List with components specified in the parameters.

Examples

```
d = def_dist(
  dist     = "gamma",
  mean     = 3.49,
  mean_sd  = 0.1477,
  shape    = 8.5,
  shape_sd = 1.8945,
  max      = 8
)
print(d)
```

`estimate_R_cl` *Estimate the effective reproduction from clinical report data*

Description

Estimate the effective reproduction from clinical report data

Usage

```
estimate_R_cl(
  cl.data,
  dist.repdelay,
  dist.repfrac,
  dist.incub,
  dist.gi,
 prm.daily = list(method = "linear", popsize = NULL, burn = 500, iter = 2000, chains =
  3, prior_R0_shape = 2, prior_R0_rate = 0.6, prior_alpha_shape = 1, prior_alpha_rate =
    1, first.agg.period = NULL),
  prm.daily.check = list(agg.reldiff.tol = 10),
  prm.smooth = list(method = "rollmean", align = "right", window = 7),
  prm.R = list(iter = 10, CI = 0.95, window = 7, config.EpiEstim = NULL),
  RL.max.iter = 10,
  silent = FALSE
)
```

Arguments

`cl.data`	Data frame. Must have variables: • `date`: calendar date of report • `value`: count of reported cases
`dist.repdelay`	List. Parameters for the reporting delay distribution in the same format as returned by `def_dist()`.
`dist.repfrac`	List. Parameters for the reporting fraction distribution in the same format as returned by `def_dist()`.
`dist.incub`	List. Parameters for the incubation period distribution in the same format as returned by `def_dist()`.
`dist.gi`	List. Parameters for the generation interval distribution in the same format as returned by `def_dist()`.
`prm.daily`	List. Parameters for daily report inference via MCMC. Elements include: • `method`: String. Method name to infer the daily incidence reports from aggregated ones. Either `linear` or `renewal` is currently implemented. The `linear` method simply performs a linear interpolation that matches the aggregated values. The `renewal` method fits a SIR-like model using a renewal equation to infer the daily incidence. In this case, the fitting algorithm is a Markov Chain Monte Carlo (MCMC) implemented in JAGS and needs the

parameters below (e.g., `burn`,`iter`,`chains`,...). The `renewal` method is more adapted for short single wave epidemics as this models i) naturally fits a single wave and ii) has longer computing time. For longer time series, user may perfer the `linear` method.

- `popsize`: Integer. Population size to use in MCMC simulation to infer daily observations from aggregated input data.
- `burn`: Numeric. Length of burn-in period (number of days).
- `iter`: Numeric. Number of iterations after burn-in period (number of days).
- `chains`: Numeric. Number of chains to simulate.
- `prior_R0_shape`: Shape of the (hyper-)parameter for the prior Gamma distribution for R0.
- `prior_R0_rate`: Rate of the (hyper-)parameter for the prior Gamma distribution for R0.
- `prior_alpha_shape`: Shape of the (hyper-)parameter for the prior Gamma distribution for alpha.
- `prior_alpha_rate`: Rate of the (hyper-)parameter for the prior Gamma distribution for alpha.
- `first.agg.period`: length of aggregation period for first aggregated observation (number of days); if NULL, assume same aggregation period as observed for second observation (gap between first and second observations)

`prm.daily.check`

List. Parameters for checking aggregated to daily report inference. Elements include:

- `agg.reldiff.tol`: numerical tolerance (%) for relative error between aggregated inferred daily reports and original aggregated reports; chronological observations are dropped until this tolerance is first acheived (convergence at the start of the timeseries is often the worst, need to maintain uninterrupted daily timeseries for input into Rt calculation).

Set this entire argument to `NULL` to use inferred daily reports as is.

`prm.smooth` List. list of smoothing parameters. Parameters should be specified as followed:

- `method`: smoothing method, either `'rollmean'` (rolling mean) or `'loess'` (LOESS smoothing via `stats::loess()`)
- `window`: for `method = 'rollmean` only; width of smoothing window in days
- `align`: for `method = 'rollmean` only; smoothing alignment, either `'center'`, `'left'`, `'right'`
- `span`: for `method = 'loess'` only; smoothing span (see the documentation for `stats::loess()` for details)
- `floor`: optional call for wastewater concentration smoothing with `method = 'loess'` only; user defined minimum smoothing concentration

Set this entire list to `NULL` to turn off smoothing

`prm.R` List. Settings for the ensemble when calculating Rt. Elements include:

- `iter`: Integer. Number of iterations for the Rt ensemble

- `CI`: Numeric between 0 and 1. Confidence interval width for Rt estimates after sampling uncertain distributions.
- `window`: Integer. Number of days defining the window of data used by `EpiEstim` to estimate Rt. If `NULL`, will default to 7.
- `config.EpiEstim`: (optional) configuration for `EpiEstim` defined via `EpiEstim::make_config()`. If `NULL`, will use default config from `EpiEstim`.

`RL.max.iter` Integer. Maximum of iterations for the Richardson-Lucy deconvolution algorithm.

`silent` Logical. Flag to suppress all output messages, warnings, and progress bars.

Value

List. Elements include:

- `cl.data`: original aggregated reports signal
- `cl.daily`: reports as input for Rt calculation (inferred daily counts, smoothed)
- `inferred.agg`: inferred daily reports aggregated on the reporting schedule as input in `cl.data`
- `R`: the effective R estimate (summary from ensemble)

See Also

`plot_diagnostic_cl()` `estimate_R_ww()`

Examples

```
# -- THIS EXAMPLE TAKES ABOUT 30 SECONDS TO RUN --
# Estimate Rt

## Not run:
# Load SARS-CoV-2 reported cases in Quebec
# during the Summer 2021
dat <- (ern::cl.data
    |> dplyr::filter(
      pt == "qc",
      dplyr::between(date, as.Date("2021-06-01"), as.Date("2021-09-01"))
    )
)
# distributions
dist.repdelay = ern::def_dist(
    dist = 'gamma',
    mean = 5,
    mean_sd = 1,
    sd = 1,
    sd_sd = 0.1,
    max = 10
)
dist.repfrac = ern::def_dist(
    dist = "unif",
    min = 0.1,
    max = 0.3
```

```
)
dist.incub = ern::def_dist(
    dist = "gamma",
    mean = 3.49,
    mean_sd = 0.1477,
    shape = 8.5,
    shape_sd = 1.8945,
    max = 8
)
dist.gi = ern::def_dist(
    dist = "gamma",
    mean = 6,
    mean_sd = 0.75,
    shape = 2.4,
    shape_sd = 0.3,
    max = 10
)

# settings
prm.daily <- list(
    method = "renewal",
    popsize = 8.5e6, # Q3 (July 1) 2022 estimate for Quebec
    burn = 500,
    iter = 500,
    chains = 2,
    prior_R0_shape = 1.1, prior_R0_rate = 0.6,
    prior_alpha_shape = 1, prior_alpha_rate = 1
)
prm.daily.check <- list(
    agg.reldiff.tol = 10
)
prm.smooth <- list(
    method = "rollmean",
    align = "center",
    window = 7
)
prm.R <- list(
    iter = 20,
    CI = 0.95,
    window = 7,
    config.EpiEstim = NULL
)

x <- estimate_R_cl(
  dat,
  dist.repdelay,
  dist.repfrac,
  dist.incub,
  dist.gi,
  prm.daily,
  prm.daily.check,
  prm.smooth,
  prm.R
```

```
)

# Rt estimates
print(x$R)

## End(Not run)
```

`estimate_R_ww` *Estimate the effective reproduction from wastewater concentration data.*

Description

Estimate the effective reproduction from wastewater concentration data.

Usage

```
estimate_R_ww(
  ww.conc,
  dist.fec,
  dist.gi,
  scaling.factor = 1,
  prm.smooth = list(window = 14, align = "center", method = "loess", span = 0.2),
  prm.R = list(iter = 10, CI = 0.95, window = 7, config.EpiEstim = NULL),
  silent = FALSE,
  RL.max.iter = 9
)
```

Arguments

`ww.conc`	Data frame. Must have variables: • `date`: calendar date of wastewater collection • `value`: pathogen concentration
`dist.fec`	List. Parameters for the fecal shedding distribution in the same format as returned by `def_dist()`.
`dist.gi`	List. Parameters for the generation interval distribution in the same format as returned by `def_dist()`.
`scaling.factor`	Numeric. Scaling from wastewater concentration to prevalence. This value may be assumed or independently calibrated to data.
`prm.smooth`	List. list of smoothing parameters. Parameters should be specified as followed: • `method`: smoothing method, either `'rollmean'` (rolling mean) or `'loess'` (LOESS smoothing via `stats::loess()`)

- window: for method = 'rollmean only; width of smoothing window in days
- align: for method = 'rollmean only; smoothing alignment, either 'center', 'left', 'right'
- span: for method = 'loess' only; smoothing span (see the documentation for stats::loess() for details)
- floor: optional call for wastewater concentration smoothing with method = 'loess' only; user defined minimum smoothing concentration

Set this entire list to NULL to turn off smoothing

prm.R — List. Settings for the ensemble when calculating Rt. Elements include:

- iter: Integer. Number of iterations for the Rt ensemble
- CI: Numeric between 0 and 1. Confidence interval width for Rt estimates after sampling uncertain distributions.
- window: Integer. Number of days defining the window of data used by EpiEstim to estimate Rt. If NULL, will default to 7.
- config.EpiEstim: (optional) configuration for EpiEstim defined via EpiEstim::make_config(). If NULL, will use default config from EpiEstim.

silent — Logical. Flag to suppress all output messages, warnings, and progress bars.

RL.max.iter — Integer. Maximum of iterations for the Richardson-Lucy deconvolution algorithm.

Value

List. Elements include:

- ww.conc: original wastewater signal
- ww.smooth: smoothed wastewater signal
- inc: inferred incidence
- R: the effective reproduction number estimate

See Also

plot_diagnostic_ww() estimate_R_cl()

Examples

```
 # Load data of viral concentration in wastewater
data("ww.data")

# Run the estimation of Rt based on the wastewater data
x = estimate_R_ww(
  ww.conc  = ww.data,
  dist.fec = ern::def_dist(
    dist = "gamma",
    mean = 12.90215,
    mean_sd = 1.136829,
    shape = 1.759937,
```

```
    shape_sd = 0.2665988,
    max = 33
    ),
  dist.gi  = ern::def_dist(
    dist     = "gamma",
    mean     = 6.84,
    mean_sd  = 0.7486,
    shape    = 2.39,
    shape_sd = 0.3573,
    max      = 15
    ),
  silent   = TRUE
)

# Rt estimates
head(x$R)

# inferred daily incidence
head(x$inc)
```

`extract_mcmc_values` *Extract MCMC chains from a JAGS object*

Description

Extract MCMC chains from a JAGS object

Usage

```
extract_mcmc_values(chain, jags.obj)
```

Arguments

`chain`	Integer. Chain number.
`jags.obj`	JAGS object as returned by `code.sample()`

Value

A dataframe of the chain values for selected parameters.

`get_discrete_dist` *Get a discretized, truncated version of a distribution*

Description

Get a discretized, truncated version of a distribution

Usage

```
get_discrete_dist(params)
```

Arguments

`params`	distribution params (output of `def_dist_*()` function)

Value

Numeric. Vector with discretized density.

Examples

```
# Define distributions
fec = ern::def_dist(
  dist = "gamma",
  mean = 12.90215,
  mean_sd = 1.136829,
  shape = 1.759937,
  shape_sd = 0.2665988,
  max = 33
  )
gi  = ern::def_dist(
  dist     = "gamma",
  mean     = 6.84,
  mean_sd  = 0.7486,
  shape    = 2.39,
  shape_sd = 0.3573,
  max      = 15
  )

# Get their (discretized) densities
d.fec = get_discrete_dist(fec)
d.gi  = get_discrete_dist(gi)

print(d.fec)
print(d.gi)
```

linear_int_daily *Daily incidence from linear interpolation*

Description

Daily incidence from linear interpolation

Usage

```
linear_int_daily(cl.data)
```

Arguments

cl.data	Aggregated incidence.

Value

A dataframe of daily incidence

plot_diagnostic_cl *Diagnostic plot for R estimation from clinical report data*

Description

Diagnostic plot for R estimation from clinical report data

Usage

```
plot_diagnostic_cl(r.estim, caption = NULL, wrap.plots = TRUE)
```

Arguments

r.estim	List. Output of estimate_R_cl().
caption	String. Caption to be inserted in the plot. Default is caption = NULL which disables the caption.
wrap.plots	Logical. Wrap the plots together into a single ggplot object? If wrap.plots = TRUE (the default) will return wrapped plots in a single object, else will return a list of separate ggplot objects.

Value

Plots of the clinical data used, the inferred daily incidence and Rt estimates. If wrap.plots = TRUE (the default) will return wrapped plots (with x-axis aligned to facilitate the comaprison) in a single object, else will return a list of separate ggplot objects.

A ggplot object (or a list of ggplot objects if wrap.plots = FALSE).

See Also

estimate_R_cl()

Examples

```
# -- THIS EXAMPLE TAKES ABOUT 30 SECONDS TO RUN --
# Estimate Rt

## Not run:
# Load SARS-CoV-2 reported cases in Quebec
# during the Summer 2021
dat <- (ern::cl.data
    |> dplyr::filter(
      pt == "qc",
      dplyr::between(date, as.Date("2021-06-01"), as.Date("2021-09-01"))
    )
)
# distributions
dist.repdelay = ern::def_dist(
    dist = 'gamma',
    mean = 5,
    mean_sd = 1,
    sd = 1,
    sd_sd = 0.1,
    max = 10
)
dist.repfrac = ern::def_dist(
    dist = "unif",
    min = 0.1,
    max = 0.3
)
dist.incub = ern::def_dist(
    dist = "gamma",
    mean = 3.49,
    mean_sd = 0.1477,
    shape = 8.5,
    shape_sd = 1.8945,
    max = 8
)
dist.gi = ern::def_dist(
    dist = "gamma",
    mean = 6,
    mean_sd = 0.75,
    shape = 2.4,
    shape_sd = 0.3,
    max = 10
)

# settings
prm.daily <- list(
    method = "renewal",
    popsize = 8.5e6, # Q3 (July 1) 2022 estimate for Quebec
```

```
    burn = 500,
    iter = 500,
    chains = 2,
    prior_R0_shape = 1.1, prior_R0_rate = 0.6,
    prior_alpha_shape = 1, prior_alpha_rate = 1
)
prm.daily.check <- list(
    agg.reldiff.tol = 10
)
prm.smooth <- list(
    method = "rollmean",
    align = "center",
    window = 7
)
prm.R <- list(
    iter = 20,
    CI = 0.95,
    window = 7,
    config.EpiEstim = NULL
)

x <- estimate_R_cl(
  dat,
  dist.repdelay,
  dist.repfrac,
  dist.incub,
  dist.gi,
  prm.daily,
  prm.daily.check,
  prm.smooth,
  prm.R
)

# Diagnostic plot for Rt estimates
# from clinical data
g = plot_diagnostic_cl(x)
plot(g)

g2 = plot_diagnostic_cl(x, caption = 'This is your caption', wrap.plots = FALSE)
plot(g2$clinical_data)
plot(g2$inferred_incidence)
plot(g2$Rt)

## End(Not run)
```

`plot_diagnostic_ww` *Diagnostic plot for R estimation from wastewater data*

Description

Diagnostic plot for R estimation from wastewater data

Usage

```
plot_diagnostic_ww(r.estim, caption = NULL, wrap.plots = TRUE)
```

Arguments

r.estim	List. Output of estimate_R_ww().
caption	Character. Optional plot caption.
wrap.plots	Logical. Wrap all diagnostic plots into one single ggplot object (default = TRUE).

Value

A ggplot object.

See Also

estimate_R_ww() plot_diagnostic_cl()

Examples

```
# Load data of viral concentration in wastewater
data("ww.data")

# Estimate Rt based on wastewater data
x = estimate_R_ww(
  ww.conc  = ww.data,
  dist.fec = ern::def_dist(
    dist = "gamma",
    mean = 12.9,
    mean_sd = 1.13,
    shape = 1.75,
    shape_sd = 0.26,
    max = 33
    ),
  dist.gi  = ern::def_dist(
    dist     = "gamma",
    mean     = 6.84,
    mean_sd  = 0.74,
    shape    = 2.39,
    shape_sd = 0.35,
    max      = 15
    ),
  silent   = TRUE
)

# Diagnostic plot
g = plot_diagnostic_ww(x)
plot(g)

g2 = plot_diagnostic_ww(x, wrap.plots = FALSE, caption = "This is your caption")
plot(g2$wastewater_data)
plot(g2$inferred_incidence)
```

```
plot(g2$Rt)
```

`plot_dist` *Plot a distribution*

Description

Plot a distribution

Usage

```
plot_dist(d)
```

Arguments

`d`	List that defines the distribution (as returned by `def_dist_incubation_period()` for example)

Value

A ggplot object.

Examples

```
# Define a `ern` distribution:
gi  = ern::def_dist(
  dist     = "gamma",
  mean     = 6.84,
  mean_sd  = 0.7486,
  shape    = 2.39,
  shape_sd = 0.3573,
  max      = 15
  )

# Plot can be customized like any `ggplot` object:
g = plot_dist(gi) + ggplot2::labs(subtitle = 'your subtitle')
plot(g)
```

plot_gelman_rubin *Plot the Gelman Rubin statistic for all parameters.*

Description

Plot the Gelman Rubin statistic for all parameters.

Usage

```
plot_gelman_rubin(jags.obj)
```

Arguments

jags.obj	JAGS object as returned by code.sample()

Value

A ggplot plot.

plot_traces *Plot MCMC traces*

Description

Plot MCMC traces

Usage

```
plot_traces(jags.obj)
```

Arguments

jags.obj	JAGS object as returned by code.sample()

Value

A ggplot plot.

`ww.data` *Sample of wastewater concentration*

Description

A subset of SARS-CoV-2 (N2 gene) concentration data in wastewater sampled from the Iona Island wastewater treatment plant in Vancouver between 7 July 2023 and 5 November 2023. Units are in N2 gene copies per milliliter of wastewater. Concentration was measured using RT-qPCR assays; RNA was extracted from suspended solids. See https://health-infobase.canada.ca/covid-19/wastewater/

Usage

```
ww.data
```

Format

`ww.data`**:**

A data frame with 47 rows and 3 columns:

- `date`: sampling date
- `value`: mean sample concentration between multiple replicates

Index

∗ **datasets**
    cl.data, 4
    ww.data, 20

agg_to_daily, 2

cl.data, 4

def_dist, 5
def_dist(), *2*, *6*, *10*

EpiEstim::make_config(), *8*, *11*
estimate_R_cl, 6
estimate_R_cl(), *5*, *11*, *14, 15*
estimate_R_ww, 10
estimate_R_ww(), *8*, *17*
extract_mcmc_values, 12

get_discrete_dist, 13

linear_int_daily, 14

plot_diagnostic_cl, 14
plot_diagnostic_cl(), *8*, *17*
plot_diagnostic_ww, 16
plot_diagnostic_ww(), *11*
plot_dist, 18
plot_gelman_rubin, 19
plot_traces, 19

stats::loess(), *7*, *10, 11*

ww.data, 20