

Package: geohabnet (via r-universe)

June 28, 2024

Title Geographical Risk Analysis Based on Habitat Connectivity

Version 2.1.3

Date 2024-06-26

Description The geohabnet package is designed to perform a geographically or spatially explicit risk analysis of habitat connectivity. Xing et al (2021) <[doi:10.1093/biosci/biaa067](https://doi.org/10.1093/biosci/biaa067)> proposed the concept of cropland connectivity as a risk factor for plant pathogen or pest invasions. As the functions in geohabnet were initially developed thinking on cropland connectivity, users are recommended to first be familiar with the concept by looking at the Xing et al paper. In a nutshell, a habitat connectivity analysis combines information from maps of host density, estimates the relative likelihood of pathogen movement between habitat locations in the area of interest, and applies network analysis to calculate the connectivity of habitat locations. The functions of geohabnet are built to conduct a habitat connectivity analysis relying on geographic parameters (spatial resolution and spatial extent), dispersal parameters (in two commonly used dispersal kernels: inverse power law and negative exponential models), and network parameters (link weight thresholds and network metrics). The functionality and main extensions provided by the functions in geohabnet to habitat connectivity analysis are a) Capability to easily calculate the connectivity of locations in a landscape using a single function, such as `sensitivity_analysis()` or `msean()`. b) As backbone datasets, the geohabnet package supports the use of two publicly available global datasets to calculate cropland density. The backbone datasets in the geohabnet package include crop distribution maps from Monfreda, C., N. Ramankutty, and J. A. Foley (2008) <[doi:10.1029/2007gb002947](https://doi.org/10.1029/2007gb002947)> ``Farming the planet: 2. Geographic distribution of crop areas, yields, physiological types, and net primary production in the year 2000, Global Biogeochem. Cycles, 22, GB1022" and International Food Policy Research Institute (2019) <[doi:10.7910/DVN/PRFF8V](https://doi.org/10.7910/DVN/PRFF8V)> ``Global

Spatially-Disaggregated Crop Production Statistics Data for 2010 Version 2.0, Harvard Dataverse, V4". Users can also provide any other geographic dataset that represents host density. c) Because the geohabnet package allows R users to provide maps of host density (as originally in Xing et al (2021)), host landscape density (representing the geographic distribution of either crops or wild species), or habitat distribution (such as host landscape density adjusted by climate suitability) as inputs, we propose the term habitat connectivity. d) The geohabnet package allows R users to customize parameter values in the habitat connectivity analysis, facilitating context-specific (pathogen- or pest-specific) analyses. e) The geohabnet package allows users to automatically visualize maps of the habitat connectivity of locations resulting from a sensitivity analysis across all customized parameter combinations. The primary function is `sean()` and `sensitivity analysis()`. Most functions in geohabnet provide as three main outcomes: i) A map of mean habitat connectivity across parameters selected by the user, ii) a map of variance of habitat connectivity across the selected parameters, and iii) a map of the difference between the ranks of habitat connectivity and habitat density. Each function can be used to generate these maps as 'final' outcomes. Each function can also provide intermediate outcomes, such as the adjacency matrices built to perform the analysis, which can be used in other network analysis. Refer to article at <https://garrettlab.github.io/HabitatConnectivity/articles/analysis.html> to see examples of each function and how to access each of these outcome types. To change parameter values, the file called `parameters.yaml` stores the parameters and their values, can be accessed using `get_parameters()` and set new parameter values with `set_parameters()`. Users can modify up to ten parameters.

License GPL-3

Encoding UTF-8

RoxygenNote 7.2.3

Imports `config` ($\geq 0.3.1$), `geodata` ($\geq 0.6.2$), `geosphere` ($\geq 1.5.18$), `igraph` ($\geq 2.0.3$), `terra` ($\geq 1.7.29$), `easycsv` ($\geq 1.0.8$), `yaml` ($\geq 2.3.7$), `stats`, `stringr` ($\geq 1.5.0$), `memoise` ($\geq 2.0.1$), `graphics`, `rlang` ($\geq 1.1.1$), `viridisLite` ($\geq 0.4.2$), `beepr` (≥ 1.3), `rnatualearth` ($\geq 0.3.3$), `tools`, `methods`, `future.apply` ($\geq 1.11.0$), `future` ($\geq 1.33.0$), `magrittr` ($\geq 2.0.3$), `ggplot2` ($\geq 3.5.1$), `patchwork` ($\geq 1.2.0$)

Suggests `devtools`, `knitr`, `lintr` ($\geq 3.0.2$), `mockthat` ($\geq 0.2.8$), `pkgdown`, `rmarkdown`, `testthat` ($\geq 3.1.7$)

URL <https://garrettlab.github.io/HabitatConnectivity/>,

<https://CRAN.R-project.org/package=geohabnet/>,
<https://github.com/GarrettLab/HabitatConnectivity/tree/main/geohabnet/>,
<https://www.garrettlab.com/>

BugReports <https://github.com/GarrettLab/HabitatConnectivity/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Krishna Keshav [aut, cre], Aaron Plex [aut]
 (<<https://orcid.org/0000-0001-7317-3090>>), Garrett Lab [ctb]
 (<https://garrettlab.com>), Karen Garrett [aut]
 (<<https://orcid.org/0000-0002-6578-1616>>), University of
 Florida [cph, fnd] (<https://www.ufl.edu>)

Maintainer Krishna Keshav <kkeshav@ufl.edu>

Repository CRAN

Date/Publication 2024-06-27 11:50:02 UTC

Contents

.indices	4
connectivity	5
cropharvest_rast	6
crops_rast	7
dist_methods	8
GeoModel-class	8
GeoNetwork-class	9
GeoRasters-class	10
geoscale_param	10
get_parameters	11
get_rasters	11
GlobalRast-class	12
global_scales	13
Gmap-class	13
gplot	14
hci_diff	15
hci_mean	15
hci_variance	16
host_density<-	17
inv_powerlaw	18
load_parameters	19
mapspam	20
monfreda	20
ndplot	21
ndplot,GeoNetwork-method	21
nn_sum	22
reset_params	23

reso	24
RiskMap-class	24
risk_indices	25
sa_onrasters	25
sean	27
search_crop	30
sensitivity_analysis	31
setmaps,Gmap-method	32
setprops	33
setprops,GeoModel,character,numeric,numeric-method	33
set_global_scales	34
set_parameters	34
sp_rast	35
supported_metrics	36
supported_sources	36
tiff_torast	37
Index	38

.indices

Internal function to extract risk indices from a list of crop rasters.

Description

Internal function to extract risk indices from a list of crop rasters.

Usage

```
.indices(crop_rasters)
```

Arguments

crop_rasters List of raster objects.

Value

A list of risk indices.

`connectivity`*Calculate and plot maps*

Description

Calculate mean, variance and difference. The result is produced in form of maps plotted with predefined settings. Currently, the settings for plot cannot be customized. Default value is TRUE for all logical arguments

Usage

```
connectivity(  
  host,  
  indices,  
  global = FALSE,  
  east = NULL,  
  west = NULL,  
  geoscale = NULL,  
  res = reso(),  
  pmean = TRUE,  
  pvar = TRUE,  
  pdiff = TRUE,  
  outdir = tempdir()  
)
```

Arguments

<code>host</code>	SpatRaster. Host density map aka SpatRaster object
<code>indices</code>	SpatRaster. Collection of risk indices.
<code>global</code>	Logical. TRUE if global analysis is desired, FALSE otherwise. east and west are required when TRUE.
<code>east</code>	SpatRaster. Collection of risk indices on eastern extent.
<code>west</code>	SpatRaster. Collection of risk indices on western extent. When TRUE, geoscale is ignored. Default is TRUE.
<code>geoscale</code>	Vector. geographical scale. Default is NULL.
<code>res</code>	Numeric. Map resolution. This value is used in aggregation and dis-aggregation operation. Default is <code>reso()</code> .
<code>pmean</code>	Logical. TRUE if map of mean should be plotted, FALSE otherwise.
<code>pvar</code>	Logical. TRUE if variance map should be plotted, FALSE otherwise.
<code>pdiff</code>	Logical. TRUE if difference map should be plotted, FALSE otherwise.
<code>outdir</code>	Character. Output directory for saving raster in TIFF format. Default is <code>tempdir()</code> .

Details

indexes are actually risk indices i.e. lis of spatRaster objects resulting from operations on crop's raster and parameters provided in either parameters.yaml or `sean()`.

It will save all the opted plots using `-pmean`, `pvar` and `pdiff`. File will be saved in provided value of `outdir` or `tempdir()`. If `interactive()` is TRUE, then plots can be seen in active plot window. E.g. Rstudio. The maps are plotted using SpatRaster object. These objects are available as a return value of this function.

Value

Gmap. See details.

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schultegeldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, doi:10.1093/biosci/biaa067

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, <https://CRAN.R-project.org/package=terra>

See Also

`hci_mean()`, `hci_variance()`, `hci_diff()`

cropharvest_rast	<i>Get raster object for crop</i>
------------------	-----------------------------------

Description

Get cropland information in a form of raster object from data source for crop

Usage

```
cropharvest_rast(crop_name, data_source)
```

Arguments

crop_name	Name of the crop
data_source	Data source for cropland information

Value

Raster.

Examples

```
cropharvest_rast("avocado", "monfreda")
```

crops_rast

Get sum of rasters for individual crops

Description

Takes crop names and returns raster object which is sum of raster of individual crops. Currently, only supports crops listed in [geodata::monfredaCrops\(\)](#), [geodata::spamCrops\(\)](#) If crop is present in multiple sources, then their mean is calculated.

Usage

```
crops_rast(crop_names)
```

Arguments

crop_names A named list of source along with crop names

Value

SpatRaster. Raster object which is sum of all the individual crop raster

See Also

[cropharvest_rast\(\)](#)

Examples

```
crops_rast(list(monfreda = c("wheat", "barley"), mapspam2010 = c("wheat", "potato")))
```

dist_methods	<i>Distance methods supported</i>
--------------	-----------------------------------

Description

Contains supported strategies to calculate distance between two points. Use of one the methods in [sean\(\)](#) or [sensitivity_analysis\(\)](#).

Usage

```
dist_methods()
```

Value

vector

Examples

```
dist_methods()
```

GeoModel-class	<i>GeoModel class</i>
----------------	-----------------------

Description

A ref class to represent results of dispersal models.

Slots

amatrix An adjacency matrix to represent network.
 index A raster object representing the index.
 hdthreshold A numeric value representing the threshold.
 aggregation A character value representing the aggregation method.
 linkthreshold A numeric value representing the link threshold.
 beta A numeric value representing the beta parameter.
 gamma A numeric value representing the gamma parameter.

GeoNetwork-class	<i>GeoNetwork</i>
------------------	-------------------

Description

An S4 class representing a network of geographical data. This will wrap all the results from the risk analysis using `sean()` or `sensitivity_analysis()`. This class contains the field from Gmap class which has results in the form of SpatRaster and TIFF file.

Usage

```
## S4 replacement method for signature 'GeoNetwork'  
host_density(x) <- value
```

Arguments

x	GeoNetwork.
value	SpatRaster.

Value

GeoNetwork.

Slots

rasters A list of GeoRasters objects.
host_density A SpatRaster representing the host density.
me_rast A raster representing mean risk index.
me_out Character. A file path to the mean risk index raster.
diff_rast A raster representing difference.
diff_out Character. A file path to the difference raster.
var_rast A raster representing variance.
var_out Character. A file path to the variance raster.

GeoRasters-class *GeoRaster class*

Description

A class to represent raster vis-a-vis risk indices. This class encapsulates the results of apply dispersal models and metrics.

Fields

host_density SpatRaster. A spatial raster representing host density.

rasters List. List of raster representing risk indices. These are of type GeoModels.

global Boolean. True if contains GlobalRast object, False otherwise.

geoscale_param *Get geographical scales from the parameters*

Description

This function returns a list of geographical scales set in global and custom extent in `parameters.yaml`. If `global` is TRUE, the `CustomExt` is ignored.

Usage

```
geoscale_param(gparams = load_parameters())
```

Arguments

`gparams` Optional. [load_parameters\(\)](#) or null

Value

Vector. A set of geographical scales

get_parameters	<i>Get Parameters</i>
----------------	-----------------------

Description

This function retrieves the parameters and copies the parameter file to the specified output path.

Usage

```
get_parameters(out_path = tempdir(), iwindow = FALSE)
```

Arguments

out_path	character. The output path where the parameter file will be copied. The default is a temporary directory tempdir()
iwindow	logical. If window = TRUE, this will prompt the user to select the output directory using a file chooser window. The default value is FALSE.

Details

Using configuration file is an alternative to [sean\(\)](#)

Value

character. The path to the copied parameter file.

See Also

[set_parameters\(\)](#)

Examples

```
get_parameters()  
get_parameters(out = tempdir())
```

get_rasters	<i>Get rasters object from parameters</i>
-------------	---

Description

Takes named list of hosts as an input. See host object in [get_parameters\(\)](#) or [load_parameters\(\)](#). This is also a wrapper of [crops_rast\(\)](#). Function creates 2 raster object - one is a sum of all the crops specified under sources and other using the provided raster file. See [tiff_torast\(\)](#)

Usage

```
get_rasters(hosts)
```

Arguments

hosts List of hosts and values. It is synonym to Hosts object in parameters

Value

List of SpatRaster.

See Also

[load_parameters\(\)](#), [get_parameters\(\)](#), [tiff_torast\(\)](#), [cropharvest_rast\(\)](#)

Examples

```
# Get default rasters
## Not run:
get_rasters(list(mapspam2010 = c("wheat"), monfreda = c("avocado"), file = "some_raster.tif"))

## End(Not run)
```

GlobalRast-class

GlobalRast class

Description

A class to represent raster for global scales. Global scales are accessible using [global_scales\(\)](#). However, this class encapsulates the results of apply dispersal models and metrics.

Fields

east A list of raster for eastern hemisphere.

west A list of raster for western hemisphere.

global_scales	<i>Global geographical extent</i>
---------------	-----------------------------------

Description

This function provides the geographical extent used in a global analysis. This function returns the geographic extents of the eastern and western hemispheres used in the analysis. Each geographic extent is in the form of `c(Xmin, Xmax, Ymin, Ymax)`. The geohabnet functions are designed to work with the coordinate reference system: lon/lat WGS 84 (EPSG:4326).

Usage

```
global_scales()
```

Details

When a habitat connectivity analysis is global, the functions in geohabnet will conduct two separate analyses, one on the geographical scale of the eastern hemisphere and another for the western hemisphere. The final outcomes (such as maps or adjacency matrices) are then combined for the global analysis.

Value

List. Named list with scales for eastern and western hemispheres

See Also

[set_global_scales\(\)](#)

Gmap-class	<i>Gmap class</i>
------------	-------------------

Description

An S4 class to represent various maps in the form of SpatRaster.

Usage

```
setmaps(x, me, vari, dif)
```

Arguments

<code>x</code>	Gmap object.
<code>me</code>	SpatRaster. A raster representing mean risk index.
<code>vari</code>	SpatRaster. A raster representing variance.
<code>dif</code>	SpatRaster. A raster representing difference.

Value

Gmap object.

Slots

me_rast A raster representing mean risk index.
me_out Character. A file path to the mean risk index raster.
diff_rast A raster representing difference.
diff_out Character. A file path to the difference raster.
var_rast A raster representing variance.
var_out Character. A file path to the variance raster.

gplot	<i>Plot a Raster* object</i>
-------	------------------------------

Description

This is a wrapper for [terra::plot\(\)](#)

Usage

```
gplot(x, ...)
```

Arguments

x	a Raster* object
...	additional arguments passed to terra::plot()

Value

a plot

Examples

```
r <- terra::rast(nrows=108, ncols=21, xmin=0, xmax=10)
gplot(r)
gplot(r, col = "red")
gplot(r, col = "red", breaks = 10)
```

hci_diff	<i>Calculate difference map</i>
----------	---------------------------------

Description

This function produces a map of difference b/w mean and sum indexes in rank of cropland harvested area fraction.

Usage

```
hci_diff(x, y, global, geoscale, res = reso(), outdir = tempdir())
```

Arguments

x	SpatRaster.
y	SpatRaster.
global	Logical. TRUE if global analysis is desired, FALSE otherwise. east and west are required when TRUE.
geoscale	Numeric vector. x will be cropped to this extent.
res	Numeric. Map resolution. This value is used in aggregation and dis-aggregation operation. Default is reso() .
outdir	Character. Output directory for saving raster in TIFF format. Default is tempdir() .

Details

Ideally, the function is tested to yield desired results when `length(which(y[] > 0)) > length(which(x[] > 0))`.

Value

RiskMap. Contains result in the form of SpatRaster objects and file path of the saved maps.

hci_mean	<i>Calculate mean of raster objects</i>
----------	---

Description

Wrapper for [terra::mean\(\)](#). Calculates mean of list of rasters.

Usage

```

hci_mean(
  indices,
  global = FALSE,
  east = NULL,
  west = NULL,
  geoscale = NULL,
  res = reso(),
  plt = TRUE,
  outdir = tempdir()
)

```

Arguments

indices	List of SpatRasters. This input represents the spatial raster collection for which mean is to be calculated.
global	Logical. TRUE if global analysis is desired, FALSE otherwise. east and west are required when TRUE.
east	SpatRaster. Collection of risk indices on eastern extent.
west	SpatRaster. Collection of risk indices on western extent. When TRUE, geoscale is ignored. Default is TRUE.
geoscale	Vector. geographical scale. Default is NULL.
res	Numeric. Map resolution. This value is used in aggregation and dis-aggregation operation. Default is <code>reso()</code> .
plt	TRUE if need to plot mean map, FALSE otherwise.
outdir	Character. Output directory for saving raster in TIFF format. Default is <code>tempdir()</code> .

Value

RiskMap. Contains result in the form of SpatRaster objects and file path of the saved maps.

hci_variance	<i>Calculate variance of CCRI</i>
--------------	-----------------------------------

Description

This function produces a map of variance of CCRI based on input parameters

Usage

```

hci_variance(
  indices,
  rast,
  global,
  east = NULL,

```



```

west = NULL,
geoscale,
res = reso(),
outdir = tempdir()
)

```

Arguments

indices	SpatRaster. Collection of risk indices.
rast	SpatRaster. Template for variance output
global	Logical. TRUE if global analysis is desired, FALSE otherwise. east and west are required when TRUE.
east	SpatRaster. Collection of risk indices on eastern extent.
west	SpatRaster. Collection of risk indices on western extent. When TRUE, geoscale is ignored. Default is TRUE.
geoscale	Vector. geographical scale. Default is NULL.
res	Numeric. Map resolution. This value is used in aggregation and dis-aggregation operation. Default is reso() .
outdir	Character. Output directory for saving raster in TIFF format. Default is tempdir() .

Value

RiskMap. Contains result in the form of SpatRaster objects and file path of the saved maps.

host_density<- *Set the host density.*

Description

Sets the host density slot in the GeoNetwork object

Usage

```
host_density(x) <- value
```

Arguments

x	the GeoNetwork object.
value	SpatRaster.

inv_powerlaw

*Dispersal kernels***Description**

-[inv_powerlaw()] Get parameters and values pertaining to the inverse power law model. -
 [neg_exp()] Get parameters and values pertaining to the negative exponential model.

Usage

```
inv_powerlaw(
  params = load_parameters(),
  betas = NULL,
  mets = NULL,
  we = NULL,
  linkcutoff = NULL
)

neg_expo(
  params = load_parameters(),
  gammas = NULL,
  mets = NULL,
  we = NULL,
  linkcutoff = NULL
)
```

Arguments

params	Object. This function uses the parameter values defined in load_parameters() by default. If load_parameters() is not provided, the function will require the user to specify all arguments as listed below. If both load_parameters() and values for the arguments listed below are provided, load_parameters() takes precedence over the specified arguments.
betas	Numeric. Beta is the dispersal parameter used in the inverse power law to estimate a species' dispersal gradient. Please refer to Mundt et al (2009) for details on how to calculate this parameter. Any beta values should be positive. Smaller beta values indicate a higher likelihood of dispersal between nodes.
mets	Character. There are seven network metrics supported by geohabnet: "node_strength", "sum_of_nearest_neighbors", "eigenvector_centrality", "closeness", "betweenness", "degree", and "page_rank". Each specified network metric is calculated for each location in the target region, based on the link weights between each pair of locations. Run, for example, pagerank() for details of each network metric.
we	Numeric. This parameter indicates the weight(s) of each specified network metric, representing the importance of the network metric in the analysis. Since these weights represent percentages, any weight(s) should be between 0 and 100, and the sum of all specified weights should be 100.

linkcutoff	Numeric. This parameter is only used to calculate <code>betweenness()</code> and <code>closeness()</code> , and is equivalent to <code>cutoff</code> in these functions in the <code>igraph</code> package.
gammas	Numeric. Gamma is the dispersal parameter used in the negative exponential to estimate a species' dispersal gradient. Any gamma values should be positive. Smaller gamma values indicate a higher likelihood of dispersal between nodes.

Details

Refer to Esker et al (2007) for a discussion on the characteristics of each dispersal gradient or kernel model (i.e., inverse power law and negative exponential). The resulting object produced by `load_parameters()` provides the following values used when running the analysis -`beta` is a dispersal parameter for calculating the inverse power law model. -`gamma` is a dispersal parameter for calculating the negative exponential model. -`metrics` Each network metric is applied to the adjacency matrix produced in the intermediate step. -`weights` The link weights that is used in the network analysis. -`cutoff` Currently used as a parameter to calculate centrality in the network - `betweenness()` and `closeness()`. As defined in `igraph::betweenness()`, it's the maximum length to consider when calculating centrality. If zero or negative, then there is no such limit.

Value

List with parameters and values. See details.

References

- Esler PD, Sparks AH, Antony G, Bates M, Dall' Acqua W, Frank EE, Huebel L, Segovia V, Garrett KA (2007). "Ecology and Epidemiology in R: Modeling dispersal gradients." *The Plant Health Instructor*. doi:10.1094/PHIA2008012903
- Mundt CC, Sackett KE, Wallace LD, Cowger C, Dudley JP (2009). "Aerial Dispersal and Multiple-Scale Spread of Epidemic Disease." *Ecohealth*. doi:10.1007/s103930090251z
- Csardi G, Nepusz T (2006). "The igraph software package for complex network research." *Inter-Journal, Complex Systems*, 1695. <https://igraph.org>.
- Csárdi G, Nepusz T, Traag V, Horvát Sz, Zanini F, Noom D, Müller K (2024). *igraph: Network Analysis and Visualization in R*. doi:10.5281/zenodo.7682609, R package version 1.5.1, <https://CRAN.R-project.org/package=igraph>.

See Also

[supported_metrics\(\)](#)

load_parameters	<i>Load Parameters from YAML File</i>
-----------------	---------------------------------------

Description

This function loads parameters from a YAML file and stores them in an object.

Usage

```
load_parameters(filepath = .param_fp())
```

Arguments

filepath Path to the YAML file containing the parameters. By default, it takes the value of parameters.yaml in R user's directory.

Value

object with parameters and values

Examples

```
# Load parameters from default file
load_parameters()
```

mapspam

Supported sources for Mapspam

Description

Supported sources for Mapspam

Usage

```
mapspam()
```

monfreda

Supported sources for monfreda

Description

Supported sources for monfreda

Usage

```
monfreda()
```

ndplot	<i>Network density</i>
--------	------------------------

Description

Calculates and plots the network density of a GeoNetwork object.

Usage

```
ndplot(x)
```

Arguments

x A GeoNetwork object

Value

Vector. Up to two ggplot2 objects

ndplot, GeoNetwork-method	
	<i>Network density</i>

Description

Calculates and plots the network density of a GeoNetwork object. The plot is produced as dispersal parameter vs edge density.

Usage

```
## S4 method for signature 'GeoNetwork'  
ndplot(x)
```

Arguments

x A GeoNetwork object

Value

Vector. Up to two ggplot2 objects

Description

These are functions under the `igraph` package adapted to calculate habitat connectivity. In the context of habitat connectivity, the functions can be interpreted as follows:

- `nn_sum()`: Calculates the sum of nearest neighbors `igraph::knn()`.
- `node_strength()`: Calculates the sum of edge weights of adjacent nodes `igraph::strength()`.
- `betweenness()`: Calculates the node betweenness based on the number of shortest paths. Because the `igraph::betweenness()` function interprets link weights as distances to calculate the shortest paths, the `betweenness()` function in `geohabnet` transforms the link weights (or the relative likelihood of pathogen or pest movement) in the adjacency matrix so that higher link weight values will be the shortest (or more likely) paths for pathogen or pest movement.
- `ev()`: Calculates the eigenvector centrality of positions within the network `igraph::eigen_centrality()`.
- `closeness()`: measures how many steps is required to access every other vertex from a given vertex `igraph::closeness()`. Because the `igraph::closeness()` function interprets link weights as distances to calculate the shortest paths, this transforms the link weights (or the relative likelihood of pathogen or pest movement) in the adjacency matrix so that higher link weight values will be the shortest (or more likely) paths for pathogen or pest movement.
- `degree()`: number of adjacent edges `igraph::degree()`.
- `pagerank()`: page rank score for vertices `igraph::page_rank()`.

Usage

```
nn_sum(crop_dm, ...)
```

```
node_strength(crop_dm, ...)
```

```
betweenness(crop_dm, ...)
```

```
ev(crop_dm, ...)
```

```
degree(crop_dm, ...)
```

```
closeness(crop_dm, ...)
```

```
pagerank(crop_dm, ...)
```

Arguments

<code>crop_dm</code>	A square adjacency matrix, in which rows and columns names represent nodes (or locations) and each entry indicate the relative likelihood of pathogen or pest movement between a pair of nodes. In the internal workflow, the adjacency matrix comes as a result of operations within <code>sean()</code> function. This weight represents the importance of the network metric in the habitat connectivity analysis.
----------------------	---

... arguments to corresponding functions in igraph

Value

SpatRaster. Representing connectivity of each node or location.

References

Csardi G, Nepusz T (2006). “The igraph software package for complex network research.” *Inter-Journal, Complex Systems*, 1695. <https://igraph.org>.

See Also

Other metrics: [supported_metrics\(\)](#)

reset_params

Reset parameters.yaml

Description

Resets the values in the parameters.yaml file to the default initial values.

Usage

```
reset_params()
```

Value

Logical. TRUE if function was successfully executed

Examples

```
reset_params()
```

reso	<i>Get resolution value</i>
------	-----------------------------

Description

Resolution stored in parameter `.yaml`. Here, resolution values refer to the aggregation factor or granularity. Granularity is the number of small grid cells that are aggregated into larger grid cells in each direction (horizontally and vertically). For example, the finest spatial resolution of the Monfreda and MAPSPAM datasets in geohabnet is 5 minutes, a granularity value of 6 will result in maps with a spatial resolution of 0.5 degrees. If not provided, the resolution value used for the analysis is by default 24 (or two degrees when using the Monfreda and MAPSPAM datasets). Otherwise, a single integer value for granularity equal to or greater than one should be specified.

Usage

```
reso()
```

Value

Numeric. Resolution from parameters `.yaml`. The default is 12.

RiskMap-class	<i>RiskMap class</i>
---------------	----------------------

Description

An S4 class representing resulting maps from the specific operation type.

Fields

`map` Character. A file path to the map.

`riid` SpatRaster. This is one of the risk maps.

`spr` SpatRaster. A spatial raster representing the risk index.

`fp` Character. A file path to the risk index raster.

risk_indices	<i>Get risk indices</i>
--------------	-------------------------

Description

Get risk indices from GeoRasters object.

Usage

```
risk_indices(ri)
```

Arguments

`ri` GeoRasters object

Details

This function will unpack SpatRasters from GeoModel and thus is `future::future()` safe.

Value

List of risk indices. If the `ri` is global, the list will contain two elements, one for each hemisphere. e.g. `list(east = list(), west = list())`. If the `ri` is not global, the list will contain a single element, e.g. `list()`.

sa_onrasters	<i>Run sensitivity analysis</i>
--------------	---------------------------------

Description

Same as `sensitivity_analysis()` but it takes raster object and other parameters as an input.

- `sa_onrasters()` is a wrapper around `sean()` function. Takes raster object and other parameters as an input.
- `msean_onrast()` same as `sa_onrasters()`. Use this for side effects + results. Produces and plots the maps for the outcomes and results are returned as an object. It produces and plots the maps for the outcomes and results are returned as an object.

Usage

```
sa_onrasters(rast, link_thresholds = c(0), hd_thresholds = c(0), ...)

msean_onrast(
  global = TRUE,
  geoscale = NULL,
  res = reso(),
  outdir = tempdir(),
  ...
)
```

Arguments

rast	Raster object which will be used in analysis.
link_thresholds	Numeric vector. link threshold values
hd_thresholds	Numeric vector. host density threshold values
...	Additional parameters to be passed to sean() .
global	Logical. TRUE if global analysis, FALSE otherwise. Default is TRUE
geoscale	Numeric vector. Geographical coordinates in the form of c(Xmin, Xmax, Ymin, Ymax) which EPSG:4326 in coordinate reference system. If geoscale is NuLL, the extent is extracted from rast(SpatRaster) using terra::ext() .
res	Numeric. Resolution of the raster. Default is reso() .
outdir	Character. Output directory for saving raster in TIFF format. Default is tempdir() .

Details

Error not handled for non-overlapping extents.

Value

A list of calculated CCRI indices after operations. An index is generated for each combination of paramters. One combination is equivalent to [sean\(\)](#) function.

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, [doi:10.1093/biosci/biaa067](https://doi.org/10.1093/biosci/biaa067)

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, <https://CRAN.R-project.org/package=terra>

See Also

Use [get_rasters\(\)](#) to obtain raster object.
[msean_onrast\(\)](#) [supported_sources\(\)](#)

Examples

```
rr <- get_rasters(list(monfreda = c("avocado")))
res1 <- sa_onrasters(rr[[1]],
  global = FALSE,
  geoscale = c(-115, -75, 5, 32),
  c(0.0001, 0.00004),
  c(0.0001, 0.00005),
  c("sum", "mean"),
  res = 12)
res2 <- sa_onrasters(rr[[1]],
  global = TRUE,
  link_thresholds = c(0.000001),
  hd_thresholds = c(0.00015),
  agg_methods = c("sum"),
  res = 12)
res3 <- msean_onrast(rast = rr[[1]],
  link_thresholds = c(0.000001),
  hd_thresholds = c(0.00015))
```

 sean

Sensitivity analysis across maps of habitat connectivity

Description

This function performs a sensitivity analysis across different values of habitat connectivity for each location in a map. For each combination of selected parameters, an index of habitat connectivity is calculated. [sensitivity_analysis\(\)](#) is a wrapper around [sean\(\)](#) function.

- [msean\(\)](#) is a wrapper around [sean\(\)](#) function. It has additional argument to specify maps which are calculated using [connectivity\(\)](#) function. The maps are essentially the risk network.

Usage

```
sean(
  rast,
  global = TRUE,
  geoscale = NULL,
  agg_methods = c("sum", "mean"),
  dist_method = "geodesic",
  link_threshold = 0,
  hd_threshold = 0,
```

```

res = reso(),
inv_pl = inv_powerlaw(NULL, betas = c(0.5, 1, 1.5), mets = c("betweenness",
  "NODE_STRENGTH", "Sum_of_nearest_neighbors", "eigenVector_centraliTY"), we = c(50,
  15, 15, 20), linkcutoff = -1),
neg_exp = neg_expo(NULL, gammas = c(0.05, 1, 0.2, 0.3), mets = c("betweenness",
  "NODE_STRENGTH", "Sum_of_nearest_neighbors", "eigenVector_centraliTY"), we = c(50,
  15, 15, 20), linkcutoff = -1)
)

msean(
  rast,
  global = TRUE,
  geoscale = NULL,
  res = reso(),
  ...,
  outdir = tempdir()
)

```

Arguments

<code>rast</code>	Raster object which will be used in analysis.
<code>global</code>	Logical. TRUE if global analysis, FALSE otherwise. Default is TRUE
<code>geoscale</code>	Numeric vector. Geographical coordinates in the form of <code>c(Xmin, Xmax, Ymin, Ymax)</code> which EPSG:4326 in coordinate reference system. If <code>geoscale</code> is <code>NULL</code> , the extent is extracted from <code>rast(SpatRaster)</code> using <code>terra::ext()</code> .
<code>agg_methods</code>	Character. One or both the values - SUM, MEAN. Aggregation strategy for scaling the input raster to the desired resolution.
<code>dist_method</code>	Character. The method to calculate the distance matrix.
<code>link_threshold</code>	Numeric. A threshold value for link weight. All link weights that are below this threshold will be replaced with zero for the connectivity analysis. Link weights represent the relative likelihood of pathogen, pest, or invasive species movement between a pair of host locations, which is calculated using gravity models based on host density (or availability) and dispersal kernels.
<code>hd_threshold</code>	Numeric. A threshold value for host density. All locations with a host density below the selected threshold will be excluded from the connectivity analysis, which focuses the analysis on the most important locations. The values for the host density threshold can range between 0 and 1; if value is 1, all locations will be excluded from the analysis and 0 will include all locations in the analysis. Selecting a threshold for host density requires at least knowing what is the maximum value in the host density map to avoid excluding all locations in the analysis. if value is 1, all locations will be excluded from the analysis and 0 will include all locations in the analysis. Selecting a threshold for host density requires at least knowing what is the maximum value in the host density map to avoid excluding all locations in the analysis.
<code>res</code>	Numeric. Resolution of the raster. Default is <code>reso()</code> .
<code>inv_pl</code>	List. A named list of parameters for inverse power law. See details.

neg_exp	List. A named list of parameters for inverse negative exponential. See details. All locations with a host density below the selected threshold will be excluded from the connectivity analysis, which focuses the analysis on the most important locations. The values for the host density threshold can range between 0 and 1;
...	arguments passed to <code>sean()</code>
outdir	Character. Output directory for saving raster in TIFF format. Default is <code>tempdir()</code> .

Details

When `global = TRUE`, `geoscale` is ignored and `global_scales()` is used by default.

The functions `sean()` and `msean()` perform the same sensitivity analysis, but they differ in their return value. The return value of `msean()` is `GeoNetwork`, which contains the result from applying the `connectivity()` function on the habitat connectivity indexes. Essentially, the risk maps.

If neither the inverse power law nor the negative exponential dispersal kernel is specified, the function will return an error.

In `msean()`, three `spatRasters` are produced with the following values. For each location in the area of interest, the mean in habitat connectivity across selected parameters is calculated. For each location in the area of interest, the variance in habitat connectivity across selected parameters is calculated. For each location in the area of interest, the difference between the rank of habitat connectivity and the rank of host density is calculated. By default, each of these `spatRasters` is plotted for visualization.

Value

`GeoRasters`.

`GeoNetwork`.

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, *BioScience*, Volume 70, Issue 9, September 2020, Pages 744–758, [doi:10.1093/biosci/biaa067](https://doi.org/10.1093/biosci/biaa067)

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, <https://CRAN.R-project.org/package=terra>

See Also

Uses `connectivity()`

Uses `msean()` `inv_powerlaw()` `neg_expo()`

Examples

```
avocado <- cropharvest_rast("avocado", "monfreda")

# global
ri <- sean(avocado) # returns a list of GeoRasters
mri <- msean(rast = avocado) # returns GeoNetwork object

# non-global
# geoscale is a vector of xmin, xmax, ymin, ymax

# returns GeoRasters object
ri <- sean(avocado, global = FALSE, geoscale = c(-115, -75, 5, 32))
ri

# returns GeoNetwork object
mri <- msean(rast = avocado, global = FALSE, geoscale = c(-115, -75, 5, 32))
mri
```

search_crop

Search for crop

Description

It returns the dataset sources in which crop data is available. Essentially, a wrapper around [geodata::spamCrops\(\)](#) and [geodata::monfredaCrops\(\)](#)

Usage

```
search_crop(name)
```

Arguments

name	name of crop
------	--------------

Value

Logical. Sources in which crop data is available.

See Also

[supported_sources\(\)](#)

Examples

```
search_crop("coffee")
search_crop("wheat")

search_crop("jackfruit")
```

sensitivity_analysis *Sensitivity analysis for habitat connectivity*

Description

This function runs a sensitivity analysis on habitat connectivity calculated based on every combination of selected parameters. Parameter values in `sensitivity_analysis()` should be provided using the function `set_parameters()`. If no parameters are provided, then the `sensitivity_analysis()` function will run the sensitivity analysis using a default set of parameter values, which is accessible through the function `get_parameters()`. To customize parameter values, open the `parameters.yaml` that was automatically downloaded when `geohabnet` was installed, change, remove, or add parameter values directly in the `parameters.yaml` and save it. Once the values have been changed manually, run `set_parameters()` to set the new parameter values, which will return `TRUE` if the parameters were set successfully.

Usage

```
sensitivity_analysis(maps = TRUE, alert = TRUE)
```

Arguments

<code>maps</code>	logical. <code>TRUE</code> if maps of outcomes are to be plotted, <code>FALSE</code> otherwise. If <code>TRUE</code> , three maps are possible: a map of mean habitat connectivity, a map of variance of habitat connectivity, and a map of the difference between the ranks in habitat connectivity and habitat density.
<code>alert</code>	logical. <code>TRUE</code> if a beep sound is to be played once the analysis is completed, <code>FALSE</code> otherwise

Details

For each location in a region, `sensitivity_analysis()` calculates the habitat connectivity risk index (CCRI) proposed by Xing et al. (2021). By default, `sensitivity_analysis()` runs a sensitivity analysis on a global extent, see `global_scales()` for details. This function also plots maps of the outcomes automatically, but it will suppress maps for outcomes if `maps = FALSE` or `interactive()` is `FALSE`. The returned object is of class `GeoNetwork`, which contains two types of outcomes. One outcome type corresponds to `spatRasters` representing the maps of habitat connectivity. The second type corresponds to adjacency matrices used to calculate the habitat connectivity, where columns and rows represent locations in the maps and entries are the relative likelihood of pathogen or pest movement between each pair of nodes.

Value

GeoNetwork. Errors are not handled.

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, doi:10.1093/biosci/biaa067

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, <https://CRAN.R-project.org/package=terra>

See Also

[sa_onrasters\(\)](#) [sean\(\)](#) [global_scales\(\)](#) [get_parameters\(\)](#) [set_parameters\(\)](#) [connectivity\(\)](#)

Examples

```
# Run analysis on specified parameters.yaml
ss1 <- sensitivity_analysis()
ss2 <- sensitivity_analysis(FALSE, FALSE)
ss3 <- sensitivity_analysis(TRUE, FALSE)
```

setmaps, Gmap-method *Sets the map slots in the Gmap object.*

Description

This wraps the results(SpatRasters) from the risk analysis.

Usage

```
## S4 method for signature 'Gmap'
setmaps(x, me, vari, dif)
```

Arguments

x	A Gmap object.
me	A GeoRaster object representing mean risk index.
vari	A GeoRaster object representing variance.
dif	A GeoRaster object representing difference.

Value

A Gmap object.

setprops	<i>Set properties of the GeoModel object.</i>
----------	---

Description

Set properties of the GeoModel object.

Usage

```
setprops(x, aggregation, hdthreshold, linkthreshold)
```

Arguments

x	The GeoModel object.
aggregation	Character. A value representing the aggregation method.
hdthreshold	Numeric. A value representing the host density threshold.
linkthreshold	Numeric. A value representing the link threshold in a network.

Value

The GeoModel object with updated properties.

setprops,GeoModel,character,numeric,numeric-method	<i>Set properties of the GeoModel object.</i>
--	---

Description

Set properties of the GeoModel object.

Usage

```
## S4 method for signature 'GeoModel,character,numeric,numeric'
setprops(x, aggregation, hdthreshold, linkthreshold)
```

Arguments

x	The GeoModel object.
aggregation	Character. A value representing the aggregation method.
hdthreshold	Numeric. A value representing the host density threshold.
linkthreshold	Numeric. A value representing the link threshold in a network.

Value

The GeoModel object with updated properties.

set_global_scales *Set global geographical extent*

Description

This function sets the geographical extents used in global analysis. See also [geoscale_param\(\)](#) to set the geographic extent of an analysis that is not global. Each geographic extent should be in the form of `c(Xmin, Xmax, Ymin, Ymax)`. Geographic extent must be specified by four values in degrees that represent the geographic limits of the area for analysis, following the order: minimum longitude, maximum longitude, minimum latitude, and maximum latitude. Degrees are in decimal notation and have a negative sign for the southern and western hemispheres.

Usage

```
set_global_scales(value)
```

Arguments

value list. Named list of eastern and western hemisphere extents. See usage.

Value

List. Named list with scales for eastern and western hemispheres

See Also

[global_scales\(\)](#) [terra::ext\(\)](#)

Examples

```
set_global_scales(list(east = c(-24, 180, -58, 60), west = c(-140, -34, -58, 60)))
```

set_parameters *Set Parameters*

Description

This function allows the user to set the parameters by replacing the existing parameters file with a new one. Use [get_parameters\(\)](#) to modify the parameter values.

Usage

```
set_parameters(new_params, iwindow = FALSE)
```

Arguments

new_params	The path to the new parameters file.
iwindow	Logical, indicating whether to prompt the user to select the new parameters file using a file selection window. The default value of this parameter is set to FALSE.

Value

None

Examples

```
param_fp <- get_parameters()
set_parameters(param_fp)
```

sp_rast	<i>Raster for mapspam crop.</i>
---------	---------------------------------

Description

get raster for crop in mapspam dataset

Usage

```
sp_rast(crp, africa = FALSE)
```

Arguments

crp	character. name of a crop. Case-insensitive.
africa	Fetch the 2017 Mpasam crop data of Africa. Default is FALSE.

Details

See [geodata::spamCrops\(\)](#) for supported crops.

Value

SpatRaster

References

International Food Policy Research Institute, 2020. Spatially-Disaggregated Crop Production Statistics Data in Africa South of the Sahara for 2017. <doi: 10.7910/DVN/FSSKBW>, Harvard Dataverse, V2

See Also

[geodata::spamCrops\(\)](#) [search_crop\(\)](#)

Examples

```
sp_rast("potato")
sp_rast("potato", TRUE)
```

supported_metrics	<i>Returns metrics currently supported in the analysis.</i>
-------------------	---

Description

Returns metrics currently supported in the analysis.

Usage

```
supported_metrics()
```

Value

vector of supported metrics.

See Also

Other metrics: [nn_sum\(\)](#)

Examples

```
supported_metrics()
```

supported_sources	<i>Get supported sources of crops</i>
-------------------	---------------------------------------

Description

When provided, [cropharvest_rast\(\)](#) will look for cropland data in this specific source.

Usage

```
supported_sources()
```

Value

Vector of supported sources. Also used as a lookup to find get raster object.

Examples

```
# Get currently supported sources
supported_sources()
```

tiff_torast	<i>Get raster object from tif file</i>
-------------	--

Description

This is a wrapper of `terra::rast()` and generates a raster object if provided with a TIF file.

Usage

```
tiff_torast(path_to_tif)
```

Arguments

`path_to_tif` TIFF file. This is an encoding of map in raster format.

Value

SpatRaster.

Examples

```
# Generate raster for usage
fp <- paste(tempfile(), ".tif", sep = "")
ret <- utils::download.file(
  "https://geohabnet.s3.us-east-2.amazonaws.com/util-rasters/avocado_HarvestedAreaFraction.tif",
  destfile = fp, method = "auto", mode = "wb")
tiff_torast(fp)
```

Index

- * **metrics**
 - nn_sum, 22
 - supported_metrics, 36
- .grast_ro (GlobalRast-class), 12
- .indices, 4
- .model_ob (GeoModel-class), 8
- .rast_ro (GeoRasters-class), 10

- betweenness (nn_sum), 22
- betweenness(), 19, 22

- closeness (nn_sum), 22
- closeness(), 19
- connectivity, 5
- connectivity(), 27, 29, 32
- cropharvest_rast, 6
- cropharvest_rast(), 7, 12, 36
- crops_rast, 7
- crops_rast(), 11

- degree (nn_sum), 22
- dist_methods, 8

- ev (nn_sum), 22

- future::future(), 25

- geodata::monfredaCrops(), 7, 30
- geodata::spamCrops(), 7, 30, 35, 36
- geohabnet, 22
- GeoModel-class, 8
- GeoNetwork-class, 9
- GeoRasters-class, 10
- geoscale_param, 10
- geoscale_param(), 34
- get_parameters, 11
- get_parameters(), 11, 12, 31, 32, 34
- get_rasters, 11
- get_rasters(), 27
- global_scales, 13
- global_scales(), 12, 29, 31, 32, 34

- GlobalRast-class, 12
- Gmap-class, 13
- gplot, 14

- hci_diff, 15
- hci_diff(), 6
- hci_mean, 15
- hci_mean(), 6
- hci_variance, 16
- hci_variance(), 6
- host_density<-, 17
- host_density<-, GeoNetwork-method (GeoNetwork-class), 9

- igraph::betweenness(), 19, 22
- igraph::closeness(), 22
- igraph::degree(), 22
- igraph::eigen_centrality(), 22
- igraph::knn(), 22
- igraph::page_rank(), 22
- igraph::strength(), 22
- interactive(), 6, 31
- inv_powerlaw, 18
- inv_powerlaw(), 29

- load_parameters, 19
- load_parameters(), 10–12, 18, 19

- mapspam, 20
- monfreda, 20
- msean (sean), 27
- msean(), 29
- msean_onrast (sa_onrasters), 25
- msean_onrast(), 27

- ndplot, 21
- ndplot, GeoNetwork-method, 21
- neg_expo (inv_powerlaw), 18
- neg_expo(), 29
- nn_sum, 22, 36
- node_strength (nn_sum), 22

pagerank (nn_sum), 22
pagerank(), 18

reset_params, 23
reso, 24
reso(), 5, 15–17, 26, 28
risk_indices, 25
RiskMap-class, 24

sa_onrasters, 25
sa_onrasters(), 25, 32
sean, 27
sean(), 6, 8, 9, 11, 25–27, 29, 32
search_crop, 30
search_crop(), 36
sensitivity_analysis, 31
sensitivity_analysis(), 8, 9, 25, 27, 31
set_global_scales, 34
set_global_scales(), 13
set_parameters, 34
set_parameters(), 11, 31, 32
setmaps (Gmap-class), 13
setmaps, Gmap-method, 32
setprops, 33
setprops, GeoModel, character, numeric, numeric-method,
33
sp_rast, 35
supported_metrics, 23, 36
supported_metrics(), 19
supported_sources, 36
supported_sources(), 27, 30

tempdir(), 5, 6, 11, 15–17, 26, 29
terra::ext(), 26, 28, 34
terra::mean(), 15
terra::plot(), 14
terra::rast(), 37
tiff_torast, 37
tiff_torast(), 11, 12