

Package: geosapi (via r-universe)

July 22, 2026

Type Package

Title GeoServer REST API R Interface

Version 0.8-1

Date 2026-07-22

Maintainer Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Description Provides an R interface to the GeoServer REST API, allowing to upload and publish data in a GeoServer web-application and expose data to OGC Web-Services. The package currently supports all CRUD (Create,Read,Update,Delete) operations on GeoServer workspaces, namespaces, datastores (stores of vector data), featuretypes, layers, styles, as well as vector data upload operations. For more information about the GeoServer REST API, see <https://docs.geoserver.org/main/en/user/rest/>.

Depends R (>= 3.1.0)

Imports R6, cli, openssl, httr, xml2, magrittr, keyring, readr

Suggests testthat, waldo, roxygen2, shiny, knitr, markdown

License MIT + file LICENSE

URL <https://github.com/eblondel/geosapi>,
<https://eblondel.github.io/geosapi/>, <https://geoserver.org/>

BugReports <https://github.com/eblondel/geosapi/issues>

LazyLoad yes

RoxygenNote 7.3.3

VignetteBuilder knitr

NeedsCompilation no

Author Emmanuel Blondel [aut, cre] (ORCID:
<https://orcid.org/0000-0002-5870-5762>)

Repository <https://cran.r-universe.dev>

Date/Publication 2026-07-22 08:20:02 UTC

RemoteUrl <https://github.com/cran/geosapi>

RemoteRef HEAD

RemoteSha 854caba07ea22ca3b05326602ad8cb5e01c58a9d

Contents

geosapi	3
GSAbstractCoverageStore	4
GSAbstractDataStore	5
GSAbstractDBDataStore	8
GSAbstractStore	13
GSAccessControlListManager	15
GSArcGridCoverageStore	19
GSCoverage	20
GSCoverageBand	22
GSCoverageStoreManager	25
GSCoverageView	32
GSDataStoreManager	35
GSDimension	43
GSFeatureDimension	46
GSFeatureType	47
GSGeoPackageDataStore	49
GSGeoTIFFCoverageStore	51
GSIImageMosaicCoverageStore	52
GSInputCoverageBand	53
GSLayer	55
GSLayerGroup	59
GSLayerManager	64
GSLayerRule	67
GSManger	68
GSMetadataLink	72
GSMonitorManager	74
GSNamespace	75
GSNamespaceManager	76
GSOacleNGDataStore	78
GSPostGISDataStore	80
GSPublishable	81
GSResource	83
GSRESTEntrySet	88
GSRESTResource	90
GSRestRule	92
GSRule	93
GSServiceManager	94
GSServiceRule	99
GSServiceSettings	100
GSShapefileDataStore	104
GSShapefileDirectoryDataStore	106

GSShinyMonitor	108
GSStyleManager	109
GSUtils	112
GSVersion	114
GSVirtualTable	116
GSVirtualTableGeometry	118
GSVirtualTableParameter	120
GSWorkspace	121
GSWorkspaceManager	122
GSWorkspaceSettings	126
GSWorldImageCoverageStore	128
Index	130

geosapi

GeoServer REST API R Interface

Description

Provides an R interface to the GeoServer REST API, allowing to upload and publish data in a GeoServer web-application and expose data to OGC Web-Services. The package currently supports all CRUD (Create,Read,Update,Delete) operations on GeoServer workspaces, namespaces, datastores (stores of vector data), featuretypes, layers, styles, as well as vector data upload operations. For more information about the GeoServer REST API, see <<https://docs.geoserver.org/main/en/user/rest/>>

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

See Also

Useful links:

- <https://github.com/eblondel/geosapi>
- <https://eblondel.github.io/geosapi/>
- <https://geoserver.org/>
- Report bugs at <https://github.com/eblondel/geosapi/issues>

GSAbstractCoverageStore

Geoserver REST API CoverageStore

Description

Geoserver REST API CoverageStore

Geoserver REST API CoverageStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer CoverageStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> GSAbstractCoverageStore

Public fields

url URL of the abstract coverage store

Methods

Public methods:

- [GSAbstractCoverageStore\\$new\(\)](#)
- [GSAbstractCoverageStore\\$decode\(\)](#)
- [GSAbstractCoverageStore\\$setUrl\(\)](#)
- [GSAbstractCoverageStore\\$clone\(\)](#)

Method `new()`: initializes an abstract coverage store

Usage:

```
GSAbstractCoverageStore$new(
  xml = NULL,
  type = NULL,
  name = NULL,
  description = "",
  enabled = TRUE,
  url = NULL
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML

type the type of coverage store
 name coverage store name
 description coverage store description
 enabled whether the store should be enabled or not. Default is TRUE
 url URL of the store

Method decode(): Decodes a coverage store from XML

Usage:

GSAbstractCoverageStore\$decode(xml)

Arguments:

xml an object of class [xml_node-class](#)

Returns: an object of class [GSAbstractCoverageStore](#)

Method setUrl(): set coverage store URL

Usage:

GSAbstractCoverageStore\$setUrl(url)

Arguments:

url the store URL to set

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSAbstractCoverageStore\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSAbstractDataStore *Geoserver REST API DataStore*

Description

Geoserver REST API DataStore

Geoserver REST API DataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer datastore

Super classes

`geosapi::GSRESTResource` -> `geosapi::GSAbstractStore` -> `GSAbstractDataStore`

Public fields

`connectionParameters` the list of connection parameters

Methods**Public methods:**

- `GSAbstractDataStore$new()`
- `GSAbstractDataStore$decode()`
- `GSAbstractDataStore$setConnectionParameters()`
- `GSAbstractDataStore$addConnectionParameter()`
- `GSAbstractDataStore$setConnectionParameter()`
- `GSAbstractDataStore$delConnectionParameter()`
- `GSAbstractDataStore$clone()`

Method `new()`: initializes an abstract data store

Usage:

```
GSAbstractDataStore$new(
  xml = NULL,
  type = NULL,
  name = NULL,
  description = "",
  enabled = TRUE,
  connectionParameters
)
```

Arguments:

`xml` an object of class `xml_node-class` to create object from XML
`type` the type of coverage store
`name` coverage store name
`description` coverage store description
`enabled` whether the store should be enabled or not. Default is TRUE
`connectionParameters` the list of connection parameters

Method `decode()`: Decodes a data store from XML

Usage:

```
GSAbstractDataStore$decode(xml)
```

Arguments:

`xml` an object of class `xml_node-class`

Returns: an object of class `GSAbstractDataStore`

Method `setConnectionParameters()`: Set list connection parameters. The argument should be an object of class `GSRESTEntrySet` giving a list of key/value parameter entries.

Usage:

GSAbstractDataStore\$setConnectionParameters(parameters)

Arguments:

parameters an object of class [GSRESTEntrySet](#)

Method addConnectionParameter(): Adds a connection parameter

Usage:

GSAbstractDataStore\$addConnectionParameter(key, value)

Arguments:

key connection parameter key

value connection parameter value

Returns: TRUE if added, FALSE otherwise

Method setConnectionParameter(): Sets a connection parameter

Usage:

GSAbstractDataStore\$setConnectionParameter(key, value)

Arguments:

key connection parameter key

value connection parameter value

Method delConnectionParameter(): Removes a connection parameter

Usage:

GSAbstractDataStore\$delConnectionParameter(key)

Arguments:

key connection parameter key

value connection parameter value

Returns: TRUE if removed, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSAbstractDataStore\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSAbstractDBDataStore *Geoserver REST API AbstractDBDataStore*

Description

Geoserver REST API AbstractDBDataStore

Geoserver REST API AbstractDBDataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer abstract DB dataStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> [geosapi::GSAbstractDataStore](#)
-> [GSAbstractDBDataStore](#)

Methods

Public methods:

- [GSAbstractDBDataStore\\$new\(\)](#)
- [GSAbstractDBDataStore\\$setDatabaseType\(\)](#)
- [GSAbstractDBDataStore\\$setNamespace\(\)](#)
- [GSAbstractDBDataStore\\$setHost\(\)](#)
- [GSAbstractDBDataStore\\$setPort\(\)](#)
- [GSAbstractDBDataStore\\$setDatabase\(\)](#)
- [GSAbstractDBDataStore\\$setSchema\(\)](#)
- [GSAbstractDBDataStore\\$setUser\(\)](#)
- [GSAbstractDBDataStore\\$setPassword\(\)](#)
- [GSAbstractDBDataStore\\$setJndiReferenceName\(\)](#)
- [GSAbstractDBDataStore\\$setExposePrimaryKeys\(\)](#)
- [GSAbstractDBDataStore\\$setMinConnections\(\)](#)
- [GSAbstractDBDataStore\\$setMaxConnections\(\)](#)
- [GSAbstractDBDataStore\\$setFetchSize\(\)](#)
- [GSAbstractDBDataStore\\$setConnectionTimeout\(\)](#)
- [GSAbstractDBDataStore\\$setValidateConnections\(\)](#)
- [GSAbstractDBDataStore\\$setPrimaryKeyMetadataTable\(\)](#)
- [GSAbstractDBDataStore\\$setLooseBBox\(\)](#)
- [GSAbstractDBDataStore\\$setPreparedStatements\(\)](#)
- [GSAbstractDBDataStore\\$setMaxOpenPreparedStatements\(\)](#)

- [GSAbstractDBDataStore\\$setEstimatedExtends\(\)](#)
- [GSAbstractDBDataStore\\$setDefaultConnectionParameters\(\)](#)
- [GSAbstractDBDataStore\\$clone\(\)](#)

Method `new()`: initializes an abstract DB data store

Usage:

```
GSAbstractDBDataStore$new(  
  xml = NULL,  
  type = NULL,  
  dbType = NULL,  
  name = NULL,  
  description = "",  
  enabled = TRUE  
)
```

Arguments:

`xml` an object of class [xml_node-class](#) to create object from XML
`type` the type of DB data store
`dbType` DB type
`name` coverage store name
`description` coverage store description
`enabled` whether the store should be enabled or not. Default is TRUE

Method `setDatabaseType()`: Set database type

Usage:

```
GSAbstractDBDataStore$setDatabaseType(dbtype)
```

Arguments:

`dbtype` DB type

Method `setNamespace()`: Set namespace

Usage:

```
GSAbstractDBDataStore$setNamespace(namespace)
```

Arguments:

`namespace` namespace

Method `setHost()`: Set host

Usage:

```
GSAbstractDBDataStore$setHost(host)
```

Arguments:

`host` host

Method `setPort()`: Set port

Usage:

```
GSAbstractDBDataStore$setPort(port)
```

Arguments:

port port

Method setDatabase(): Set database

Usage:

GSAbstractDBDataStore\$setDatabase(database)

Arguments:

database database

Method setSchema(): Set schema

Usage:

GSAbstractDBDataStore\$setSchema(schema)

Arguments:

schema schema

Method setUser(): Set user

Usage:

GSAbstractDBDataStore\$setUser(user)

Arguments:

user user

Method setPassword(): Set password

Usage:

GSAbstractDBDataStore\$setPassword(password)

Arguments:

password password

Method setJndiReferenceName(): Set JNDI reference name

Usage:

GSAbstractDBDataStore\$setJndiReferenceName(jndiReferenceName)

Arguments:

jndiReferenceName JNDI reference name

Method setExposePrimaryKeys(): Set expose primary keyws

Usage:

GSAbstractDBDataStore\$setExposePrimaryKeys(exposePrimaryKeys)

Arguments:

exposePrimaryKeys expose primary keys

Method setMinConnections(): Set min connections

Usage:

GSAbstractDBDataStore\$setMinConnections(minConnections = 1)

Arguments:

minConnections min connections. Default is 11

Method setMaxConnections(): Set max connections

Usage:

```
GSAbstractDBDataStore$setMaxConnections(maxConnections = 10)
```

Arguments:

maxConnections max connections. Default is 10

Method setFetchSize(): Set fetch size

Usage:

```
GSAbstractDBDataStore$setFetchSize(fetchSize = 1000)
```

Arguments:

fetchSize fetch size. Default is 1000

Method setConnectionTimeout(): Set connection timeout

Usage:

```
GSAbstractDBDataStore$setConnectionTimeout(seconds = 20)
```

Arguments:

seconds timeout (in seconds). Default is 20

Method setValidateConnections(): Set validate connection

Usage:

```
GSAbstractDBDataStore$setValidateConnections(validateConnections)
```

Arguments:

validateConnections Validate connections

Method setPrimaryKeyMetadataTable(): Set primary key metadata table

Usage:

```
GSAbstractDBDataStore$setPrimaryKeyMetadataTable(primaryKeyMetadataTable)
```

Arguments:

primaryKeyMetadataTable primary key metadata table

Method setLooseBBox(): Set loose bbox

Usage:

```
GSAbstractDBDataStore$setLooseBBox(looseBBox = TRUE)
```

Arguments:

looseBBox loose bbox. Default is TRUE

Method setPreparedStatements(): Set prepared statements

Usage:

```
GSAbstractDBDataStore$setPreparedStatements(preparedStatements = FALSE)
```

Arguments:

preparedStatements prepared Statements. Default is FALSE

Method setMaxOpenPreparedStatements(): Set max open prepared statements

Usage:

```
GSAbstractDBDataStore$setMaxOpenPreparedStatements(  
  maxOpenPreparedStatements = 50  
)
```

Arguments:

maxOpenPreparedStatements max open preprepared statements. Default is 50

Method setEstimatedExtends(): Set estimatedExtends

Usage:

```
GSAbstractDBDataStore$setEstimatedExtends(estimatedExtends = FALSE)
```

Arguments:

estimatedExtends estimated extends. Default is FALSE

Method setDefaultConnectionParameters(): Set default connection parameters

Usage:

```
GSAbstractDBDataStore$setDefaultConnectionParameters()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSAbstractDBDataStore$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Internal abstract class used for setting DB stores

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSAbstractStore	<i>Geoserver REST API Store</i>
-----------------	---------------------------------

Description

Geoserver REST API Store

Geoserver REST API Store

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer store

Super class

[geosapi : GSRESTResource](#) -> GSAbstractStore

Public fields

full whether store object is fully described

name store name

enabled if the store is enabled or not

description store description

type store type

workspace workspace name

Methods**Public methods:**

- [GSAbstractStore\\$new\(\)](#)
- [GSAbstractStore\\$decode\(\)](#)
- [GSAbstractStore\\$setType\(\)](#)
- [GSAbstractStore\\$setEnabled\(\)](#)
- [GSAbstractStore\\$setDescription\(\)](#)
- [GSAbstractStore\\$clone\(\)](#)

Method [new\(\)](#): initializes an abstract store

Usage:

```
GSAbstractStore$new(
  xml = NULL,
  storeType,
  type = NULL,
  name = NULL,
  description = "",
  enabled = TRUE
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML
 storeType store type
 type the type of coverage store
 name coverage store name
 description coverage store description
 enabled whether the store should be enabled or not. Default is TRUE

Method decode(): Decodes store from XML

Usage:

```
GSAbstractStore$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method setType(): Set type

Usage:

```
GSAbstractStore$setType(type)
```

Arguments:

type type

Method setEnabled(): Set enabled

Usage:

```
GSAbstractStore$setEnabled(enabled)
```

Arguments:

enabled enabled

Method setDescription(): Set description

Usage:

```
GSAbstractStore$setDescription(description)
```

Arguments:

description description

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSAbstractStore$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSAccessControlListManager

Geoserver REST API Access Control List Manager

Description

Geoserver REST API Access Control List Manager

Geoserver REST API Access Control List Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing GeoServer Access Control List (ACL) operations.

Super class

[geosapi::GManager](#) -> GSAccessControlListManager

Methods**Public methods:**

- [GSAccessControlListManager\\$setCatalogMode\(\)](#)
- [GSAccessControlListManager\\$getCatalogMode\(\)](#)
- [GSAccessControlListManager\\$getRules\(\)](#)
- [GSAccessControlListManager\\$getLayerRules\(\)](#)
- [GSAccessControlListManager\\$getServiceRules\(\)](#)
- [GSAccessControlListManager\\$getRestRules\(\)](#)
- [GSAccessControlListManager\\$getRule\(\)](#)
- [GSAccessControlListManager\\$getLayerRule\(\)](#)
- [GSAccessControlListManager\\$getServiceRule\(\)](#)
- [GSAccessControlListManager\\$getRestRule\(\)](#)
- [GSAccessControlListManager\\$addRule\(\)](#)
- [GSAccessControlListManager\\$addLayerRule\(\)](#)
- [GSAccessControlListManager\\$addServiceRule\(\)](#)
- [GSAccessControlListManager\\$addRestRule\(\)](#)
- [GSAccessControlListManager\\$modifyRule\(\)](#)
- [GSAccessControlListManager\\$deleteRule\(\)](#)
- [GSAccessControlListManager\\$clone\(\)](#)

Method setCatalogMode(): Set the catalog mode

Usage:

```
GSAccessControlListManager$setCatalogMode(  
  mode = c("HIDE", "MIXED", "CHALLENGE")  
)
```

Arguments:

mode mode

Returns: TRUE if set, FALSE otherwise

Method getCatalogMode(): Get the catalog mode

Usage:

```
GSAccessControlListManager$getCatalogMode()
```

Returns: the mode either HIDE, MIXED or CHALLENGE

Method getRules(): Get rules

Usage:

```
GSAccessControlListManager$getRules(domain = c("layers", "services", "rest"))
```

Arguments:

domain the access control domain

Returns: the list of rules for a given domain

Method getLayerRules(): Method to get the list of 'layers' rules

Usage:

```
GSAccessControlListManager$getLayerRules()
```

Returns: the list of 'layers' rules

Method getServiceRules(): Method to get the list of 'services' rules

Usage:

```
GSAccessControlListManager$getServiceRules()
```

Returns: the list of 'services' rules

Method getRestRules(): Method to get the list of 'rest' rules

Usage:

```
GSAccessControlListManager$getRestRules()
```

Returns: the list of 'rest' rules

Method getRule(): Method to get a rule by resource

Usage:

```
GSAccessControlListManager$getRule(  
  domain = c("layers", "services", "rest"),  
  resource  
)
```

Arguments:

domain the access control domain

resource resource

Returns: an object of class [GSRule](#) or NULL if no rule is found

Method getLayerRule(): Method to get a 'layers' rule

Usage:

```
GSAccessControlListManager$getLayerRule(resource)
```

Arguments:

resource resource

Returns: an object of class [GSLayerRule](#) or NULL if no rule is found

Method getServiceRule(): Method to get a 'services' rule

Usage:

```
GSAccessControlListManager$getServiceRule(resource)
```

Arguments:

resource resource

Returns: an object of class [GSServiceRule](#) or NULL if no rule is found

Method getRestRule(): Method to get a 'rest' rule

Usage:

```
GSAccessControlListManager$getRestRule(resource)
```

Arguments:

resource resource

Returns: an object of class [GSRestRule](#) or NULL if no rule is found

Method addRule(): Generic method to add an access control rule

Usage:

```
GSAccessControlListManager$addRule(rule, position = c("first", "last"))
```

Arguments:

rule object of class [GSRule](#)

position position with the list of rules, either "first" or "last". The position is especially true to capture to the order of priority. For priority, put 'first'.

Returns: TRUE if added, FALSE otherwise

Method addLayerRule(): Adds an access control layer rule

Usage:

```
GSAccessControlListManager$addLayerRule(
  ws = NULL,
  lyr = "*",
  permission = c("r", "w", "a"),
  roles
)
```

Arguments:

ws the resource workspace. Default is NULL
 lyr the target layer to which the access control should be added
 permission the rule permission, either r (read), w (write) or a (administer)
 roles one or more roles to add for the rule

Returns: TRUE if added, FALSE otherwise

Method addServiceRule(): Adds an access control service rule

Usage:

```
GSAccessControlListManager$addServiceRule(
  service,
  method,
  permission = c("r", "w", "a"),
  roles
)
```

Arguments:

service service subject to the access control rule, eg. 'wfs'
 method service method subject to the access control rule, eg. 'GetFeature'
 permission the rule permission, either r (read), w (write) or a (administer)
 roles one or more roles to add for the rule

Returns: TRUE if added, FALSE otherwise

Method addRestRule(): Adds an access control rest rule

Usage:

```
GSAccessControlListManager$addRestRule(pattern = "/*", methods, roles)
```

Arguments:

pattern a URL Ant pattern, only applicable for domain rest. Default is /*
 methods HTTP method(s)
 roles one or more roles to add for the rule

Returns: TRUE if added, FALSE otherwise

Method modifyRule(): Generic method to modify an access control rule

Usage:

```
GSAccessControlListManager$modifyRule(rule, position = c("first", "last"))
```

Arguments:

rule object of class [GSRule](#)
 position position with the list of rules, either "first" or "last". The position is especially true to capture to the order of priority. For priority, put 'first'.

Returns: TRUE if modified, FALSE otherwise

Method deleteRule(): Generic method to delete an access control rule

Usage:

GSAccessControlListManager\$deleteRule(rule)

Arguments:

rule object of class [GSRule](#)

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSAccessControlListManager\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
  GSAccessControlListManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)
```

GSArcGridCoverageStore

Geoserver REST API ArcGridCoverageStore

Description

Geoserver REST API ArcGridCoverageStore

Geoserver REST API ArcGridCoverageStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer ArcGrid CoverageStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> [geosapi::GSAbstractCoverageStore](#)
-> GSArcGridCoverageStore

Public fields

url url

Methods**Public methods:**

- [GSArcGridCoverageStore\\$new\(\)](#)
- [GSArcGridCoverageStore\\$clone\(\)](#)

Method new(): initializes an abstract ArcGrid coverage store

Usage:

```
GSArcGridCoverageStore$new(  
    xml = NULL,  
    name = NULL,  
    description = "",  
    enabled = TRUE,  
    url = NULL  
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML
name coverage store name
description coverage store description
enabled whether the store should be enabled or not. Default is TRUE
url url

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSArcGridCoverageStore$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSCoverage

A GeoServer coverage

Description

This class models a GeoServer coverage. This class is to be used for manipulating representations of vector data with GeoServer.

Format

[R6Class](#) object.

Details

Geoserver REST API Resource

Value

Object of [R6Class](#) for modelling a GeoServer coverage

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSResource](#) -> [GSCoverage](#)

Public fields

cqlFilter CQL filter

Methods**Public methods:**

- [GSCoverage\\$new\(\)](#)
- [GSCoverage\\$decode\(\)](#)
- [GSCoverage\\$setView\(\)](#)
- [GSCoverage\\$delView\(\)](#)
- [GSCoverage\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [GSCoverage](#) from XML

Usage:

[GSCoverage\\$new](#)(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method [decode\(\)](#): Decodes coverage from XML

Usage:

[GSCoverage\\$decode](#)(xml)

Arguments:

xml object of class [xml_node-class](#)

Method [setView\(\)](#): Set view

Usage:

[GSCoverage\\$setView](#)(cv)

Arguments:

cv cv, object of class [GSCoverageView](#)

Returns: TRUE if set, FALSE otherwise

Method delView(): Deletes view

Usage:

```
GSCoverage$delView()
```

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSCoverage$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
gt <- GSCoverage$new()
```

GSCoverageBand

Geoserver REST API GSCoverageBand

Description

Geoserver REST API GSCoverageBand

Geoserver REST API GSCoverageBand

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer coverage band

Methods

new(xml) This method is used to instantiate a GSCoverageBand
 decode(xml) This method is used to decode a GSCoverageBand from XML
 encode() This method is used to encode a GSCoverageBand to XML
 setDefinition(definition) Sets the coverage band definition
 setIndex(index) Sets the coverage band index
 setCompositionType Sets the composition type. Only 'BAND_SELECT' is supported by GeoServer for now.
 addInputBand(band) Adds a input coverage band, object of class GSInputCoverageBand
 delInputBand(band) Removes a input coverage band, object of class GSInputCoverageBand

Super class

[geosapi::GSRESTResource](#) -> GSCoverageBand

Public fields

inputCoverageBands list of input coverage bands
 definition coverage band definition
 index coverage band index
 compositionType coverage band composition type

Methods**Public methods:**

- [GSCoverageBand\\$new\(\)](#)
- [GSCoverageBand\\$decode\(\)](#)
- [GSCoverageBand\\$setName\(\)](#)
- [GSCoverageBand\\$setDefinition\(\)](#)
- [GSCoverageBand\\$setIndex\(\)](#)
- [GSCoverageBand\\$setCompositionType\(\)](#)
- [GSCoverageBand\\$addInputBand\(\)](#)
- [GSCoverageBand\\$delInputBand\(\)](#)
- [GSCoverageBand\\$clone\(\)](#)

Method new(): Initializes a [GSCoverageBand](#)

Usage:

GSCoverageBand\$new(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method decode(): Decodes from XML

Usage:

GSCoverageBand\$decode(xml)

Arguments:

xml object of class [xml_node-class](#)

Method setName(): Set name

Usage:

GSCoverageBand\$setName(name)

Arguments:

name name

Method setDefinition(): Set definition

Usage:

GSCoverageBand\$setDefinition(definition)

Arguments:

definition definition

Method setIndex(): Set index

Usage:

GSCoverageBand\$setIndex(index)

Arguments:

index index

Method setCompositionType(): Set composition type

Usage:

GSCoverageBand\$setCompositionType(compositionType)

Arguments:

compositionType composition type

Method addInputBand(): Adds an input band

Usage:

GSCoverageBand\$addInputBand(band)

Arguments:

band object of class [GSInputCoverageBand](#)

Returns: TRUE if added, FALSE otherwise

Method delInputBand(): Deletes an input band

Usage:

GSCoverageBand\$delInputBand(band)

Arguments:

band object of class [GSInputCoverageBand](#)

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSCoverageBand\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSCoverageBand$new()
```

GSCoverageStoreManager

Geoserver REST API CoverageStore Manager

Description

Geoserver REST API CoverageStore Manager

Geoserver REST API CoverageStore Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing GeoServer CoverageStores (i.e. stores of coverage data)

Super class

[geosapi : GManager](#) -> GSCoverageStoreManager

Methods**Public methods:**

- [GSCoverageStoreManager\\$getCoverageStores\(\)](#)
- [GSCoverageStoreManager\\$getCoverageStoreNames\(\)](#)
- [GSCoverageStoreManager\\$getCoverageStore\(\)](#)
- [GSCoverageStoreManager\\$createCoverageStore\(\)](#)
- [GSCoverageStoreManager\\$updateCoverageStore\(\)](#)
- [GSCoverageStoreManager\\$deleteCoverageStore\(\)](#)
- [GSCoverageStoreManager\\$getCoverages\(\)](#)
- [GSCoverageStoreManager\\$getCoverageNames\(\)](#)
- [GSCoverageStoreManager\\$getCoverage\(\)](#)
- [GSCoverageStoreManager\\$createCoverage\(\)](#)
- [GSCoverageStoreManager\\$updateCoverage\(\)](#)

- [GSCoverageStoreManager\\$deleteCoverage\(\)](#)
- [GSCoverageStoreManager\\$uploadCoverage\(\)](#)
- [GSCoverageStoreManager\\$uploadGeoTIFF\(\)](#)
- [GSCoverageStoreManager\\$uploadWorldImage\(\)](#)
- [GSCoverageStoreManager\\$uploadArcGrid\(\)](#)
- [GSCoverageStoreManager\\$uploadImageMosaic\(\)](#)
- [GSCoverageStoreManager\\$clone\(\)](#)

Method [getCoverageStores\(\)](#): Get the list of available coverage stores. Returns an object of class [list](#) giving items of class [GSAbstractCoverageStore](#)

Usage:

```
GSCoverageStoreManager$getCoverageStores(ws)
```

Arguments:

ws workspace name

Returns: the list of coverage stores

Method [getCoverageStoreNames\(\)](#): Get the list of available coverage store names. Returns an vector of class [character](#)

Usage:

```
GSCoverageStoreManager$getCoverageStoreNames(ws)
```

Arguments:

ws workspace name

Returns: the list of coverage store names, as [character](#)

Method [getCoverageStore\(\)](#): Get an object of class [GSAbstractDataStore](#) given a workspace and coverage store names.

Usage:

```
GSCoverageStoreManager$getCoverageStore(ws, cs)
```

Arguments:

ws workspace name

cs coverage store name

Returns: the coverage store

Method [createCoverageStore\(\)](#): Creates a new coverage store given a workspace, coverage store name. Abstract method used in below format-specific methods to create coverage stores.

Usage:

```
GSCoverageStoreManager$createCoverageStore(ws, coverageStore)
```

Arguments:

ws workspace name

coverageStore coverage store object

Returns: TRUE if created, FALSE otherwise

Method updateCoverageStore(): Updates a coverage store given a workspace, coverage store name. Abstract method used in below format-specific methods to create coverage stores.

Usage:

```
GSCoverageStoreManager$updateCoverageStore(ws, coverageStore)
```

Arguments:

ws workspace name

coverageStore coverage store object

Returns: TRUE if updated, FALSE otherwise

Method deleteCoverageStore(): Deletes a coverage store given a workspace and an object of class [GSAbstractCoverageStore](#). By default, the option recurse is set to FALSE, ie datastore layers are not removed. To remove all coverage store layers, set this option to TRUE. The purge parameter is used to customize the delete of files on disk (in case the underlying reader implements a delete method). It can take one of the three values: none, metadata, all. For more details see https://docs.geoserver.org/main/en/user/rest/api/coveragelayers/#rest_api_coveragelayers_purge

Usage:

```
GSCoverageStoreManager$deleteCoverageStore(  
  ws,  
  cs,  
  recurse = FALSE,  
  purge = NULL  
)
```

Arguments:

ws workspace name

cs coverage store name

recurse recurse

purge purge

Returns: TRUE if deleted, FALSE otherwise

Method getCoverages(): Get the list of available coverages for given workspace and coverage store. Returns an object of class list giving items of class [GSCoverage](#)

Usage:

```
GSCoverageStoreManager$getCoverages(ws, cs)
```

Arguments:

ws workspace name

cs coverage store name

Returns: the list of [GSCoverage](#)

Method getCoverageNames(): Get the list of available coverage names for given workspace and coverage store. Returns an object of class list giving items of class [GSCoverage](#)

Usage:

```
GSCoverageStoreManager$getCoverageNames(ws, cs)
```

Arguments:

ws workspace name
cs coverage store name

Returns: the list of coverage names

Method `getCoverage()`: Get coverage

Usage:

`GSCoverageStoreManager$getCoverage(ws, cs, cv)`

Arguments:

ws workspace name
cs coverage store name
cv coverage name

Method `createCoverage()`: Creates a new coverage given a workspace, coverage store names and an object of class [GSCoverage](#)

Usage:

`GSCoverageStoreManager$createCoverage(ws, cs, coverage)`

Arguments:

ws workspace name
cs coverage store name
coverage object of class [GSCoverage](#)

Returns: TRUE if created, FALSE otherwise

Method `updateCoverage()`: Updates a coverage given a workspace, coverage store names and an object of class [GSCoverage](#)

Usage:

`GSCoverageStoreManager$updateCoverage(ws, cs, coverage)`

Arguments:

ws workspace name
cs coverage store name
coverage object of class [GSCoverage](#)

Returns: TRUE if updated, FALSE otherwise

Method `deleteCoverage()`: Deletes a coverage given a workspace, coverage store names, and an object of class [GSCoverage](#). By default, the option `recurse` is set to `FALSE`, ie coverage layers are not removed.

Usage:

`GSCoverageStoreManager$deleteCoverage(ws, cs, cv, recurse = FALSE)`

Arguments:

ws workspace name
cs coverage store name
cv coverage name

recurse recurse

Method uploadCoverage(): Abstract method to upload a coverage file targeting a workspace (ws) and datastore (cs). The extension corresponds to the format/type of coverage to be uploaded (among values 'geotiff', 'worldimage', 'arcgrid', or 'imagemosaic'). The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSCoverageStoreManager$uploadCoverage(
    ws,
    cs,
    endpoint = "file",
    extension,
    filename,
    configure = "first",
    update = "append",
    contentType
)
```

Arguments:

ws workspace name
 cs coverage store name
 endpoint endpoint. Default is "file"
 extension extension
 filename filename
 configure configure. Default is "first"
 update update. Default is "append"
 contentType content type

Returns: TRUE if uploaded, FALSE otherwise

Method uploadGeoTIFF(): Uploads a GeoTIFF file targeting a workspace (ws) and datastore (cs). The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the GeoTIFF file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSCoverageStoreManager$uploadGeoTIFF(
    ws,
    cs,
    endpoint = "file",
    filename,
    configure = "first",
```

```

        update = "append"
    )

```

Arguments:

ws workspace name
 cs coverage store name
 endpoint endpoint. Default is "file"
 filename filename
 configure configure. Default is "first"
 update update. Default is "append"

Returns: TRUE if uploaded, FALSE otherwise

Method uploadWorldImage(): Uploads a WorldImage file targeting a workspace (ws) and datastore (cs). The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the zipped file to upload and set for the newly created datastore. It is assumed the zip archive contains the .prj file to set the SRS. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```

GSCoverageStoreManager$uploadWorldImage(
  ws,
  cs,
  endpoint = "file",
  filename,
  configure = "first",
  update = "append"
)

```

Arguments:

ws workspace name
 cs coverage store name
 endpoint endpoint. Default is "file"
 filename filename
 configure configure. Default is "first"
 update update. Default is "append"

Returns: TRUE if uploaded, FALSE otherwise

Method uploadArcGrid(): Uploads an ArcGrid file targeting a workspace (ws) and datastore (cs). The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the ArcGrid file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSCoverageStoreManager$uploadArcGrid(  
    ws,  
    cs,  
    endpoint = "file",  
    filename,  
    configure = "first",  
    update = "append"  
)
```

Arguments:

ws workspace name
cs coverage store name
endpoint endpoint. Default is "file"
filename filename
configure configure. Default is "first"
update update. Default is "append"

Returns: TRUE if uploaded, FALSE otherwise

Method uploadImageMosaic(): Uploads an ImageMosaic file targeting a workspace (ws) and datastore (cs). The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the ImageMosaic file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSCoverageStoreManager$uploadImageMosaic(  
    ws,  
    cs,  
    endpoint = "file",  
    filename,  
    configure = "first",  
    update = "append"  
)
```

Arguments:

ws workspace name
cs coverage store name
endpoint endpoint. Default is "file"
filename filename
configure configure. Default is "first"
update update. Default is "append"

Returns: TRUE if uploaded, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSCoverageStoreManager$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  GSCoverageStoreManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)
```

GSCoverageView

Geoserver REST API GSCoverageView

Description

Geoserver REST API GSCoverageView

Geoserver REST API GSCoverageView

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer coverage view

Super class

[geosapi::GSRESTResource](#) -> GSCoverageView

Public fields

name name

envelopeCompositionType envelope composition type

selectedResolution selected resolution

selectedResolutionIndex selected resolution index

coverageBands coverage bands

Methods

Public methods:

- [GSCoverageView\\$new\(\)](#)
- [GSCoverageView\\$decode\(\)](#)
- [GSCoverageView\\$setName\(\)](#)
- [GSCoverageView\\$setEnvelopeCompositionType\(\)](#)
- [GSCoverageView\\$setSelectedResolution\(\)](#)
- [GSCoverageView\\$setSelectedResolutionIndex\(\)](#)
- [GSCoverageView\\$addBand\(\)](#)
- [GSCoverageView\\$delBand\(\)](#)
- [GSCoverageView\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSCoverageView](#)

Usage:

```
GSCoverageView$new(xml = NULL)
```

Arguments:

xml object of class [xml_node-class](#)

Method [decode\(\)](#): Decodes from XML

Usage:

```
GSCoverageView$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method [setName\(\)](#): Set name

Usage:

```
GSCoverageView$setName(name)
```

Arguments:

name name

Method [setEnvelopeCompositionType\(\)](#): Sets the envelope composition type. Type of Envelope Composition, used to expose the bounding box of the CoverageView, either 'UNION' or 'INTERSECTION'.

Usage:

```
GSCoverageView$setEnvelopeCompositionType(envelopeCompositionType)
```

Arguments:

envelopeCompositionType envelope composition type

Method [setSelectedResolution\(\)](#): Set selected resolution

Usage:

```
GSCoverageView$setSelectedResolution(selectedResolution)
```

Arguments:

selectedResolution selected resolution

Method setSelectedResolutionIndex(): Set selected resolution index

Usage:

GSCoverageView\$setSelectedResolutionIndex(selectedResolutionIndex)

Arguments:

selectedResolutionIndex selected resolution index

Method addBand(): Adds band

Usage:

GSCoverageView\$addBand(band)

Arguments:

band object of class [GSCoverageBand](#)

Returns: TRUE if added, FALSE otherwise

Method delBand(): Deletes band

Usage:

GSCoverageView\$delBand(band)

Arguments:

band object of class [GSCoverageBand](#)

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSCoverageView\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSCoverageView$new()
```

GSDataStoreManager	<i>Geoserver REST API DataStore Manager</i>
--------------------	---

Description

Geoserver REST API DataStore Manager

Geoserver REST API DataStore Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing GeoServer DataStores (i.e. stores of vector data)

Super class

[geosapi::GManager](#) -> GSDataStoreManager

Methods**Public methods:**

- [GSDataStoreManager\\$getDataStores\(\)](#)
- [GSDataStoreManager\\$getDataStoreNames\(\)](#)
- [GSDataStoreManager\\$getDataStore\(\)](#)
- [GSDataStoreManager\\$createDataStore\(\)](#)
- [GSDataStoreManager\\$updateDataStore\(\)](#)
- [GSDataStoreManager\\$deleteDataStore\(\)](#)
- [GSDataStoreManager\\$getFeatureTypes\(\)](#)
- [GSDataStoreManager\\$getFeatureTypeNames\(\)](#)
- [GSDataStoreManager\\$getFeatureType\(\)](#)
- [GSDataStoreManager\\$createFeatureType\(\)](#)
- [GSDataStoreManager\\$updateFeatureType\(\)](#)
- [GSDataStoreManager\\$deleteFeatureType\(\)](#)
- [GSDataStoreManager\\$publishLayer\(\)](#)
- [GSDataStoreManager\\$unpublishLayer\(\)](#)
- [GSDataStoreManager\\$uploadData\(\)](#)
- [GSDataStoreManager\\$uploadShapefile\(\)](#)
- [GSDataStoreManager\\$uploadProperties\(\)](#)
- [GSDataStoreManager\\$uploadH2\(\)](#)
- [GSDataStoreManager\\$uploadSpatialite\(\)](#)
- [GSDataStoreManager\\$uploadAppschema\(\)](#)
- [GSDataStoreManager\\$uploadGeoPackage\(\)](#)

- [GSDataStoreManager\\$clone\(\)](#)

Method `getDataStores()`: Get the list of available dataStores.

Usage:

`GSDataStoreManager$getDataStores(ws)`

Arguments:

`ws` workspace name

Returns: an object of class `list` giving items of class [GSAbstractDataStore](#)

Method `getDataStoreNames()`: Get the list of available dataStore names.

Usage:

`GSDataStoreManager$getDataStoreNames(ws)`

Arguments:

`ws` workspace name

Returns: a vector of class `character`

Method `getDataStore()`: Get an object of class [GSAbstractDataStore](#) given a workspace and datastore names.

Usage:

`GSDataStoreManager$getDataStore(ws, ds)`

Arguments:

`ws` workspace name

`ds` datastore name

Returns: the datastore

Method `createDataStore()`: Creates a datastore given a workspace and an object of class [GSAbstractDataStore](#).

Usage:

`GSDataStoreManager$createDataStore(ws, dataStore)`

Arguments:

`ws` workspace name

`dataStore` datastore object of class [GSAbstractDataStore](#)

Returns: `TRUE` if created, `FALSE` otherwise

Method `updateDataStore()`: Updates a datastore given a workspace and an object of class [GSAbstractDataStore](#).

Usage:

`GSDataStoreManager$updateDataStore(ws, dataStore)`

Arguments:

`ws` workspace name

`dataStore` datastore object of class [GSAbstractDataStore](#)

Returns: `TRUE` if updated, `FALSE` otherwise

Method deleteDataStore(): Deletes a datastore given workspace and datastore names. By default, the option recurse is set to FALSE, ie datastore layers are not removed. To remove all datastore layers, set this option to TRUE.

Usage:

```
GSDataStoreManager$deleteDataStore(ws, ds, recurse = FALSE)
```

Arguments:

ws workspace name

ds datastore name

recurse recurse

Returns: TRUE if deleted, FALSE otherwise

Method getFeatureTypes(): Get the list of available feature types for given workspace and datastore.

Usage:

```
GSDataStoreManager$getFeatureTypes(ws, ds, list = "configured")
```

Arguments:

ws workspace name

ds datastore name

list list type value, among "configured", "available", "available_with_geom", "all"

Returns: an object of class list giving items of class [GSFeatureType](#)

Method getFeatureTypeNames(): Get the list of available feature type names for given workspace and datastore.

Usage:

```
GSDataStoreManager$getFeatureTypeNames(ws, ds)
```

Arguments:

ws workspace name

ds datastore name

Returns: a vector of classcharacter

Method getFeatureType(): Get an object of class [GSFeatureType](#) given a workspace, datastore and feature type names.

Usage:

```
GSDataStoreManager$getFeatureType(ws, ds, ft)
```

Arguments:

ws workspace name

ds datastore name

ft feature type name

Returns: an object of class [GSFeatureType](#)

Method createFeatureType(): Creates a new featureType given a workspace, datastore names and an object of class [GSFeatureType](#)

Usage:

GSDataStoreManager#createFeatureType(ws, ds, featureType)

Arguments:

ws workspace name

ds datastore name

featureType feature type

Returns: TRUE if created, FALSE otherwise

Method updateFeatureType(): Updates a featureType given a workspace, datastore names and an object of class [GSFeatureType](#)

Usage:

GSDataStoreManager\$updateFeatureType(ws, ds, featureType)

Arguments:

ws workspace name

ds datastore name

featureType feature type

Returns: TRUE if updated, FALSE otherwise

Method deleteFeatureType(): Deletes a featureType given a workspace, datastore names, and an object of class [GSFeatureType](#). By default, the option recurse is set to FALSE, ie datastore layers are not removed.

Usage:

GSDataStoreManager\$deleteFeatureType(ws, ds, ft, recurse = FALSE)

Arguments:

ws workspace name

ds datastore name

ft feature type name

recurse recurse

Returns: TRUE if deleted, FALSE otherwise

Method publishLayer(): Publish a feature type/layer pair given a workspace and datastore. The name 'layer' here encompasses both [GSFeatureType](#) and [GSLayer](#) resources.

Usage:

GSDataStoreManager\$publishLayer(ws, ds, featureType, layer)

Arguments:

ws workspace name

ds datastore name

featureType object of class [GSFeatureType](#)

layer object of class [GSLayer](#)

Returns: TRUE if published, FALSE otherwise

Method unpublishLayer(): Unpublish a feature type/layer pair given a workspace and datastore. The name 'layer' here encompasses both [GSFeatureType](#) and [GSLayer](#) resources.

Usage:

```
GSDataStoreManager$unpublishLayer(ws, ds, lyr)
```

Arguments:

ws workspace name

ds datastore name

lyr layer name

Returns: TRUE if published, FALSE otherwise

Method `uploadData()`: Uploads features data. The extension corresponds to the format/type of features to be uploaded among "shp", "spatialite", "h2", "gpkg". The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSDataStoreManager$uploadData(
  ws,
  ds,
  endpoint = "file",
  extension,
  configure = "first",
  update = "append",
  filename,
  charset,
  contentType
)
```

Arguments:

ws workspace name

ds datastore name

endpoint endpoint

extension extension

configure configure strategy among values: "first" or "none"

update update strategy, among values: "append", "overwrite"

filename file name of the resource to upload

charset charset

contentType content type

Returns: TRUE if uploaded, FALSE otherwise

Method `uploadShapefile()`: Uploads zipped shapefile. The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```

GSDataStoreManager$uploadShapefile(
  ws,
  ds,
  endpoint = "file",
  configure = "first",
  update = "append",
  filename,
  charset = "UTF-8"
)

```

Arguments:

ws workspace name
 ds datastore name
 endpoint endpoint
 configure configure strategy among values: "first" or "none"
 update update strategy, among values: "append", "overwrite"
 filename file name of the resource to upload
 charset charset

Returns: TRUE if uploaded, FALSE otherwise

Method `uploadProperties()`: Uploads properties. The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```

GSDataStoreManager$uploadProperties(
  ws,
  ds,
  endpoint = "file",
  configure = "first",
  update = "append",
  filename,
  charset = "UTF-8"
)

```

Arguments:

ws workspace name
 ds datastore name
 endpoint endpoint
 configure configure strategy among values: "first" or "none"
 update update strategy, among values: "append", "overwrite"
 filename file name of the resource to upload
 charset charset

Returns: TRUE if uploaded, FALSE otherwise

Method uploadH2(): Uploads H2 database. The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSDataStoreManager$uploadH2(  
  ws,  
  ds,  
  endpoint = "file",  
  configure = "first",  
  update = "append",  
  filename,  
  charset = "UTF-8"  
)
```

Arguments:

ws workspace name

ds datastore name

endpoint endpoint

configure configure strategy among values: "first" or "none"

update update strategy, among values: "append", "overwrite"

filename file name of the resource to upload

charset charset

Returns: TRUE if uploaded, FALSE otherwise

Method uploadSpatialite(): Uploads spatialite file. The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSDataStoreManager$uploadSpatialite(  
  ws,  
  ds,  
  endpoint = "file",  
  configure = "first",  
  update = "append",  
  filename,  
  charset = "UTF-8"  
)
```

Arguments:

ws workspace name

ds datastore name
 endpoint endpoint
 configure configure strategy among values: "first" or "none"
 update update strategy, among values: "append", "overwrite"
 filename file name of the resource to upload
 charset charset

Returns: TRUE if uploaded, FALSE otherwise

Method uploadAppschema(): Uploads App schema. The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSDataStoreManager$uploadAppschema(
  ws,
  ds,
  endpoint = "file",
  configure = "first",
  update = "append",
  filename,
  charset = "UTF-8"
)
```

Arguments:

ws workspace name
 ds datastore name
 endpoint endpoint
 configure configure strategy among values: "first" or "none"
 update update strategy, among values: "append", "overwrite"
 filename file name of the resource to upload
 charset charset

Returns: TRUE if uploaded, FALSE otherwise

Method uploadGeoPackage(): Uploads GeoPackage. The endpoint takes a value among "file" (default), "url" or "external". The filename is the name of the coverage file to upload and set for the newly created datastore. The configure parameter can take a value among values "none" (indicates to configure only the datastore but no layer configuration) or "first" (configure both datastore and layer). The update defines the strategy for the upload: "append" (default value) for the first upload, "overwrite" in case the file should be overwritten.

Usage:

```
GSDataStoreManager$uploadGeoPackage(
  ws,
  ds,
  endpoint = "file",
```

```

        configure = "first",
        update = "append",
        filename,
        charset = "UTF-8"
    )

```

Arguments:

ws workspace name

ds datastore name

endpoint endpoint

configure configure strategy among values: "first" or "none"

update update strategy, among values: "append", "overwrite"

filename file name of the resource to upload

charset charset

Returns: TRUE if uploaded, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSDataStoreManager$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```

## Not run:
GSDataStoreManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)

```

GSDimension

A GeoServer dimension

Description

This class models a GeoServer resource dimension.

Format

[R6Class](#) object.

Details

Geoserver REST API Dimension

Value

Object of [R6Class](#) for modelling a GeoServer dimension

Super class

[geosapi::GSRESTResource](#) -> GSDimension

Public fields

enabled true/false

presentation dimension presentation

resolution dimension resolution

units dimension units

unitSymbol dimension unitSymbol

Methods**Public methods:**

- [GSDimension\\$new\(\)](#)
- [GSDimension\\$decode\(\)](#)
- [GSDimension\\$setEnabled\(\)](#)
- [GSDimension\\$setPresentation\(\)](#)
- [GSDimension\\$setUnit\(\)](#)
- [GSDimension\\$setUnitSymbol\(\)](#)
- [GSDimension\\$clone\(\)](#)

Method new(): Initializes an object of class [GSDimension](#)

Usage:

[GSDimension\\$new](#)(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method decode(): Decodes from XML

Usage:

[GSDimension\\$decode](#)(xml)

Arguments:

xml object of class [xml_node-class](#)

Method setEnabled(): Set enabled

Usage:

```
GSDimension$setEnabled(enabled)
```

Arguments:

enabled enabled

Method setPresentation(): Set presentation

Usage:

```
GSDimension$setPresentation(presentation, interval = NULL)
```

Arguments:

presentation presentation. Possible values: "LIST", "CONTINUOUS_INTERVAL", "DIS-CRETE_INTERVAL"

interval interval

Method setUnit(): Set unit

Usage:

```
GSDimension$setUnit(unit)
```

Arguments:

unit unit

Method setUnitSymbol(): Set unit symbol

Usage:

```
GSDimension$setUnitSymbol(unitSymbol)
```

Arguments:

unitSymbol unit symbol

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSDimension$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
dim <- GSDimension$new()
```

GSFeatureDimension	<i>A GeoServer dimension</i>
--------------------	------------------------------

Description

This class models a GeoServer feature dimension.

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer feature dimension

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSDimension](#) -> GSFeatureDimension

Public fields

attribute attribute
endAttribute end attribute

Methods**Public methods:**

- [GSFeatureDimension\\$new\(\)](#)
- [GSFeatureDimension\\$decode\(\)](#)
- [GSFeatureDimension\\$setAttribute\(\)](#)
- [GSFeatureDimension\\$setEndAttribute\(\)](#)
- [GSFeatureDimension\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSFeatureDimension](#)

Usage:

[GSFeatureDimension\\$new](#)(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method [decode\(\)](#): Decodes from XML

Usage:

[GSFeatureDimension\\$decode](#)(xml)

Arguments:

xml object of class [xml_node-class](#)

Method `setAttribute()`: Set attribute

Usage:

```
GSFeatureDimension$setAttribute(attribute)
```

Arguments:

attribute attribute

Method `setEndAttribute()`: Set end attribute

Usage:

```
GSFeatureDimension$setEndAttribute(endAttribute)
```

Arguments:

endAttribute end attribute

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSFeatureDimension$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
dim <- GSFeatureDimension$new()
```

GSFeatureType

A GeoServer feature type

Description

This class models a GeoServer feature type. This class is to be used for manipulating representations of vector data with GeoServer.

Format

[R6Class](#) object.

Details

Geoserver REST API Resource

Value

Object of [R6Class](#) for modelling a GeoServer feature type

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSResource](#) -> [GSFeatureType](#)

Public fields

cqlFilter CQL filter

Methods**Public methods:**

- [GSFeatureType\\$new\(\)](#)
- [GSFeatureType\\$decode\(\)](#)
- [GSFeatureType\\$setCqlFilter\(\)](#)
- [GSFeatureType\\$setVirtualTable\(\)](#)
- [GSFeatureType\\$delVirtualTable\(\)](#)
- [GSFeatureType\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSFeatureType](#)

Usage:

[GSFeatureType\\$new](#)(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method [decode\(\)](#): Decodes from XML

Usage:

[GSFeatureType\\$decode](#)(xml)

Arguments:

xml object of class [xml_node-class](#)

Method [setCqlFilter\(\)](#): Set CQL filter

Usage:

[GSFeatureType\\$setCqlFilter](#)(cqlFilter)

Arguments:

cqlFilter CQL filter

Method [setVirtualTable\(\)](#): Set virtual table

Usage:

[GSFeatureType\\$setVirtualTable](#)(vt)

Arguments:

vt object of class [GSVirtualTable](#)

Returns: TRUE if set/added, FALSE otherwise

Method [delVirtualTable\(\)](#): Deletes virtual table

Usage:

```
GSFeatureType$delVirtualTable()
```

Arguments:

vt object of class [GSVirtualTable](#)

Returns: TRUE if deleted, FALSE otherwise

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSFeatureType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
ft <- GSFeatureType$new()
```

GSGeoPackageDataStore *Geoserver REST API GeoPackageDataStore*

Description

Geoserver REST API GeoPackageDataStore

Geoserver REST API GeoPackageDataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer GeoPackage dataStore

Super classes

```
geosapi::GSRESTResource -> geosapi::GSAbstractStore -> geosapi::GSAbstractDataStore
-> geosapi::GSAbstractDBDataStore -> GSGeoPackageDataStore
```

Methods

Public methods:

- [GSGeoPackageDataStore\\$new\(\)](#)
- [GSGeoPackageDataStore\\$clone\(\)](#)

Method `new()`: initializes an GeoPackage data store

Usage:

```
GSGeoPackageDataStore$new(  
  xml = NULL,  
  name = NULL,  
  description = "",  
  enabled = TRUE,  
  database = NULL  
)
```

Arguments:

`xml` an object of class [xml_node-class](#) to create object from XML
`name` coverage store name
`description` coverage store description
`enabled` whether the store should be enabled or not. Default is TRUE
`database` database

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSGeoPackageDataStore$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
ds <- GSGeoPackageDataStore$new(  
  name = "ds", description = "des",  
  enabled = TRUE, database = NULL  
)
```

GSGeoTIFFCoverageStore

Geoserver REST API GeoTIFF CoverageStore

Description

Geoserver REST API GeoTIFF CoverageStore

Geoserver REST API GeoTIFF CoverageStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer GeoTIFF CoverageStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> [geosapi::GSAbstractCoverageStore](#)
 -> GSGeoTIFFCoverageStore

Public fields

url url

Methods**Public methods:**

- [GSGeoTIFFCoverageStore\\$new\(\)](#)
- [GSGeoTIFFCoverageStore\\$clone\(\)](#)

Method [new\(\)](#): Initializes an GeoTIFF coverage store

Usage:

```
GSGeoTIFFCoverageStore$new(
  xml = NULL,
  name = NULL,
  description = "",
  enabled = TRUE,
  url = NULL
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML

name coverage store name

description coverage store description

enabled whether the store should be enabled or not. Default is TRUE
url url

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSGeoTIFFCoverageStore$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSImageMosaicCoverageStore

Geoserver REST API ImageMosaicCoverageStore

Description

Geoserver REST API ImageMosaicCoverageStore

Geoserver REST API ImageMosaicCoverageStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer ImageMosaic CoverageStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> [geosapi::GSAbstractCoverageStore](#)
-> GSImageMosaicCoverageStore

Public fields

url url

Methods**Public methods:**

- [GSImageMosaicCoverageStore\\$new\(\)](#)
- [GSImageMosaicCoverageStore\\$clone\(\)](#)

Method `new()`: Initializes an Image Mosaic coverage store

Usage:

```
GSImageMosaicCoverageStore$new(
  xml = NULL,
  name = NULL,
  description = "",
  enabled = TRUE,
  url = NULL
)
```

Arguments:

`xml` an object of class [xml_node-class](#) to create object from XML
`name` coverage store name
`description` coverage store description
`enabled` whether the store should be enabled or not. Default is TRUE
`url` url

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSImageMosaicCoverageStore$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSInputCoverageBand *Geoserver REST API GSInputCoverageBand*

Description

Geoserver REST API GSInputCoverageBand

Geoserver REST API GSInputCoverageBand

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer input coverage band

Super class

[geosapi : GSRESTResource](#) -> GSInputCoverageBand

Public fields

coverageName coverage name

band band

Methods**Public methods:**

- [GSInputCoverageBand\\$new\(\)](#)
- [GSInputCoverageBand\\$decode\(\)](#)
- [GSInputCoverageBand\\$setCoverageName\(\)](#)
- [GSInputCoverageBand\\$setBand\(\)](#)
- [GSInputCoverageBand\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSInputCoverageBand](#)

Usage:

[GSInputCoverageBand\\$new](#)(xml = NULL, coverageName = NULL, band = NULL)

Arguments:

xml object of class [xml_node-class](#)

coverageName coverage name

band band name

Method [decode\(\)](#): Decodes from XML

Usage:

[GSInputCoverageBand\\$decode](#)(xml)

Arguments:

xml object of class [xml_node-class](#)

Method [setCoverageName\(\)](#): Set coverage name

Usage:

[GSInputCoverageBand\\$setCoverageName](#)(coverageName)

Arguments:

coverageName coverage name

Method [setBand\(\)](#): Set band

Usage:

[GSInputCoverageBand\\$setBand](#)(band)

Arguments:

band band

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSInputCoverageBand\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSInputCoverageBand$new()
```

GSLayer

A GeoServer layer resource

Description

This class models a GeoServer layer. This class is to be used for published resource (feature type or coverage).

This class models a GeoServer style.

Format

[R6Class](#) object.

[R6Class](#) object.

Details

Geoserver REST API Resource

Geoserver REST API Style

Value

Object of [R6Class](#) for modelling a GeoServer layer

Object of [R6Class](#) for modelling a GeoServer style

Super class

[geosapi::GSRESTResource](#) -> GSLayer

Public fields

full full
name name
path path
defaultStyle default style
styles styles
enabled enabled
queryable queryable
advertised advertised

Methods**Public methods:**

- [GSLayer\\$new\(\)](#)
- [GSLayer\\$decode\(\)](#)
- [GSLayer\\$setName\(\)](#)
- [GSLayer\\$setPath\(\)](#)
- [GSLayer\\$setEnabled\(\)](#)
- [GSLayer\\$setQueryable\(\)](#)
- [GSLayer\\$setAdvertised\(\)](#)
- [GSLayer\\$setDefaultStyle\(\)](#)
- [GSLayer\\$setStyles\(\)](#)
- [GSLayer\\$addStyle\(\)](#)
- [GSLayer\\$delStyle\(\)](#)
- [GSLayer\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSLayer](#)

Usage:

`GSLayer$new(xml = NULL)`

Arguments:

xml object of class [xml_node-class](#)

Method [decode\(\)](#): Decodes from XML

Usage:

`GSLayer$decode(xml)`

Arguments:

xml object of class [xml_node-class](#)

Method [setName\(\)](#): Set name

Usage:

`GSLayer$setName(name)`

Arguments:

name name

Method `setPath()`: Set path

Usage:

`GSLayer$setPath(path)`

Arguments:

path path

Method `setEnabled()`: Set enabled

Usage:

`GSLayer$setEnabled(enabled)`

Arguments:

enabled enabled

Method `setQueryable()`: Set queryable

Usage:

`GSLayer$setQueryable(queryable)`

Arguments:

queryable queryable

Method `setAdvertised()`: Set advertised

Usage:

`GSLayer$setAdvertised(advertised)`

Arguments:

advertised advertised

Method `setDefaultStyle()`: Set default style

Usage:

`GSLayer$setDefaultStyle(style)`

Arguments:

style object o class [GSStyle](#) or character

Method `setStyles()`: Set styles

Usage:

`GSLayer$setStyles(styles)`

Arguments:

styles styles

Method `addStyle()`: Adds style

Usage:

`GSLayer$addStyle(style)`

Arguments:

style style, object o class [GSStyle](#) or character

Returns: TRUE if added, FALSE otherwise

Method delStyle(): Deletes style

Usage:

GSLayer\$delStyle(style)

Arguments:

style style, object o class [GSStyle](#) or character

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSLayer\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Super class

[geosapi::GSRESTResource](#) -> [GSStyle](#)

Public fields

full full

name name

filename filename

Methods

Public methods:

- [GSStyle\\$new\(\)](#)
- [GSStyle\\$decode\(\)](#)
- [GSStyle\\$setName\(\)](#)
- [GSStyle\\$setFilename\(\)](#)
- [GSStyle\\$clone\(\)](#)

Method new(): Initializes a [GSStyle](#)

Usage:

GSStyle\$new(xml = NULL, name = NULL, filename = NULL)

Arguments:

xml an object of class [xml_node-class](#)

name name

filename filename

Method decode(): Decodes from XML

Usage:

```
GSStyle$decode(xml)
```

Arguments:

xml an object of class [xml_node-class](#)

Method setName(): set name

Usage:

```
GSStyle$setName(name)
```

Arguments:

name name

Method setFilename(): Set filename

Usage:

```
GSStyle$setFilename(filename)
```

Arguments:

filename filename

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSStyle$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
lyr <- GSLayer$new()
```

```
lyr <- GSStyle$new()
```

GSLayerGroup

A GeoServer layergroup resource

Description

This class models a GeoServer layer group. This class is to be used for clustering layers into a group.

Format

[R6Class](#) object.

Details

Geoserver REST API LayerGroup

Value

Object of [R6Class](#) for modelling a GeoServer layergroup

Super class

[geosapi::GSRESTResource](#) -> GSLayerGroup

Public fields

full full
name name
mode mode
title title
abstractTxt abstract
workspace workspace
publishables publishables
styles styles
metadataLinks metadata links
bounds bounds

Methods**Public methods:**

- [GSLayerGroup\\$new\(\)](#)
- [GSLayerGroup\\$decode\(\)](#)
- [GSLayerGroup\\$setName\(\)](#)
- [GSLayerGroup\\$setMode\(\)](#)
- [GSLayerGroup\\$setTitle\(\)](#)
- [GSLayerGroup\\$setAbstract\(\)](#)
- [GSLayerGroup\\$setWorkspace\(\)](#)
- [GSLayerGroup\\$addLayer\(\)](#)
- [GSLayerGroup\\$addLayerGroup\(\)](#)
- [GSLayerGroup\\$addPublishable\(\)](#)
- [GSLayerGroup\\$setStyles\(\)](#)
- [GSLayerGroup\\$addStyle\(\)](#)
- [GSLayerGroup\\$setMetadataLinks\(\)](#)
- [GSLayerGroup\\$addMetadataLink\(\)](#)
- [GSLayerGroup\\$deleteMetadataLink\(\)](#)
- [GSLayerGroup\\$setBounds\(\)](#)

- [GSLayerGroup\\$clone\(\)](#)

Method new(): Initializes an object of class [GSLayerGroup](#)

Usage:

GSLayerGroup\$new(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method decode(): Decodes from XML

Usage:

GSLayerGroup\$decode(xml)

Arguments:

xml object of class [xml_node-class](#)

Method setName(): Set name

Usage:

GSLayerGroup\$setName(name)

Arguments:

name name

Method setMode(): Set mode

Usage:

GSLayerGroup\$setMode(mode)

Arguments:

mode a mode value among "SINGLE", "NAMED", "CONTAINER", "EO"

Method setTitle(): Set title

Usage:

GSLayerGroup\$setTitle(title)

Arguments:

title title

Method setAbstract(): Set abstract

Usage:

GSLayerGroup\$setAbstract(abstract)

Arguments:

abstract abstract

Method setWorkspace(): Set workspace

Usage:

GSLayerGroup\$setWorkspace(workspace)

Arguments:

workspace workspace name, object of class [GSWorkspace](#) or character

Method addLayer(): Adds layer

Usage:

GSLayerGroup\$addLayer(layer, style)

Arguments:

layer layer name

style style name

Method addLayerGroup(): Adds layer group

Usage:

GSLayerGroup\$addLayerGroup(layerGroup)

Arguments:

layerGroup layer group

Method addPublishable(): Adds publishable

Usage:

GSLayerGroup\$addPublishable(publishable)

Arguments:

publishable publishable

Returns: TRUE if added, FALSE otherwise

Method setStyles(): Set styles

Usage:

GSLayerGroup\$setStyles(styles)

Arguments:

styles styles

Method addStyle(): Adds a style

Usage:

GSLayerGroup\$addStyle(style)

Arguments:

style style

Returns: TRUE if added, FALSE otherwise

Method setMetadataLinks(): Set metadata links

Usage:

GSLayerGroup\$setMetadataLinks(metadataLinks)

Arguments:

metadataLinks metadata links

Method addMetadataLink(): Adds metadata link

Usage:

```
GSLayerGroup$addMetadataLink(metadataLink)
```

Arguments:

metadataLink object of class [GSMetadataLink](#)

Returns: TRUE if added, FALSE otherwise

Method deleteMetadataLink(): Deletes metadata link

Usage:

```
GSLayerGroup$deleteMetadataLink(metadataLink)
```

Arguments:

metadataLink object of class [GSMetadataLink](#)

Returns: TRUE if deleted, FALSE otherwise

Method setBounds(): Set bounds

Usage:

```
GSLayerGroup$setBounds(minx, miny, maxx, maxy, bbox = NULL, crs)
```

Arguments:

minx minx

miny miny

maxx maxx

maxy maxy

bbox bbox

crs crs

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSLayerGroup$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
lyr <- GSLayerGroup$new()
```

GSLayerManager

Geoserver REST API Layer Manager

Description

Geoserver REST API Layer Manager

Geoserver REST API Layer Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing GeoServer Layers as results of published feature types or coverages

Super class

[geosapi : GSManager](#) -> GSLayerManager

Methods**Public methods:**

- [GSLayerManager\\$getLayers\(\)](#)
- [GSLayerManager\\$getLayerNames\(\)](#)
- [GSLayerManager\\$getLayer\(\)](#)
- [GSLayerManager\\$createLayer\(\)](#)
- [GSLayerManager\\$updateLayer\(\)](#)
- [GSLayerManager\\$deleteLayer\(\)](#)
- [GSLayerManager\\$getLayerGroups\(\)](#)
- [GSLayerManager\\$getLayerGroupNames\(\)](#)
- [GSLayerManager\\$getLayerGroup\(\)](#)
- [GSLayerManager\\$createLayerGroup\(\)](#)
- [GSLayerManager\\$updateLayerGroup\(\)](#)
- [GSLayerManager\\$deleteLayerGroup\(\)](#)
- [GSLayerManager\\$clone\(\)](#)

Method [getLayers\(\)](#): Get the list of layers.

Usage:

[GSLayerManager\\$getLayers\(\)](#)

Returns: an object of class [list](#) giving items of class [GSLayer](#)

Method [getLayerNames\(\)](#): Get the list of layer names.

Usage:

GSLayerManager\$getLayerNames()

Returns: a vector of class character

Method getLayer(): Get layer by name

Usage:

GSLayerManager\$getLayer(lyr)

Arguments:

lyr layer name

Returns: an object of class [GSLayer](#)

Method createLayer(): Creates a new layer given an object of class [GSLayer](#)

Usage:

GSLayerManager\$createLayer(layer)

Arguments:

layer object of class [GSLayer](#)

Returns: TRUE if created, FALSE otherwise

Method updateLayer(): Updates a layer given an object of class [GSLayer](#)

Usage:

GSLayerManager\$updateLayer(layer)

Arguments:

layer object of class [GSLayer](#)

Returns: TRUE if updated, FALSE otherwise

Method deleteLayer(): Deletes layer given an object of class [GSLayer](#)

Usage:

GSLayerManager\$deleteLayer(lyr)

Arguments:

lyr layer name

Returns: TRUE if deleted, FALSE otherwise

Method getLayerGroups(): Get layer groups

Usage:

GSLayerManager\$getLayerGroups(ws = NULL)

Arguments:

ws workspace name. Optional

Returns: a list of objects of class [GSLayerGroup](#)

Method getLayerGroupNames(): Get layer group names

Usage:

GSLayerManager\$getLayerGroupNames(ws = NULL)

Arguments:

ws workspace name

Returns: a list of layer group names, as vector of class character

Method getLayerGroup(): Get layer group

Usage:

GSLayerManager\$getLayerGroup(lyr, ws = NULL)

Arguments:

lyr lyr

ws workspace name

Returns: an object of class [GSLayerGroup](#)

Method createLayerGroup(): Creates a layer group

Usage:

GSLayerManager\$createLayerGroup(layerGroup, ws = NULL)

Arguments:

layerGroup object of class [GSLayerGroup](#)

ws workspace name. Optional

Returns: TRUE if created, FALSE otherwise

Method updateLayerGroup(): Updates a layer group

Usage:

GSLayerManager\$updateLayerGroup(layerGroup, ws = NULL)

Arguments:

layerGroup object of class [GSLayerGroup](#)

ws workspace name. Optional

Returns: TRUE if updated, FALSE otherwise

Method deleteLayerGroup(): Deletes a layer group

Usage:

GSLayerManager\$deleteLayerGroup(lyr, ws = NULL)

Arguments:

lyr layer group name

ws workspace name. Optional

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSLayerManager\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  GSLayerManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)
```

GSLayerRule

A GeoServer access control list layer rule

Description

This class models a GeoServer access control list layer rule

Format

[R6Class](#) object.

Details

Geoserver REST API Access Control List Layer Rule

Value

Object of [R6Class](#) for modelling a GeoServer access control list layer rule

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSRule](#) -> GSLayerRule

Public fields

roles one or more roles

Methods**Public methods:**

- [GSLayerRule\\$new\(\)](#)
- [GSLayerRule\\$clone\(\)](#)

Method `new()`: Initializes a [GSLayerRule](#)

Usage:

```

GSLayerRule$new(
  xml = NULL,
  ws = NULL,
  lyr,
  permission = c("r", "w", "a"),
  roles
)

```

Arguments:

xml an object of class [xml_node-class](#)

ws the resource workspace. Default is NULL

lyr the target layer to which the access control should be added

permission the rule permission, either r (read), w (write) or a (administer)

roles one or more roles to add for the rule

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSLayerRule$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSManager

Geoserver REST API Manager

Description

Geoserver REST API Manager

Geoserver REST API Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for communication with the REST API of a GeoServer instance.

Public fields

verbose.info if geosapi logs have to be printed

verbose.debug if curl logs have to be printed

loggerType the type of logger

url the Base url of GeoServer

version the version of Geoserver. Handled as GSVersion object

Methods

Public methods:

- [GSManager\\$logger\(\)](#)
- [GSManager\\$INFO\(\)](#)
- [GSManager\\$WARN\(\)](#)
- [GSManager\\$ERROR\(\)](#)
- [GSManager\\$new\(\)](#)
- [GSManager\\$getUrl\(\)](#)
- [GSManager\\$connect\(\)](#)
- [GSManager\\$reload\(\)](#)
- [GSManager\\$getSystemStatus\(\)](#)
- [GSManager\\$monitor\(\)](#)
- [GSManager\\$getClassName\(\)](#)
- [GSManager\\$getWorkspaceManager\(\)](#)
- [GSManager\\$getNamespaceManager\(\)](#)
- [GSManager\\$getDataStoreManager\(\)](#)
- [GSManager\\$getCoverageStoreManager\(\)](#)
- [GSManager\\$getServiceManager\(\)](#)
- [GSManager\\$getStyleManager\(\)](#)
- [GSManager\\$clone\(\)](#)

Method `logger()`: Prints a log message

Usage:

`GSManager$logger(type, text)`

Arguments:

type type of log, "INFO", "WARN", "ERROR"

text text

Method `INFO()`: Prints an INFO log message

Usage:

`GSManager$INFO(text)`

Arguments:

text text

Method `WARN()`: Prints an WARN log message

Usage:

`GSManager$WARN(text)`

Arguments:

text text

Method `ERROR()`: Prints an ERROR log message

Usage:

```
GSManager$ERROR(text)
```

Arguments:

```
text text
```

Method new(): This method is used to instantiate a GSManager with the url of the GeoServer and credentials to authenticate (user/pwd).

By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only geosapi logs, DEBUG: to print geosapi and CURL logs.

The keyring_backend can be set to use a different backend for storing the Geoserver user password with **keyring** (Default value is 'env').

Usage:

```
GSManager$new(url, user, pwd, logger = NULL, keyring_backend = "env")
```

Arguments:

```
url url
```

```
user user
```

```
pwd pwd
```

```
logger logger
```

```
keyring_backend keyring backend. Default is 'env'
```

Method getUrl(): Get URL

Usage:

```
GSManager$getUrl()
```

Returns: the Geoserver URL

Method connect(): Connects to geoServer

Usage:

```
GSManager$connect()
```

Returns: TRUE if connected, raises an error otherwise

Method reload(): Reloads the GeoServer catalog

Usage:

```
GSManager$reload()
```

Returns: TRUE if reloaded, FALSE otherwise

Method getSystemStatus(): Get system status

Usage:

```
GSManager$getSystemStatus()
```

Returns: an object of class data.frame given the date time and metrics value

Method monitor(): Monitors the Geoserver by launching a small shiny monitoring application

Usage:

```
GSManager$monitor(file = NULL, append = FALSE, sleep = 1)
```

Arguments:

file file where to store monitoring results
append whether to append results to existing files
sleep sleeping interval to trigger a system status call

Method `getClassName()`: Get class name

Usage:

`GManager$getClassName()`

Returns: the self class name, as character

Method `getWorkspaceManager()`: Get Workspace manager

Usage:

`GManager$getWorkspaceManager()`

Returns: an object of class [GSWorkspaceManager](#)

Method `getNamespaceManager()`: Get Namespace manager

Usage:

`GManager$getNamespaceManager()`

Returns: an object of class [GSNamespaceManager](#)

Method `getDataStoreManager()`: Get Datastore manager

Usage:

`GManager$getDataStoreManager()`

Returns: an object of class [GSDataStoreManager](#)

Method `getCoverageStoreManager()`: Get Coverage store manager

Usage:

`GManager$getCoverageStoreManager()`

Returns: an object of class [GSCoverageStoreManager](#)

Method `getServiceManager()`: Get service manager

Usage:

`GManager$getServiceManager()`

Returns: an object of class [GSServiceManager](#)

Method `getStyleManager()`: Get style manager

Usage:

`GManager$getStyleManager()`

Returns: an object of class [GSStyleManager](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`GManager$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  GSManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)
```

GSMetadataLink	<i>A GeoServer resource metadataLink</i>
----------------	--

Description

This class models a GeoServer resource metadataLink made of a type (free text e.g. text/xml, text/html), a metadataType (Possible values are ISO19115:2003, FGDC, TC211, 19139, other), and a content: an URL that gives the metadataLink

Format

[R6Class](#) object.

Details

Geoserver REST API Metadatalink

Value

Object of [R6Class](#) for modelling a GeoServer resource metadataLink

Super class

[geosapi:GSRESTResource](#) -> GSMetadataLink

Public fields

type type
metadataType metadata type
content content

Methods

Public methods:

- [GSMetadataLink\\$new\(\)](#)
- [GSMetadataLink\\$decode\(\)](#)
- [GSMetadataLink\\$setType\(\)](#)
- [GSMetadataLink\\$setMetadataType\(\)](#)
- [GSMetadataLink\\$setContent\(\)](#)
- [GSMetadataLink\\$clone\(\)](#)

Method `new()`: Initializes an object of class [GSMetadataLink](#)

Usage:

`GSMetadataLink$new(xml = NULL, type, metadataType, content)`

Arguments:

`xml` object of class [xml_node-class](#)

`type` type

`metadataType` metadata type

`content` content

Method `decode()`: Decodes from XML

Usage:

`GSMetadataLink$decode(xml)`

Arguments:

`xml` object of class [xml_node-class](#)

Method `setType()`: Set type type

Usage:

`GSMetadataLink$setType(type)`

Arguments:

`type` type

Method `setMetadataType()`: Set metadata type

Usage:

`GSMetadataLink$setMetadataType(metadataType)`

Arguments:

`metadataType` metadata type. Supported values: "ISO19115:2003", "FGDC", "TC211", "19139", "other"

Method `setContent()`: Set content

Usage:

`GSMetadataLink$setContent(content)`

Arguments:

`content` content

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSMetadataLink\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSMonitorManager

Geoserver REST API Monitor Manager

Description

Geoserver REST API Monitor Manager

Geoserver REST API Monitor Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for the GeoServer Monitoring extension.

Super class

[geosapi::GSManager](#) -> GSMonitorManager

Methods

Public methods:

- [GSMonitorManager\\$getRequests\(\)](#)
- [GSMonitorManager\\$clone\(\)](#)

Method getRequests(): Get the requests

Usage:

GSMonitorManager\$getRequests(offset = 0)

Arguments:

offset offset

Returns: an object of class data.frame

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSMonitorManager\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:  
  GSMonitorManager$new("http://localhost:8080/geoserver", "admin", "geoserver")  
  
## End(Not run)
```

GSNamespace

Geoserver REST API Namespace

Description

Geoserver REST API Namespace

Geoserver REST API Namespace

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer namespace

Super class

[geosapi::GSRESTResource](#) -> GSNamespace

Public fields

name namespace name

prefix namespace prefix

uri namespace URI

full completeness of the namespace description

Methods**Public methods:**

- [GSNamespace\\$new\(\)](#)
- [GSNamespace\\$decode\(\)](#)
- [GSNamespace\\$clone\(\)](#)

Method `new()`: Initializes an object of class [GSNamespace](#)

Usage:

```
GSNamespace$new(xml = NULL, prefix, uri)
```

Arguments:

```
xml  object of class xml\_node-class
prefix prefix
uri  uri
```

Method `decode()`: Decodes from XML

Usage:

```
GSNamespace$decode(xml)
```

Arguments:

```
xml  object of class xml\_node-class
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSNamespace$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSNamespace$new(prefix = "my_ns", uri = "http://my_ns")
```

GSNamespaceManager

Geoserver REST API Namespace Manager

Description

Geoserver REST API Namespace Manager

Geoserver REST API Namespace Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing the namespaces of a GeoServer instance.

Super class

`geosapi::GManager` -> `GSNamespaceManager`

Methods**Public methods:**

- `GSNamespaceManager$getNamespaces()`
- `GSNamespaceManager$getNamespaceNames()`
- `GSNamespaceManager$getNamespace()`
- `GSNamespaceManager$createNamespace()`
- `GSNamespaceManager$updateNamespace()`
- `GSNamespaceManager$deleteNamespace()`
- `GSNamespaceManager$clone()`

Method `getNamespaces()`: Get the list of available namespace. Re

Usage:

`GSNamespaceManager$getNamespaces()`

Returns: an object of class `list` containing items of class `GSNamespace`

Method `getNamespaceNames()`: Get the list of available namespace names.

Usage:

`GSNamespaceManager$getNamespaceNames()`

Returns: a vector of class `character`

Method `getNamespace()`: Get a `GSNamespace` object given a namespace name.

Usage:

`GSNamespaceManager$getNamespace(ns)`

Arguments:

`ns` namespace

Returns: an object of class `GSNamespace`

Method `createNamespace()`: Creates a GeoServer namespace given a prefix, and an optional URI.

Usage:

`GSNamespaceManager$createNamespace(prefix, uri)`

Arguments:

`prefix` prefix

`uri` uri

Returns: `TRUE` if the namespace has been successfully created, `FALSE` otherwise

Method `updateNamespace()`: Updates a GeoServer namespace given a prefix, and an optional URI.

Usage:

GSNamespaceManager\$updateNamespace(prefix, uri)

Arguments:

prefix prefix

uri uri

Returns: TRUE if the namespace has been successfully updated, FALSE otherwise

Method deleteNamespace(): Deletes a GeoServer namespace given a name.

Usage:

GSNamespaceManager\$deleteNamespace(name, recurse = FALSE)

Arguments:

name name

recurse recurse

Returns: TRUE if the namespace has been successfully deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSNamespaceManager\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
  GSNamespaceManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)
```

GSOracleNGDataStore *Geoserver REST API OracleNGDataStore*

Description

Geoserver REST API OracleNGDataStore

Geoserver REST API OracleNGDataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer OracleNG dataStore

Super classes

```
geosapi::GSRESTResource -> geosapi::GSAbstractStore -> geosapi::GSAbstractDataStore  
-> geosapi::GSAbstractDBDataStore -> GSOracleNGDataStore
```

Methods**Public methods:**

- [GSOracleNGDataStore\\$new\(\)](#)
- [GSOracleNGDataStore\\$clone\(\)](#)

Method `new()`: initializes an Oracle NG data store

Usage:

```
GSOracleNGDataStore$new(  
  xml = NULL,  
  name = NULL,  
  description = "",  
  enabled = TRUE  
)
```

Arguments:

`xml` an object of class [xml_node-class](#) to create object from XML
`name` coverage store name
`description` coverage store description
`enabled` whether the store should be enabled or not. Default is TRUE

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSOracleNGDataStore$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSOracleNGDataStore$new(name = "ds", description = "des", enabled = TRUE)
```

GSPostGISDataStore *Geoserver REST API PostGISDataStore*

Description

Geoserver REST API PostGISDataStore

Geoserver REST API PostGISDataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer PostGIS dataStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> [geosapi::GSAbstractDataStore](#)
-> [geosapi::GSAbstractDBDataStore](#) -> GSPostGISDataStore

Methods**Public methods:**

- [GSPostGISDataStore\\$new\(\)](#)
- [GSPostGISDataStore\\$clone\(\)](#)

Method [new\(\)](#): initializes a PostGIS data store

Usage:

```
GSPostGISDataStore$new(
  xml = NULL,
  name = NULL,
  description = "",
  enabled = TRUE
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML
name coverage store name
description coverage store description
enabled whether the store should be enabled or not. Default is TRUE

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
GSPostGISDataStore$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSPostGISDataStore$new(name = "ds", description = "des", enabled = TRUE)
```

GSPublishable

A GeoServer layer group publishable

Description

This class models a GeoServer layer. This class is to be used internally by **geosapi** for configuring layers or layer groups within an object of class GSLayerGroup

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer layer group publishable

Super class

[geosapi::GSRESTResource](#) -> GSPublishable

Public fields

full full

name name

attr_type type of attribute

Methods**Public methods:**

- [GSPublishable\\$new\(\)](#)
- [GSPublishable\\$decode\(\)](#)
- [GSPublishable\\$setName\(\)](#)
- [GSPublishable\\$setType\(\)](#)
- [GSPublishable\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [GSPublishable](#)

Usage:

```
GSPublishable$new(xml = NULL, name, type)
```

Arguments:

xml an object of class [xml_node-class](#)

name name

type type

Method decode(): Decodes from XML*Usage:*

```
GSPublishable$decode(xml)
```

Arguments:

xml an object of class [xml_node-class](#)

Method setName(): set name*Usage:*

```
GSPublishable$setName(name)
```

Arguments:

name name

Method setType(): Set type*Usage:*

```
GSPublishable$setType(type)
```

Arguments:

type type

Method clone(): The objects of this class are cloneable with this method.*Usage:*

```
GSPublishable$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
publishable <- GSPublishable$new(name = "name", type = "layer")
```

GSResource	<i>A GeoServer abstract resource</i>
------------	--------------------------------------

Description

This class models an abstract GeoServer resource. This class is used internally for modelling instances of class GSFeatureType or GSCoverage

Format

[R6Class](#) object.

Details

Geoserver REST API Resource

Value

Object of [R6Class](#) for modelling a GeoServer resource

Super class

[geosapi:GSRESTResource](#) -> GSResource

Public fields

- full full
- name resource name
- nativeName resource native name
- title resource title
- description resource description
- abstract resource abstract
- keywords resource keywords
- metadataLinks resource metadata links
- nativeCRS resource native CRS
- srs resource srs
- nativeBoundingBox resource lat/lon native bounding box
- latLonBoundingBox resource lat/lon bounding box
- projectionPolicy resource projection policy
- enabled enabled
- metadata metadata

Methods

Public methods:

- [GSResource\\$new\(\)](#)
- [GSResource\\$decode\(\)](#)
- [GSResource\\$setEnabled\(\)](#)
- [GSResource\\$setName\(\)](#)
- [GSResource\\$setNativeName\(\)](#)
- [GSResource\\$setTitle\(\)](#)
- [GSResource\\$setDescription\(\)](#)
- [GSResource\\$setAbstract\(\)](#)
- [GSResource\\$setKeywords\(\)](#)
- [GSResource\\$addKeyword\(\)](#)
- [GSResource\\$delKeyword\(\)](#)
- [GSResource\\$setMetadataLinks\(\)](#)
- [GSResource\\$addMetadataLink\(\)](#)
- [GSResource\\$deleteMetadataLink\(\)](#)
- [GSResource\\$setProjectionPolicy\(\)](#)
- [GSResource\\$setSrs\(\)](#)
- [GSResource\\$setNativeCRS\(\)](#)
- [GSResource\\$setLatLonBoundingBox\(\)](#)
- [GSResource\\$setNativeBoundingBox\(\)](#)
- [GSResource\\$setMetadata\(\)](#)
- [GSResource\\$delMetadata\(\)](#)
- [GSResource\\$setMetadataDimension\(\)](#)
- [GSResource\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [GSResource](#)

Usage:

```
GSResource$new(rootName = NULL, xml = NULL)
```

Arguments:

rootName root name

xml object of class [xml_node-class](#)

Method [decode\(\)](#): Decodes from XML

Usage:

```
GSResource$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method [setEnabled\(\)](#): Set enabled

Usage:

```
GSResource$setEnabled(enabled)
```

Arguments:

enabled enabled

Method setName(): Set name

Usage:

GSResource\$setName(name)

Arguments:

name name

Method setNativeName(): Set native name

Usage:

GSResource\$setNativeName(nativeName)

Arguments:

nativeName native name

Method setTitle(): Set title

Usage:

GSResource\$setTitle(title)

Arguments:

title title

Method setDescription(): Set description

Usage:

GSResource\$setDescription(description)

Arguments:

description description

Method setAbstract(): Set abstract

Usage:

GSResource\$setAbstract(abstract)

Arguments:

abstract abstract

Method setKeywords(): Set keyword(s)

Usage:

GSResource\$setKeywords(keywords)

Arguments:

keywords keywords

Method addKeyword(): Adds keyword

Usage:

GSResource\$addKeyword(keyword)

Arguments:

keyword keyword

Returns: TRUE if added, FALSE otherwise

Method delKeyword(): Deletes keyword

Usage:

GSResource\$delKeyword(keyword)

Arguments:

keyword keyword

Returns: TRUE if deleted, FALSE otherwise

Method setMetadataLinks(): Set metadata links

Usage:

GSResource\$setMetadataLinks(metadataLinks)

Arguments:

metadataLinks metadata links

Method addMetadataLink(): Adds metadata link

Usage:

GSResource\$addMetadataLink(metadataLink)

Arguments:

metadataLink object of class [GSMetadataLink](#)

Returns: TRUE if added, FALSE otherwise

Method deleteMetadataLink(): Deletes metadata link

Usage:

GSResource\$deleteMetadataLink(metadataLink)

Arguments:

metadataLink object of class [GSMetadataLink](#)

Returns: TRUE if deleted, FALSE otherwise

Method setProjectionPolicy(): Set projection policy

Usage:

GSResource\$setProjectionPolicy(projectionPolicy)

Arguments:

projectionPolicy projection policy

Method setSrs(): Set SRS

Usage:

GSResource\$setSrs(srs)

Arguments:

srs srs

Method setNativeCRS(): Set native CRS

Usage:

GSResource\$setNativeCRS(nativeCRS)

Arguments:

nativeCRS native crs

Method setLatLonBoundingBox(): Set LatLon bounding box

Usage:

GSResource\$setLatLonBoundingBox(minx, miny, maxx, maxy, bbox = NULL, crs)

Arguments:

minx minx

miny miny

maxx maxx

maxy maxy

bbox bbox

crs crs

Method setNativeBoundingBox(): Set native bounding box

Usage:

GSResource\$setNativeBoundingBox(minx, miny, maxx, maxy, bbox = NULL, crs)

Arguments:

minx minx

miny miny

maxx maxx

maxy maxy

bbox bbox

crs crs

Method setMetadata(): Set metadata

Usage:

GSResource\$setMetadata(key, metadata)

Arguments:

key key

metadata metadata

Returns: TRUE if added, FALSE otherwise

Method delMetadata(): Deletes metadata

Usage:

GSResource\$delMetadata(key)

Arguments:

key key

Returns: TRUE if deleted, FALSE otherwise

Method `setMetadataDimension()`: Set metadata dimension

Usage:

```
GSResource$setMetadataDimension(key, dimension, custom = FALSE)
```

Arguments:

key key

dimension dimension

custom custom

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSResource$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
res <- GSResource$new(rootName = "featureType")
```

GSRESTEntrySet

Geoserver REST API XML entry set

Description

Geoserver REST API XML entry set

Geoserver REST API XML entry set

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a entry set

Super class

[geosapi::GSRESTResource](#) -> GSRESTEntrySet

Public fields

entryset entryset

Methods**Public methods:**

- [GSRESEntrySet\\$new\(\)](#)
- [GSRESEntrySet\\$decode\(\)](#)
- [GSRESEntrySet\\$setEntryset\(\)](#)
- [GSRESEntrySet\\$addEntry\(\)](#)
- [GSRESEntrySet\\$setEntry\(\)](#)
- [GSRESEntrySet\\$delEntry\(\)](#)
- [GSRESEntrySet\\$clone\(\)](#)

Method new(): Initializes an object of class [GSRESEntrySet](#)

Usage:

GSRESEntrySet\$new(rootName, xml = NULL, entryset)

Arguments:

rootName root name

xml object of class [xml_node-class](#)

entryset entry set

Method decode(): Decodes from XML

Usage:

GSRESEntrySet\$decode(xml)

Arguments:

xml object of class [xml_node-class](#)

Method setEntryset(): Set entry set

Usage:

GSRESEntrySet\$setEntryset(entryset)

Arguments:

entryset entry set

Method addEntry(): Adds entry set

Usage:

GSRESEntrySet\$addEntry(key, value)

Arguments:

key key

value value

Returns: TRUE if added, FALSE otherwise

Method setEntry(): Sets entry set

Usage:

GSRESTREntrySet\$setEntry(key, value)

Arguments:

key key

value value

Method delEntry(): Deletes entry set

Usage:

GSRESTREntrySet\$delEntry(key)

Arguments:

key key

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSRESTREntrySet\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSRESTRResource

Geoserver REST API REST Resource interface

Description

Geoserver REST API REST Resource interface

Geoserver REST API REST Resource interface

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer REST resource interface

Public fields

rootName root name

attrs attrs

Methods

Public methods:

- [GSRESTResource\\$new\(\)](#)
- [GSRESTResource\\$decode\(\)](#)
- [GSRESTResource\\$encode\(\)](#)
- [GSRESTResource\\$print\(\)](#)
- [GSRESTResource\\$getClassName\(\)](#)
- [GSRESTResource\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSRESTResource](#)

Usage:

```
GSRESTResource$new(xml, rootName)
```

Arguments:

xml object of class [xml_node-class](#)

rootName root name

Method [decode\(\)](#): Decodes from XML. Abstract method to be implemented by sub-classes

Usage:

```
GSRESTResource$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method [encode\(\)](#): Encodes as XML

Usage:

```
GSRESTResource$encode()
```

Returns: an object of class [xml_node-class](#)

Method [print\(\)](#): Provides a custom print output (as tree) of the current class

Usage:

```
GSRESTResource$print(..., depth = 1)
```

Arguments:

... args

depth class nesting depth

Method [getClassName\(\)](#): Get class name

Usage:

```
GSRESTResource$getClassName()
```

Returns: an object of class character

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
GSRESTResource$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSRestRule

A GeoServer access control list service rule

Description

This class models a GeoServer access control list service rule

Format

[R6Class](#) object.

Details

Geoserver REST API Access Control List REST Rule

Value

Object of [R6Class](#) for modelling a GeoServer access control list service rule

Super classes

[geosapi::GSRESTRessource](#) -> [geosapi::GSRule](#) -> GSRestRule

Public fields

roles one or more roles

Methods**Public methods:**

- [GSRestRule\\$new\(\)](#)
- [GSRestRule\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [GSLayerRule](#)

Usage:

[GSRestRule\\$new](#)(xml = NULL, pattern = "/*", methods, roles)

Arguments:

xml an object of class [xml_node-class](#)

pattern a URL Ant pattern, only applicable for domain rest. Default is /*

methods HTTP method(s)

roles one or more roles to add for the rule

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
GSRule$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSRule

A GeoServer access control list rule

Description

This class models a GeoServer access control list rule

Format

[R6Class](#) object.

Details

Geoserver REST API Access Control List Rule

Value

Object of [R6Class](#) for modelling a GeoServer access control list rule

Super class

[geosapi::GSRESTResource](#) -> GSRule

Methods**Public methods:**

- [GSRule\\$new\(\)](#)
- [GSRule\\$encode\(\)](#)
- [GSRule\\$decode\(\)](#)
- [GSRule\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [GSRule](#)

Usage:

```
GSRule$new(xml = NULL)
```

Arguments:

xml an object of class [xml_node-class](#)

Method encode(): Encodes as XML

Usage:

GSRule\$encode()

Returns: an object of class [xml_node-class](#)

Method decode(): Decodes from XML

Usage:

GSRule\$decode(xml)

Arguments:

xml an object of class [xml_node-class](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSRule\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSServiceManager

Geoserver REST API Service Manager

Description

Geoserver REST API Service Manager

Geoserver REST API Service Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing GeoServer services

Super class

[geosapi::GSManager](#) -> GSServiceManager

Methods

Public methods:

- [GSServiceManager\\$getServiceSettings\(\)](#)
- [GSServiceManager\\$getWmsSettings\(\)](#)
- [GSServiceManager\\$getWfsSettings\(\)](#)
- [GSServiceManager\\$getWcsSettings\(\)](#)
- [GSServiceManager\\$updateServiceSettings\(\)](#)
- [GSServiceManager\\$deleteServiceSettings\(\)](#)
- [GSServiceManager\\$updateWmsSettings\(\)](#)
- [GSServiceManager\\$updateWfsSettings\(\)](#)
- [GSServiceManager\\$updateWcsSettings\(\)](#)
- [GSServiceManager\\$enableWMS\(\)](#)
- [GSServiceManager\\$enableWFS\(\)](#)
- [GSServiceManager\\$enableWCS\(\)](#)
- [GSServiceManager\\$disableServiceSettings\(\)](#)
- [GSServiceManager\\$disableWMS\(\)](#)
- [GSServiceManager\\$disableWFS\(\)](#)
- [GSServiceManager\\$disableWCS\(\)](#)
- [GSServiceManager\\$clone\(\)](#)

Method [getServiceSettings\(\)](#): Get the service settings. To get the service settings for a specific workspace, specify the workspace name as ws parameter, otherwise global settings are retrieved.

Usage:

```
GSServiceManager$getServiceSettings(service, ws = NULL)
```

Arguments:

service service
ws workspace name

Returns: an object of class [GSServiceSettings](#)

Method [getWmsSettings\(\)](#): Get WMS settings. To get the WMS settings for a specific workspace, specify the workspace name as ws parameter, otherwise global settings are retrieved.

Usage:

```
GSServiceManager$getWmsSettings(ws = NULL)
```

Arguments:

ws workspace name

Returns: an object of class [GSServiceSettings](#)

Method [getWfsSettings\(\)](#): Get WFS settings. To get the WFS settings for a specific workspace, specify the workspace name as ws parameter, otherwise global settings are retrieved.

Usage:

```
GSServiceManager$getWfsSettings(ws = NULL)
```

Arguments:

ws workspace name

Returns: an object of class [GSServiceSettings](#)

Method `getWcsSettings()`: Get WCS settings. To get the WCS settings for a specific workspace, specify the workspace name as ws parameter, otherwise global settings are retrieved.

Usage:

```
GSServiceManager$getWcsSettings(ws = NULL)
```

Arguments:

ws workspace name

Returns: an object of class [GSServiceSettings](#)

Method `updateServiceSettings()`: Updates the service settings with an object of class [GSServiceSettings](#). An optional workspace name ws can be specified to update service settings applying to a workspace.

Usage:

```
GSServiceManager$updateServiceSettings(serviceSettings, service, ws = NULL)
```

Arguments:

serviceSettings serviceSettings object of class [GSServiceSettings](#)

service service

ws workspace name

Returns: TRUE if updated, FALSE otherwise

Method `deleteServiceSettings()`: Deletes the service settings. This method is used internally by **geosapi** for disabling a service setting at workspace level.

Usage:

```
GSServiceManager$deleteServiceSettings(service, ws = NULL)
```

Arguments:

service service

ws workspace name

Returns: TRUE if deleted, FALSE otherwise

Method `updateWmsSettings()`: Updates the WMS settings with an object of class [GSServiceSettings](#). An optional workspace name ws can be specified to update WMS settings applying to a workspace.

Usage:

```
GSServiceManager$updateWmsSettings(serviceSettings, ws = NULL)
```

Arguments:

serviceSettings service settings object of class [GSServiceSettings](#)

ws workspace name

Returns: TRUE if deleted, FALSE otherwise

Method `updateWfsSettings()`: Updates the WFS settings with an object of class [GSServiceSettings](#). An optional workspace name ws can be specified to update WFS settings applying to a workspace.

Usage:

GSServiceManager\$updateWfsSettings(serviceSettings, ws = NULL)

Arguments:

serviceSettings service settings object of class [GSServiceSettings](#)

ws workspace name

Returns: TRUE if deleted, FALSE otherwise

Method `updateWcsSettings()`: Updates the WCS settings with an object of class `GSServiceSettings`. An optional workspace name `ws` can be specified to update WCS settings applying to a workspace.

Usage:

GSServiceManager\$updateWcsSettings(serviceSettings, ws = NULL)

Arguments:

serviceSettings service settings object of class [GSServiceSettings](#)

ws workspace name

Returns: TRUE if deleted, FALSE otherwise

Method `enableWMS()`: Enables WMS service settings

Usage:

GSServiceManager\$enableWMS(ws = NULL)

Arguments:

ws workspace name

Returns: TRUE if enabled, FALSE otherwise

Method `enableWFS()`: Enables WFS service settings

Usage:

GSServiceManager\$enableWFS(ws = NULL)

Arguments:

ws workspace name

Returns: TRUE if enabled, FALSE otherwise

Method `enableWCS()`: Enables WCS service settings

Usage:

GSServiceManager\$enableWCS(ws = NULL)

Arguments:

ws workspace name

Returns: TRUE if enabled, FALSE otherwise

Method `disableServiceSettings()`: Disables service settings

Usage:

GSServiceManager\$disableServiceSettings(service, ws = NULL)

Arguments:

service service
ws workspace name

Returns: TRUE if disabled, FALSE otherwise

Method disableWMS(): Disables WMS service settings

Usage:

GSServiceManager\$disableWMS(ws = NULL)

Arguments:

ws workspace name

Returns: TRUE if disabled, FALSE otherwise

Method disableWFS(): Disables WFS service settings

Usage:

GSServiceManager\$disableWFS(ws = NULL)

Arguments:

ws workspace name

Returns: TRUE if disabled, FALSE otherwise

Method disableWCS(): Disables WCS service settings

Usage:

GSServiceManager\$disableWCS(ws = NULL)

Arguments:

ws workspace name

Returns: TRUE if disabled, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSServiceManager\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

Not run:

```
GSServiceManager$new("http://localhost:8080/geoserver", "admin", "geoserver")
```

End(Not run)

GSServiceRule

A GeoServer access control list service rule

Description

This class models a GeoServer access control list service rule

Format

[R6Class](#) object.

Details

Geoserver REST API Access Control List Service Rule

Value

Object of [R6Class](#) for modelling a GeoServer access control list service rule

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSRule](#) -> GSServiceRule

Public fields

roles one or more roles

Methods**Public methods:**

- [GSServiceRule\\$new\(\)](#)
- [GSServiceRule\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [GSLayerRule](#)

Usage:

```
GSServiceRule$new(
  xml = NULL,
  service,
  method,
  permission = c("r", "w", "a"),
  roles
)
```

Arguments:

xml an object of class [xml_node-class](#)

service service subject to the access control rule, eg. 'wfs'

method service method subject to the access control rule, eg. 'GetFeature'

permission the rule permission, either r (read), w (write) or a (administer)
 roles one or more roles to add for the rule

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSServiceRule\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

GSServiceSettings *A GeoServer service settings resource*

Description

This class models a GeoServer OWS service settings.

Format

[R6Class](#) object.

Details

Geoserver REST API Service Setting

Value

Object of [R6Class](#) for modelling a GeoServer OWS service setting

Super class

[geosapi::GSRESTResource](#) -> GSServiceSettings

Public fields

enabled is service enabled or not?
 citeCompliant is service cite compliant?
 name service name
 title service title
 maintainer service maintainer
 abstract service abstract
 accessConstraints service access constraints

fees service fees
keywords services keywords
onlineResource service online resource
schemaBaseUrl service schema base URL
verbose service verbose or not?

Methods

Public methods:

- [GSServiceSettings\\$new\(\)](#)
- [GSServiceSettings\\$decode\(\)](#)
- [GSServiceSettings\\$setEnabled\(\)](#)
- [GSServiceSettings\\$setCiteCompliant\(\)](#)
- [GSServiceSettings\\$setName\(\)](#)
- [GSServiceSettings\\$setTitle\(\)](#)
- [GSServiceSettings\\$setMaintainer\(\)](#)
- [GSServiceSettings\\$setAbstract\(\)](#)
- [GSServiceSettings\\$setAccessConstraints\(\)](#)
- [GSServiceSettings\\$setFees\(\)](#)
- [GSServiceSettings\\$setKeywords\(\)](#)
- [GSServiceSettings\\$addKeyword\(\)](#)
- [GSServiceSettings\\$delKeyword\(\)](#)
- [GSServiceSettings\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSServiceSettings](#)

Usage:

`GSServiceSettings$new(xml = NULL, service)`

Arguments:

xml object of class [xml_node-class](#)

service service service acronym

Method [decode\(\)](#): Decodes from XML

Usage:

`GSServiceSettings$decode(xml)`

Arguments:

xml object of class [xml_node-class](#)

Method [setEnabled\(\)](#): Set enabled

Usage:

`GSServiceSettings$setEnabled(enabled)`

Arguments:

enabled enabled

Method setCiteCompliant(): Set cite compliant

Usage:

GSServiceSettings\$setCiteCompliant(citeCompliant)

Arguments:

citeCompliant cite compliant

Method setName(): Set name

Usage:

GSServiceSettings\$setName(name)

Arguments:

name name

Method setTitle(): Set title

Usage:

GSServiceSettings\$setTitle(title)

Arguments:

title title

Method setMaintainer(): Set maintainer

Usage:

GSServiceSettings\$setMaintainer(maintainer)

Arguments:

maintainer maintainer

Method setAbstract(): Set abstract

Usage:

GSServiceSettings\$setAbstract(abstract)

Arguments:

abstract abstract

Method setAccessConstraints(): Set access constraints

Usage:

GSServiceSettings\$setAccessConstraints(accessConstraints)

Arguments:

accessConstraints access constraints

Method setFees(): Set fees

Usage:

GSServiceSettings\$setFees(fees)

Arguments:

fees fees

Method setKeywords(): Set keywords

Usage:

```
GSServiceSettings$setKeywords(keywords)
```

Arguments:

keywords keywords

Method addKeyword(): Adds a keyword

Usage:

```
GSServiceSettings$addKeyword(keyword)
```

Arguments:

keyword keyword

Returns: TRUE if added, FALSE otherwise

Method delKeyword(): Deletes a keyword

Usage:

```
GSServiceSettings$delKeyword(keyword)
```

Arguments:

keyword keyword

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSServiceSettings$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
settings <- GSServiceSettings$new(service = "WMS")
settings$setEnabled(TRUE)
```

GSShapefileDataStore *Geoserver REST API ShapeFileDataStore*

Description

Geoserver REST API ShapeFileDataStore

Geoserver REST API ShapeFileDataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer Shapefile dataStore

Super classes

[geosapi::GSRESTResource](#) -> [geosapi::GSAbstractStore](#) -> [geosapi::GSAbstractDataStore](#)
-> GSShapefileDataStore

Methods**Public methods:**

- [GSShapefileDataStore\\$new\(\)](#)
- [GSShapefileDataStore\\$setUrl\(\)](#)
- [GSShapefileDataStore\\$setCharset\(\)](#)
- [GSShapefileDataStore\\$setCreateSpatialIndex\(\)](#)
- [GSShapefileDataStore\\$setMemoryMappedBuffer\(\)](#)
- [GSShapefileDataStore\\$setCacheReuseMemoryMaps\(\)](#)
- [GSShapefileDataStore\\$setDefaultConnectionParameters\(\)](#)
- [GSShapefileDataStore\\$clone\(\)](#)

Method [new\(\)](#): initializes a shapefile data store

Usage:

```
GSShapefileDataStore$new(
  xml = NULL,
  name = NULL,
  description = "",
  enabled = TRUE,
  url
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML

name coverage store name

description coverage store description
enabled whether the store should be enabled or not. Default is TRUE
url url

Method `setUrl()`: Set the spatial files data URL

Usage:

`GSShapefileDataStore$setUrl(url)`

Arguments:

url url

Method `setCharset()`: Set the charset used for DBF file.

Usage:

`GSShapefileDataStore$setCharset(charset = "ISO-8859-1")`

Arguments:

charset charset. Default value is 'ISO-8859-1'

Method `setCreateSpatialIndex()`: Set the 'Create Spatial Index' option

Usage:

`GSShapefileDataStore$setCreateSpatialIndex(create = TRUE)`

Arguments:

create create. Default is TRUE

Method `setMemoryMappedBuffer()`: Set the 'Memory Mapped Buffer' option

Usage:

`GSShapefileDataStore$setMemoryMappedBuffer(buffer = FALSE)`

Arguments:

buffer buffer. Default is FALSE

Method `setCacheReuseMemoryMaps()`: Set the 'Cache & Reuse Memory Maps' option.

Usage:

`GSShapefileDataStore$setCacheReuseMemoryMaps/maps = TRUE)`

Arguments:

maps maps. Default is TRUE

Method `setDefaultConnectionParameters()`: Set default connection parameters

Usage:

`GSShapefileDataStore$setDefaultConnectionParameters()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`GSShapefileDataStore$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSShapefileDataStore$new(name = "ds", description = "des",
                          enabled = TRUE, url = "file://data/shape.shp")
```

GSShapefileDirectoryDataStore

Geoserver REST API ShapeFileDirectoryDataStore

Description

Geoserver REST API ShapeFileDirectoryDataStore

Geoserver REST API ShapeFileDirectoryDataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer Shapefile directory dataStore

Super classes

```
geosapi::GSRESTResource -> geosapi::GSAbstractStore -> geosapi::GSAbstractDataStore
-> geosapi::GSShapefileDataStore -> GSShapefileDirectoryDataStore
```

Methods**Public methods:**

- [GSShapefileDirectoryDataStore\\$new\(\)](#)
- [GSShapefileDirectoryDataStore\\$setUrl\(\)](#)
- [GSShapefileDirectoryDataStore\\$setCharset\(\)](#)
- [GSShapefileDirectoryDataStore\\$setCreateSpatialIndex\(\)](#)
- [GSShapefileDirectoryDataStore\\$setMemoryMappedBuffer\(\)](#)
- [GSShapefileDirectoryDataStore\\$setCacheReuseMemoryMaps\(\)](#)
- [GSShapefileDirectoryDataStore\\$setDefaultConnectionParameters\(\)](#)
- [GSShapefileDirectoryDataStore\\$clone\(\)](#)

Method [new\(\)](#): initializes a shapefile directory data store

Usage:

```
GSShapefileDirectoryDataStore$new(  
  xml = NULL,  
  name = NULL,  
  description = "",  
  enabled = TRUE,  
  url  
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML
name coverage store name
description coverage store description
enabled whether the store should be enabled or not. Default is TRUE
url url

Method `setUrl()`: Set the spatial files data URL

Usage:

```
GSShapefileDirectoryDataStore$setUrl(url)
```

Arguments:

url url

Method `setCharset()`: Set the charset used for DBF file.

Usage:

```
GSShapefileDirectoryDataStore$setCharset(charset = "ISO-8859-1")
```

Arguments:

charset charset. Default value is 'ISO-8859-1'

Method `setCreateSpatialIndex()`: Set the 'Create Spatial Index' option

Usage:

```
GSShapefileDirectoryDataStore$setCreateSpatialIndex(create = TRUE)
```

Arguments:

create create. Default is TRUE

Method `setMemoryMappedBuffer()`: Set the 'Memory Mapped Buffer' option

Usage:

```
GSShapefileDirectoryDataStore$setMemoryMappedBuffer(buffer = FALSE)
```

Arguments:

buffer buffer. Default is FALSE

Method `setCacheReuseMemoryMaps()`: Set the 'Cache & Reuse Memory Maps' option.

Usage:

```
GSShapefileDirectoryDataStore$setCacheReuseMemoryMaps/maps = TRUE)
```

Arguments:

maps maps. Default is TRUE

Method `setDefaultConnectionParameters()`: Set default connection parameters

Usage:

```
GSShapefileDirectoryDataStore$setDefaultConnectionParameters()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSShapefileDirectoryDataStore$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
GSShapefileDirectoryDataStore$new(name = "ds", description = "des",
  enabled = TRUE, url = "file://data")
```

GSShinyMonitor

Geoserver REST API DataStore

Description

Geoserver REST API DataStore

Geoserver REST API DataStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for setting a GS Shiny monitoring app

Methods

Public methods:

- [GSShinyMonitor\\$new\(\)](#)
- [GSShinyMonitor\\$getMetric\(\)](#)
- [GSShinyMonitor\\$run\(\)](#)
- [GSShinyMonitor\\$clone\(\)](#)

Method `new()`: Initializes a Geoserver shiny monitoring tool

Usage:

```
GSShinyMonitor$new(manager, file = NULL, append = FALSE, sleep = 1)
```

Arguments:

manager object of class [GManager](#)

file file File where to store monitoring results

append append. Whether results should be appended to existing file

sleep sleep. Interval in seconds to trigger monitor calls

Method getMetric(): Get metric

Usage:

```
GSShinyMonitor$getMetric(name)
```

Arguments:

name name

Returns: the Geoserver monitored metric

Method run(): Runs the application

Usage:

```
GSShinyMonitor$run()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSShinyMonitor$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Internal class used for GManager\$monitor method

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSShinyManager

Geoserver REST API Style Manager

Description

Geoserver REST API Style Manager

Geoserver REST API Style Manager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for managing the styles of a GeoServer instance.

Super class

`geosapi::GSManager` -> `GSStyleManager`

Methods**Public methods:**

- `GSStyleManager$getStyles()`
- `GSStyleManager$getStyleNames()`
- `GSStyleManager$getStyle()`
- `GSStyleManager$createStyle()`
- `GSStyleManager$updateStyle()`
- `GSStyleManager$deleteStyle()`
- `GSStyleManager$getSLDVersion()`
- `GSStyleManager$getSLDBody()`
- `GSStyleManager$clone()`

Method `getStyles()`: Get the list of available styles.

Usage:

`GSStyleManager$getStyles(ws = NULL)`

Arguments:

`ws` an optional workspace name

Returns: an object of class `list` containing items of class [GSStyle](#)

Method `getStyleNames()`: Get the list of available style names

Usage:

`GSStyleManager$getStyleNames(ws = NULL)`

Arguments:

`ws` an optional workspace name

Returns: a vector of class `character`

Method `getStyle()`: Get a [GSStyle](#) object given a style name.

Usage:

`GSStyleManager$getStyle(style, ws = NULL)`

Arguments:

`style` style name

`ws` workspace name. Optional

Returns: object of class [GSStyle](#)

Method `createStyle()`: Creates a GeoServer style given a name.

Usage:

```
GSStyleManager$createStyle(file, sldBody = NULL, name, raw = FALSE, ws = NULL)
```

Arguments:

file file

sldBody SLD body

name name

raw raw

ws workspace name

Returns: TRUE if the style has been successfully created, FALSE otherwise

Method updateStyle(): Updates a GeoServer style given a name.

Usage:

```
GSStyleManager$updateStyle(file, sldBody = NULL, name, raw = FALSE, ws = NULL)
```

Arguments:

file file

sldBody SLD body

name name

raw raw

ws workspace name

Returns: TRUE if the style has been successfully updated, FALSE otherwise

Method deleteStyle(): Deletes a style given a name. By default, the option recurse is set to FALSE, ie datastore layers are not removed. To remove all coverage store layers, set this option to TRUE. The purge parameter is used to customize the delete of files on disk (in case the underlying reader implements a delete method).

Usage:

```
GSStyleManager$deleteStyle(name, recurse = FALSE, purge = FALSE, ws = NULL)
```

Arguments:

name name

recurse recurse

purge purge

ws workspace name

Returns: TRUE if the style has been successfully deleted, FALSE otherwise

Method getSLDVersion(): Get SLD version

Usage:

```
GSStyleManager$getSLDVersion(sldBody)
```

Arguments:

sldBody SLD body

Method getSLDBody(): Get SLD body

Usage:

```
GSStyleManager$getSLDBody(style, ws = NULL)
```

Arguments:

style style name

ws workspace name

Returns: an object of class [xml_node-class](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSStyleManager$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  GSStyleManager$new("http://localhost:8080/geoserver", "admin", "geoserver")

## End(Not run)
```

GSUtils

Geoserver REST API Manager Utils

Description

Geoserver REST API Manager Utils

Geoserver REST API Manager Utils

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with static util methods for communication with the REST API of a GeoServer instance.

Static methods

`getUserAgent()` This method is used to get the user agent for performing GeoServer API requests. Here the user agent will be compound by geosapi package name and version.

`getUserToken(user, pwd)` This method is used to get the user authentication token for performing GeoServer API requests. Token is given a Base64 encoded string.

`GET(url, user, pwd, path, verbose)` This method performs a GET request for a given path to GeoServer REST API

`PUT(url, user, pwd, path, filename, contentType, verbose)` This method performs a PUT request for a given path to GeoServer REST API, to upload a file of name filename with given contentType

`POST(url, user, pwd, path, content, contentType, verbose)` This method performs a POST request for a given path to GeoServer REST API, to post content of given contentType

`DELETE(url, user, pwd, path, verbose)` This method performs a DELETE request for a given GeoServer resource identified by a path in GeoServer REST API

`parseResponseXML(req)` Convenience method to parse XML response from GeoServer REST API.

`getPayloadXML(obj)` Convenience method to create payload XML to send to GeoServer.

`setBbox(minx, miny, maxx, maxy, bbox, crs)` Creates an list object representing a bbox. Either from coordinates or from a bbox object (matrix).

Methods**Public methods:**

- [`GSUtils\$clone\(\)`](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
GSUtils$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

GSVersion

A GeoServer version

Description

This class allows to grab the GeoServer version. By default, a tentative is made to fetch version from web admin default page, since Geoserver REST API did not support GET operation for the Geoserver version in past releases of Geoserver.

Format

[R6Class](#) object.

Details

Geoserver REST API - Geoserver Version

Value

Object of [R6Class](#) for modelling a GeoServer version

Public fields

version version

value value

Methods

Public methods:

- [GSVersion\\$new\(\)](#)
- [GSVersion\\$lowerThan\(\)](#)
- [GSVersion\\$greaterThan\(\)](#)
- [GSVersion\\$equalTo\(\)](#)
- [GSVersion\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSVersion](#)

Usage:

[GSVersion\\$new](#)(url, user, pwd)

Arguments:

url url

user user

pwd pwd

Method [lowerThan\(\)](#): Compares to a version and returns TRUE if it is lower, FALSE otherwise

Usage:

```
GSVersion$lowerThan(version)
```

Arguments:

version version

Returns: TRUE if lower, FALSE otherwise

Method greaterThan(): Compares to a version and returns TRUE if it is greater, FALSE otherwise

Usage:

```
GSVersion$greaterThan(version)
```

Arguments:

version version

Returns: TRUE if greater, FALSE otherwise

Method equalTo(): Compares to a version and returns TRUE if it is equal, FALSE otherwise

Usage:

```
GSVersion$equalTo(version)
```

Arguments:

version version

Returns: TRUE if equal, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSVersion$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
version <- GSVersion$new(
  url = "http://localhost:8080/geoserver",
  user = "admin", pwd = "geoserver"
)

## End(Not run)
```

 GSVirtualTable

Geoserver REST API GSVirtualTable

Description

Geoserver REST API GSVirtualTable

Geoserver REST API GSVirtualTable

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer virtual table

Super class

[geosapi::GSRESTResource](#) -> GSVirtualTable

Public fields

name name

sql SQL statement

escapeSql escape SQL?

keyColumn key column

geometry geometry

parameters list of virtual parameters

Methods**Public methods:**

- [GSVirtualTable\\$new\(\)](#)
- [GSVirtualTable\\$decode\(\)](#)
- [GSVirtualTable\\$setName\(\)](#)
- [GSVirtualTable\\$setSql\(\)](#)
- [GSVirtualTable\\$setEscapeSql\(\)](#)
- [GSVirtualTable\\$setKeyColumn\(\)](#)
- [GSVirtualTable\\$setGeometry\(\)](#)
- [GSVirtualTable\\$addParameter\(\)](#)
- [GSVirtualTable\\$delParameter\(\)](#)
- [GSVirtualTable\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSVirtualTable](#)

Usage:

GSVirtualTable\$new(xml = NULL)

Arguments:

xml object of class [xml_node-class](#)

Method decode(): Decodes from XML

Usage:

GSVirtualTable\$decode(xml)

Arguments:

xml object of class [xml_node-class](#)

Method setName(): Set name

Usage:

GSVirtualTable\$setName(name)

Arguments:

name name

Method setSql(): Set SQL

Usage:

GSVirtualTable\$setSql(sql)

Arguments:

sql sql

Method setEscapeSql(): Set escape SQL

Usage:

GSVirtualTable\$setEscapeSql(escapeSql)

Arguments:

escapeSql escape SQL

Method setKeyColumn(): Set key column

Usage:

GSVirtualTable\$setKeyColumn(keyColumn)

Arguments:

keyColumn key column

Method setGeometry(): Set geometry

Usage:

GSVirtualTable\$setGeometry(vtg)

Arguments:

vtg object of class [GSVirtualTableGeometry](#)

Method addParameter(): Adds parameter

Usage:

GSVirtualTable\$addParameter(parameter)

Arguments:

parameter object of class [GSVirtualTableParameter](#)

Returns: TRUE if added, FALSE otherwise

Method delParameter(): Deletes parameter

Usage:

GSVirtualTable\$delParameter(parameter)

Arguments:

parameter object of class [GSVirtualTableParameter](#)

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

GSVirtualTable\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSVirtualTable$new()
```

GSVirtualTableGeometry

Geoserver REST API GSVirtualTableGeometry

Description

Geoserver REST API GSVirtualTableGeometry

Geoserver REST API GSVirtualTableGeometry

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer virtual table geometry

Super class

[geosapi::GSRESTResource](#) -> GSVirtualTableGeometry

Public fields

name geometry name

type geometry type

srid geometry SRID

Methods**Public methods:**

- [GSVirtualTableGeometry\\$new\(\)](#)
- [GSVirtualTableGeometry\\$decode\(\)](#)
- [GSVirtualTableGeometry\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [GSVirtualTableGeometry](#)

Usage:

```
GSVirtualTableGeometry$new(xml = NULL, name, type, srid)
```

Arguments:

xml object of class [xml_node-class](#)

name name

type type

srid srid

Method [decode\(\)](#): Decodes from XML

Usage:

```
GSVirtualTableGeometry$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
GSVirtualTableGeometry$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSVirtualTableGeometry$new(name = "work", type = "MultiPolygon", srid = 4326)
```

 GSVirtualTableParameter

Geoserver REST API GSVirtualTableParameter

Description

Geoserver REST API GSVirtualTableParameter

Geoserver REST API GSVirtualTableParameter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer virtual table parameter

Super class

[geosapi::GSRESTResource](#) -> GSVirtualTableParameter

Public fields

name parameter name

defaultValue parameter default value

regexValidator parameter regexp validator

Methods

Public methods:

- [GSVirtualTableParameter\\$new\(\)](#)
- [GSVirtualTableParameter\\$decode\(\)](#)
- [GSVirtualTableParameter\\$clone\(\)](#)

Method new(): Initializes an object of class [GSVirtualTableParameter](#)

Usage:

[GSVirtualTableParameter\\$new](#)(xml = NULL, name, defaultValue, regexValidator)

Arguments:

xml object of class [xml_node-class](#)

name name

defaultValue default value

regexValidator regexp validator

Method decode(): Decodes from XML

Usage:

```
GSVirtualTableParameter$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSVirtualTableParameter$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSVirtualTableParameter$new(name = "fieldname", defaultValue = "default_value",  
                             regexpValidator = "someregexp")
```

GSWorkspace

Geoserver REST API Workspace

Description

Geoserver REST API Workspace

Geoserver REST API Workspace

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer workspace

Super class

[geosapi::GSRESTResource](#) -> GSWorkspace

Public fields

name name

Methods

Public methods:

- [GSWorkspace\\$new\(\)](#)
- [GSWorkspace\\$decode\(\)](#)
- [GSWorkspace\\$clone\(\)](#)

Method [new\(\)](#): initializes a [GSWorkspace](#)

Usage:

```
GSWorkspace$new(xml = NULL, name)
```

Arguments:

xml an object of class [xml_node-class](#)
name name

Method [decode\(\)](#): Decodes from XML

Usage:

```
GSWorkspace$decode(xml)
```

Arguments:

xml an object of class [xml_node-class](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
GSWorkspace$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
GSWorkspace$new(name = "work")
```

GSWorkspaceManager

Geoserver REST API Workspace Manager

Description

Geoserver REST API Workspace Manager

Geoserver REST API Workspace Manager

Format

R6Class object.

Value

Object of [R6Class](#) with methods for managing the workspaces of a GeoServer instance.

Super class

[geosapi::GManager](#) -> GSWorkspaceManager

Methods**Public methods:**

- [GSWorkspaceManager\\$getWorkspaces\(\)](#)
- [GSWorkspaceManager\\$getWorkspaceNames\(\)](#)
- [GSWorkspaceManager\\$getWorkspace\(\)](#)
- [GSWorkspaceManager\\$createWorkspace\(\)](#)
- [GSWorkspaceManager\\$updateWorkspace\(\)](#)
- [GSWorkspaceManager\\$deleteWorkspace\(\)](#)
- [GSWorkspaceManager\\$getWorkspaceSettings\(\)](#)
- [GSWorkspaceManager\\$createWorkspaceSettings\(\)](#)
- [GSWorkspaceManager\\$updateWorkspaceSettings\(\)](#)
- [GSWorkspaceManager\\$deleteWorkspaceSettings\(\)](#)
- [GSWorkspaceManager\\$clone\(\)](#)

Method [getWorkspaces\(\)](#): Get the list of available workspace. Returns an object of class [list](#) containing items of class [GSWorkspace](#)

Usage:

```
GSWorkspaceManager$getWorkspaces()
```

Arguments:

a list of [GSWorkspace](#)

Method [getWorkspaceNames\(\)](#): Get the list of available workspace names. Returns an vector of class [character](#)

Usage:

```
GSWorkspaceManager$getWorkspaceNames()
```

Returns: a list of workspace names

Method [getWorkspace\(\)](#): Get a [GSWorkspace](#) object given a workspace name.

Usage:

```
GSWorkspaceManager$getWorkspace(ws)
```

Arguments:

ws workspace name

Returns: an object of class [GSWorkspace](#)

Method `createWorkspace()`: Creates a GeoServer workspace given a name, and an optional URI. If the URI is not specified, GeoServer will automatically create an associated Namespace with the URI built from the workspace name. If the URI is specified, the method invokes the method `createNamespace(ns, uri)` of the [GSNamespaceManager](#). Returns TRUE if the workspace has been successfully created, FALSE otherwise

Usage:

```
GSWorkspaceManager$createWorkspace(name, uri)
```

Arguments:

name name

uri uri

Returns: TRUE if created, FALSE otherwise

Method `updateWorkspace()`: Updates a GeoServer workspace given a name, and an optional URI. If the URI is not specified, GeoServer will automatically update the associated Namespace with the URI built from the workspace name. If the URI is specified, the method invokes the method `updateNamespace(ns, uri)` of the [GSNamespaceManager](#). Returns TRUE if the workspace has been successfully updated, FALSE otherwise

Usage:

```
GSWorkspaceManager$updateWorkspace(name, uri)
```

Arguments:

name name

uri uri

Returns: TRUE if created, FALSE otherwise

Method `deleteWorkspace()`: Deletes a GeoServer workspace given a name.

Usage:

```
GSWorkspaceManager$deleteWorkspace(name, recurse = FALSE)
```

Arguments:

name name

recurse recurse

Returns: TRUE if the workspace has been successfully deleted, FALSE otherwise

Method `getWorkspaceSettings()`: Updates workspace settings

Usage:

```
GSWorkspaceManager$getWorkspaceSettings(ws)
```

Arguments:

ws workspace name

Returns: an object of class [GSWorkspaceSettings](#)

Method `createWorkspaceSettings()`: Creates workspace settings

Usage:

```
GSWorkspaceManager#createWorkspaceSettings(ws, workspaceSettings)
```

Arguments:

ws workspace name

workspaceSettings object of class [GSWorkspaceSettings](#)

Returns: TRUE if created, FALSE otherwise

Method updateWorkspaceSettings(): Updates workspace settings

Usage:

```
GSWorkspaceManager$updateWorkspaceSettings(ws, workspaceSettings)
```

Arguments:

ws workspace name

workspaceSettings object of class [GSWorkspaceSettings](#)

Returns: TRUE if updated, FALSE otherwise

Method deleteWorkspaceSettings(): Deletes workspace settings

Usage:

```
GSWorkspaceManager$deleteWorkspaceSettings(ws)
```

Arguments:

ws workspace name

Returns: TRUE if deleted, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSWorkspaceManager$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:  
GSWorkspaceManager$new("http://localhost:8080/geoserver", "admin", "geoserver")  
  
## End(Not run)
```

GSWorkspaceSettings	<i>Geoserver REST API Workspace Setting</i>
---------------------	---

Description

Geoserver REST API Workspace Setting

Geoserver REST API Workspace Setting

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer workspace settings

Super class

[geosapi::GSRESTResource](#) -> GSWorkspaceSettings

Public fields

contact contact

charset charset

numDecimals number of decimal

onlineResource online resource

verbose verbose

verboseExceptions verbose exceptions

localWorkspaceIncludesPrefix local workspace includes prefix

Methods**Public methods:**

- [GSWorkspaceSettings\\$new\(\)](#)
- [GSWorkspaceSettings\\$decode\(\)](#)
- [GSWorkspaceSettings\\$setCharset\(\)](#)
- [GSWorkspaceSettings\\$setNumDecimals\(\)](#)
- [GSWorkspaceSettings\\$setOnlineResource\(\)](#)
- [GSWorkspaceSettings\\$setVerbose\(\)](#)
- [GSWorkspaceSettings\\$setVerboseExceptions\(\)](#)
- [GSWorkspaceSettings\\$setLocalWorkspaceIncludesPrefix\(\)](#)
- [GSWorkspaceSettings\\$clone\(\)](#)

Method new(): This method is used to instantiate a GSWorkspaceSettings. This settings object is required to activate a workspace configuration, using the method GSManager#createWorkspaceSettings. Supported from GeoServer 2.12

Usage:

```
GSWorkspaceSettings$new(xml = NULL)
```

Arguments:

xml object of class [xml_node-class](#)

Method decode(): Decodes from XML

Usage:

```
GSWorkspaceSettings$decode(xml)
```

Arguments:

xml object of class [xml_node-class](#)

Method setCharset(): Set charset

Usage:

```
GSWorkspaceSettings$setCharset(charset)
```

Arguments:

charset charset

Method setNumDecimals(): Set number of decimals

Usage:

```
GSWorkspaceSettings$setNumDecimals(numDecimals)
```

Arguments:

numDecimals number of decimals

Method setOnlineResource(): Set online resource

Usage:

```
GSWorkspaceSettings$setOnlineResource(onlineResource)
```

Arguments:

onlineResource online resource

Method setVerbose(): Set verbose

Usage:

```
GSWorkspaceSettings$setVerbose(verbose)
```

Arguments:

verbose verbose

Method setVerboseExceptions(): Set verbose exceptions

Usage:

```
GSWorkspaceSettings$setVerboseExceptions(verboseExceptions)
```

Arguments:

verboseExceptions verbose exceptions

Method setLocalWorkspaceIncludesPrefix(): Set local workspace includes prefix

Usage:

```
GSWorkspaceSettings$setLocalWorkspaceIncludesPrefix(includesPrefix)
```

Arguments:

includesPrefix includes prefix

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSWorkspaceSettings$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
settings <- GSWorkspaceSettings$new()
settings$setCharset("UTF-8")
settings$setNumDecimals(5)
```

GSWorldImageCoverageStore

Geoserver REST API WorldImageCoverageStore

Description

Geoserver REST API WorldImageCoverageStore

Geoserver REST API WorldImageCoverageStore

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GeoServer WorldImage CoverageStore

Super classes

```
geosapi::GSRESTResource -> geosapi::GSAbstractStore -> geosapi::GSAbstractCoverageStore
-> GSWorldImageCoverageStore
```

Public fields

url url

Methods**Public methods:**

- [GSWorldImageCoverageStore\\$new\(\)](#)
- [GSWorldImageCoverageStore\\$clone\(\)](#)

Method new(): Initializes an WorldImage coverage store

Usage:

```
GSWorldImageCoverageStore$new(  
    xml = NULL,  
    name = NULL,  
    description = "",  
    enabled = TRUE,  
    url = NULL  
)
```

Arguments:

xml an object of class [xml_node-class](#) to create object from XML
name coverage store name
description coverage store description
enabled whether the store should be enabled or not. Default is TRUE
url url

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GSWorldImageCoverageStore$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Index

- * **ACL**
 - GSAccessControllistManager, [15](#)
- * **ArcGrid**
 - GSArcGridCoverageStore, [19](#)
- * **CoverageStore**
 - GSAbstractCoverageStore, [4](#)
 - GSArcGridCoverageStore, [19](#)
 - GSCoverageStoreManager, [25](#)
 - GSGeoTIFFCoverageStore, [51](#)
 - GSIImageMosaicCoverageStore, [52](#)
 - GSWorldImageCoverageStore, [128](#)
- * **DB**
 - GSAbstractDBDataStore, [8](#)
- * **DataStore**
 - GSAbstractDataStore, [5](#)
 - GSAbstractDBDataStore, [8](#)
 - GSDataStoreManager, [35](#)
 - GSGeoPackageDataStore, [49](#)
 - GSOracleNGDataStore, [78](#)
 - GSPostGISDataStore, [80](#)
 - GSShapefileDataStore, [104](#)
 - GSShapefileDirectoryDataStore, [106](#)
- * **ESRI**
 - GSShapefileDataStore, [104](#)
 - GSShapefileDirectoryDataStore, [106](#)
- * **GeoPackage**
 - GSGeoPackageDataStore, [49](#)
- * **GeoTIFF**
 - GSGeoTIFFCoverageStore, [51](#)
- * **ImageMosaic**
 - GSIImageMosaicCoverageStore, [52](#)
- * **Layer**
 - GSLayerManager, [64](#)
 - GSMonitorManager, [74](#)
- * **OGC**
 - GSServiceSettings, [100](#)
- * **OWS**
 - GSServiceSettings, [100](#)
- * **OracleNG**
 - GSOracleNGDataStore, [78](#)
- * **PostGIS**
 - GSPostGISDataStore, [80](#)
- * **WCS**
 - GSServiceSettings, [100](#)
- * **WFS**
 - GSServiceSettings, [100](#)
- * **WMS**
 - GSServiceSettings, [100](#)
- * **WorldImage**
 - GSWorldImageCoverageStore, [128](#)
- * **access**
 - GSAccessControllistManager, [15](#)
 - GSLayerRule, [67](#)
 - GSRestRule, [92](#)
 - GSRule, [93](#)
 - GSServiceRule, [99](#)
- * **api**
 - GSAbstractCoverageStore, [4](#)
 - GSAbstractDataStore, [5](#)
 - GSAbstractDBDataStore, [8](#)
 - GSAbstractStore, [13](#)
 - GSAccessControllistManager, [15](#)
 - GSArcGridCoverageStore, [19](#)
 - GSCoverage, [20](#)
 - GSCoverageBand, [22](#)
 - GSCoverageStoreManager, [25](#)
 - GSCoverageView, [32](#)
 - GSDataStoreManager, [35](#)
 - GSDimension, [43](#)
 - GSFeatureDimension, [46](#)
 - GSFeatureType, [47](#)
 - GSGeoPackageDataStore, [49](#)
 - GSGeoTIFFCoverageStore, [51](#)
 - GSIImageMosaicCoverageStore, [52](#)
 - GSInputCoverageBand, [53](#)
 - GSLayer, [55](#)
 - GSLayerGroup, [59](#)
 - GSLayerManager, [64](#)

- GSLayerRule, [67](#)
- GSManger, [68](#)
- GSMetadataLink, [72](#)
- GSMonitorManager, [74](#)
- GSNamespace, [75](#)
- GSNamespaceManager, [76](#)
- GSOacleNGDataStore, [78](#)
- GSPostGISDataStore, [80](#)
- GSPublishable, [81](#)
- GSResource, [83](#)
- GSRESTEntrySet, [88](#)
- GSRESTResource, [90](#)
- GSRestRule, [92](#)
- GSRule, [93](#)
- GSServiceManager, [94](#)
- GSServiceRule, [99](#)
- GSServiceSettings, [100](#)
- GSShapefileDataStore, [104](#)
- GSShapefileDirectoryDataStore, [106](#)
- GSStyleManager, [109](#)
- GSUtils, [112](#)
- GSVersion, [114](#)
- GSVirtualTable, [116](#)
- GSVirtualTableGeometry, [118](#)
- GSVirtualTableParameter, [120](#)
- GSWorkspace, [121](#)
- GSWorkspaceManager, [122](#)
- GSWorkspaceSettings, [126](#)
- GSWorldImageCoverageStore, [128](#)
- * **control**
 - GSAccessControlListManager, [15](#)
 - GSLayerRule, [67](#)
 - GSRestRule, [92](#)
 - GSRule, [93](#)
 - GSServiceRule, [99](#)
- * **coverageBand**
 - GSCoverageBand, [22](#)
- * **coverageType**
 - GSCoverage, [20](#)
- * **coverageView**
 - GSCoverageView, [32](#)
- * **coverage**
 - GSLayer, [55](#)
 - GSLayerGroup, [59](#)
- * **database**
 - GSAbstractDBDataStore, [8](#)
- * **dimension**
 - GSDimension, [43](#)
- * **featureType**
 - GSFeatureDimension, [46](#)
 - GSFeatureType, [47](#)
- * **directory**
 - GSShapefileDirectoryDataStore, [106](#)
- * **entryset**
 - GSRESTEntrySet, [88](#)
- * **featureType**
 - GSFeatureType, [47](#)
 - GSLayer, [55](#)
 - GSLayerGroup, [59](#)
- * **geoserver**
 - GSAbstractCoverageStore, [4](#)
 - GSAbstractDataStore, [5](#)
 - GSAbstractDBDataStore, [8](#)
 - GSAbstractStore, [13](#)
 - GSAccessControlListManager, [15](#)
 - GSArcGridCoverageStore, [19](#)
 - GSCoverage, [20](#)
 - GSCoverageBand, [22](#)
 - GSCoverageStoreManager, [25](#)
 - GSCoverageView, [32](#)
 - GSDataStoreManager, [35](#)
 - GSDimension, [43](#)
 - GSFeatureDimension, [46](#)
 - GSFeatureType, [47](#)
 - GSGeoPackageDataStore, [49](#)
 - GSGeoTIFFCoverageStore, [51](#)
 - GSImageMosaicCoverageStore, [52](#)
 - GSInputCoverageBand, [53](#)
 - GSLayer, [55](#)
 - GSLayerGroup, [59](#)
 - GSLayerManager, [64](#)
 - GSLayerRule, [67](#)
 - GSManger, [68](#)
 - GSMetadataLink, [72](#)
 - GSMonitorManager, [74](#)
 - GSNamespace, [75](#)
 - GSNamespaceManager, [76](#)
 - GSOacleNGDataStore, [78](#)
 - GSPostGISDataStore, [80](#)
 - GSPublishable, [81](#)
 - GSResource, [83](#)
 - GSRESTEntrySet, [88](#)
 - GSRESTResource, [90](#)
 - GSRestRule, [92](#)
 - GSRule, [93](#)
 - GSServiceManager, [94](#)
 - GSServiceRule, [99](#)
 - GSServiceSettings, [100](#)

- GSShapefileDataStore, 104
 - GSShapefileDirectoryDataStore, 106
 - GSShinyMonitor, 108
 - GSStyleManager, 109
 - GSUtils, 112
 - GSVersion, 114
 - GSVirtualTable, 116
 - GSVirtualTableGeometry, 118
 - GSVirtualTableParameter, 120
 - GSWorkspace, 121
 - GSWorkspaceManager, 122
 - GSWorkspaceSettings, 126
 - GSWorldImageCoverageStore, 128
- * **group**
 - GSLayerGroup, 59
 - GSPublishable, 81
- * **inputCoverageBand**
 - GSInputCoverageBand, 53
- * **layer**
 - GSLayer, 55
 - GSLayerGroup, 59
 - GSPublishable, 81
- * **list**
 - GSAccessControllistManager, 15
- * **metadataLink**
 - GSMetadataLink, 72
- * **monitoring**
 - GSShinyMonitor, 108
- * **namespace**
 - GSNamespace, 75
 - GSNamespaceManager, 76
- * **publishable**
 - GSPublishable, 81
- * **resourcelayer**
 - GSLayer, 55
- * **resource**
 - GSCoverage, 20
 - GSDimension, 43
 - GSFeatureDimension, 46
 - GSFeatureType, 47
 - GSLayer, 55
 - GSLayerGroup, 59
 - GSMetadataLink, 72
 - GSPublishable, 81
 - GSResource, 83
- * **rest**
 - GSAbstractCoverageStore, 4
 - GSAbstractDataStore, 5
 - GSAbstractDBDataStore, 8
 - GSAbstractStore, 13
 - GSAccessControllistManager, 15
 - GSArcGridCoverageStore, 19
 - GSCoverage, 20
 - GSCoverageBand, 22
 - GSCoverageStoreManager, 25
 - GSCoverageView, 32
 - GSDataStoreManager, 35
 - GSDimension, 43
 - GSFeatureDimension, 46
 - GSFeatureType, 47
 - GSGeoPackageDataStore, 49
 - GSGeoTIFFCoverageStore, 51
 - GSImageMosaicCoverageStore, 52
 - GSInputCoverageBand, 53
 - GSLayer, 55
 - GSLayerGroup, 59
 - GSLayerManager, 64
 - GSLayerRule, 67
 - GSManager, 68
 - GSMetadataLink, 72
 - GSMonitorManager, 74
 - GSNamespace, 75
 - GSNamespaceManager, 76
 - GSOracleNGDataStore, 78
 - GSPostGISDataStore, 80
 - GSPublishable, 81
 - GSResource, 83
 - GSRESTEntrySet, 88
 - GSRESTResource, 90
 - GSRestRule, 92
 - GSRule, 93
 - GSServiceManager, 94
 - GSServiceRule, 99
 - GSServiceSettings, 100
 - GSShapefileDataStore, 104
 - GSShapefileDirectoryDataStore, 106
 - GSStyleManager, 109
 - GSUtils, 112
 - GSVersion, 114
 - GSVirtualTable, 116
 - GSVirtualTableGeometry, 118
 - GSVirtualTableParameter, 120
 - GSWorkspace, 121
 - GSWorkspaceManager, 122
 - GSWorkspaceSettings, 126
 - GSWorldImageCoverageStore, 128

- * **rule**
 - GSLayerRule, 67
 - GSRestRule, 92
 - GSRule, 93
 - GSServiceRule, 99
- * **service**
 - GSServiceManager, 94
 - GSServiceSettings, 100
- * **settings**
 - GSSettings, 126
- * **shapefile**
 - GSShapefileDataStore, 104
 - GSShapefileDirectoryDataStore, 106
- * **store**
 - GSAbstractStore, 13
- * **style**
 - GSLayer, 55
 - GSStyleManager, 109
- * **version**
 - GSVersion, 114
- * **virtualTable**
 - GSVirtualTable, 116
 - GSVirtualTableGeometry, 118
 - GSVirtualTableParameter, 120
- * **workspace**
 - GSSettings, 121
 - GSSettingsManager, 122
 - GSSettingsSettings, 126
- geosapi, 3
- geosapi-package (geosapi), 3
- geosapi::GSAbstractCoverageStore, 19, 51, 52, 128
- geosapi::GSAbstractDataStore, 8, 49, 79, 80, 104, 106
- geosapi::GSAbstractDBDataStore, 49, 79, 80
- geosapi::GSAbstractStore, 4, 6, 8, 19, 49, 51, 52, 79, 80, 104, 106, 128
- geosapi::GSDimension, 46
- geosapi::GSManager, 15, 25, 35, 64, 74, 77, 94, 110, 123
- geosapi::GSResource, 21, 48
- geosapi::GSRESTResource, 4, 6, 8, 13, 19, 21, 23, 32, 44, 46, 48, 49, 51, 52, 54, 55, 58, 60, 67, 72, 75, 79–81, 83, 88, 92, 93, 99, 100, 104, 106, 116, 119–121, 126, 128
- geosapi::GSRule, 67, 92, 99
- geosapi::GSShapefileDataStore, 106
- GSAbstractCoverageStore, 4, 5, 26, 27
- GSAbstractDataStore, 5, 6, 26, 36
- GSAbstractDBDataStore, 8
- GSAbstractStore, 13
- GSAccessControlListManager, 15
- GSArcGridCoverageStore, 19
- GSCoverage, 20, 21, 27, 28
- GSCoverageBand, 22, 23, 34
- GSCoverageStoreManager, 25, 71
- GSCoverageView, 21, 32, 33
- GSDataStoreManager, 35, 71
- GSDimension, 43, 44
- GSFeatureDimension, 46, 46
- GSFeatureType, 37, 38, 47, 48
- GSGeoPackageDataStore, 49
- GSGeoTIFFCoverageStore, 51
- GSIImageMosaicCoverageStore, 52
- GSInputCoverageBand, 24, 53, 54
- GSLayer, 38, 55, 56, 64, 65
- GSLayerGroup, 59, 61, 65, 66
- GSLayerManager, 64
- GSLayerRule, 17, 67, 67, 92, 99
- GSSettings, 68, 109
- GSMetadataLink, 63, 72, 73, 86
- GSMonitorManager, 74
- GSNamespace, 75, 75, 77
- GSNamespaceManager, 71, 76, 124
- GSSOracleNGDataStore, 78
- GSPostGISDataStore, 80
- GSPublishable, 81, 81
- GSResource, 83, 84
- GSRESTEntrySet, 7, 88, 89
- GSRESTResource, 90, 91
- GSRestRule, 17, 92
- GSRule, 17–19, 93, 93
- GSServiceManager, 71, 94
- GSServiceRule, 17, 99
- GSServiceSettings, 95–97, 100, 101
- GSShapefileDataStore, 104
- GSShapefileDirectoryDataStore, 106
- GSShinyMonitor, 108
- GSStyle, 57, 58, 110
- GSStyle (GSLayer), 55
- GSStyleManager, 71, 109
- GSUtils, 112
- GSVersion, 114, 114
- GSVirtualTable, 48, 49, 116, 116

GSVirtualTableGeometry, [117](#), [118](#), [119](#)
GSVirtualTableParameter, [118](#), [120](#), [120](#)
GWorkspace, [62](#), [121](#), [122–124](#)
GWorkspaceManager, [71](#), [122](#)
GWorkspaceSettings, [124](#), [125](#), [126](#)
GSWorldImageCoverageStore, [128](#)

R6Class, [4](#), [5](#), [8](#), [13](#), [15](#), [19](#), [21](#), [22](#), [25](#), [32](#), [35](#),
[43](#), [44](#), [46](#), [47](#), [49](#), [51–55](#), [59](#), [60](#), [64](#),
[67](#), [68](#), [72](#), [74–76](#), [78–81](#), [83](#), [88](#), [90](#),
[92–94](#), [99](#), [100](#), [104](#), [106](#), [108–110](#),
[112](#), [114](#), [116](#), [118](#), [120](#), [121](#), [123](#),
[126](#), [128](#)

xml_node-class, [4–6](#), [9](#), [14](#), [20](#), [21](#), [23](#), [24](#),
[33](#), [44](#), [46](#), [48](#), [50](#), [51](#), [53](#), [54](#), [56](#), [58](#),
[59](#), [61](#), [68](#), [73](#), [76](#), [79](#), [80](#), [82](#), [84](#), [89](#),
[91–94](#), [99](#), [101](#), [104](#), [107](#), [112](#), [117](#),
[119–122](#), [127](#), [129](#)