

# Package: ggperiodic (via r-universe)

July 2, 2026

**Title** Easy Plotting of Periodic Data with 'ggplot2'  
**Version** 1.0.4  
**Description** Implements methods to plot periodic data in any arbitrary range on the fly.  
**License** GPL-3  
**URL** <https://github.com/eliocamp/ggperiodic>  
**BugReports** <https://github.com/eliocamp/ggperiodic/issues>  
**Imports** dplyr, ggplot2, sticky, tidyselect, data.table  
**Suggests** covr, knitr, maps, rmarkdown, testthat  
**VignetteBuilder** knitr  
**ByteCompile** true  
**Encoding** UTF-8  
**Config/roxygen2/version** 8.0.0  
**NeedsCompilation** no  
**Author** Elio Campitelli [cre, aut] (ORCID: <https://orcid.org/0000-0002-7742-9230>)  
**Maintainer** Elio Campitelli <eliocampitelli@gmail.com>  
**Repository** <https://cran.r-universe.dev>  
**Date/Publication** 2026-07-02 13:30:02 UTC  
**RemoteUrl** <https://github.com/cran/ggperiodic>  
**RemoteRef** HEAD  
**RemoteSha** 6e47832d2c5a21e81cf8ee9af1b1bf90b888e5ec

## Contents

get_period . . . . .	2
ggperiodic . . . . .	2
is.periodic . . . . .	3
periodic . . . . .	3

qwrap . . . . .	4
unperiodic . . . . .	5
wrap . . . . .	5

<b>Index</b>	<b>7</b>
--------------	----------

---

get_period	<i>Get period information from an object</i>
------------	--

---

### Description

Get period information from an object

### Usage

```
get_period(object)
```

### Arguments

object            a periodic object

---

ggperiodic	<i>ggperiodic: Easy Plotting of Periodic Data with 'ggplot2'</i>
------------	--

---

### Description

Implements methods to plot periodic data in any arbitrary range on the fly.

### Overview

The only thing you need to do is add the periodic information to a data frame with `periodic()`. You then can manually wrap your data around any domain with `wrap()` or just let `ggplot2` do it automatically for you

### Author(s)

**Maintainer:** Elio Campitelli <eliocampitelli@gmail.com> ([ORCID](#))

Authors:

- Elio Campitelli <eliocampitelli@gmail.com> ([ORCID](#))

### See Also

Useful links:

- <https://github.com/eliocamp/ggperiodic>
- Report bugs at <https://github.com/eliocamp/ggperiodic/issues>

---

is.periodic	<i>Check if an object is periodic</i>
-------------	---------------------------------------

---

**Description**

Check if an object is periodic

**Usage**

```
is.periodic(object)
```

**Arguments**

object	an object
--------	-----------

---

periodic	<i>Add or remove periodic variables</i>
----------	---

---

**Description**

Creates a periodic object by specifying the periodic variables and their periods.

**Usage**

```
periodic(object, ...)

## Default S3 method:
periodic(object, period, ...)

## S3 method for class 'data.frame'
periodic(object, ...)

setperiodic(object, ...)
```

**Arguments**

object	the object to coerce to periodic
...	name-value pairs of expressions defining the period
period	a numeric vector whose range defines the period

**Value**

An object of subclass `periodic_df` or `periodic_v`.

If `object` is of class `data.table`, then it will modify the object by reference. To modify this behaviour, use `options(ggperiodic.data.table.copy = TRUE)`. `setperiodic()` will modify a `data.table` by reference bypassing the global option.

**Examples**

```

library(ggplot2)

x <- seq(0, 360 - 20, by = 20)
df <- data.frame(x = x, y = cos(x*pi/180))
df_p <- periodic(df, x = c(0, 360))

ggplot(df_p, aes(x, y)) +
  geom_line() +           # periodic data
  geom_point(data = df)  # non periodic data

# Extend domain
ggplot(df_p, aes(x, y), x = c(-180, 540)) +
  geom_line() +
  geom_point(data = df)

# with non regular intervals
x <- runif(30, 0, 360)
df <- periodic(data.frame(x = x, y = cos(x*pi/180)),
              x = c(0, 360))
ggplot(df, aes(x, y), x = c(-180, 540)) +
  geom_point()

```

---

qwrap

*Quickly wrap data*


---

**Description**

Wraps periodic data from one specified range to the other in one line.

**Usage**

```
qwrap(object, ..., .group = NULL)
```

**Arguments**

object	the object to wrap
...	named formulas with the form from ~ to (see examples)
.group	optional group column (see <a href="#">wrap</a> )

**Details**

qwrap is a shortcut to `wrap(periodic(object, x = range_from), x = range_to)`

**Examples**

```
x <- seq(0, 360 - 20, by = 20)
df <- data.frame(x = x, y = cos(x*pi/180))
qwrap(df, x = c(0, 360) ~ c(-180, 180))
```

---

unperiodic	<i>Remove periodic specifications</i>
------------	---------------------------------------

---

**Description**

Remove periodic specifications

**Usage**

```
unperiodic(object, ...)
setunperiodic(object, ...)
```

**Arguments**

object	the object to remove periodicities
...	arguments to methods

**Value**

An object of the same class as `object` but with no periodic subclass or periodicity specifications.

If `object` is of class `data.table`, then it will modify the object by reference. To modify this behaviour, use `options(ggperiodic.data.table.copy = TRUE)`. `setperiodic()` will modify a `data.table` by reference bypassing the global option.

---

wrap	<i>Wrap periodic data to an arbitrary range</i>
------	---

---

**Description**

Wrap periodic data to an arbitrary range

**Usage**

```
wrap(object, ...)

## S3 method for class 'periodic_df'
wrap(object, ..., .group = NULL)
```

**Arguments**

object	a periodic data frame
...	name-value pairs of expressions defining range specifications
.group	optional group column (see examples)

**Value**

An object of the same class as `object` but with no periodic subclass or periodicity specifications and wrapped dimensions.

**Examples**

```
x <- seq(0, 360 - 20, by = 20)
df <- data.frame(x = x, y = cos(x*pi/180))
df_p <- periodic(df, x = c(0, 360))

# wrap in default range
df_wrapped <- wrap(df_p)
range(df_wrapped$x)
range(df$x)

# specify range
df_wrapped <- wrap(df_p, x = c(-145, 365))
range(df_wrapped$x)

# with non regular intervals
x <- runif(30, 0, 360)
df <- periodic(data.frame(x = x, y = cos(x*pi/180)),
               x = c(0, 360))
df_wrapped <- wrap(df, x = c(-180, 540))
range(df_wrapped$x)
range(df$x)
## Not run:
# This example illustrates the use of the .group parameter
library(ggplot2)
map <- periodic(map_data("world"), long = long)

# If wrapped without .group, the repeated parts of the map
# have the same group and so polygons are not correctly defined.
map_wrapped <- wrap(map, long = c(-180, 360))
ggplot(map_wrapped, aes(long, lat, group = group)) +
  geom_path()

# Using groups, you get the correct grouping.
map_wrapped <- wrap(map, long = c(-180, 360), .group = group)
ggplot(map_wrapped, aes(long, lat, group = group)) +
  geom_path()

## End(Not run)
```

# Index

`get_period`, 2  
`ggperiodic`, 2  
`ggperiodic-package (ggperiodic)`, 2  
  
`is.periodic`, 3  
  
`periodic`, 3  
`periodic()`, 2  
  
`qwrap`, 4  
  
`setperiodic (periodic)`, 3  
`setunperiodic (unperiodic)`, 5  
  
`unperiodic`, 5  
  
`wrap`, 4, 5  
`wrap()`, 2