

Package: gp (via r-universe)

September 17, 2024

Type Package

Title Maximum Likelihood Estimation of the Generalized Poisson Distribution

Version 1.1

Date 2023-10-23

Author Michail Tsagris [aut, cre]

Maintainer Michail Tsagris <mtsagris@uoc.gr>

Depends R (>= 4.0)

Imports Rfast, RNGforGPD, stats

Description Functions to estimate the parameters of the generalized Poisson distribution with or without covariates using maximum likelihood. The references include Nikoloulopoulos A.K. & Karlis D. (2008). ``On modeling count data: a comparison of some well-known discrete distributions". Journal of Statistical Computation and Simulation, 78(3): 437--457, <doi:10.1080/10629360601010760> and Consul P.C. & Famoye F. (1992). ``Generalized Poisson regression model". Communications in Statistics - Theory and Methods, 21(1): 89--109, <doi:10.1080/03610929208830766>.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2023-10-23 15:50:16 UTC

Contents

| | |
|---|---|
| gp-package | 2 |
| Cumulative probability mass of the generalized Poisson distribution | 3 |
| Density computation of the generalized Poisson distribution | 4 |
| gp.mle | 5 |
| gp.reg | 6 |
| rgp | 7 |

Index**9**

| | |
|------------|---|
| gp-package | <i>Maximum Likelihood Estimation of the Generalized Poisson Distribution.</i> |
|------------|---|

Description

Maximum likelihood estimation of the generalized Poisson distribution. Regression modelling is also supported.

Details

Package: gp
Type: Package
Version: 1.1
Date: 2023-10-23
License: GPL-2

Maintainers

Michail Tsagris <mtsagris@uoc.gr>.

Author(s)

Michail Tsagris <mtsagris@uoc.gr>.

References

Nikoloulopoulos A.K. & Karlis D. (2008). On modeling count data: a comparison of some well-known discrete distributions. *Journal of Statistical Computation and Simulation*, 78(3): 437–457.
Consul P.C. & Famoye F. (1992). Generalized poisson regression model. *Communications in Statistics - Theory and Methods*, 21(1): 89–109.

Cumulative probability mass of the generalized Poisson distribution
Cumulative probability mass of the generalized Poisson distribution

Description

Cumulative probability mass of the generalized Poisson distribution.

Usage

```
pgp(y, theta, lambda)
```

Arguments

| | |
|--------|--|
| y | A vector with non negative integer values. |
| theta | The value of the θ parameter. |
| lambda | The value of the λ parameter. |

Details

The cumulative probability mass of the generalized Poisson distribution is computed.

Value

A vector with the probabilities.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Nikoloulopoulos A.K. & Karlis D. (2008). On modeling count data: a comparison of some well-known discrete distributions. *Journal of Statistical Computation and Simulation*, 78(3): 437–457.

Demirtas H. (2017). On accurate and precise generation of generalized Poisson variates. *Communications in Statistics - Simulation and Computation*, 46(1): 489–499.

See Also

[dgp](#), [rgp](#)

Examples

```
y <- rgp(1000, 10, 0.5, method = "Inversion")
a <- gp.mle(y)
pgp(y[1:10], a[1], a[2])
```

Density computation of the generalized Poisson distribution
Density computation of the generalized Poisson distribution

Description

Density computation of the generalized Poisson distribution.

Usage

```
dgp(y, theta, lambda, logged = TRUE)
```

Arguments

| | |
|---------------------|--|
| <code>y</code> | A vector with non negative integer values. |
| <code>theta</code> | The value of the θ parameter. |
| <code>lambda</code> | The value of the λ parameter. |
| <code>logged</code> | Should the logarithm of the density values be computed? The default value is TRUE. |

Details

The density of the generalized Poisson distribution is computed.

Value

A vector with the logged density values.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Nikoloulopoulos A.K. & Karlis D. (2008). On modeling count data: a comparison of some well-known discrete distributions. *Journal of Statistical Computation and Simulation*, 78(3): 437–457.

Demirtas H. (2017). On accurate and precise generation of generalized Poisson variates. *Communications in Statistics - Simulation and Computation*, 46(1): 489–499.

See Also

[rgp](#), [pgp](#)

Examples

```
y <- rgp(1000, 10, 0.5, method = "Inversion")
a <- gp.mle(y)
f <- dgp(y, a[1], a[2])
sum(f)
```

`gp.mle`*Maximum likelihood estimation of the generalized Poisson distribution*

Description

Maximum likelihood estimation of the generalized Poisson distribution.

Usage

```
gp.mle(y)
```

Arguments

`y` A vector with non negative integer values.

Details

The probability density function of the generalized Poisson distribution is the following (Nikoloulopoulos & Karlis, 2008):

$$P(Y = y|\theta, \lambda) = \theta(\theta + \lambda y)^{y-1} \frac{e^{-\theta - \lambda y}}{y!}, \quad y = 0, 1, \dots \quad \theta > 0, \quad 0 \leq \lambda \leq 1.$$

To ensure that θ is positive we use the "log" link and for λ to lie within 0 and 1 we use the "logit" link within the `optim` function.

Value

A vector with three numbers, the θ and λ parameters and the value of the log-likelihood.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Nikoloulopoulos A.K. & Karlis D. (2008). On modeling count data: a comparison of some well-known discrete distributions. *Journal of Statistical Computation and Simulation*, 78(3): 437–457.

See Also

`gp.reg`, `rgp`

Examples

```
y <- rgp(1000, 10, 0.5, method = "Inversion")
gp.mle(y)
```

| | |
|--------|---------------------------------------|
| gp.reg | <i>Generalized Poisson regression</i> |
|--------|---------------------------------------|

Description

Generalized Poisson regression.

Usage

```
gp.reg(y, x, tol = 1e-7)
gp.reg2(y, x, tol = 1e-7)
```

Arguments

| | |
|-----|---|
| y | The response variable, a vector with non negative integer values. |
| x | A data.frame or a matrix with the independent variables. |
| tol | The tolerance value to terminate the optimization. |

Details

The loglikelihood of the generalised Poisson distribution when covariates are present is the following (Consul & Famoye, 1992):

$$\ell(\beta, \phi) = \sum_{i=1}^n \log(\mu_i) + \sum_{i=1}^n (y_i - 1) \log[\mu_i + (\phi - 1)y_i] - \log \phi \sum_{i=1}^n y_i - \frac{1}{\phi} \sum_{i=1}^n [\mu_i + (\phi - 1)y_i] - \sum_{i=1}^n \log(y_i),$$

where $\mu_i = e^{\sum_{j=0}^k X_{ij}\beta_j}$, n denotes the sample size, k is the number of β coefficients, and $\phi > 0$.

Breslow (1984) suggested the (moment) estimation of a dispersion parameter by equating the chi-square statistic to its degrees of freedom. For the generalised Poisson regression model, this leads to $\sum_{i=1}^n \frac{(y_i - \mu_i)^2}{\mu_i \phi^2} = n - k$ and we solve this for ϕ .

According to Consul and Famoye (1992) we begin by fitting a Poisson regression model and obtain initial values for β_s and ϕ . If $\hat{\phi} \approx 1$, it implies that the Poisson regression model is appropriate and no further estimation needs to be done. However, if $\hat{\phi} \neq 1$, this is used to obtain new values of the estimated β_s by maximizing the log-likelihood. This process is iterated until we obtain a stable solution.

The function as seen below returns the log-likelihood of the initial Poisson regression as well. This is useful if one wants to test, via the log-likelihood ratio test as 1 degree of freedom, if the generalized Poisson regression is to be preferred over the Poisson regression.

gp.reg() estimates the *beta* coefficients using Newton-Raphson, whereas gp.reg2() uses the `optim` function. For some reason these two do not always agree. One might yield higher log-likelihood than the other and this is why I offer both ways.

Value

A list including:

| | |
|--------------------------|--|
| <code>pois.loglik</code> | The initial Poisson regression log-likelihood. |
| <code>gp.loglik</code> | The generalized Poisson regression log-likelihood. |
| <code>be</code> | The estimated <i>beta</i> coefficients. |
| <code>phi</code> | The estimated ϕ parameter. |

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Consul P.C. & Famoye F. (1992). Generalized poisson regression model. *Communications in Statistics - Theory and Methods*, 21(1): 89–109.

Breslow N. E. (1984). Extra-Poisson variation in log-linear models. *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 33(1): 38–44.

See Also

[gp.mle](#)

Examples

```
n <- 500
x <- matrix (rnorm(n * 2), nrow = n, ncol = 2)
be <- c(1, 1)
mi <- x[, 1] * be[1] + x[, 2] * be[2] + 1
mi <- exp(mi)
y <- numeric(n)
for (i in 1:n) y[i] <- rgp(2, mi[i], 0.5, method = "Inversion")[1]
gp.reg(y, x)
gp.reg2(y, x)
```

rgp

Random values simulation from the generalized Poisson distribution

Description

Random values simulation from the generalized Poisson distribution.

Usage

```
rgp(n, theta, lambda, method)
```

Arguments

| | |
|--------|--|
| n | The number of random values to generate. |
| theta | The value of the θ parameter. |
| lambda | The value of the λ parameter. |
| method | The simulation method to use. The available options are: "Inversion", "Branching", "Normal-Approximation", "Build-Up" and "Chop-Down". |

Details

The values θ and λ affect the method of simulation to use. See Li et al. (2020) for more information.

Value

A vector with values from the generalized Poisson distribution.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Li H., Demirtas H. & Chen R. (2020). RNGforGPD: An R Package for Generation of Univariate and Multivariate Generalized Poisson Data. R JOURNAL, 12(2): 173–188.

Demirtas H. (2017). On accurate and precise generation of generalized Poisson variates. Communications in Statistics - Simulation and Computation, 46(1): 489–499.

See Also

[gp.mle](#)

Examples

```
y <- rgp(1000, 10, 0.5, method = "Inversion")
gp.mle(y)
```


Index

Cumulative probability mass of the
generalized Poisson
distribution, [3](#)

Density computation of the generalized
Poisson distribution, [4](#)

`dgp`, [3](#)

`dgp` (Density computation of the
generalized Poisson
distribution), [4](#)

`gp-package`, [2](#)

`gp.mle`, [5](#), [7](#), [8](#)

`gp.reg`, [5](#), [6](#)

`gp.reg2` (`gp.reg`), [6](#)

`optim`, [5](#), [6](#)

`pgp`, [4](#)

`pgp` (Cumulative probability mass of
the generalized Poisson
distribution), [3](#)

`rgp`, [3–5](#), [7](#)